

SLM / Edge Device arXiv Daily Summary

생성일: 2026-06-14 05:50 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 7일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 7일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: Holding the FP8 Quality Ceiling at 8-Bit Weights and Activations: INT8 and GGUF Post-Training Quantization of Ideogram 4.0 for Consumer GPUs

저자: Deep Gandhi, Ali Asaria, Tony Salomone

카테고리: Deployment/Quantization/Efficiency

arXiv ID: 2606.12280

제출일: 2026-06-10T16:19:49+00:00

수정일: 2026-06-10T16:19:49+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.12280.pdf>

[초록 원문]

Post-training quantization lets large text-to-image diffusion transformers run on consumer GPUs, yet the hardware-specific trade-offs are seldom measured directly. We quantize Ideogram 4.0 - a 9.3B flow-matching diffusion transformer (DiT), shipped as two separate-weight copies of a single-stream 34-layer backbone for classifier-free guidance and conditioned by a Qwen3-VL-8B encoder - for Ampere RTX 3090 GPUs, which lack FP8 tensor cores. Our INT8 W8A8 recipe (per-channel weights, per-token dynamic activations, SmoothQuant, and mixed-precision protection of a small high-fragility layer set) holds the FP8 quality ceiling: on a 200-prompt benchmark the paired same-seed bootstrap CI for INT8-FP8 includes zero on both Pick and CLIP, while INT8 improves on NF4 by \$+1.9\$ CLIP (95% CI \$[+1.21,+2.64]\$, excluding zero). A per-category OCR analysis, to our knowledge unreported for this model class, confirms text legibility is preserved, and an ablation isolates protection of the FFN down-projections as the dominant quality lever. Our GGUF Q4_K quantization beats NF4 at equal on-disk size and is the Pareto winner on the quality-memory frontier, with paired confidence intervals excluding zero (Q8_0 is quality neutral). Finally, we characterize where 8-bit quantization helps and where it does not: INT8's

weights match FP8's footprint rather than shrink it, so a speed gain on Ampere awaits a fused INT8 kernel.

[PDF 앞부분/서론 일부]

Holding the FP8 Quality Ceiling at 8-Bit Weights and Activations: INT8 and GGUF Post-Training Quantization of Ideogram 4.0 for Consumer GPUs Deep Gandhi Transformer Lab Ali Asaria Transformer Lab Tony Salomone Transformer Lab Abstract Post-training quantization lets large text-to-image diffusion transformers run on consumer GPUs, yet the hardware-specific trade-offs are seldom measured directly. We quantize Ideogram 4.0 - a 9.3B flow-matching diffusion transformer (DiT), shipped as two separate-weight copies of a single-stream 34-layer backbone for classifier-free guidance and conditioned by a Qwen3-VL-8B encoder - for Ampere RTX 3090 GPUs, which lack FP8 tensor cores. Our INT8 W8A8 recipe (per-channel weights, per-token dynamic activations, SmoothQuant, and mixed-precision protection of a small high-fragility layer set) holds the FP8 quality ceiling: on a 200-prompt benchmark the paired same-seed bootstrap CI for INT8FP8 includes zero on both Pick and CLIP, while INT8 improves on NF4 by +1.9CLIP (95% CI [+1.21, +2.64], excluding zero). A per-category OCR analysis - to our knowledge unreported for this model class - confirms text legibility is preserved, and an ablation isolates protection of the FFN down-projections as the dominant quality lever. Our GGUF Q4_K quantization beats NF4 at equal on-disk size and is the Pareto winner on the quality-memory frontier, with paired confidence intervals excluding zero (Q8_0 is quality-neutral). Finally, we characterize where 8-bit quantization helps and where it does not: INT8's weights match FP8's footprint rather than shrink it, so a speed gain on Ampere awaits a fused INT8 kernel (§7).

1 Introduction Text-to-image diffusion transformers have grown past the point where their published checkpoints fit comfortably on consumer GPUs, and the community increasingly relies on quantized redistributions. Ideogram 4.0 ships two: a weight-only FP8 variant and an NF4 variant, both under a noncommercial license. Our deployment target is deliberately also our development hardware - a cluster of RTX 3090s (24GB, Ampere). Ampere has no FP8 tensor cores, so the FP8 checkpoint executes by dequantizing each linear to bf16 every forward. On our single-GPU-compute recipe this dequantization overhead is modest - the FP8 variant runs at 172.9s/image, only $\approx 5\%$ over NF4 (164.5s/image). The published FP8 variant is therefore reusable on Ampere - the gaps it leaves are (i) NF4's quality loss, which is largest on text, and (ii) the absence of an Ampere-native low-precision compute path (Ampere has fast native INT8, but the ideogram4 stack ships no fused INT8 GEMM). Corresponding author: deep@lab.cloud 1 arXiv:2606.12280v1 [cs.LG] 10 Jun 2026 INT8 and GGUF Quantization of Ideogram 4.0.0 We target the first gap with a quality-preserving INT8 W8A8 recipe and a memory-competitive GGUF Q4_K, and lay the groundwork for the second by validating the INT8 recipe as the substrate a fused Ampere-INT8 kernel would accelerate (§7). Ideogram 4.0 is a single-stream 34-layer flow-matching DiT, but classifier-free guidance is realized by shipping two separate-weight copies of that backbone - a conditional and an unconditional transformer ($\approx 9.3\text{GB}$ each at FP8) - so quantization must cover both ($211\text{ linear layers} \times 2$). We use "branch" to mean these two weight sets, not a dual-stream architecture. Text rendering is the model's signature strength and, by the literature's consensus, the first casualty of aggressive quantization [1, 2, 3]; we therefore measure OCR fidelity in every evaluation rather than trusting aggregate image-quality scores. We make four contributions: 1. An INT8 W8A8 recipe for this dual-branch flow-matching DiT that holds the FP8 quality ceiling at 8-bit weights and activations - the paired INT8FP8 CI includes zero on Pick and CLIP - and beats the published NF4 baseline by +1.9CLIP (CI excluding zero) (§5). 2. A per-module activation fragility analysis: a timestep-stable profile that identifies the FFN

down-projections as the fragile set, and an ablation showing that protecting just 17 of them ($\approx 8\%$ of linears) is the dominant quality lever, with a sharp recovery knee (§5). 3. GGUF k-quants for a diffusion transformer: Q4_K beats NF4 at equal on-disk size, making it the Pareto winner on the quality-memory frontier, and Q8_0 is quality-neutral (§5). 4. A per-category OCR-under-quantization evaluation - to our knowledge unreported for a model of this class - showing text legibility is preserved, together with a reference-fidelity (PSNR/SSIM/LPIPS) analysis reconciling pixel-similarity with standalone quality (§5). We further give a precise account of where 8-bit quantization does and does not pay off on this hardware (§7). 2 Related Work Weight-activation PTQ. The W8A8 recipe is well converged: SmoothQuant migrates activation outliers into weights with a tunable strength α [4], addressing the collapse of naive per-tensor INT8 activations under outlier channels [5]. On diffusion transformers, per-token dynamic activation quantization with per-channel weights is the validated configuration [6, 7], and FP4DiT argues DiT activations are token/channel-dominated rather than timestep-dominated, so online per-token scales sidestep U-Net-style temporal calibration [8]. PTQD reports a CUTLASS INT8 W8A8 kernel at $2.03\times$ on an RTX 3090 [9] - the most direct evidence that an Ampere INT8 thesis pays off. At 8 bits, heavy machinery matters less: several works find W8A8 near-lossless with modest calibration [10, 11], reserving rotation/low-rank tricks for ≤ 4 -bit (and offline rotations are in any case blocked by adaLN's runtime-generated modulation [7, 12]). Weight-only / GGUF. GPTQ's Hessian-compensated group-wise rounding is the calibrated backbone for ≤ 4 -bit weights [13]; AWQ's activation-aware channel scaling is orthogonal and robust to the calibration distribution [14]; QLoRA defines the NF4 format we must beat and the block-scale accounting for honest bits-per-weight comparisons [15]. A key caveat we exploit: at 8 bits ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '사후 훈련 양자화(PTQ)는 대규모 텍스트-이미지 확산 트랜스포머를 소비자용 GPU에서 실행할 수 있게 하지만, 하드웨어별 절충점은 직접적으로 측정되는 경우가 드물다. 우리는 FP8 텐서 코어가 없는 Ampere RTX 3090 GPU를 대상으로, 분류기 없는'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 425, 'candidatesTokenCount': 79, 'totalTokenCount': 2469, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 425}], 'thoughtsTokenCount': 1965, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'h8ltapqLArGA1MkPrbqvAw'}

[논문 후보 2]

제목: Non-frontal face recognition using GANs and memristor-based classifiers
저자: Semih Vazgecen, Cristian Sestito, Spyros Stathopoulos, Themis Prodromakis
카테고리: SLM/Edge/On-device
arXiv ID: 2606.12074
제출일: 2026-06-10T13:41:00+00:00
수정일: 2026-06-10T13:41:00+00:00
최근성: 최근 3일 이내
arXiv PDF: <https://arxiv.org/pdf/2606.12074.pdf>

[초록 원문]

Face recognition systems have advanced significantly through deep learning techniques, delivering high performance and robustness in complex scenarios. However, these approaches incur substantial computational overhead, limiting their in situ applicability in resource-constrained platforms such as drones, where they can address challenges including non-frontal facial imagery. Memristor-based neuromorphic systems have emerged as a compelling approach for edge AI applications, combining biologically inspired processing with efficient and scalable computation. In this work, we propose a facial recognition framework that addresses non-frontal pose variations by integrating lightweight generative adversarial network (GAN)-based pose frontalisation with memristor-based neuromorphic recognition. The experimental results on two datasets demonstrate the effectiveness of combining adversarial learning with memristive technology, achieving up to 96% identification accuracy. The proposed approach alleviates the computational bottlenecks of conventional AI and offers a scalable, efficient solution for face recognition in dynamic real-world environments.

[PDF 앞부분/서론 일부]

Non-frontal face recognition using GANs and memristor-based classifiers Semih Vazgecen*, Cristian Sestito, Spyros Stathopoulos, Themis Prodromakis Centre for Electronics Frontiers, Institute for Integrated Micro and Nano Systems, School of Engineering, The University of Edinburgh, UK. *Corresponding author. E-mail: S.A.Vazgecen@sms.ed.ac.uk; Abstract Face recognition systems have advanced significantly through deep learning techniques, delivering high performance and robustness in complex scenarios. However, these approaches incur substantial computational overhead, limiting their in situ applicability in resource-constrained platforms such as drones, where they can address challenges including non-frontal facial imagery. Memristor-based neuromorphic systems have emerged as a compelling approach for edge AI applications, combining biologically inspired processing with efficient and scalable computation. In this work, we propose a facial recognition framework that addresses non-frontal pose variations by integrating lightweight generative adversarial network (GAN)-based pose frontalisation with memristor-based neuromorphic recognition. The experimental results on two datasets demonstrate the effectiveness of combining adversarial learning with memristive technology, achieving up to 96% identification accuracy. The proposed approach alleviates the computational bottlenecks of conventional AI and offers a scalable, efficient solution for face recognition in dynamic real-world environments. 1 Introduction Face recognition has emerged from the longstanding need to identify individuals for various purposes, including fraud detection [1], authentication and access control [2], surveillance [3], forensic investigation [4], and border security [5]. Despite its widespread adoption and utility, each implementation of face recognition systems suffers from inherent challenges and limitations in practical deployments. Typically, individuals provide frontal biometric images to the relevant authorities, and these images commonly serve as reference templates for custom application contexts. However, in real-world scenarios, it is not always possible to capture front-facing images of individuals of interest. In some deployments, the acquisition process is relatively straightforward, relying on static ground-based cameras operating under controlled imaging conditions, such as those used in smartphone face-unlock systems [6] or ePassport gates [7] at airports. Beyond these constrained and stationary identification settings, emerging surveillance applications increasingly require mobile and adaptive recognition systems capable of operating in dynamic, large-scale environments. In such scenarios, facial imagery is frequently acquired under unconstrained and suboptimal conditions, where environmental factors substantially degrade recognition accuracy. Moreover,

even under favourable imaging conditions, individuals may deliberately attempt to evade detection through partial facial occlusion [8, 9]. Deep learning approaches offer substantial potential to address these challenges through generative augmentation, robust feature extraction, and domain-adaptive learning strategies [10-12]. However, enhanced machine cognition incurs substantial computational costs, which poses a major challenge for edge platforms operating under low size, weight, and power (SWaP) constraints, such as drones [13]. To alleviate this challenge, various strategies have been proposed [14-17]; yet these approaches remain less suitable for mission-critical applications involving sensitive data, such as law enforcement and defence, and are impractical in environments with limited or unreliable connectivity. 1 arXiv:2606.12074v1 [cs.CV] 10 Jun 2026 In order to mitigate the growing computational burden, post-CMOS devices are progressively replacing conventional von Neumann architectures. This has driven the development of emerging computing paradigms, including neuromorphic computing, which seek to overcome the limitations above. Memristors, in particular, holds substantial promise for enabling efficient neural computation on edge devices. These two-terminal analogue devices exhibit non-volatile resistive states and low-power operation, making them suitable for in-memory and neuromorphic computing architectures [18-20]. Memristive neuromorphic systems, often in conjunction with spiking neural networks (SNNs), have demonstrated promising performance in tasks such as classification [21, 22] and generation [23-25]. In this work, we propose a face recognition framework that addresses the non-frontal pose problem and targets resource-constrained edge environments. The framework integrates two complementary strategies. First, a convolutional generative adversarial network (GAN) is employed for face reconstruction, synthesising frontal facial images from non-frontal captures to mitigate self-occlusion caused by the angle between the camera and the subject. Second, memristor-based classifiers are leveraged for face recognition, processing the synthetic frontal images to efficiently and accurately identify the target. In addition to identifying known individuals, the framework also accommodates an auxiliary mechanism for unknown rejection and online learning, as real-world recognition scenarios are inherently open-set and continuously evolving. Together, these techniques aim to harness the potential of AI for mobile and resource-constrained face recognition applications. Evaluated on two independent benchmark datasets, our framework demonstrates significant improvements in identification accuracy, achieving average recognition rates of 96.3% on the CMU Multi-PIE dataset [26] and 73.4% on the DroneFace dataset [27]. 2 Results 2.1 Impact of pose variability on face recognition performance To investigate the impact of pose variance on face recognition performance, we evaluated the proposed memristor-based face classification unit (FCU) on the CMU Multi-PI ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '얼굴 인식 시스템은 딥러닝 기술을 통해 복잡한 시나리오에서 높은 성능과 강건성을 제공하며 괄목할 만한 발전을 이루었습니다. 그러나 이러한 접근 방식은 상당한 계산 오버헤드를 수반하며, 비정면 얼굴 이미지와 같은 문제들을 해결할 수 있는 드론과 같은 자원 제약적인 플랫폼에서의 현장'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 252, 'candidatesTokenCount': 80, 'totalTokenCount': 2296, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 252}], 'thoughtsTokenCount': 1964, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'j8ItavCCNMXQjMcPscyUkAU'}

[논문 후보 3]

제목: Stereo Vision-Based Fall Prediction and Detection using Human Pose Estimation on the AMD Kria K26 SOM
저자: Shreyas Narasimhiah Ramesh, P. D. Rathika, Mahasweta Sarkar, Kristen Wells, Michel Audette, Christopher Paolini
카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency
arXiv ID: 2606.12473
제출일: 2026-06-10T05:08:35+00:00
수정일: 2026-06-10T05:08:35+00:00
최근성: 최근 3일 이내
arXiv PDF: <https://arxiv.org/pdf/2606.12473.pdf>

[초록 원문]

Background and Objective: Falls among elderly people can cause serious injury and reduce quality of life. Timely prediction and detection are essential to prevent harm and support well-being. We propose a portable, low-power, battery-operated, vision-based fall prediction and detection system using HPE on an AMD Kria K26 System-on-Module (SOM). The objective is a non-intrusive, privacy-preserving system for real-time fall detection.

Methods: The system uses an Intel RealSense D455 range-sensing camera connected to the K26 SOM by USB. It captures synchronized RGB and depth frames, 640 x 480 x 3 and 640 x 480 pixels, at 60 FPS. The SOM runs a three-stage pipeline with quantized YOLOX, Anchor-to-Joint (A2J), and fall-detection models. YOLOX identifies human bounding boxes from RGB frames, then discards the RGB frames to preserve privacy. A2J uses depth frames to estimate 15 joint keypoints per person. A CNN uses selected joint coordinates (x, y, z) to classify fall activity. YOLOX was trained on CrowdHuman; A2J on ITOP, MP-3DHP, UR Fall Detection, and a custom SDSU PSG dataset; and the CNN on UR Fall Detection and SDSU PSG. The design used a single-core DPU with a serial pipeline and a dual-core DPU running YOLOX and A2J with multiple threads.

Results: Quantized accuracy was evaluated using IoU $\geq 50\%$ for YOLOX, mAP with a 10-cm rule for A2J, and classification accuracy, $(TP + TN)/(TP + TN + FP + FN)$, for the CNN. Accuracies were 74%, 84.13%, and 75.85%. Throughput improved from 2.5 FPS for the single-threaded pipeline to 4.5 FPS for the multi-threaded version.

Conclusion: Results demonstrate the feasibility of privacy-preserving fall detection on an AMD Kria K26 edge device. On-device HPE and fall classification runs without cloud dependency, supporting elderly monitoring and assistive healthcare. Future work will improve model accuracy and speed.

[PDF 앞부분/서론 일부]

Highlights Stereo Vision-Based Fall Prediction and Detection using Human Pose Estimation on the AMD Kria K26 SOM ShreyasNarasimhiahRamesh, P.D.Rathika, MahaswetaSarkar, KristenWells, MichelAudette, Christopher Paolini

- Design, implementation, and performance evaluation of a novel embedded, accelerated, vision-based fall detection system for elderly at-risk individuals.
- Deployment is on an AMD System on a Module (SoM), with a Zynq UltraScale+ MultiProcessor System on Chip (MPSoC), which supports low power accelerated AI.
- Implementation employs a 3-stage pipeline architecture to process RGB and depth frames through a quantized YOLOX, A2J, and fall detection model.

arXiv:2606.12473v1 [cs.CV] 10 Jun 2026 Stereo Vision-Based Fall Prediction

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '초록wnwn배경 및

목표: 노인 낙상은 심각한 부상을 초래하고 삶의 질을 저하시킬 수 있습니다. 피해를 예방하고 웰빙을 지원하기 위해서는 시기적절한 예측 및 감지가 필수적입니다. 우리는 AMD Kria K26 시스템 온 모듈(SOM)에서 HPE(Human Pose Estimation)를 사용하는}}, 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}}, 'usageMetadata': {'promptTokenCount': 555, 'candidatesTokenCount': 81, 'totalTokenCount': 2599, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 555}], 'thoughtsTokenCount': 1963, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'mMItauHHJuSf1MkP0ZOj6A8'}