

SLM / Edge Device arXiv Daily Summary

생성일: 2026-07-03 05:44 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 30일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 30일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: Little Brains, Big Feats: Exploring Compact Language Models

저자: Dari Baturova, Elena Bruches, Ivan Chernov, Roman Derunets, Arsenii Fomin, Andrey Kostin

카테고리: SLM/Edge/On-device

arXiv ID: 2606.30062

제출일: 2026-06-29T09:55:01+00:00

수정일: 2026-06-29T09:55:01+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.30062.pdf>

[초록 원문]

While large language models have been dominating the research landscape recently, small language models remain highly relevant across various domains; yet, they receive far less attention. In this study, we investigate how smaller language models perform during the generation stage within a Retrieval-Augmented Generation (RAG) system. To benchmark these models effectively, we utilised both open-source and proprietary datasets covering diverse subject areas and question types. Our findings demonstrate that a RAG system with small language models can be executed directly on-device without requiring any GPU hardware within a reasonable time. The experimental code and links to the supplementary materials can be accessed through the GitHub repository: <https://github.com/SibNN/SLM-RAG-EVAL>.

[PDF 앞부분/서론 일부]

Little Brains, Big Feats: Exploring Compact Language Models Dari Baturova, Elena Bruches, Ivan Chernov, Roman Derunets (), Arsenii Fomin, and Andrey Kostin Siberian Neuronets LLC, Novosibirsk, Russia r.derunets@alumni.nsu.ru Abstract.While large language models have been dominating the research landscape recently, small language models remain highly relevant across various domains; yet, they receive far less attention.

In this study, we investigate how smaller language models perform during the generation stage within a Retrieval-Augmented Generation (RAG) system. To benchmark these models effectively, we utilised both open-source and proprietary datasets covering diverse subject areas and question types. Our findings demonstrate that a RAG system with small language models can be executed directly on-device without requiring any GPU hardware within a reasonable time. The experimental code and links to the supplementary materials can be accessed through the GitHub repository¹. Keywords: SmallLanguageModels·Benchmarking·Retrieval-Augmented Generation

1 Introduction

In recent years, Large Language Models (LLMs) have demonstrated remarkable performance across various tasks. However, certain limitations persist, including their inability to rapidly process novel data and effectively manage domain-specific facts. To address these challenges, the RAG approach has been introduced [19]. Conventionally, a RAG system comprises two primary components: Retrieval and Generation. The Retrieval module focuses on identifying the most relevant segments within external knowledge storage - such as databases - in accordance with user queries. Meanwhile, the Generation component leverages retrieved information alongside the user's input to generate accurate responses. Although Retrieval utilises smaller-scale language models to compute text embeddings for both database content and inputs, the Generation phase relies heavily on LLMs to deliver high-quality output. Furthermore, embedding models require significantly fewer computational resources since they encode the knowledge base once. Conversely, LLMs employed during the Generation step demand substantial computing power. Consequently, when sufficient resources or budgetary allocations are unavailable, employing Small Language Models (SLMs) could provide a viable alternative solution. Small Language Models (SLMs) are compact AI models that contain significantly fewer parameters - ranging from millions to several billions - compared to LLMs. These smaller models are engineered to operate efficiently in resource-constrained environments like edge devices, smartphones, or personal computers, requiring less computational power, memory storage, and energy consumption. Their advantages include faster processing times, enhanced privacy due to local operation (often functioning offline), and optimisation for specialised tasks within particular domains instead of broad general-purpose reasoning capabilities. These models proved to be beneficial in scenarios where computational resources are insufficient to support larger-scale LLMs, particularly on edge computing platforms [36]. Additionally, SLMs become essential when handling sensitive information that cannot be transmitted through APIs to external service providers [32]. Such situations necessitate deploying the model directly onto internal hardware, which frequently lacks sufficient capacity to execute highly parameterised models effectively. For instance, executing a model with as many as 14 billion parameters demands substantial computational resources typically beyond the reach of standard end-users. By comparison, SLMs demand far fewer resources, enabling deployment even on CPUs, thereby expanding their applicability across diverse settings. In this work, we investigate the generation capabilities of SLMs within our product-oriented RAG framework, which features local CPU language model inference. To enable a comprehensive evaluation, we construct a benchmark consisting of both open-source and proprietary datasets that cover diverse subject areas and question types. Our results demonstrate that RAG systems built with SLMs can operate efficiently without GPU hardware, making fully on-device deployment feasible for many applications. The overall system is illustrated in Figure 1. The main contributions of this work are summarised as follows:

- Dataset construction: We assemble a Russian-language benchmark that

combines available open-source and proprietary sources to evaluate retrieval-augmented generation performance. - Model benchmarking: We conduct a systematic evaluation of SLMs within a RAG framework. - Extensive analysis: We provide a detailed analysis of performance characteristics, evaluation methods, and practical considerations for deploying SLMs in on-device RAG systems.

[초록 번역]

최근 대규모 언어 모델이 연구 분야를 지배하고 있지만, 소규모 언어 모델은 다양한 영역에서 여전히 높은 관련성을 가지며, 그럼에도 불구하고 훨씬 적은 관심을 받고 있습니다. 본 연구에서는 검색 증강 생성(RAG) 시스템 내에서 소규모 언어 모델이 생성 단계 동안 어떻게 성능을 발휘하는지 조사합니다. 이 모델들을 효과적으로 벤치마킹하기 위해, 우리는 다양한 주제 영역과 질문 유형을 포괄하는 오픈 소스 및 독점 데이터셋을 활용했습니다. 우리의 연구 결과는 소규모 언어 모델을 활용한 RAG 시스템이 GPU 하드웨어 없이도 합리적인 시간 내에 장치에서 직접 실행될 수 있음을 보여줍니다. 실험 코드와 보충 자료 링크는 GitHub 저장소(<https://github.com/SibNN/SLM-RAG-EVAL>)를 통해 접근할 수 있습니다.

[논문 후보 2]

제목: Labeling Training Data for Entity Matching Using Large Language Models

저자: Aaron Steiner, Christian Bizer

카테고리: SLM/Edge/On-device

arXiv ID: 2606.28823

제출일: 2026-06-27T09:15:09+00:00

수정일: 2026-06-27T09:15:09+00:00

최근성: 최근 5일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.28823.pdf>

[초록 원문]

Recent large language models (LLMs) achieve strong performance on entity matching without requiring task-specific training data. However, applying these models to large sets of candidate pairs remains slow and costly. In contrast, entity matchers using traditional machine learning methods or small language models (SLMs), such as RoBERTa, offer much faster inference but require task-specific training data. This paper investigates whether the need to provide task-specific training data can be avoided by using knowledge-distillation workflows, in which an LLM serves as a teacher model to label training pairs that are subsequently used to train a smaller student model. We investigate knowledge distillation for entity matching along the following dimensions: pair-selection strategy, teacher model, label post-processing method, and student model. We evaluate the workflows using the Abt-Buy, Walmart-Amazon, WDC Products, DBLP-ACM, and DBLP-Scholar benchmarks, and compare the performance of student models trained with machine-labeled data to the performance of the same models trained using the benchmark training sets. Our experiments show that student models trained using the machine-labeled sets perform approximately on par with models trained on the benchmark training sets, with the remaining differences in both directions staying below two F1 points. Using GPT-5.2 to label the training sets for all five benchmarks costs US\$28.31 to US\$40.88, whereas manually labeling the same training sets is estimated to require 470 hours of work. At inference time, Ditto is 41.5 to 534 times faster than directly using an LLM to perform the matching tasks. These results indicate that current LLMs, when combined with a suitable pair-selection method,

can substantially reduce or even eliminate the manual effort required to label use case-specific training data for entity matching.

[PDF 앞부분/서론 일부]

Labeling Training Data for Entity Matching Using Large Language Models Aaron Steiner Data and Web Science Group University of Mannheim Mannheim, Germany aaron.steiner@uni-mannheim.de Christian Bizer Data and Web Science Group University of Mannheim Mannheim, Germany christian.bizer@uni-mannheim.de Abstract Recent large language models (LLMs) achieve strong performance on entity matching without requiring task-specific training data. However, applying these models to large sets of candidate pairs remains slow and costly. In contrast, entity matchers using traditional machine learning methods or small language models (SLMs), such as RoBERTa, offer much faster inference but require task-specific training data. This paper investigates whether the need to provide task-specific training data can be avoided by using knowledge distillation workflows, in which an LLM serves as a teacher model to label training pairs that are subsequently used to train a smaller student model. We investigate knowledge distillation for entity matching along the following dimensions: pair-selection strategy, teacher model, label post-processing method, and student model. We evaluate the workflows using the Abt-Buy, Walmart-Amazon, WDC Products, DBLP-ACM, and DBLP-Scholar benchmarks, and compare the performance of student models trained with machine-labeled data to the performance of the same models trained using the benchmark training sets. Our experiments show that student models trained using the machine-labeled sets perform approximately on par with models trained on the benchmark training sets, with the remaining differences in both directions staying below two F1 points. Using GPT-5.2 to label the training sets for all five benchmarks costs US\$28.31 to US\$40.88, whereas manually labeling the same training sets is estimated to require 470 hours of work. At inference time, Ditto is 41.5 to 534 times faster than directly using an LLM to perform the matching tasks. These results indicate that current LLMs, when combined with a suitable pair-selection method, can substantially reduce or even eliminate the manual effort required to label use case-specific training data for entity matching. Keywords entity matching, knowledge distillation, teacher/student architecture, training data labeling, training set construction

1 Introduction

Entity matching (EM) is a core step in data integration. Given two collections of records, EM decides which pairs of records refer to the same real-world entity [5, 6]. Modern EM systems often use supervised learning, including transformer-based matchers [2, 3, 15, 18]. A major limitation of these matchers is their dependence on use case-specific training data in order to achieve high F1 performance [19]. Creating such training data is costly because useful training sets must include obvious matches and non-matches as well as corner cases: same-family products, compatible components, near-duplicate publication titles, and other pairs that are easy to confuse [4, 19]. A corner case is a pair whose surface form gives plausible evidence for both labels. Resolving these pairs usually requires human inspection, raising costs and limiting scalability. Large language models (LLMs) enable us to revisit this bottleneck. Prior work shows that LLMs can directly classify entity pairs in a zero-shot setting, achieving strong entity matching performance [20]. Direct LLM matching is expensive and slow at scale because the large model must be queried for every candidate pair. Smaller language models (SLMs), such as RoBERTa, can process high-volume candidate sets faster with lower resource consumption, but their accuracy depends on the quality of their training set. This shifts the bottleneck from inference to training set construction. This paper analyzes teacher/student knowledge distillation for entity matching [8, 25, 26]. In our setting, an LLM

teacher labels selected candidate pairs, and a computationally cheaper student matcher is trained on the resulting machine-labeled training set. We compare distillation workflows along four dimensions: pair selection, teacher model, label post-processing method, and student model. For pair selection, we use similarity search and active learning. As teachers, we use GPT-5.2, Qwen 3.6 Plus, and the openweight Kimi K2.6. For post-processing, we evaluate a self-review method and a graph-based consistency filter. As students, we use Ditto [15] with RoBERTa, an XGBoost classifier over embeddings, string-similarity, and numeric-similarity features, and the smaller LLMs Qwen3-0.6B, Qwen3-1.7B, and Qwen3-8B. We judge the machine-labeled training sets by their fitness for use [17]: We consider a training set fit for use if a student model trained on it achieves the same F1 score as the same student model trained on the benchmark training set. We also analyze the internal structure of the machine-labeled training sets and the cost of the labeling process. We use the Abt-Buy, Walmart-Amazon, WDC Products, DBLP-ACM, and DBLP-Scholar benchmark datasets for our experiments. The contributions of this paper are: (1) We compare knowledge-distillation workflows for entity matching along four dimensions: pair selection, teacher model, label post-processing, and student model. (2) We show that students trained on machine-labeled sets reach F1 scores comparable to the same students trained on the benchmark. Using GPT-5.2 and Ditto, the best machine-labeled set stays within a range of 1.78 F1 points on every benchmark. (3) We compare the structure of the generated training sets with that of the benchmark sets and find that active learning 1 arXiv:2606.28823v1 [cs.CL] 27 Jun 2026 Steiner and Bizer shifts the class balance toward positives while selecting more corner case pairs. (4) We quantify efficiency along two axes: Labeling all five datasets with GPT-5.2 costs US\$28.31 to US\$40.88, a small fraction of the estimated cost of manual labeling. At inference time, Ditto is 41.5 to 534 times ...

[앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '최근 대규모 언어 모델(LLM)은 작업별 훈련 데이터 없이도 개체 매칭(entity matching)에서 강력한 성능을 달성합니다. 하지만, 이러한 모델을 대규모 후보 쌍 집합에 적용하는 것은 여전히 느리고 비용이 많이 듭니다. 이와 대조적으로, RoBERTa와 같은 전통적인 기계 학습 방법'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 448, 'candidatesTokenCount': 79, 'totalTokenCount': 2492, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 448}], 'thoughtsTokenCount': 1965, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'hM1Gate_IPmVjMcP09rf4Q4'}

[논문 후보 3]

제목: BaseRT: Best-in-Class LLM Inference on Apple Silicon via Native Metal

저자: Prabod Rathnayaka, Fabian Waschkowski, Lukas Wesemann

카테고리: SLM/Edge/On-device

arXiv ID: 2607.00501

제출일: 2026-07-01T06:37:11+00:00

수정일: 2026-07-01T06:37:11+00:00

최근성: 최근 1일 이내

arXiv PDF: <https://arxiv.org/pdf/2607.00501.pdf>

[초록 원문]

We present BaseRT, a native Metal inference runtime for large language models (LLMs) on Apple Silicon, and report the highest inference throughput on this hardware to date. Existing runtimes, including llama.cpp and MLX-based frameworks, incur overhead from abstractions not designed for Metal's execution model or Apple Silicon's unified memory topology. By building natively on Metal with chip-specific kernel fusion, unified memory-aware optimisation, and custom dispatch logic, BaseRT recovers performance that framework-based approaches leave on the table. BaseRT supports a wide range of model families across eight quantisation formats (Q2 to FP16) on all Apple M-series devices. In this paper, we evaluate the Qwen3, Llama 3.2, and Gemma 4 families at Q4 and Q8 quantisation on M3 and M4 Pro devices. BaseRT achieves up to 1.56x higher decode throughput than llama.cpp and up to 1.35x higher than MLX, with substantially larger margins on prefill for mixture-of-experts models, delivering consistent best-in-class throughput from sub-1B to 30B parameter models. These results establish Apple Silicon as a more capable inference platform than previously reported, with direct implications for the emerging edge inference paradigm: as privacy requirements, latency constraints, and cloud cost pressures drive inference toward on-device deployment, performance-optimised local runtimes are a critical enabling layer for this transition. BaseRT is publicly available at <https://github.com/basecompute/baseRT>

[PDF 앞부분/서론 일부]

BaseRT: Best-in-Class LLM Inference on Apple Silicon via Native Metal Prabod Rathnayaka Fabian Waschkowski Lukas Wesemann Base Compute, Melbourne, Australia Abstract We present BaseRT, a native Metal inference runtime for large language models (LLMs) on Apple Silicon, and report the highest inference throughput on this hardware to date. Existing runtimes, including llama.cpp and MLX-based frameworks, incur overhead from abstractions not designed for Metal's execution model or Apple Silicon's unified memory topology. By building natively on Metal with chip-specific kernel fusion, unified memory-aware optimisation, and custom dispatch logic, BaseRT recovers performance that framework-based approaches leave on the table. BaseRT supports a wide range of model families across eight quantisation formats (Q2 to FP16) on all Apple M-series devices. In this paper, we evaluate the Qwen3, Llama 3.2, and Gemma 4 families at Q4 and Q8 quantisation on M3 and M4 Pro devices. BaseRT achieves up to 1.56x higher decode throughput than llama.cpp and up to 1.35x higher than MLX, with substantially larger margins on prefill for mixture-of-experts models, delivering consistent best-in-class throughput from sub-1B to 30B parameter models. These results establish Apple Silicon as a more capable inference platform than previously reported, with direct implications for the emerging edge inference paradigm: as privacy requirements, latency constraints, and cloud cost pressures drive inference toward on-device deployment, performance-optimised local runtimes are a critical enabling layer for this transition. BaseRT is publicly available at <https://github.com/basecompute/baseRT>. 1 Introduction AI inference demand is growing at a rate that challenges the scalability of centralised cloud infrastructure. Token usage across major providers has grown by roughly an order of magnitude year-on-year as evidenced by token usage via Google Cloud API and a broader mix of providers on Open Router [1, 2]. However, the majority of enterprise adoption is still nascent and this trend is likely to continue [3]. Global inference compute is projected to overtake training compute for the first in 2027, with AI inference expected to make up 40% of global data center compute by 2030 [4]. This trajectory places increasing pressure on the economic and architectural assumptions underlying cloud-only inference, and makes a

compelling case for a structural shift toward edge inference: running LLMs locally on consumer and professional hardware. The case for this shift rests on four independent drivers. Privacy and Data Residency: Prompts processed in the cloud are subject to multi-tenancy, third-party infrastructure risk, and complex legal jurisdictions [5], risks that Gartner projects will cause over 40% of AI-related data breaches by 2027 through insufficient oversight of cross-border prompt routing [6]. Local inference keeps all data within controlled environments, enabling compliance with air-gapped and zero-trust requirements. Latency: Cloud inference adds request handling, queueing, and GPU scheduling overhead that can push time-to-first-token (TTFT) into the hundreds of milliseconds, especially under load [7]. On-device inference Correspondence: prabod@basecompute.co 1 arXiv:2607.00501v1 [cs.CL] 1 Jul 2026 Qwen3-0.6B Llama-3.2-1B Llama-3.2-3B 0 200 400 +35% Model Decode throughput (tok/s) 128 256 512 1024 2048 400 600 800 +78% Prompt length (tokens) Prefill throughput (tok/s) BaseRT MLX llama.cpp Figure 1: BaseRT delivers best-in-class throughput on Apple Silicon. Decode throughput (left) is improved by 1.15-1.56× over llama.cpp and up to 1.35× over MLX across the Q4 models tested on Apple M4 Pro. For prefill throughput (right), BaseRT leads across all prompt lengths for the Qwen3-30B-A3B model in 4-bit quantisation with up to 1.78×improvement over MLX. avoids network and queueing delays, often reducing latency enough to support sub-100 ms interactive responses and making real-time robotic [8] and responsive agentic workflows [9, 10] feasible. Connectivity: A hard dependency on external network availability means that failures in networking, authentication, or shared cloud infrastructure can render AI systems entirely unavailable, regardless of whether the underlying model is functioning. Local inference removes this dependency, enabling deterministic operation in low-connectivity or air-gapped environments and ensuring continuity for latency-sensitive applications in the field. Recent cloud outages underscore the potential impact of this [11, 12]. Cost: Cloud inference pricing scales linearly with usage, whereas local inference converts this into a fixed hardware cost, with marginal cost per inference approaching zero at scale [13]. The hardware precondition for this shift has largely been met. Across consumer and professional device categories, purpose-built AI accelerators now support useful on-device LLM inference: Qualcomm's Snapdragon X Elite includes a Hexagon NPU and is positioned to run LLMs over 13B parameters on-device, while Intel's Core Ultra Series 2 and AMD's Ryzen AI platforms also integrate dedicated NPUs, with runtimes such as OpenVINO and ONNX Runtime providing execution paths for quantized models on these devices [14-16]. Among these platforms, Apple Silicon stands out for its combination of high memory bandwidth, large unified memory capacity, and a mature GPU compute stack [17]. Memory has historically been the primary limiting factor for local LLM inference: model weights must be streamed from memory to compute units for every generated token, placing a hard capacity and bandwidth constraint on which models can run locally. Apple's unified memory architecture removed the traditional segregation between CPU and GPU memory pools, giving the GPU direct access to the full system memory at high bandwidth, a structural change that made it practical to run large models locally. Modern M-series devices can run q ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '본 논문에서는 Apple Silicon용 대규모 언어 모델(LLM)을 위한 네이티브 Metal 추론 런타임인 BaseRT를 제안하며, 현재까지 이 하드웨어에서 가장 높은 추론 처리량을 달성했음을 보고합니다. llama.cpp 및 MLX 기반 프레임워크를 포함한 기존 런타임들은 Metal의 실행 모델'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 393,

'candidatesTokenCount': 80, 'totalTokenCount': 2437, 'promptTokensDetails': [{ 'modality': 'TEXT', 'tokenCount': 393}], 'thoughtsTokenCount': 1964, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'jc1Gap3EHv-u-8YP_YXZ6Q4'}