

SLM / Edge Device arXiv Daily Summary

생성일: 2026-08-30 06:55 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 30일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 30일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: Quantization Effects on Bangla Language Understanding in Large Language Models: A Systematic Evaluation

저자: Ismail Hossain, Nafi Ullah Shafin, Mohammad Abdullah Al Mumin

카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency

arXiv ID: 2608.24615

제출일: 2026-08-25T14:36:09+00:00

수정일: 2026-08-25T14:36:09+00:00

최근성: 최근 4일 이내

arXiv PDF: <https://arxiv.org/pdf/2608.24615.pdf>

[초록 원문]

Post-training quantization lowers the memory footprint of Large Language Models (LLMs) and speeds up inference, which is why it is now common for on-device deployment. Most of what we know about its effects, however, comes from English benchmarks. It is not clear whether the same holds for morphologically complex, low-resource languages such as Bangla, and this gap is what we address here. We evaluate three model families---Qwen-2.5-7B, LLaMA-3.1-8B, and GPT-OSS-20B---in full precision and in three quantized formats (GPTQ-Int8, GPTQ-Q8, GGUF-W8A16) across five Bangla natural language understanding benchmarks (Bangla MMLU, CommonsenseQA-BN, OpenBookQA-BN, PIQA-BN, and BoolQ-BN), using zero-shot evaluation through lm-evaluation-harness. To our knowledge this is the first controlled comparison of quantization formats on Bangla NLU. The three families do not respond the same way: GPT-OSS loses up to 57.35% accuracy on reasoning-heavy tasks under GGUF-W8A16, while Qwen and LLaMA hold steady under GPTQ, and in a few cases the quantized version edges out the full-precision one. BoolQ-BN, a comprehension task, stays stable across all three families regardless of format. Taken together, these results suggest quantization can work well for Bangla deployment, but the choice of architecture and quantization method matters more than the bit width alone. We discuss what this

means for practitioners choosing a model to run on constrained hardware.

[PDF 앞부분/서론 일부]

Quantization Effects on Bangla Language Understanding in Large Language Models: A Systematic Evaluation Ismail Hossain Nafi Ullah Shafin Mohammad Abdullah Al Mumin Institute of Information and Communication Technology (IICT) Shahjalal University of Science and Technology (SUST), Sylhet, Bangladesh {ismail33, nafi04}@student.sust.edu, mumin-cse@sust.edu

Abstract Post-training quantization lowers the memory footprint of Large Language Models (LLMs) and speeds up inference, which is why it is now common for on-device deployment. Most of what we know about its effects, however, comes from English benchmarks. It is not clear whether the same holds for morphologically complex, low-resource languages such as Bangla, and this gap is what we address here. We evaluate three model families—Qwen-2.5-7B, LLaMA-3.1-8B, and GPT-OSS-20B—in full precision and in three quantized formats (GPTQ-Int8, GPTQ-Q8, GGUF-W8A16) across five Bangla natural language understanding benchmarks (Bangla MMLU, CommonsenseQA-BN, OpenBookQA-BN, PIQA-BN, and BoolQBN), using zero-shot evaluation through lm-evaluation-harness. To our knowledge this is the first controlled comparison of quantization formats on Bangla NLU. The three families do not respond the same way: GPT-OSS loses up to 57.35% accuracy on reasoning-heavy tasks under GGUF-W8A16, while Qwen and LLaMA hold steady under GPTQ, and in a few cases the quantized version edges out the full-precision one. BoolQ-BN, a comprehension task, stays stable across all three families regardless of format. Taken together, these results suggest quantization can work well for Bangla deployment, but the choice of architecture and quantization method matters more than the bit width alone. We discuss what this means for practitioners choosing a model to run on constrained hardware.

1 Introduction Large language models such as GPT-4, LLaMA, and Qwen now deliver strong performance across a wide range of NLP tasks (Jin et al., 2024; Li et al., 2024), but running them is expensive. Frontier models need tens to hundreds of gigabytes of GPU memory, which puts them out of reach in places where computing infrastructure is limited, including much of South Asia, home to more than 230 million Bangla speakers. Post-training quantization (PTQ) is one way around this problem (Lang et al., 2024; Lee et al., 2025). Dropping weight precision from 16-bit floating point to 8-bit integers or lower cuts memory use by 2×–8× and speeds up inference by 2×–5×, with little extra engineering effort, enough to make on-device deployment realistic on laptops, phones, and edge servers. Methods such as GPTQ and AWQ push this further, using second-order weight information or activation-aware compression to limit accuracy loss (Frantar et al., 2023; Liu et al., 2025). Nearly all of this evaluation work, though, happens on English benchmarks: MMLU, GSM8K, HumanEval (Ding et al., 2024; Li et al., 2024). That leaves a question we have not seen answered in the literature: does quantization error compound differently for a linguistically complex, low-resource language like Bangla? Bangla's agglutinative morphology, its conjunct consonant clusters, and the grapheme composition rules of its Unicode script all complicate tokenization in ways that could plausibly make representation degradation worse under compression (Bhowmik et al., 2025; Nahin et al., 2025).

Research questions. RQ1. How does post-training quantization affect LLM accuracy on Bangla NLU benchmarks? RQ2. Which quantization formats (GPTQ-Int8, GPTQ-Q8, GGUF-W8A16) best preserve Bangla accuracy? RQ3. Are specific Bangla task categories (reasoning, commonsense, comprehension) differentially sensitive to quantization? Contributions. This paper makes four contributions. 1. We run the first controlled, multi-family

comparison of PTQ effects on Bangla NLU that we are aware of, covering 15 model- benchmark pairs across five task categories. 2. We find a sharp split between model families: GGUF-quantized GPT-OSS degrades by up to 57.35% on reasoning tasks, while GPTQ-quantized Qwen and LLaMA show under 1.5% degradation, and sometimes a small improvement, across all five benchmarks. 3. Reasoning and commonsense benchmarks turn out to be far more fragile under quantization than reading comprehension, in the Bangla setting specifically. 4. We turn these results into concrete recommendations for choosing a model architecture and quantization format for on-device Bangla NLP.

2 Related Work

2.1 Multilingual LLMs and Low-Resource Languages

GPT, LLaMA, Qwen, Mixtral, and Mistral are all pretrained on large multilingual corpora and generalize well in zero-shot settings for the languages that dominate their training data. Performance drops off for low-resource languages, and the usual reasons are sparse token coverage, tokenization mismatches, and morphological complexity (Bhowmik et al., 2025). Bangla runs into all three: agglutinative morphology, conjunct-consonant orthography, and a comparatively small web-scale footprint. Even strong multilingual models underperforming on Bangla tasks (Bhowmik et al., 2025; Nahin et al., 2025). Two efforts try to close this gap directly. BanglaBERT is a BERT-style encoder trained on curated Bangla text, and IndicLLMs extends multilingual pretraining to South Asian scripts more broadly. The largest recent effort is TituLLMs (Nahin et al., 2025), a family of Bangla-native decoder-only models built with Bangla-aware subword tokenizers and benchmarked across CommonsenseQABN, MMLU-BN, PIQA-BN, and BoolQ-BN. The TituLLMs authors argue that tokenizer design and corpus quality are what mainly control Bangla NLU performance, which raises a question they do not answer: if tokenizer and corpus quality matter this much, does compressing the model after training erode that advantage? We did not find any prior work that looks at quantization and Bangla-specific linguistic properties together.

2.2 Post-Training Quantization

... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '사후 훈련 양자화(Post-training quantization)는 대규모 언어 모델(LLM)의 메모리 점유율을 낮추고 추론 속도를 향상시켜, 현재 온디바이스(on-device) 배포에 널리 활용되고 있습니다. 그러나 그 효과에 대한 대부분의 지식은 영어 벤치마크에서 도출된 것입니다'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 419, 'candidatesTokenCount': 82, 'totalTokenCount': 2463, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 419}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'VWWTapWHA_LkjMcPzu6egQs'}

[논문 후보 2]

제목: Retrieval Heads Meet Vision: Uncovering How VLMs Locate and Extract Visual Information

저자: Chanhho Park, Daehyeon Choi, Jihyun Lee, Minhyuk Sung

카테고리: Format-LoRA/Structured Output

arXiv ID: 2608.27417

제출일: 2026-08-27T17:43:58+00:00

수정일: 2026-08-27T17:43:58+00:00

최근성: 최근 2일 이내

[초록 원문]

Vision-language models (VLMs) can locate an image region referred to by a text prompt and route the corresponding visual evidence to the output, yet the internal mechanism behind this behavior is not understood. Inspired by retrieval heads in large language models, we ask whether VLMs contain an analogous mechanism for visual retrieval. We answer affirmatively by introducing Visual Retrieval Heads (VRHs), a small subset of attention heads (about 1.7-2.6%) that are causally responsible for grounding text descriptions to image regions. To find them, we recast existing head-scoring methods under a unified design space over query tokens, key aggregation, and cross-sample aggregation. We then show that scoring attention from output prediction tokens with a sum over the ground-truth referent region most reliably identifies causal heads. Across eleven VLMs and five referring-expression benchmarks, masking only the top 20 VRHs reduces grounding accuracy by up to 80 percentage points, while masking the same number of random heads has little effect. Beyond replicating the causal-sparse-universal triad established for text retrieval heads, VRHs exhibit several properties not previously reported: they generalize across visual reference tasks, remaining causal on attribute, spatial, counting, and visual-math benchmarks despite being discovered through bounding-box prediction; they are functionally specific, preserving output format while corrupting localization; and they are architecturally shared, transferring causally across VLMs that share an LLM backbone but differ in vision encoder, projector, and instruction tuning.

[PDF 앞부분/서론 일부]

Retrieval Heads Meet Vision: Uncovering How VLMs Locate and Extract Visual Information Chanhoo Park¹ Daehyeon Choi¹ Jihyun Lee² Minhyuk Sung¹ 1KAIST 2Independent Researcher {charlieppark, daehyeonchoi, mhsung}@kaist.ac.kr jihyunlee1027@gmail.com "Blackguyin" [463, 150, 552, 358] (Correct) [1, 10, 644, 443] (Wrong) Unmasked VRH Masked The tiny bicycle in the image is located at the center-left and has a purple frame. Answer: Purple (Correct) The image does not contain any a bicycle, but only cars and buses. Answer: No (Wrong) Unmasked VRH Masked "The tiny bicycle is what color?" Visual Grounding Visual Question Answering Figure 1: Visual Retrieval Heads mediate visual reference resolution in VLMs. We identify a sparse set of attention heads, Visual Retrieval Heads (VRHs), that are causally necessary for resolving the image region referred to by the text prompt. On visual grounding (left), masking the VRHs redirects prediction-stage attention away from the ground-truth referent and causes the model to output a delocalized bounding box. The same heads, discovered only from grounding, also transfer to visual question answering (right): masking them removes attention to the referred object and leads to a fluent but visually unfaithful answer. Yellow boxes denote ground-truth referents; dashed yellow ellipses indicate regions where attention vanishes after VRH masking. Abstract Vision-language models (VLMs) can locate an image region referred to by a text prompt and route the corresponding visual evidence to the output, yet the internal mechanism behind this behavior is not understood. Inspired by retrieval heads in large language models, we ask whether VLMs contain an analogous mechanism for visual retrieval. We answer affirmatively by introducing Visual Retrieval Heads (VRHs), a small subset of attention heads (about 1.7-2.6%) that are causally responsible for grounding text descriptions to image regions. To find them, we recast existing head-scoring methods under a unified design space over query tokens, key aggregation, and cross-sample

aggregation. We then show that scoring attention from output prediction tokens with a sum over the ground-truth referent region most reliably identifies causal heads. Across eleven VLMs and five referring-expression benchmarks, masking only the top 20 VRHs reduces grounding accuracy by up to 80 percentage points, while masking the same number of random heads has little effect. Beyond replicating the causal-sparse-universal triad established for text retrieval heads, VRHs exhibit several properties not previously reported: they generalize across visual reference tasks, remaining causal on attribute, spatial, counting, and visual-math benchmarks despite being discovered through boundingbox prediction; they are functionally specific, preserving output format while corrupting localization; and they are architecturally shared, transferring causally across VLMs that share an LLM backbone but differ in vision encoder, projector, and instruction tuning. Preprint. arXiv:2608.27417v1 [cs.CV] 27 Aug 2026

1 Introduction

How do foundation models locate a specific piece of information buried in a long input context? This "needle-in-a-haystack" question has recently been answered, at least partially, for large language models (LLMs): a small set of attention heads called retrieval heads [1] is largely responsible for routing relevant input tokens to the output. These heads exhibit three properties that together make them a meaningful unit of analysis. They are causal: ablating them collapses long-context retrieval while leaving fluency intact. They are sparse: fewer than 5% of all heads carry the behavior. And they are universal: they appear across model families and scales, suggesting that long-context retrieval converges onto a shared internal mechanism rather than an idiosyncratic implementation. This observation motivates our key question: whether Vision-Language Models (VLMs) contain an analogous mechanism for visual retrieval—locating an image region referred to by a text prompt and routing it to the output. Existing extensions of retrieval-head analysis to VLMs do not yet answer it. OCR Heads [2] and VERA [3] identify heads that retrieve textual evidence from images, but only when the image is itself a rendering of text; the retrieval target is still a string of characters, not a general visual concept. Localization Heads [4] move beyond rendered text and aim to identify heads whose attention maps align with referred objects, but the analysis stops at attention shape: the heads are not characterized by causal necessity. In this work we ask whether causal, universal, and sparse retrieval heads exist in VLMs for general image retrieval, and how to find them. We answer affirmatively by introducing Visual Retrieval Heads (VRHs), a small subset of attention heads that are causally responsible for grounding text descriptions to image regions. We show that these heads share the defining properties of their text-only counterparts. We use referring-expression visual grounding [5] as our probing task: given an image and a referring expression, the model must output a bounding box for the referent. This task makes the retrieval target spatially explicit; the ground-truth bounding box defines exactly which visual tokens the model needs to consult. This lets us define a head's contribution to retrieval by how strongly it attends from the model's prediction-stage tokens to the visual tokens inside that box. Beyond identifying VRHs, our contributions are three-fold. First, on the methodology side, we observe that existing head-scoring methods can all be written in a single form, with a per-head score obtained by aggregating attention weights over a set of key tokens (the tokens to be retrieved) for each query token, and then aggregating these per-query scores across all queries. Under this view, prior methods differ along three axes: the query token set (input prompt tokens vs. output prediction tokens), t ...

[앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '시각-언어

모델(VLM)은 텍스트 프롬프트가 참조하는 이미지 영역을 찾아 해당 시각적 증거를 출력으로 보낼 수 있지만, 이러한 행동의 내부 메커니즘은 아직 이해되지 않고 있습니다. 대규모 언어 모델(LLM)의 검색 헤드에서 영감을 받아, 우리는 VLM에 시각적 검색을 위한 유사}}, 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}}, 'usageMetadata': {'promptTokenCount': 373, 'candidatesTokenCount': 82, 'totalTokenCount': 2417, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 373}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'XVWTateTNLHZjMcP5NDusAQ'}

[논문 후보 3]

제목: Circuit Condensation: Post-Training that Concentrates a Behavior's Causal Circuit

저자: Sai Adith Senthil Kumar

카테고리: Format-LoRA/Structured Output

arXiv ID: 2608.27254

제출일: 2026-08-27T15:38:58+00:00

수정일: 2026-08-27T15:38:58+00:00

최근성: 최근 2일 이내

arXiv PDF: <https://arxiv.org/pdf/2608.27254.pdf>

[초록 원문]

One approach to mechanistic interpretability explains behavior through circuits: the components and connections that carry it. Frozen discovery often returns hundreds of edges, making them hard to inspect, compare, or verify exhaustively. We introduce Circuit Condensation, which post-trains models to concentrate behaviors into smaller causal graphs. Each round prunes low-attribution edges and trains a low-rank adapter to match the original through what remains, retaining the cut only if task performance and general capability survive. Across four behaviors and eight models, condensed circuits are smaller than the strongest frozen baseline in 30 of 32 settings, by $8.1\times$ on average and up to $316\times$. Repeating the search without weight updates produces larger circuits in 29 of 32 settings, showing that weight updates, rather than search alone, drive the reduction. Testing every subset of 19 circuits finds 11 that cannot be reduced and reveals removable edges in the rest. Pair ablations expose dependencies between edges, showing that their effects cannot be understood independently. On indirect object identification, condensation isolates 24 heads, 17 of them with documented roles, against 61 heads and 36 undocumented ones for the matched frozen circuit: a sufficient sub-circuit of the published mechanism rather than a reconstruction of it. The resulting circuit tracks the original model's next-token distribution and predicts its errors.

[PDF 앞부분/서론 일부]

Circuit Condensation: Post-Training that Concentrates a Behavior's Causal Circuit Sai Adith Senthil Kumar George Mason University ssenthi2@gmu.edu Abstract One approach to mechanistic interpretability explains behavior through circuits: the components and connections that carry it. Frozen discovery often returns hundreds of edges, making them hard to inspect, compare, or verify exhaustively. We introduce Circuit Condensation, which post-trains models to concentrate behaviors into smaller causal graphs. Each round prunes low-attribution edges and trains a low-rank adapter to match the original through what remains, retaining the cut only if task performance and

general capability survive. Across four behaviors and eight models, condensed circuits are smaller than the strongest frozen baseline in 30 of 32 settings, by $8.1\times$ on average and up to $316\times$. Repeating the search without weight updates produces larger circuits in 29 of 32 settings, showing that weight updates, rather than search alone, drive the reduction. Testing every subset of 19 circuits finds 11 that cannot be reduced and reveals removable edges in the rest. Pair ablations expose dependencies between edges, showing that their effects cannot be understood independently. On indirect object identification, condensation isolates 24 heads, 17 of them with documented roles, against 61 heads and 36 undocumented ones for the matched frozen circuit: a sufficient subcircuit of the published mechanism rather than a reconstruction of it. The resulting circuit tracks the original model's next-token distribution and predicts its errors.

1 Introduction Mechanistic interpretability explains a language model through the internal computations that produce its behavior, testing those explanations by intervention rather than observation alone. One approach analyzes that computation as a circuit: a subgraph of components and connections sufficient to carry a particular behavior (Olah et al., 2020; Elhage et al., 2021; Olsson et al., 2022; Wang et al., 2023). The circuit view makes a precise claim that can be checked: a circuit is faithful if the model still performs the behavior when activations outside it are replaced. Faithfulness is only a starting point. To understand a circuit, we would also like to know whether it contains unnecessary components and how its retained edges work together. These checks quickly become combinatorial, and circuits recovered from real models are often too large to test exhaustively. Proving that no smaller circuit suffices requires testing every subset, while testing whether retained edges depend on one another requires ablating every pair. Wang et al. (2023) likewise found exhaustive completeness testing infeasible for an indirect object identification (IOI) circuit containing 26 attention heads and used three subset-sampling strategies instead. A 13-edge circuit admits $8,192$ subsets and 78 pairs; a 400-edge circuit admits 2^400 subsets. Size decides which questions can be asked at all, which is why it is a practical proxy for interpretability (Bhaskar et al., 2024; Gao et al., 2025). The natural response is to search the fixed model more carefully, and most work does. Activation and path patching exchange internal states between clean and corrupted inputs (Goldowsky-Dill et al., 2023; Zhang & Nanda, 2024), Edge Attribution Patching and its integrated-gradient and saturation-corrected variants EAP-IG and EAP-GP scale that search with gradients (Syed et al., 2024; Hanna et al., 2024; Zhang et al., 2025), and learned gates and feature-level decompositions offer further routes to sparse structure (Bhaskar et al., 2024; Yu et al., 2025; Marks et al., 2025). These methods may improve the search, but they do not change how the model carries the behavior. The exact circuit may still shift with the estimator, the data, and the choice among equally faithful graphs (Méloux et al., 2026; Chen et al., 2026b).

1 arXiv:2608.27254v1 [cs.LG] 27 Aug 2026

Figure 1: One round of Circuit Condensation. Rank surviving edges by causal importance, cut the weakest, then train only the adapter to reproduce the original model through what is left. A round is kept only if the target behavior and general language ability both survive; otherwise the previous state is restored and a smaller cut tried. C 1 is the smallest circuit ever accepted. We therefore ask a different question: rather than searching harder for where a behavior already lives, can we move it? Circuit Condensation treats findability as a property a model can be trained to have. Starting from a fresh low-rank adapter (Hu et al., 2022) with every edge open, each round ranks the surviving connections by causal importance, deletes the weakest, and trains only the adapter to reproduce the original model's outputs through what remains. A controller on held-out data accepts a deletion only if the target behavior and held-out

language-modeling performance both survive, restoring the previous state otherwise (Figure 1). We call the smallest accepted circuit C 1. Two things must hold for this to be worth doing, and we test both. The circuit must get small enough to change what is computable rather than merely become smaller, and it must still describe the model we started from; explaining only the modified network would not establish that connection. The reduced circuits make exhaustive subset and pairwise tests runnable (§5.3). They also track the original model's next-token distribution, at a median KL of 0.215 across the grid and 0.056 on the IOI anchor, where the matched frozen circuit sits at 0.50, and predict where that model will fail better than a frozen circuit of the same size (§5.4). Contributions.

- We formulate circuit findability as a trainable property of a model rather than a fixed target for search, and give an adaptive prune, heal, and backtrack procedure that concentrates a named behavior under held-out faithfulness and capability constraints, returning a usable circuit in every cell without pe ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '기계론적 해석 가능성(mechanistic interpretability)에 대한 한 가지 접근 방식은 모델의 행동을 이를 수행하는 구성 요소와 연결인 회로(circuit)를 통해 설명하는 것이다. 그러나 기존의 "frozen discovery" 방식은 종종 수백 개의 엷지를 도출하여, 이를 철저히 검사하고, 비교하며, 검증하기 어렵게 만든'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 358, 'candidatesTokenCount': 81, 'totalTokenCount': 2402, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 358}], 'thoughtsTokenCount': 1963, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'ZIWTatvyAqWujMcP3PnMiQ8'}