

SLM / Edge Device arXiv Daily Summary

생성일: 2026-08-23 04:48 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 30일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 30일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: FlashAttention for Scalable Vector Architectures

저자: Sonia Rani Gupta, Nikela Papadopoulou, Miquel Pericàs

카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency

arXiv ID: 2608.18656

제출일: 2026-08-19T08:02:17+00:00

수정일: 2026-08-19T08:02:17+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2608.18656.pdf>

[초록 원문]

Inference with transformer models on CPUs is increasingly important, especially for Small Language Models (SLMs), where vector architectures are emerging as a promising execution substrate. The attention module is a major bottleneck due to high memory bandwidth requirements; FlashAttention mitigates this by fusing operations to improve data locality and reduce intermediate memory traffic. In this paper, we present FlashAttention-V, a blocked FlashAttention for scalable vector architectures that adapts efficiently from short to very long vectors by exploiting parallelism across attention heads, inter-head packing to enable efficient utilization of vector lengths beyond the head dimension, and improving vector register utilization and memory access locality. We integrate FlashAttention-V into ggml within llama.cpp and evaluate it on TinyLlama, Llama 3.2, Qwen2.5, and Pythia-410M using gem5 and a Banana Pi BPI-F3. On the Banana Pi BPI-F3, we confirm that loop reordering and loop unrolling across attention heads are effective optimization principles, scaling performance gains with larger models and most pronounced with short contexts and during decoding. Simulation-based analysis shows that FlashAttention-V achieves 22x-42x speedup over scalar FlashAttention at 512-bit VL in prefill, with an additional 2x-2.5x gain scaling to 64 lanes and 4096-bit VL. During decode, FlashAttention-V achieves 8x-11x speedup using 512-bit vector

lengths over scalar FlashAttention, with performance showing diminishing sensitivity to vector width and lane count due to single-token, memory-bound execution. We further identify structural bottlenecks in Q8_0 quantized linear layers that limit arithmetic amortization under long-vector execution, consistent across RVV and Arm SVE, indicating that current quantization formats pose a fundamental challenge to long-vector scalability.

[PDF 앞부분/서론 일부]

FlashAttention for Scalable Vector Architectures Sonia Rani Gupta Chalmers University of Technology Gothenburg, Sweden soniar@chalmers.se Nikela Papadopoulou University of Glasgow Glasgow, UK nikela.papadopoulou@glasgow.ac.uk Miquel Pericàs Chalmers University of Technology Gothenburg, Sweden miquelp@chalmers.se

Abstract Inference with transformer models on CPUs is increasingly important, especially for Small Language Models (SLMs), where vector architectures are emerging as a promising execution substrate. The attention module is a major bottleneck due to high memory bandwidth requirements; FlashAttention mitigates this by fusing operations to improve data locality and reduce intermediate memory traffic. In this paper, we present FlashAttention-V, a blocked FlashAttention for scalable vector architectures that adapts efficiently from short to very long vectors by exploiting parallelism across attention heads, inter-head packing to enable efficient utilization of vector lengths beyond the head dimension, and improving vector register utilization and memory access locality. We integrate FlashAttention-V into ggml within llama.cpp and evaluate it on TinyLlama, Llama 3.2, Qwen2.5, and Pythia-410M using gem5 and a Banana Pi BPI-F3. On the Banana Pi BPI-F3, we confirm that loop reordering and loop unrolling across attention heads are effective optimization principles, scaling performance gains with larger models and most pronounced with short contexts and during decoding. Simulation-based analysis shows that FlashAttention-V achieves 22×-42× speedup over scalar FlashAttention at 512-bit VL in prefill, with an additional 2×-2.5× gain scaling to 64 lanes and 4096-bit VL. During decode, FlashAttention-V achieves 8×-11× speedup using 512-bit vector lengths over scalar FlashAttention, with performance showing diminishing sensitivity to vector width and lane count due to single-token, memory-bound execution. We further identify structural bottlenecks in Q8_0 quantized linear layers that limit arithmetic amortization under long-vector execution, consistent across RVV and Arm SVE, indicating that current quantization formats pose a fundamental challenge to long-vector scalability.

1 Introduction

Transformer-based models underpin modern AI systems, powering applications ranging from chatbots and coding assistants to machine translation and AI agents, spanning a wide range of scales. Large Language Models (LLMs), with hundreds of billions of parameters, are typically deployed in data centers, whereas Small Language Models (SLMs), in the 1-10B parameter range, are optimized for edge deployment [19, 23, 46]. Across this spectrum, transformer inference demands high throughput, low latency, and strong energy efficiency, from large-scale server deployments to battery-constrained edge platforms [3, 4]. The attention module is a core component of all transformer architectures [41]. Multi-head attention (MHA) extends the original formulation by computing multiple attention heads in parallel, enabling the model to capture diverse relational patterns. To reduce the memory and bandwidth overhead of storing the key-value (KV) cache during inference, variants such as Multi-Query Attention (MQA) and Grouped-Query Attention (GQA) share keys and values across query heads, reducing the KV cache footprint [1, 23, 37]. Efficient execution of these attention variants has been explored across diverse hardware platforms. Attention implementations have been optimized for GPUs [15, 20, 32, 42] and dedicated AI accelerators [17, 18, 42] to maximize throughput for both training and inference. They have also

been explored on CPUs to improve transformers inference due to the CPUs' high availability, low latency, and portability across edge devices and data centers [15, 40, 42]. Although these variants differ in how queries, keys, and values are organized, they all rely on the same underlying self-attention computation. Self-attention requires computing and storing large intermediate matrices, such as score matrix $S = QK^T$, where Q and K represent Queries and Keys, as well as the resulting softmax attention weights. This leads to significant memory capacity and bandwidth overhead, which becomes particularly pronounced as the sequence length grows. To address this memory bottleneck, Rabe and Staats [34] introduced a memory-efficient attention algorithm with online softmax, enabling exact self-attention without storing the full intermediate score matrix S . Building on this foundation, FlashAttention [11, 12] further optimizes execution by using tiling and fused kernels to keep intermediate data in on-chip GPU memory. While originally optimized for GPUs, recent work has explored FlashAttention on CPUs with vector units to improve transformer inference [15, 39]. Modern vector processors with vector-length-agnostic Instruction Set Architectures (ISAs), such as the RISC-V Vector Extension (RVV) and the ARM Scalable Vector Extension (Arm SVE), support variable vector lengths. This makes them attractive for HPC and AI workloads, which can exploit the SIMD parallelism exposed by these architectures. However, FlashAttention exposes limited vector-level parallelism along the head dimension. Queries, Keys, and Values have dimensions $N \times D$, where N is the sequence length, and D is the head dimension. The FlashAttention output has the same shape, $N \times D$, with the size of N varying widely (collapsing to 1 during token generation) and D being small, typically 64 or 128 (see Table 3). Existing implementations of FlashAttention on RISC-V, ARM, and x86 follow a restrictive design choice: the vector length (VL) is tied to D . The vectorized FlashAttention implementations in llama.cpp are all limited to $VL \leq D$ [15]. Titopoulos et al. [39] vectorize FlashAttention on RVV specifically for $VL \leq D$. MEATTEN [13], a NEON-based fused-attention implementation, vectorizes over the head dimension, thereby imposing the same restriction. For 16-bit precision, these implementa ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': 'CPU 기반 트랜스포머 모델 추론은 점점 더 중요해지고 있으며, 특히 소형 언어 모델(SLM)의 경우 벡터 아키텍처가 유망한 실행 기반으로 부상하고 있습니다. 어텐션 모듈은 높은 메모리 대역폭 요구 사항으로 인해 주요 병목 현상입니다. FlashAttention은 연산을 융합하여 데이터 지역성을}}, {'role': 'model'}, {'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 459, 'candidatesTokenCount': 82, 'totalTokenCount': 2503, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 459}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'D_2JavK4MKaf-8YPtJCZsQs'}

[논문 후보 2]

제목: A Real-Time Tsetlin Machine-based Non-intrusive Load Monitoring System on MCUs
저자: Tianhang Tan, Han Wu, Tousif Rahman, Shengyu Duan, Alex Yakovlev, Rishad Shafik
카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency
arXiv ID: 2608.18780
제출일: 2026-08-19T10:35:14+00:00
수정일: 2026-08-19T10:35:14+00:00

[초록 원문]

Non-Intrusive Load Monitoring (NILM) systems estimate individual appliance energy consumption from a single aggregate meter, without requiring separate sensors for each device. By installing a single meter that measures a building's total electricity consumption, NILM algorithms can determine the active status of each appliance. However, traditional NILM systems use computationally intensive optimization algorithms to process offline data, limiting their capability for on-device deployment, where sensitive household data must be processed locally. This paper proposes a Tsetlin Machine (TM)-based NILM framework, targeting real-time applications on resource-constrained microcontrollers (MCUs), enabling privacy-preserving edge deployment. The problem is reformulated as a classification task, and the proposed approach achieves an average precision of 90% and recall of 96% for two-appliance classification, and 77% precision and 80% recall for four appliances on the REDD dataset. The trained model occupies only 18 KB of flash memory and achieves an inference latency of 0.43 ms on an ESP32, demonstrating its suitability for embedded NILM applications on MCUs.

[PDF 앞부분/서론 일부]

A Real-Time Tsetlin Machine-based Non-intrusive Load Monitoring System on MCUs Tianhang Tan, Han Wu, Tousif Rahman, Shengyu Duan, Alex Yakovlev, Rishad Shafik School of Engineering, Newcastle University, Newcastle Upon Tyne, United Kingdom {t.tan8, han.wu2, Tousif.Rahman, Alex.Yakovlev, Rishad.Shafik}@newcastle.ac.uk

Abstract-Non-Intrusive Load Monitoring (NILM) systems estimate individual appliance energy consumption from a single aggregate meter, without requiring separate sensors for each device. By installing a single meter that measures a building's total electricity consumption, NILM algorithms can determine the active status of each appliance. However, traditional NILM systems use computationally intensive optimization algorithms to process offline data, limiting their capability for on-device deployment, where sensitive household data must be processed locally. This paper proposes a Tsetlin Machine (TM)-based NILM framework, targeting real-time applications on resource-constrained microcontrollers (MCUs), enabling privacy-preserving edge deployment. The problem is reformulated as a classification task, and the proposed approach achieves an average precision of 90% and recall of 96% for two-appliance classification, and 77% precision and 80% recall for four appliances on the REDD dataset. The trained model occupies only 18 KB of flash memory and achieves an inference latency of 0.43 ms on an ESP32, demonstrating its suitability for embedded NILM applications on MCUs. Index Terms-Machine Learning.

I. INTRODUCTION Non-intrusive Load Monitoring (NILM) aims to estimate the energy consumption of individual appliances within a building without installing a power meter for each device. Since deploying dedicated sensors for every appliance is both time-consuming and expensive, a more cost-effective approach is to install a single meter at the point where electricity enters the building (see Fig. 1a). Therefore, extracting the energy consumption of individual appliances from the total load becomes a key challenge, known as energy disaggregation. Traditional Model-based Methods: The first NILM algorithm was proposed in [1], where the energy disaggregation problem was formulated as a combinatorial optimization problem. In this approach, a Finite State Machine (FSM) is used to represent the operating states of individual appliances. Subsequently, a variety of model-based methods have been

developed, including Factorial Hidden Markov Models (FHMMs) [2] and Mixed-Integer Linear Programming (MILP) approaches [3]. Machine Learning-based Methods: Model-based methods typically require prior knowledge of appliance characteristics and the number of appliances present in the household, which is often unavailable in real-world settings. To overcome these limitations, researchers turned to data-driven approaches that automatically extract appliance features from aggregated data. Both traditional Machine Learning (ML) models, such as kNearest Neighbor (KNN) and Support Vector Machine (SVM) [4], as well as Deep Learning models [5], [6] are studied for the NILM problem. Real-time Applications: Both Model-based methods and ML-based methods rely on computationally intensive optimization algorithms, which limit their applicability in real-time monitoring applications [7]. To address this limitation, this work adopts a lightweight and memory-efficient machine learning model, the Tsetlin Machine (TM) [8], to enable near real-time NILM on a microcontroller unit (MCU). The NILM problem is reformulated as a classification task and solved using the TM model. The implementation of the proposed TM-based NILM system is released as open source on GitHub 1. II. TM-BASED NILM SYSTEM Due to the limited memory and computational power on MCUs, this work adopts the Tsetlin Machine (TM) as the underlying machine learning model. TM is a classification model that operates on binary input features, where each feature is a Boolean value (0 or 1) (see Fig. 2). Without heavy floating-point multiplications, TM is more computationally efficient than neural networks and enables real-time NILM on MCUs. The TM-based NILM system consists of four main components: Edge Detection, Event Pairing, Feature Extraction, and TM-based Machine Learning classification:

- Edge Detection module takes raw sensor data as input and identifies power transitions, which correspond to appliance activation (rising edges) and deactivation (falling edges) events.
- Event Pairing algorithm groups corresponding rising and falling edges into complete appliance activity windows, which are then used for feature extraction and classification.
- Feature Extraction module converts each appliance activity window into a compact feature representation, capturing transition characteristics, temporal patterns, steady-state behavior, and energy consumption information.
- TM-based Machine learning module first converts extracted features to boolean values (either 0 or 1) and

1The source code is available at: <https://github.com/wuhanstudio/nilm>. arXiv:2608.18780v1 [cs.LG] 19 Aug 2026 (a) Illustration of a NILM system. (b) Demonstration of the proposed system on a MCU. Fig. 1: (a) Non-Intrusive Load Monitoring (NILM) estimates the power consumption of individual appliances from a single aggregated mains meter without requiring dedicated sensors for each device. (b) Demonstration of the proposed TM-based NILM system on a MCU. then classifies the appliance associated with each activity window. A. Edge Detection To reduce computational overhead on MCUs, the proposed NILM system adopts an event-driven architecture. Processing is triggered only when a transition is detected, that is, when the change in power consumption exceeds a predefined threshold, indicating that the power consumption has reached a new steady state. However, raw sensor data are inherently noisy, and transient spikes should not be detected as state transitions. To address this issue, Hart [1] proposed a steady-state detect ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '비침습 부하 모니터링(NILM) 시스템은 각 장치에 별도의 센서를 요구하지 않고 단일 통합 계량기로부터 개별 가전제품의 에너지 소비량을 추정합니다. 건물의 총 전력 소비량을 측정하는 단일 계량기를 설치함으로써, NILM 알고리즘은 각 가전제품의 활성 상태를

}]}}]

파악할'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 301, 'candidatesTokenCount': 82, 'totalTokenCount': 2345, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 301}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'GP2Jap-iCJGCqtsPI4XUwQU'}

[논문 후보 3]

제목: Benchmarking the Benchmarks: Evaluating Automated Safety Benchmarks for Small Language Models

저자: Nyamtulla Shaik, Fengjun Li, Bo Luo

카테고리: SLM/Edge/On-device

arXiv ID: 2608.17183

제출일: 2026-08-17T22:47:14+00:00

수정일: 2026-08-17T22:47:14+00:00

최근성: 최근 4일 이내

arXiv PDF: <https://arxiv.org/pdf/2608.17183.pdf>

[초록 원문]

Small Language Models (SLMs) are increasingly deployed in resource-constrained, privacy-sensitive settings, where safety and bias failures can cause security and societal risks. However, existing AI safety/security/compliance benchmarks are designed for large language models that may not transfer reliably to SLMs. We therefore ask: Can these benchmarks effectively and reliably evaluate SLMs? To answer this question, we conduct a large-scale assessment of the effectiveness and robustness of these automated pipelines by evaluating five widely used benchmark suites across 26 open-source SLMs under a unified judging rubric, which assigns a score of 0, 1, or 0.5 to harmful, safe, or ambiguous/irrelevant responses, respectively. Across the benchmarks, ambiguous judgments dominate and correlate with prompt complexity and model architecture, indicating that {Wem LLM-centric safety benchmarks are insufficient as standalone evidence for SLM safety assessment}. In general, the ambiguity rate increases with lexical density, output perplexity, and output length and decreases with lexical sophistication, self-coherence, and reply-prompt similarity. This reveals a capability-safety confound that mixes model capability with apparent safety. Since ambiguity is prevalent, aggregate mean-score leaderboards are mathematically brittle: model rankings change significantly under reasonable ambiguity treatments, even when the underlying outputs remain unchanged.

[PDF 앞부분/서론 일부]

Benchmarking the Benchmarks: Evaluating Automated Safety Benchmarks for Small Language Models Nyamtulla Shaik, Fengjun Li, and Bo Luo EECS/I2S, University of Kansas, Lawrence, KS, 66045, USA {nyam, fli, blau}@ku.edu
Abstract. Small Language Models (SLMs) are increasingly deployed in resource-constrained, privacy-sensitive settings, where safety and bias failures can cause security and societal risks. However, existing AI safety/security/compliance benchmarks are designed for large language models that may not transfer reliably to SLMs. We therefore ask: Can these benchmarks effectively and reliably evaluate SLMs? To answer this question, we conduct a large-scale assessment of the effectiveness and robustness of these automated pipelines by evaluating five widely used benchmark suites across 26 open-source SLMs under a unified judging rubric, which assigns a

score of 0, 1, or 0.5 to harmful, safe, or ambiguous/irrelevant responses, respectively. Across the benchmarks, ambiguous judgments dominate and correlate with prompt complexity and model architecture, indicating that LLM-centric safety benchmarks are insufficient as standalone evidence for SLM safety assessment. In general, the ambiguity rate increases with lexical density, output perplexity, and output length, and decreases with lexical sophistication, self-coherence, and reply-prompt similarity. This reveals a capability-safety confound that mixes model capability with apparent safety. Since ambiguity is prevalent, aggregate mean-score leaderboards are mathematically brittle: model rankings change significantly under reasonable ambiguity treatments, even when the underlying outputs remain unchanged.

1 Introduction Small language models (SLMs), with hundreds of millions to a few billion parameters, have emerged as a distinct choice in edge, IoT, and other resource-constrained settings with strict latency, cost, and privacy/security compliance limitations. Many sub-10B SLMs continue to be released in the open-source community and increasingly adopted in commercial products [50,39,53,14]. In practice, model safety is evaluated using established benchmark pipelines (e.g., [24]) originally developed for larger, more fluent LLMs. These automated

This is the author's accepted version of a paper accepted for publication at ESORICS 2026. The final authenticated version will be available online at Springer's Lecture Notes in Computer Science (LNCS) series once published. arXiv:2608.17183v1 [cs.AI] 17 Aug 2026

2 Nyamtulla Shaik, Fengjun Li, and Bo Luo judges typically compress open-ended LLM outputs into a single aggregate score derived from ternary labels ("harmful", "ambiguous", or "safe"). However, SLM outputs differ systematically from their larger counterparts, as SLMs often produce shorter, less fluent, and more failure-prone outputs [45]. Prior work also shows that the automated judges in LLM safety benchmarks are highly sensitive to surface features such as length and fluency [58]. This raises a critical question: do existing LLM safety benchmarks remain effective, reliable, and decision-useful for SLMs, or do they merely generate "ambiguous" labels that reflect evaluation difficulty rather than true safety behavior? Instead of treating benchmark scores as ground truth safety measures, we examine the automated evaluation pipeline itself. In particular, we study the capability-safety confound and ask whether this confound is empirically significant for SLMs under standard LLM-oriented benchmarks. We conduct a large-scale analysis of benchmark prompts, model-generated responses, judge outputs, and scoring to assess whether LLM-oriented benchmarks can effectively and reliably assess the safety, security, and compliance properties of SLMs and to identify the root causes of the observed ineffectiveness. In particular, we aim to answer five research questions: [RQ1] What do current safety benchmarks indicate about SLM safety, and how consistent are rankings across model-benchmark pairs? [RQ2] Are benchmark outputs interpretable and decision-useful? [RQ3] How sensitive are aggregate safety rankings, and how much do SLM rankings shift under alternative treatments of ambiguity? [RQ4] What factors predict an "ambiguous" judge decision, and does this ambiguity merely reflect model capability (e.g., output quality or prompt difficulty) rather than safety? And [RQ5] what quality-aware reporting strategies and metric adjustments can mitigate this confound to yield more robust and reliable safety evaluations for SLMs? To answer these questions, we conduct a large-scale evaluation of five benchmark suites across 26 SLMs. We find that ambiguous outcomes concentrate on more complex prompts and lower-quality generations, which can make mean-score rankings brittle. Taken together, our findings support a defensible conclusion without additional human labeling: even when the "true" safety of ambiguous cases is unknown, the automated pipeline is demonstrably biased by capability-related surface features, yielding aggregate rankings that are unstable under reasonable scoring choices.

The main contributions of this paper is summarized as follows: • We present a large-scale measurement study of automated LLM-safety evaluation pipelines by executing 741,312 model-prompt evaluations across five benchmark suites over 26 SLMs, with 715,312 judge-scored safety evaluations and 26,000 BBQ bias evaluations [46]. • We show that ambiguous outcomes are strongly associated with output quality, prompt complexity, and model architecture, which indicates the presence of a capability-safety confound in automated judging.

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '소형 언어 모델(SLM)은 자원 제약적이고 프라이버시 민감한 환경에 점차 더 많이 배포되고 있으며, 이러한 환경에서 안전 및 편향 실패는 보안 및 사회적 위험을 초래할 수 있습니다. 그러나 기존의 AI 안전/보안/규정 준수 벤치마크는 대형 언어 모델(LLM)'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 336, 'candidatesTokenCount': 82, 'totalTokenCount': 2380, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 336}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'IP2JaujSLtyd-8YP5oGxwAs'}