

SLM / Edge Device arXiv Daily Summary

생성일: 2026-06-29 05:44 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 30일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 30일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: AnySimLite: A Lightweight Few-Shot Similarity Encoder for On-Device Speech-Adjacent Classification

저자: Sourav Ghosh, Yash Bhatia, Keshav Goyal, Sahil Singh Bagri, Mohamed Akram Ulla Shariff, Saravana Balaji Shanmugam

카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency

arXiv ID: 2606.26452

제출일: 2026-06-24T23:25:28+00:00

수정일: 2026-06-24T23:25:28+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.26452.pdf>

[초록 원문]

To minimize privacy concerns and inference latency on edge devices like smartphones, lightweight on-device models remain important for end-user applications. Many of these applications involve natural language classification, but deploying multiple specialized models creates a memory footprint challenge. We investigate: Can a single lightweight architecture solve multiple Speech-Adjacent (SA) classification tasks through reduction to a nuanced text similarity formulation? We propose AnySimLite, a lightweight similarity encoder that combines word-level and character-level channels. Together with a dataset transformation strategy, we evaluate AnySimLite across multiple SA classification tasks and show that it consistently achieves state-of-the-art (SOTA) or SOTA-competitive performance in few-shot settings while maintaining a low memory footprint. Even in the worst case, the performance drop remains below 7% while using $\frac{1}{250}^{\mathrm{th}}$ of the model size of the SOTA qLLaMA_LoRA-7B baseline.

[PDF 앞부분/서론 일부]

ANYSIMLITE: A Lightweight Few-Shot Similarity Encoder for On-Device Speech-Adjacent Classification Sourav

Ghosh ID 1, Yash Bhatia ID 1, Keshav Goyal ID 2, Sahil Singh Bagri³, Mohamed Akram Ulla Shariff ID 1, Saravana Balaji Shanmugam ID 1^{1,2,3} Samsung R&D Institute Bangalore, India sourav.ghosh@samsung.com, yash.bhatia@samsung.com, keshavgoyal885.kg@gmail.com, sahil.singhbagri.cse22@itbhu.ac.in, m.shariff@samsung.com, saravana.bs@samsung.com

Abstract To minimize privacy concerns and inference latency on edge devices like smartphones, lightweight on-device models remain important for end-user applications. Many of these applications involve natural language classification, but deploying multiple specialized models creates a memory footprint challenge. We investigate: Can a single lightweight architecture solve multiple Speech-Adjacent (SA) classification tasks through reduction to a nuanced text similarity formulation? We propose ANYSIMLITE, a lightweight similarity encoder that combines word-level and character-level channels. Together with a dataset transformation strategy, we evaluate ANYSIMLITE across multiple SA classification tasks and show that it consistently achieves state-of-the-art (SOTA) or SOTA-competitive performance in few-shot settings while maintaining a low memory footprint. Even in the worst case, the performance drop remains below 7% while using $< 1/250$ th of the model size of the SOTA qLLaMA LoRA-7B baseline.

Index Terms: classification, natural language processing, text embedding, document similarity

1. Introduction

On-device models are essential in inference pipelines on edge devices for obvious benefits in terms of network latency, data privacy, and overall low carbon footprint at data centers. These models should have low latency and low resource requirements (storage, memory, power). Modern smartphones contain multiple models as part of SDK runtimes and OEM/third-party applications. Due to the sheer number of such models, these add up in storage resource requirement. Thus, there is a perennial need to optimize the resource consumption for all on-device solutions. Now, many on-device models are designed for very specific use cases, and thus their architectures and training methodologies pertain only to narrow scenarios. However, there are many other redundant models across different solutions and SDKs that solve an identical core task or target problems that are reducible to the same problem. Many speech related tasks require processing of transcriptions from automatic speech recognition (ASR). One salient example is intent detection in voice assistants, where transcripts need to be classified into a set of multiple known intents. In speech-adjacent natural language processing (NLP), this involves text similarity. Text similarity is the task of identifying whether two text units are similar or not. The input covers short texts like tweets to long text documents. Text similarity may also cover quantifying the similarity between a short query and a much longer document.

There are multiple approaches in literature towards text similarity, ranging from token matching and TF-IDF to semantic embeddings. In practice, based on the specific problem and the available dataset(s), one of these approaches is selected - algorithmic, neural, or a hybrid of both. In many cases, the text similarity may also be highly specialized, where two texts are said to be similar solely on the basis of the alignment of certain common features and not in the traditional lexicographic or semantic sense. We refer to this as "nuanced text similarity" (NTS). To this end, we are motivated to design a lightweight architecture for on-device deployment to singularly address a multitude of tasks that are reducible to an NTS task (Fig. 1). At its core, we propose a set of lightweight architectures and tune them with a toy problem called "Event Title Similarity". The designs of these architectures are motivated by the goals of on-device deployment and near-real-time latency for concerned applications. We first showcase the efficacy of such architecture in solving the toy problem, and conduct detailed ablation study to

identify the components with the most significant impact. Thereafter, we identify the best variant of each proposed architecture and evaluate their usefulness in addressing different problem statements on popular public-domain datasets using relevant metrics. Our contributions can be summarized as:

- We propose a lightweight architecture to solve an exemplar nuanced text similarity (NTS) problem titled "Event Title Similarity", optimized for on-device deployment and low inference latency.
- We demonstrate how multiple NLP tasks can be reduced to NTS and solved using our lightweight architecture in a fewarXiv:2606.26452v1 [cs.CL] 24 Jun 2026 shot setting with SOTA-competitive performance. Our proposed model ANYSIMLITE consistently achieves state-of-the-art (SOTA) or SOTA-competitive scores with a significantly lower memory footprint.
- We introduce a novel dataset transformation technique to derive labeled pairs of documents from classification datasets with focus on sampling "hard" pairs. To the best of our knowledge, we are the first to explore a unified lightweight model for solving a variety of speech-adjacent NLP classification tasks via problem reduction.

2. Preliminaries

2.1. Problem Formulation

In text similarity problem, the aim is to model the similarity between two text documents to a quantifiable score. Mathematically, the goal is to formulate a model f , such that two text documents, d_1 and d_2 , are said to be more similar, compared to d_3 and d_4 , if and only if $f(d_1, d_2) > f(d_3, d_4)$. This implies that the commutative property holds, i.e., $f(d_i, d_j) = f(d_j, d_i)$. In this work, we demonstrate a methodology to reduce select NLP problems to ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '최종 사용자 애플리케이션의 경우, 스마트폰과 같은 엣지 기기에서 개인 정보 보호 문제와 추론 지연 시간을 최소화하기 위해 경량 온디바이스 모델이 여전히 중요하다. 이러한 애플리케이션 중 다수는 자연어 분류를 포함하지만, 여러 개의 특화된 모델을 배포하는 것은 메모리 점유율 문제를 야기한다. 우리는 단일 경량 아키텍처가 미묘한 텍스트 유사성 공식화로의 환원을 통해 여러 음성 인접}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 266, 'candidatesTokenCount': 112, 'totalTokenCount': 2310, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 266}], 'thoughtsTokenCount': 1932, 'serviceTier': 'standard', 'modelVersion': 'gemini-2.5-flash', 'responseId': 'gYdBavXqLLzsjrEPw4ixgQI'}}

[논문 후보 2]

제목: Charting the Growth of Social-Physical HRI (spHRI): A Systematic Review Pipeline Augmented by Small Language Models

저자: Mayumi Mohan, Ju-Hung Chen, Alexis E. Block

카테고리: SLM/Edge/On-device

arXiv ID: 2606.26382

제출일: 2026-06-24T21:09:20+00:00

수정일: 2026-06-24T21:09:20+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.26382.pdf>

[초록 원문]

Social-physical human-robot interaction (spHRI) has grown rapidly across robotics, human-computer interaction,

human-robot interaction, and haptics. Yet, fragmented terminology and inconsistent methodologies make systematic synthesis difficult. To support scalable review practices, we evaluated the extent to which small language models (SLMs; $< 1.5\text{B}$ parameters) can assist with title and abstract screening for a large spHRI systematic review. While no SLMs matched human reviewers' performance, the models operated locally and screened papers orders of magnitude faster. The combined SLM ensemble identified 39 papers reviewers missed, representing 10.29% of the final relevant dataset. These results demonstrate that SLMs can augment, rather than replace, expert reviewers and make large-scale literature reviews accessible and sustainable.

[PDF 앞부분/서론 일부]

Charting the Growth of Social-Physical HRI (spHRI): A Systematic Review Pipeline Augmented by Small Language Models
Mayumi Mohan MPI for Intelligent Systems Stuttgart, Germany maymohan@is.mpg.de Ju-Hung Chen
Case Western Reserve University Cleveland, USA jxc2350@case.edu Alexis E. Block Case Western Reserve University
Cleveland, USA alexis.block@case.edu

Abstract Social-physical human-robot interaction (spHRI) has grown rapidly across robotics, human-computer interaction, human-robot interaction, and haptics. Yet, fragmented terminology and inconsistent methodologies make systematic synthesis difficult. To support scalable review practices, we evaluated the extent to which small language models (SLMs; ≤ 1.5 parameters) can assist with title and abstract screening for a large spHRI systematic review. While no SLMs matched human reviewers' performance, the models operated locally and screened papers orders of magnitude faster. The combined SLM ensemble identified 39 papers reviewers missed, representing 10.29% of the final relevant dataset. These results demonstrate that SLMs can augment, rather than replace, expert reviewers and make large-scale literature reviews accessible and sustainable.

CCS Concepts • Computing methodologies→ Natural language processing; • Human-centered computing→ Interaction paradigms; • Information systems→ Document filtering. Keywords social touch, human-robot interaction, AI-assisted literature review, title and abstract screening, low-resource model deployment

ACM Reference Format: Mayumi Mohan, Ju-Hung Chen, and Alexis E. Block. 2026. Charting the Growth of Social-Physical HRI (spHRI): A Systematic Review Pipeline Augmented by Small Language Models. In Companion Proceedings of the 21st ACM/IEEE International Conference on Human-Robot Interaction (HRI Companion '26), March 16-19, 2026, Edinburgh, Scotland, UK. ACM, New York, NY, USA, 5 pages. <https://doi.org/10.1145/3776734.3794506>

1 Introduction Social-physical human-robot interaction (spHRI), a subfield that studies physical interactions with robots where social intent is the primary goal, has gained growing attention [14, 28] in robotics, humanrobot interaction (HRI), human-computer interaction (HCI), and haptics communities [8, 16, 20, 26, 27] (see Fig.1). These interactions denotes that both authors contributed equally to this research. This work is licensed under a Creative Commons Attribution 4.0 International License. HRI Companion '26, Edinburgh, Scotland, UK © 2026 Copyright held by the owner/author(s). ACM ISBN 979-8-4007-2321-6/2026/03 <https://doi.org/10.1145/3776734.3794506> include both physical modalities such as affective touch, haptic feedback, and embodied emotional expression and non-tactile modalities, including gaze and verbal communication. However, despite its relevance, the social-physical human-robot interaction (spHRI) domain suffers from fragmented terminology and disciplinary silos, limiting systematic knowledge accumulation and comparative analysis across studies. The literature reflects this fragmentation, as spHRI-related topics are approached from diverse disciplinary perspectives [18], resulting in a lack of unified vocabulary across domains

such as HRI, HCI, affective computing, and healthcare. The absence of consistent terminology complicates efforts to compare studies, classify interaction types, or interpret results consistently [8, 18, 20, 27]. For example, a survey on nonverbal communication in HRI extensively examines the impact of robot touch, yet does not explicitly reference the spHRI construct [18]. Existing surveys often focus predominantly on direct interpersonal touch with robots and overlook interactions with robotic objects (robjects), physical interfaces, wearables, or haptic devices [8, 18, 20, 26], resulting in gaps in how spHRI is understood and classified. To address these gaps, we initiated a large-scale systematic literature review, drawing from over 130,000 candidate publications across robotics, HRI, HCI, and related venues. The review aimed to clarify conceptual foundations and map the methodological landscape of spHRI research. However, the scale of modern literature presents a critical bottleneck for human reviewers. Comprehensive title and abstract screening, an early but essential stage, can be prohibitively time-consuming. Large Language Models (LLMs) are increasingly being explored for this task, but most require cloud access, substantial computational power [23], raise ethical concerns Figure 1: Yearly publication counts for social-physical human-robot interaction (spHRI) research from 1992-2024. The pink bars show the number of included papers per year, and the red dotted line represents the raw annual counts. A generalized additive model (GAM; purple solid line) was fitted to estimate the underlying trend, with the shaded region indicating the 95% confidence interval. arXiv:2606.26382v1 [cs.CL] 24 Jun 2026 HRI Companion '26, March 16-19, 2026, Edinburgh, Scotland, UK Mohan et al. due to carbon footprint and propriety opacity [3], or accessibility issues due to prohibitive costs [3]. Thus, in this Late-Breaking Report (LBR), we investigate how open-source, lightweight small language models (SLMs), which run locally on consumer hardware, can support accessible and environmentally responsible systematic reviews as a supportive screening aid without sacrificing accuracy. Specifically, we ask: To what extent can an SLM serve as a reliable second-pass filter that recovers missed relevant papers in title and abstract screening? We do not frame SLMs as replacements for human reviewers. The performance comparisons are used to assess the reliability of SLMs. To answer our research question, we benchmark SLMs against human reviewers and test their utility, precision, conservatism, and potential role as assistive screeners in large-scale review workflows by testing the following hypotheses: H1: spHRI exhibits sustained publication growth consistent with ...

[앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '사회-물리적 인간-로봇 상호작용(spHRI)은 로봇공학, 인간-컴퓨터 상호작용, 인간-로봇 상호작용, 햅틱스 등 다양한 분야에서 급성장하였다. 그러나 파편화된 용어와 일관성 없는 방법론으로 인해 체계적인 종합이 어려운 실정'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 234, 'candidatesTokenCount': 80, 'totalTokenCount': 2278, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 234}], 'thoughtsTokenCount': 1964, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'iodBatbHGIHwjEP1KLQuQ4'}

[논문 후보 3]

제목: Cascaded Multi-Granularity Pruning for On-Device LLM Inference in Industrial IoT
저자: Jinghan Wang, Yanjun Chen, Wei Zhang, Xiaotong Huang, Tianchen Liu, Gaoliang Peng
카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency

arXiv ID: 2606.26861

제출일: 2026-06-25T10:44:48+00:00

수정일: 2026-06-25T10:44:48+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.26861.pdf>

[초록 원문]

Deploying large language models (LLMs) on Industrial Internet of Things (IIoT) edge devices demands extreme compression, yet existing structured pruning methods collapse at high compression ratios due to one-shot importance estimation, and their cross-architecture behavior remains unpredictable. This article presents a cascaded multi-granularity pruning framework that removes layers, attention heads, and feed-forward channels in coarse-to-fine order, with lightweight low-rank recovery between stages to re-estimate component importance. An information-theoretic analysis motivates this ordering, and the Structural Independence Assumption (SIA) is formalized as a checkable condition predicting whether per-component pruning criteria are reliable for a given architecture: Multi-Head Attention (MHA)+GELU designs satisfy the SIA, whereas Grouped Query Attention (GQA)+SwiGLU designs violate it. On bearing fault diagnosis spanning 88M to 6.25B-parameter models, the framework extends achievable compression to 13.8 times on MHA+GELU architectures with 83.82% accuracy (+3.70 percentage points (pp) over the strongest baseline), while exposing a ~74pp accuracy collapse on GQA+SwiGLU architectures that violate the SIA. Deployed on an industrial slewing bearing fault diagnosis platform with NVIDIA DGX Spark, compressed models reduce inference latency by up to 67.2% and peak memory by 62.5%, demonstrating viability for IIoT edge inference.

[PDF 앞부분/서론 일부]

1 > REPLACE THIS LINE WITH YOUR MANUSCRIPT ID NUMBER (DOUBLE -CLICK HERE TO EDIT) < Cascaded Multi-Granularity Pruning for On-Device LLM Inference in Industrial IoT Jinghan Wang, Student Member, IEEE , Yanjun Chen, Wei Zhang, Member, IEEE, Xiaotong Huang, Tianchen Liu Member, IEEE, Gaoliang Peng*, Member, IEEE Abstract-Deploying large language models (LLMs) on Industrial Internet of Things (IIoT) edge devices demands extreme compression, yet existing structured pruning methods collapse at high compression ratios due to one -shot importance estimation, and their cross-architecture behavior remains unpredictable. This article presents a cascaded multi-granularity pruning framework that removes layers, attention heads, and feed-forward channels in coarse-to-fine order, with lightweight low -rank recovery between stages to re -estimate component importance. An information theoretic analysis motivates this ordering, and the Structural Independence Assu mption (SIA) is formalized as a checkable condition predicting whether per-component pruning criteria are reliable for a given architecture: Multi -Head Attention (MHA)+GELU designs satisfy the SIA, whereas Grouped Query Attention (GQA)+SwiGLU designs viola te it. On bearing fault diagnosis spanning 88M to 6.25B -parameter models, the framework extends achievable compression to 13.8× on MHA+GELU architectures with 83.82% accuracy (+3.70 percentage points (pp) over the strongest baseline), while exposing a ~74 pp accuracy collapse on GQA+SwiGLU architectures that violate the SIA. Deployed on an industrial slewing bearing fault diagnosis platform with NVIDIA DGX Spark, compressed models reduce inference latency by up to 67.2% and peak memory by 62.5%,

demonstrating viability for IIoT edge inference. Keywords-Edge intelligence, Industrial Internet of Things (IIoT), Large Language Models (LLMs), On-device inference, Structured pruning.

1. INTRODUCTION

INDUSTRIAL Internet of Things (IIoT) systems generate continuous high-frequency sensor streams that increasingly demand on-device intelligence. Uploading raw signals to a centralized cloud encounters three compounding bottlenecks: bandwidth that scales linearly with sensor density, round-trip latency incompatible with millisecond-level control loops, and privacy constraints that prohibit data from leaving the factory floor [1]. These factors have elevated edge intelligence, i.e., performing inference directly on resource constrained nodes co-located with sensors, from an optimization option to a design imperative [2]. Large language models (LLMs), with their cross-task generalization capability, are now entering IoT perception workloads including predictive maintenance and fault detection [3], [4]. Even when memory This work was supported by the National Natural Science Foundation of China (No. 52275099). Corresponding author: Gaoliang Peng (pgl7782@hit.edu.cn). Jinghan Wang, Xiaotong Huang, Tianchen Liu, and Gaoliang Peng are with the School of Mechanical and Electrical Engineering, Harbin Institute of Technology, Harbin 150001, China (e-mail: 23B908011@stu.hit.edu.cn; 25S108110@stu.hit.edu.cn; tianchenliu@hit.edu.cn; pgl7782@hit.edu.cn). suffices, a 6B-parameter FP16 model still occupies roughly 12 GB and incurs significant per-token compute, making real-time multi-model serving on a single node impractical in terms of latency and energy without compression. Structured pruning is therefore not an optimization nicety but the critical path for efficient on-device LLM inference in IIoT. Among compression techniques, structured pruning directly reduces dense matrix dimensions, yielding speedups on any commodity hardware without sparse-tensor accelerators. Unstructured methods such as Wanda [5] and SparseGPT [6] achieve high sparsity but depend on specialized hardware support absent from most edge SoCs. Representative structured approaches include gradient-based LLM-Pruner [7], fluctuation-based FLAP [8], orthogonal-projection SliceGPT [9], and layer-removal methods ShortGPT [10] and LaCo [11]. At moderate compression ($2\text{--}4\times$), these methods perform adequately. However, when pushed toward the compression ratios that edge deployment actually demands ($>8\times$) and applied across the rapidly diversifying landscape of LLM architectures, three fundamental limitations emerge. Existing structured methods operate at one or two granularity levels, typically attention heads and FFN channels, without exploiting layer-level redundancy. In our experimental setting, such single- or dual-granularity approaches reach at most approximately $9.4\times$ compression, because the untouched granularity retains all its redundancy while the targeted granularity is over-pruned. Current methods estimate component importance once, on the original dense model. Yet pruning itself alters the importance landscape: removing entire layers triggers importance redistribution among surviving components, causing their relative contributions to shift substantially. This discrepancy grows with the compression ratio, explaining why one-shot methods collapse beyond moderate compression; capturing redistribution inherently requires interleaving pruning with recovery and re-estimation, which no single-pass criterion can achieve. The same criterion can produce negligible accuracy loss on one architecture yet catastrophic collapse on another at comparable compression, and existing observations of such sensitivity [9], [12] remain empirical with no predictive power. For heterogeneous edge fleets, such trial-and-error behavior is

YanJun Chen and Wei Zhang are with the School of Information Science and Technology, Eastern Institute of Technology, Ningbo, China (e-mail: yychen@eitech.edu.cn; zhw@eitech.edu.cn).

2 > REPLACE THIS LINE WITH YOUR

MANUSCRIPT ID NUMBER (DOUBLE-CLICK HERE TO EDIT) < disqualifying: practitioners need an a priori

applicability criterion before committing to a pruning strategy. These three limitations reflect a deeper pro ...
[앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '대규모 언어 모델(LLM)을 산업용 사물 인터넷(IoT) 엣지 장치에 배포하려면 극도의 압축이 필수적입니다. 그러나 기존의 구조적 가지치기(pruning) 방법은 일회성 중요도 추정으로 인해 높은 압축률에서 성능이 급격히 저하되며, 아키텍처 간 동작'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 379, 'candidatesTokenCount': 81, 'totalTokenCount': 2423, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 379}], 'thoughtsTokenCount': 1963, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'IldBarKkN6mR-8YP8JG2qAo'}