

SLM / Edge Device arXiv Daily Summary

생성일: 2026-07-07 06:13 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 30일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 30일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: Embodied.cpp: A Portable Inference Runtime of Embodied AI Models on Heterogeneous Robots

저자: Ling Xu, Chuyu Han, Borui Li, Hao Wu, Shiqi Jiang, Ting Cao, Chuanyou Li, Sheng Zhong, Shuai Wang

카테고리: SLM/Edge/On-device, Format-LoRA/Structured Output

arXiv ID: 2607.02501

제출일: 2026-07-02T17:58:28+00:00

수정일: 2026-07-02T17:58:28+00:00

최근성: 최근 4일 이내

arXiv PDF: <https://arxiv.org/pdf/2607.02501.pdf>

[초록 원문]

Embodied AI models now span vision-language-action (VLA) models and world-action models (WAMs), but practical deployment remains fragmented across model-specific Python stacks, backend assumptions, and robot-side glue code, especially on heterogeneous edge devices. Existing inference runtimes are designed mainly for request-response serving and therefore do not satisfy the runtime contract of embodied deployment: multi-rate execution inside closed-loop control, latency-first batch-1 inference on heterogeneous hardware, and extensible embodied interfaces beyond fixed token I/O. We present Embodied.cpp, a portable C++ inference runtime for embodied models. Based on an architectural analysis of representative VLA models and WAMs, Embodied.cpp captures a shared execution path and organizes it into five layers: input adapters, sequence builders, backbone execution, head plugins, and deployment adapters. The runtime provides modular multi-rate execution, latency-first fused inference, and extensible operator and I/O support, enabling deployment across heterogeneous devices, robots, and simulators through one backend abstraction. We evaluate Embodied.cpp on two VLA models, HY-VLA and pi0.5, and on a preliminary WAM benchmark using a LingBot-VA Transformer block. The VLA deployments achieve successful closed-loop execution with 100.0% and 91.0% task success rates, respectively.

The WAM benchmark reduces block memory from 312.2 MiB to 88.1 MiB. These results show that Embodied.cpp improves deployment efficiency while preserving high accuracy across diverse embodied model architectures.

[PDF 앞부분/서론 일부]

2026-07-01 Embodied.cpp: A Portable Inference Runtime of Embodied AI Models on Heterogeneous Robots Ling Xu¹ Chuyu Han² Borui Li^{1,+} Hao Wu^{2,+} Shiqi Jiang³ Ting Cao⁴ Chuanyou Li¹ Sheng Zhong² Shuai Wang¹ 1 Southeast University 2 Nanjing University 3 Microsoft Research 4 Institute for AI Industry Research (AIR), Tsinghua University +Project Leader EmbodiedAImodelsnowspanvision-language-action(VLA) modelsandworld-actionmodels(WAMs), butpracticaldeploymentremainsfragmentedacrossmodel-specificPythonstacks,backendassumptions, and robot-side glue code, especially on heterogeneous edge devices. Existing inference runtimes are designed mainly for request-response serving and therefore do not satisfy the runtime contract of embodied deployment: multi-rate execution inside closed-loop control, latency-first batch-1 inference on heterogeneous hardware, and extensible embodied interfaces beyond fixed token I/O. We present Embodied.cpp, a portable C++ inference runtime for embodied models. Based on an architectural analysis of representative VLA models and WAMs, Embodied.cpp captures a shared execution path and organizes it into five layers: input adapters, sequence builders, backbone execution, head plugins, and deployment adapters. The runtime provides modular multi-rate execution, latency-first fused inference, and extensible operator and I/O support, enabling deployment across heterogeneous devices, robots, and simulators through one backend abstraction. We evaluate Embodied.cpp on two VLA models, HY-VLA and pi0.5, and on a preliminary WAM benchmark using a LingBot-VA Transformer block. The VLA deployments achieve successful closed-loop execution with 100.0% and 91.0% task success rates, respectively. The WAM benchmark reduces block memory from 312.2 MiB to 88.1 MiB. These results show that Embodied.cpp improves deployment efficiency while preserving high accuracy across diverse embodied model architectures. Project Link: <https://github.com/SEU-PAISys/Embodied.cpp>

1. Introduction Academia and industry have already produced a rapidly growing set of embodied models. Recent systems now span vision-language-action (VLA) models and world-action models (WAMs), showing substantial progress in model architecture and capability [1, 2, 3, 4, 5, 6, 7]. At the same time, the surrounding ecosystem for data, training, and simulation has also improved substantially through projects such as LeRobot, Open X-Embodiment, ManiSkill, LIBERO, and Isaac Sim [8, 9, 10, 11, 12]. But practical impact does not end at model construction. To become reliable robot-side systems, these models must run on heterogeneous and resource-constrained devices, from Jetson and RK-based boards to x86 edge boxes and workstation-class robots, without rebuilding the software stack for each new model family. Achieving this requires a unified inference runtime. Existing inference runtimes, however, do not yet provide such support. General LLM or VLM runtimes are designed for request-response serving, relatively arXiv:2607.02501v1 [cs.RO] 2 Jul 2026 uniform token interfaces, and throughput-oriented optimization [13, 14, 15, 16]. Embodied inference, by contrast, lives inside a closed-loop interaction process with robot- and simulator-side dependencies. As a result, even a strong checkpoint still has to be stitched into Python research code, backend-specific inference paths, handwritten sensor wrappers, and platform-specific control logic before it can act on a robot. As embodied architectures diversify, this integration burden only grows, making a portable inference runtime for embodied AI models increasingly necessary. The challenge arises because embodied deployment fundamentally changes the runtime contract. Compared with

conventional LLM or VLM serving, an embodied inference runtime must satisfy three key requirements.(1) Multi-rate execution. Embodied inference is not a single synchronous forward pass: perception encoders, transformer backbones, predictive branches, and action heads may need to run at different rates inside the same control loop, as increasingly visible in hierarchical and fast-slow VLA systems as well as recent WAMs [3, 4, 5].(2) Latency-first closed-loop control. The optimization target is not throughput but stable closed-loop control, which requires low latency, low jitter, and efficient batch-1 execution on heterogeneous edge hardware.(3) Extensible embodied interfaces. Embodied deployment must go beyond fixed token I/O and absorb custom operators, embodied multimodal inputs, and heterogeneous outputs ranging from action chunks to predicted futures. These are not peripheral engineering details; together they define the runtime contract that a practical embodied inference runtime must satisfy. Motivated by these observations, we present Embodied.cpp, a portable C++ inference runtime for embodied models. Its design directly addresses the three challenges: modular multi-rate execution decouples components with different refresh frequencies; latency-first fused execution targets predictable small-batch control on heterogeneous devices; and extensible operator and embodied I/O support turns model-specific heads, interfaces, and backends into pluggable runtime modules instead of one-off glue code. These principles are realized in a unified five-layer architecture spanning input adapters, sequence builders, backbone execution, head plugins, and deployment adapters. The result is an inference runtime with a stable reusable core, while still leaving enough extension surface for new embodied model variants. We make three contributions:

- An architectural analysis of representative embodied models spanning vision-language-action (VLA) models and world-action models (WAMs), revealing a shared execution path whose main divergences are confined to a small set of pluggable heads and predictive modules.
- The design of Embodied.cpp as a portable C++ inference runtime that maps this shared path into five layers: input adapters, sequence builders, ...

[앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '임바디드(Embodied) AI 모델은 이제 시각-언어-행동(VLA) 모델과 세계-행동 모델(WAM)을 아우르지만, 실제 배포는 모델별 Python 스택, 백엔드 가정, 로봇 측 글루 코드에 걸쳐 파편화되어 있으며, 특히 이종 엣지 장치에서 이러한'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 402, 'candidatesTokenCount': 80, 'totalTokenCount': 2446, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 402}], 'thoughtsTokenCount': 1964, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'WRpMaqmFApjM-8YPjLamwQM'}

[논문 후보 2]

제목: Object Aligner: A Configurable JSON Schema Similarity Score for Graphs, Applied to LLM Prompt Optimization

저자: Jan Drchal

카테고리: Format-LoRA/Structured Output

arXiv ID: 2607.01972

제출일: 2026-07-02T10:07:34+00:00

수정일: 2026-07-02T10:07:34+00:00

최근성: 최근 4일 이내

arXiv PDF: <https://arxiv.org/pdf/2607.01972.pdf>

[초록 원문]

Large language models (LLMs) are often asked to produce JSON conforming to a fixed schema, powering information extraction, tool calling, agentic planning, and knowledge-graph construction. Measuring how closely an output matches a gold reference is essential yet surprisingly hard: exact match is brittle, text similarity ignores structure, and an LLM judge is expensive, opaque, and non-deterministic. We address this with Object Aligner (OA), an open-source Python library that scores two JSON objects deterministically by recursively aligning their trees (the Hungarian algorithm for unordered collections, sequence alignment for ordered ones) and awarding partial credit at the granularity the schema declares. The Object Aligner is configured entirely through a set of JSON Schema extensions, so adapting it to a new task involves annotating a schema rather than writing code. Complex structured data, however, are rarely flat trees: records may form graphs or hypergraphs keyed by arbitrary identifiers, breaking the assumptions of prior similarity metrics. Our central contribution, referential alignment, closes this gap by inferring a bijection between gold and candidate identifiers and scoring every reference through it, so the score is invariant to relabeling. Since recovering this bijection exactly is graph isomorphism, the Object Aligner approximates it with Weisfeiler-Leman color refinement. An order-sensitive sequence regime targets ranking and planning. Since the same alignment localizes every mismatch, the Object Aligner emits ranked repair suggestions at no extra cost. Used as a reward inside the GEPA prompt optimizer, Object Aligner helps or stays neutral across all datasets.

[PDF 앞부분/서론 일부]

DRCHAL: OBJECT ALIGNER: A CONFIGURABLE JSON SCHEMA SIMILARITY SCORE FOR GRAPHS 1 Object Aligner: A Configurable JSON Schema Similarity Score for Graphs, Applied to LLM Prompt Optimization Jan Drchal Abstract—Large language models (LLMs) are often asked to produce JSON conforming to a fixed schema, powering information extraction, tool calling, agentic planning, and knowledgegraph construction. Measuring how closely an output matches a gold reference is essential yet surprisingly hard: exact match is brittle, text similarity ignores structure, and an LLM judge is expensive, opaque, and non-deterministic. We address this with OBJECTALIGNER(OA), an open-source Python library that scores two JSON objects deterministically by recursively aligning their trees (the Hungarian algorithm for unordered collections, sequence alignment for ordered ones) and awarding partial credit at the granularity the schema declares. The OBJECTALIGNER is configured entirely through a set of JSON Schema extensions, so adapting it to a new task involves annotating a schema rather than writing code. Complex structured data, however, are rarely flat trees: records may form graphs or hypergraphs keyed by arbitrary identifiers, breaking the assumptions of prior similarity metrics. Our central contribution, referential alignment, closes this gap by inferring a bijection between gold and candidate identifiers and scoring every reference through it, so the score is invariant to relabeling. Since recovering this bijection exactly is graph isomorphism, the OBJECTALIGNER approximates it with Weisfeiler-Leman color refinement. An order-sensitive sequence regime targets ranking and planning. Since the same alignment localizes every mismatch,

the OBJECTALIGNERemits ranked repair suggestions at no extra cost. Used as a reward inside the GEPA prompt optimizer, OBJECTALIGNERhelps or stays neutral across all datasets. Index Terms-Object Aligner, complex structured data, large language models, prompt optimization, graph similarity score, JSON schema I.

INTRODUCTION

COMPARING complex structured data, i.e., measuring how closely two structured objects agree,

is a basic operation in many settings: automated testing, change detection between versions, record linkage, and the evaluation of machine-learning systems against reference outputs. It has become more urgent with large language models (LLMs). Along with free-form text, an LLM is often asked to return data conforming to a fixed schema (most often JSON) so that its output can be parsed, stored, and consumed directly by downstream systems: information extraction, document understanding, tool and function calling, agentic planning, and J. Drchal is with the Artificial Intelligence Center, Faculty of Electrical Engineering, Czech Technical University in Prague, Czech Republic (e-mail: drchajan@fel.cvut.cz). This work was created with the state support of the Technology Agency of the Czech Republic within the Sigma Programme, Project No. TQ01000100. Preprint. This is a submitted version of a manuscript under review at IEEE Access; it has not been peer reviewed.

knowledge-graph construction all rely on it.

JSON is among the most widely used data formats in practice, and although it is essentially a tree, cross-references between records allow it to encode general graphs and hypergraph structures (Fig. 1). Judging whether two such objects agree (for instance a model prediction against a gold reference) is therefore both common and hard: the comparison must look past cosmetic differences such as reordering or identifier renumbering and credit what is structurally correct. When the scoring procedure itself must be controlled-reproducible and auditable-LLM-based judging is not a solution. LLM-as-a-judge [1] replaces a human evaluator with another model, but it inherits the very difficulty we are trying to escape: the judge must itself be prompted, calibrated, and validated; it is costly, noisy, and non-deterministic; it is prone to position and verbosity bias; and its verdicts are opaque, which makes them hard to audit. Generic text-similarity metrics [2]-[4] avoid these costs but discard the structure entirely. What is needed instead is a deterministic, schema-aware score that compares a prediction directly against a gold object and credits the parts it gets right. We introduceObject Aligner(OA), a highly configurable similarity score 1 for structured outputs, computed by a recursive, schema-driven alignment of gold and candidate trees that matches each node's children with the appropriate optimalalignment algorithm: the Hungarian algorithm for unordered collections and a sequence-alignment dynamic program for ordered ones (such as our example in Fig. 1). By design, the score is deterministic, decomposable, and schema-aware, so partially correct objects receive partial credit at the granularity declared by the schema. The comparison is driven entirely by a schema expressed as a small set of JSON Schema extensions (per-field weights, leaf comparators, and ordering and reference semantics) so adapting OBJECTALIGNERto a new task amounts to annotating a schema rather than writing code. OBJECTALIGNERships as an open-source Python module. Such a score has many uses; this study concentrates on one of them, prompt optimization. Coaxing an LLM to produce thecorrectstructured output is difficult: performance is highly sensitive to how the task is phrased, which examples are shown, and how the schema and its constraints are explained. Therefore building a reliable pipeline is increasingly 1Following common usage in the evaluation literature, we use the terms "score" and "metric" interchangeably, even though OBJECTALIGNERis not a metric in the strict mathematical sense.

arXiv:2607.01972v1 [cs.CL] 2 Jul 2026 DRCHAL: OBJECT ALIGNER: A CONFIGURABLE JSON SCHEMA SIMILARITY SCORE FOR GRAPHS 2 schema= {"type":"object",

"properties": { "people": {"type": "array", "order": "align", "items": {"type": "object", "keyl ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '대규모 언어 모델(LLM)은 정보 추출, 도구 호출, 에이전트 계획 수립, 지식 그래프 구축의 기반이 되는 고정된 스키마에 부합하는 JSON을 생성하도록 요청받는 경우가 많습니다. 출력물이 골드 레퍼런스와 얼마나 일치하는지 측정하는 것은 필수적이지만 놀랍도록 어렵습니다. 정확히'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 381, 'candidatesTokenCount': 81, 'totalTokenCount': 2425, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 381}], 'thoughtsTokenCount': 1963, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'YhpMaqPPDJzqjrEP4a3u0Ac'}

[논문 후보 3]

제목: Verifiable Knowledge Expansion through Retrieval-Grounded Formal Concept Analysis

저자: Yujin Yang, Heejung Lee

카테고리: SLM/Edge/On-device

arXiv ID: 2607.01773

제출일: 2026-07-02T06:44:35+00:00

수정일: 2026-07-02T06:44:35+00:00

최근성: 최근 4일 이내

arXiv PDF: <https://arxiv.org/pdf/2607.01773.pdf>

[초록 원문]

Ontology construction requires deciding which objects, attributes, and structural relations should be accepted as valid knowledge. Language models can propose such structures from text, but their outputs can still be unsupported or inconsistent. This paper proposes a retrieval-augmented small language model (SLM) framework that uses formal concept analysis (FCA) as a symbolic verification loop for knowledge expansion. Starting from seed attributes, FCA proposes implications over a growing formal context. A retrieval-grounded SLM oracle then validates each implication or returns a counterexample. The oracle also supports incidence judgments, consistency checks, and attribute proposals, making accepted implications, counterexamples, contradictions, and corrections inspectable. In a rare ataxia setting constructed from Orphadata resources, retrieval-grounded 10-seed runs obtain relation F1 of 0.29-0.52 and closure-based implication F1 of 0.22-0.30. Larger seed sets increase the number of evaluated implications and often improve implication F1. The lower implication scores reflect a stricter evaluation of derived implications, where one missed or extra relation can affect several implication judgments. Ablations show that incidence judgments in a fixed object-attribute setting can improve closure-based implication scores. However, identifying positive object-attribute pairs remains difficult even when the candidate objects and attributes are fixed.

[PDF 앞부분/서론 일부]

Verifiable Knowledge Expansion through Retrieval-Grounded Formal Concept Analysis Yujin Yang yujinyang@hanyang.ac.kr Hanyang University Seoul, Korea Heejung Lee stdream@hanyang.ac.kr Hanyang University Seoul, Korea Abstract Ontology construction requires deciding which objects, attributes, and structural

relations should be accepted as valid knowledge. Language models can propose such structures from text, but their outputs can still be unsupported or inconsistent. This paper proposes a retrieval-augmented small language model (SLM) framework that uses formal concept analysis (FCA) as a symbolic verification loop for knowledge expansion. Starting from seed attributes, FCA proposes implications over a growing formal context. A retrieval-grounded SLM oracle then validates each implication or returns a counterexample. The oracle also supports incidence judgments, consistency checks, and attribute proposals, making accepted implications, counterexamples, contradictions, and corrections inspectable. In a rare ataxia setting constructed from Orphadata resources, retrieval-grounded 10-seed runs obtain relation F1 of 0.29- 0.52 and closure-based implication F1 of 0.22-0.30. Larger seed sets increase the number of evaluated implications and often improve implication F1. The lower implication scores reflect a stricter evaluation of derived implications, where one missed or extra relation can affect several implication judgments. Ablations show that incidence judgments in a fixed object-attribute setting can improve closure-based implication scores. However, identifying positive object-attribute pairs remains difficult even when the candidate objects and attributes are fixed.

CCS Concepts • Computing methodologies → Knowledge representation and reasoning; Natural language processing; • Information systems → Information retrieval; • Applied computing → Life and medical sciences. Keywords Formal concept analysis, Retrieval-augmented generation, Ontology construction, Small language models, Rare disease phenotyping

ACM Reference Format: Yujin Yang and Heejung Lee. 2026. Verifiable Knowledge Expansion through Retrieval-Grounded Formal Concept Analysis. In Proceedings of the 8th epiDAMIK ACM SIGKDD Workshop on Data-driven Decision Making for Corresponding author. Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s). epiDAMIK @ KDD '26, Jeju Island, Republic of Korea ©2026 Copyright held by the owner/author(s). Public and Population Health, August 10, 2026, Jeju Island, Republic of Korea. ACM, New York, NY, USA, 8 pages.

1 Introduction Ontologies turn domain knowledge into a structure that can be shared, queried, checked, and reused [4, 6, 17]. In biomedical domains, for example, an ontology-like representation can connect rare disease objects to phenotype attributes and expose regularities among those phenotypes [7, 15]. However, building such structures manually is costly. Domain experts must inspect source documents, encode object-attribute relations, and revise the structure when new evidence reveals missing or inconsistent knowledge [1, 6, 17]. This makes ontology and knowledge graph construction a natural setting for language model assistance, but errors in domain specific knowledge make unverifiable generation risky [5, 11, 12]. The key technical challenge is therefore to verify proposed knowledge before it becomes a structural commitment. For example, the system may propose that a rare ataxia disease with Ataxia, Cerebellar atrophy, and Tremor should also have Dysarthria. This rule is rejected if even one disease has the first three phenotypes but lacks Dysarthria. Ontology construction therefore needs a procedure that asks targeted structural questions and incorporates counterexamples when a proposed regularity fails [2]. Formal concept analysis (FCA) provides such a procedure. Its attribute exploration procedure proposes implications over a formal context and requires a counterexample when an implication is invalid [2, 3]. The proposed framework combines FCA with retrieval-grounded SLM judgments for rare ataxia diseases. The task is to build a disease-phenotype formal context

over standardized HPO labels such as Ataxia, Tremor, and Dysarthria. The practical question is whether a small seed attribute set can activate useful parts of the controlled phenotype attribute set while preserving verifiable incidence judgments and implication checks. Across three small language models (SLMs), the system expands the context over 20 rounds, keeping accepted implications, counterexamples, contradictions, and corrections inspectable. This paper makes three contributions. • An FCA-based verification loop that tests object-attribute structures through implications and counterexamples. • A retrieval-grounded SLM oracle for lower cost evidence based local judgments. • A symbolic-subsymbolic hybrid where FCA controls construction and the language model makes evidence-based local decisions. Together, the experiments position the method as a verifiable construction procedure rather than an unchecked ontology generator. The ablations further separate the difficulty of discovering object arXiv:2607.01773v1 [cs.AI] 2 Jul 2026 epiDAMIK @ KDD '26, August 10, 2026, Jeju Island, Republic of Korea Yang and Lee and attribute sets from the difficulty of judging incidences within those sets. 2 Background FCA supplies the symbolic side by representing the current construction state as a formal context and testing implications with counterexamples. RAG supplies the evidence grounding side by retrieving disease level text for the SLM oracle, turning ontology construction into a verifiable loop of implicatio ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '온톨로지 구축은 어떤 객체, 속성, 구조적 관계를 유효한 지식으로 수용할지 결정하는 과정을 수반한다. 언어 모델은 텍스트로부터 그러한 구조를 제안할 수 있지만, 그 결과는 여전히 근거가 없거나 일관성이 없을 수 있다. 본 논문은 지식 확장을 위한 기호적 검'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 340, 'candidatesTokenCount': 82, 'totalTokenCount': 2384, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 340}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'axpMavLILv7kqtsPs8CkiQM'}