

SLM / Edge Device arXiv Daily Summary

생성일: 2026-07-10 06:07 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 30일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 30일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: CSTutorBench: Benchmarking Small Language Models as Tutors for Block-Based Programming

저자: H. Chad Lane, Bryson Kageler

카테고리: SLM/Edge/On-device

arXiv ID: 2607.05571

제출일: 2026-07-06T19:15:07+00:00

수정일: 2026-07-06T19:15:07+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2607.05571.pdf>

[초록 원문]

Large language models are increasingly explored as AI tutors, yet deploying them in K-12 settings raises concerns around privacy, cost, and reliance on proprietary models. Small language models (SLMs) offer a promising alternative, but selecting the right model for a specific educational context remains difficult, particularly when the target domain, such as block-based programming, is largely absent from model training data. We introduce CSTutorBench, a benchmark for evaluating language models as CS tutors in VEX VR, a block-based robotics environment. The benchmark comprises 17 scenario-based questions scored against a pedagogical rubric grounded in established tutoring and feedback research, with a human-in-the-loop LLM-as-judge pipeline for evaluation. Preliminary findings across 11 models (4B-120B parameters) reveal that models perform well on surface-level criteria such as vocabulary and tone but struggle with deeper pedagogical behaviors, particularly avoiding answer leakage and engaging with student debugging histories. In our sample, model family and instruction-tuning approach appear to be better predictors of tutoring quality than parameter count alone, though the small number of models limits the strength of this conclusion. A targeted prompt revision grounded in recent educational prompt engineering research improved scores for 10 of 11 models. These results underscore the value

of context-specific, pedagogically grounded benchmarks for SLM selection in educational deployment.

[PDF 앞부분/서론 일부]

CSTutorBench: Benchmarking Small Language Models as Tutors for Block-Based Programming H. Chad Lane¹, Bryson Kageler¹ ¹University of Illinois Urbana-Champaign, Champaign, IL, USA Abstract Large language models are increasingly explored as AI tutors, yet deploying them in K-12 settings raises concerns around privacy, cost, and reliance on proprietary models. Small language models (SLMs) offer a promising alternative, but selecting the right model for a specific educational context remains difficult, particularly when the target domain, such as block-based programming, is largely absent from model training data. We introduce CSTutorBench, a benchmark for evaluating language models as CS tutors in VEX VR, a block-based robotics environment. The benchmark comprises 17 scenario-based questions scored against a pedagogical rubric grounded in established tutoring and feedback research, with a human-in-the-loop LLM-as-judge pipeline for evaluation. Preliminary findings across 11 models (4B-120B parameters) reveal that models perform well on surface-level criteria such as vocabulary and tone but struggle with deeper pedagogical behaviors, particularly avoiding answer leakage and engaging with student debugging histories. In our sample, model family and instruction-tuning approach appear to be better predictors of tutoring quality than parameter count alone, though the small number of models limits the strength of this conclusion. A targeted prompt revision grounded in recent educational prompt engineering research improved scores for 10 of 11 models. These results underscore the value of context-specific, pedagogically grounded benchmarks for SLM selection in educational deployment. Keywords small language models, benchmark, intelligent tutoring, block-based programming, LLM-as-judge

1. Introduction Large language models (LLMs) have demonstrated considerable potential as educational tools, particularly for tasks that involve generating explanations, providing feedback, and engaging learners in dialogue [1]. For computer science education, it is particularly appealing that many models are trained on large code corpora, meaning they can reliably produce syntactically correct solutions, trace through program logic, and explain programming concepts with impressive fluency [2]. But, echoing a classic lesson learned in AI in Education showing that it is unwise to simply wrap a tutor around an expert system [3]: we should not expect an LLM that is good at coding to be good at teaching people how to code. Effective tutoring involves a delicate balance of providing guidance, but allowing learners to maintain a sense of agency [4, 5, 6]. Although some benchmarks do focus on the educational capabilities of LLMs [7] and others on tutoring [8], there continues to be a need to more directly assess the tutoring and coaching capabilities of modern LLMs and investigate new methods for customizing their behavior. These challenges are amplified when the target population consists of young learners working in block-based programming environments such as Scratch, VEX, or Snap!. Block-based environments are designed specifically for education and are largely absent from the training data of even the most capable models. At the same time, practical constraints in K-12 settings around privacy, limited budgets, and the need for a high degree of local control, all point toward small language models (SLMs) as a viable path for addressing these needs. But SLMs vary widely in their behavior and there is little guidance to deciding which 8B or 30B model to deploy as a classroom tutor. In this paper, we introduce CSTutorBench, a benchmark for evaluating language models as CS tutors in VEX VR, a block-based robotics simulation for middle school students. The benchmark includes 17 scenario-based questions, an 8-criterion pedagogical rubric, and an automated LLM-as-judge evaluation pipeline. We present preliminary results comparing

models from 4B to 120B parameters and discuss implications for SLM selection in educational contexts. SLM4ED'26: The 1st Workshop of Small Language Models for Education (SLM4ED), June 28, 2026, Seoul, Republic of Korea ©2026 Copyright for this paper by its authors. Use permitted under Creative Commons License Attribution 4.0 International (CC BY 4.0). 2. CSTutorBench Figure 1: VEX VR Coral Reef Rescue environment. Task Domain. CSTutorBench is deliberately scoped to a single task and audience: middle school students (grades 6-8) working on VEX VR Coral Reef Rescue, a simulation in which students program a virtual robot to navigate an underwater environment and collect trash using a drag-and-drop Blockly interface. The task spans three levels of increasing complexity: Level 1 introduces sequencing and basic movement, Level 2 adds distance sensor navigation, and Level 3 requires algorithmic optimization. We needed a benchmark that draws from the actual task, audience, and pedagogical goals. General-purpose benchmarks cannot capture domain-specific requirements such as knowing that a VEX Drive Forward block is non-blocking or that the simulator arena is 2000 mm × 2000 mm. Student programs are represented as Blockly XML, a format largely absent from standard code training corpora, making this a particularly revealing test of whether a model can tutor effectively in a domain where it lacks deep pre-training. Dataset. The benchmark contains 17 scenario-based questions across four types: debugging(8), debugging_iterative(6), optimization(1), and conceptual(2). The questions are not drawn from real student data but are inspired by common errors and bugs we observe students making when working with VEX VR, including missing forever loops, inverted conditional logic, blocking commands, sensor misuse, and confusion between absolute and relative headings. Each entry includes the student's question text, one or more Blockly XML code snapshots, an 8-criterion rubric with universal and entry-specific scoring guides, and evalu ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '대규모 언어 모델(LLM)은 AI 튜터로서 활발히 연구되고 있지만, K-12 교육 환경에 배포할 경우 개인 정보 보호, 비용, 그리고 독점 모델에 대한 의존성 문제와 같은 우려를 제기한다. 소규모 언어 모델(SLM)은 유망한 대안을 제공하나, 특정 교육'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 350, 'candidatesTokenCount': 79, 'totalTokenCount': 2394, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 350}], 'thoughtsTokenCount': 1965, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'Xw1Qat-QJ4yb9MoPhqnToAg'}

[논문 후보 2]

제목: TF-Engram: A Train-Free Engram with SSD-Backed Memory for Large Language Models

저자: Yutang Ma, Kecheng Huang, Xikun Jiang, Zili Shao

카테고리: Format-LoRA/Structured Output

arXiv ID: 2607.07388

제출일: 2026-07-08T13:19:52+00:00

수정일: 2026-07-08T13:19:52+00:00

최근성: 최근 1일 이내

arXiv PDF: <https://arxiv.org/pdf/2607.07388.pdf>

[초록 원문]

Large Language Models (LLMs) store factual knowledge and domain-specific patterns implicitly in dense Transformer parameters, making knowledge expansion costly through pretraining, fine-tuning, retrieval augmentation, or longer contexts. Engram-style memory offers a compact hidden-state injection pathway, but existing GPU-resident designs often rely on hash-based compression, causing unrelated phrases to collide in shared slots and weakening phrase-level semantic fidelity. We present TF-Engram, a train-free Engram system that constructs phrase-specific semantic memory offline from external corpora, stores large memory tables across a GPU--DRAM--SSD hierarchy, and uses Early-Exit Guided Predictive Prefetching to hide external-memory latency during autoregressive decoding. On Qwen3-0.6B, TF-Engram improves the average downstream score from 57.6 to 59.4, outperforming both the frozen backbone and a parameter-matched LoRA baseline. System evaluation shows that large TF-Engram tables can be built with moderate offline cost, SSD-backed storage substantially reduces GPU memory demand, and predictive prefetching recovers much of the throughput loss caused by external memory access. These results demonstrate that static phrase memory can be integrated into LLM inference as a scalable, train-free, and low-overhead system component.

[PDF 앞부분/서론 일부]

TF-Engram: A Train-Free Engram with SSD-Backed Memory for Large Language Models Yutang MA The Chinese University of Hong Kong ytma2@cse.cuhk.edu.hk Kecheng HUANG Beijing Institute of Technology, Zhuhai huangkecheng@bitzh.edu.cn Xikun JIANG The Chinese University of Hong Kong xkjiang24@cse.cuhk.edu.hk Zili SHAO The Chinese University of Hong Kong shao@cse.cuhk.edu.hk

ABSTRACT Large Language Models (LLMs) store factual knowledge and domainspecific patterns implicitly in dense Transformer parameters, making knowledge expansion costly through pretraining, fine-tuning, retrieval augmentation, or longer contexts. Engram-style memory offers a compact hidden-state injection pathway, but existing GPUresident designs often rely on hash-based compression, causing unrelated phrases to collide in shared slots and weakening phrase-level semantic fidelity. We present TF-Engram, a train-free Engram system that constructs phrase-specific semantic memory offline from external corpora, stores large memory tables across a GPU-DRAM- SSD hierarchy, and uses Early-Exit Guided Predictive Prefetching to hide external-memory latency during autoregressive decoding. On Qwen3-0.6B, TF-Engram improves the average downstream score from 57.6 to 59.4, outperforming both the frozen backbone and a parameter-matched LoRA baseline. System evaluation shows that large TF-Engram tables can be built with moderate offline cost, SSD-backed storage substantially reduces GPU memory demand, and predictive prefetching recovers much of the throughput loss caused by external memory access. These results demonstrate that static phrase memory can be integrated into LLM inference as a scalable, train-free, and low-overhead system component.

1 INTRODUCTION Large Language Models (LLMs) have become the dominant architecture for natural language understanding, reasoning, code generation, and knowledge-intensive question answering [3, 7, 10, 28-30]. Their success is largely driven by scaling dense Transformer parameters and training data [12, 18]. However, this design also tightly couples knowledge capacity with model size: factual knowledge, domain-specific terminology, and frequently occurring semantic patterns are implicitly stored inside billions of neural parameters. Improving such knowledge often requires more pretraining, supervised fine-tuning, retrieval augmentation, or longer context windows [2, 3, 11, 23]. These solutions increase training cost, inference latency,

memory consumption, or deployment complexity. As LLMs are increasingly used in domain-specific and knowledge-intensive applications, it becomes important to decouple static knowledge storage from dense Transformer computation. Recent work on memory-augmented LLMs explores this decoupling from several directions. Retrieval-Augmented Generation (RAG) systems maintain an external document corpus and retrieve relevant passages during inference, usually appending the retrieved text to the prompt [2, 11, 15, 23]. Long-context and KV-cache based methods extend the amount of information accessible to the model by keeping more historical tokens or intermediate states [8, 9, 20]. Adapter-based and parameter-efficient memory methods inject additional trainable modules into the model, allowing new knowledge to be stored in a smaller number of parameters than full fine-tuning [13, 14, 21, 24]. Another line of work, represented by Engram-style memory, introduces a lightweight side memory pathway that stores token-level or phrase-level patterns and injects retrieved memory signals into the hidden states of the backbone model [5]. These categories differ substantially in memory granularity, training cost, inference overhead, and system scalability. Although RAG, long-context, and adapter-based methods are effective in many scenarios, they are not ideal for fine-grained static phrase memory. RAG retrieves coarse-grained text chunks rather than compact phrase-level memory entries, and the retrieved passages increase context length and attention cost [2, 15, 23]. Longcontext methods allow the model to attend to more information, but they still require the Transformer to process additional tokens, even when the useful knowledge corresponds to short and stable phrases [8, 9]. Adapter-based memory methods reduce the cost of full fine-tuning, but they still require training and are usually tied to a specific backbone model [13, 14, 21, 24]. In contrast, Engram-style memory is a more suitable starting point for a system-oriented design. It provides a compact side pathway, operates closer to token or phrase granularity, and can be integrated into LLM inference without restructuring the main Transformer computation [5]. Therefore, this paper focuses on extending Engram-style memory into a scalable external memory system for LLMs. Despite its promise, Engram-style memory is not yet a practical large-scale static memory system. Existing designs are mainly optimized as compact GPU-resident neural memory modules. To fit a large number of token patterns into limited accelerator memory, they often rely on hash-based compression, where many token sequences are mapped into a fixed-size table. This design reduces memory footprint, but it introduces a tension between memory coverage and memory fidelity. To make Engram suitable for large static phrase knowledge, three critical issues must be addressed: how to construct phrase-specific memory without additional training, how to scale memory capacity without relying on ambiguous hash-collision slots, and how to access external memory without stalling autoregressive decoding. arXiv:2607.07388v1 [cs.CL] 8 Jul 2026 Yutang MA, Kecheng HUANG, Xikun JIANG, and Zili SHAO The first critical issue is that memory construction remains training-dependent and model-specific. Conventional Engram designs typically learn memory entries, projection layers, gates, or auxiliary parameters from data, either jointly with the backbone model or through additional post-training [5, 13 ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '대규모 언어 모델(LLM)은 사실적 지식과 도메인별 패턴을 조밀한 트랜스포머 매개변수 내에 암묵적으로 저장하며, 이는 사전 학습, 미세 조정, 검색 증강 또는 더 긴 컨텍스트를 통해 지식을 확장하는 데 높은 비용을 수반한다. 엔그램(Engram) 방식의 메모'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 336,

'candidatesTokenCount': 82, 'totalTokenCount': 2380, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 336}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'aQ1Qaqb5BZ6MjMcPwK6c0Q0{'

[논문 후보 3]

제목: Optimizing ML Workload Partitioning between CPUs and CIM Accelerators for Heterogeneous Computing

저자: Joel Klein, Rebecca Pelke, Roberto Laudani, Jan Moritz Joseph, Rainer Leupers

카테고리: Deployment/Quantization/Efficiency

arXiv ID: 2607.05240

제출일: 2026-07-06T15:50:44+00:00

수정일: 2026-07-06T15:50:44+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2607.05240.pdf>

[초록 원문]

Computing-in-Memory (CIM) accelerators execute Matrix-Vector Multiplications (MVMs) in memory, making them a compelling solution for Machine Learning (ML) workloads. However, existing ML workload partitioning approaches for CIM accelerators do not fully account for Resistive Random Access Memory (RRAM) constraints such as limited memory, high write latency, and limited endurance. They also neglect parallelism, low-level architectural effects, or the Central Processing Unit (CPU) as a complementary compute resource. To address these limitations, we propose an Integer Linear Programming (ILP)-based workload partitioning framework for heterogeneous CPU-CIM systems. It minimizes end-to-end inference latency under RRAM constraints, captures parallelism, and combines empirical profiling with analytical models. Using our framework, heterogeneous CPU-CIM execution achieves speedups of up to 30.9x over CPU-only execution on an edge CPU and 7.3x over a high-performance CPU. A Design Space Exploration (DSE) yields further design insights for future CIM accelerators.

[PDF 앞부분/서론 일부]

or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works. including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale ©2026 IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other uses, in any current or future media, October 11-14, 2026, in Limassol, Cyprus. PREPRINT - Accepted for publication at the 34th IFIP/IEEE International Conference on Very Large Scale Integration SoC (VLSI-SoC), Optimizing ML Workload Partitioning between CPUs and CIM Accelerators for Heterogeneous Computing Joel Klein, Rebecca Pelke, Roberto Laudani, Jan Moritz Joseph, Rainer Leupers Institute for Communication Technologies and Embedded Systems, RWTH Aachen University, Germany {klein, pelke, laudani, joseph, leupers}@ice.rwth-aachen.de Abstract-Computing-in-Memory (CIM) accelerators execute Matrix-Vector Multiplications (MVMs) in memory, making them a compelling solution for Machine Learning (ML) workloads. However, existing ML workload partitioning approaches for CIM accelerators do not fully account for Resistive Random Access Memory (RRAM) constraints such as limited memory, high write latency, and limited endurance. They also neglect parallelism, low-level architectural effects, or the Central Processing Unit (CPU) as a

complementary compute resource. To address these limitations, we propose an Integer Linear Programming (ILP)-based workload partitioning framework for heterogeneous CPU-CIM systems. It minimizes end-to-end inference latency under RRAM constraints, captures parallelism, and combines empirical profiling with analytical models. Using our framework, heterogeneous CPU-CIM execution achieves speedups of up to 30.9× over CPU-only execution on an edge CPU and 7.3× over a high-performance CPU. A Design Space Exploration (DSE) yields further design insights for future CIM accelerators.

Index Terms- CIM, Heterogeneous Computing, Workload Partitioning, RRAM, ILP

INTRODUCTION

Efficient execution of Machine Learning (ML) workloads requires new hardware architectures. Computing-in-Memory (CIM) fuses computation and memory to address the von Neumann bottleneck [1], executing Matrix-Vector Multiplications (MVMs) with $O(1)$ latency using crossbar arrays [2]-[4]. Resistive Random Access Memory (RRAM) is a promising CIM candidate due to its high device density, low power consumption, non-volatility, and CMOS compatibility [1], [5], [6]. However, CIM accelerators rely on a host Central Processing Unit (CPU) to execute unsupported operators, requiring workload partitioning between CPU and CIM accelerator [4]. Furthermore, CIM storage is limited by the available crossbars [7]. Modern Convolutional Neural Networks (CNNs) often exceed this capacity [7]-[11]. Moreover, RRAM write latency and endurance limits make dynamic weight replacement impractical [5], [6], [12]. Hence, deployment requires static assignment of selected operators to the CIM accelerator. Existing ML partitioning approaches [13]-[16] treat devices as black boxes, neglect low-level architectural characteristics or assume sequential execution. CIM-specific methods either assume full-model fit [17], [18] or rely on weight reprogramming [7], [11]. Furthermore, workload partitioning between the host CPU and the CIM accelerator remains an open problem. This work was funded by the Federal Ministry of Research, Technology and Space, Germany, in the project NeuroSys II (03ZU2106CA).

Design Space Exploration

III Partitioned Model Performance Statistics

Hardware Specifications

ONNX Model Workload Partitioning using ILP

Model II

Profiling (Host CPU)

Analytical Models (CIM + Interconnect)

Latency Data Generation

I Fig. 1: Overview of the proposed partitioning framework

We propose a system-level workload partitioning framework for heterogeneous CPU-CIM systems. It covers latency characterization and static operator assignment. The resulting partitioning between CPU and CIM achieves up to 30.9× and 7.3× speedup over CPU-only execution on ARM edge and x86 CPUs, respectively. Fig. 1 illustrates the framework's components. We highlight the following contributions:

- I A hybrid latency characterization methodology, integrating empirical host CPU profiling with an analytical CIM accelerator and interconnect performance model.
- II An Integer Linear Programming (ILP) formulation for static operator assignment that minimizes the end-to-end inference latency accounting for limited CIM memory budget, operator support, and parallelism constraints.
- III A Design Space Exploration (DSE) using the proposed framework to analyze the impact of model architectures and hardware parameters on system performance, providing design insights for future CIM accelerators.

Sections II and III provide background and review prior work. Section IV presents our framework. Section V reports results and a DSE. Section VI concludes the paper.

II. BACKGROUND

This section presents background related to RRAM-based CIM accelerators and the ILP concepts used in this work.

A. RRAM-based CIM Accelerators

RRAM is a memristive non-volatile memory technology that stores data as resistance states [1], [5], [6]. By arranging RRAM cells in crossbar arrays, CIM accelerators perform analog MVMs via Ohm's and Kirchhoff's laws [2]-[4]. Since programming RRAM cells is slow and repeated writes degrade device endurance [6], [12], a weight-stationary dataflow, where

weights are programmed once before inference, is particularly well-suited for RRAM-based CIM accelerators [2], [4]. The PUMA architecture [4] is hierarchically organized into CIM cores, connected by an internal bus. Each core contains a control unit, instruction memory, a Matrix-Vector Multiplication Unit (MVMU), a General-Purpose Execution Unit (GPEU), and a data buffer. The MVMU comprises multiple RRAM crossbars with peripheral circuits. The GPEU performs ... [앞부분 텍스트 일부 생략]

[초록 번역]

Computing-in-Memory (CIM) 가속기는 메모리 내에서 행렬-벡터 곱셈(MVM)을 실행하여, 머신러닝(ML) 워크로드에 매력적인 솔루션입니다. 그러나 기존 CIM 가속기용 ML 워크로드 분할 접근 방식은 제한된 메모리, 높은 쓰기 지연 시간, 제한된 내구성 등 저항성 랜덤 액세스 메모리(RRAM) 제약 조건을 완전히 고려하지 않습니다. 또한, 이들은 병렬 처리, 저수준 아키텍처 효과, 또는 보완적인 컴퓨팅 자원으로서의 중앙 처리 장치(CPU)를 간과합니다.

이러한 한계를 해결하기 위해, 우리는 이중 CPU-CIM 시스템을 위한 정수 선형 계획법(ILP) 기반 워크로드 분할 프레임워크를 제안합니다. 이 프레임워크는 RRAM 제약 조건 하에서 종단 간 추론 지연 시간을 최소화하고, 병렬 처리를 포착하며, 경험적 프로파일링과 분석 모델을 결합합니다. 우리 프레임워크를 사용하여, 이중 CPU-CIM 실행은 엣지 CPU에서 CPU 단독 실행 대비 최대 30.9배, 고성능 CPU 대비 7.3배의 속도 향상을 달성합니다. 설계 공간 탐색(DSE)은 미래 CIM 가속기를 위한 추가적인 설계 통찰력을 제공합니다.