# SLM / Edge Device arXiv Daily Summary

생성일: 2026-10-26 07:01 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 30일

**Gemini 전체 요약 실패**

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.
대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.
각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.
이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 30일
오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

**[논문 후보 1]**

제목: WorldForge V2: Eliciting Camera-Trajectory Alignment in Video Diffusion Models
저자: Chenxi Song, Yanming Yang, Tong Zhao, Ruibo Li, Joey Tianyi Zhou, Chi Zhang
카테고리: Format-LoRA/Structured Output
arXiv ID: 2610.31640
제출일: 2026-10-22T17:53:03+00:00
수정일: 2026-10-22T17:53:03+00:00
최근성: 최근 3일 이내
arXiv PDF: https://arxiv.org/pdf/2610.31640.pdf

**[초록 원문]**

Video diffusion models have learned rich 3D/4D priors, making them promising for scene generation and video re-rendering. However, their use in spatial tasks is limited by imprecise camera control, spatial and temporal inconsistencies, and entangled camera motion with scene dynamics. Existing approaches, such as task-specific fine-tuning and post-process warping, often introduce visual artifacts, generalize poorly, or incur high computational costs. We propose WorldForge V2 to achieve accurate camera control while preserving the generative capabilities of pretrained video models. We first develop a training-free guidance framework using warped references to iteratively refine generation along a target camera path. Optical-flow analysis identifies motion-related latent channels for selective guidance, helping separate motion control from appearance. A dual-path strategy further compares guided and unguided predictions to correct artifacts from imperfect references. Together, these components guide viewpoint changes while preserving scene appearance and object motion. To reduce refinement costs, v-cache approximates the correction using the preceding denoising prediction, avoiding an additional model evaluation. We further extend motion localization from latent channels to network blocks and introduce Trajectory LoRA, which concentrates adaptation on blocks most responsive to trajectory

guidance. A two-stage training strategy teaches these adapters to denoise the states encountered during guided generation, using limited supervision effectively. This enables reliable camera control with very little training data, with a single training scene already supporting generalization to unseen scenes. Quantitative and qualitative evaluations across multiple datasets show that our method achieves state-of-the-art generation quality and trajectory accuracy in camera-controlled video generation.

**[PDF 앞부분/서론 일부]**

WORLDFORGE V2 1 WorldForge V2: Eliciting Camera-Trajectory Alignment in Video Diffusion Models Chenxi Song, Yanming Yang, Tong Zhao, Ruibo Li, Joey Tianyi Zhou,Senior Member, IEEE,and Chi Zhang,Member, IEEE Abstract-Video diffusion models have learned rich 3D/4D priors, making them promising for scene generation and video re-rendering. However, their use in these spatial tasks is limited by imprecise camera control, spatial and temporal inconsistencies, and the entanglement of camera motion with scene dynamics. Existing approaches, such as task-specific fine-tuning and post-process warping, often introduce visual artifacts, generalize poorly, or incur high computational costs. We propose WorldForge V2, which aims to achieve accurate camera control while preserving the generative capabilities of pretrained video models. We first develop a training-free guidance framework using warped references to iteratively refine generation along a target camera path. Optical-flow analysis identifies motionrelated latent channels for selective guidance, helping separate motion control from appearance. A dual-path strategy further compares guided and unguided predictions to correct artifacts from imperfect references. Together, these components guide viewpoint changes while preserving scene appearance and object motion. To reduce refinement costs, v-cache approximates the correction using the preceding denoising prediction, avoiding an additional model evaluation. We further extend motion localization from latent channels to network blocks and introduce Trajectory LoRA, which concentrates adaptation on blocks most responsive to trajectory guidance. A two-stage training strategy teaches these adapters to denoise the states encountered during guided generation, using limited supervision effectively. This enables reliable camera control with very little training data, with a single training scene already supporting generalization to unseen scenes. Quantitative and qualitative evaluations across multiple datasets show that our method achieves state-of-the-art generation quality and trajectory accuracy in camera-controlled video generation. Index Terms-Camera control, video diffusion models, 3D/4D generation. I. INTRODUCTION R ECENT video diffusion models (VDMs) can synthesize videos with coherent motion, consistent scene content, and plausible viewpoint changes over time [1]-[3]. Trained on large-scale video data, these models acquire strong spatiotemporal priors, making them powerful backbones for spatial-intelligence tasks such as 3D/4D generation, video rerendering, and world modeling [4]-[11]. In these applications, the camera trajectory determines how a scene is observed over time, which regions become visible, and how viewpoint changes relate to scene geometry. Effective trajectory control is therefore essential. The generated video should follow a C. Song, Y . Yang, T. Zhao, and C. Zhang are with Westlake University, Hangzhou, China. R. Li is with Beihang University, Beijing, China. J. T. Zhou is with Singapore Management University, Singapore. Corresponding author: Chi Zhang (e-mail: chizhang@westlake.edu.cn). PSNR ↑ SSIM ↑ LPIPS ↓ Vis-LPIPS ↓ Disocc-LPIPS ↓ ATE ↓ RPE-T ↓ RPE-R ↓ Ours UniWorld-View TrajectoryCrafter SymphoMotion Warp-as-History Fig. 1. Comparison with existing methods. With limited training data and iterations, our method achieves state-of-the-art visual quality and trajectory accuracy in camera-controlled video generation. specified camera path while preserving scene content,

object motion, temporal coherence, and visual quality. To realize such control, existing approaches broadly follow two directions. One direction adapts VDMs for camera control through additional trainable modules, pose-aware conditioning interfaces, or model fine-tuning [5], [12]-[16]. These methods provide explicit camera control but often require largescale trajectory-video supervision or careful fine-tuning. With limited supervision, such adaptation may weaken the visual and temporal priors of the pretrained model. Recent work has therefore explored training-free alternatives that keep the pretrained VDM fixed and inject trajectory cues only during inference [6], [17], including the zero-shot variant of Warp-asHistory [18]. A representative route iswarping-and-repainting, which warps already observed content along the target camera path and uses the pretrained video model to synthesize newly revealed regions. This route enables direct camera control at inference time while preserving the pretrained model, making it well suited to downstream spatial-intelligence tasks. Despite these advantages, warping-and-repainting can introduce a denoising-state mismatch during diffusion sampling. When warped visible regions are directly combined with model-generated regions in a noisy latent, the two parts may correspond to different noise states. The warped regions are associated with externally sampled noise, whereas the arXiv:2610.31640v1 [cs.CV] 22 Oct 2026 WORLDFORGE V2 2 generated regions follow the model's own denoising trajectory. We refer to this mismatch as adenoising-state domain gap. It can lead to boundary discontinuities, geometric artifacts, noisy patches, and texture degradation. The key challenge is therefore to inject useful trajectory evidence from warped references while reducing the denoising-state gap introduced by their fusion. To address this problem, we proposeWorldForge V2, a camera-trajectory-control framework that helps VDMs use imperfect warped trajectory signals more effectively while preserving generation quality. WorldForge V2 follows the warping-and-repainting route. First, it addresses the incompatibility introduced by warped-reference fusion: direct fusion in noisy latents mixes externally noised warped regions with generated regions following the model's current denoising state. WorldForge V2 reduces this mismatch by fusing the warped reference into the model-predicted clean estimate a ... [앞부분 텍스트 일부 생략]

**[초록 번역]**

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '비디오 확산 모델은 풍부한 3D/4D 사전 지식을 학습하여 장면 생성 및 비디오 재렌더링에 유망합니다. 그러나 부정확한 카메라 제어, 공간적 및 시간적 불일치, 그리고 카메라 움직임과 장면 역학의 얽힘으로 인해 공간 작업에서의 활용이 제한됩니다. 작업별 미세 조정 및 후처리 워핑과 같은 기존 접근 방식은 종종 시각적 아티팩트를 유발하고, 일반화 성능이 낮거나, 높은 계산 비용을 초래합니다.₩n₩n저희는 사전 학습된 비디오 모델의 생성 능력을 보존하면서 정확한 카메라 제어를 달성하기 위해 WorldForge V2를 제안합니다. 먼저, 워핑된 참조를 사용하여 목표 카메라 경로를 따라 생성을 반복적으로 개선하는 훈련 없는 안내 프레임워크를 개발합니다. 광학 흐름 분석은 선택적 안내를 위해 움직임 관련 잠재 채널을 식별하여 움직임 제어를 외형으로부터 분리하는 데 기여합니다. 이중 경로 전략은 안내된 예측과 안내되지 않은 예측을 비교하여 불완전한 참조로'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 384, 'candidatesTokenCount': 242, 'totalTokenCount': 2428, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 384}], 'thoughtsTokenCount': 1802, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'AXzeatDzDqiV39IPp_XR6A0'}

**[논문 후보 2]**

제목: SAKURA: Serving Attention Key-Value State Under Rate Adaptation for Private Image Editing on Phones

저자: Shuncheng Jie, Desen Sun, Ri Hong, Yuyang Tian, Hong Zhang, Sihang Liu

카테고리: SLM/Edge/On-device

arXiv ID: 2610.29733

제출일: 2026-10-21T13:35:39+00:00

수정일: 2026-10-21T13:35:39+00:00

최근성: 최근 4일 이내

arXiv PDF: https://arxiv.org/pdf/2610.29733.pdf

**[초록 원문]**

Diffusion transformers are widely used in image-editing services. To preserve both efficiency and privacy, existing systems commonly rely on cloud-device collaboration. Keeping request-specific inference on the device avoids sending personal images and prompts to the cloud. These workloads often use common templates, such as in face swapping and virtual try-on, enabling KV state to be precomputed and reused across requests. However, this reusable state is large and scales with the number of templates, making it impractical to store all of them on mobile devices. Storing them in the cloud addresses this capacity issue, but cache transfer is placed onto the inference path and can even be slower than on-device computation, especially under fluctuating mobile networks. We introduce SAKURA, a cloud-edge architecture that delivers reusable attention state to mobile devices under a bandwidth budget. It first uses a fine-grained token-importance-aware compression method to preserve image quality under limited transfer budgets. At runtime, SAKURA adaptively selects the cache representation for each upcoming shard based on network bandwidth. To enable efficient execution, we develop a pipelined runtime that overlaps cache transfer and reconstruction with on-device execution. We evaluate SAKURA using three editing tasks and two diffusion models, using a Snapdragon 8 Elite Gen 5 phone. SAKURA reduces latency by 1.82x and 3.27x over CacheGen adapted to DiT and on-device generation, respectively. It also reduces cache storage by 3.06x over uncompressed cache, while preserving image quality.

**[PDF 앞부분/서론 일부]**

SAKURA: Serving Attention Key-Value State Under Rate Adaptation for Private Image Editing on Phones Shuncheng Jie University of Waterloo Canada kevin.jie@uwaterloo.ca Desen Sun University of Waterloo Canada desen.sun@uwaterloo.ca Ri Hong University of Waterloo Canada r7hong@uwaterloo.ca Yuyang Tian University of Waterloo Canada y254tian@uwaterloo.ca Hong Zhang University of Waterloo Canada hongzhangblaze@gmail.com Sihang Liu University of Waterloo Canada sihangliu@uwaterloo.ca Abstract Diffusion transformers are widely used in image-editing services. To preserve both efficiency and privacy, existing systems commonly rely on cloud-device collaboration. Keeping request-specific inference on the device avoids sending personal images and prompts to the cloud. These workloads often use common templates, such as in face swapping and virtual try-on, enabling KV state to be precomputed and reused across requests. However, this reusable state is large and scales with the number of templates, making it impractical to store all of them on mobile devices. Storing them in the cloud addresses this capacity issue, but cache transfer is placed onto the inference path and can even be slower than on-device computation, especially under fluctuating mobile networks. We

introduce SAKURA, a cloud-edge architecture that delivers reusable attention state to mobile devices under a bandwidth budget. It first uses a fine-grained token-importanceaware compression method to preserve image quality under limited transfer budgets. At runtime, SAKURA adaptively selects the cache representation for each upcoming shard based on network bandwidth. To enable efficient execution, we develop a pipelined runtime that overlaps cache transfer and reconstruction with on-device execution. We evaluate SAKURA using three editing tasks and two diffusion models, using a Snapdragon 8 Elite Gen 5 phone. SAKURA reduces latency by 1.82× and 3.27× over CacheGen adapted to DiT and on-device generation, respectively. It also reduces cache storage by 3.06× over uncompressed cache, while preserving image quality. 1 Introduction Diffusion transformers (DiTs) have become a leading architecture for high-fidelity image generation and editing [7, 10, 16, 47]. A widely deployed class of editing applications personalizes only part of a provider-supplied image while preserving the surrounding content. Virtual try-on [28, 58, 75], face swapping [6, 23, 70], and localized image editing [25, 43, 52] are representative examples. Personalized editing is already offered by cloud services, such as Google Shopping's photo-conditioned virtual try-on and Amazon Nova Canvas's managed virtual try-on API [3-5, 20]. These applications take two kinds of different inputs: providerowned templates can be public and reused across users, whereas each request contains privacy-sensitive user data such as personal photographs, reference images, and editing instructions. Keeping request-specific inference on the device is therefore attractive because these inputs and the intermediate states derived from them need not be sent to a remote execution service. Recent advances in model compression, architecture optimization, and heterogeneous mobile execution have made on-device diffusion inference increasingly practical [11, 34, 77]. When requests share a template and a fixed mask defining the editable region, computation associated with the unchanged region can be reused across requests. In a DiT, the key/value (KV) state of these reusable tokens can be precomputed for each template and reused while the device computes only the request-dependent state for the edited region [25, 31, 49, 71]. Cross-request reuse can therefore substantially reduce repeated on-device computation. Every template has a different reusable state and the aggregate footprint grows with the number of templates. This creates a mobile-specific scalability gap betweenexecution capacityandreuse capacity: a device may have enough compute and working memory to run each edit, yet lack the storage to retain caches across a large template catalog. In our FLUX.2-klein-4B deployment [7] at512× 512resolution, the reusable FP16 KV state occupies up to 1.46 GiB for a single template. A catalog with hundreds of templates would therefore require hundreds of gigabytes of persistent storage, far beyond what is practical to replicate on individual mobile devices. Cloud-only execution avoids this storage constraint but requires sending private user requests to the server. We instead consider a different cloud-edge split: request-specific inference remains on the device, while the cloud stores the much larger, provider-owned reusable templates and supplies the required cache on demand. Unlike conventional 1 arXiv:2610.29733v1 [cs.SE] 21 Oct 2026 cloud-edge inference, which offloads all or part of a request to remote compute [22, 27, 68], this scheme uses the cloud for template storage. The network carries reusable template state, while user inputs and request-specific activations remain on the device. Moving reusable state to the cloud resolves the device-side capacity problem, but places cache transfer on the inference path. At the 545 Mbps median bandwidth of the 5G trace used in our evaluation [45], transferring the full FP16 cache takes approximately 23 s, even without device-side cache reconstruction. In comparison, executing the complete model locally without cache reuse takes about 13 s on our

mobile platform. Naively fetching the full cache is therefore slower than running the complete model locally. Remote reuse must both reduce the transmitted bytes and hide cache transfer behind local computation. These requirements translate into two challenges. First, the cache must be compressed aggressively enough to arrive before use while preserving editing quality. At an approximately 10% mask ratio, only 2.3 s of local computation is available in total to hide cache transfer; even uniform 2-bit quantization requires at least ... [앞부분 텍스트 일부 생략]

**[초록 번역]**

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '확산 트랜스포머는 이미지 편집 서비스에서 널리 활용되고 있습니다. 효율성과 프라이버시를 동시에 보존하기 위해, 기존 시스템들은 일반적으로 클라우드-기기 협업에 의존합니다. 요청별 추론을 기기에서 수행함으로써 개인 이미지와 프롬프트가 클라우드로 전송되는 것을 방지합니다. 이러한 워크로드들은'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 385, 'candidatesTokenCount': 82, 'totalTokenCount': 2429, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 385}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'CnzeatPJFY3B39IPlbvW2AU'}

**[논문 후보 3]**

제목: Model Exposure on One Device Endangers Others: Rethinking Edge Neural Network Security across Devices
저자: Yuyang Zhang, Kangjie Chen, Yihui Jin, Run Wang
카테고리: SLM/Edge/On-device
arXiv ID: 2610.27152
제출일: 2026-10-19T18:45:18+00:00
수정일: 2026-10-19T18:45:18+00:00
최근성: 최근 6일 이내
arXiv PDF: https://arxiv.org/pdf/2610.27152.pdf

**[초록 원문]**

Neural networks (NNs) are increasingly deployed on edge devices such as mobile and IoT platforms, offering low latency and improved privacy compared to cloud-based deployment. However, on-device models embedded in mobile applications can be unpacked and exposed to adversaries, enabling cross-node attacks in centrally distributed ecosystems, where adversarial examples crafted on one compromised device transfer effectively to other nodes sharing the same models. To address this threat, we propose VeilNN, a defense framework that reduces adversarial transferability across on-device models via model obfuscation. The core idea of VeilNN is to introduce controlled model diversity while preserving original task functionality. Specifically, VeilNN applies stealthy and irreversible obfuscation at both the architectural and parameter levels through network cell obfuscation and layer assembling, and is applicable to diverse NN architectures, including MLPs, CNNs, and Vision Transformers. Extensive experiments demonstrate that VeilNN effectively defends against cross-node attacks, achieving an average defense success of 49.19% and up to 81.19% across four adversarial attack types, with more than 33.16% improvement over existing defenses.

**[PDF 앞부분/서론 일부]**

Model Exposure on One Device Endangers Others: Rethinking Edge Neural Network Security across Devices Yuyang Zhang ,Kangjie Chen ,Yihui Jin ,Run Wang Equal contribution. Abstract Neural networks (NNs) are increasingly deployed on edge devices such as mobile and IoT platforms, offering low latency and improved privacy compared to cloud-based deployment. However, on-device models embedded in mobile applications can be unpacked and exposed to adversaries, enablingcross-node attacksin centrally distributed ecosystems, where adversarial examples crafted on one compromised device transfer effectively to other nodes sharing the same models. To address this threat, we propose VeilNN, a defense framework that reduces adversarial transferability across on-device models via model obfuscation. The core idea of VeilNN is to introduce controlled model diversity while preserving original task functionality. Specifically, VeilNN applies stealthy and irreversible obfuscation at both the architectural and parameter levels throughnetwork cell obfuscationandlayer assembling, and is applicable to diverse NN architectures, including MLPs, CNNs, and Vision Transformers. Extensive experiments demonstrate that VeilNN effectively defends against cross-node attacks, achieving an average defense success of49.19%and up to81.19% across four adversarial attack types, with more than 33.16%improvement over existing defenses. 1 Introduction In the past decades, deep learning (DL) models have been widely applied in many cutting-edge fields (e.g., image classification, speech recognition, natural language processing) and achieved impressive progress [Linet al., 2020 ]. These DL models are commonly deployed in cloud servers (traditional AI systems) to provide services to our users[Sunet al., 2021; Oliynyket al., 2023 ]. In the very recent few years, AI chips that are dedicated to edge devices have been developed and widely assembled in mobile and IoT devices for empowering their capability in tackling heavy computing on edge devices [Ignatovet al., 2019 ]. Thus, we are witnessing massive applications with on-device models for providing many fruitful services to end users [Xuet al., 2019 ]. Those ondevice models are gaining popularity due to their low latency Distribute Safe Nodes Adversary Model Adversarial Attacks Attack Stealing Model Knowledge Unpacking AppStore Compromised Node App Target System FeedBack Cross-Node Scenario Hacked Single-Node Scenario Figure 1:Threat of adversarial attacks incross-node scenarios. Unlike single-node scenarios, which evaluate adversarial robustness solely on the targeted device and overlook threats to other identical nodes, cross-node scenarios allow an attacker to compromise one node, gain white-box access, and craft adversarial examples that successfully transfer to other devices running the same deep-learningdriven applications. in prediction and needless user data transmission, thus this paradigm becomes more efficient and safe[Wanget al., 2025; Huang and Chen, 2022]. Unfortunately, numerous studies have revealed that a large quantity of edge devices are untrustable, where the applications deployed could be easily reversed by adopting the popular unpacking techniques [Sunet al., 2021 ] and the embedded on-device models could be easily stolen by the popular model stealing techniques [Oliynyket al., 2023 ]. Thus, the on-device models are exposed to the adversary in the whitebox setting which is more vulnerable to various adversarial attacks, such as evasion attacks and bit-flip attacks [Dongetal., 2023 ],etc. In a more practical and real scenario, the on-device models are distributed in a centralized manner via the app store (e.g., Google Play) [Huetal., 2023 ] and suffer thecross-node attack.Figure 1shows the adversarial attacks incross-node scenariosagainst on-device models from the same mobile application. The attacker aims at compromising a target on-device model by unpacking the app directly or reversing the model weights to conduct a white-box adversarial attack and leverage the knowledge(e.g., model architecture, trainable weight, defense strategies) of the compromised node could be leveraged to attack the other on-device

models sharing the same models or applications in black-box settings. For example, Huanget al. [Huang and Chen, 2022] 1 arXiv:2610.27152v1 [cs.CR] 19 Oct 2026 found that the adversarial examples crafted from the compromised node could be easily applied to fool the on-device models (safe nodes) from the same mobile application. Although these target nodes are not compromised themselves, the uniformity of model deployment allows the attack to succeed in a black-box manner. This contrasts with single-node attacks, which only evaluate whether adversarial examples succeed on the targeted device, while overlooking the broader threat posed to other identical nodes. As a result, defense methods that appear effective insingle-nodesettings fail entirely under cross-node scenarios. Prior studies have shown that models with similar architectures and partially aligned parameters exhibit strong adversarial attack transferability [Sunet al., 2021; Wanget al., 2024]. Such transferability is a key enabler of black-box attacks. However, incross-node scenarios, the deployed models are identical in both architecture and parameters across devices. This complete homogeneity further amplifies the vulnerability, as adversaries can generate highly effective attacks using white-box access to any compromised node [Zhouet al., 2024b]. This makes safeguarding the model's architecture and weights from being exposed crucial for defending against the adversarial attack incross-node scenarios. A straightforward approach to mitigating transferability is to design a special model in a different architecture and retrain the model with different hyperparameters. However, re-designing and retraining the model is computationally expensive, and the illogical structure and training parameters c ... [앞부분 텍스트 일부 생략]

**[초록 번역]**

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '신경망(NN)은 모바일 및 IoT 플랫폼과 같은 엣지 디바이스에 점점 더 많이 배포되어, 클라우드 기반 배포에 비해 낮은 지연 시간과 향상된 프라이버시를 제공한다. 그러나 모바일 애플리케이션에 내장된 온디바이스 모델은 언팩(unpacked)되어 공격자에게 노출될'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 299, 'candidatesTokenCount': 82, 'totalTokenCount': 2343, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 299}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'E3zeauapJZyFjrEP8PbAAQ'}