

SLM / Edge Device arXiv Daily Summary

생성일: 2026-06-10 06:32 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 7일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 7일

오류 메시지: 모든 Gemini 모델 호출 실패:

```
{
  "error": {
    "code": 429,
    "message": "Your prepayment credits are depleted. Please go to AI Studio at https://ai.studio/projects to manage your project and billing. Learn more at https://ai.google.dev/gemini-api/docs/billing#prep ay. ",
    "status": "RESOURCE_EXHAUSTED"
  }
}
```

[논문 후보 1]

제목: Distilling Safe LLM Systems via Soft Prompts for On Device Settings

저자: Motasem Alfarrar, Cristina Pinneri, Dana Kianfar, Mohammed Almousa, Christos Louizos

카테고리: SLM/Edge/On-device

arXiv ID: 2606.09388

제출일: 2026-06-08T12:03:51+00:00

수정일: 2026-06-08T12:03:51+00:00

최근성: 최근 1일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.09388.pdf>

[초록 원문]

Deploying safe large language models (LLMs) on resource-constrained edge devices presents a critical challenge: while dual-model systems combining LLMs with guard models provide effective safety guarantees, their substantial memory and computational demands make them prohibitively expensive for on-device deployment. This paper presents a comprehensive study of parameter-efficient safety alignment methods for resource-constrained settings. Through systematic evaluation across multiple LLM architectures, training objectives, and parameter-efficient

fine-tuning approaches, we identify that soft prompts combined with distillation-based training consistently outperform alternative methods. We introduce distillation frameworks based on total variation and KL divergence that effectively transfer safety behaviors from guard models into learned soft prompts. Our evaluations on various benchmarks demonstrate that this combination achieves superior safety-usefulness trade-offs compared to LoRA adapters, steering vectors, and direct optimization methods, while requiring minimal additional memory and compute at inference time. These findings establish soft prompt distillation as the preferred approach for safety alignment in on-device LLM deployment.

[PDF 앞부분/서론 일부]

Distilling Safe LLM Systems via Soft Prompts for On Device Settings Motasem Alfarra¹ Cristina Pinneri¹ Dana Kianfar¹ Mohammed Almousa¹ Christos Louizos¹ ¹Qualcomm AI Research Abstract Deploying safe large language models (LLMs) on resource-constrained edge devices presents a critical challenge: while dual-model systems combining LLMs with guard models provide effective safety guarantees, their substantial memory and computational demands make them prohibitively expensive for on-device deployment. This paper presents a comprehensive study of parameter-efficient safety alignment methods for resource-constrained settings. Through systematic evaluation across multiple LLM architectures, training objectives, and parameter-efficient fine-tuning approaches, we identify that soft prompts combined with distillation-based training consistently outperform alternative methods. We introduce distillation frameworks based on total variation and KL divergence that effectively transfer safety behaviors from guard models into learned soft prompts. Our evaluations on various benchmarks demonstrate that this combination achieves superior safety-usefulness trade-offs compared to LoRA adapters, steering vectors, and direct optimization methods, while requiring minimal additional memory and compute at inference time. These findings establish soft prompt distillation as the preferred approach for safety alignment in on-device LLM deployment.

1 INTRODUCTION Despite their remarkable adoption across research and industry, large language models (LLMs) can generate unsafe and toxic content in response to certain prompts. For example, an LLM might produce harmful or offensive language if Corr. to: malfarra@qti.qualcomm.com. Qualcomm AI Research is an initiative of Qualcomm Technologies, Inc Figure 1: Safety - Compute Trade-off. LLMs (denoted as Base Model) can generate unsafe and toxic content. When paired with a Guard Model; altogether called a safe LLM system, their safety improves at the expense of a substantial compute and memory penalty which may hinder their usability. In this work, we systematically study safety alignment methods for on-device deployment and identify soft prompts with distillation as the optimal approach. manipulated by a malicious user [Xu et al., 2023, Brundage et al., 2018, Liu et al., 2023]. Safety fine-tuning methods such as reinforcement learning (RL), supervised fine-tuning, etc. [Bai et al., 2022], can offer improvements in terms of safety alignment of the base LLM but system-level enhancements and layered defenses are necessary for minimizing risks [Meta, 2024]. To address this, guard models [Inan et al., 2023] have been introduced to evaluate and maintain the safety of LLM responses to user prompts. In this design the guard model assesses the safety of the response before exposing it to the user. In a nutshell, a guard model is a separate LLM that classifies the input pair (x, y) as safe or unsafe with x being the user's prompt and y being the response of the LLM. When (x, y) is deemed unsafe a pre-defined refusal answer, such as "Sorry, I cannot help with this matter.", overrides the initial response arXiv:2606.09388v1 [cs.LG] 8 Jun 2026 y. This approach is the last line of defense against toxic and harmful responses, while preserving the

capabilities of the LLM when its response is deemed safe. While recent studies [Mangaokar et al., 2024] have shown that guard models are vulnerable to adversarial perturbations, they are used as a de-facto method for building safe LLM systems. However, the dual-model approach demands significant memory and computational resources, making it especially unsuitable for on-device deployment where memory and compute are severely limited [Qin et al., 2024]. This challenge is illustrated in Figure 1. In addition, the sequential nature of this approach (i.e. the guard waits for the full output of the LLM before classifying it) degrades important metrics such as time-to-first-token. Various strategies have been proposed to address this issue, including quantizing the models to reduce memory consumption, distilling large LLMs into smaller models, and fine-tuning LLMs to mitigate toxic outputs [Lin et al., 2024, Fedorov et al., 2024]. While these methods improve memory efficiency and enhance safety, they often compromise the LLM's generalization capabilities [Xu et al., 2024a] and the effectiveness of different parameter-efficient fine-tuning (PEFT) methods and training objectives for safety alignment in resource-constrained settings remains unclear. Which combination of adaptation method and training objective best balances safety, usefulness, and computational efficiency for on-device deployment? In this work, we conduct a comprehensive study to answer this question. We systematically compare different PEFT methods and training objectives to identify the most effective approach for on-device safety alignment. Through extensive experiments across multiple LLM architectures and safety benchmarks, we find that soft prompts trained via distillation consistently achieve the best safety-usefulness tradeoffs. At test-time, the learned soft prompts are prepended to the user's prompt before feeding them to the LLM. We validate our findings through on-device measurements on smart phones powered with Qualcomm Snapdragon hardware, demonstrating practical applicability for edge deployment. Our contributions are thus three-fold: 1. We demonstrate through systematic comparison that soft prompts trained via distillation consistently outperform LoRA adapters, steering vectors, and alternative training objectives (perplexity, policy gradients) for on-device safety alignment, achieving superior safetyusefulness trade-offs. 2. We develop distillation frameworks based on total variation and KL divergence that effectively transfer safety behaviors from guard models to compact soft prompts, with guarantees on downstream performance. 3. We establish that soft prompt distillation provides ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: 모든 Gemini 모델 호출 실패:

```
{
  "error": {
    "code": 429,
    "message": "Your prepayment credits are depleted. Please go to AI Studio at https://ai.studio/projects to manage your project and billing. Learn more at https://ai.google.dev/gemini-api/docs/billing#prep ay. ",
    "status": "RESOURCE_EXHAUSTED"
  }
}
```

[논문 후보 2]

제목: Data Synthesis and Parameter-Efficient Fine-Tuning for Low-Resource NMT: A Case Study on Q'eqchi' Mayan

저자: Alexander Chulzhanov, Soeren Eberhardt, Arjun Mukherjee

카테고리: Format-LoRA/Structured Output

arXiv ID: 2606.09767

제출일: 2026-06-08T17:29:08+00:00

수정일: 2026-06-08T17:29:08+00:00

최근성: 최근 1일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.09767.pdf>

[초록 원문]

Neural machine translation for digitally low-resource Indigenous languages is often hindered by extreme data scarcity, prompting reliance on extractive web-scraping. To ensure data sovereignty, this study introduces a data synthesis methodology to bootstrap NMT models without scraping target-language parallel text. Focusing on Q'eqchi' Mayan, we transformed community-sourced dictionaries into a massive synthetic corpus, utilizing Parameter-Efficient Fine-Tuning (PEFT) via LoRA adapters on an mT5-base model. In-domain evaluation demonstrates high structural acquisition (BLEU 42.02), proving that synthetic constraints effectively teach complex agglutinative morphology and VOS word order. However, evaluation against an organic glossary reveals a structural-semantic gap (BLEU 0.59), where the model maintains grammatical integrity but lacks the lexical grounding of natural language. The model exhibits overfitting to the constrained structural variance of the synthetic templates; despite high semantic entropy in the pipeline, it struggles with the syntactic fluidity of natural language, forcing organic inputs into rigid learned patterns. Furthermore, an ablation study utilizing a Multi-Task Learning architecture resulted in negative transfer, suggesting that auxiliary tasks competed for limited parameter capacity within the LoRA adapters, causing over-optimization for synthetic markers at the expense of organic flexibility. Ultimately, we establish that synthetic bootstrapping is a highly effective structural primer, but requires authentic data for semantic refinement via Curriculum Learning.

[PDF 앞부분/서론 일부]

Data Synthesis and Parameter-Efficient Fine-Tuning for Low-Resource NMT: A Case Study on Q'eqchi' Mayan
Alexander Chulzhanov^{1,2}[0009000554818179], Soeren Eberhardt³[0009000576439743], and Arjun Mukherjee¹[000000028896604X]
1 University of Houston, Houston TX 77004, USA achulzha@cougarnet.uh.edu 2 MasterWord Services, Inc., Houston TX 77079, USA 3 University of Washington, Seattle WA 98195, USA
Abstract. Neural machine translation for digitally low-resource Indigenous languages is often hindered by extreme data scarcity, prompting reliance on extractive web-scraping. To ensure data sovereignty, this study introduces a data synthesis methodology to bootstrap NMT models without scraping target-language parallel text. Focusing on Q'eqchi' Mayan, we transformed community-sourced dictionaries into a massive synthetic corpus, utilizing Parameter-Efficient Fine-Tuning (PEFT) via LoRA adapters on an mT5-base model. In-domain evaluation demonstrates high structural acquisition (BLEU 42.02), proving that synthetic constraints effectively teach complex agglutinative morphology and VOS word order. However, evaluation against an organic glossary reveals a structural-semantic gap (BLEU 0.59), where the model maintains grammatical integrity but lacks the lexical grounding of natural language. The model exhibits overfitting to the constrained structural

variance of the synthetic templates; despite high semantic entropy in the pipeline, it struggles with the syntactic fluidity of natural language, forcing organic inputs into rigid learned patterns. Furthermore, an ablation study utilizing a Multi-Task Learning architecture resulted in negative transfer, suggesting that auxiliary tasks competed for limited parameter capacity within the LoRA adapters, causing over-optimization for synthetic markers at the expense of organic flexibility. Ultimately, we establish that synthetic bootstrapping is a highly effective structural primer, but requires authentic data for semantic refinement via Curriculum Learning. Keywords: Low-Resource Machine Translation · Synthetic Data Generation · Q'eqchi' Mayan · Parameter-Efficient Fine-Tuning · Multi-Task Learning

This version of the contribution has been accepted for publication, after peer review but is not the Version of Record and does not reflect postacceptance improvements, or any corrections. The Version of Record is available online at: [http://dx.doi.org/\[insert DOI\]](http://dx.doi.org/[insert DOI]). Use of this Accepted Version is subject to the publisher's Accepted Manuscript terms of use <https://www.springernature.com/gp/open-research/policies/accepted-manuscriptterms>

arXiv:2606.09767v1 [cs.CL] 8 Jun 2026 2 A. Chulzhanov et al. 1

Introduction

Neural Machine Translation (NMT) relies heavily on massive web-scraped datasets, creating a fundamental "cold start" problem for digitally low-resource Indigenous languages. Opportunistic web-scraping frequently violates data sovereignty and introduces severe domain skew, as public corpora are overwhelmingly dominated by archaic religious texts. Motivated by a strict "Zero Target-Language Scrape" policy, this research investigates how to ethically bootstrap a high-fidelity NMT system. While we leverage a foundational model pre-trained on high-resource languages, we ensure the Indigenous target data is sourced exclusively from contemporary community dictionaries without relying on web-scraped parallel text. While synthetic data generation is a common augmentation technique, its efficacy as the sole foundational training mechanism for morphologically rich languages remains under-explored. Standard open-source NMT baselines do not currently exist for Q'eqchi', and anecdotal evaluations of commercial translation systems by fluent speakers reveal severe degradation and archaic bias. Therefore, a primary objective of this study is to establish a reproducible, zero-scrape baseline. Specifically, it is unclear if rule-based templates can successfully teach a pre-trained transformer procedural syntax without the semantic grounding of human-translated corpora. In this paper, we evaluate the structural and semantic boundaries of synthetic bootstrapping. We developed a distribution-aware, template-based generation pipeline to transform static Q'eqchi' dictionaries into a large-scale synthetic corpus. We fine-tuned an mT5-base model using Parameter-Efficient Fine-Tuning (LoRA) and focal loss optimization to map Q'eqchi' syntax to the model's pre-trained English and Spanish latent spaces. Additionally, an ablation study using a Multi-Task Learning (MTL) architecture tested whether auxiliary part-of-speech tagging could anchor semantics during synthetic training. Our evaluation reveals a distinct dichotomy in model acquisition. The model successfully acquired complex agglutinative morphology and Verb-Object-Subject (VOS) word order, proving that synthetic constraints solve the syntactic cold start problem. However, evaluation against an out-of-domain organic glossary resulted in semantic collapse, where the model reverse-engineered templates but hallucinated vocabulary. Crucially, the MTL ablation study resulted in negative transfer, demonstrating that auxiliary tasks compete with primary translation objectives and cannot compensate for ungrounded training data. Ultimately, we demonstrate that data synthesis is highly effective for establishing a grammatical foundation, but requires organic data for lexical resolution. The main contributions of this work are: (1) A distribution-aware synthesis pipeline designed to

ethically bootstrap NMT without scraping target-language text. (2) Empirical proof that parameter-efficient fine-tuning on synthetic data successfully teaches procedural grammar and VOS word order. (3) An ablation study demonstrating that MTL architectures cause negative transfer in LoRA adapters under purely synthetic constraints. (4) A proposed Curriculum Learning framework utilizing synthetic data strictly as a structural primer prior to authentic semantic refinement.

[초록 번역]

초록 번역 실패: 모든 Gemini 모델 호출 실패:

```
{
  "error": {
    "code": 429,
    "message": "Your prepayment credits are depleted. Please go to AI Studio at https://ai.studio/projects to manage your project and billing. Learn more at https://ai.google.dev/gemini-api/docs/billing#prep ay. ",
    "status": "RESOURCE_EXHAUSTED"
  }
}
```

[논문 후보 3]

제목: Model Multiplicity for Adversarial Detection in Small Language Model Training on Edge Devices

저자: Stefan Behfar, Richard Mortier

카테고리: SLM/Edge/On-device

arXiv ID: 2606.07857

제출일: 2026-06-05T21:38:07+00:00

수정일: 2026-06-05T21:38:07+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.07857.pdf>

[초록 원문]

The rise of edge-based machine learning has enabled distributed adaptation of language models across mobile and IoT devices, offering privacy preservation and real-time responsiveness. However, distributed fine-tuning of language models on untrusted or heterogeneous edge nodes introduces new vulnerabilities. Compromised or unreliable devices can inject poisoned updates, leading to stealthy model manipulation or convergence degradation. Classical defenses such as robust aggregation or temporal anomaly detection operate on a single global model and are therefore limited in detecting coordinated or persistent poisoning. This work proposes a new system-level defense based on model multiplicity. Instead of maintaining one global model, the system rotates or concurrently trains multiple small language models (e.g., DistilGPT-2), each updated by independently sampled subsets of edge nodes. These models evolve under distinct training trajectories, creating multiple independent views of the same distributed population. Divergence between models quantified through gradient similarity, loss evolution, or parameter variance serves as a signal of anomalous or adversarial behavior. When one model deviates

significantly from the ensemble mean, the system flags its contributing nodes for isolation or re-weighting. We implement this framework and evaluate it on edge-scale simulations of Small Language Model (SLM) training under varying heterogeneity and attack conditions. Results show that model multiplicity enables earlier and more reliable detection of poisoning compared to classical single-model defenses such as Flanders and Robust methods. Our findings demonstrate that diversity in model evolution can serve as a practical and effective defense mechanism for secure distributed learning on resource-constrained edge devices.

[PDF 앞부분/서론 일부]

Model Multiplicity for Adversarial Detection in Small Language Model Training on Edge Devices Stefan Behfar Computer Lab, University of Cambridge Cambridge, United Kingdom skb67@cam.ac.uk Richard Mortier Computer Lab, University of Cambridge Cambridge, United Kingdom rmm1002@cam.ac.uk Abstract The rise of edge-based machine learning has enabled distributed adaptation of language models across mobile and IoT devices, offering privacy preservation and real-time responsiveness. However, distributed fine-tuning of language models on untrusted or heterogeneous edge nodes introduces new vulnerabilities. Compromised or unreliable devices can inject poisoned updates, leading to stealthy model manipulation or convergence degradation. Classical defenses such as robust aggregation or temporal anomaly detection operate on a single global model and are therefore limited in detecting coordinated or persistent poisoning. This work proposes a new system-level defense based on model multiplicity. Instead of maintaining one global model, the system rotates or concurrently trains multiple small language models (e.g., DistilGPT-2), each updated by independently sampled subsets of edge nodes. These models evolve under distinct training trajectories, creating multiple independent views of the same distributed population. Divergence between models quantified through gradient similarity, loss evolution, or parameter variance serves as a signal of anomalous or adversarial behavior. When one model deviates significantly from the ensemble mean, the system flags its contributing nodes for isolation or re-weighting. We implement this framework and evaluate it on edge-scale simulations of Small Language Model (SLM) training under varying heterogeneity and attack conditions. Results show that model multiplicity enables earlier and more reliable detection of poisoning compared to classical single-model defenses such as Flanders and Robust methods. Our findings demonstrate that diversity in model evolution can serve as a practical and effective defense mechanism for secure distributed learning on resource-constrained edge devices.

1 Introduction Machine learning at the edge is becoming increasingly important as modern applications demand real-time inference, privacy-preserving computation, and scalable deployment across heterogeneous networks of mobile and IoT devices. Rather than relying solely on centralized training, recent approaches explore training or fine-tuning models directly across distributed pools of devices, where each device contributes local computation and private data. However, training or fine-tuning in such environments introduces a key challenge: ensuring robustness and reliability in the presence of resource variability and potential adversarial behavior. Advances in compact and quantized model architectures such as DistilGPT-2 Li et al. (2021), TinyLLaMA Zhang et al. (2024), OPT-125M Zhang et al. (2022), and MobileBERT Sun et al. (2020) combined with parameter-efficient fine-tuning methods (LoRA adapters Hu et al. (2021)) have made it feasible to deploy and adapt language models directly on edge devices. Frameworks such as llama.cpp enable low-latency, on-device inference, opening new possibilities for personalized and privacy-preserving applications. At the same time, this shift exposes distributed training and Preprint. arXiv:2606.07857v1 [cs.CR] 5 Jun 2026 adaptation processes to

new vulnerabilities, since edge devices are often untrusted, intermittently connected, and constrained in compute and communication. Distributed training over heterogeneous and semi-trusted devices introduces susceptibility to malicious updates, poisoned data, and Sybil attacks. A small number of compromised nodes can inject poisoned gradients, backdoor triggers, or misleading updates that gradually shift the global model away from the intended objective. Such model poisoning attacks are especially dangerous when they unfold across multiple rounds, remaining stealthy by mimicking normal training statistics. Recent work, such as PoisonedFL Xie et al. (2025), demonstrates that even small, temporally consistent deviations can bypass classical robust aggregation mechanisms. Existing countermeasures largely fall into two families: (1) Robust aggregation methods (e.g., Krum Blanchard et al. (2017), Median Pillutla et al. (2022), Trimmed Mean Yin et al. (2018)) that suppress statistical outliers during aggregation, and (2) Pre-aggregation anomaly detectors such as Flanders Gabrielli et al. (2023), which analyze temporal sequences of updates to identify suspicious client behavior before aggregation. While aggregation-based defenses mitigate extreme outliers, they fail against coordinated or slow-drifting adversaries. Temporal detectors like Flanders improve detection by leveraging cross-round consistency, but they operate over a single global model offering only one view of the training process. This single-view design limits the ability to identify subpopulations of poisoned or biased nodes. We propose a different approach: leveraging model multiplicity as an intrinsic anomaly detection mechanism. Instead of maintaining a single global model, the system rotates or concurrently trains several SLM instances ($M_1, M_2, M_3, \dots$), each updated by independently sampled groups of edge nodes. These models evolve under slightly different client subsets, effectively creating multiple independent views of the global training population. By monitoring divergence between model trajectories measured via gradient similarity, loss evolution, or parameter variance, the system can identify adversarial influence or systematic bias. Significant divergence of one model from the ensemble mean acts as a red flag, prompting isolation or rollback of contributing nodes. This paper introduces a novel model-level ensemble anomaly detection framework for secure and robust distributed training of lightweight language models on heterogeneous edge devices. Unlike pri ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: 모든 Gemini 모델 호출 실패:

```
{
  "error": {
    "code": 429,
    "message": "Your prepayment credits are depleted. Please go to AI Studio at https://ai.studio/projects to manage your project and billing. Learn more at https://ai.google.dev/gemini-api/docs/billing#prep ay. ",
    "status": "RESOURCE_EXHAUSTED"
  }
}
```