

SLM / Edge Device arXiv Daily Summary

생성일: 2026-08-10 05:00 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 30일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 30일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: BALANCE: Hybrid Autoregressive-Speculative LLM Inference in Wireless Edge Networks

저자: Guanhao Qu, Shuo Chen, Qian Chen, Kin K. Leung, Xianhao Chen

카테고리: SLM/Edge/On-device

arXiv ID: 2608.05926

제출일: 2026-08-06T11:57:36+00:00

수정일: 2026-08-06T11:57:36+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2608.05926.pdf>

[초록 원문]

Edge inference is a promising paradigm to provide large language model (LLM) inference services in next-generation mobile networks. LLM inference mainly relies on two approaches: Autoregressive decoding (AD) generates output tokens sequentially, resulting in long latency; Speculative decoding (SD) accelerates inference by using a small language model (SLM) to generate multiple draft tokens for LLM verification, but incurs extra memory costs. Due to this latency-memory tradeoff, neither approach alone can efficiently serve users with heterogeneous demands under limited edge computing resources. To address this challenge, we propose a hybrid autoregressive-speculative inference (BALANCE) framework for edge LLM inference. In BALANCE, an edge server hosts both an SLM and an LLM, assigns each user to AD or SD, and performs the two modes simultaneously. To maximize the number of served users, we formulate a task throughput maximization problem to jointly determine user scheduling and computing resource allocation between AD and SD under user latency requirements and server memory constraints. Since the problem is NP-hard, we develop a polynomial-time algorithm that transforms the original problem into two sub-problems and obtains a sub-optimal solution with a constant approximation guarantee. Experiments demonstrate that BALANCE consistently outperforms conventional AD and SD and

significantly improves task throughput.

[PDF 앞부분/서론 일부]

1 BALANCE: Hybrid Autoregressive-Speculative LLM Inference in Wireless Edge Networks Guanyao Qu, Graduate Student Member, IEEE, Shuo Chen, Graduate Student Member, IEEE, Qian Chen, Member, IEEE, Kin K. Leung, Fellow, IEEE, Xianhao Chen, Member, IEEE Abstract-Edge inference is a promising paradigm to provide large language model (LLM) inference services in next-generation mobile networks. LLM inference mainly relies on two approaches: Autoregressive decoding (AD) generates output tokens sequentially, resulting in long latency; Speculative decoding (SD) accelerates inference by using a small language model (SLM) to generate multiple draft tokens for LLM verification, but incurs extra memory costs. Due to this latency-memory tradeoff, neither approach alone can efficiently serve users with heterogeneous demands under limited edge computing resources. To address this challenge, we propose a hybrid autoregressive-speculative inference (BALANCE) framework for edge LLM inference. In BALANCE, an edge server hosts both an SLM and an LLM, assigns each user to AD or SD, and performs the two modes simultaneously. To maximize the number of served users, we formulate a task throughput maximization problem to jointly determine user scheduling and computing resource allocation between AD and SD under user latency requirements and server memory constraints. Since the problem is NP-hard, we develop a polynomial-time algorithm that transforms the original problem into two sub-problems and obtains a sub-optimal solution with a constant approximation guarantee. Experiments demonstrate that BALANCE consistently outperforms conventional AD and SD and significantly improves task throughput. Index Terms-Large language models, edge inference, autoregressive decoding, speculative decoding, user scheduling, task throughput maximization. I. INTRODUCTION In next-generation mobile networks, large language model (LLM) inference at the network edge is emerging as an important paradigm for delivering LLM services to users [1]. In a typical edge LLM inference system, users upload their prompts to an edge server, which performs inference using the hosted LLM and returns the generated responses [2]. By placing LLMs on edge servers closer to end users, edge LLM inference can reduce transmission latency, compared with cloud-based serving [3], [4]. As such, edge LLM inference is becoming a key enabler for real-time LLM applications [5]. Autoregressive decoding (AD) and speculative decoding (SD) are two representative approaches in LLM inference. Guanyao Qu, Qian Chen, and Xianhao Chen are with the Department of Electrical and Computer Engineering, The University of Hong Kong, Hong Kong SAR, China (e-mail: gqu@eee.hku.hk; qchen@eee.hku.hk; xchen@eee.hku.hk). Shuo Chen is with the Electrical and Electronic Engineering Department, Imperial College, London SW7 2BT, U.K. (e-mail: shuo.chen22@imperial.ac.uk). Kin K. Leung is with the Electrical and Electronic Engineering, and Computing Departments, Imperial College, London SW7 2BT, U.K. (e-mail: kin.leung@imperial.ac.uk). The work was supported in part by the Research Grants Council of Hong Kong under Grant 27213824, Grant 17207826, and Grant CRS HKU702/24. Kin K. Leung is supported by the EPSRC grant EP/Y037243/1. (Corresponding author: Xianhao Chen.)

Output length (tokens)	AD End-to-end latency (s)	SD End-to-end latency (s)	AD Required GPU memory (GB)	SD Required GPU memory (GB)
200	0.398%	0.372%	18.6%	18.3%
600	1.000%	0.980%	18.0%	17.8%
1000	1.200%	1.160%	18.0%	17.8%

Fig. 1. Comparison between AD and SD when serving a single user using an NVIDIA GeForce RTX 4090 GPU, where the output length varies, and the input length is fixed at 500 tokens. In this experiment, the end-to-end latency denotes the time from feeding the prompt to the model to completing

output generation. Llama-2-7B is used as the LLM in both AD and SD, and TinyLlama-1.1B is used as the SLM in SD. In AD, an LLM generates the response token by token, producing one new token in each forward pass based on the input and previously generated tokens [6], [7]. However, the sequential decoding process of AD incurs high response latency [8]. This issue becomes more severe for tasks with long output responses and stringent latency requirements [8]. To reduce decoding latency, SD has been proposed [9]. In SD, a small language model (SLM) first generates multiple draft tokens via AD, and the target LLM verifies them in parallel within a single forward pass. By accepting multiple verified draft tokens at once, SD reduces the number of serial LLM forward passes. This reduction can significantly reduce response latency, since each forward pass of the SLM is typically faster than the target LLM [10]. Meanwhile, SD maintains output quality, since the verification preserves the target LLM's output distribution [11]. When applying SD to edge LLM inference, the SLM and LLM can be co-deployed on the edge server to serve users [12]. However, despite its latency advantage, SD introduces higher memory overhead due to the coexistence of the SLM and LLM as well as the memory for parallel draft verification [13]. Challenge. Neither AD nor SD alone can efficiently serve users with heterogeneous demands on resource-constrained edge servers. Serving users with AD alone is memory-efficient but may fail to satisfy stringent latency requirements, whereas relying solely on SD reduces latency but may exceed available memory resources [14], [15]. As illustrated in Fig. 1, when serving a single user, SD reduces the average end-to-end (E2E) latency by 39.1% compared with AD, but increases the GPU memory consumption by 18.3%. This latency-memory tradeoff raises a key challenge: how to efficiently serve users with heterogeneous demands by jointly exploiting AD and SD under arXiv:2608.05926v1 [cs.NI] 6 Aug 2026 2 constrained computing and memory resources on edge servers. Solution. To address the above ... [앞부분 텍스트 일부 생략]

[초록 번역]

엣지 추론은 차세대 모바일 네트워크에서 대규모 언어 모델(LLM) 추론 서비스를 제공하는 유망한 패러다임입니다. LLM 추론은 주로 두 가지 접근 방식에 의존합니다. 자기회귀 디코딩(AD)은 출력 토큰을 순차적으로 생성하여 긴 지연 시간을 초래하며, 추측 디코딩(SD)은 소형 언어 모델(SLM)을 사용하여 LLM 검증을 위한 여러 초안 토큰을 생성함으로써 추론 속도를 높이지만 추가 메모리 비용이 발생합니다. 이러한 지연 시간-메모리 상충 관계 때문에, 제한된 엣지 컴퓨팅 자원 하에서 이질적인 요구를 가진 사용자들에게 어떤 접근 방식도 단독으로는 효율적으로 서비스를 제공할 수 없습니다.

이러한 문제를 해결하기 위해, 우리는 엣지 LLM 추론을 위한 하이브리드 자기회귀-추측 추론 (BALANCE) 프레임워크를 제안합니다. BALANCE에서 엣지 서버는 SLM과 LLM을 모두 호스팅하고, 각 사용자를 AD 또는 SD에 할당하며, 두 모드를 동시에 수행합니다. 서비스되는 사용자 수를 최대화하기 위해, 우리는 사용자 지연 시간 요구 사항과 서버 메모리 제약 조건 하에서 AD와 SD 간의 사용자 스케줄링 및 컴퓨팅 자원 할당을 공동으로 결정하는 태스크 처리량 최대화 문제를 정식화합니다. 이 문제는 NP-난해하기 때문에, 우리는 원래 문제를 두 개의 하위 문제로 변환하고 상수 근사 보장을 통해 준최적 해를 얻는 다항 시간 알고리즘을 개발합니다. 실험 결과는 BALANCE가 기존 AD 및 SD를 일관되게 능가하며 태스크 처리량을 크게 향상시킨다는 것을 보여줍니다.

[논문 후보 2]

제목: EdgeXpert: An Edge Device for Memory-Efficient LLM Inference with Mixture-of-Experts and Speculative Decoding

저자: Sangwoo Ha, Hyunwoo Seo, Yurim Jo, Youngjin Moon, Hoi-Jun Yoo

카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency

arXiv ID: 2608.05303

제출일: 2026-08-05T18:03:47+00:00

수정일: 2026-08-05T18:03:47+00:00

최근성: 최근 4일 이내

arXiv PDF: <https://arxiv.org/pdf/2608.05303.pdf>

[초록 원문]

On-device deployment of Large Language Models (LLMs) has become essential for personalized edge applications. A primary bottleneck is external memory access (EMA) in feed-forward network (FFN) layers. Speculative decoding and mixture-of-experts (MoE) are promising solutions. Speculative decoding reduces the number of decoding stages by generating multiple tokens per stage, and MoE minimizes per-stage cost through sparse expert activation. However, there is an incompatibility when combining these two techniques. We propose EdgeXpert, a software-hardware co-designed LLM accelerator that resolves this incompatibility. In the prefill stage, the prompt-wise expert reuse reformulates routing as prompt-level expert reuse rather than independent per-token expert selection. It identifies important tokens using a lightweight encoder, constructs a shared expert set from them, and routes less important tokens with a reduced expert budget to lower expert EMA. In the decode stage, depth-aware expert coalescing exploits the contextual similarity and mutual exclusivity of same-depth candidate tokens. Rather than loading the union of all required channels, EdgeXpert loads only salient channels and applies computational calibration to recover accuracy without additional memory access. Synthesized in Samsung 28nm technology at 800 MHz, EdgeXpert achieves up to 56.3% latency reduction and 44.1% energy reduction compared to prior works, while maintaining near-baseline accuracy.

[PDF 앞부분/서론 일부]

EdgeXpert: An Edge Device for Memory-Efficient LLM Inference with Mixture-of-Experts and Speculative Decoding
Sangwoo Ha KAIST Daejeon, South Korea sangwoo_ha@kaist.ac.kr Hyunwoo Seo KAIST Daejeon, South Korea shw4166@kaist.ac.kr Yurim Jo KAIST Daejeon, South Korea yurim.jo@kaist.ac.kr Youngjin Moon KAIST Daejeon, South Korea yj.moon@kaist.ac.kr Hoi-Jun Yoo KAIST Daejeon, South Korea hjyoo@kaist.ac.kr Abstract-On-device deployment of Large Language Models (LLMs) has become essential for personalized edge applications. A primary bottleneck is external memory access (EMA) in feed-forward network (FFN) layers. Speculative decoding and mixture-of-experts (MoE) are promising solutions. Speculative decoding reduces the number of decoding stages by generating multiple tokens per stage, and MoE minimizes per-stage cost through sparse expert activation. However, there is an incompatibility when combining these two techniques. We propose EdgeXpert, a software-hardware co-designed LLM accelerator that resolves this incompatibility. In the prefill stage, the prompt-wise expert reuse reformulates routing as prompt-level expert reuse rather than independent per-token expert selection. It identifies important tokens using a lightweight encoder, constructs a shared expert set from them, and routes less important tokens with a reduced expert budget to lower expert EMA. In the decode stage, depth-aware expert coalescing exploits the contextual similarity and mutual exclusivity of same-depth candidate tokens. Rather than loading the union of all required channels, EdgeXpert loads only salient channels and applies

computational calibration to recover accuracy without additional memory access. Synthesized in Samsung 28nm technology at 800 MHz, EdgeXpert achieves up to 56.3% latency reduction and 44.1% energy reduction compared to prior works [1]-[3], while maintaining near-baseline accuracy. Index Terms-Edge device, large language model, mixture-of-experts, speculative decoding

INTRODUCTION

Large language models (LLMs) [4]-[6] are being adopted across a wide range of applications, and there is growing interest in deploying them directly on edge devices for personalized, low-latency experiences. However, on-device inference is constrained by memory bandwidth and capacity. Edge LLMs typically operate in single-batch, autoregressive inference, which requires all model parameters to be loaded from external memory for each output token. This characteristic incurs substantial external memory access (EMA) latency and energy, becoming a primary cause of system bottlenecks. As shown in Figure 1, the EMA of the weight parameters constitutes the largest overhead. Specifically, the weight EMA in the feed-forward network (FFN) layers is the most dominant factor, and this overhead grows linearly with the number of decoding stages. While recent works have Fig. 1. Overall LLM system breakdown in edge devices. focused on mitigating KV cache overhead in long-context scenarios [7], [8], on-device contexts are typically short (tens to a thousand tokens) [9], [10], making KV cache a less significant bottleneck. Consequently, weight EMA emerges as the primary overhead for on-device LLM. For a conventional autoregressive decoding LLM, the weight EMA per token is defined by the total number of weight parameters (P_{total}) that must be accessed from external memory per output token, as expressed in Equation (1). Previous works [9], [11], [12] have focused on reducing P_{total} by employing various model compression techniques, such as quantization, pruning, and tensor decomposition. EM AW, Conventional = P_{total} (1) The substantial computation overhead associated with FFN layers has driven the exploration of more efficient models. The mixture-of-experts (MoE) models [13]-[18] have emerged as a promising approach to mitigate this challenge. In MoE-based transformers, a single large FFN layer is replaced by an MoE layer, which consists of multiple smaller expert networks. During inference, instead of executing the entire set of parameters for an FFN layer, a router selects only a few relevant experts for each input token. This selective activation reduces the computation cost while achieving superior model performance. Applying MoE to edge devices [2] directly translates to a reduction in EMA cost while reducing the arXiv:2608.05303v1 [cs.AR] 5 Aug 2026 overall computation. The weight EMA per token in the MoE model is substantially reduced compared to the conventional LLM, as shown in Equation (2). S represents the number of deactivated experts and P_{expert} denotes the weight parameters of a single expert. As demonstrated by EdgeMoE [2] and SMoLPU [3], MoE models are well-suited for edge devices because they substantially reduce the inference cost of FFN layers. EM AW, MoE = $P_{total} \times S \times P_{expert}$ (2) Recent LLMs adopt speculative decoding (SD) [19]-[26] to reduce the repeated loading of model parameters. This is typically achieved by employing a smaller, low-cost draft model to generate multiple candidate tokens, which are then verified in a single pass by the larger target LLM model. The target model accepts only the verified tokens, which are denoted by accepted tokens. Such approaches accelerate decoding stages by producing multiple tokens for each stage. The application of speculative decoding is particularly beneficial for edge LLM devices [3], [27], [28]. Speculative decoding can significantly lower the EMA cost by reducing the frequent loading of large target model parameters. The weight EMA per token with speculative decoding is shown in Equation (3). N_A represents the average number of accepted tokens per stage (acceptance length). EAGLE-3 [25] generates an average of five tokens per stage on the DeepSeek-R1 8B model [29], thereby reducing the model

parameter load by approximately five times. Therefore, integrating speculative decoding with MoE models presents a compelling strategy for edge LLMs. This combination offers a twofold advan ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '" for academic tone).Wn * "추측 디코딩은 단계당 여러 토큰을 생성하여 디코딩 단계 수를 줄이고, MoE는 희소 전문가 활성화를 통해 단계별 비용을 최소화한다." -> "추측 디코딩은 단계당 여러 토큰을 생성함으로써 디코딩 단계 수를 줄이며, MoE는 희소 전문가 활성화'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 358, 'candidatesTokenCount': 82, 'totalTokenCount': 2402, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 358}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'S9x4apDrCe-tz7IP56XJqAw'}

[논문 후보 3]

제목: GROM: Gradient-Free Rapid One-Shot Machine Unlearning

저자: Paweł Batorski, Przemysław Spurek, Paul Swoboda

카테고리: Deployment/Quantization/Efficiency

arXiv ID: 2608.05783

제출일: 2026-08-06T09:16:53+00:00

수정일: 2026-08-06T09:16:53+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2608.05783.pdf>

[초록 원문]

Machine unlearning has become a critical capability for safely removing specific, sensitive knowledge from large language models (LLMs). Current state-of-the-art approaches primarily rely on iterative, training-time unlearning via fine-tuning. However, even when utilizing parameter-efficient dimensionality reduction techniques like LoRA, gradient-based optimization remains computationally expensive and lacks explicit analytical formulations. It can also leave the targeted knowledge merely hidden rather than removed, to the point that simply quantizing the unlearned model restores much of what it was supposed to have erased. To resolve this, we propose a novel one-shot unlearning approach, abandoning iterative optimization in favor of a direct, exact analytical solution. We frame the unlearning process as a ridge-regularized least-squares optimization problem, deriving a closed-form additive update for targeted weight matrices. This update forces the selected layer to suppress unwanted content while strictly preserving its behavior on retained data. Computed from gradient-free forward passes alone, with no backpropagation and no iteration to convergence, GROM applies the weight edit in mere seconds, which makes it orders of magnitude faster than traditional fine-tuning. Extensive evaluations demonstrate that GROM achieves state-of-the-art forgetting-utility trade-offs on TOFU-5%, TOFU-10%, MUSE-Books, MUSE-News and WMDP, significantly reducing computational overhead without sacrificing overall model performance. Because the update removes the targeted content from the weights instead of masking it, GROM also withstands the low-bit quantization attack that recovers much of the content a gradient-based baseline had appeared to forget. Our code is publicly available at <https://github.com/Batorskq/GROM>.

[PDF 앞부분/서론 일부]

GROM: Gradient-Free Rapid One-Shot Machine Unlearning Paweł Batorski¹, Przemysław Spurek^{2,3}, Paul Swoboda¹ ¹Heinrich Heine University Düsseldorf ²Jagiellonian University ³IDEAS Research Institute 0.52 0.56 0.60

Model	utility (MU) ↓	0.5	0.6	0.7	0.8	0.9	Forgetting quality ↓	IDKDPO	UNDIAL	SimNPO	AltPO	IDKNLL	NPO	RMU		
GradDiff	GROM (ours)	TOFU-5%	TOFU-10%	WMDP	MUSE News	MUSE Books	101	100	101	102	Update time (min, log)	#	GROM (ours)	SimNPO		
		1.8	0.5	0.2	0.3	0.3	2.6	2.5	21.6	36.3	53.8	1.4£	5.0£	108£	121£	179£

Figure 1: GROM is fast and Pareto-best. Left, top: on TOFU-10%, GROM (red star) reaches the top-right corner, strong forgetting and the highest model utility. Left, bottom: it is closed-form edit and applies in seconds, up to ~180× faster than SimNPO, a gap that widens on the larger 7-8B corpus benchmarks (single NVIDIA H100). Right: GROM replaces iterative fine-tuning with a single gradient-free closed-form edit W+P to one target layer, erasing the targeted knowledge in one step. Abstract Machine unlearning has become a critical capability for safely removing specific, sensitive knowledge from large language models (LLMs). Current state-of-the-art approaches primarily rely on iterative, training-time unlearning via fine-tuning. However, even when utilizing parameter-efficient dimensionality reduction techniques like LoRA, gradient-based optimization remains computationally expensive and lacks explicit analytical formulations. It can also leave the targeted knowledge merely hidden rather than removed, to the point that simply quantizing the unlearned model restores much of what it was supposed to have erased. To resolve this, we propose a novel one-shot unlearning approach, abandoning iterative optimization in favor of a direct, exact analytical solution. We frame the unlearning process as a ridge-regularized least squares optimization problem, deriving a closed-form additive update for targeted weight matrices. This update forces the selected layer to suppress unwanted content while strictly preserving its behavior on retained data. Computed from gradient-free forward passes alone, with no backpropagation and no iteration to convergence, GROM applies the weighted edit in mere seconds, which makes it orders of magnitude faster than traditional fine-tuning. Extensive evaluations demonstrate that GROM achieves state-of-the-art forgetting-utility trade-offs on TOFU-5%, TOFU-10%, MUSE-Books, MUSE News and WMDP, significantly reducing computational overhead without sacrificing overall model performance. Because the update removes the targeted content from the weights instead of masking it, GROM also withstands the low-bit quantization attack that recovers much of the content a gradient-based baseline had appeared to forget. Our code is publicly available at <https://github.com/Batorskq/GROM>.

Introduction Large Language Models (LLMs) frequently memorize sensitive, private, or copyrighted information from their vast training corpora. Consequently, machine unlearning has emerged as a crucial mechanism to selectively erase this targeted knowledge. Existing interventions span a continuum from inference-time mitigation to parameter editing and training-time updates (Liu et al. 2025; Ren et al. 2025). Mitigation strategies, such as decoding controls or prompt-based defenses (Yu et al. 2021; Huang et al. 2024; Thaker et al. 2024a), act as lightweight shields that deflect rather than physically remove the underlying information. Conversely, localized parameter editing methods (Ilharco et al. 2022; Meng et al. 2022) offer rapid updates for specific associations but often struggle to scale effectively to broad, distributional forget sets. Currently, training-time unlearning provides the strongest performance by optimizing model parameters to reduce the likelihood of the forget set while preserving retain-set utility. This encompasses a wide range of objectives,

including gradient ascent (Thudi et al. 2022; Yao, Xu, and Liu 2024a), reverse KL divergence (Wang et al. 2024), and preference-style optimization (Rafailov et al. 2023; Zhang et al. 2024b; Fan et al. 2025). While effective, these methods inherently rely on iterative fine-tuning. Even when utilizing parameter-efficient dimensionality reduction techniques like LoRA, gradient-based optimization remains computationally expensive. More troubling, the forgetting it produces can be superficial: recent work shows that simply quantizing an unlearned model restores much of the content it was supposed to have removed (Zhang et al. 2025), which suggests that fine-tuning often hides the targeted knowledge in low-magnitude weight adjustments that low-bit rounding undo. Crucially, these approaches also lack an explicit analytical formulation, forcing practitioners to rely on costly, step-by-step gradient descent to approximate an unlearned state. To address these fundamental inefficiencies, we introduce GROM (Gradient-free Rapid One-shot Machine unlearning), a new unlearning formulation that abandons iterative optimization in favor of a direct, exact analytical solution. Instead of training additional parameters over multiple epochs, GROM computes a precise, additive update to targeted weight matrices in a single step. We frame the unlearning process as a ridge-regularized least-squares optimization problem, forcing a selected layer to suppress unwanted content while strictly maintaining its output on retained data. By solving this system in closed form, GROM computes the optimal weight update from gradient-free forward passes over the forget and retain data, one pair per edited layer, executing the entire unlearning procedure in mere seconds. The main contributions of this work are threefold:

- Closed-Form Unlearning Formulation: We mathematically frame machine unlearning as an exact optimization problem with a closed-form analytical solution, completely bypassing the computational overhead and optimization instability of iterative fine-tuning.
- Gradient-Free Efficiency: GROM computes each layer's optimal additive update from gradient-free forward passes alone, with no backpropagation and no iteration to convergence, which makes it up to two orders of magnitude faster.

[앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '기계 언러닝은 대규모 언어 모델(LLM)에서 특정 민감한 지식을 안전하게 제거하는 데 필수적인 기능이 되었습니다. 현재 최첨단 접근 방식은 주로 미세 조정을 통한 반복적, 학습 시 언러닝에 의존합니다. 그러나 LoRA와 같은 파라미터 효율적인 차원 축소 기술을 활용하더라도, 기울기 기반 최적화는 계산 비용'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 414, 'candidatesTokenCount': 90, 'totalTokenCount': 2458, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 414}], 'thoughtsTokenCount': 1954, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'VNx4asfcEfiHz7IPptaR6Qg'}