

SLM / Edge Device arXiv Daily Summary

생성일: 2026-06-09 06:35 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 7일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 7일

오류 메시지: 모든 Gemini 모델 호출 실패:

```
{
  "error": {
    "code": 429,
    "message": "Your prepayment credits are depleted. Please go to AI Studio at https://ai.studio/projects to manage your project and billing. Learn more at https://ai.google.dev/gemini-api/docs/billing#prep ay. ",
    "status": "RESOURCE_EXHAUSTED"
  }
}
```

[논문 후보 1]

제목: The Fine-Tuning Trap: Evaluating Negative Transfer and the Role of PEFT in Sub-1B Mathematical Reasoning

저자: Rahul Nair, Chun Tao

카테고리: SLM/Edge/On-device

arXiv ID: 2606.06920

제출일: 2026-06-05T05:34:13+00:00

수정일: 2026-06-05T05:34:13+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.06920.pdf>

[초록 원문]

Deploying Small Language Models (SLMs) on edge devices requires efficient fine-tuning strategies that adapt models to new tasks without degrading their general capabilities. In this study, we benchmark five sub-1B models (135M-1B) on mathematical reasoning tasks and uncover a critical vulnerability: Full Fine-Tuning (Full FT) actively harms performance in models under 300M parameters, often dropping accuracy below zero-shot baselines. This "negative transfer" makes Parameter-Efficient Fine-Tuning (PEFT) not just an efficiency preference, but a stability

requirement. We find that while Low-Rank Adaptation (LoRA) and Weight-Decomposed LoRA (DoRA) perform comparably, their strengths vary by task; DoRA excels in complex reasoning (GSM8K), while LoRA dominates pattern matching (OrcaMath). In particular, Full FT is outperformed by LoRA on aligned models (Qwen2.5-0.5B) and even by simple 5-shot In-Context Learning on the smallest architectures (SmolLM2-135M). Based on these findings, we recommend defaulting to PEFT for all aligned sub-1B models and caution against Full FT for any architecture smaller than 500M parameters to prevent catastrophic forgetting. Reproduction of this work can be found at <https://github.com/gulguloo/tiny-slm-finetune-comp> are.

[PDF 앞부분/서론 일부]

The Fine-Tuning Trap: Evaluating Negative Transfer and the Role of PEFT in Sub-1B Mathematical Reasoning Rahul Nair Chun Tao rahulunair@gmail.com taochun1008@yahoo.com (a) The Stability Cliff (b) Intruder Dimensions (c) Deep & Thin Architecture Figure 1: Multidimensional Analysis of Stability. (a) Empirical results show Full FT performance collapses below 200M parameters, while PEFT remains stable. (b) Conceptualizing how Full FT explores orthogonal "Intruder" subspaces (Δ) that lead to high-loss regions, whereas PEFT is constrained to the pre-trained manifold. (c) Modern SLMs utilize deep, narrow stacks which exacerbate gradient vanishing/explosion during full parameter updates compared to traditional wide architectures. Abstract Deploying Small Language Models (SLMs) on edge devices requires efficient fine-tuning strategies that adapt models to new tasks without degrading their general capabilities. In this study, we benchmark five sub-1B models (135M-1B) on mathematical reasoning tasks and uncover a critical vulnerability: Full Fine-Tuning (Full FT) actively harms performance in models under 300M parameters, often dropping accuracy below zero-shot baselines. This "negative transfer" makes Parameter-Efficient Fine-Tuning (PEFT) not just an efficiency preference, but a stability requirement. We find that while Low-Rank Adaptation (LoRA) and Weight-Decomposed LoRA (DoRA) perform comparably, their strengths vary by task; DoRA excels in complex reasoning (GSM8K), while LoRA dominates pattern matching (OrcaMath). In particular, Full FT is outperformed by LoRA on aligned models (Qwen2.5-0.5B) and even by simple 5-shot In-Context Learning on the smallest architectures (SmolLM2-135M). Based on these findings, we recommend defaulting to PEFT for all aligned sub-1B models and caution against Full FT for any architecture smaller than 500M parameters to prevent catastrophic forgetting. Reproduction of this work can be found at <https://github.com/gulguloo/tiny-slm-finetune-comp> are. CCS Concepts • Computing methodologies → Natural language generation; Supervised learning by regression; Cost-sensitive learning. Both authors contributed equally to this research. Keywords Small Language Models (SLMs), Parameter-Efficient Fine-Tuning (PEFT), LoRA, DoRA, Mathematical Reasoning, Catastrophic Forgetting, In-Context Learning 1 Introduction Natural Language Processing (NLP) is shifting focus from cloudcentric scaling to edge-centric optimization. While "Scaling Laws" [5] have long dictated that larger models yield better performance, the industry is increasingly investing in "Small Language Models" (SLMs) designed for on-device deployment [9, 13]. These models, typically under 1 billion parameters, are essential for privacy-preserving, low-latency applications on devices like smartphones and IoT endpoints. As illustrated in Figure 2, the cost-performance landscape is non-linear. While standard scaling laws predict a smooth curve, we observe "outlier" behaviors in modern SLMs like Qwen2.5-0.5B, which achieve parity with significantly larger models (e.g., OLMo1B) at a fraction of the training compute. However, capitalizing on this potential requires navigating a treacherous optimization landscape. Despite mature pre-training techniques for SLMs-such as

token-rich training and knowledge distillation-the best methods for adapting them to downstream tasks remain unclear. For Large Language Models (LLMs), Full Fine-Tuning (Full FT) is generally arXiv:2606.06920v1 [cs.LG] 5 Jun 2026 Nair et al. Figure 2: Pareto Frontier of Cost vs. Accuracy. Sub-1B SLMs (Blue Dots) offer a low-cost entry point but suffer from high variance in accuracy. The high outlier (Qwen2.5-0.5B) demonstrates that excellent architecture and alignment can push tiny models closer to the performance of >1B LMs (Red Stars) at a fraction of the cost, the gold standard given sufficient compute. However, our research suggests this assumption fails in the sub-1B regime.

1.1 The Challenge of Capacity Saturation SLMs operate near "capacity saturation." Unlike LLMs, which have redundant parameters to absorb new task-specific circuits, SLMs are densely packed with essential pre-trained knowledge. This makes them highly susceptible to negative transfer, where fine-tuning gradients interfere with the model's core linguistic and reasoning capabilities [1].

1.2 The Phenomenon of Negative Transfer We define negative transfer here as the degradation of a model's performance on a target task or general benchmarks after finetuning, often falling below the zero-shot baseline. While pre-trained representations are generally robust, models with low intrinsic dimensionality often have non-convex optimization landscapes filled with sharp minima [10]. When Full FT is applied to a sub-300M parameter model, unconstrained gradient updates (Δ) can push weights significantly off the pre-trained manifold. This causes "catastrophic forgetting," erasing the fragile "world knowledge" needed for basic coherence [6].

1.3 Convergence under Resource Constraints The push for sub-1B models is driven by the goal of accessible AI. While training a 70B model requires a cluster, a 300M model can theoretically run on consumer hardware or mobile NPUs. However, strict constraints on convergence speed and memory bandwidth apply. If Full FT requires extensive hyperparameter tuning to avoid divergence, it undermines the efficiency of using a small model. Therefore, finding an adaptation method that is both performant and stable by default is critical. This paper investigates whether Parameter-Efficient Fine-Tuning (PEFT) methods-specifically LowRank Adaptation (LoRA) [4] and Weight-Decomposed LoRA (DoRA) [7]-can act as regularizers to prevent reasoning collapse in tiny architectures.

1.4 Contributions This paper addresses the "Stability-Capacity Trade-off" in tiny models through a systematic empirical study. Our primary contributions are: (1) The Phase Transition: We identify a stability thresh ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: 모든 Gemini 모델 호출 실패:

```
{
  "error": {
    "code": 429,
    "message": "Your prepayment credits are depleted. Please go to AI Studio at https://ai.studio/projects to manage your project and billing. Learn more at https://ai.google.dev/gemini-api/docs/billing#prep ay. ",
    "status": "RESOURCE_EXHAUSTED"
  }
}
```

[논문 후보 2]

제목: How Far Can Chord-Symbol Time-Series Adaptation Carry Genre Identity? Capabilities and Boundaries in

Multi-Genre Chord-Symbol Modeling

저자: Jinju Lee

카테고리: Format-LoRA/Structured Output

arXiv ID: 2606.07334

제출일: 2026-06-05T14:49:24+00:00

수정일: 2026-06-05T14:49:24+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.07334.pdf>

[초록 원문]

Harmony is a compact symbolic layer where mathematical pitch relations, acoustic consonance, and musical convention meet. This report treats chord-symbol sequences not as a complete representation of music, but as an interpretable, controllable time series for genre-local harmonic modeling. Starting from a frozen pop-jazz Music Transformer checkpoint, I evaluate how far small adaptation interfaces can extend the model to eleven target genres: blues, bossa nova, Bach chorales, country, electronic, folk, funk, gospel, hip-hop, R&B/soul, and rock. The main evaluation compares LoRA, IA3, BitFit, prefix tuning, and full fine-tuning over 11 genres and 3 seeds, a complete 165-cell grid. All five methods improve over the frozen base on held-out chord prediction, with macro gains from +2.89 to +3.61 points; LoRA and IA3 score highest, but Wilcoxon tests with Holm and Benjamini-Hochberg correction do not support a decisive winner. A matched-data-size control sharpens this: when genres are sub-sampled to a common corpus size, IA3 stays on top but LoRA's full-data edge disappears and it falls to last, indicating the small gaps are partly data-driven. A control-token baseline is also strong, and wrong-genre adapters often beat the frozen base, suggesting much of the effect comes from lightweight conditioning over a reusable harmonic base rather than one particular adapter family. Additional diagnostics (rank sweeps, wrong-genre rotation, a base-checkpoint ablation, chord-only genre classification, generated-output statistics, real-song evaluation, and duplicate analysis) support a bounded conclusion: chord-symbol adaptation reliably improves genre-local harmonic prediction, but chord symbols alone do not carry complete genre identity. The report therefore avoids claims about perceived genre authenticity or full musical quality, which require controlled listener or musician evaluation.

[PDF 앞부분/서론 일부]

How Far Can Chord-Symbol Time-Series Adaptation Carry Genre Identity? Capabilities and Boundaries in Multi-Genre Chord-Symbol Modeling Jinju Lee - PearlLeeStudio June 2026 Abstract Harmony is a compact symbolic layer where mathematical pitch relations, acoustic consonance, and musical convention meet. This report studies that layer directly: chord-symbol sequences are treated not as a complete representation of music, but as an interpretable and controllable time series for genre-local harmonic modeling. Starting from a frozen pop-jazz Music Transformer checkpoint, I evaluate how far small adaptation interfaces can extend the model to eleven target genres: blues, bossa nova, Bach chorales, country, electronic, folk, funk, gospel, hip-hop, R&B/soul, and rock. The main evaluation compares five adaptation methods, LoRA, IA3, BitFit, prefix tuning, and full fine-tuning, over 11 genres and 3 seeds, yielding a complete 165-cell grid. All five methods improve over the frozen base on held-out

chord prediction, with macro gains from +2.89 to +3.61 percentage points; LoRA and IA3 have the highest macro top-1 scores, but pairwise Wilcoxon tests with Holm and Benjamini-Hochberg correction do not support a decisive method winner. A matched-data-size control sharpens this: when all genres are sub-sampled to a common corpus size, IA3 remains on top but LoRA's full-data edge disappears and it falls to last, indicating the small method gaps are partly data-driven rather than representational. A control-token baseline is also strong, and wrong-genre adapters often beat the frozen base, suggesting that much of the adaptation effect is exposed through lightweight conditioning over a reusable harmonic base rather than through one particular adapter family or purely genre-specific adapter memory. Additional diagnostics, including rank sweeps, wrong-genre adapter rotation, a matched-data-size control, a base-checkpoint ablation, chord-only genre classification, generated-output distribution statistics, real-song chord-chart evaluation, and duplicate/near-duplicate analysis, support a bounded conclusion: chord-symbol adaptation reliably improves genre-local harmonic prediction, but chord symbols alone do not carry complete genre identity. The report therefore avoids claims about perceived genre authenticity or full musical quality; those require controlled listener or musician evaluation.

1. Introduction

This project began as an engineering problem. I was building an interactive chord-composition system in which a user could edit a harmonic skeleton, ask a model for continuations, and keep the result under direct musical control. The system needed a practical capability: a frozen chord model should be extensible to new genres without training and serving a full separate model for every genre. That engineering need became the empirical question of this report: How much genre identity can chord-symbol time series carry, and where does that representation reach its boundary? The question is narrower than full music generation. A genre is not only a sequence of chords. It also includes rhythm, timbre, instrumentation, voicing, production, performance practice, lyrical convention, and listening context. Still, harmony is a meaningful intermediate layer. In Western and jazz-adjacent traditions, chord symbols encode root motion, functional patterns, modal mixture, cadential habits, extensions, and repetition.

1 arXiv:2606.07334v1 [cs.SD] 5 Jun 2026

These structures connect mathematical pitch relations, acoustic consonance and dissonance, and the practical vocabulary musicians use to compose and communicate. This is why the work focuses on chord-symbol generation rather than melody, lyrics, raw audio, or full arrangement. The choice is not a legal claim that chord symbols eliminate copyright or licensing concerns. They do not. Instead, this work studies a compact symbolic representation of harmonic structure, using research-permitting chord-chart corpora, and avoids modeling melody, lyrics, recordings, or performer-specific audio. The representation is deliberately limited. That limitation is the point: if chord symbols are used as a controllable layer for music AI, we need to know both what they can support and what they cannot. The prior arXiv report in this project studied a pop-to-jazz rehearsal-mix problem: how much pop data should be retained while fine-tuning a pop chord model toward jazz (arXiv:2605.04998). The current report changes the question. It freezes a pop-jazz base checkpoint and asks whether multiple adaptation methods can specialize it to eleven target genres. This is not a PEFT comparison that was later given a musical interpretation. The PEFT comparison follows from a composition-tool problem: how to make genre-specific chord continuation controllable while keeping one reusable base model. LoRA was the first practical choice because it supports modular genre adapters, but the study is not a "LoRA for music" paper. LoRA, IA3, BitFit, prefix tuning, full fine-tuning, and a control-token baseline are used as probes of the genre information available in chord-symbol sequences. The central result is balanced. Adaptation works: every main method improves over the frozen base on

the held-out target-genre chord prediction task. But no method is statistically dominant after correction, and several diagnostics show that chord-symbol genre information is real but incomplete. This makes the contribution a representation-boundary study rather than a method leaderboard. The report makes four contributions: 1. A complete 5-method x 11-genre x 3-seed evaluation of chord-symbol genre adaptation over a frozen pop-jazz base. 2. A control-token and wrong-genre diagnostic package that tests whether gains are method-specific, genrespecific, or generic adaptation effects, yielding two reusable observations: control-token conditioning is close to adapter performance, and many wrong-genre adapters still improve over the fro ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: 모든 Gemini 모델 호출 실패:

```
{
  "error": {
    "code": 429,
    "message": "Your prepayment credits are depleted. Please go to AI Studio at https://ai.studio/projects to manage your project and billing. Learn more at https://ai.google.dev/gemini-api/docs/billing#prep ay. ",
    "status": "RESOURCE_EXHAUSTED"
  }
}
```

[논문 후보 3]

제목: Robotic Policy Adaptation via Weight-Space Meta-Learning
저자: Christian Bianchi, Siamak Yousefi, Alessio Sampieri, Andrea Roberti, Luca Rigazio, Fabio Galasso, Luca Franco
카테고리: Format-LoRA/Structured Output
arXiv ID: 2606.07217
제출일: 2026-06-05T12:29:28+00:00
수정일: 2026-06-05T12:29:28+00:00
최근성: 최근 3일 이내
arXiv PDF: https://arxiv.org/pdf/2606.07217.pdf

[초록 원문]

Vision-Language-Action (VLA) models are emerging as a promising paradigm for robotic manipulation, enabling general-purpose policies trained from large corpora of demonstrations and action labels. However, adapting these models to new tasks still typically requires task-specific demonstrations, action annotations, and additional fine-tuning, making deployment costly and difficult to scale. We propose WIZARD, a weight-space meta-learning framework that sidesteps task-specific fine-tuning by generating task-specific LoRA parameters for a frozen VLA policy. Given only a language instruction and a short demonstration video, WIZARD predicts the corresponding adaptation weights in a single forward pass, without target-task action labels or test-time optimization. During meta-training, WIZARD learns to map task evidence directly to expert LoRA updates, capturing relationships between tasks in weight space. Experiments on LIBERO show that WIZARD improves performance by up to ~2x

on unseen dataset collections and up to $\sim 14\times$ on unseen tasks. On a Franka Emika Panda, WIZARD consistently improves over a real-domain adapted baseline, showing that generated adapters provide task-level specialization beyond simulation.

[PDF 앞부분/서론 일부]

Robotic Policy Adaptation via Weight-Space Meta-Learning Christian Bianchi[†] ItAI Siamak Yousefi ItAI Alessio Sampieri ItAI Andrea Roberti University of Verona Luca Rigazio ItAI Fabio Galasso ItAI and Sapeinza University of Rome Luca Franco ItAI Abstract: Vision-Language-Action (VLA) models are emerging as a promising paradigm for robotic manipulation, enabling general-purpose policies trained from large corpora of demonstrations and action labels. However, adapting these models to new tasks still typically requires task-specific demonstrations, action annotations, and additional fine-tuning, making deployment costly and difficult to scale. We propose WIZARD, a weight-space meta-learning framework that sidesteps task-specific fine-tuning by generating task-specific LoRA parameters for a frozen VLA policy. Given only a language instruction and a short demonstration video, WIZARD predicts the corresponding adaptation weights in a single forward pass, without target-task action labels or test-time optimization. During meta-training, WIZARD learns to map task evidence directly to expert LoRA updates, capturing relationships between tasks in weight space. Experiments on LIBERO show that WIZARD improves performance by up to $\sim 2\times$ on unseen dataset collections and up to $\sim 14\times$ on unseen tasks. On a Franka Emika Panda, WIZARD consistently improves over a real-domain adapted baseline, showing that generated adapters provide task-level specialization beyond simulation. Keywords: Meta-Learning, Policy Parameter Generation, Test-Time Adaptation

$j \rightarrow j$ 1 $j \rightarrow 1$ Task i Task j new new Task new Figure 1: WIZARD: Weight-space Inference for Zero-shot Adaptation from Robotic Demonstration. (Left) Meta-Training. A repository of task experts is built from LIBERO-Goal, -Object, and -10 datasets. For each task, a LoRA adapter (ΔW_i) is trained while a multimodal encoder extracts a task embedding z_i from the instruction and visual demonstration. The meta-network learns to map embeddings to LoRA parameters by reconstructing the expert weights ($z_i \rightarrow \Delta \tilde{W}_i$). (Right) Zero-Shot Inference. Given a new task (e.g., from LIBERO-Spatial), WIZARD directly predicts the adaptation weights $\Delta \tilde{W}_{\text{new}}$ from the task embedding z_{new} , enabling zero-shot policy adaptation without gradient-based fine-tuning, even for unseen tasks. [†]Correspondence to <christian.bianchi@italailabs.com> arXiv:2606.07217v1 [cs.RO] 5 Jun 2026

1 Introduction Robotic manipulation is increasingly addressed through large Vision-Language-Action (VLA) models, which reframe control as large-scale data-driven pretraining followed by task-specific adaptation [1, 2]. Despite their broad pretraining, these models often suffer a severe performance drop when deployed on unseen tasks or distribution shifts. The standard solution is to specialize the base model through task-specific fine-tuning, often using lightweight adapters such as Low-Rank Adaptation (LoRA) [3]. While effective, this paradigm poses two key scalability issues: every new task requires task-specific demonstrations with action labels, and adaptation still requires additional fine-tuning to train a separate expert policy [4]. This limitation is particularly evident in modern VLA models [5, 6, 7], where the need for adaptation is drastic: the pretrained state-of-the-art $\pi_0.5$ achieves a 0% success rate on unseen dataset suites such as LIBERO-Spatial. While fine-tuning on related datasets (LIBERO-Object, -Goal, -10) improves performance only marginally to 19%, direct test-time fine-tuning on LIBERO-Spatial reaches 94%. Although effective, such pipelines still require learning a dedicated expert for each target distribution, raising a central question: can we adapt VLA policies to new tasks

without task-specific optimization at test time? Existing alternatives address only part of this scalability problem. Task-specific expert policies require dedicated data, optimization, and model storage for every new task. LoRA-based fine-tuning reduces the storage cost by learning lightweight adapters, but it still requires action-labeled demonstrations and additional optimization for each target task. Meta-learning could avoid repeated fine-tuning by directly generating task-specific policies, yet generating full VLA parameters is impractical for modern robotic foundation models. Recent parameter-generation methods remain limited in this respect: they rely on action-space supervision [8, 9], require privileged task information such as goal images [10], or synthesize full policy parameters, which does not scale to large VLA backbones. We introduce WIZARD (Weight-space Inference for Zero-shot Adaptation from Robotic Demonstration), a weight-space meta-learning framework that generates task-specific adapters on demand from a language instruction and a short demonstration video. Our formulation treats robotic adaptation as a parameter inference problem, where a meta-network predicts the appropriate policy update from task evidence. This differs from classic test-time adaptation, which typically relies on optimizing policies in the action space through supervision or gradient-based fine-tuning that leverages action labels. To this end, as illustrated in Fig. 1, we introduce a task-oriented meta-dataset of pairs $(z, \Delta W)$, where z denotes task evidence composed of language instructions and visual observations, and ΔW is the LoRA update of an expert policy trained for that task. A meta-network is then trained to map task evidence directly to expert adapter weights, learning relationships across tasks in the weight space of policy parameters. This novel formulation yields a scalable adaptation mechanism for modern state-of-the-art VLA models. At inference time, given only a prompt and a short video from an unseen task z_{new} , WIZARD generates the corresponding LoRA weights ΔW_{new} in a single forward pass, without action annotations, privileged goal information, or gradient-based optimization. The generated adapter is injected into the ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: 모든 Gemini 모델 호출 실패:

```
{
  "error": {
    "code": 429,
    "message": "Your prepayment credits are depleted. Please go to AI Studio at https://ai.studio/projects to manage your project and billing. Learn more at https://ai.google.dev/gemini-api/docs/billing#prepay.",
    "status": "RESOURCE_EXHAUSTED"
  }
}
```