

SLM / Edge Device arXiv Daily Summary

생성일: 2026-06-15 05:50 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 7일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 7일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: WHAR Arena: Benchmarking the State of the Art in Efficient Wearable Human Activity Recognition

저자: Maximilian Burzer, Tobias King, Till Riedel, Michael Beigl, Tobias Röddiger

카테고리: SLM/Edge/On-device, Format-LoRA/Structured Output

arXiv ID: 2606.13194

제출일: 2026-06-11T11:01:36+00:00

수정일: 2026-06-11T11:01:36+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.13194.pdf>

[초록 원문]

Deep learning has become the dominant paradigm in Wearable Human Activity Recognition (WHAR), yet progress is obscured by a comparability crisis. Results are often reported using inconsistent datasets, custom data processing, and varying evaluation protocols, making state-of-the-art claims fragile. We address this with a large-scale, open-source benchmark that integrates 30 diverse datasets under standardized processing, unified model interfaces, and a shared cross-subject evaluation protocol. Evaluating 17 representative architectures across 4760 training runs, we jointly measure predictive performance alongside on-device latency, peak memory, and model size on an Android reference device. Our results reveal that the WHAR state of the art is distributed rather than dominated by a single architecture. While CNN-HAR achieves the highest mean macro-F1, top-performing models cluster tightly, indicating contemporary architectures have converged near a predictive performance ceiling. When accounting for deployment efficiency, compact neural models, such as TinierHAR, and classical Random Forests define the practically relevant Pareto frontier, whereas larger recurrent and hybrid models incur high hardware costs without corresponding performance gains. Consequently, while predictive performance has plateaued, substantial potential for future progress remains in optimizing deployment efficiency and improving

adaptation to domain shifts. We release our full framework to support transparent reuse and extension.

[PDF 앞부분/서론 일부]

WHAR Arena: Benchmarking the State of the Art in Efficient Wearable Human Activity Recognition MAXIMILIAN BURZER, Karlsruhe Institute of Technology, Germany TOBIAS KING, Karlsruhe Institute of Technology, Germany TILL RIEDEL, Karlsruhe Institute of Technology, Germany MICHAEL BEIGL, Karlsruhe Institute of Technology, Germany TOBIAS RÖDDIGER, IPAI Foundation gGmbH, Germany Various Formats (e.g. CSV, TXT, MAT) Heterogeneous Structures Uncleaned, Missing Values Large-Scale Benchmarking Impractical Unstructured Literature Heterogeneous Dataset Landscape in WHAR WHAR Datasets Library WHAR Models Library Standardized Data Format & Processing Curation of 17 Models Cross-Subject Performance Evaluation Latency / RAM Usage Macro F1 Model X Model Y Curation of 30 Datasets Standardized Interfaces Our Benchmarking Solution for Assessing the Joint State of the Art in WHAR Benchmarking Protocol On-Device Efficiency Evaluation Leaderboard Rankings via Efficiency-Index Fig. 1. Public Wearable Human Activity Recognition (WHAR) datasets are highly heterogeneous in terms of file formats, structure, and data quality, which makes standardized processing and fair comparison challenging. Our framework addresses this issue through two components: a WHAR Datasets library that parses and standardizes 30 datasets, and a WHAR Models library that unifies 17 representative models under a common inference interface. Together, these components enable large-scale benchmarking and reproducible analysis of performance-efficiency trade-offs in WHAR, culminating in robust relative leaderboard rankings. Deep learning has become the dominant paradigm in Wearable Human Activity Recognition (WHAR), yet progress is obscured by a comparability crisis. Results are often reported using inconsistent datasets, custom data processing, and varying evaluation protocols, making state-of-the-art claims fragile. We address this with a large-scale, open-source benchmark that integrates 30 diverse datasets under standardized processing, unified model interfaces, and a shared cross-subject evaluation protocol. Evaluating 17 representative architectures across 4760 training runs, we jointly measure predictive performance alongside on-device latency, peak memory, and model size on an Android reference device. Our results reveal that the WHAR state of the art is distributed rather than dominated by a single architecture. While CNN-HAR achieves the highest mean macro-F1, top-performing models cluster tightly, indicating contemporary architectures have converged near a predictive performance ceiling. When accounting for deployment efficiency, compact neural models, such as TinierHAR, and classical Random Forests define the practically relevant Pareto frontier, whereas larger recurrent and hybrid models incur high hardware costs without corresponding performance gains. Consequently, while predictive performance has plateaued, substantial potential for future progress remains in optimizing deployment efficiency and improving adaptation to domain shifts. We release our full framework to support transparent reuse and extension. CCS Concepts: • Computing methodologies -> Machine learning; • Human-centered computing -> Ubiquitous and mobile computing. Additional Key Words and Phrases: Human Activity Recognition, HAR, Benchmarking, Dataset Standardization, Data Processing, Wearables Both authors contributed equally to this research. Authors' Contact Information: Maximilian Burzer, maximilian.burzer@kit.edu, Karlsruhe Institute of Technology, Karlsruhe, Germany; Tobias King, tobias.king@kit.edu, Karlsruhe Institute of Technology, Karlsruhe, Germany; Till Riedel, till.riedel@kit.edu, Karlsruhe Institute of Technology, Karlsruhe, Germany; Michael Beigl, michael.beigl@kit.edu, Karlsruhe Institute of Technology, Karlsruhe, Germany; Tobias Röddiger, tobias.roeddiger@ipai-foundation.ai, IPAI Foundation gGmbH, Heilbronn,

Germany. 1 arXiv:2606.13194v1 [cs.LG] 11 Jun 2026 2 Burzer, King et al. 1 Introduction Wearable Human Activity Recognition (WHAR) infers human activities from time-series signals collected by wearable sensors such as smartwatches [61], earables [44], and rings [65]. It is a core capability for applications in healthcare, fitness, sports, smart environments, and assistive systems [14, 43, 44, 81, 84], which operate in real-time and continuously. Current WHAR research is heavily influenced by the availability of open datasets [4], with classically used datasets such as WISDM [51] and OPPORTUNITY [85] complemented by newer datasets that cover a wider range of activity classes, sensor modalities, and configurations [20]. The need to support this increasing diversity and new compute capabilities of embedded devices has driven a shift from classical machine learning methods based on handcrafted features to deep learning approaches that model multivariate time-series data end-to-end using neural architectures incorporating convolutional, recurrent, and attention mechanisms [20]. While the field has shown increasing interest in efficient models for wearable and edge hardware, and continues to emphasize cross-subject generalization as a core requirement, comparability across studies remains limited by heterogeneous datasets, inconsistent data processing pipelines, insufficiently standardized cross-subject evaluation protocols, narrow dataset selections, and uneven reporting of on-device deployment-relevant efficiency metrics. Despite this progress, predicting the actual performance WHAR under realistic conditions remains challenging. Unlike more mature benchmarking ecosystems in fields such as Natural Language Processing and Computer Vision [38], WHAR is increasingly affected by a comparability crisis [20, 26, 69, 109]. Commonly accepted benchmarks do not exist. The datasets used vary substantially in file formats, structural organization, and metadata, and in the absence of standardized data processing pipelines, studies typically rely on their own combinations of ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '웨어러블 인간 활동 인식(WHAR) 분야에서 딥러닝은 지배적인 패러다임이 되었지만, 비교 가능성 위기로 인해 발전이 저해되고 있습니다. 결과는 종종 일관성 없는 데이터셋, 맞춤형 데이터 처리, 그리고 다양한 평가 프로토콜을 사용하여 보고되며, 이는 최첨단(state-of-the-art)'}, {'role': 'model'}, {'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 332, 'candidatesTokenCount': 82, 'totalTokenCount': 2376, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 332}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': '9hMvasTqM6Ot1MkPxoDRiAQ'}

[논문 후보 2]

제목: Quantum Reservoir Computing for Short-Term Power Load Forecasting in Resource-Constrained Energy Systems
저자: Mansi Od, Param Pathak, Nouhaila Innan, Muhammad Shafique
카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency
arXiv ID: 2606.12806
제출일: 2026-06-11T02:05:25+00:00
수정일: 2026-06-11T02:05:25+00:00
최근성: 최근 3일 이내

[초록 원문]

Short-term load forecasting is essential for reliable energy management, but practical deployment on edge devices requires models that remain accurate under limited memory, finite measurement budgets, and hardware noise. This work proposes a hardware-efficient Quantum Reservoir Computing (QRC) framework for energy load forecasting, where a fixed quantum reservoir transforms temporal input windows into high-dimensional features and only a classical Elastic Net readout is trained. To reduce deployment cost, the trained readout is compressed using post-training fixed-point quantization at bit widths from 8 to 2 bits. The framework is evaluated on the Tetouan and Spain energy load datasets under exact statevector simulation, 512-shot finite sampling, and realistic hardware-noise models from IBM FakeTorino and IBM FakeMarrakesh. Results show that 6-bit readout precision preserves full-precision forecasting performance while reducing readout memory by 81.2%. Below this point, degradation becomes dataset dependent, with Tetouan showing stronger sensitivity and Spain degrading more gradually. Hardware-noise validation further shows that the trained readout transfers to noisy reservoir states without retraining. These findings support quantized QRC as a resource-aware forecasting approach for near-term quantum time-series applications.

[PDF 앞부분/서론 일부]

Quantum Reservoir Computing for Short-Term Power Load Forecasting in Resource-Constrained Energy Systems
Mansi Od ¹, Param Pathak ², Nouhaila Innan ^{3,4}, and Muhammad Shafique ^{3,4} ¹University of Greenwich, London, United Kingdom ²Fractal Analytics, QuantumAI Lab, Mumbai, Maharashtra, India ³eBRAIN Lab, Division of Engineering, New York University Abu Dhabi (NYUAD), Abu Dhabi, UAE ⁴Center for Quantum and Topological Systems (CQTS), NYUAD Research Institute, NYUAD, Abu Dhabi, UAE mansiod2049@gmail.com, param.pathak@fractal.ai, {nouhaila.innan, muhammad.shafique}@nyu.edu

Abstract-Short-term load forecasting is essential for reliable energy management, but practical deployment on edge devices requires models that remain accurate under limited memory, finite measurement budgets, and hardware noise. This work proposes a hardware-efficient Quantum Reservoir Computing (QRC) framework for energy load forecasting, where a fixed quantum reservoir transforms temporal input windows into highdimensional features and only a classical Elastic Net readout is trained. To reduce deployment cost, the trained readout is compressed using post-training fixed-point quantization at bit widths from 8 to 2 bits. The framework is evaluated on the Tetouan and Spain energy load datasets under exact statevector simulation, 512-shot finite sampling, and realistic hardware-noise models from IBM FakeTorino and IBM FakeMarrakesh. Results show that 6-bit readout precision preserves full-precision forecasting performance while reducing readout memory by 81.2%. Below this point, degradation becomes dataset dependent, with Tetouan showing stronger sensitivity and Spain degrading more gradually. Hardware-noise validation further shows that the trained readout transfers to noisy reservoir states without retraining. These findings support quantized QRC as a resource-aware forecasting approach for near-term quantum time-series applications.

Index Terms-Quantum machine learning, quantum reservoir computing, short-term load forecasting, post-training quantization, edge computing, smart grids.

I. INTRODUCTION Modern power grids are becoming increasingly distributed, pushing Short-Term Load Forecasting (STLF) from centralized

control rooms toward edge nodes embedded in smart meters and local controllers [1]. Accurate sub-hourly demand prediction is indispensable for operational planning, frequency regulation, and demand-response dispatch [2]. The volatility and nonstationarity of high-frequency consumption data make this a fundamentally difficult sequential regression task, and the stakes of forecasting error are high in both economic and grid-reliability terms. Recurrent architectures such as Long Short-Term Memory (LSTM) networks and Gated Recurrent Units (GRUs), as well as attention-based Transformers, have set the current performance ceiling for STLF [3]. By learning rich temporal dependencies through backpropagation across many layers, these models achieve low forecasting error on standard benchmarks. However, their accuracy comes at a steep hardware cost: millions of trainable parameters, large activation buffers, and repeated floating-point matrix multiplications make inference latency and storage requirements incompatible with the memory and energy limits of resource-constrained edge devices [4]. Reservoir Computing (RC) offers a structurally different solution to this deployment gap [5]. Rather than propagating gradients through a recurrent network, RC projects input signals into a fixed, randomly initialized dynamical system and trains only a linear readout layer on top of the resulting high-dimensional state trajectory. Because the reservoir is never updated, training reduces to a convex readout regression problem, avoiding the costly backpropagation passes required by deep recurrent models. This makes RC attractive for lowpower deployment. However, classical echo-state reservoirs rely on random recurrent matrices whose effective dimensionality is bounded by the number of physical nodes, potentially limiting their representational capacity for complex multivariate energy signals [6]. Quantum Reservoir Computing (QRC) extends the RC paradigm to quantum mechanical systems, where the reservoir is a parameterized quantum circuit with frozen weights [7]. Even a modest register of N qubits evolves in a Hilbert space of dimension 2^N , providing access to a high-dimensional nonlinear feature space with a compact physical register. Superposition and entanglement generate intricate correlations across input features that are difficult to replicate in classical systems, while the fixed-circuit design preserves the core RC advantage of gradient-free training. Critically, QRC sidesteps the barren-plateau problem that undermines the trainability of fully parameterized quantum models [8], making it a suitable candidate for resource-constrained forecasting. Despite these advantages, a concrete hardware barrier remains. Even when the quantum processing stage is fixed, the classical readout layer must store a weight vector whose dimensionality scales with the number of measured observables. At full 32-bit floating-point precision this readout imposes a non-trivial memory footprint that can exceed the on-chip Static Random-Access Memory budget of embedded energy controllers. Post-training fixed-point quantization of the readout weights is therefore a necessary step toward genuine edge deployability, yet its effect on the rich high-dimensional representations produced by a quantum reservoir has not been systematically studied. It is unclear whether the informational redundancy embedded in quantum feature maps offers any resilience against aggressive low-bit compression, or whether quantization noise degrades the forecasting signal in the same way it affects classical dense readouts. Through this work, we close this gap by proposing a Hardware-Efficient QRC framework that treats the classical readout as the ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '단기 부하 예측은 신뢰할 수 있는 에너지 관리에 필수적이지만, 엣지 장치에 실제로 배포하려면 제한된 메모리, 유한한 측정 예산, 그리고

하드웨어 노이즈 하에서도 정확도를 유지하는 모델이 필요하다. 본 연구는 에너지 부하 예측을 위한 하드웨어 효율적인 양자 리저버 컴퓨팅(')], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0]], 'usageMetadata': {'promptTokenCount': 315, 'candidatesTokenCount': 80, 'totalTokenCount': 2359, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 315}], 'thoughtsTokenCount': 1964, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': '_xMvar2hOpeysOIP8oqTqQ0'}

[논문 후보 3]

제목: Privacy-Preserving Federated Autoencoder for ECG Anomaly Detection on Edge Devices
저자: Kaan Arda Akyol, Jakub Kacper Szelg, Aydin Abadi, Maha Alghamdi, Ghadah Albalawi, Ghouse Ibrahim Kaleelullah, Hilal Tutus, Sarah Al Subaiei, Shardul Kapse, Syed Mohammed Raheeb, Mujeeb Ahmed, Rehmat Ullah
카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency
arXiv ID: 2606.11556
제출일: 2026-06-10T01:33:20+00:00
수정일: 2026-06-10T01:33:20+00:00
최근성: 최근 4일 이내
arXiv PDF: <https://arxiv.org/pdf/2606.11556.pdf>

[초록 원문]

Continuous electrocardiography (ECG) monitoring could surface rhythm abnormalities before they escalate into cardiovascular events. However, a deployable system must satisfy three requirements simultaneously: legal-grade privacy (GDPR, HIPAA), real-time inference on constrained edge hardware, and detection quality under non-IID cross-hospital data. We design and evaluate an end-to-end federated system addressing all three for unsupervised 12-lead ECG anomaly detection on PTB-XL dataset, combining three autoencoder families (VanillaAE, ConvAE, VAE), Flower-based federated averaging (FedAvg) across ten simulated hospitals, client-side differentially private SGD (DP-SGD) with a Rényi-DP accountant, and 8-bit integer (INT8) post-training quantization with Raspberry Pi 4 benchmarking. Our main contributions are: an empirical characterization of how these mechanisms compose, practical DP-specific recommendations, and technical and security insights for a clinically sensitive setting. Federated learning matches or exceeds the centralized baseline across all architectures (ConvAE federated area under the ROC curve, AUROC, \$0.782\$), and an \$\epsilon\$ sweep identifies \$\epsilon=4\$ as the recommended clinical operating point. INT8 quantization roughly halves model size and cuts Pi 4 latency by up to \$44\%\$ with \$<0.12\%\$ AUROC loss. Crucially, DP and quantization penalties are empirically independent, so practitioners need not trade a strong privacy guarantee for a compact edge footprint. To our knowledge, this is the first system combining federated learning, formal \$(\epsilon,\delta)\$-DP, unsupervised reconstruction-based detection, and quantized AArch64 deployment.

[PDF 앞부분/서론 일부]

Privacy-Preserving Federated Autoencoder for ECG Anomaly Detection on Edge Devices Kaan Arda Akyol, Jakub Kacper Szelg, Aydin Abadi, Maha Alghamdi, Ghadah Albalawi, Ghouse Ibrahim Kaleelullah, Hilal Tutus, Sarah Al Subaiei, Shardul Kapse, Syed Mohammed Raheeb, Mujeeb Ahmed, Rehmat Ullah School of Computing, Newcastle University, Newcastle upon Tyne, United Kingdom Email: {K.A.Akyol2, J.K.Szelag2, Aydin.Abadi, M.Alghamdi2,

G.S.S.Albalawi², G.M.Ibrahim-Kaleelullah², H.Tutus², S.S.A.Alsubaiei², S.Kapse², S.M.Mohammed-Raheeb², Mujeeb.Ahmed, Rehmat.Ullah}@newcastle.ac.uk

Abstract—Continuous electrocardiography (ECG) monitoring could surface rhythm abnormalities before they escalate into cardiovascular events. However, a deployable system must satisfy three requirements simultaneously: legal-grade privacy (GDPR, HIPAA), real-time inference on constrained edge hardware, and detection quality under non-IID cross-hospital data. We design and evaluate an end-to-end federated system addressing all three for unsupervised 12-lead ECG anomaly detection on PTB-XL dataset, combining three autoencoder families (VanillaAE, ConvAE, VAE), Flower-based federated averaging (FedAvg) across ten simulated hospitals, client-side differentially private SGD (DP-SGD) with a Rényi-DP accountant, and 8-bit integer (INT8) post-training quantization with Raspberry Pi 4 benchmarking. Our main contributions are: an empirical characterization of how these mechanisms compose, practical DP-specific recommendations, as well as technical and security insights to an otherwise clinically sensitive subject, all while prioritizing ethical considerations. Federated learning matches or exceeds the centralized baseline across all architectures (ConvAE federated area under the ROC curve, AUROC, 0.782), and an ϵ -sweep identifies $\epsilon=4$ as the recommended clinical operating point. INT8 quantization roughly halves model size and cuts Pi 4 latency by up to 44% with $<0.12\%$ AUROC loss. Crucially, DP and quantization penalties are empirically independent, so practitioners need not trade a strong privacy guarantee for a compact edge footprint. To our knowledge, this is the first system combining federated learning, formal (ϵ, δ) -DP, unsupervised reconstruction-based detection, and quantized AArch64 deployment.

Keywords—Federated Learning, Differential Privacy, ECG Anomaly Detection, Edge Computing, Autoencoder, Quantization.

I. INTRODUCTION Cardiovascular disease is the world's leading cause of mortality, responsible for an estimated 17.9 million deaths annually [42], and a substantial fraction are preceded by detectable rhythm abnormalities that continuous electrocardiography (ECG) surveillance could catch before escalation. Wearable and implantable monitors promise real-time cardiac screening that bridges onset and intervention [34], shifting cardiology from reactive treatment toward proactive prevention. Turning that promise into a deployable system, however, requires three properties simultaneously. Privacy compliance. Patient ECG data is among the most sensitive categories under GDPR (EU 2016/679) and HIPAA, and cannot be freely centralized. Federated learning (FL) [25] keeps raw records local and shares only model updates, and has been increasingly adopted in distributed medical systems [20, 34]. FL alone is insufficient: gradient inversion, membership inference, and de-anonymization attacks can reconstruct training records or re-identify individuals from shared updates or deployed ECG models [2, 3, 40]. Differential privacy (DP) via differentially private stochastic gradient descent (DP-SGD) [1, 44] closes this gap with a rigorous (ϵ, δ) -guarantee [15], but its utility cost on reconstruction-based anomaly detectors, which rely on subtle mean-squared error (MSE) differences between normal and pathological waveforms, remains poorly characterized. Edge efficiency. Continuous monitoring devices are overwhelmingly AArch64-based, typically shipping with ARM Cortex-A cores [18, 36], and the Raspberry Pi 4 is the canonical research proxy for this class. 8-bit integer (INT8) post-training quantization (PTQ) can halve model size with negligible accuracy loss in supervised settings [23], yet its effect on the fine-grained reconstruction fidelity that drives ECG anomaly scoring has not been validated on AArch64 hardware. Detection effectiveness. Any model satisfying the first two requirements must still maintain sufficient detection quality under non-independent and identically distributed (non-IID) hospital-scale partitioning for population-level screening. Satisfying each property in isolation is tractable;

satisfying all three end-to-end on real edge hardware is where the literature is currently sparse. Simply stacking FedAvg, DP-SGD, and INT8 PTQ is insufficient for two reasons. First, DP noise interacts with reconstruction error differently than with classification crossentropy: supervised pipelines tolerate moderate DP-SGD noise because cross-entropy provides strong per-class gradients, whereas reconstruction-based detectors exhibit a sharp utility floor below which noise overwhelms the signal. Second, PTQ has not been validated on the reconstruction fidelity required for ECG anomaly scoring on AArch64. These gaps motivate a fully evaluated end-to-end system. The proposed framework targets two complementary dimensions within a unified federated pipeline: (i) security and arXiv:2606.11556v1 [cs.CR] 10 Jun 2026 privacy, through formal(ϵ , δ)-DP at the client level, and (ii) computational efficiency, through INT8 PTQ and on-device benchmarking on AArch64 edge hardware. A. Our Contributions We design, implement, and evaluate an end-to-end federated system addressing privacy compliance, edge efficiency, and detection effectiveness in a single unified pipeline. Our contributions are as follows. 1)Federation effect.Federated training matches the centralized baseline across three autoencoder families under non-IID partitioning ($K=10$, Dirichlet $\alpha=0.5$). ConvAE gains ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '지속적인 심전도(ECG) 모니터링은 리듬 이상이 심혈관 질환으로 악화되기 전에 이를 발견할 수 있습니다. 그러나 배포 가능한 시스템은 법적 수준의 프라이버시(GDPR, HIPAA), 제약된 엣지 하드웨어에서의 실시간 추론, 그리고 비독립동일분포(')}, 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 414, 'candidatesTokenCount': 79, 'totalTokenCount': 2458, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 414}], 'thoughtsTokenCount': 1965, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'CBQvauO-J8qo1MkPscK36AY'}