

igraph Reference Manual

Gábor Csárdi, Department of Statistics, Harvard University

Tamás Nepusz, Department of Biological Physics, Eötvös Loránd University

Vincent Traag, Centre for Science and Technology Studies, Leiden University

Szabolcs Horvát, Center for Systems Biology Dres-

den, Max Planck Institute for Cell Biology and Genetics

Fabio Zanini, Lowy Cancer Research Centre, University of New South Wales

igraph Reference Manual

by Gábor Csárdi, Tamás Nepusz, Vincent Traag, Szabolcs Horvát, and Fabio Zanini

0.10.0-dev+2b1ad04b

This manual is for igraph, version 0.10.0-dev+2b1ad04b.

Copyright (C) 2005-2019 Gábor Csárdi and Tamás Nepusz. Copyright (C) 2020-2022 igraph development team. Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled “GNU Free Documentation License”.

Table of Contents

1. Introduction	1
igraph is free software	1
Citing igraph	2
2. Installation	3
Prerequisites	3
Installation	3
General build instructions	3
Specific instructions for Windows	4
Notable configuration options	5
Building the documentation	6
Notes for package maintainers	6
Auto-detection of dependencies	6
Shared and static builds	7
Cross-compiling	7
Additional notes	8
3. Tutorial	9
Compiling programs using igraph	9
Compiling with CMake	9
Compiling without CMake	10
Running the program	11
Creating your first graphs	11
Calculating various properties of graphs	12
4. Basic data types and interface	14
The igraph data model	14
General conventions of igraph functions	15
Atomic data types	15
The basic interface	15
Graph constructors and destructors	16
Basic query operations	18
Adding and deleting vertices and edges	25
Miscellaneous macros and helper functions	28
IGRAPH_VCOUNT_MAX — The maximum number of vertices supported in igraph graphs.	28
IGRAPH_ECOUNTER_MAX — The maximum number of edges supported in igraph graphs.	29
igraph_expand_path_to_pairs — Helper function to convert a sequence of vertex IDs describing a path into a "pairs" vector.	29
igraph_invalidate_cache — Invalidates the internal cache of an igraph graph	29
igraph_is_same_graph — Are two graphs identical as labelled graphs?	30
5. Error handling	31
Error handling basics	31
Error handlers	31
igraph_error_handler_t — The type of error handler functions.	31
igraph_error_handler_abort — Abort program in case of error.	32
igraph_error_handler_ignore — Ignore errors.	32
igraph_error_handler_printignore — Print and ignore errors.	32
Error codes	32
igraph_error_t — Type alias because igraph_error_t used to be an integer, and was used	32
igraph_error_type_t — Error code type.	32
igraph_strerror — Textual description of an error.	36
Warning messages	36
igraph_warning_handler_t — The type of igraph warning handler func- tions.	36

igraph_set_warning_handler — Installs a warning handler.	36
IGRAPH_WARNING — Triggers a warning.	37
IGRAPH_WARNINGF — Triggers a warning, with printf-like syntax.	37
igraph_warning — Triggers a warning.	37
igraph_warningf — Triggers a warning, printf-like version.	38
igraph_warning_handler_ignore — Ignores all warnings.	38
igraph_warning_handler_print — Prints all warnings to the standard error.	38
Advanced topics	39
Writing error handlers	39
Error handling internals	39
Deallocating memory	42
Writing igraph functions with proper error handling	43
Fatal errors	43
Error handling and threads	46
6. Memory (de)allocation	47
igraph_malloc — Allocate memory that can be safely deallocated by igraph functions.	47
igraph_calloc — Allocate memory that can be safely deallocated by igraph functions.	47
igraph_realloc — Reallocate memory that can be safely deallocated by igraph functions.	48
igraph_free — Deallocate memory that was allocated by igraph functions.	48
7. Data structure library: vector, matrix, other data types	49
About template types	49
Vectors	50
About igraph_vector_t objects	50
Constructors and destructors	50
Initializing elements	53
Accessing elements	54
Vector views	56
Copying vectors	56
Exchanging elements	58
Vector operations	59
Vector comparisons	62
Finding minimum and maximum	67
Vector properties	69
Searching for elements	72
Resizing operations	75
Complex vector operations	78
Sorting	81
Set operations on sorted vectors	82
Pointer vectors (igraph_vector_ptr_t)	83
Deprecated functions	90
Matrices	92
About igraph_matrix_t objects	92
Matrix constructors and destructors	93
Initializing elements	94
Accessing elements of a matrix	94
Matrix views	96
Copying matrices	97
Operations on rows and columns	98
Matrix operations	102
Matrix comparisons	106
Combining matrices	108
Finding minimum and maximum	109
Matrix properties	111
Searching for elements	114

Resizing operations	115
Complex matrix operations	117
Deprecated functions	120
Sparse matrices	121
About sparse matrices	121
Creating sparse matrix objects	121
Query properties of a sparse matrix	125
Operations on sparse matrices	132
Operations on sparse matrix iterators	138
Operations that change the internal representation	140
Decompositions and solving linear systems	141
Eigenvalues and eigenvectors	147
Conversion to other data types	149
Writing to a file, or to the screen	150
Deprecated functions	150
Stacks	151
igraph_stack_init — Initializes a stack.	151
igraph_stack_destroy — Destroys a stack object.	152
igraph_stack_reserve — Reserve memory.	152
igraph_stack_empty — Decides whether a stack object is empty.	152
igraph_stack_size — Returns the number of elements in a stack.	153
igraph_stack_clear — Removes all elements from a stack.	153
igraph_stack_push — Places an element on the top of a stack.	153
igraph_stack_pop — Removes and returns an element from the top of a stack.	154
igraph_stack_top — Query top element.	154
Double-ended queues	154
igraph_dqueue_init — Initialize a double ended queue (deque).	154
igraph_dqueue_destroy — Destroy a double ended queue.	155
igraph_dqueue_empty — Decide whether the queue is empty.	155
igraph_dqueue_full — Check whether the queue is full.	155
igraph_dqueue_clear — Remove all elements from the queue.	156
igraph_dqueue_size — Number of elements in the queue.	156
igraph_dqueue_head — Head of the queue.	156
igraph_dqueue_back — Tail of the queue.	157
igraph_dqueue_pop — Remove the head.	157
igraph_dqueue_pop_back — Remove the tail	157
igraph_dqueue_push — Appends an element.	157
Maximum and minimum heaps	158
igraph_heap_init — Initializes an empty heap object.	158
igraph_heap_init_array — Build a heap from an array.	158
igraph_heap_destroy — Destroys an initialized heap object.	159
igraph_heap_clear — Removes all elements from a heap.	159
igraph_heap_empty — Decides whether a heap object is empty.	159
igraph_heap_push — Add an element.	160
igraph_heap_top — Top element.	160
igraph_heap_delete_top — Removes and returns the top element.	160
igraph_heap_size — Number of elements in the heap.	161
igraph_heap_reserve — Reserves memory for a heap.	161
String vectors	161
igraph_strvector_init — Initializes a string vector.	161
igraph_strvector_init_copy — Initialization by copying.	162
igraph_strvector_destroy — Frees the memory allocated for the string vector.	162
STR — Indexing string vectors.	162
igraph_strvector_get — Retrieves an element of the string vector.	163
igraph_strvector_set — Takes elements at given positions from a string vector.	163

igraph_strvector_set_len — Sets an element of the string vector given a buffer and its size.	164
igraph_strvector_push_back — Adds an element to the back of a string vector.	164
igraph_strvector_push_back_len — Adds a string of the given length to the back of a string vector.	164
igraph_strvector_remove — Removes a single element from a string vector.	165
igraph_strvector_remove_section — Removes a section from a string vector.	165
igraph_strvector_append — Concatenates two string vectors.	165
igraph_strvector_merge — Moves the contents of a string vector to the end of another.	166
igraph_strvector_clear — Removes all elements from a string vector.	166
igraph_strvector_resize — Resizes a string vector.	167
igraph_strvector_reserve — Reserves memory for a string vector.	167
igraph_strvector_resize_min — Deallocates the unused memory of a string vector.	168
igraph_strvector_size — Returns the size of a string vector.	168
igraph_strvector_capacity — Returns the capacity of a string vector.	168
Deprecated functions	169
Lists of vectors, matrices and graphs	169
About igraph_vector_list_t objects	169
Constructors and destructors	170
Accessing elements	171
Vector properties	173
Resizing operations	174
Sorting and reordering	181
Adjacency lists	183
Adjacent vertices	184
Incident edges	187
Lazy adjacency list for vertices	189
Lazy incidence list for edges	190
Partial prefix sum trees	192
igraph_psumtree_init — Initializes a partial prefix sum tree.	193
igraph_psumtree_destroy — Destroys a partial prefix sum tree.	193
igraph_psumtree_size — Returns the size of the tree.	193
igraph_psumtree_get — Retrieves the value corresponding to an item in the tree.	194
igraph_psumtree_sum — Returns the sum of the values of the leaves in the tree.	194
igraph_psumtree_search — Finds an item in the tree, given a value.	194
igraph_psumtree_update — Updates the value associated to an item in the tree.	195
8. Random numbers	196
About random numbers in igraph	196
The default random number generator	196
igraph_rng_default — Query the default random number generator.	196
igraph_rng_set_default — Set the default igraph random number generator.	196
Creating random number generators	197
igraph_rng_init — Initializes a random number generator.	197
igraph_rng_destroy — Deallocates memory associated with a random number generator.	197
igraph_rng_seed — Seeds a random number generator.	197
igraph_rng_bits — The number of random bits that a random number generator can produce in a single round.	198

igraph_rng_max — The maximum possible integer for a random number generator.	198
igraph_rng_name — The type of a random number generator.	198
Generating random numbers	199
igraph_rng_get_integer — Generate an integer random number from an interval.	199
igraph_rng_get_unif01 — Samples uniformly from the unit interval.	199
igraph_rng_get_unif — Samples real numbers from a given interval.	199
igraph_rng_get_normal — Samples from a normal distribution.	200
igraph_rng_get_exp — Samples from an exponential distribution.	200
igraph_rng_get_gamma — Samples from a gamma distribution.	201
igraph_rng_get_binom — Samples from a binomial distribution.	201
igraph_rng_get_geom — Samples from a geometric distribution.	202
igraph_rng_get_pois — Samples from a Poisson distribution.	202
Supported random number generators	203
igraph_rngtype_mt19937 — The MT19937 random number generator.	203
igraph_rngtype_glibc2 — The random number generator introduced in GNU libc 2.	203
igraph_rngtype_pcg32 — The PCG random number generator (32-bit version).	204
igraph_rngtype_pcg64 — The PCG random number generator (64-bit version).	204
Use cases	205
Normal (default) use	205
Reproducible simulations	205
Changing the default generator	205
Using multiple generators	205
Example	206
9. Graph generators	207
Deterministic graph generators	207
igraph_create — Creates a graph with the specified edges.	207
igraph_small — Shorthand to create a small graph, giving the edges as arguments.	207
igraph_adjacency — Creates a graph from an adjacency matrix.	208
igraph_weighted_adjacency — Creates a graph from a weighted adjacency matrix.	209
igraph_sparse_adjacency — Creates a graph from a sparse adjacency matrix.	210
igraph_sparse_weighted_adjacency — Creates a graph from a weighted sparse adjacency matrix.	211
igraph_adjlist — Creates a graph from an adjacency list.	211
igraph_star — Creates a <i>star</i> graph, every vertex connects only to the center. ..	211
igraph_wheel — Creates a <i>wheel</i> graph, a union of a star and a cycle graph.	212
igraph_square_lattice — Arbitrary dimensional square lattices.	213
igraph_ring — Creates a <i>cycle</i> graph or a <i>path</i> graph.	214
igraph_kary_tree — Creates a k-ary tree in which almost all vertices have k children.	215
igraph_symmetric_tree — Creates a symmetric tree with the specified number of branches at each level.	215
igraph_regular_tree — Creates a regular tree.	216
igraph_full — Creates a full graph (directed or undirected, with or without loops).	217
igraph_full_citation — Creates a full citation graph.	218
igraph_full_multipartite — Create a full multipartite graph.	218
igraph_turan — Create a Turán graph.	219
igraph_realize_degree_sequence — Generates a graph with the given degree sequence.	219
igraph_famous — Create a famous graph by simply providing its name.	222

igraph_lcf	— Creates a graph from LCF notation.	224
igraph_lcf_vector	— Creates a graph from LCF notation.	225
igraph_from_prufer	— Generates a tree from a Prüfer sequence.	225
igraph_atlas	— Create a small graph from the “Graph Atlas”.	226
igraph_de_bruijn	— Generate a de Bruijn graph.	226
igraph_kautz	— Generate a Kautz graph.	227
igraph_circulant	— Creates a circulant graph.	227
igraph_generalized_petersen	— Creates a Generalized Petersen graph.	228
igraph_extended_chordal_ring	— Create an extended chordal ring.	229
Games: Randomized graph generators		229
igraph_grg_game	— Generates a geometric random graph.	230
igraph_barabasi_game	— Generates a graph based on the Barabási-Albert model.	230
igraph_erdos_renyi_game	— Generates a random (Erdős-Rényi) graph.	232
igraph_watts_strogatz_game	— The Watts-Strogatz small-world model.	232
igraph_rewire_edges	— Rewires the edges of a graph with constant probability.	233
igraph_rewire_directed_edges	— Rewires the chosen endpoint of directed edges.	234
igraph_degree_sequence_game	— Generates a random graph with a given degree sequence.	235
igraph_k_regular_game	— Generates a random graph where each vertex has the same degree.	236
igraph_static_fitness_game	— Non-growing random graph with edge probabilities proportional to node fitness scores.	237
igraph_static_power_law_game	— Generates a non-growing random graph with expected power-law degree distributions.	238
igraph_forest_fire_game	— Generates a network according to the “forest fire game”.	239
igraph_rewire	— Randomly rewires a graph while preserving its degree sequence.	240
igraph_growing_random_game	— Generates a growing random graph.	241
igraph_callaway_traits_game	— Simulates a growing network with vertex types.	241
igraph_establishment_game	— Generates a graph with a simple growing model with vertex types.	242
igraph_preference_game	— Generates a graph with vertex types and connection preferences.	243
igraph_asymmetric_preference_game	— Generates a graph with asymmetric vertex types and connection preferences.	244
igraph_recent_degree_game	— Stochastic graph generator based on the number of incident edges a node has gained recently.	245
igraph_barabasi_aging_game	— Preferential attachment with aging of vertices.	246
igraph_recent_degree_aging_game	— Preferential attachment based on the number of edges gained recently, with aging of vertices.	247
igraph_lastcit_game	— Simulates a citation network, based on time passed since the last citation.	248
igraph_cited_type_game	— Simulates a citation based on vertex types.	249
igraph_citing_cited_type_game	— Simulates a citation network based on vertex types.	250
igraph_sbm_game	— Sample from a stochastic block model.	251
igraph_hsbm_game	— Hierarchical stochastic block model.	251
igraph_hsbm_list_game	— Hierarchical stochastic block model, more general version.	252
igraph_dot_product_game	— Generates a random dot product graph.	253

igraph_tree_game — Generates a random tree with the given number of nodes.	253
igraph_correlated_game — Generates a random graph correlated to an existing graph.	254
igraph_correlated_pair_game — Generates pairs of correlated random graphs.	255
igraph_simple_interconnected_islands_game — Generates a random graph made of several interconnected islands, each island being a random graph.	255
Deprecated functions	256
igraph_lattice — Arbitrary dimensional square lattices (deprecated).	256
igraph_tree — Creates a k-ary tree in which almost all vertices have k children (deprecated alias).	256
10. Games on graphs	258
Microscopic update rules	258
igraph_deterministic_optimal_imitation — Adopt a strategy via deterministic optimal imitation.	258
igraph_moran_process — The Moran process in a network setting.	259
igraph_roulette_wheel_imitation — Adopt a strategy via roulette wheel selection.	261
igraph_stochastic_imitation — Adopt a strategy via stochastic imitation with uniform selection.	262
Epidemic models	264
igraph_sir — Performs a number of SIR epidemics model runs on a graph.	264
igraph_sir_t — The result of one SIR model simulation.	264
igraph_sir_destroy — Deallocates memory associated with a SIR simulation run.	265
11. Vertex and edge selectors and sequences, iterators	266
About selectors, iterators	266
Vertex selector constructors	266
igraph_vs_all — Vertex set, all vertices of a graph.	266
igraph_vs_adj — Adjacent vertices of a vertex.	267
igraph_vs_nonadj — Non-adjacent vertices of a vertex.	267
igraph_vs_none — Empty vertex set.	268
igraph_vs_1 — Vertex set with a single vertex.	268
igraph_vs_vector — Vertex set based on a vector.	269
igraph_vs_vector_small — Create a vertex set by giving its elements.	269
igraph_vs_vector_copy — Vertex set based on a vector, with copying.	270
igraph_vs_range — Vertex set, an interval of vertices.	270
Generic vertex selector operations	271
igraph_vs_copy — Creates a copy of a vertex selector.	271
igraph_vs_destroy — Destroy a vertex set.	271
igraph_vs_is_all — Check whether all vertices are included.	272
igraph_vs_size — Returns the size of the vertex selector.	272
igraph_vs_type — Returns the type of the vertex selector.	272
Immediate vertex selectors	272
igraph_vss_all — All vertices of a graph (immediate version).	272
igraph_vss_none — Empty vertex set (immediate version).	273
igraph_vss_1 — Vertex set with a single vertex (immediate version).	273
igraph_vss_vector — Vertex set based on a vector (immediate version).	274
igraph_vss_range — An interval of vertices (immediate version).	274
Vertex iterators	274
igraph_vit_create — Creates a vertex iterator from a vertex selector.	274
igraph_vit_destroy — Destroys a vertex iterator.	275
Stepping over the vertices	275
IGRAPH_VIT_NEXT — Next vertex.	276
IGRAPH_VIT_END — Are we at the end?	276
IGRAPH_VIT_SIZE — Size of a vertex iterator.	276

IGRAPH_VIT_RESET — Reset a vertex iterator.	277
IGRAPH_VIT_GET — Query the current position.	277
Edge selector constructors	277
igraph_es_all — Edge set, all edges.	277
igraph_es_incident — Edges incident on a given vertex.	278
igraph_es_none — Empty edge selector.	278
igraph_es_1 — Edge selector containing a single edge.	279
igraph_es_vector — Handle a vector as an edge selector.	279
igraph_es_range — Edge selector, a sequence of edge IDs.	280
igraph_es_pairs — Edge selector, multiple edges defined by their endpoints in a vector.	280
igraph_es_pairs_small — Edge selector, multiple edges defined by their endpoints as arguments.	281
igraph_es_path — Edge selector, edge IDs on a path.	281
igraph_es_vector_copy — Edge set, based on a vector, with copying.	282
Immediate edge selectors	282
igraph_ess_all — Edge set, all edges (immediate version)	282
igraph_ess_none — Immediate empty edge selector.	283
igraph_ess_1 — Immediate version of the single edge edge selector.	283
igraph_ess_vector — Immediate vector view edge selector.	284
igraph_ess_range — Immediate version of the sequence edge selector.	284
Generic edge selector operations	284
igraph_es_as_vector — Transform edge selector into vector.	284
igraph_es_copy — Creates a copy of an edge selector.	285
igraph_es_destroy — Destroys an edge selector object.	285
igraph_es_is_all — Check whether an edge selector includes all edges.	285
igraph_es_size — Returns the size of the edge selector.	286
igraph_es_type — Returns the type of the edge selector.	286
Edge iterators	286
igraph_eit_create — Creates an edge iterator from an edge selector.	286
igraph_eit_destroy — Destroys an edge iterator.	287
Stepping over the edges	287
IGRAPH_EIT_NEXT — Next edge.	287
IGRAPH_EIT_END — Are we at the end?	288
IGRAPH_EIT_SIZE — Number of edges in the iterator.	288
IGRAPH_EIT_RESET — Reset an edge iterator.	288
IGRAPH_EIT_GET — Query an edge iterator.	288
Deprecated functions	289
igraph_es_seq — Edge selector, a sequence of edge IDs, with inclusive end- points (deprecated).	289
igraph_ess_seq — Immediate version of the sequence edge selector, with in- clusive endpoints.	289
igraph_vs_seq — Vertex set, an interval of vertices with inclusive endpoints (deprecated).	290
igraph_vss_seq — An interval of vertices with inclusive endpoints (immedi- ate version, deprecated).	290
12. Graph, vertex and edge attributes	292
The Attribute Handler Interface	292
igraph_attribute_table_t — Table of functions to perform operations on attributes	292
igraph_set_attribute_table — Attach an attribute table.	294
igraph_attribute_type_t — The possible types of the attributes.	295
Handling attribute combination lists	295
igraph_attribute_combination_init — Initialize attribute combina- tion list.	296
igraph_attribute_combination_add — Add combination record to at- tribute combination list.	296

igraph_attribute_combination_remove — Remove a record from an attribute combination list.	297
igraph_attribute_combination_destroy — Destroy attribute combination list.	297
igraph_attribute_combination_type_t — The possible types of attribute combinations.	297
Accessing attributes from C	298
Query attributes	299
Set attributes	312
Remove attributes	324
13. Structural properties of graphs	328
Basic properties	328
igraph_are_connected — Decides whether two vertices are connected	328
Sparsifiers	328
igraph_spanner — Calculates a spanner of a graph with a given stretch factor.	328
(Shortest)-path related functions	329
igraph_distances — Length of the shortest paths between vertices.	329
igraph_distances_dijkstra — Weighted shortest path lengths between vertices.	330
igraph_distances_bellman_ford — Weighted shortest path lengths between vertices, allowing negative weights.	331
igraph_distances_johnson — Weighted shortest path lengths between vertices, using Johnson's algorithm.	332
igraph_get_shortest_paths — Shortest paths from a vertex.	333
igraph_get_shortest_path — Shortest path from one vertex to another one.	334
igraph_get_shortest_paths_dijkstra — Weighted shortest paths from a vertex.	335
igraph_get_shortest_path_dijkstra — Weighted shortest path from one vertex to another one.	336
igraph_get_shortest_paths_bellman_ford — Weighted shortest paths from a vertex, allowing negative weights.	337
igraph_get_shortest_path_bellman_ford — Weighted shortest path from one vertex to another one.	338
igraph_get_all_shortest_paths — All shortest paths (geodesics) from a vertex.	339
igraph_get_all_shortest_paths_dijkstra — All weighted shortest paths (geodesics) from a vertex.	340
igraph_get_k_shortest_paths — k shortest paths between two vertices.	342
igraph_get_all_simple_paths — List all simple paths from one source. ...	343
igraph_average_path_length — Calculates the average unweighted shortest path length between all vertex pairs.	343
igraph_average_path_length_dijkstra — Calculates the average weighted shortest path length between all vertex pairs.	344
igraph_path_length_hist — Create a histogram of all shortest path lengths.	345
igraph_diameter — Calculates the diameter of a graph (longest geodesic).	346
igraph_diameter_dijkstra — Calculates the weighted diameter of a graph using Dijkstra's algorithm.	347
igraph_girth — The girth of a graph is the length of the shortest cycle in it.	348
igraph_eccentricity — Eccentricity of some vertices.	348
igraph_eccentricity_dijkstra — Eccentricity of some vertices, using weighted edges.	349
igraph_graph_center — Central vertices of a graph.	350
igraph_radius — Radius of a graph.	350

igraph_pseudo_diameter — Approximation and lower bound of diameter.	351
igraph_vertex_path_from_edge_path — Converts a path of edge IDs to the traversed vertex IDs.	352
Widest-path related functions	352
igraph_get_widest_path — Widest path from one vertex to another one. ...	352
igraph_get_widest_paths — Widest paths from a single vertex.	353
igraph_widest_path_widths_dijkstra — Widths of widest paths between vertices.	354
igraph_widest_path_widths_floyd_warshall — Widths of widest paths between vertices.	355
Efficiency measures	356
igraph_global_efficiency — Calculates the global efficiency of a network.	356
igraph_local_efficiency — Calculates the local efficiency around each vertex in a network.	357
igraph_average_local_efficiency — Calculates the average local efficiency in a network.	358
Neighborhood of a vertex	359
igraph_neighborhood_size — Calculates the size of the neighborhood of a given vertex.	359
igraph_neighborhood — Calculate the neighborhood of vertices.	360
igraph_neighborhood_graphs — Create graphs from the neighborhood(s) of some vertex/vertices.	360
Local scan statistics	361
"Us" statistics	361
"Them" statistics	363
Pre-calculated subsets	365
Graph components	366
igraph_subcomponent — The vertices in the same component as a given vertex.	366
igraph_connected_components — Calculates the (weakly or strongly) connected components in a graph.	366
igraph_clusters — Calculates the (weakly or strongly) connected components in a graph (deprecated alias).	367
igraph_is_connected — Decides whether the graph is (weakly or strongly) connected.	367
igraph_decompose — Decomposes a graph into connected components.	368
igraph_decompose_destroy — Frees the contents of a pointer vector holding graphs.	369
igraph_biconnected_components — Calculates biconnected components.	369
igraph_articulation_points — Finds the articulation points in a graph. ..	370
igraph_bridges — Finds all bridges in a graph.	371
Degree sequences	371
igraph_is_graphical — Is there a graph with the given degree sequence? ...	371
igraph_is_bigraphical — Is there a bipartite graph with the given bi-degree-sequence?	373
Centrality measures	373
igraph_closeness — Closeness centrality calculations for some vertices.	373
igraph_harmonic_centrality — Harmonic centrality for some vertices. ...	375
igraph_betweenness — Betweenness centrality of some vertices.	376
igraph_edge_betweenness — Betweenness centrality of the edges.	377
igraph_pagerank_algo_t — PageRank algorithm implementation	377
igraph_pagerank — Calculates the Google PageRank for the specified vertices.	378
igraph_personalized_pagerank — Calculates the personalized Google PageRank for the specified vertices.	379

igraph_personalized_pagerank_vs — Calculates the personalized Google PageRank for the specified vertices.	380
igraph_constraint — Burt's constraint scores.	382
igraph_maxdegree — The maximum degree in a graph (or set of vertices).	382
igraph_strength — Strength of the vertices, also called weighted vertex degree.	383
igraph_eigenvector_centrality — Eigenvector centrality of the vertices.	384
igraph_hub_score — Kleinberg's hub scores.	385
igraph_authority_score — Kleinberg's authority scores.	386
igraph_convergence_degree — Calculates the convergence degree of each edge in a graph.	387
Range-limited centrality measures	387
igraph_closeness_cutoff — Range limited closeness centrality.	387
igraph_harmonic_centrality_cutoff — Range limited harmonic centrality.	389
igraph_betweenness_cutoff — Range-limited betweenness centrality.	390
igraph_edge_betweenness_cutoff — Range-limited betweenness centrality of the edges.	390
Subset-limited Centrality Measures	391
igraph_betweenness_subset — Betweenness centrality for a subset of source and target vertices.	391
igraph_edge_betweenness_subset — Edge betweenness centrality for a subset of source and target vertices.	392
Centralization	393
igraph_centralization — Calculate the centralization score from the node level scores.	393
igraph_centralization_degree — Calculate vertex degree and graph centralization.	394
igraph_centralization_betweenness — Calculate vertex betweenness and graph centralization.	395
igraph_centralization_closeness — Calculate vertex closeness and graph centralization.	395
igraph_centralization_eigenvector_centrality — Calculate eigenvector centrality scores and graph centralization.	396
igraph_centralization_degree_tmax — Theoretical maximum for graph centralization based on degree.	397
igraph_centralization_betweenness_tmax — Theoretical maximum for graph centralization based on betweenness.	398
igraph_centralization_closeness_tmax — Theoretical maximum for graph centralization based on closeness.	399
igraph_centralization_eigenvector_centrality_tmax — Theoretical maximum centralization for eigenvector centrality.	400
Similarity measures	400
igraph_bibcoupling — Bibliographic coupling.	400
igraph_cocitation — Cocitation coupling.	401
igraph_similarity_jaccard — Jaccard similarity coefficient for the given vertices.	402
igraph_similarity_jaccard_pairs — Jaccard similarity coefficient for given vertex pairs.	402
igraph_similarity_jaccard_es — Jaccard similarity coefficient for a given edge selector.	403
igraph_similarity_dice — Dice similarity coefficient.	404
igraph_similarity_dice_pairs — Dice similarity coefficient for given vertex pairs.	405
igraph_similarity_dice_es — Dice similarity coefficient for a given edge selector.	406

igraph_similarity_inverse_log_weighted — Vertex similarity based on the inverse logarithm of vertex degrees.	407
Trees and forests	408
igraph_minimum_spanning_tree — Calculates one minimum spanning tree of a graph.	408
igraph_minimum_spanning_tree_unweighted — Calculates one minimum spanning tree of an unweighted graph.	409
igraph_minimum_spanning_tree_prim — Calculates one minimum spanning tree of a weighted graph.	409
igraph_random_spanning_tree — Uniformly sample the spanning trees of a graph	410
igraph_is_tree — Decides whether the graph is a tree.	411
igraph_is_forest — Decides whether the graph is a forest.	411
igraph_to_prufer — Converts a tree to its Prüfer sequence	412
Transitivity or clustering coefficient	413
igraph_transitivity_undirected — Calculates the transitivity (clustering coefficient) of a graph.	413
igraph_transitivity_local_undirected — Calculates the local transitivity (clustering coefficient) of a graph.	414
igraph_transitivity_avglocal_undirected — Average local transitivity (clustering coefficient).	414
igraph_transitivity_barrat — Weighted transitivity, as defined by A. Barrat.	415
Directedness conversion	416
igraph_to_directed — Convert an undirected graph to a directed one	416
igraph_to_undirected — Convert a directed graph to an undirected one.	417
Spectral properties	417
igraph_get_laplacian — Returns the Laplacian matrix of a graph.	417
igraph_get_laplacian_sparse — Returns the Laplacian of a graph in a sparse matrix format.	418
igraph_laplacian_normalization_t — Normalization methods for a Laplacian matrix.	419
Non-simple graphs: Multiple and loop edges	420
igraph_is_simple — Decides whether the input graph is a simple graph.	420
igraph_is_loop — Find the loop edges in a graph.	420
igraph_is_multiple — Find the multiple edges in a graph.	421
igraph_has_multiple — Check whether the graph has at least one multiple edge.	421
igraph_count_multiple — Count the number of appearances of the edges in a graph.	422
Mixing patterns	422
igraph_assortativity_nominal — Assortativity of a graph based on vertex categories.	422
igraph_assortativity — Assortativity based on numeric properties of vertices.	424
igraph_assortativity_degree — Assortativity of a graph based on vertex degree.	425
K-Cores and K-Trusses	426
igraph_coreness — Finding the coreness of the vertices in a network.	426
igraph_trussness — Finding the "trussness" of the edges in a network.	426
Topological sorting, directed acyclic graphs	427
igraph_is_dag — Checks whether a graph is a directed acyclic graph (DAG).	427
igraph_topological_sorting — Calculate a possible topological sorting of the graph.	427
igraph_feedback_arc_set — Calculates a feedback arc set of the graph using different	428
Maximum cardinality search and chordal graphs	429

igraph_maximum_cardinality_search — Maximum cardinality search.	429
igraph_is_chordal — Decides whether a graph is chordal.	430
Matchings	431
igraph_is_matching — Checks whether the given matching is valid for the given graph.	431
igraph_is_maximal_matching — Checks whether a matching in a graph is maximal.	431
igraph_maximum_bipartite_matching — Calculates a maximum matching in a bipartite graph.	432
Unfolding a graph into a tree	433
igraph_unfold_tree — Unfolding a graph into a tree, by possibly multiplying its vertices.	433
Other operations	434
igraph_density — Calculate the density of a graph.	434
igraph_reciprocity — Calculates the reciprocity of a directed graph.	434
igraph_diversity — Structural diversity index of the vertices	435
igraph_is_mutual — Check whether some edges of a directed graph are mutual.	436
igraph_avg_nearest_neighbor_degree — Average neighbor degree. ...	436
igraph_get_adjacency — Returns the adjacency matrix of a graph	437
igraph_get_adjacency_sparse — Returns the adjacency matrix of a graph in a sparse matrix format.	439
igraph_get_stochastic — Stochastic adjacency matrix of a graph	439
igraph_get_stochastic_sparse — Stochastic adjacency matrix of a graph	440
igraph_get_edgelist — Returns the list of edges in a graph	440
igraph_is_acyclic — Checks whether a graph is acyclic or not.	441
Deprecated functions	441
igraph_shortest_paths — Length of the shortest paths between vertices. ...	441
igraph_shortest_paths_dijkstra — Weighted shortest path lengths between vertices (deprecated).	442
igraph_shortest_paths_bellman_ford — Weighted shortest path lengths between vertices, allowing negative weights (deprecated).	442
igraph_shortest_paths_johnson — Weighted shortest path lengths between vertices, using Johnson's algorithm (deprecated).	442
igraph_get_stochastic_sparsemat — Stochastic adjacency matrix of a graph (deprecated).	443
igraph_get_sparsemat — Converts an igraph graph to a sparse matrix (deprecated).	443
igraph_laplacian — Returns the Laplacian matrix of a graph (deprecated). ..	444
14. Graph cycles	445
Eulerian cycles and paths	445
igraph_is_eulerian — Checks whether an Eulerian path or cycle exists	445
igraph_eulerian_cycle — Finds an Eulerian cycle	445
igraph_eulerian_path — Finds an Eulerian path	446
15. Graph visitors	447
Breadth-first search	447
igraph_bfs — Breadth-first search	447
igraph_bfs_simple — Breadth-first search, single-source version	448
igraph_bfshandler_t — Callback type for BFS function	449
Depth-first search	450
igraph_dfs — Depth-first search	450
igraph_dfshandler_t — Callback type for the DFS function	451
Random walks	452
igraph_random_walk — Performs a random walk on a graph.	452
Deprecated functions	453

igraph_random_edge_walk — Performs a random walk on a graph and re-	
turns the traversed edges.	453
16. Cliques and independent vertex sets	454
Cliques	454
igraph_cliques — Finds all or some cliques in a graph.	454
igraph_clique_size_hist — Counts cliques of each size in the graph.	454
igraph_cliques_callback — Calls a function for each clique in the	
graph.	455
igraph_clique_handler_t — Type of clique handler functions.	456
igraph_largest_cliques — Finds the largest clique(s) in a graph.	456
igraph_maximal_cliques — Finds all maximal cliques in a graph.	457
igraph_maximal_cliques_count — Count the number of maximal	
cliques in a graph	458
igraph_maximal_cliques_file — Find maximal cliques and write them	
to a file.	459
igraph_maximal_cliques_subset — Maximal cliques for a subset of	
initial vertices	459
igraph_maximal_cliques_hist — Counts the number of maximal	
cliques of each size in a graph.	460
igraph_maximal_cliques_callback — Finds maximal cliques in a	
graph and calls a function for each one.	461
igraph_clique_number — Finds the clique number of the graph.	462
Weighted cliques	462
igraph_weighted_cliques — Finds all cliques in a given weight range in	
a vertex weighted graph.	462
igraph_largest_weighted_cliques — Finds the largest weight	
clique(s) in a graph.	463
igraph_weighted_clique_number — Finds the weight of the largest	
weight clique in the graph.	464
Independent vertex sets	464
igraph_independent_vertex_sets — Finds all independent vertex sets	
in a graph.	464
igraph_largest_independent_vertex_sets — Finds the largest in-	
dependent vertex set(s) in a graph.	465
igraph_maximal_independent_vertex_sets — Finds all maximal in-	
dependent vertex sets of a graph.	466
igraph_independence_number — Finds the independence number of the	
graph.	466
17. Graph isomorphism	468
The simple interface	468
igraph_isomorphic — Decides whether two graphs are isomorphic	468
igraph_subisomorphic — Decide subgraph isomorphism.	469
The BLISS algorithm	469
igraph_bliss_sh_t — Splitting heuristics for Bliss.	470
igraph_bliss_info_t — Information about a BLISS run	470
igraph_canonical_permutation — Canonical permutation using Bliss. ...	471
igraph_isomorphic_bliss — Graph isomorphism via Bliss.	472
igraph_automorphisms — Number of automorphisms using Bliss.	472
igraph_automorphism_group — Automorphism group generators using	
Bliss.	473
The VF2 algorithm	474
igraph_isomorphic_vf2 — Isomorphism via VF2	474
igraph_count_isomorphisms_vf2 — Number of isomorphisms via VF2 ..	475
igraph_get_isomorphisms_vf2 — Collect all isomorphic mappings of	
two graphs.	476
igraph_get_isomorphisms_vf2_callback — The generic VF2 inter-	
face	477

igraph_isohandler_t — Callback type, called when an isomorphism was found	478
igraph_isocompat_t — Callback type, called to check whether two vertices or edges are compatible	479
igraph_subisomorphic_vf2 — Decide subgraph isomorphism using VF2 ..	479
igraph_count_subisomorphisms_vf2 — Number of subgraph isomorphisms using VF2	480
igraph_get_subisomorphisms_vf2 — Return all subgraph isomorphic mappings.	481
igraph_get_subisomorphisms_vf2_callback — Generic VF2 function for subgraph isomorphism problems	482
Deprecated aliases	484
The LAD algorithm	484
igraph_subisomorphic_lad — Check subgraph isomorphism with the LAD algorithm	485
Functions for small graphs	486
igraph_isoclass — Determine the isomorphism class of small graphs.	486
igraph_isoclass_subgraph — The isomorphism class of a subgraph of a graph.	486
igraph_isoclass_create — Creates a graph from the given isomorphism class.	487
igraph_graph_count — The number of unlabelled graphs on the given number of vertices.	488
Utility functions	488
igraph_permute_vertices — Permute the vertices.	488
igraph_simplify_and_colorize — Simplify the graph and compute self-loop and edge multiplicities.	489
Deprecated functions	489
igraph_isomorphic_34 — Graph isomorphism for 3-4 vertices (deprecated alias).	489
18. Graph coloring	491
igraph_vertex_coloring_greedy — Computes a vertex coloring using a greedy algorithm.	491
igraph_coloring_greedy_t — Ordering heuristics for greedy graph coloring.	491
igraph_is_perfect — Checks if the graph is perfect.	492
19. Graph motifs, dyad census and triad census	493
igraph_dyad_census — Calculating the dyad census as defined by Holland and Leinhardt.	493
igraph_triad_census — Triad census, as defined by Davis and Leinhardt	493
Finding triangles	495
igraph_adjacent_triangles — Count the number of triangles a vertex is part of.	495
igraph_list_triangles — Find all triangles in a graph.	495
Graph motifs	496
igraph_motifs_randesu — Count the number of motifs in a graph.	496
igraph_motifs_randesu_no — Count the total number of motifs in a graph.	497
igraph_motifs_randesu_estimate — Estimate the total number of motifs in a graph.	497
igraph_motifs_randesu_callback — Finds motifs in a graph and calls a function for each of them.	498
igraph_motifs_handler_t — Callback type for igraph_motifs_randesu_callback	499
20. Generating layouts for graph drawing	501
2D layout generators	501
igraph_layout_random — Places the vertices uniform randomly on a plane.	501

igraph_layout_circle — Places the vertices uniformly on a circle, in the order of vertex IDs.	501
igraph_layout_star — Generates a star-like layout.	502
igraph_layout_grid — Places the vertices on a regular grid on the plane.	502
igraph_layout_graphopt — Optimizes vertex layout via the graphopt algorithm.	503
igraph_layout_bipartite — Simple layout for bipartite graphs.	504
The DrL layout generator	504
igraph_layout_fruchterman_reingold — Places the vertices on a plane according to the Fruchterman-Reingold algorithm.	508
igraph_layout_kamada_kawai — Places the vertices on a plane according to the Kamada-Kawai algorithm.	510
igraph_layout_gem — Layout graph according to GEM algorithm.	511
igraph_layout_davidson_harel — Davidson-Harel layout algorithm	512
igraph_layout_mds — Place the vertices on a plane using multidimensional scaling.	513
igraph_layout_lgl — Force based layout algorithm for large graphs.	513
Layouts for trees and acyclic graphs	514
igraph_layout_reingold_tilford — Reingold-Tilford layout for tree graphs	514
igraph_layout_reingold_tilford_circular — Circular Reingold-Tilford layout for trees	515
igraph_roots_for_tree_layout — Roots suitable for a nice tree layout. ..	516
igraph_layout_sugiyama — Sugiyama layout algorithm for layered directed acyclic graphs.	517
igraph_layout_umap — Layout using Uniform Manifold Approximation and Projection for Dimension Reduction	518
3D layout generators	520
igraph_layout_random_3d — Places the vertices uniform randomly in a cube.	520
igraph_layout_sphere — Places vertices (more or less) uniformly on a sphere.	520
igraph_layout_grid_3d — Places the vertices on a regular grid in the 3D space.	521
igraph_layout_fruchterman_reingold_3d — 3D Fruchterman-Reingold algorithm.	521
igraph_layout_kamada_kawai_3d — 3D version of the Kamada-Kawai layout generator.	522
igraph_layout_umap_3d — 3D layout using UMAP.	523
Merging layouts	524
igraph_layout_merge_dla — Merge multiple layouts by using a DLA algorithm	524
21. Reading and writing graphs from and to files	526
Simple edge list and similar formats	526
igraph_read_graph_edgelist — Reads an edge list from a file and creates a graph.	526
igraph_write_graph_edgelist — Writes the edge list of a graph to a file.	526
igraph_read_graph_ncol — Reads an .ncol file used by LGL.	527
igraph_write_graph_ncol — Writes the graph to a file in .ncol format. ..	528
igraph_read_graph_lgl — Reads a graph from an .lgl file	528
igraph_write_graph_lgl — Writes the graph to a file in .lgl format	530
igraph_read_graph_dimacs_flow — Read a graph in DIMACS format. ...	530
igraph_write_graph_dimacs_flow — Write a graph in DIMACS format.	531
Binary formats	532
igraph_read_graph_graphdb — Read a graph in the binary graph database format.	532

GraphML format	533
igraph_read_graph_graphml — Reads a graph from a GraphML file.	533
igraph_write_graph_graphml — Writes the graph to a file in GraphML format.	533
GML format	534
igraph_read_graph_gml — Read a graph in GML format.	534
igraph_write_graph_gml — Write the graph to a stream in GML format. ...	535
Pajek format	536
igraph_read_graph_pajek — Reads a file in Pajek format	536
igraph_write_graph_pajek — Writes a graph to a file in Pajek format.	537
UCINET's DL file format	538
igraph_read_graph_dl — Read a file in the DL format of UCINET	538
Graphviz format	539
igraph_write_graph_dot — Write the graph to a stream in DOT format	539
Convenience functions for locale change	539
igraph_enter_safelocale — Temporarily set the C locale.	539
igraph_exit_safelocale — Temporarily set the C locale.	540
Deprecated functions	541
igraph_read_graph_dimacs — Read a graph in DIMACS format (depre- cated alias).	541
igraph_write_graph_dimacs — Write a graph in DIMACS format (dep- recated alias).	541
22. Maximum flows, minimum cuts and related measures	542
Maximum flows	542
igraph_maxflow — Maximum network flow between a pair of vertices	542
igraph_maxflow_value — Maximum flow in a network with the push/rela- bel algorithm	543
igraph_dominator_tree — Calculates the dominator tree of a flowgraph	544
igraph_maxflow_stats_t — A simple data type to return some statistics from the	545
Cuts and minimum cuts	545
igraph_st_mincut — Minimum cut between a source and a target vertex	545
igraph_st_mincut_value — The minimum s-t cut in a graph	546
igraph_all_st_cuts — List all edge-cuts between two vertices in a directed graph	547
igraph_all_st_mincuts — All minimum s-t cuts of a directed graph	548
igraph_mincut — Calculates the minimum cut in a graph.	549
igraph_mincut_value — The minimum edge cut in a graph	550
igraph_gomory_hu_tree — Gomory-Hu tree of a graph.	550
Connectivity	551
igraph_st_edge_connectivity — Edge connectivity of a pair of ver- tices	551
igraph_edge_connectivity — The minimum edge connectivity in a graph.	552
igraph_st_vertex_connectivity — The vertex connectivity of a pair of vertices	552
igraph_vertex_connectivity — The vertex connectivity of a graph	553
Edge- and vertex-disjoint paths	554
igraph_edge_disjoint_paths — The maximum number of edge-disjoint paths between two vertices.	554
igraph_vertex_disjoint_paths — Maximum number of vertex-disjoint paths between two vertices.	555
Graph adhesion and cohesion	555
igraph_adhesion — Graph adhesion, this is (almost) the same as edge con- nectivity.	555
igraph_cohesion — Graph cohesion, this is the same as vertex connectivity. ..	556
Cohesive blocks	557

igraph_cohesive_blocks — Identifies the hierarchical cohesive block structure of a graph	557
23. Vertex separators	558
igraph_is_separator — Would removing this set of vertices disconnect the graph?	558
igraph_is_minimal_separator — Decides whether a set of vertices is a minimal separator.	558
igraph_all_minimal_st_separators — List all vertex sets that are minimal (s,t) separators for some s and t.	559
igraph_minimum_size_separators — Find all minimum size separating vertex sets.	560
igraph_even_tarjan_reduction — Even-Tarjan reduction of a graph.	560
24. Detecting community structure	562
Common functions related to community structure	562
igraph_modularity — Calculates the modularity of a graph with respect to some clusters or vertex types.	562
igraph_modularity_matrix — Calculates the modularity matrix.	563
igraph_community_optimal_modularity — Calculate the community structure with the highest modularity value	564
igraph_community_to_membership — Create membership vector from community structure dendrogram	565
igraph_reindex_membership — Makes the IDs in a membership vector continuous	566
igraph_compare_communities — Compares community structures using various metrics.	566
igraph_split_join_distance — Calculates the split-join distance of two community structures	567
Community structure based on statistical mechanics	568
igraph_community_spinglass — Community detection based on statistical mechanics	568
igraph_community_spinglass_single — Community of a single node based on statistical mechanics	570
Community structure based on eigenvectors of matrices	572
igraph_community_leading_eigenvector — Leading eigenvector community finding (proper version).	572
igraph_community_leading_eigenvector_callback_t — Callback for the leading eigenvector community finding method.	574
igraph_le_community_to_membership — Vertex membership from the leading eigenvector community structure	575
Walktrap: Community structure based on random walks	576
igraph_community_walktrap — This function is the implementation of the Walktrap community	576
Edge betweenness based community detection	577
igraph_community_edge_betweenness — Community finding based on edge betweenness.	577
igraph_community_eb_get_merges — Calculating the merges, i.e. the dendrogram for an edge betweenness community structure.	578
Community structure based on the optimization of modularity	579
igraph_community_fastgreedy — Finding community structure by greedy optimization of modularity.	579
igraph_community_multilevel — Finding community structure by multi-level optimization of modularity.	580
igraph_community_leiden — Finding community structure using the Leiden algorithm.	581
Fluid communities	583
igraph_community_fluid_communities — Community detection based on fluids interacting on the graph.	583
Label propagation	584

igraph_community_label_propagation — Community detection based on label propagation.	584
The InfoMAP algorithm	585
igraph_community_infomap — Find community structure that minimizes the expected description length of a random walker trajectory.	585
25. Graphlets	587
Introduction	587
Performing graphlet decomposition	587
igraph_graphlets — Calculate graphlets basis and project the graph on it	587
igraph_graphlets_candidate_basis — Calculate a candidate graphlets basis	588
igraph_graphlets_project — Project a graph on a graphlets basis	588
26. Hierarchical random graphs	590
Introduction	590
Representing HRGs	590
igraph_hrg_t — Data structure to store a hierarchical random graph	590
igraph_hrg_init — Allocate memory for a HRG.	591
igraph_hrg_destroy — Deallocate memory for an HRG.	591
igraph_hrg_size — Returns the size of the HRG, the number of leaf nodes. ...	591
igraph_hrg_resize — Resize a HRG.	592
Fitting HRGs	592
igraph_hrg_fit — Fit a hierarchical random graph model to a network.	592
igraph_hrg_consensus — Calculate a consensus tree for a HRG.	593
HRG sampling	593
igraph_hrg_sample — Sample from a hierarchical random graph model.	593
igraph_hrg_game — Generate a hierarchical random graph.	594
Conversion to and from igraph graphs	594
igraph_hrg_dendrogram — Create a dendrogram from a hierarchical random graph.	594
igraph_hrg_create — Create a HRG from an igraph graph.	595
Predicting missing edges	595
igraph_hrg_predict — Predict missing edges in a graph, based on HRG models.	595
27. Embedding of graphs	597
Spectral embedding	597
igraph_adjacency_spectral_embedding — Adjacency spectral embedding	597
igraph_laplacian_spectral_embedding — Spectral embedding of the Laplacian of a graph	598
igraph_dim_select — Dimensionality selection	599
28. Graph operators	601
Union and intersection	601
igraph_disjoint_union — Creates the union of two disjoint graphs	601
igraph_disjoint_union_many — The disjoint union of many graphs.	601
igraph_union — Calculates the union of two graphs.	602
igraph_union_many — Creates the union of many graphs.	603
igraph_intersection — Collect the common edges from two graphs.	603
igraph_intersection_many — The intersection of more than two graphs. ..	604
Other set-like operators	605
igraph_difference — Calculate the difference of two graphs	605
igraph_complementer — Create the complementer of a graph	605
igraph_compose — Calculates the composition of two graphs.	606
Miscellaneous operators	607
igraph_connect_neighborhood — Graph power: connect each vertex to its neighborhood.	607
igraph_contract_vertices — Replace multiple vertices with a single one.	608

igraph_induced_subgraph — Creates a subgraph induced by the specified vertices.	608
igraph_linegraph — Create the line graph of a graph.	609
igraph_simplify — Removes loop and/or multiple edges from the graph.	609
igraph_subgraph_edges — Creates a subgraph with the specified edges and their endpoints.	610
igraph_reverse_edges — Reverses some edges of a directed graph.	611
29. Using BLAS, LAPACK and ARPACK for igraph matrices and graphs	612
BLAS interface in igraph	612
igraph_blas_ddot — Dot product of two vectors.	612
igraph_blas_dnorm2 — Euclidean norm of a vector.	612
igraph_blas_dgemv — Matrix-vector multiplication using BLAS, vector version.	613
igraph_blas_dgemm — Matrix-matrix multiplication using BLAS.	613
igraph_blas_dgemv_array — Matrix-vector multiplication using BLAS, array version.	614
LAPACK interface in igraph	615
Matrix factorization, solving linear systems	615
Eigenvalues and eigenvectors of matrices	617
ARPACK interface in igraph	621
Data structures	622
ARPACK solvers	627
30. Bipartite, i.e. two-mode graphs	630
Bipartite networks in igraph	630
Create two-mode networks	630
igraph_create_bipartite — Create a bipartite graph.	630
igraph_full_bipartite — Create a full bipartite network.	631
igraph_bipartite_game — Generate a bipartite random graph (similar to Erdős-Rényi).	631
Incidence matrices	632
igraph_incidence — Creates a bipartite graph from an incidence matrix.	632
igraph_get_incidence — Convert a bipartite graph into an incidence matrix.	633
Project two-mode graphs	634
igraph_bipartite_projection_size — Calculate the number of vertices and edges in the bipartite projections.	634
igraph_bipartite_projection — Create one or both projections of a bipartite (two-mode) network.	635
Other operations on bipartite graphs	636
igraph_is_bipartite — Check whether a graph is bipartite.	636
31. Advanced igraph programming	637
Using igraph in multi-threaded programs	637
IGRAPH_THREAD_SAFE — Specifies whether igraph was built in thread-safe mode.	637
Thread-safe ARPACK library	637
Thread-safety of random number generators	637
Progress handlers	637
About progress handlers	637
Setting up progress handlers	638
Invoking the progress handler	639
Writing progress handlers	640
Writing igraph functions with progress reporting	641
Multi-threaded programs	641
Status handlers	641
Status reporting	641
Setting up status handlers	641
Invoking the status handler	642
32. Non-igraph related functions	645

igraph version number	645
igraph_version — Return the version of the igraph C library	645
Running mean of a time series	645
igraph_running_mean — Calculates the running mean of a vector.	645
Random sampling from very long sequences	646
igraph_random_sample — Generates an increasing random sequence of in-	
tegers.	646
Random sampling of spatial points	647
igraph_sample_sphere_surface — Sample points uniformly from the	
surface of a sphere.	647
igraph_sample_sphere_volume — Sample points uniformly from the	
volume of a sphere.	647
igraph_sample_dirichlet — Sample points from a Dirichlet distribution. ..	648
Convex hull of a set of points on a plane	648
igraph_convex_hull — Determines the convex hull of a given set of points	
in the 2D plane	648
Fitting power-law distributions to empirical data	649
igraph_plfit_result_t — Result of fitting a power-law distribution to a	
vector	649
igraph_power_law_fit — Fits a power-law distribution to a vector of num-	
bers	650
igraph_plfit_result_calculate_p_value — Calculates the p-value	
of a fitted power-law model	651
Comparing floats with a tolerance	652
igraph_cmp_epsilon — Compare two double-precision floats with a toler-	
ance.	652
igraph_almost_equals — Compare two double-precision floats with a tol-	
erance.	652
igraph_complex_almost_equals — Compare two complex numbers	
with a tolerance.	652
33. Licenses for igraph and this manual	654
THE GNU GENERAL PUBLIC LICENSE	654
Preamble	654
GNU GENERAL PUBLIC LICENSE	654
How to Apply These Terms to Your New Programs	657
The GNU Free Documentation License	658
0. PREAMBLE	658
1. APPLICABILITY AND DEFINITIONS	659
2. VERBATIM COPYING	660
3. COPYING IN QUANTITY	660
4. MODIFICATIONS	660
5. COMBINING DOCUMENTS	662
6. COLLECTIONS OF DOCUMENTS	662
7. AGGREGATION WITH INDEPENDENT WORKS	662
8. TRANSLATION	662
9. TERMINATION	663
10. FUTURE REVISIONS OF THIS LICENSE	663
G.1.1 ADDENDUM: How to use this License for your documents	663
Index	664

List of Examples

4.1. File examples/simple/creation.c	16
4.2. File examples/simple/igraph_copy.c	17
4.3. File examples/simple/igraph_is_directed.c	19
4.4. File examples/simple/igraph_get_eid.c	22
4.5. File examples/simple/igraph_get_eids.c	23
4.6. File examples/simple/igraph_neighbors.c	24
4.7. File examples/simple/igraph_degree.c	25
4.8. File examples/simple/creation.c	26
4.9. File examples/simple/creation.c	27
4.10. File examples/simple/igraph_delete_edges.c	27
4.11. File examples/simple/igraph_delete_vertices.c	28
4.12. File examples/simple/igraph_delete_vertices.c	28
7.1. File examples/simple/igraph_fisher_yates_shuffle.c	59
7.2. File examples/simple/igraph_vector_int_list_sort.c	65
7.3. File examples/simple/igraph_vector_int_list_sort.c	66
7.4. File examples/simple/igraph_sparsemat.c	121
7.5. File examples/simple/igraph_sparsemat3.c	121
7.6. File examples/simple/igraph_sparsemat4.c	121
7.7. File examples/simple/igraph_sparsemat6.c	121
7.8. File examples/simple/igraph_sparsemat7.c	121
7.9. File examples/simple/igraph_sparsemat8.c	121
7.10. File examples/simple/dqueue.c	154
7.11. File examples/simple/igraph_strvector.c	161
7.12. File examples/simple/adjlist.c	184
8.1. File examples/simple/random_seed.c	206
9.1. File examples/simple/igraph_create.c	207
9.2. File examples/simple/igraph_small.c	208
9.3. File examples/simple/igraph_adjacency.c	209
9.4. File examples/simple/igraph_weighted_adjacency.c	210
9.5. File examples/simple/igraph_star.c	212
9.6. File examples/simple/igraph_ring.c	215
9.7. File examples/simple/igraph_kary_tree.c	215
9.8. File examples/simple/igraph_symmetric_tree.c	216
9.9. File examples/simple/igraph_regular_tree.c	217
9.10. File examples/simple/igraph_full.c	218
9.11. File examples/simple/igraph_realize_degree_sequence.c	222
9.12. File examples/simple/igraph_lcf.c	225
9.13. File examples/simple/igraph_atlas.c	226
9.14. File examples/simple/igraph_grg_game.c	230
9.15. File examples/simple/igraph_barabasi_game.c	232
9.16. File examples/simple/igraph_barabasi_game2.c	232
9.17. File examples/simple/igraph_erdos_renyi_game.c	232
9.18. File examples/simple/igraph_degree_sequence_game.c	236
10.1. File examples/simple/igraph_deterministic_optimal_imitation.c	259
10.2. File examples/simple/igraph_roulette_wheel_imitation.c	262
10.3. File examples/simple/igraph_stochastic_imitation.c	264
11.1. File examples/simple/igraph_vs_nonadj.c	268
11.2. File examples/simple/igraph_vs_vector.c	269
11.3. File examples/simple/igraph_vs_seq.c	271
11.4. File examples/simple/igraph_es_pairs.c	281
11.5. File examples/simple/igraph_vs_seq.c	290
12.1. File examples/simple/cattributes.c	299
12.2. File examples/simple/cattributes2.c	299
12.3. File examples/simple/cattributes3.c	299
12.4. File examples/simple/cattributes4.c	299

13.1. File examples/simple/dijkstra.c	331
13.2. File examples/simple/bellman_ford.c	332
13.3. File examples/simple/igraph_get_shortest_paths.c	334
13.4. File examples/simple/igraph_get_shortest_paths_dijkstra.c	336
13.5. File examples/simple/igraph_get_all_shortest_paths_dijkstra.c	342
13.6. File examples/simple/igraph_average_path_length.c	344
13.7. File examples/simple/igraph_grg_game.c	345
13.8. File examples/simple/igraph_diameter.c	347
13.9. File examples/simple/igraph_girth.c	348
13.10. File examples/simple/igraph_eccentricity.c	349
13.11. File examples/simple/igraph_radius.c	351
13.12. File examples/simple/igraph_decompose.c	369
13.13. File examples/simple/igraph_biconnected_components.c	370
13.14. File examples/simple/igraph_pagerank.c	379
13.15. File examples/simple/eigenvector_centrality.c	385
13.16. File examples/simple/centralization.c	394
13.17. File examples/simple/igraph_cocitation.c	401
13.18. File examples/simple/igraph_cocitation.c	402
13.19. File examples/simple/igraph_similarity.c	402
13.20. File examples/simple/igraph_similarity.c	403
13.21. File examples/simple/igraph_similarity.c	404
13.22. File examples/simple/igraph_similarity.c	405
13.23. File examples/simple/igraph_similarity.c	406
13.24. File examples/simple/igraph_similarity.c	407
13.25. File examples/simple/igraph_similarity.c	408
13.26. File examples/simple/igraph_minimum_spanning_tree.c	409
13.27. File examples/simple/igraph_minimum_spanning_tree.c	410
13.28. File examples/simple/igraph_kary_tree.c	411
13.29. File examples/simple/igraph_transitivity.c	413
13.30. File examples/simple/igraph_to_undirected.c	417
13.31. File examples/simple/igraph_get_laplacian.c	418
13.32. File examples/simple/igraph_get_laplacian_sparse.c	419
13.33. File examples/simple/igraph_is_loop.c	421
13.34. File examples/simple/igraph_is_multiple.c	421
13.35. File examples/simple/igraph_has_multiple.c	422
13.36. File examples/simple/igraph_assortativity_nominal.c	423
13.37. File examples/simple/igraph_assortativity_degree.c	426
13.38. File examples/simple/igraph_topological_sorting.c	428
13.39. File examples/simple/igraph_feedback_arc_set.c	429
13.40. File examples/simple/igraph_feedback_arc_set_ip.c	429
13.41. File examples/simple/igraph_maximum_bipartite_matching.c	431
13.42. File examples/simple/igraph_maximum_bipartite_matching.c	432
13.43. File examples/simple/igraph_maximum_bipartite_matching.c	433
13.44. File examples/simple/igraph_reciprocity.c	435
13.45. File examples/simple/igraph_knn.c	437
15.1. File examples/simple/igraph_bfs.c	448
15.2. File examples/simple/igraph_bfs_callback.c	448
15.3. File examples/simple/igraph_bfs_simple.c	449
16.1. File examples/simple/igraph_cliques.c	454
16.2. File examples/simple/igraph_maximal_cliques.c	458
16.3. File examples/simple/igraph_maximal_cliques.c	459
16.4. File examples/simple/igraph_independent_sets.c	465
17.1. File examples/simple/igraph_isomorphic_vf2.c	475
17.2. File examples/simple/igraph_subisomorphic_lad.c	485
18.1. File examples/simple/igraph_coloring.c	491
19.1. File examples/simple/igraph_list_triangles.c	496
19.2. File examples/simple/igraph_motifs_randesu.c	497
19.3. File examples/simple/igraph_motifs_randesu.c	499

20.1. File examples/simple/igraph_layout_reingold_tilford.c	515
21.1. File examples/simple/igraph_read_graph_lgl.c	529
21.2. File examples/simple/igraph_write_graph_lgl.c	530
21.3. File examples/simple/igraph_read_graph_graphdb.c	533
21.4. File examples/simple/graphml.c	533
21.5. File examples/simple/graphml.c	534
21.6. File examples/simple/gml.c	535
21.7. File examples/simple/gml.c	536
21.8. File examples/simple/foreign.c	537
21.9. File examples/simple/igraph_write_graph_pajek.c	538
21.10. File examples/simple/igraph_read_graph_dl.c	539
21.11. File examples/simple/dot.c	539
21.12. File examples/simple/safelocale.c	540
22.1. File examples/simple/flow.c	543
22.2. File examples/simple/flow2.c	543
22.3. File examples/simple/dominator_tree.c	545
22.4. File examples/simple/igraph_all_st_mincuts.c	548
22.5. File examples/simple/igraph_mincut.c	549
22.6. File examples/simple/cohesive_blocks.c	557
23.1. File examples/simple/igraph_is_separator.c	558
23.2. File examples/simple/igraph_is_minimal_separator.c	559
23.3. File examples/simple/igraph_minimal_separators.c	559
23.4. File examples/simple/igraph_minimum_size_separators.c	560
23.5. File examples/simple/even_tarjan.c	561
24.1. File examples/simple/igraph_community_optimal_modularity.c	565
24.2. File examples/simple/igraph_community_leading_eigenvector.c	572
24.3. File examples/simple/walktrap.c	577
24.4. File examples/simple/igraph_community_edge_betweenness.c	578
24.5. File examples/simple/igraph_community_fastgreedy.c	580
24.6. File examples/simple/igraph_community_multilevel.c	581
24.7. File examples/simple/igraph_community_leiden.c	583
24.8. File examples/simple/igraph_community_label_propagation.c	585
28.1. File examples/simple/igraph_disjoint_union.c	601
28.2. File examples/simple/igraph_union.c	603
28.3. File examples/simple/igraph_union.c	603
28.4. File examples/simple/igraph_intersection.c	604
28.5. File examples/simple/igraph_difference.c	605
28.6. File examples/simple/igraph_complementer.c	606
28.7. File examples/simple/igraph_compose.c	607
28.8. File examples/simple/igraph_simplify.c	610
29.1. File examples/simple/blas.c	612
29.2. File examples/simple/blas.c	613
29.3. File examples/simple/blas_dgemm.c	614
29.4. File examples/simple/igraph_lapack_dgesv.c	616
29.5. File examples/simple/igraph_lapack_dsyevr.c	618
29.6. File examples/simple/igraph_lapack_dgeev.c	619
29.7. File examples/simple/igraph_lapack_dgeevx.c	621
30.1. File examples/simple/igraph_bipartite_create.c	630
30.2. File examples/simple/igraph_bipartite_projection.c	635
30.3. File examples/simple/igraph_bipartite_projection.c	636
32.1. File examples/simple/igraph_version.c	645
32.2. File examples/simple/igraph_random_sample.c	646
32.3. File examples/simple/igraph_convex_hull.c	649
32.4. File examples/simple/igraph_power_law_fit.c	651

Chapter 1. Introduction

igraph is a library for creating and manipulating graphs. You can look at it in two ways: first, igraph contains the implementation of quite a lot of graph algorithms. These include classic graph algorithms like graph isomorphism, graph girth and connectivity and also the new wave graph algorithms like transitivity, graph motifs and community structure detection. Skim through the table of contents or the index of this book to get an impression of what is available.

Second, igraph provides a platform for developing and/or implementing graph algorithms. It has an efficient data structure for representing graphs, and a number of other data structures like flexible vectors, stacks, heaps, queues, adjacency lists that are useful for implementing graph algorithms. In fact these data structures evolved along with the implementation of the classic and non-classic graph algorithms which make up the major part of the igraph library. This way, they were fine-tuned and checked for correctness several times.

Our main goal with developing igraph was to create a graph library which is efficient on large, but not extremely large graphs. More precisely, it is assumed that the graph(s) fit into the physical memory of the computer. Nowadays this means graphs with several million vertices and/or edges. Our definition of efficient is that it runs fast, both in theory and (more importantly) in practice.

We believe that one of the big strengths of igraph is that it can be embedded into a higher-level language or environment. Three such embeddings (or interfaces if you look at them another way) are currently being developed by us: an R package, a Python extension module, and a Mathematica (Wolfram Language) package. Others are likely to come. High level languages such as R or Python make it possible to use graph routines with much greater comfort, without actually writing a single line of C code. They have some, usually very small, speed penalty compared to the C version, but add ease of use and much flexibility. This manual, however, covers only the C library. If you want to use Python, R or the Wolfram Language, please see the documentation written specifically for these interfaces and come back here only if you are interested in some detail which is not covered in those documents.

We still consider igraph as a child project. It has much room for development and we are sure that it will improve a lot in the near future. Any feedback we can get from the users is very important for us, as most of the time these questions and comments guide us in what to add and what to improve.

igraph is open source and distributed under the terms of the GNU GPL. We strongly believe that all the algorithms used in science, let that be graph theory or not, should have an efficient open-source implementation allowing use and modification for anyone.

igraph is free software

igraph library

Copyright (C) 2003-2004 Gábor Csárdi <csardi.gabor@gmail.com>

Copyright (C) 2005-2019 Gábor Csárdi <csardi.gabor@gmail.com> and Tamás Nepusz <ntamas@gmail.com>

Copyright (C) 2020-2022 The igraph development team

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc.

Citing igraph

To cite igraph in publications, please use the following reference:

Gábor Csárdi, Tamás Nepusz: The igraph software package for complex network research. *InterJournal Complex Systems*, 1695, 2006.

The igraph C library is assigned the DOI 10.5281/zenodo.3630268 [<https://doi.org/10.5281/zenodo.3630268>] on Zenodo.

Chapter 2. Installation

Prerequisites

To build igraph from sources, you will need at least:

- CMake [<https://cmake.org>] 3.18 or later
- C and C++ compilers

Visual Studio 2015 and later are supported. Earlier Visual Studio versions may or may not work.

Certain features also require the following libraries:

- libxml2 [<http://www.xmlsoft.org/>], required for GraphML support

igraph bundles a number of libraries for convenience. However, it is preferable to use external versions of these libraries, which may improve performance. These are:

- GMP [<https://gmplib.org/>] (the bundled alternative is Mini-GMP)
- GLPK [<https://www.gnu.org/software/glpk/>] (version 4.57 or later)
- ARPACK [<https://www.caam.rice.edu/software/ARPACK/>]
- A library providing a BLAS [<https://www.netlib.org/blas/>] API (available by default on macOS; OpenBLAS [<https://www.openblas.net>] is one option on other systems)
- A library providing a LAPACK [<https://www.netlib.org/lapack/>] API (available by default on macOS; OpenBLAS [<https://openblas.net>] is one option on other systems)

When building the development version of igraph, `bison`, `flex` and `git` are also required. Released versions do not require these tools.

To run the tests, `diff` is also required.

Installation

General build instructions

igraph uses a CMake-based build system [<https://cmake.org/cmake/help/latest/guide/user-interaction/index.html>]. To compile it,

- Enter the directory where the igraph sources are:

```
$ cd igraph
```

- Create a new directory. This is where igraph will be built:

```
$ mkdir build
$ cd build
```

- Run CMake, which will automatically configure igraph, and report the configuration:

```
$ cmake ..
```

To set a non-default installation location, such as `/opt/local`, use:

```
cmake .. -DCMAKE_INSTALL_PREFIX=/opt/local
```

- Check the output carefully, and ensure that all features you need are enabled. If CMake could not find certain libraries, some features such as GraphML support may have been automatically disabled.
- There are several ways to adjust the configuration:
 - Run `ccmake ..` on Unix-like systems or `cmake-gui` on Windows for a convenient interface.
 - Simply edit the `CMakeCache.txt` file. Some of the relevant options are listed below.
- Once the configuration has been adjusted, run `cmake ..` again.
- Once `igraph` has been successfully configured, it can be built, tested and installed using:

```
$ cmake --build .  
$ cmake --build . --target check  
$ cmake --install .
```

Specific instructions for Windows

Microsoft Visual Studio

With Visual Studio, the steps to build `igraph` are generally the same as above. However, since the Visual Studio CMake generator is a multi-configuration one, we must specify the configuration (typically Release or Debug) with each build command using the `--config` option:

```
mkdir build  
cd build  
cmake ..  
cmake --build . --config Release  
cmake --build . --target check --config Release
```

When building the development version, `bison` and `flex` must be available on the system. `winflexbison` [<https://github.com/lexxmark/winflexbison>] for Bison version 3.x can be useful for this purpose—make sure that the executables are in the system `PATH`. The easiest installation option is probably by installing `winflexbison3` from the Chocolatey package manager [<https://chocolatey.org/packages/winflexbison3>].

vcpkg

Most external dependencies can be conveniently installed using `vcpkg` [<https://github.com/microsoft/vcpkg#quick-start-windows>]. Note that `igraph` bundles all dependencies except `libxml2`, which is needed for GraphML support.

In order to use `vcpkg` integrate it in the build environment by executing `vcpkg.exe integrate install` on the command line. When configuring `igraph`, point CMake to the correct `vcpkg.cmake` file using `-DCMAKE_TOOLCHAIN_FILE=...`, as instructed.

Additionally, it might be that you need to set the appropriate so-called triplet using `-DVCPKG_TARGET_TRIPLET` when running `cmake`, for example, setting it to `x64-windows` when using shared builds of packages or `x64-windows-static` when using static builds. Similarly, you also need

to specify this target triplet when installing packages. For example, to install `libxml2` as a shared library, use `vcpkg.exe install libxml2:x64-windows` and to install `libxml2` as a static library, use `vcpkg.exe install libxml2:x64-windows-static`. In addition, there is the possibility to use a static library with dynamic runtime linking using the `x64-windows-static-md` triplet.

MSYS2

MSYS2 can be installed from [msys2.org](https://www.msys2.org/) [https://www.msys2.org/]. After installing MSYS2, ensure that it is up to date by opening a terminal and running `pacman -Syuu`.

The instructions below assume that you want to compile for a 64-bit target.

Install the following packages using `pacman -S`.

- Minimal requirements: `mingw-w64-x86_64-toolchain`, `mingw-w64-x86_64-cmake`.
- Optional dependencies that enable certain features: `mingw-w64-x86_64-gmp`, `mingw-w64-x86_64-libxml2`
- Optional external libraries for better performance: `mingw-w64-x86_64-openblas`, `mingw-w64-x86_64-suitesparse`, `mingw-w64-x86_64-arpack`, `mingw-w64-x86_64-glpk`
- Only needed for running the tests: `diffutils`
- Required only when building the development version: `git`, `bison`, `flex`

The following command will install of these at once:

```
pacman -S \
  mingw-w64-x86_64-toolchain mingw-w64-x86_64-cmake \
  mingw-w64-x86_64-gmp mingw-w64-x86_64-libxml2 \
  mingw-w64-x86_64-openblas mingw-w64-x86_64-suitesparse mingw-w64-x86_64-arpack \
  mingw-w64-x86_64-glpk diffutils git bison flex
```

In order to build `igraph`, follow the **General build instructions** above, paying attention to the following:

- When using MSYS2, start the “MSYS2 MinGW 64-bit” terminal, and *not* the “MSYS2 MSYS” one.
- Be sure to install the `mingw-w64-x86_64-cmake` package and not the `cmake` one. The latter will not work.
- When running `cmake`, pass the option `-G"MSYS Makefiles"`.
- Note that `ccmake` is not currently available. `cmake-gui` can be used only if the `mingw-w64-x86_64-qt5` package is installed.

Notable configuration options

The following options may be set to ON or OFF. Some of them have an AUTO setting, which chooses a reasonable default based on what libraries are available on the current system.

- `igraph` bundles some of its dependencies for convenience. The `IGRAPH_USE_INTERNAL_XXX` flags control whether these should be used instead of external versions. Set them to ON to use the bundled (“vendored”) versions. Generally, external versions are preferable as they may be newer and usually provide better performance.

- `IGRAPH_GLPK_SUPPORT`: whether to make use of the GLPK [<https://www.gnu.org/software/glpk/>] library. Some features, such as finding a minimum feedback arc set or finding communities through exact modularity optimization, require this.
- `IGRAPH_GRAPHML_SUPPORT`: whether to enable support for reading and writing GraphML [<http://graphml.graphdrawing.org/>] files. Requires the libxml2 [<http://xmlsoft.org/>] library.
- `IGRAPH_OPENMP_SUPPORT`: whether to use OpenMP parallelization to accelerate certain functions such as PageRank calculation. Compiler support is required.
- `IGRAPH_ENABLE_LTO`: whether to build igraph with link-time optimization, which improves performance. Not supported with all compilers.
- `IGRAPH_ENABLE_TLS`: whether to enable thread-local storage. Required when using igraph from multiple threads.
- `IGRAPH_WARNINGS_AS_ERRORS`: whether to treat compiler warnings as errors. We strive to eliminate all compiler warnings during development so this switch is turned on by default. If your compiler prints warnings for some parts of the code that we did not anticipate, you can turn off this option to prevent the warnings from stopping the compilation.
- `BUILD_SHARED_LIBS` [https://cmake.org/cmake/help/latest/variable/BUILD_SHARED_LIBS.html]: whether to build a shared library instead of a static one.
- `BLA_VENDOR`: controls which library to use for BLAS [<https://cmake.org/cmake/help/latest/module/FindBLAS.html>] and LAPACK [<https://cmake.org/cmake/help/latest/module/FindLAPACK.html>] functionality.
- `CMAKE_INSTALL_PREFIX` [https://cmake.org/cmake/help/latest/variable/CMAKE_INSTALL_PREFIX.html]: the location where igraph will be installed.

Building the documentation

Most users will not need to build the documentation, as the release tarball contains pre-built HTML documentation in the `doc` directory.

To build the documentation for the development version, simply build the `html` or `pdf` targets for the HTML and PDF versions of the documentation, respectively.

```
$ cmake --build . --target html
```

Building the HTML documentation requires Python 3, `xmlto` and `source-highlight`. Building the PDF documentation also requires `xsltproc`, `xmllint` and `fop`.

Notes for package maintainers

This section is for people who package igraph for Linux distros or other package managers. Please read it carefully before packaging igraph.

Auto-detection of dependencies

igraph bundles several of its dependencies (or simplified versions of its dependencies). During configuration time, it checks whether each dependency is present on the system. If yes, it uses it. Otherwise, it falls back to the bundled (“vendored”) version. In order to make configuration as deterministic as possible, you may want to disable this auto-detection. To do so, set each of the `IGRAPH_USE_INTERNAL_XXX` option described above. Additionally, set `BLA_VENDOR` to use the BLAS and LAPACK implementations of your choice. This should be the same BLAS and LAPACK library that igraph's other dependencies (e.g., ARPACK) are linked against.

For example, to force igraph to use external versions of all dependencies, and to use OpenBLAS for BLAS/LAPACK, use

```
$ cmake .. \  
  -DIGRAPH_USE_INTERNAL_BLAS=OFF \  
  -DIGRAPH_USE_INTERNAL_LAPACK=OFF \  
  -DIGRAPH_USE_INTERNAL_ARPACK=OFF \  
  -DIGRAPH_USE_INTERNAL_GLPK=OFF \  
  -DIGRAPH_USE_INTERNAL_GMP=OFF \  
  -DBLA_VENDOR=OpenBLAS \  
  -DIGRAPH_GRAPHML_SUPPORT=ON
```

Shared and static builds

On Windows, shared and static builds should not be installed in the same location. If you decide to do so anyway, keep in mind the following: Both builds contain an `igraph.lib` file. The static one should be renamed to avoid conflict. The headers from the static build are incompatible with the shared library. The headers from the shared build may be used with the static library, but `IGRAPH_STATIC` must be defined when compiling programs that will link to igraph statically.

These issues do not affect Unix-like systems.

Cross-compiling

When building igraph with an internal ARPACK, LAPACK or BLAS, it makes use of `f2c`, which compiles and runs the `arithchk` program at build time to detect the floating point characteristics of the current system. It writes the results into the `arith.h` header. However, running this program is not possible when cross-compiling without providing a userspace emulator that can run executables of the target platform on the host system. Therefore, when cross-compiling, you either need to provide such an emulator with the `CMAKE_CROSSCOMPILING_EMULATOR` option, or you need to specify a pre-generated version of the `arith.h` header file through the `F2C_EXTERNAL_ARITH_HEADER` CMake option. An example version of this header follows for the `x86_64` and `arm64` target architectures on macOS. Warning: Do not use this version of `arith.h` on other systems or architectures.

```
#define IEEE_8087  
#define Arith_Kind_ASX 1  
#define Long int  
#define Intcast (int)(long)  
#define Double_Align  
#define X64_bit_pointers  
#define NANCHECK  
#define QNaN0 0x0  
#define QNaN1 0x7ff80000
```

igraph also checks whether the endianness of `uint64_t` matches the endianness of `double` on the platform being compiled. This is needed to ensure that certain functions in igraph's random number generator work properly. However, it is not possible to execute this check when cross-compiling without an emulator, so in this case igraph simply assumes that the endianness matches (which is the case for the vast majority of platforms anyway). The only case where you might run into problems is when you cross-compile for Apple Silicon (`arm64`) from an Intel-based Mac, in which case CMake might not realize that you are cross-compiling and will try to execute the check anyway. You can work around this by setting `IEEE754_DOUBLE_ENDIANNES_MATCHES` to `ON` explicitly before invoking CMake.

Providing an emulator in `CMAKE_CROSSCOMPILING_EMULATOR` has the added benefit that you can run the compiled unit tests on the host platform. We have experimented with cross-compiling

to 64-bit ARM CPUs (aarch64) on 64-bit Intel CPUs (amd64), and we can confirm that using `qemu-aarch64` works as a cross-compiling emulator in this setup.

Additional notes

- As of igraph 0.9, there is no tangible benefit to using an external GMP, as igraph does not yet use GMP in any performance-critical way. The bundled Mini-GMP is sufficient.
- Link-time optimization noticeably improves the performance of some igraph functions. To enable it, use `-DIGRAPH_ENABLE_LTO=ON`. The `AUTO` setting is also supported, and will enable link-time optimization only if the current compiler supports it. Note that this is detected by CMake, and the detection is not always accurate.
- We saw occasional hangs on Windows when igraph was built for a 32-bit target with MinGW and linked to OpenBLAS. We believe this to be an issue with OpenBLAS, not igraph. On this platform, you may want to opt for a different BLAS/LAPACK or the bundled BLAS/LAPACK.

Chapter 3. Tutorial

Compiling programs using igraph

The following short example program demonstrates the basic usage of the **igraph** library.

```
#include <igraph.h>

int main() {
    igraph_integer_t num_vertices = 1000;
    igraph_integer_t num_edges = 1000;
    igraph_real_t diameter;
    igraph_t graph;

    igraph_rng_seed(igraph_rng_default(), 42);

    igraph_erdos_renyi_game(&graph, IGRAPH_ERDOS_RENYI_GNM,
                           num_vertices, num_edges,
                           IGRAPH_UNDIRECTED, IGRAPH_NO_LOOPS);

    igraph_diameter(&graph, &diameter, NULL, NULL, NULL, NULL, IGRAPH_UNDIRECTED,
    printf("Diameter of a random graph with average degree %g: %g\n",
           2.0 * igraph_ecount(&graph) / igraph_vcount(&graph),
           (double) diameter);

    igraph_destroy(&graph);

    return 0;
}
```

This example illustrates a couple of points:

- First, programs using the **igraph** library should include the `igraph.h` header file.
- Second, **igraph** uses the `igraph_integer_t` type for integers instead of `int` or `long int`, and it also uses the `igraph_real_t` type for real numbers instead of `double`. Depending on how **igraph** was compiled, and whether you are using a 32-bit or 64-bit system, `igraph_integer_t` may be a 32-bit or 64-bit integer.
- Third, **igraph** graph objects are represented by the `igraph_t` data type.
- Fourth, the `igraph_erdos_renyi_game()` creates a graph and `igraph_destroy()` destroys it, i.e. deallocates the memory associated to it.

For compiling this program you need a C compiler. Optionally, CMake [<https://cmake.org>] can be used to automate the compilation.

Compiling with CMake

It is convenient to use CMake because it can automatically discover the necessary compilation flags on all operating systems. Many IDEs support CMake, and can work with CMake projects directly. To create a CMake project for this example program, create a file name `CMakeLists.txt` with the following contents:

```
cmake_minimum_required(VERSION 3.18)
project(igraph_test)
```

```
find_package(igraph REQUIRED)

add_executable(igraph_test igraph_test.c)
target_link_libraries(igraph_test PUBLIC igraph::igraph)
```

To compile the project, create a new directory called `build` in the root of the `igraph` source tree, and switch to it:

```
mkdir build
cd build
```

Run CMake to configure the project:

```
cmake ..
```

If `igraph` was installed at a non-standard location, specify its prefix using the `-DCMAKE_PREFIX_PATH=...` option. The prefix must be the same directory that was specified as the `CMAKE_INSTALL_PREFIX` when compiling `igraph`.

If configuration has succeeded, build the program using

```
cmake --build .
```

C++ must be enabled in igraph projects

Parts of `igraph` are implemented in C++; therefore, any CMake target that depends on `igraph` should use the C++ linker. Furthermore, OpenMP support in `igraph` works correctly only if C++ is enabled in the CMake project. The script that finds `igraph` on the host machine will throw an error if C++ support is not enabled in the CMake project.

C++ support is enabled by default when no languages are explicitly specified in CMake's `project` command. If you do specify some languages explicitly, make sure to also include `CXX`.

Compiling without CMake

On most Unix-like systems, the default C compiler is called `cc`. To compile the test program, you will need a command similar to the following:

```
cc igraph_test.c -I/usr/local/include/igraph -L/usr/local/lib -ligraph -o igraph_test
```

The exact form depends on where **igraph** was installed on your system, whether it was compiled as a shared or static library, and the external libraries it was linked to. The directory after the `-I` switch is the one containing the `igraph.h` file, while the one following `-L` should contain the library file itself, usually a file called `libigraph.a` (static library on macOS and Linux), `libigraph.so` (shared library on Linux), `libigraph.dylib` (shared library on macOS), `igraph.lib` (static library on Windows) or `igraph.dll` (shared library on Windows). If **igraph** was compiled as a static library, it is also necessary to manually link to all of its dependencies.

If your system has the **pkg-config** utility you are likely to get the necessary compile options by issuing the command

```
pkg-config --libs --cflags igraph
```

(if **igraph** was built as a shared library) or

```
pkg-config --static --libs --cflags igraph
```

(if **igraph** was built as a static library).

Running the program

On most systems, the executable can be run by simply typing its name like this:

```
./igraph_test
```

If you use dynamic linking and the **igraph** library is not in a standard place, you may need to add its location to the `LD_LIBRARY_PATH` (Linux), `DYLD_LIBRARY_PATH` (macOS) or `PATH` (Windows) environment variables.

Creating your first graphs

The functions generating graph objects are called graph generators. Stochastic (i.e. randomized) graph generators are called “games”.

igraph can handle directed and undirected graphs. Most graph generators are able to create both types of graphs and most other functions are usually also capable of handling both. E.g., `igraph_get_shortest_paths()`, which calculates shortest paths from a vertex to other vertices, can calculate directed or undirected paths.

igraph has sophisticated ways for creating graphs. The simplest graphs are deterministic regular structures like star graphs (`igraph_star()`), ring graphs (`igraph_ring()`), lattices (`igraph_square_lattice()`) or trees (`igraph_kary_tree()`).

The following example creates an undirected regular circular lattice, adds some random edges to it and calculates the average length of shortest paths between all pairs of vertices in the graph before and after adding the random edges. (The message is that some random edges can reduce path lengths a lot.)

```
#include <igraph.h>
```

```
int main() {
    igraph_t graph;
    igraph_vector_int_t dimvector;
    igraph_vector_int_t edges;
    igraph_vector_bool_t periodic;
    igraph_real_t avg_path_len;

    igraph_vector_int_init(&dimvector, 2);
    VECTOR(dimvector)[0]=30;
    VECTOR(dimvector)[1]=30;

    igraph_vector_bool_init(&periodic, 2);
    igraph_vector_bool_fill(&periodic, true);
    igraph_square_lattice(&graph, &dimvector, 0, IGRAPH_UNDIRECTED, /* mutual= */

    igraph_average_path_length(&graph, &avg_path_len, NULL, IGRAPH_UNDIRECTED, /*
    printf("Average path length (lattice):           %g\n", (double) avg_path_len

    igraph_rng_seed(igraph_rng_default(), 42); /* seed RNG before first use */
    igraph_vector_int_init(&edges, 20);
```

```
for (igraph_integer_t i=0; i < igraph_vector_int_size(&edges); i++) {
    VECTOR(edges)[i] = RNG_INTEGER(0, igraph_vcount(&graph) - 1);
}

igraph_add_edges(&graph, &edges, NULL);
igraph_average_path_length(&graph, &avg_path_len, NULL, IGRAPH_UNDIRECTED, /*
printf("Average path length (randomized lattice): %g\n", (double) avg_path_len);

igraph_vector_bool_destroy(&periodic);
igraph_vector_int_destroy(&dimvector);
igraph_vector_int_destroy(&edges);
igraph_destroy(&graph);

return 0;
}
```

This example illustrates some new points. **igraph** uses `igraph_vector_t` and its related types (`igraph_vector_int_t`, `igraph_vector_bool_t` and so on) instead of plain C arrays. `igraph_vector_t` is superior to regular arrays in almost every sense. Vectors are created by the `igraph_vector_init()` function and, like graphs, they should be destroyed if not needed any more by calling `igraph_vector_destroy()` on them. A vector can be indexed by the `VECTOR()` function (right now it is a macro). The elements of a vector are of type `igraph_real_t` for `igraph_vector_t`, and of type `igraph_integer_t` for `igraph_vector_int_t`. As you might expect, `igraph_vector_bool_t` holds `igraph_bool_t` values. Vectors can be resized and most **igraph** functions returning the result in a vector automatically resize it to the size they need.

`igraph_square_lattice()` takes an integer vector argument specifying the dimensions of the lattice. In this example we generate a 30x30 two dimensional periodic lattice. See the documentation of `igraph_square_lattice()` in the reference manual for the other arguments.

The vertices in a graph are identified by a *vertex ID*, an integer between 0 and $N-1$, where N is the number of vertices in the graph. The vertex count can be retrieved using `igraph_vcount()`, as in the example.

The `igraph_add_edges()` function simply takes a graph and a vector of vertex IDs defining the new edges. The first edge is between the first two vertex IDs in the vector, the second edge is between the second two, etc. This way we add ten random edges to the lattice.

Note that this example program may add *loop edges*, edges pointing a vertex to itself, or *multiple edges*, more than one edge between the same pair of vertices. `igraph_t` can of course represent loops and multiple edges, although some routines expect simple graphs, i.e. graphs which contain neither of these. This is because some structural properties are ill-defined for non-simple graphs. Loop and multi-edges can be removed by calling `igraph_simplify()`.

Calculating various properties of graphs

In our next example we will calculate various centrality measures in a friendship graph. The friendship graph is from the famous Zachary karate club study. (Do a web search on "Zachary karate" if you want to know more about this.) Centrality measures quantify how central is the position of individual vertices in the graph.

```
#include <igraph.h>

int main() {
    igraph_t graph;
    igraph_vector_int_t v;
    igraph_vector_int_t result;
    igraph_vector_t result_real;
```

```

igraph_integer_t edges[] = { 0,1, 0,2, 0,3, 0,4, 0,5, 0,6, 0,7, 0,8,
                             0,10, 0,11, 0,12, 0,13, 0,17, 0,19, 0,21, 0,31,
                             1, 2, 1, 3, 1, 7, 1,13, 1,17, 1,19, 1,21, 1,30,
                             2, 3, 2, 7, 2,27, 2,28, 2,32, 2, 9, 2, 8, 2,13,
                             3, 7, 3,12, 3,13, 4, 6, 4,10, 5, 6, 5,10, 5,16,
                             6,16, 8,30, 8,32, 8,33, 9,33, 13,33, 14,32, 14,33,
                             15,32, 15,33, 18,32, 18,33, 19,33, 20,32, 20,33,
                             22,32, 22,33, 23,25, 23,27, 23,32, 23,33, 23,29,
                             24,25, 24,27, 24,31, 25,31, 26,29, 26,33, 27,33,
                             28,31, 28,33, 29,32, 29,33, 30,32, 30,33, 31,32,
                             31,33, 32,33 };

igraph_vector_int_view(&v, edges, sizeof(edges) / sizeof(edges[0]));
igraph_create(&graph, &v, 0, IGRAPH_UNDIRECTED);

igraph_vector_int_init(&result, 0);
igraph_vector_init(&result_real, 0);

igraph_degree(&graph, &result, igraph_vss_all(), IGRAPH_ALL, IGRAPH_LOOPS);
printf("Maximum degree is      %10" IGRAPH_PRId ", vertex %2" IGRAPH_PRId ".\n",
       igraph_vector_int_max(&result),
       igraph_vector_int_which_max(&result));

igraph_closeness(&graph, &result_real, NULL, NULL, igraph_vss_all(), IGRAPH_ALL,
                /* weights= */ NULL, /* normalized= */ false);
printf("Maximum closeness is   %10g, vertex %2" IGRAPH_PRId ".\n",
       (double) igraph_vector_max(&result_real),
       igraph_vector_which_max(&result_real));

igraph_betweenness(&graph, &result_real, igraph_vss_all(),
                  IGRAPH_UNDIRECTED, /* weights= */ NULL);
printf("Maximum betweenness is %10g, vertex %2" IGRAPH_PRId ".\n",
       (double) igraph_vector_max(&result_real),
       igraph_vector_which_max(&result_real));

igraph_vector_int_destroy(&result);
igraph_vector_destroy(&result_real);
igraph_destroy(&graph);

return 0;
}

```

This example demonstrates some new operations. First of all, it shows a way to create a graph a list of edges stored in a plain C array. Function `igraph_vector_view()` creates a *view* of a C array. It does not copy any data, which means that you must not call `igraph_vector_destroy()` on a vector created this way. This vector is then used to create the undirected graph.

Then the degree, closeness and betweenness centrality of the vertices is calculated and the highest values are printed. Note that the vector `result`, into which these functions will write their result, must be initialized first, and also that the functions resize it to be able to hold the result.

Notice that in order to print values of type `igraph_integer_t`, we used the `IGRAPH_PRId` format macro constant. This macro is similar to the standard `PRI` constants defined in `stdint.h`, and expands to the correct `printf` format specifier on each platform that **igraph** supports.

The `igraph_vss_all()` argument tells the functions to calculate the property for every vertex in the graph. It is shorthand for a *vertex selector*, represented by type `igraph_vs_t`. Vertex selectors help perform operations on a subset of vertices. You can read more about them in one of the following chapters.

Chapter 4. Basic data types and interface

The igraph data model

The igraph library can handle directed and undirected graphs. The igraph graphs are multisets of ordered (if directed) or unordered (if undirected) labeled pairs. The labels of the pairs plus the number of vertices always starts with zero and ends with the number of edges minus one. In addition to that, a table of metadata is also attached to every graph, its most important entries being the number of vertices in the graph and whether the graph is directed or undirected.

Like the edges, the igraph vertices are also labeled by numbers between zero and the number of vertices minus one. So, to summarize, a directed graph can be imagined like this:

```
( vertices: 6,
  directed: yes,
  {
    (0,2),
    (2,2),
    (3,2),
    (3,3),
    (3,4),
    (3,4),
    (4,3),
    (4,1)
  }
)
```

Here the edges are ordered pairs of vertex ids, and the graph is a multiset of edges plus some metadata.

An undirected graph is like this:

```
( vertices: 6,
  directed: no,
  {
    (0,2),
    (2,2),
    (2,3),
    (3,3),
    (3,4),
    (3,4),
    (3,4),
    (1,4)
  }
)
```

Here, an edge is an unordered pair of two vertex IDs. A graph is a multiset of edges plus metadata, just like in the directed case.

It is possible to convert between directed and undirected graphs, see the `igraph_to_directed()` and `igraph_to_undirected()` functions.

igraph aims to robustly support multigraphs, i.e. graphs which have more than one edge between some pairs of vertices, as well as graphs with self-loops. Most functions which do not support such graphs

will check their input and issue an error if it is not valid. Those rare functions which do not perform this check clearly indicate this in their documentation. To eliminate multiple edges from a graph, you can use `igraph_simplify()`.

General conventions of igraph functions

igraph has a simple and consistent interface. Most functions check their input for validity and display an informative error message when something goes wrong. In order to support this, the majority of functions return an error code. In basic usage, this code can be ignored, as the default behaviour is to abort the program immediately upon error. See the section on error handling for more information on this topic.

Results are typically returned through *output arguments*, i.e. pointers to a data structure into which the result will be written. In almost all cases, this data structure is expected to be pre-initialized. A few simple functions communicate their result directly through their return value—these functions can never encounter an error.

Atomic data types

igraph introduces a few aliases to standard C data types that are then used throughout the library. The most important of these types is `igraph_integer_t`, which is an alias to either a 32-bit or a 64-bit *signed* integer, depending on whether igraph was compiled in 32-bit or 64-bit mode. The size of `igraph_integer_t` also influences the maximum number of vertices that an igraph graph can represent as the number of vertices is stored in a variable of type `igraph_integer_t`.

Since the size of a variable of type `igraph_integer_t` may change depending on how igraph is compiled, you cannot simply use `%d` or `%ld` as a placeholder for igraph integers in `printf` format strings. igraph provides the `IGRAPH_PRId` macro, which maps to `d`, `ld` or `lld` depending on the size of `igraph_integer_t`, and you must use this macro in `printf` format strings to avoid compiler warnings.

Similarly to how `igraph_integer_t` maps to the standard size signed integer in the library, `igraph_uint_t` maps to a 32-bit or a 64-bit *unsigned* integer. It is guaranteed that the size of `igraph_integer_t` is the same as the size of `igraph_uint_t`. igraph provides `IGRAPH_PRIu` as a format string placeholder for variables of type `igraph_uint_t`.

Real numbers (i.e. quantities that can potentially be fractional or infinite) are represented with a type named `igraph_real_t`. Currently `igraph_real_t` is always aliased to `double`, but it is still good practice to use `igraph_real_t` in your own code for sake of consistency.

Boolean values are represented with a type named `igraph_bool_t`. It tries to be as small as possible since it only needs to represent a truth value. For printing purposes, you can treat it as an integer and use `%d` in format strings as a placeholder for an `igraph_bool_t`.

Upper and lower limits of `igraph_integer_t` and `igraph_uint_t` are provided by the constants named `IGRAPH_INTEGER_MIN`, `IGRAPH_INTEGER_MAX`, `IGRAPH_UINT_MIN` and `IGRAPH_UINT_MAX`.

The basic interface

This is the very minimal API in **igraph**. All the other functions use this minimal set for creating and manipulating graphs.

This is a very important principle since it makes possible to implement other data representations by implementing only this minimal set.

This section lists all the functions and macros that are considered as part of the core API from the point of view of the *users* of igraph. Some of these functions and macros have sensible default implementations that simply call some other core function (e.g., `igraph_empty()` calls `igraph_empty_attrs()` with a null attribute table pointer). If you wish to experiment with implementing an alternative data type, the actual number of functions that you need to replace is lower as you can rely on the same default implementations in most cases.

Graph constructors and destructors

`igraph_empty` — Creates an empty graph with some vertices and no edges.

```
igraph_error_t igraph_empty(igraph_t *graph, igraph_integer_t n, igraph_bool_t directed)
```

The most basic constructor, all the other constructors should call this to create a minimal graph object. Our use of the term "empty graph" in the above description should be distinguished from the mathematical definition of the empty or null graph. Strictly speaking, the empty or null graph in graph theory is the graph with no vertices and no edges. However by "empty graph" as used in igraph we mean a graph having zero or more vertices, but no edges.

Arguments:

graph: Pointer to a not-yet initialized graph object.

n: The number of vertices in the graph, a non-negative integer number is expected.

directed: Boolean; whether the graph is directed or not. Supported values are:

<code>IGRAPH_DIRECTED</code>	The graph will be <i>directed</i> .
<code>IGRAPH_UNDIRECTED</code>	The graph will be <i>undirected</i> .

Returns:

Error code: `IGRAPH_EINVAL`: invalid number of vertices.

Time complexity: $O(|V|)$ for a graph with $|V|$ vertices (and no edges).

Example 4.1. File `examples/simple/creation.c`

`igraph_empty_attrs` — Creates an empty graph with some vertices, no edges and some graph attributes.

```
igraph_error_t igraph_empty_attrs(igraph_t *graph, igraph_integer_t n, igraph_bool_t directed,
```

Use this instead of `igraph_empty()` if you wish to add some graph attributes right after initialization. This function is currently not very interesting for the ordinary user. Just supply 0 here or use `igraph_empty()`.

This function does not set any vertex attributes. To create a graph which has vertex attributes, call this function specifying 0 vertices, then use `igraph_add_vertices()` to add vertices and their attributes.

Arguments:

graph: Pointer to a not-yet initialized graph object.

n: The number of vertices in the graph; a non-negative integer number is expected.

directed: Boolean; whether the graph is directed or not. Supported values are:

`IGRAPH_DIRECTED` Create a *directed* graph.

`IGRAPH_UNDIRECTED` Create an *undirected* graph.

attr: The graph attributes. Supply `NULL` if no graph attributes are to be set.

Returns:

Error code: `IGRAPH_EINVAL`: invalid number of vertices.

See also:

`igraph_empty()` to create an empty graph without attributes; `igraph_add_vertices()` and `igraph_add_edges()` to add vertices and edges, possibly with associated attributes.

Time complexity: $O(|V|)$ for a graph with $|V|$ vertices (and no edges).

igraph_copy — Creates an exact (deep) copy of a graph.

```
igraph_error_t igraph_copy(igraph_t *to, const igraph_t *from);
```

This function deeply copies a graph object to create an exact replica of it. The new replica should be destroyed by calling `igraph_destroy()` on it when not needed any more.

You can also create a shallow copy of a graph by simply using the standard assignment operator, but be careful and do *not* destroy a shallow replica. To avoid this mistake, creating shallow copies is not recommended.

Arguments:

to: Pointer to an uninitialized graph object.

from: Pointer to the graph object to copy.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$ for a graph with $|V|$ vertices and $|E|$ edges.

Example 4.2. File `examples/simple/igraph_copy.c`

igraph_destroy — Frees the memory allocated for a graph object.

```
void igraph_destroy(igraph_t *graph);
```

This function should be called for every graph object exactly once.

This function invalidates all iterators (of course), but the iterators of a graph should be destroyed before the graph itself anyway.

Arguments:

graph: Pointer to the graph to free.

Time complexity: operating system specific.

Basic query operations

igraph_vcount — The number of vertices in a graph.

```
igraph_integer_t igraph_vcount(const igraph_t *graph);
```

Arguments:

graph: The graph.

Returns:

Number of vertices.

Time complexity: $O(1)$

igraph_ecount — The number of edges in a graph.

```
igraph_integer_t igraph_ecount(const igraph_t *graph);
```

Arguments:

graph: The graph.

Returns:

Number of edges.

Time complexity: $O(1)$

igraph_is_directed — Is this a directed graph?

```
igraph_bool_t igraph_is_directed(const igraph_t *graph);
```

Arguments:

graph: The graph.

Returns:

Logical value, true if the graph is directed, false otherwise.

Time complexity: $O(1)$

Example 4.3. File `examples/simple/igraph_is_directed.c`

igraph_edge — Returns the head and tail vertices of an edge.

```
igraph_error_t igraph_edge(  
    const igraph_t *graph, igraph_integer_t eid,  
    igraph_integer_t *from, igraph_integer_t *to  
);
```

Arguments:

graph: The graph object.

eid: The edge ID.

from: Pointer to an `igraph_integer_t`. The tail (source) of the edge will be placed here.

to: Pointer to an `igraph_integer_t`. The head (target) of the edge will be placed here.

Returns:

Error code. The current implementation always returns with success.

See also:

`igraph_get_eid()` for the opposite operation; `igraph_edges()` to get the endpoints of several edges; `IGRAPH_TO()`, `IGRAPH_FROM()` and `IGRAPH_OTHER()` for a faster but non-error-checked version.

Added in version 0.2.

Time complexity: $O(1)$.

igraph_edges — Gives the head and tail vertices of a series of edges.

```
igraph_error_t igraph_edges(const igraph_t *graph, igraph_es_t eids, igraph_vec
```

Arguments:

graph: The graph object.

edges: Edge selector, the series of edges.

edges: Pointer to an initialized vector. The start and endpoints of each edge will be placed here.

Returns:

Error code.

See also:

`igraph_get_edgelist()` to get the endpoints of all edges; `igraph_get_eids()` for the opposite operation; `igraph_edge()` for getting the endpoints of a single edge; `IGRAPH_TO()`, `IGRAPH_FROM()` and `IGRAPH_OTHER()` for a faster but non-error-checked method.

Time complexity: $O(k)$ where k is the number of edges in the selector.

IGRAPH_FROM — The source vertex of an edge.

```
#define IGRAPH_FROM(graph,eid)
```

Faster than `igraph_edge()`, but no error checking is done: *eid* is assumed to be valid.

Arguments:

graph: The graph.

eid: The edge ID.

Returns:

The source vertex of the edge.

See also:

`igraph_edge()` if error checking is desired.

IGRAPH_TO — The target vertex of an edge.

```
#define IGRAPH_TO(graph,eid)
```

Faster than `igraph_edge()`, but no error checking is done: *eid* is assumed to be valid.

Arguments:

graph: The graph object.

eid: The edge ID.

Returns:

The target vertex of the edge.

See also:

`igraph_edge()` if error checking is desired.

IGRAPH_OTHER — The other endpoint of an edge.

```
#define IGRAPH_OTHER(graph,eid,vid)
```

Typically used with undirected edges when one endpoint of the edge is known, and the other endpoint is needed. No error checking is done: *eid* and *vid* are assumed to be valid.

Arguments:

graph: The graph object.

eid: The edge ID.

vid: The vertex ID of one endpoint of an edge.

Returns:

The other endpoint of the edge.

See also:

`IGRAPH_TO()` and `IGRAPH_FROM()` to get the source and target of directed edges.

igraph_get_eid — Get the edge ID from the end points of an edge.

```
igraph_error_t igraph_get_eid(const igraph_t *graph, igraph_integer_t *eid,  
                             igraph_integer_t pfrom, igraph_integer_t pto,  
                             igraph_bool_t directed, igraph_bool_t error);
```

For undirected graphs *pfrom* and *pto* are exchangeable.

Arguments:

graph: The graph object.

eid: Pointer to an integer, the edge ID will be stored here.

pfrom: The starting point of the edge.

pto: The end point of the edge.

directed: Logical constant, whether to search for directed edges in a directed graph. Ignored for undirected graphs.

error: Logical scalar, whether to report an error if the edge was not found. If it is false, then -1 will be assigned to *eid*. Note that invalid vertex IDs in input arguments (*pfrom* or *pto*) always return an error code.

Returns:

Error code.

See also:

`igraph_edge()` for the opposite operation, `igraph_get_all_eids_between()` to retrieve all edge IDs between a pair of vertices.

Time complexity: $O(\log(d))$, where d is smaller of the out-degree of *pfrom* and in-degree of *pto* if *directed* is true. If *directed* is false, then it is $O(\log(d)+\log(d2))$, where d is the same as before and $d2$ is the minimum of the out-degree of *pto* and the in-degree of *pfrom*.

Example 4.4. File `examples/simple/igraph_get_eid.c`

Added in version 0.2.

igraph_get_eids — Return edge IDs based on the adjacent vertices.

```
igraph_error_t igraph_get_eids(const igraph_t *graph, igraph_vector_int_t *eids,
                              const igraph_vector_int_t *pairs,
                              igraph_bool_t directed, igraph_bool_t error);
```

The pairs of vertex IDs for which the edges are looked up are taken consecutively from the *pairs* vector, i.e. `VECTOR(pairs)[0]` and `VECTOR(pairs)[1]` specify the first pair, `VECTOR(pairs)[2]` and `VECTOR(pairs)[3]` the second pair, etc.

If you have a sequence of vertex IDs that describe a *path* on the graph, use `igraph_expand_path_to_pairs()` to convert them to a list of vertex pairs along the path.

If the *error* argument is true, then it is an error to specify pairs of vertices that are not connected. Otherwise -1 is reported for vertex pairs without at least one edge between them.

If there are multiple edges in the graph, then these are ignored; i.e. for a given pair of vertex IDs, *igraph* always returns the same edge ID, even if the pair appears multiple times in *pairs*.

Arguments:

graph: The input graph.

eids: Pointer to an initialized vector, the result is stored here. It will be resized as needed.

pairs: Vector giving pairs of vertices to fetch the edges for.

directed: Logical scalar, whether to consider edge directions in directed graphs. This is ignored for undirected graphs.

error: Logical scalar, whether it is an error to supply non-connected vertices. If false, then -1 is returned for non-connected pairs.

Returns:

Error code.

Time complexity: $O(n \log(d))$, where n is the number of queried edges and d is the average degree of the vertices.

See also:

`igraph_get_eid()` for a single edge.

Example 4.5. File `examples/simple/igraph_get_eids.c`

`igraph_get_all_eids_between` — Returns all edge IDs between a pair of vertices.

```
igraph_error_t igraph_get_all_eids_between(  
    const igraph_t *graph, igraph_vector_int_t *eids,  
    igraph_integer_t source, igraph_integer_t target, igraph_bool_t directed  
);
```

For undirected graphs `source` and `target` are exchangeable.

Arguments:

graph: The input graph.

eids: Pointer to an initialized vector, the result is stored here. It will be resized as needed.

source: The ID of the source vertex

target: The ID of the target vertex

directed: Logical scalar, whether to consider edge directions in directed graphs. This is ignored for undirected graphs.

Returns:

Error code.

Time complexity: TODO

See also:

`igraph_get_eid()` for a single edge.

`igraph_neighbors` — Adjacent vertices to a vertex.

```
igraph_error_t igraph_neighbors(const igraph_t *graph, igraph_vector_int_t *nei,  
                                igraph_neimode_t mode);
```

Arguments:

graph: The graph to work on.

neis: This vector will contain the result. The vector should be initialized beforehand and will be resized. Starting from igraph version 0.4 this vector is always sorted, the vertex IDs are in increasing order. If one neighbor is connected with multiple edges, the neighbor will be returned multiple times.

pnode: The id of the node for which the adjacent vertices are to be searched.

mode: Defines the way adjacent vertices are searched in directed graphs. It can have the following values: IGRAPH_OUT, vertices reachable by an edge from the specified vertex are searched; IGRAPH_IN, vertices from which the specified vertex is reachable are searched; IGRAPH_ALL, both kinds of vertices are searched. This parameter is ignored for undirected graphs.

Returns:

Error code: IGRAPH_EINVVID: invalid vertex ID. IGRAPH_EINVMODE: invalid mode argument. IGRAPH_ENOMEM: not enough memory.

Time complexity: $O(d)$, d is the number of adjacent vertices to the queried vertex.

Example 4.6. File `examples/simple/igraph_neighbors.c`**igraph_incident — Gives the incident edges of a vertex.**

```
igraph_error_t igraph_incident(const igraph_t *graph, igraph_vector_int_t *eids,
                              igraph_neimode_t mode);
```

Arguments:

graph: The graph object.

eids: An initialized vector. It will be resized to hold the result.

pnode: A vertex ID.

mode: Specifies what kind of edges to include for directed graphs. IGRAPH_OUT means only outgoing edges, IGRAPH_IN only incoming edges, IGRAPH_ALL both. This parameter is ignored for undirected graphs.

Returns:

Error code. IGRAPH_EINVVID: invalid *pnode* argument, IGRAPH_EINVMODE: invalid *mode* argument.

Added in version 0.2.

Time complexity: $O(d)$, the number of incident edges to *pnode*.

igraph_degree — The degree of some vertices in a graph.

```
igraph_error_t igraph_degree(const igraph_t *graph, igraph_vector_int_t *res,
```

```
const igraph_vs_t vids,  
igraph_neimode_t mode, igraph_bool_t loops);
```

This function calculates the in-, out- or total degree of the specified vertices.

This function returns the result as a vector of `igraph_integer_t` values. In applications where `igraph_real_t` is desired, use `igraph_strength()` with `NULL` weights.

Arguments:

graph: The graph.

res: Integer vector, this will contain the result. It should be initialized and will be resized to be the appropriate size.

vids: Vertex selector, giving the vertex IDs of which the degree will be calculated.

mode: Defines the type of the degree for directed graphs. Valid modes are: `IGRAPH_OUT`, out-degree; `IGRAPH_IN`, in-degree; `IGRAPH_ALL`, total degree (sum of the in- and out-degree). This parameter is ignored for undirected graphs.

loops: Boolean, gives whether the self-loops should be counted.

Returns:

Error code: `IGRAPH_EINVVID`: invalid vertex ID. `IGRAPH_EINVMODE`: invalid mode argument.

Time complexity: $O(v)$ if *loops* is `true`, and $O(v*d)$ otherwise. *v* is the number of vertices for which the degree will be calculated, and *d* is their (average) degree.

See also:

`igraph_strength()` for the version that takes into account edge weights.

Example 4.7. File `examples/simple/igraph_degree.c`

Adding and deleting vertices and edges

`igraph_add_edge` — Adds a single edge to a graph.

```
igraph_error_t igraph_add_edge(igraph_t *graph, igraph_integer_t from, igraph_integer_t to);
```

For directed graphs the edge points from *from* to *to*.

Note that if you want to add many edges to a big graph, then it is inefficient to add them one by one, it is better to collect them into a vector and add all of them via a single `igraph_add_edges()` call.

Arguments:

igraph: The graph.

from: The id of the first vertex of the edge.

to: The id of the second vertex of the edge.

Returns:

Error code.

See also:

`igraph_add_edges()` to add many edges, `igraph_delete_edges()` to remove edges and `igraph_add_vertices()` to add vertices.

Time complexity: $O(|V|+|E|)$, the number of edges plus the number of vertices.

igraph_add_edges — Adds edges to a graph object.

```
igraph_error_t igraph_add_edges(igraph_t *graph, const igraph_vector_int_t *edges,
                                void *attr);
```

The edges are given in a vector, the first two elements define the first edge (the order is from, to for directed graphs). The vector should contain even number of integer numbers between zero and the number of vertices in the graph minus one (inclusive). If you also want to add new vertices, call `igraph_add_vertices()` first.

Arguments:

graph: The graph to which the edges will be added.

edges: The edges themselves.

attr: The attributes of the new edges. You can supply a null pointer here if you do not need edge attributes.

Returns:

Error code: `IGRAPH_EINVEVECTOR`: invalid (odd) edges vector length, `IGRAPH_EINVVID`: invalid vertex ID in edges vector.

This function invalidates all iterators.

Time complexity: $O(|V|+|E|)$ where $|V|$ is the number of vertices and $|E|$ is the number of edges in the *new*, extended graph.

Example 4.8. File `examples/simple/creation.c`

igraph_add_vertices — Adds vertices to a graph.

```
igraph_error_t igraph_add_vertices(igraph_t *graph, igraph_integer_t nv, void *attr);
```

This function invalidates all iterators.

Arguments:

graph: The graph object to extend.

nv: Non-negative integer specifying the number of vertices to add.

attr: The attributes of the new vertices. You can supply a null pointer here if you do not need vertex attributes.

Returns:

Error code: IGRAPH_EINVAL: invalid number of new vertices.

Time complexity: $O(|V|)$ where $|V|$ is the number of vertices in the *new*, extended graph.

Example 4.9. File `examples/simple/creation.c`

igraph_delete_edges — Removes edges from a graph.

```
igraph_error_t igraph_delete_edges(igraph_t *graph, igraph_es_t edges);
```

The edges to remove are specified as an edge selector.

This function cannot remove vertices; vertices will be kept even if they lose all their edges.

This function invalidates all iterators.

Arguments:

graph: The graph to work on.

edges: The edges to remove.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$ where $|V|$ and $|E|$ are the number of vertices and edges in the *original* graph, respectively.

Example 4.10. File `examples/simple/igraph_delete_edges.c`

igraph_delete_vertices — Removes some vertices (with all their edges) from the graph.

```
igraph_error_t igraph_delete_vertices(igraph_t *graph, const igraph_vs_t vertices);
```

This function changes the IDs of the vertices (except in some very special cases, but these should not be relied on anyway).

This function invalidates all iterators.

Arguments:

graph: The graph to work on.

vertices: The IDs of the vertices to remove, in a vector. The vector may contain the same ID more than once.

Returns:

Error code: IGRAPH_EINVVID: invalid vertex ID.

Time complexity: $O(|V|+|E|)$, $|V|$ and $|E|$ are the number of vertices and edges in the original graph.

Example 4.11. File `examples/simple/igraph_delete_vertices.c`

igraph_delete_vertices_idx — Removes some vertices (with all their edges) from the graph

```
igraph_error_t igraph_delete_vertices_idx(  
    igraph_t *graph, const igraph_vs_t vertices, igraph_vector_int_t *idx,  
    igraph_vector_int_t *invidx  
);
```

This function changes the IDs of the vertices (except in some very special cases, but these should not be relied on anyway). You can use the `idx` argument to obtain the mapping from old vertex IDs to the new ones, and the `newidx` argument to obtain the reverse mapping.

This function invalidates all iterators.

Arguments:

- graph*: The graph to work on.
- vertices*: The IDs of the vertices to remove, in a vector. The vector may contain the same ID more than once.
- idx*: An optional pointer to a vector that provides the mapping from the vertex IDs *before* the removal to the vertex IDs *after* the removal. You can supply NULL here if you are not interested.
- invidx*: An optional pointer to a vector that provides the mapping from the vertex IDs *after* the removal to the vertex IDs *before* the removal. You can supply NULL here if you are not interested.

Returns:

Error code: IGRAPH_EINVVID: invalid vertex ID.

Time complexity: $O(|V|+|E|)$, $|V|$ and $|E|$ are the number of vertices and edges in the original graph.

Example 4.12. File `examples/simple/igraph_delete_vertices.c`

Miscellaneous macros and helper functions

IGRAPH_VCOUNT_MAX — The maximum number of vertices supported in igraph graphs.

```
#define IGRAPH_VCOUNT_MAX
```

The value of this constant is one less than `IGRAPH_INTEGER_MAX`. When igraph is compiled in 32-bit mode, this means that you are limited to $2^{31} - 2$ (about 2.1 billion) vertices. In 64-bit mode, the limit is $2^{63} - 2$ so you are much more likely to hit out-of-memory issues due to other reasons before reaching this limit.

IGRAPH_ECOUNT_MAX — The maximum number of edges supported in igraph graphs.

```
#define IGRAPH_ECOUNT_MAX
```

The value of this constant is half of `IGRAPH_INTEGER_MAX`. When igraph is compiled in 32-bit mode, this means that you are limited to approximately 2^{30} (about 1.07 billion) vertices. In 64-bit mode, the limit is approximately 2^{62} so you are much more likely to hit out-of-memory issues due to other reasons before reaching this limit.

igraph_expand_path_to_pairs — Helper function to convert a sequence of vertex IDs describing a path into a "pairs" vector.

```
igraph_error_t igraph_expand_path_to_pairs(igraph_vector_int_t* path);
```

This function is useful when you have a sequence of vertex IDs in a graph and you would like to retrieve the IDs of the edges between them. The function duplicates all but the first and the last elements in the vector, effectively converting the path into a vector of vertex IDs that can be passed to `igraph_get_eids()`.

Arguments:

path: the input vector. It will be modified in-place and it will be resized as needed. When the vector contains less than two vertex IDs, it will be cleared.

Returns:

Error code: `IGRAPH_ENOMEM` if there is not enough memory to expand the vector.

igraph_invalidate_cache — Invalidates the internal cache of an igraph graph

```
void igraph_invalidate_cache(const igraph_t* graph);
```

igraph graphs cache some basic properties about themselves in an internal data structure. This function invalidates the contents of the cache and forces a recalculation of the cached properties the next time they are needed.

You should not need to call this function during normal usage; however, we might ask you to call this function explicitly if we suspect that you are running into a bug in igraph's cache handling. A tell-tale sign of an invalid cache entry is that the result of a cached igraph function (such as `igraph_is_dag()` or `igraph_is_simple()`) is different before and after a cache invalidation.

Arguments:

graph: The graph whose cache is to be invalidated.

Time complexity: $O(1)$.

igraph_is_same_graph — Are two graphs identical as labelled graphs?

```
igraph_error_t igraph_is_same_graph(const igraph_t *graph1, const igraph_t *graph2)
```

Two graphs are considered to be the same if they have the same vertex and edge sets. Graphs which are the same may have multiple different representations in igraph, hence the need for this function.

This function verifies that the two graphs have the same directedness, the same number of vertices, and that they contain precisely the same edges (regardless of their ordering) when written in terms of vertex indices. Graph attributes are not taken into account.

This concept is different from isomorphism. For example, the graphs 0-1, 2-1 and 1-2, 0-1 are considered the same because they only differ in the ordering of their edge lists and the ordering of vertices in an undirected edge. However, they are not the same as 0-2, 1-2, even though they are isomorphic to it. Note that this latter graph contains the edge 0-2 while the former two do not — thus their edge sets differ.

Arguments:

graph1: The first graph object.

graph2: The second graph object.

res: The result will be stored here.

Returns:

Error code.

Time complexity: $O(E)$, the number of edges in the graphs.

See also:

`igraph_isomorphic()` to test if two graphs are isomorphic.

Chapter 5. Error handling

Error handling basics

igraph functions can run into various problems preventing them from normal operation. The user might have supplied invalid arguments, e.g. a non-square matrix when a square-matrix was expected, or the program has run out of memory while some more memory allocation is required, etc.

By default **igraph** aborts the program when it runs into an error. While this behavior might be good enough for smaller programs, it is without doubt avoidable in larger projects. Please read further if your project requires more sophisticated error handling. You can safely skip the rest of this chapter otherwise.

Error handlers

If **igraph** runs into an error - an invalid argument was supplied to a function, or we've ran out of memory - the control is transferred to the *error handler* function.

The default error handler is `igraph_error_handler_abort` which prints an error message and aborts the program.

The `igraph_set_error_handler()` function can be used to set a new error handler function of type `igraph_error_handler_t`; see the documentation of this type for details.

There are two other predefined error handler functions, `igraph_error_handler_ignore` and `igraph_error_handler_printignore`. These deallocate the temporarily allocated memory (more about this later) and return with the error code. The latter also prints an error message. If you use these error handlers you need to take care about possible errors yourself by checking the return value of (almost) every non-void **igraph** function.

Independently of the error handler installed, all functions in the library do their best to leave their arguments *semantically* unchanged if an error happens. By semantically we mean that the implementation of an object supplied as an argument might change, but its “meaning” in most cases does not. The rare occasions when this rule is violated are documented in this manual.

`igraph_error_handler_t` — The type of error handler functions.

```
typedef void igraph_error_handler_t (const char *reason, const char *file,
                                     int line, igraph_error_t igraph_errno);
```

This is the type of the error handler functions.

Arguments:

<i>reason</i> :	Textual description of the error.
<i>file</i> :	The source file in which the error is noticed.
<i>line</i> :	The number of the line in the source file which triggered the error
<i>igraph_errno</i> :	The igraph error code.

igraph_error_handler_abort — Abort program in case of error.

```
IGRAPH_EXPORT igraph_error_handler_t igraph_error_handler_abort;
```

The default error handler, prints an error message and aborts the program.

igraph_error_handler_ignore — Ignore errors.

```
IGRAPH_EXPORT igraph_error_handler_t igraph_error_handler_ignore;
```

This error handler frees the temporarily allocated memory and returns with the error code.

igraph_error_handler_printignore — Print and ignore errors.

```
IGRAPH_EXPORT igraph_error_handler_t igraph_error_handler_printignore;
```

Frees temporarily allocated memory, prints an error message to the standard error and returns with the error code.

Error codes

Every **igraph** function which can fail return a single integer error code. Some functions are very simple and cannot run into any error, these may return other types, or void as well. The error codes are defined by the `igraph_error_type_t` enumeration.

igraph_error_t — Type alias because igraph_error_t used to be an integer, and was used

```
typedef igraph_error_type_t igraph_error_t;
```

slightly differently than `igraph_error_type_t`. This type is used as the return type of `igraph` functions that return an error code.

igraph_error_type_t — Error code type.

```
typedef enum {  
    IGRAPH_SUCCESS           = 0,  
    IGRAPH_FAILURE          = 1,  
    IGRAPH_ENOMEM           = 2,  
    IGRAPH_PARSEERROR       = 3,  
    IGRAPH_EINVAL           = 4,  
    IGRAPH_EXISTS           = 5,  
    IGRAPH_EINVEVECTOR      = 6,  
    IGRAPH_EINVVID          = 7,  
}
```

```
IGRAPH_NONSQUARE      = 8,
IGRAPH_EINVMODE       = 9,
IGRAPH_EFILE          = 10,
IGRAPH_UNIMPLEMENTED  = 12,
IGRAPH_INTERRUPTED    = 13,
IGRAPH_DIVERGED       = 14,
IGRAPH_ARPACK_PROD     = 15, /* unused, reserved */
IGRAPH_ARPACK_NPOS     = 16,
IGRAPH_ARPACK_NEVNPOS  = 17,
IGRAPH_ARPACK_NCVSMALL = 18,
IGRAPH_ARPACK_NONPOSI  = 19,
IGRAPH_ARPACK_WHICHINV = 20,
IGRAPH_ARPACK_BMATINV  = 21,
IGRAPH_ARPACK_WORKLSMALL = 22,
IGRAPH_ARPACK_TRIDERR  = 23,
IGRAPH_ARPACK_ZEROSTART = 24,
IGRAPH_ARPACK_MODEINV  = 25,
IGRAPH_ARPACK_MODEBMAT = 26,
IGRAPH_ARPACK_ISHIFT   = 27,
IGRAPH_ARPACK_NEVBE    = 28,
IGRAPH_ARPACK_NOFACT   = 29,
IGRAPH_ARPACK_FAILED   = 30,
IGRAPH_ARPACK_HOWMNY   = 31,
IGRAPH_ARPACK_HOWMNYS  = 32,
IGRAPH_ARPACK_EVDIFF   = 33,
IGRAPH_ARPACK_SHUR     = 34,
IGRAPH_ARPACK_LAPACK   = 35,
IGRAPH_ARPACK_UNKNOWN  = 36,
IGRAPH_ENEGLOOP        = 37,
IGRAPH_EINTERNAL       = 38,
IGRAPH_ARPACK_MAXIT    = 39,
IGRAPH_ARPACK_NOSHIFT  = 40,
IGRAPH_ARPACK_REORDER  = 41,
IGRAPH_EDIVZERO        = 42,
IGRAPH_GLP_EBOUND      = 43,
IGRAPH_GLP_EROOT       = 44,
IGRAPH_GLP_ENOPFS      = 45,
IGRAPH_GLP_ENODFS      = 46,
IGRAPH_GLP_EFAIL       = 47,
IGRAPH_GLP_EMIPGAP     = 48,
IGRAPH_GLP_ETMLIM      = 49,
IGRAPH_GLP_ESTOP       = 50,
IGRAPH_EATTRIBUTES     = 51,
IGRAPH_EATTRCOMBINE    = 52,
IGRAPH_ELAPACK         = 53,
IGRAPH_EDRL            = 54,
IGRAPH_EOVERFLOW       = 55,
IGRAPH_EGLP            = 56,
IGRAPH_CPUTIME         = 57,
IGRAPH_EUNDERFLOW      = 58,
IGRAPH_ERWSTUCK        = 59,
IGRAPH_STOP            = 60,
IGRAPH_ERANGE          = 61
} igraph_error_type_t;
```

These are the possible values returned by **igraph** functions. Note that these are interesting only if you defined an error handler with `igraph_set_error_handler()`. Otherwise the program is aborted and the function causing the error never returns.

Values:

IGRAPH_SUCCESS:	The function successfully completed its task.
IGRAPH_FAILURE:	Something went wrong. You'll almost never meet this error as normally more specific error codes are used.
IGRAPH_ENOMEM:	There wasn't enough memory to allocate on the heap.
IGRAPH_PARSEERROR:	A parse error was found in a file.
IGRAPH_EINVAL:	A parameter's value is invalid. E.g. negative number was specified as the number of vertices.
IGRAPH_EXISTS:	A graph/vertex/edge attribute is already installed with the given name.
IGRAPH_EINVEVECTOR:	Invalid vector of vertex IDs. A vertex ID is either negative or bigger than the number of vertices minus one.
IGRAPH_EINVVID:	Invalid vertex ID, negative or too big.
IGRAPH_NONSQUARE:	A non-square matrix was received while a square matrix was expected.
IGRAPH_EINVMODE:	Invalid mode parameter.
IGRAPH_EFILE:	A file operation failed. E.g. a file doesn't exist, or the user has no rights to open it.
IGRAPH_UNIMPLEMENTED:	Attempted to call an unimplemented or disabled (at compile-time) function.
IGRAPH_DIVERGED:	A numeric algorithm failed to converge.
IGRAPH_ARPACK_PROD:	Matrix-vector product failed (not used any more).
IGRAPH_ARPACK_NPOS:	N must be positive.
IGRAPH_ARPACK_NEVNPOS:	NEV must be positive.
IGRAPH_ARPACK_NCVSMALL:	NCV must be bigger.
IGRAPH_ARPACK_NONPOSI:	Maximum number of iterations should be positive.
IGRAPH_ARPACK_WHICHINV:	Invalid WHICH parameter.
IGRAPH_ARPACK_BMATINV:	Invalid BMAT parameter.
IGRAPH_ARPACK_WORKLSMALL:	WORKL is too small.
IGRAPH_ARPACK_TRIDERR:	LAPACK error in tridiagonal eigenvalue calculation.
IGRAPH_ARPACK_ZEROSTART:	Starting vector is zero.
IGRAPH_ARPACK_MODEINV:	MODE is invalid.
IGRAPH_ARPACK_MODEBMAT:	MODE and BMAT are not compatible.
IGRAPH_ARPACK_ISHIFT:	ISHIFT must be 0 or 1.

IGRAPH_ARPACK_NEVBE:	NEV and WHICH='BE' are incompatible.
IGRAPH_ARPACK_NOFACT:	Could not build an Arnoldi factorization.
IGRAPH_ARPACK_FAILED:	No eigenvalues to sufficient accuracy.
IGRAPH_ARPACK_HOVMNY:	HOVMNY is invalid.
IGRAPH_ARPACK_HOVMNYS:	HOVMNY='S' is not implemented.
IGRAPH_ARPACK_EVDIFF:	Different number of converged Ritz values.
IGRAPH_ARPACK_SHUR:	Error from calculation of a real Schur form.
IGRAPH_ARPACK_LAPACK:	LAPACK (dtrevc) error for calculating eigenvectors.
IGRAPH_ARPACK_UNKNOWN:	Unknown ARPACK error.
IGRAPH_ENEGLOOP:	Negative loop detected while calculating shortest paths.
IGRAPH_EINTERNAL:	Internal error, likely a bug in igraph.
IGRAPH_EDIVZERO:	Big integer division by zero.
IGRAPH_GLP_EBOUND:	GLPK error (GLP_EBOUND).
IGRAPH_GLP_EROOT:	GLPK error (GLP_EROOT).
IGRAPH_GLP_ENOPFS:	GLPK error (GLP_ENOPFS).
IGRAPH_GLP_ENODFS:	GLPK error (GLP_ENODFS).
IGRAPH_GLP_EFAIL:	GLPK error (GLP_EFAIL).
IGRAPH_GLP_EMIPGAP:	GLPK error (GLP_EMIPGAP).
IGRAPH_GLP_ETMLIM:	GLPK error (GLP_ETMLIM).
IGRAPH_GLP_ESTOP:	GLPK error (GLP_ESTOP).
IGRAPH_EATTRIBUTES:	Attribute handler error. The user is not expected to find this; it is signalled if some igraph function is not using the attribute handler interface properly.
IGRAPH_EATTRCOMBINE:	Unimplemented attribute combination method for the given attribute type.
IGRAPH_ELAPACK:	A LAPACK call resulted in an error.
IGRAPH_EDRL:	Internal error in the DrL layout generator.
IGRAPH_EOVERFLOW:	Integer or double overflow.
IGRAPH_EGLP:	Internal GLPK error.
IGRAPH_CPUTIME:	CPU time exceeded.
IGRAPH_EUNDERFLOW:	Integer or double underflow.
IGRAPH_ERWSTUCK:	Random walk got stuck.

igraph_strerror — Textual description of an error.

```
const char* igraph_strerror(const igraph_error_t igraph_errno);
```

This is a simple utility function, it gives a short general textual description for an **igraph** error code.

Arguments:

igraph_errno: The **igraph** error code.

Returns:

pointer to the textual description of the error code.

Warning messages

igraph also supports warning messages in addition to error messages. Warning messages typically do not terminate the program, but they are usually crucial to the user.

igraph warnings are handled similarly to errors. There is a separate warning handler function that is called whenever an **igraph** function triggers a warning. This handler can be set by the `igraph_set_warning_handler()` function. There are two predefined simple warning handlers, `igraph_warning_handler_ignore()` and `igraph_warning_handler_print()`, the latter being the default.

To trigger a warning, **igraph** functions typically use the `IGRAPH_WARNING()` macro, the `igraph_warning()` function, or if more flexibility is needed, `igraph_warningf()`.

igraph_warning_handler_t — The type of igraph warning handler functions.

```
typedef void igraph_warning_handler_t (const char *reason, const char *file, in
```

Currently it is defined to have the same type as `igraph_error_handler_t`, although the last (error code) argument is not used.

igraph_set_warning_handler — Installs a warning handler.

```
igraph_warning_handler_t* igraph_set_warning_handler(igraph_warning_handler_t*
```

Install the supplied warning handler function.

Arguments:

new_handler: The new warning handler function to install. Supply a null pointer here to uninstall the current warning handler, without installing a new one.

Returns:

The current warning handler function.

IGRAPH_WARNING — Triggers a warning.

```
#define IGRAPH_WARNING(reason)
```

This is the usual way of triggering a warning from an igraph function. It calls `igraph_warning()`.

Arguments:

reason: The warning message.

IGRAPH_WARNINGF — Triggers a warning, with printf-like syntax.

```
#define IGRAPH_WARNINGF
```

igraph functions can use this macro when they notice a warning and want to pass on extra information to the user about what went wrong. It calls `igraph_warningf()` with the proper parameters and no error code.

Arguments:

reason: Textual description of the warning, a template string with the same syntax as the standard `printf` C library function.

...: The additional arguments to be substituted into the template string.

igraph_warning — Triggers a warning.

```
void igraph_warning(const char *reason, const char *file, int line);
```

Call this function if you want to trigger a warning from within a function that uses **igraph**.

Arguments:

reason: Textual description of the warning.

file: The source file in which the warning was noticed.

line: The number of line in the source file which triggered the warning.

igraph_errno: Warnings could have potentially error codes as well, but this is currently not used in igraph.

Returns:

The supplied error code.

igraph_warningf — Triggers a warning, printf-like version.

```
IGRAPH_FUNCATTR_PRINTFLIKE(1,4)
IGRAPH_EXPORT void igraph_warningf(const char *reason, const char *file, int line,
```

This function is similar to `igraph_warning()`, but uses a printf-like syntax. It substitutes the additional arguments into the *reason* template string and calls `igraph_warning()`.

Arguments:

<i>reason</i> :	Textual description of the warning, a template string with the same syntax as the standard printf C library function.
<i>file</i> :	The source file in which the warning was noticed.
<i>line</i> :	The number of line in the source file which triggered the warning.
<i>igraph_errno</i> :	Warnings could have potentially error codes as well, but this is currently not used in igraph.
<i>...</i> :	The additional arguments to be substituted into the template string.

igraph_warning_handler_ignore — Ignores all warnings.

```
void igraph_warning_handler_ignore(const char *reason, const char *file, int line,
```

This warning handler function simply ignores all warnings.

Arguments:

<i>reason</i> :	Textual description of the warning.
<i>file</i> :	The source file in which the warning was noticed.
<i>line</i> :	The number of line in the source file which triggered the warning..
<i>igraph_errno</i> :	Warnings could have potentially error codes as well, but this is currently not used in igraph.

igraph_warning_handler_print — Prints all warnings to the standard error.

```
void igraph_warning_handler_print(const char *reason, const char *file, int line,
```

This warning handler function simply prints all warnings to the standard error.

Arguments:

<i>reason</i> :	Textual description of the warning.
<i>file</i> :	The source file in which the warning was noticed.
<i>line</i> :	The number of line in the source file which triggered the warning..
<i>igraph_errno</i> :	Warnings could have potentially error codes as well, but this is currently not used in igraph.

Advanced topics

Writing error handlers

The contents of the rest of this chapter might be useful only for those who want to create an interface to **igraph** from another language, or use igraph from a GUI application. Most readers can safely skip to the next chapter.

You can write and install error handlers simply by defining a function of type `igraph_error_handler_t` and calling `igraph_set_error_handler()`. This feature is useful for interface writers, as **igraph** will have the chance to signal errors the appropriate way. For example, the R interface uses R's native printing facilities to communicate errors, while the Python interface converts them into Python exceptions.

The two main tasks of the error handler are to report the error (i.e. print the error message) and ensure proper resource cleanup. This is ensured by calling `IGRAPH_FINALLY_FREE()`, which deallocates some of the temporary memory to avoid memory leaks. Note that this may invalidate the error message buffer *reason* passed to the error handler. Do not access it after having called `IGRAPH_FINALLY_FREE()`.

As of **igraph** 0.10, temporary memory is deallocated in stages, through multiple calls to the error handler (and indirectly to `IGRAPH_FINALLY_FREE()`). Therefore, error handlers that do not abort the program immediately are expected to return. The error handler should not perform a `longjmp`, as this may lead to some of the memory not getting freed.

igraph_set_error_handler — Sets a new error handler.

```
igraph_error_handler_t* igraph_set_error_handler(igraph_error_handler_t* new_h
```

Installs a new error handler. If called with `NULL`, it installs the default error handler (which is currently `igraph_error_handler_abort`).

Arguments:

new_handler: The error handler function to install.

Returns:

The old error handler function. This should be saved and restored if *new_handler* is not needed any more.

Error handling internals

If an error happens, the functions in the library call the `IGRAPH_ERROR()` macro with a textual description of the error and an **igraph** error code. This macro calls (through the `igraph_error()`

function) the installed error handler. Another useful macro is `IGRAPH_CHECK()`. This checks the return value of its argument, which is normally a function call, and calls `IGRAPH_ERROR()` if it is not `IGRAPH_SUCCESS`.

IGRAPH_ERROR — Trigger an error.

```
#define IGRAPH_ERROR(reason, igraph_errno)
```

igraph functions usually use this macro when they notice an error. It calls `igraph_error()` with the proper parameters and if that returns the macro returns the "calling" function as well, with the error code. If for some (suspicious) reason you want to call the error handler without returning from the current function, call `igraph_error()` directly.

Arguments:

reason: Textual description of the error. This should be something more descriptive than the text associated with the error code. E.g. if the error code is `IGRAPH_EINVAL`, its associated text (see `igraph_strerror()`) is "Invalid value" and this string should explain which parameter was invalid and maybe why.

igraph_errno: The **igraph** error code.

IGRAPH_ERRORF — Triggers an error, with printf-like syntax.

```
#define IGRAPH_ERRORF
```

igraph functions can use this macro when they notice an error and want to pass on extra information to the user about what went wrong. It calls `igraph_errorf()` with the proper parameters and if that returns the macro returns the "calling" function as well, with the error code. If for some (suspicious) reason you want to call the error handler without returning from the current function, call `igraph_errorf()` directly.

Arguments:

reason: Textual description of the error, a template string with the same syntax as the standard `printf` C library function. This should be something more descriptive than the text associated with the error code. E.g. if the error code is `IGRAPH_EINVAL`, its associated text (see `igraph_strerror()`) is "Invalid value" and this string should explain which parameter was invalid and maybe what was expected and what was recieved.

igraph_errno: The **igraph** error code.

...: The additional arguments to be substituted into the template string.

igraph_error — Triggers an error.

```
igraph_error_t igraph_error(const char *reason, const char *file, int line,  
                           igraph_error_t igraph_errno);
```

igraph functions usually call this function (most often via the `IGRAPH_ERROR` macro) if they notice an error. It calls the currently installed error handler function with the supplied arguments.

Arguments:

reason: Textual description of the error.

file: The source file in which the error was noticed.

line: The number of line in the source file which triggered the error.

igraph_errno: The **igraph** error code.

Returns:

the error code (if it returns)

See also:

`igraph_errorf()`.

igraph_errorf — Triggers an error, printf-like version.

```
IGRAPH_FUNCATTR_PRINTFLIKE(1,5)
IGRAPH_EXPORT igraph_error_t igraph_errorf(const char *reason, const char *file
                                           igraph_error_t igraph_errno, ...);
```

Arguments:

reason: Textual description of the error, interpreted as a `printf` format string.

file: The source file in which the error was noticed.

line: The line in the source file which triggered the error.

igraph_errno: The **igraph** error code.

...: Additional parameters, the values to substitute into the format string.

See also:

`igraph_error()`.

IGRAPH_CHECK — Checks the return value of a function call.

```
#define IGRAPH_CHECK(expr)
```

Arguments:

expr: An expression, usually a function call. It is guaranteed to be evaluated only once.

Executes the expression and checks its value. If this is not `IGRAPH_SUCCESS`, it calls `IGRAPH_ERROR` with the value as the error code. Here is an example usage:

```
IGRAPH_CHECK(vector_push_back(&v, 100));
```

There is only one reason to use this macro when writing **igraph** functions. If the user installs an error handler which returns to the auxiliary calling code (like `igraph_error_handler_ignore` and `igraph_error_handler_printignore`), and the **igraph** function signalling the error is called from another **igraph** function then we need to make sure that the error is propagated back to the auxiliary (i.e. non-igraph) calling function. This is achieved by using `IGRAPH_CHECK` on every **igraph** call which can return an error code.

IGRAPH_CHECK_CALLBACK — Checks the return value of a callback.

```
#define IGRAPH_CHECK_CALLBACK(expr, code)
```

Identical to `IGRAPH_CHECK`, but treats `IGRAPH_STOP` as a normal (non-erroneous) return code. This macro is used in some **igraph** functions that allow the user to hook into a long-running calculation with a callback function. When the user-defined callback function returns `IGRAPH_SUCCESS`, the calculation will proceed normally. Returning `IGRAPH_STOP` from the callback will terminate the calculation without reporting an error. Returning any other value from the callback is treated as an error code, and **igraph** will trigger the necessary cleanup functions before exiting the function.

Note that `IGRAPH_CHECK_CALLBACK` does not handle `IGRAPH_STOP` by any means except returning it in the variable pointed to by `code`. It is the responsibility of the caller to handle `IGRAPH_STOP` accordingly.

Arguments:

expr: An expression, usually a call to a user-defined callback function. It is guaranteed to be evaluated only once.

code: Pointer to an optional variable of type `igraph_error_t`; the value of this variable will be set to the error code if it is not a null pointer.

Deallocating memory

If a function runs into an error (and the program is not aborted) the error handler should deallocate all temporary memory. This is done by storing the address and the destroy function of all temporary objects in a stack. The `IGRAPH_FINALLY` function declares an object as temporary by placing its address in the stack. If an **igraph** function returns with success it calls `IGRAPH_FINALLY_CLEAN()` with the number of objects to remove from the stack. If an error happens however, the error handler should call `IGRAPH_FINALLY_FREE()` to deallocate each object added to the stack. This means that the temporary objects allocated in the calling function (and etc.) will be freed as well.

IGRAPH_FINALLY — Registers an object for deallocation.

```
#define IGRAPH_FINALLY(func, ptr)
```

This macro places the address of an object, together with the address of its destructor in a stack. This stack is used if an error happens to deallocate temporarily allocated objects to prevent memory leaks. After manual deallocation, objects are removed from the stack using `IGRAPH_FINALLY_CLEAN()`.

Arguments:

func: The function which is normally called to destroy the object.

ptr: Pointer to the object itself.

IGRAPH_FINALLY_CLEAN — Signals clean deallocation of objects.

```
void IGRAPH_FINALLY_CLEAN(int num);
```

Removes the specified number of objects from the stack of temporarily allocated objects. It is typically called immediately after manually destroying the objects:

```
igraph_vector_t vector;  
igraph_vector_init(&vector, 10);  
IGRAPH_FINALLY(igraph_vector_destroy, &vector);  
// use vector  
igraph_vector_destroy(&vector);  
IGRAPH_FINALLY_CLEAN(1);
```

Arguments:

num: The number of objects to remove from the bookkeeping stack.

IGRAPH_FINALLY_FREE — Deallocates objects registered at the current level.

```
void IGRAPH_FINALLY_FREE(void);
```

Calls the destroy function for all objects in the current level of the stack of temporarily allocated objects, i.e. up to the nearest mark set by `IGRAPH_FINALLY_ENTER()`. This function must only be called from an error handler. It is *not* appropriate to use it instead of destroying each unneeded object of a function, as it destroys the temporary objects of the caller function (and so on) as well.

Writing igraph functions with proper error handling

There are some simple rules to keep in order to have functions behaving well in erroneous situations. First, check the arguments of the functions and call `IGRAPH_ERROR()` if they are invalid. Second, call `IGRAPH_FINALLY` on each dynamically allocated object and call `IGRAPH_FINALLY_CLEAN()` with the proper argument before returning. Third, use `IGRAPH_CHECK` on all **igraph** function calls which can generate errors.

The size of the stack used for this bookkeeping is fixed, and small. If you want to allocate several objects, write a destroy function which can deallocate all of these. See the `adjlist.c` file in the **igraph** source for an example.

For some functions these mechanisms are simply not flexible enough. These functions should define their own error handlers and restore the error handler before they return.

Fatal errors

In some rare situations, **igraph** may encounter an internal error that cannot be fully handled. In this case, it will call the current fatal error handler. The default fatal error handler simply prints the error and aborts the program.

Fatal error handlers do not return. Typically, they might abort the the program immediately, or in the case of the high-level **igraph** interfaces, they might return to the top level using a `longjmp()`. The fatal error handler is only called when a serious error has occurred, and as a result igraph may be in an inconsistent state. The purpose of returning to the top level is to give the user a chance to save their work instead of aborting immediately. However, the program session should be restarted as soon as possible.

Most projects that use **igraph** will use the default fatal error handler.

igraph_fatal_handler_t — The type of igraph fatal error handler functions.

```
typedef void igraph_fatal_handler_t (const char *reason, const char *file, int line);
```

Functions of this type *must* not return. Typically they call `abort()` or do a `longjmp()`.

Arguments:

reason: Textual description of the error.

file: The source file in which the error is noticed.

line: The number of the line in the source file which triggered the error

igraph_fatal_handler_abort — Abort program in case of fatal error.

```
IGRAPH_EXPORT igraph_fatal_handler_t igraph_fatal_handler_abort;
```

The default fatal error handler, prints an error message and aborts the program.

IGRAPH_FATAL — Triggers a fatal error.

```
#define IGRAPH_FATAL(reason)
```

This is the usual way of triggering a fatal error from an igraph function. It calls `igraph_fatal()`.

Use this macro only in situations where the error cannot be handled. The normal way to handle errors is `IGRAPH_ERROR()`.

Arguments:

reason: The error message.

IGRAPH_FATALF — Triggers a fatal error, with printf-like syntax.

```
#define IGRAPH_FATALF
```

igraph functions can use this macro when a fatal error occurs and want to pass on extra information to the user about what went wrong. It calls `igraph_fatal_f()` with the proper parameters.

Arguments:

reason: Textual description of the error, a template string with the same syntax as the standard `printf` C library function.

...: The additional arguments to be substituted into the template string.

IGRAPH_ASSERT — igraph-specific replacement for `assert()`.

```
#define IGRAPH_ASSERT(condition)
```

This macro is like the standard `assert()`, but instead of calling `abort()`, it calls `igraph_fatal()`. This allows for returning the control to the calling program, e.g. returning to the top level in a high-level **igraph** interface.

Unlike `assert()`, `IGRAPH_ASSERT()` is not disabled when the `NDEBUG` macro is defined.

This macro is meant for internal use by **igraph**.

Since a typical fatal error handler does a `longjmp()`, avoid using this macro in C++ code. With most compilers, destructor will not be called when `longjmp()` leaves the current scope.

Arguments:

condition: The condition to be checked.

igraph_fatal — Triggers a fatal error.

```
IGRAPH_FUNCATTR_NORETURN void igraph_fatal(const char *reason, const char *file,
```

This function triggers a fatal error. Typically it is called indirectly through `IGRAPH_FATAL()` or `IGRAPH_ASSERT()`.

Arguments:

reason: Textual description of the error.

file: The source file in which the error was noticed.

line: The number of line in the source file which triggered the error.

igraph_fatal_f — Triggers a fatal error, printf-like syntax.

```
IGRAPH_FUNCATTR_PRINTF_LIKE(1,4)
IGRAPH_EXPORT IGRAPH_FUNCATTR_NORETURN void igraph_fatal_f(const char *reason, c
```

This function is similar to `igraph_fatal()`, but uses a printf-like syntax. It substitutes the additional arguments into the *reason* template string and calls `igraph_fatal()`.

Arguments:

reason: Textual description of the error.

file: The source file in which the error was noticed.
line: The number of line in the source file which triggered the error.
...: The additional arguments to be substituted into the template string.

Error handling and threads

It is likely that the **igraph** error handling method is *not* thread-safe, mainly because of the static global stack which is used to store the address of the temporarily allocated objects. This issue might be addressed in a later version of **igraph**.

Chapter 6. Memory (de)allocation

igraph_malloc — Allocate memory that can be safely deallocated by igraph functions.

```
void *igraph_malloc(size_t size);
```

This function behaves like `malloc()`, but it ensures that at least one byte is allocated even when the caller asks for zero bytes.

Arguments:

size: Number of bytes to be allocated. Zero is treated as one byte.

Returns:

Pointer to the piece of allocated memory; `NULL` if the allocation failed.

See also:

`igraph_calloc()`, `igraph_realloc()`, `igraph_free()`

igraph_calloc — Allocate memory that can be safely deallocated by igraph functions.

```
void *igraph_calloc(size_t count, size_t size);
```

This function behaves like `calloc()`, but it ensures that at least one byte is allocated even when the caller asks for zero bytes.

Arguments:

count: Number of items to be allocated.

size: Size of a single item to be allocated.

Returns:

Pointer to the piece of allocated memory; `NULL` if the allocation failed.

See also:

`igraph_malloc()`, `igraph_realloc()`, `igraph_free()`

igraph_realloc — Reallocate memory that can be safely deallocated by igraph functions.

```
void *igraph_realloc(void* ptr, size_t size);
```

This function behaves like `realloc()`, but it ensures that at least one byte is allocated even when the caller asks for zero bytes.

Arguments:

ptr: The pointer to reallocate.

size: Number of bytes to be allocated.

Returns:

Pointer to the piece of allocated memory; `NULL` if the allocation failed.

See also:

`igraph_free()`, `igraph_malloc()`

igraph_free — Deallocate memory that was allocated by igraph functions.

```
void igraph_free(void *ptr);
```

This function exposes the `free()` function used internally by igraph.

Arguments:

ptr: Pointer to the piece of memory to be deallocated.

Time complexity: platform dependent, ideally it should be $O(1)$.

See also:

`igraph_calloc()`, `igraph_malloc()`, `igraph_realloc()`

Chapter 7. Data structure library: vector, matrix, other data types

About template types

Some of the container types listed in this section are defined for many base types. This is similar to templates in C++ and generics in Ada, but it is implemented via preprocessor macros since the C language cannot handle it. Here is the list of template types and the all base types they currently support:

vector	Vector is currently defined for <code>igraph_real_t</code> , <code>igraph_integer_t</code> (int), <code>char</code> (char), <code>igraph_bool_t</code> (bool) and <code>igraph_complex_t</code> (complex). The default is <code>igraph_real_t</code> .
matrix	Matrix is currently defined for <code>igraph_real_t</code> , <code>igraph_integer_t</code> (int), <code>char</code> (char), <code>igraph_bool_t</code> (bool) and <code>igraph_complex_t</code> (complex). The default is <code>igraph_real_t</code> .
array3	Array3 is currently defined for <code>igraph_real_t</code> , <code>igraph_integer_t</code> (int), <code>char</code> (char) and <code>igraph_bool_t</code> (bool). The default is <code>igraph_real_t</code> .
stack	Stack is currently defined for <code>igraph_real_t</code> , <code>igraph_integer_t</code> (int), <code>char</code> (char), <code>igraph_bool_t</code> (bool) and <code>void*</code> (ptr). The default is <code>igraph_real_t</code> .
double-ended queue	Dqueue is currently defined for <code>igraph_real_t</code> , <code>igraph_integer_t</code> (int), <code>char</code> (char) and <code>igraph_bool_t</code> (bool). The default is <code>igraph_real_t</code> .
heap	Heap is currently defined for <code>igraph_real_t</code> , <code>igraph_integer_t</code> (int), <code>char</code> (char). In addition both maximum and minimum heaps are available. The default is the <code>igraph_real_t</code> maximum heap.
list of vectors	Lists of vectors are currently defined for vectors holding <code>igraph_real_t</code> and <code>igraph_integer_t</code> (int). The default is <code>igraph_real_t</code> .
list of matrices	Lists of matrices are currently defined for matrices holding <code>igraph_real_t</code> only.

The name of the base element (in parentheses) is added to the function names, except for the default type.

Some examples:

- `igraph_vector_t` is a vector of `igraph_real_t` elements. Its functions are `igraph_vector_init`, `igraph_vector_destroy`, `igraph_vector_sort`, etc.
- `igraph_vector_bool_t` is a vector of `igraph_bool_t` elements; initialize it with `igraph_vector_bool_init`, destroy it with `igraph_vector_bool_destroy`, etc.
- `igraph_heap_t` is a maximum heap with `igraph_real_t` elements. The corresponding functions are `igraph_heap_init`, `igraph_heap_pop`, etc.
- `igraph_heap_min_t` is a minimum heap with `igraph_real_t` elements. The corresponding functions are called `igraph_heap_min_init`, `igraph_heap_min_pop`, etc.

- `igraph_heap_int_t` is a maximum heap with `igraph_integer_t` elements. Its functions have the `igraph_heap_int_` prefix.
- `igraph_heap_min_int_t` is a minimum heap containing `igraph_integer_t` elements. Its functions have the `igraph_heap_min_int_` prefix.
- `igraph_vector_list_t` is a list of (floating-point) vectors; each element in this data structure is an `igraph_vector_t`. Similarly, `igraph_matrix_list_t` is a list of (floating-point) matrices; each element in this data structure is an `igraph_matrix_t`.
- `igraph_vector_int_list_t` is a list of integer vectors; each element in this data structure is an `igraph_vector_int_t`.

Note that the `VECTOR` and the `MATRIX` macros can be used on *all* vector and matrix types. `VECTOR` cannot be used on *lists* of vectors, though, only on the individual vectors in the list.

Vectors

About `igraph_vector_t` objects

The `igraph_vector_t` data type is a simple and efficient interface to arrays containing numbers. It is something similar to (but much simpler than) the vector template in the C++ standard library.

There are multiple variants of `igraph_vector_t`; the basic variant stores doubles, but there is also `igraph_vector_int_t` for integers (of type `igraph_integer_t`), `igraph_vector_bool_t` for booleans (of type `igraph_bool_t`) and so on. Vectors are used extensively in **igraph**; all functions that expect or return a list of numbers use `igraph_vector_t` or `igraph_vector_int_t` to achieve this. Integer vectors are typically used when the vector is supposed to hold vertex or edge identifiers, while `igraph_vector_t` is used when the vector is expected to hold fractional numbers or infinities.

The `igraph_vector_t` type and its variants usually use $O(n)$ space to store n elements. Sometimes they use more, this is because vectors can shrink, but even if they shrink, the current implementation does not free a single bit of memory.

The elements in an `igraph_vector_t` object and its variants are indexed from zero, we follow the usual C convention here.

The elements of a vector always occupy a single block of memory, the starting address of this memory block can be queried with the `VECTOR` macro. This way, vector objects can be used with standard mathematical libraries, like the GNU Scientific Library.

Almost all of the functions described below for `igraph_vector_t` also exist for all the other vector type variants. These variants are not documented separately; you can simply replace `vector` with `vector_int`, `vector_bool` or something similar if you need a function for another variant. For instance, to initialize a vector of type `igraph_vector_int_t`, you need to use `igraph_vector_int_t_init()` and not `igraph_vector_init()`.

Constructors and destructors

`igraph_vector_t` objects have to be initialized before using them, this is analogous to calling a constructor on them. There are a number of `igraph_vector_t` constructors, for your convenience. `igraph_vector_init()` is the basic constructor, it creates a vector of the given length, filled with zeros. `igraph_vector_init_copy()` creates a new identical copy of an already existing and initialized vector. `igraph_vector_init_array()` creates a vector by copying a regular C array. `igraph_vector_init_range()` creates a vector containing a regular sequence with increment one.

`igraph_vector_view()` is a special constructor, it allows you to handle a regular C array as a vector without copying its elements.

If a `igraph_vector_t` object is not needed any more, it should be destroyed to free its allocated memory by calling the `igraph_vector_t` destructor, `igraph_vector_destroy()`.

Note that vectors created by `igraph_vector_view()` are special, you must not call `igraph_vector_destroy()` on these.

`igraph_vector_init` — Initializes a vector object (constructor).

```
igraph_error_t igraph_vector_init(igraph_vector_t* v, igraph_integer_t size);
```

Every vector needs to be initialized before it can be used, and there are a number of initialization functions or otherwise called constructors. This function constructs a vector of the given size and initializes each entry to 0. Note that `igraph_vector_null()` can be used to set each element of a vector to zero. However, if you want a vector of zeros, it is much faster to use this function than to create a vector and then invoke `igraph_vector_null()`.

Every vector object initialized by this function should be destroyed (ie. the memory allocated for it should be freed) when it is not needed anymore, the `igraph_vector_destroy()` function is responsible for this.

Arguments:

v: Pointer to a not yet initialized vector object.

size: The size of the vector.

Returns:

error code: `IGRAPH_ENOMEM` if there is not enough memory.

Time complexity: operating system dependent, the amount of “time” required to allocate $O(n)$ elements, n is the number of elements.

`igraph_vector_init_array` — Initializes a vector from an ordinary C array (constructor).

```
igraph_error_t igraph_vector_init_array(
    igraph_vector_t *v, const igraph_real_t *data, igraph_integer_t length)
```

Arguments:

v: Pointer to an uninitialized vector object.

data: A regular C array.

length: The length of the C array.

Returns:

Error code: `IGRAPH_ENOMEM` if there is not enough memory.

Time complexity: operating system specific, usually $O(\text{length})$.

igraph_vector_init_copy — Initializes a vector from another vector object (constructor).

```
igraph_error_t igraph_vector_init_copy(
    igraph_vector_t *to, const igraph_vector_t *from
);
```

The contents of the existing vector object will be copied to the new one.

Arguments:

to: Pointer to a not yet initialized vector object.

from: The original vector object to copy.

Returns:

Error code: IGRAPH_ENOMEM if there is not enough memory.

Time complexity: operating system dependent, usually $O(n)$, n is the size of the vector.

igraph_vector_init_range — Initializes a vector with a range.

```
igraph_error_t igraph_vector_init_range(igraph_vector_t *v, igraph_real_t from,
```

The vector will contain the numbers *start*, *start*+1, ..., *end*-1. Note that the range is closed from the left and open from the right, according to C conventions.

Arguments:

v: Pointer to an uninitialized vector object.

start: The lower limit in the range (inclusive).

end: The upper limit in the range (exclusive).

Returns:

Error code: IGRAPH_ENOMEM: out of memory.

Time complexity: $O(n)$, the number of elements in the vector.

igraph_vector_destroy — Destroys a vector object.

```
void igraph_vector_destroy(igraph_vector_t* v);
```

All vectors initialized by `igraph_vector_init()` should be properly destroyed by this function. A destroyed vector needs to be reinitialized by `igraph_vector_init()`, `igraph_vector_init_array()` or another constructor.

Arguments:

v: Pointer to the (previously initialized) vector object to destroy.

Time complexity: operating system dependent.

Initializing elements

igraph_vector_null — Sets each element in the vector to zero.

```
void igraph_vector_null(igraph_vector_t* v);
```

Note that `igraph_vector_init()` sets the elements to zero as well, so it makes no sense to call this function on a just initialized vector. Thus if you want to construct a vector of zeros, then you should use `igraph_vector_init()`.

Arguments:

v: The vector object.

Time complexity: $O(n)$, the size of the vector.

igraph_vector_fill — Fill a vector with a constant element

```
void igraph_vector_fill(igraph_vector_t* v, igraph_real_t e);
```

Sets each element of the vector to the supplied constant.

Arguments:

vector: The vector to work on.

e: The element to fill with.

Time complexity: $O(n)$, the size of the vector.

igraph_vector_range — Updates a vector to store a range.

```
igraph_error_t igraph_vector_range(igraph_vector_t *v, igraph_real_t from, igraph_real_t to);
```

Sets the elements of the vector to contain the numbers *start*, *start*+1, ..., *end*-1. Note that the range is closed from the left and open from the right, according to C conventions.

Arguments:

v: The vector to update.

start: The lower limit in the range (inclusive).

end: The upper limit in the range (exclusive).

Returns:

Error code: IGRAPH_ENOMEM: out of memory.

Time complexity: $O(n)$, the number of elements in the vector.

Accessing elements

The simplest way to access an element of a vector is to use the `VECTOR` macro. This macro can be used both for querying and setting `igraph_vector_t` elements. If you need a function, `igraph_vector_get()` queries and `igraph_vector_set()` sets an element of a vector. `igraph_vector_get_ptr()` returns the address of an element.

`igraph_vector_tail()` returns the last element of a non-empty vector. There is no `igraph_vector_head()` function however, as it is easy to write `VECTOR(v)[0]` instead.

VECTOR — Accessing an element of a vector.

```
#define VECTOR(v)
```

Usage:

```
VECTOR(v)[0]
```

to access the first element of the vector, you can also use this in assignments, like:

```
VECTOR(v)[10]=5;
```

Note that there are no range checks right now. This functionality might be redefined later as a real function instead of a `#define`.

Arguments:

`v`: The vector object.

Time complexity: $O(1)$.

igraph_vector_get — Access an element of a vector.

```
igraph_real_t igraph_vector_get(const igraph_vector_t* v, igraph_integer_t pos)
```

Arguments:

`v`: The `igraph_vector_t` object.

`pos`: The position of the element, the index of the first element is zero.

Returns:

The desired element.

See also:

`igraph_vector_get_ptr()` and the `VECTOR` macro.

Time complexity: $O(1)$.

igraph_vector_get_ptr — Get the address of an element of a vector

```
igraph_real_t* igraph_vector_get_ptr(const igraph_vector_t* v, igraph_integer_t
```

Arguments:

v: The `igraph_vector_t` object.

pos: The position of the element, the position of the first element is zero.

Returns:

Pointer to the desired element.

See also:

`igraph_vector_get()` and the `VECTOR` macro.

Time complexity: $O(1)$.

igraph_vector_set — Assignment to an element of a vector.

```
void igraph_vector_set(igraph_vector_t* v, igraph_integer_t pos, igraph_real_t
```

Arguments:

v: The `igraph_vector_t` element.

pos: Position of the element to set.

value: New value of the element.

See also:

`igraph_vector_get()`.

igraph_vector_tail — Returns the last element in a vector.

```
igraph_real_t igraph_vector_tail(const igraph_vector_t *v);
```

It is an error to call this function on an empty vector, the result is undefined.

Arguments:

v: The vector object.

Returns:

The last element.

Time complexity: $O(1)$.

Vector views

igraph_vector_view — Handle a regular C array as a **igraph_vector_t**.

```
const igraph_vector_t* igraph_vector_view(const igraph_vector_t *v,  
                                           const igraph_real_t *data, igraph_integer_t length);
```

This is a special `igraph_vector_t` constructor. It allows to handle a regular C array as a `igraph_vector_t` temporarily. Be sure that you *don't* ever call the destructor (`igraph_vector_destroy()`) on objects created by this constructor.

Arguments:

v: Pointer to an uninitialized `igraph_vector_t` object.

data: Pointer, the C array. It may not be NULL, except when *length* is zero.

length: The length of the C array.

Returns:

Pointer to the vector object, the same as the *v* parameter, for convenience.

Time complexity: $O(1)$

Copying vectors

igraph_vector_copy_to — Copies the contents of a vector to a C array.

```
void igraph_vector_copy_to(const igraph_vector_t *v, igraph_real_t *to);
```

The C array should have sufficient length.

Arguments:

v: The vector object.

to: The C array.

Time complexity: $O(n)$, *n* is the size of the vector.

igraph_vector_update — Update a vector from another one.

```
igraph_error_t igraph_vector_update(igraph_vector_t *to,
                                     const igraph_vector_t *from);
```

After this operation the contents of *to* will be exactly the same as that of *from*. The vector *to* will be resized if it was originally shorter or longer than *from*.

Arguments:

to: The vector to update.

from: The vector to update from.

Returns:

Error code.

Time complexity: $O(n)$, the number of elements in *from*.

igraph_vector_append — Append a vector to another one.

```
igraph_error_t igraph_vector_append(igraph_vector_t *to,
                                     const igraph_vector_t *from);
```

The target vector will be resized (except when *from* is empty).

Arguments:

to: The vector to append to.

from: The vector to append, it is kept unchanged.

Returns:

Error code.

Time complexity: $O(n)$, the number of elements in the new vector.

igraph_vector_swap — Swap all elements of two vectors.

```
igraph_error_t igraph_vector_swap(igraph_vector_t *v1, igraph_vector_t *v2);
```

Arguments:

v1: The first vector.

v2: The second vector.

Returns:

Error code.

Time complexity: $O(1)$.

Exchanging elements

igraph_vector_swap_elements — Swap two elements in a vector.

```
igraph_error_t igraph_vector_swap_elements(igraph_vector_t *v,  
                                           igraph_integer_t i, igraph_integer_t j);
```

Note that currently no range checking is performed.

Arguments:

v: The input vector.

i: Index of the first element.

j: Index of the second element (may be the same as the first one).

Returns:

Error code, currently always IGRAPH_SUCCESS.

Time complexity: $O(1)$.

igraph_vector_reverse — Reverse the elements of a vector.

```
igraph_error_t igraph_vector_reverse(igraph_vector_t *v);
```

The first element will be last, the last element will be first, etc.

Arguments:

v: The input vector.

Returns:

Error code, currently always IGRAPH_SUCCESS.

Time complexity: $O(n)$, the number of elements.

igraph_vector_shuffle — Shuffles a vector in-place using the Fisher-Yates method

```
igraph_error_t igraph_vector_shuffle(igraph_vector_t *v);
```

The Fisher-Yates shuffle ensures that every permutation is equally probable when using a proper randomness source. Of course this does not apply to pseudo-random generators as the cycle of these generators is less than the number of possible permutations of the vector if the vector is long enough.

Arguments:

v: The vector object.

Returns:

Error code, currently always IGRAPH_SUCCESS.

Time complexity: $O(n)$, n is the number of elements in the vector.

References:

(Fisher & Yates 1963) R. A. Fisher and F. Yates. *Statistical Tables for Biological, Agricultural and Medical Research*. Oliver and Boyd, 6th edition, 1963, page 37.

(Knuth 1998) D. E. Knuth. *Seminumerical Algorithms*, volume 2 of *The Art of Computer Programming*. Addison-Wesley, 3rd edition, 1998, page 145.

Example	7.1.	File	examples/simple/
igraph_fisher_yates_shuffle.c			

igraph_vector_permute — Permutes the elements of a vector in place according to an index vector.

```
igraph_error_t igraph_vector_permute(igraph_vector_t* v, const igraph_vector_int_t* ind)
```

This function takes a vector v and a corresponding index vector ind , and permutes the elements of v such that $v[ind[i]]$ is moved to become $v[i]$ after the function is executed.

It is an error to call this function with an index vector that does not represent a valid permutation. Each element in the index vector must be between 0 and the length of the vector minus one (inclusive), and each such element must appear only once. The function does not attempt to validate the index vector.

The index vector that this function takes is compatible with the index vector returned from `igraph_vector_qsort_ind()`; passing in the index vector from `igraph_vector_qsort_ind()` will sort the original vector.

As a special case, this function allows the index vector to be *shorter* than the vector being permuted, in which case the elements whose indices do not occur in the index vector will be removed from the vector.

Arguments:

v : the vector to permute

ind : the index vector

Returns:

Error code: IGRAPH_ENOMEM if there is not enough memory.

Time complexity: $O(n)$, the size of the vector.

Vector operations

igraph_vector_add_constant — Add a constant to the vector.

```
void igraph_vector_add_constant(igraph_vector_t *v, igraph_real_t plus);
```

plus is added to every element of *v*. Note that overflow might happen.

Arguments:

v: The input vector.

plus: The constant to add.

Time complexity: $O(n)$, the number of elements.

igraph_vector_scale — Multiply all elements of a vector by a constant

```
void igraph_vector_scale(igraph_vector_t *v, igraph_real_t by);
```

Arguments:

v: The vector.

by: The constant.

Returns:

Error code. The current implementation always returns with success.

Added in version 0.2.

Time complexity: $O(n)$, the number of elements in a vector.

igraph_vector_add — Add two vectors.

```
igraph_error_t igraph_vector_add(igraph_vector_t *v1,  
                                const igraph_vector_t *v2);
```

Add the elements of *v2* to *v1*, the result is stored in *v1*. The two vectors must have the same length.

Arguments:

v1: The first vector, the result will be stored here.

v2: The second vector, its contents will be unchanged.

Returns:

Error code.

Time complexity: $O(n)$, the number of elements.

igraph_vector_sub — Subtract a vector from another one.

```
igraph_error_t igraph_vector_sub(igraph_vector_t *v1,  
                                const igraph_vector_t *v2);
```

Subtract the elements of *v2* from *v1*, the result is stored in *v1*. The two vectors must have the same length.

Arguments:

v1: The first vector, to subtract from. The result is stored here.

v2: The vector to subtract, it will be unchanged.

Returns:

Error code.

Time complexity: $O(n)$, the length of the vectors.

igraph_vector_mul — Multiply two vectors.

```
igraph_error_t igraph_vector_mul(igraph_vector_t *v1,  
                                const igraph_vector_t *v2);
```

v1 will be multiplied by *v2*, elementwise. The two vectors must have the same length.

Arguments:

v1: The first vector, the result will be stored here.

v2: The second vector, it is left unchanged.

Returns:

Error code.

Time complexity: $O(n)$, the number of elements.

igraph_vector_div — Divide a vector by another one.

```
igraph_error_t igraph_vector_div(igraph_vector_t *v1,  
                                const igraph_vector_t *v2);
```

v1 is divided by *v2*, elementwise. They must have the same length. If the base type of the vector can generate divide by zero errors then please make sure that *v2* contains no zero if you want to avoid trouble.

Arguments:

v1: The dividend. The result is also stored here.

v2: The divisor, it is left unchanged.

Returns:

Error code.

Time complexity: $O(n)$, the length of the vectors.

igraph_vector_floor — Transform a real vector to an integer vector by flooring each element.

```
igraph_error_t igraph_vector_floor(const igraph_vector_t *from, igraph_vector_int_t to);
```

Flooring means rounding down to the nearest integer.

Arguments:

from: The original real vector object.

to: Pointer to an initialized integer vector. The result will be stored here.

Returns:

Error code: IGRAPH_ENOMEM: out of memory

Time complexity: $O(n)$, where n is the number of elements in the vector.

Vector comparisons

igraph_vector_all_e — Are all elements equal?

```
igraph_bool_t igraph_vector_all_e(const igraph_vector_t *lhs,  
                                  const igraph_vector_t *rhs);
```

Checks element-wise equality of two vectors. For vectors containing floating point values, consider using `igraph_matrix_all_almost_e()`.

Arguments:

lhs: The first vector.

rhs: The second vector.

Returns:

True if the elements in the *lhs* are all equal to the corresponding elements in *rhs*. Returns false if the lengths of the vectors don't match.

Time complexity: $O(n)$, the length of the vectors.

igraph_vector_all_almost_e — Are all elements almost equal?

```
igraph_bool_t igraph_vector_all_almost_e(const igraph_vector_t *lhs,  
                                          const igraph_vector_t *rhs,  
                                          igraph_real_t eps);
```

Checks if the elements of two vectors are equal within a relative tolerance.

Arguments:

lhs: The first vector.

rhs: The second vector.

eps: Relative tolerance, see `igraph_almost_equals()` for details.

Returns:

True if the two vectors are almost equal, false if there is at least one differing element or if the vectors are not of the same size.

igraph_vector_all_l — Are all elements less?

```
igraph_bool_t igraph_vector_all_l(const igraph_vector_t *lhs,
                                   const igraph_vector_t *rhs);
```

Arguments:

lhs: The first vector.

rhs: The second vector.

Returns:

Positive integer (=true) if the elements in the *lhs* are all less than the corresponding elements in *rhs*. Returns 0 (=false) if the lengths of the vectors don't match. If any element is NaN, it will return 0 (=false).

Time complexity: $O(n)$, the length of the vectors.

igraph_vector_all_g — Are all elements greater?

```
igraph_bool_t igraph_vector_all_g(const igraph_vector_t *lhs,
                                   const igraph_vector_t *rhs);
```

Arguments:

lhs: The first vector.

rhs: The second vector.

Returns:

Positive integer (=true) if the elements in the *lhs* are all greater than the corresponding elements in *rhs*. Returns 0 (=false) if the lengths of the vectors don't match. If any element is NaN, it will return 0 (=false).

Time complexity: $O(n)$, the length of the vectors.

igraph_vector_all_le — Are all elements less or equal?

```
igraph_bool_t  
igraph_vector_all_le(const igraph_vector_t *lhs,  
                    const igraph_vector_t *rhs);
```

Arguments:

lhs: The first vector.

rhs: The second vector.

Returns:

Positive integer (=true) if the elements in the *lhs* are all less than or equal to the corresponding elements in *rhs*. Returns 0 (=false) if the lengths of the vectors don't match. If any element is NaN, it will return 0 (=false).

Time complexity: $O(n)$, the length of the vectors.

igraph_vector_all_ge — Are all elements greater or equal?

```
igraph_bool_t  
igraph_vector_all_ge(const igraph_vector_t *lhs,  
                    const igraph_vector_t *rhs);
```

Arguments:

lhs: The first vector.

rhs: The second vector.

Returns:

Positive integer (=true) if the elements in the *lhs* are all greater than or equal to the corresponding elements in *rhs*. Returns 0 (=false) if the lengths of the vectors don't match. If any element is NaN, it will return 0 (=false).

Time complexity: $O(n)$, the length of the vectors.

igraph_vector_zapsmall — Replaces small elements of a vector by exact zeros.

```
igraph_error_t igraph_vector_zapsmall(igraph_vector_t *v, igraph_real_t tol);
```

Vector elements which are smaller in magnitude than the given absolute tolerance will be replaced by exact zeros. The default tolerance corresponds to two-thirds of the representable digits of `igraph_real_t`, i.e. $\text{DBL_EPSILON}^{(2/3)}$ which is approximately 10^{-10} .

Arguments:

v: The vector to process, it will be changed in-place.

tol: Tolerance value. Numbers smaller than this in magnitude will be replaced by zeros. Pass in zero to use the default tolerance. Must not be negative.

Returns:

Error code.

See also:

`igraph_vector_all_almost_e()` and `igraph_almost_equals()` to perform comparisons with relative tolerances.

`igraph_vector_lex_cmp` — Lexicographical comparison of two vectors (type-safe variant).

```
int igraph_vector_lex_cmp(  
    const igraph_vector_t *lhs, const igraph_vector_t *rhs  
);
```

If the elements of two vectors match but one is shorter, the shorter one comes first. Thus {1, 3} comes after {1, 2, 3}, but before {1, 3, 4}.

This function is typically used together with `igraph_vector_list_sort()`.

Arguments:

lhs: Pointer to the first vector.

rhs: Pointer to the second vector.

Returns:

-1 if *lhs* is lexicographically smaller, 0 if *lhs* and *rhs* are equal, else 1.

See also:

`igraph_vector_lex_cmp_untyped()` for an untyped variant of this function, or `igraph_vector_colex_cmp()` to compare vectors starting from the last element.

Time complexity: $O(n)$, the number of elements in the smaller vector.

Example	7.2.	File	examples/simple/
<code>igraph_vector_int_list_sort.c</code>			

`igraph_vector_lex_cmp_untyped` — Lexicographical comparison of two vectors (non-type-safe).

```
int igraph_vector_lex_cmp_untyped(const void *lhs, const void *rhs);
```

If the elements of two vectors match but one is shorter, the shorter one comes first. Thus {1, 3} comes after {1, 2, 3}, but before {1, 3, 4}.

This function is typically used together with `igraph_vector_ptr_sort()`.

Arguments:

lhs: Pointer to a pointer to the first vector (interpreted as an `igraph_vector_t **`).

rhs: Pointer to a pointer to the second vector (interpreted as an `igraph_vector_t **`).

Returns:

-1 if *lhs* is lexicographically smaller, 0 if *lhs* and *rhs* are equal, else 1.

See also:

`igraph_vector_lex_cmp()` for a type-safe variant of this function, or `igraph_vector_colex_cmp_untyped()` to compare vectors starting from the last element.

Time complexity: $O(n)$, the number of elements in the smaller vector.

igraph_vector_colex_cmp — Colexicographical comparison of two vectors.

```
int igraph_vector_colex_cmp(  
    const igraph_vector_t *lhs, const igraph_vector_t *rhs  
);
```

This comparison starts from the last element of both vectors and moves backward. If the elements of two vectors match but one is shorter, the shorter one comes first. Thus {1, 2} comes after {3, 2, 1}, but before {0, 1, 2}.

This function is typically used together with `igraph_vector_list_sort()`.

Arguments:

lhs: Pointer to a pointer to the first vector.

rhs: Pointer to a pointer to the second vector.

Returns:

-1 if *lhs* in reverse order is lexicographically smaller than the reverse of *rhs*, 0 if *lhs* and *rhs* are equal, else 1.

See also:

`igraph_vector_colex_cmp_untyped()` for an untyped variant of this function, or `igraph_vector_lex_cmp()` to compare vectors starting from the first element.

Time complexity: $O(n)$, the number of elements in the smaller vector.

Example	7.3.	File	examples/simple/
igraph_vector_int_list_sort.c			

igraph_vector_colex_cmp_untyped — Colexicographical comparison of two vectors.

```
int igraph_vector_colex_cmp_untyped(const void *lhs, const void *rhs);
```

This comparison starts from the last element of both vectors and moves backward. If the elements of two vectors match but one is shorter, the shorter one comes first. Thus {1, 2} comes after {3, 2, 1}, but before {0, 1, 2}.

This function is typically used together with `igraph_vector_ptr_sort()`.

Arguments:

lhs: Pointer to a pointer to the first vector (interpreted as an `igraph_vector_t **`).

rhs: Pointer to a pointer to the second vector (interpreted as an `igraph_vector_t **`).

Returns:

-1 if *lhs* in reverse order is lexicographically smaller than the reverse of *rhs*, 0 if *lhs* and *rhs* are equal, else 1.

See also:

`igraph_vector_colex_cmp()` for a type-safe variant of this function, `igraph_vector_lex_cmp_untyped()` to compare vectors starting from the first element.

Time complexity: $O(n)$, the number of elements in the smaller vector.

Finding minimum and maximum

igraph_vector_min — Smallest element of a vector.

```
igraph_real_t igraph_vector_min(const igraph_vector_t* v);
```

The vector must be non-empty.

Arguments:

v: The input vector.

Returns:

The smallest element of *v*, or NaN if any element is NaN.

Time complexity: $O(n)$, the number of elements.

igraph_vector_max — Largest element of a vector.

```
igraph_real_t igraph_vector_max(const igraph_vector_t* v);
```

If the size of the vector is zero, an arbitrary number is returned.

Arguments:

`v`: The vector object.

Returns:

The maximum element of `v`, or NaN if any element is NaN.

Time complexity: $O(n)$, the number of elements.

`igraph_vector_which_min` — Index of the smallest element.

```
igraph_integer_t igraph_vector_which_min(const igraph_vector_t* v);
```

The vector must be non-empty. If the smallest element is not unique, then the index of the first is returned. If the vector contains NaN values, the index of the first NaN value is returned.

Arguments:

`v`: The input vector.

Returns:

Index of the smallest element.

Time complexity: $O(n)$, the number of elements.

`igraph_vector_which_max` — Gives the index of the maximum element of the vector.

```
igraph_integer_t igraph_vector_which_max(const igraph_vector_t* v);
```

If the size of the vector is zero, -1 is returned. If the largest element is not unique, then the index of the first is returned. If the vector contains NaN values, the index of the first NaN value is returned.

Arguments:

`v`: The vector object.

Returns:

The index of the first maximum element.

Time complexity: $O(n)$, n is the size of the vector.

`igraph_vector_minmax` — Minimum and maximum elements of a vector.

```
void igraph_vector_minmax(const igraph_vector_t *v,
                          igraph_real_t *min, igraph_real_t *max);
```

Handy if you want to have both the smallest and largest element of a vector. The vector is only traversed once. The vector must be non-empty. If a vector contains at least one NaN, both min and max will be NaN.

Arguments:

v: The input vector. It must contain at least one element.

min: Pointer to a base type variable, the minimum is stored here.

max: Pointer to a base type variable, the maximum is stored here.

Time complexity: $O(n)$, the number of elements.

igraph_vector_which_minmax — Index of the minimum and maximum elements.

```
void igraph_vector_which_minmax(const igraph_vector_t *v,
                                igraph_integer_t *which_min, igraph_integer_t *which_max);
```

Handy if you need the indices of the smallest and largest elements. The vector is traversed only once. The vector must be non-empty. If the minimum or maximum is not unique, the index of the first minimum or the first maximum is returned, respectively. If a vector contains at least one NaN, both *which_min* and *which_max* will point to the first NaN value.

Arguments:

v: The input vector. It must contain at least one element.

which_min: The index of the minimum element will be stored here.

which_max: The index of the maximum element will be stored here.

Time complexity: $O(n)$, the number of elements.

Vector properties

igraph_vector_empty — Decides whether the size of the vector is zero.

```
igraph_bool_t igraph_vector_empty(const igraph_vector_t* v);
```

Arguments:

v: The vector object.

Returns:

Non-zero number (true) if the size of the vector is zero and zero (false) otherwise.

Time complexity: $O(1)$.

igraph_vector_size — Returns the size (=length) of the vector.

```
igraph_integer_t igraph_vector_size(const igraph_vector_t* v);
```

Arguments:

v: The vector object

Returns:

The size of the vector.

Time complexity: $O(1)$.

igraph_vector_capacity — Returns the allocated capacity of the vector.

```
igraph_integer_t igraph_vector_capacity(const igraph_vector_t*v);
```

Note that this might be different from the size of the vector (as queried by `igraph_vector_size()`), and specifies how many elements the vector can hold, without reallocation.

Arguments:

v: Pointer to the (previously initialized) vector object to query.

Returns:

The allocated capacity.

See also:

`igraph_vector_size()`.

Time complexity: $O(1)$.

igraph_vector_sum — Calculates the sum of the elements in the vector.

```
igraph_real_t igraph_vector_sum(const igraph_vector_t *v);
```

For the empty vector 0.0 is returned.

Arguments:

v: The vector object.

Returns:

The sum of the elements.

Time complexity: $O(n)$, the size of the vector.

igraph_vector_prod — Calculates the product of the elements in the vector.

```
igraph_real_t igraph_vector_prod(const igraph_vector_t *v);
```

For the empty vector one (1) is returned.

Arguments:

v: The vector object.

Returns:

The product of the elements.

Time complexity: $O(n)$, the size of the vector.

igraph_vector_isininterval — Checks if all elements of a vector are in the given

```
igraph_bool_t igraph_vector_isininterval(const igraph_vector_t *v,  
                                         igraph_real_t low,  
                                         igraph_real_t high);
```

interval.

Arguments:

v: The vector object.

low: The lower limit of the interval (inclusive).

high: The higher limit of the interval (inclusive).

Returns:

True (positive integer) if the vector is empty or all vector elements are in the interval, false (zero) otherwise. If any element is NaN, it will return 0 (=false).

Time complexity: $O(n)$, the number of elements in the vector.

igraph_vector_maxdifference — The maximum absolute difference of *m1* and *m2*

```
igraph_real_t igraph_vector_maxdifference(const igraph_vector_t *m1,  
                                           const igraph_vector_t *m2);
```

The element with the largest absolute value in $m1 - m2$ is returned. Both vectors must be non-empty, but they not need to have the same length, the extra elements in the longer vector are ignored. If any value is NaN in the shorter vector, the result will be NaN.

Arguments:

$m1$: The first vector.

$m2$: The second vector.

Returns:

The maximum absolute difference of $m1$ and $m2$.

Time complexity: $O(n)$, the number of elements in the shorter vector.

igraph_vector_is_nan — Check for each element if it is NaN.

```
igraph_error_t igraph_vector_is_nan(const igraph_vector_t *v, igraph_vector_bool_t is_nan);
```

Arguments:

v : The `igraph_vector_t` object to check.

is_nan : The resulting boolean vector indicating for each element whether it is NaN or not.

Returns:

Error code, `IGRAPH_ENOMEM` if there is not enough memory. Note that this function *never* returns an error if the vector is_nan will already be large enough.

Time complexity: $O(n)$, the number of elements.

igraph_vector_is_any_nan — Check if any element is NaN.

```
igraph_bool_t igraph_vector_is_any_nan(const igraph_vector_t *v);
```

Arguments:

v : The `igraph_vector_t` object to check.

Returns:

1 if any element is NaN, 0 otherwise.

Time complexity: $O(n)$, the number of elements.

Searching for elements

igraph_vector_contains — Linear search in a vector.

```
igraph_bool_t igraph_vector_contains(const igraph_vector_t *v,  
                                     igraph_real_t e);
```

Check whether the supplied element is included in the vector, by linear search.

Arguments:

v: The input vector.

e: The element to look for.

Returns:

true if the element is found and false otherwise.

Time complexity: $O(n)$, the length of the vector.

igraph_vector_search — Search from a given position

```
igraph_bool_t igraph_vector_search(const igraph_vector_t *v,  
                                   igraph_integer_t from, igraph_real_t what, igraph_integer_t *pos);
```

The supplied element *what* is searched in vector *v*, starting from element index *from*. If found then the index of the first instance (after *from*) is stored in *pos*.

Arguments:

v: The input vector.

from: The index to start searching from. No range checking is performed.

what: The element to find.

pos: If not NULL then the index of the found element is stored here.

Returns:

Boolean, true if the element was found, false otherwise.

Time complexity: $O(m)$, the number of elements to search, the length of the vector minus the *from* argument.

igraph_vector_binsearch — Finds an element by binary searching a sorted vector.

```
igraph_bool_t igraph_vector_binsearch(const igraph_vector_t *v,  
                                       igraph_real_t what, igraph_integer_t *pos);
```

It is assumed that the vector is sorted. If the specified element (*what*) is not in the vector, then the position of where it should be inserted (to keep the vector sorted) is returned. If the vector contains any NaN values, the returned value is undefined and *pos* may point to any position.

Arguments:

v: The `igraph_vector_t` object.

what: The element to search for.

pos: Pointer to an `igraph_integer_t`. This is set to the position of an instance of *what* in the vector if it is present. If *v* does not contain *what* then *pos* is set to the position to which it should be inserted (to keep the the vector sorted of course).

Returns:

Positive integer (true) if *what* is found in the vector, zero (false) otherwise.

Time complexity: $O(\log(n))$, *n* is the number of elements in *v*.

igraph_vector_binsearch_slice — Finds an element by binary searching a sorted slice of a vector.

```
igraph_bool_t igraph_vector_binsearch_slice(const igraph_vector_t *v,  
                                             igraph_real_t what, igraph_integer_t *pos, igraph_integer_t start, igraph_integer_t end);
```

It is assumed that the indicated slice of the vector, from *start* to *end*, is sorted. If the specified element (*what*) is not in the slice of the vector, then the position of where it should be inserted (to keep the *slice* sorted) is returned. Note that this means that the returned index will point *inside* the slice (including its endpoints), but will not evaluate values *outside* the slice. If the indicated slice contains any NaN values, the returned value is undefined and *pos* may point to any position within the slice.

Arguments:

v: The `igraph_vector_t` object.

what: The element to search for.

pos: Pointer to an `igraph_integer_t`. This is set to the position of an instance of *what* in the slice of the vector if it is present. If *v* does not contain *what* then *pos* is set to the position to which it should be inserted (to keep the the vector sorted).

start: The start position of the slice to search (inclusive).

end: The end position of the slice to search (exclusive).

Returns:

Positive integer (true) if *what* is found in the vector, zero (false) otherwise.

Time complexity: $O(\log(n))$, *n* is the number of elements in the slice of *v*, i.e. *end* - *start*.

igraph_vector_binsearch2 — Binary search, without returning the index.

```
igraph_bool_t igraph_vector_binsearch2(const igraph_vector_t *v,  
                                         igraph_real_t what);
```

It is assumed that the vector is sorted.

Arguments:

v: The `igraph_vector_t` object.

what: The element to search for.

Returns:

Positive integer (true) if *what* is found in the vector, zero (false) otherwise.

Time complexity: $O(\log(n))$, n is the number of elements in *v*.

Resizing operations

`igraph_vector_clear` — Removes all elements from a vector.

```
void igraph_vector_clear(igraph_vector_t* v);
```

This function simply sets the size of the vector to zero, it does not free any allocated memory. For that you have to call `igraph_vector_destroy()`.

Arguments:

v: The vector object.

Time complexity: $O(1)$.

`igraph_vector_reserve` — Reserves memory for a vector.

```
igraph_error_t igraph_vector_reserve(igraph_vector_t* v, igraph_integer_t capacity);
```

igraph vectors are flexible, they can grow and shrink. Growing however occasionally needs the data in the vector to be copied. In order to avoid this, you can call this function to reserve space for future growth of the vector.

Note that this function does *not* change the size of the vector. Let us see a small example to clarify things: if you reserve space for 100 elements and the size of your vector was (and still is) 60, then you can surely add additional 40 elements to your vector before it will be copied.

Arguments:

v: The vector object.

capacity: The new *allocated* size of the vector.

Returns:

Error code: `IGRAPH_ENOMEM` if there is not enough memory.

Time complexity: operating system dependent, should be around $O(n)$, n is the new allocated size of the vector.

igraph_vector_resize — Resize the vector.

```
igraph_error_t igraph_vector_resize(igraph_vector_t* v, igraph_integer_t new_size);
```

Note that this function does not free any memory, just sets the size of the vector to the given one. It can on the other hand allocate more memory if the new size is larger than the previous one. In this case the newly appeared elements in the vector are *not* set to zero, they are uninitialized.

Arguments:

v: The vector object

new_size: The new size of the vector.

Returns:

Error code, IGRAPH_ENOMEM if there is not enough memory. Note that this function *never* returns an error if the vector is made smaller.

See also:

`igraph_vector_reserve()` for allocating memory for future extensions of a vector.
`igraph_vector_resize_min()` for deallocating the unnneded memory for a vector.

Time complexity: $O(1)$ if the new size is smaller, operating system dependent if it is larger. In the latter case it is usually around $O(n)$, n is the new size of the vector.

igraph_vector_resize_min — Deallocate the unused memory of a vector.

```
void igraph_vector_resize_min(igraph_vector_t*v);
```

This function attempts to deallocate the unused reserved storage of a vector. If it succeeds, `igraph_vector_size()` and `igraph_vector_capacity()` will be the same. The data in the vector is always preserved, even if deallocation is not successful.

Arguments:

v: Pointer to an initialized vector.

See also:

`igraph_vector_resize()`, `igraph_vector_reserve()`.

Time complexity: operating system dependent, $O(n)$ at worst.

igraph_vector_push_back — Appends one element to a vector.

```
igraph_error_t igraph_vector_push_back(igraph_vector_t* v, igraph_real_t e);
```

This function resizes the vector to be one element longer and sets the very last element in the vector to *e*.

Arguments:

v: The vector object.

e: The element to append to the vector.

Returns:

Error code: IGRAPH_ENOMEM: not enough memory.

Time complexity: operating system dependent. What is important is that a sequence of *n* subsequent calls to this function has time complexity $O(n)$, even if there hadn't been any space reserved for the new elements by `igraph_vector_reserve()`. This is implemented by a trick similar to the C++ vector class: each time more memory is allocated for a vector, the size of the additionally allocated memory is the same as the vector's current length. (We assume here that the time complexity of memory allocation is at most linear.)

igraph_vector_pop_back — Removes and returns the last element of a vector.

```
igraph_real_t igraph_vector_pop_back(igraph_vector_t* v);
```

It is an error to call this function with an empty vector.

Arguments:

v: The vector object.

Returns:

The removed last element.

Time complexity: $O(1)$.

igraph_vector_insert — Inserts a single element into a vector.

```
igraph_error_t igraph_vector_insert(
    igraph_vector_t *v, igraph_integer_t pos, igraph_real_t value);
```

Note that this function does not do range checking. Insertion will shift the elements from the position given to the end of the vector one position to the right, and the new element will be inserted in the empty space created at the given position. The size of the vector will increase by one.

Arguments:

v: The vector object.

pos: The position where the new element is to be inserted.

value: The new element to be inserted.

igraph_vector_remove — Removes a single element from a vector.

```
void igraph_vector_remove(igraph_vector_t *v, igraph_integer_t elem);
```

Note that this function does not do range checking.

Arguments:

v: The vector object.

elem: The position of the element to remove.

Time complexity: $O(n - \text{elem})$, n is the number of elements in the vector.

igraph_vector_remove_section — Deletes a section from a vector.

```
void igraph_vector_remove_section(
    igraph_vector_t *v, igraph_integer_t from, igraph_integer_t to);
```

Arguments:

v: The vector object.

from: The position of the first element to remove.

to: The position of the first element *not* to remove.

Time complexity: $O(n - \text{from})$, n is the number of elements in the vector.

Complex vector operations

igraph_vector_complex_real — Gives the real part of a complex vector.

```
igraph_error_t igraph_vector_complex_real(const igraph_vector_complex_t *v,
    igraph_vector_t *real);
```

Arguments:

v: Pointer to a complex vector.

real: Pointer to an initialized vector. The result will be stored here.

Returns:

Error code.

Time complexity: $O(n)$, n is the number of elements in the vector.

igraph_vector_complex_imag — Gives the imaginary part of a complex vector.

```
igraph_error_t igraph_vector_complex_imag(const igraph_vector_complex_t *v,  
                                           igraph_vector_t *imag);
```

Arguments:

v: Pointer to a complex vector.

real: Pointer to an initialized vector. The result will be stored here.

Returns:

Error code.

Time complexity: $O(n)$, n is the number of elements in the vector.

igraph_vector_complex_realimag — Gives the real and imaginary parts of a complex vector.

```
igraph_error_t igraph_vector_complex_realimag(const igraph_vector_complex_t *v,  
                                               igraph_vector_t *real,  
                                               igraph_vector_t *imag);
```

Arguments:

v: Pointer to a complex vector.

real: Pointer to an initialized vector. The real part will be stored here.

imag: Pointer to an initialized vector. The imaginary part will be stored here.

Returns:

Error code.

Time complexity: $O(n)$, n is the number of elements in the vector.

igraph_vector_complex_create — Creates a complex vector from a real and imaginary part.

```
igraph_error_t igraph_vector_complex_create(igraph_vector_complex_t *v,  
                                             const igraph_vector_t *real,  
                                             const igraph_vector_t *imag);
```

Arguments:

v: Pointer to an uninitialized complex vector.
real: Pointer to the real part of the complex vector.
imag: Pointer to the imaginary part of the complex vector.

Returns:

Error code.

Time complexity: $O(n)$, n is the number of elements in the vector.

igraph_vector_complex_create_polar — Creates a complex matrix from a magnitude and an angle.

```
igraph_error_t igraph_vector_complex_create_polar(igraph_vector_complex_t *v,  
                                                  const igraph_vector_t *r,  
                                                  const igraph_vector_t *theta);
```

Arguments:

m: Pointer to an uninitialized complex vector.
r: Pointer to a real vector containing magnitudes.
theta: Pointer to a real vector containing arguments (phase angles).

Returns:

Error code.

Time complexity: $O(n)$, n is the number of elements in the vector.

igraph_vector_complex_all_almost_e — Are all elements almost equal?

```
igraph_bool_t igraph_vector_complex_all_almost_e(const igraph_vector_complex_t  
                                                  const igraph_vector_complex_t  
                                                  igraph_real_t eps);
```

Checks if the elements of two complex vectors are equal within a relative tolerance.

Arguments:

lhs: The first vector.
rhs: The second vector.
eps: Relative tolerance, see `igraph_complex_almost_equals()` for details.

Returns:

True if the two vectors are almost equal, false if there is at least one differing element or if the vectors are not of the same size.

igraph_vector_complex_zapsmall — Replaces small elements of a complex vector by exact zeros.

```
igraph_error_t igraph_vector_complex_zapsmall(igraph_vector_complex_t *v, igraph_real_t tol);
```

Similarly to `igraph_vector_zapsmall()`, small elements will be replaced by zeros. The operation is performed separately on the real and imaginary parts of the numbers. This way, complex numbers with a large real part and tiny imaginary part will effectively be transformed to real numbers. The default tolerance corresponds to two-thirds of the representable digits of `igraph_real_t`, i.e. $\text{DBL_EPSILON}^{(2/3)}$ which is approximately 10^{-10} .

Arguments:

- v:** The vector to process, it will be changed in-place.
- tol:** Tolerance value. Real and imaginary parts smaller than this in magnitude will be replaced by zeros. Pass in zero to use the default tolerance. Must not be negative.

Returns:

Error code.

See also:

`igraph_vector_complex_all_almost_e()` and `igraph_complex_almost_equals()` to perform comparisons with relative tolerances.

Sorting

igraph_vector_sort — Sorts the elements of the vector into ascending order.

```
void igraph_vector_sort(igraph_vector_t *v);
```

If the vector contains any NaN values, the resulting ordering of NaN values is undefined and may appear anywhere in the vector.

Arguments:

- v:** Pointer to an initialized vector object.
- Time complexity: $O(n \log n)$ for n elements.

igraph_vector_reverse_sort — Sorts the elements of the vector into descending order.

```
void igraph_vector_reverse_sort(igraph_vector_t *v);
```

If the vector contains any NaN values, the resulting ordering of NaN values is undefined and may appear anywhere in the vector.

Arguments:

v: Pointer to an initialized vector object.

Time complexity: $O(n \log n)$ for n elements.

igraph_vector_qsort_ind — Return a permutation of indices that sorts a vector

```
igraph_error_t igraph_vector_qsort_ind(igraph_vector_t *v,  
                                       igraph_vector_int_t *inds, igraph_order_t order);
```

Takes an unsorted array *v* as input and computes an array of indices *inds* such that *v*[*inds*[*i*]], with *i* increasing from 0, is an ordered array (either ascending or descending, depending on *order*). The order of indices for identical elements is not defined. If the vector contains any NaN values, the ordering of NaN values is undefined.

Arguments:

v: the array to be sorted

inds: the output array of indices. This must be initialized, but will be resized

order: whether the output array should be sorted in ascending or descending order. Use IGRAPH_ASCENDING for ascending and IGRAPH_DESCENDING for descending order.

Returns:

Error code.

This routine uses igraph's built-in qsort routine. Algorithm: 1) create an array of pointers to the elements of *v*. 2) Pass this array to qsort. 3) after sorting the difference between the pointer value and the first pointer value gives its original position in the array. Use this to set the values of *inds*.

Set operations on sorted vectors

igraph_vector_intersect_sorted — Calculates the intersection of two sorted vectors

```
igraph_error_t igraph_vector_intersect_sorted(const igraph_vector_t *v1,  
                                              const igraph_vector_t *v2, igraph_vector_t *result);
```

The elements that are contained in both vectors are stored in the result vector. All three vectors must be initialized.

Instead of the naive intersection which takes $O(n)$, this function uses the set intersection method of Ricardo Baeza-Yates, which is more efficient when one of the vectors is significantly smaller than the other, and gives similar performance on average when the two vectors are equal.

The algorithm keeps the multiplicities of the elements: if an element appears k_1 times in the first vector and k_2 times in the second, the result will include that element $\min(k_1, k_2)$ times.

Reference: Baeza-Yates R: A fast set intersection algorithm for sorted sequences. In: Lecture Notes in Computer Science, vol. 3109/2004, pp. 400--408, 2004. Springer Berlin/Heidelberg. ISBN: 978-3-540-22341-2.

Arguments:

v1: the first vector

v2: the second vector

result: the result vector, which will also be sorted.

Time complexity: $O(m \log(n))$ where m is the size of the smaller vector and n is the size of the larger one.

igraph_vector_difference_sorted — Calculates the difference between two sorted vectors (considered as sets)

```
igraph_error_t igraph_vector_difference_sorted(const igraph_vector_t *v1,
                                              const igraph_vector_t *v2, igraph_vector_t *result);
```

The elements that are contained in only the first vector but not the second are stored in the result vector. All three vectors must be initialized.

Arguments:

v1: the first vector

v2: the second vector

result: the result vector

Pointer vectors (igraph_vector_ptr_t)

The `igraph_vector_ptr_t` data type is very similar to the `igraph_vector_t` type, but it stores generic pointers instead of real numbers.

This type has the same space complexity as `igraph_vector_t`, and most implemented operations work the same way as for `igraph_vector_t`.

The same `VECTOR` macro used for ordinary vectors can be used for pointer vectors as well, please note that a typeless generic pointer will be provided by this macro and you may need to cast it to a specific pointer before starting to work with it.

Pointer vectors may have an associated item destructor function which takes a pointer and returns nothing. The item destructor will be called on each item in the pointer vector when it is destroyed by `igraph_vector_ptr_destroy()` or `igraph_vector_ptr_destroy_all()`, or when its elements are freed by `igraph_vector_ptr_free_all()`. Note that the semantics of an item destructor does not coincide with C++ destructors; for instance, when a pointer vector is resized to a smaller size, the extra items will *not* be destroyed automatically! Nevertheless, item destructors may become handy in many cases; for instance, a vector of graphs generated by some function can be destroyed with a single call to `igraph_vector_ptr_destroy_all()` if the item destructor is set to `igraph_destroy()`.

igraph_vector_ptr_init — Initialize a pointer vector (constructor).

```
igraph_error_t igraph_vector_ptr_init(igraph_vector_ptr_t* v, igraph_integer_t
```

This is the constructor of the pointer vector data type. All pointer vectors constructed this way should be destroyed via calling `igraph_vector_ptr_destroy()`.

Arguments:

v: Pointer to an uninitialized `igraph_vector_ptr_t` object, to be created.

size: Integer, the size of the pointer vector.

Returns:

Error code: `IGRAPH_ENOMEM` if out of memory

Time complexity: operating system dependent, the amount of “time” required to allocate *size* elements.

`igraph_vector_ptr_init_copy` — Initializes a pointer vector from another one (constructor).

```
igraph_error_t igraph_vector_ptr_init_copy(igraph_vector_ptr_t *to, const igraph
```

This function creates a pointer vector by copying another one. This is shallow copy, only the pointers in the vector will be copied.

It is potentially dangerous to copy a pointer vector with an associated item destructor. The copied vector will inherit the item destructor, which may cause problems when both vectors are destroyed as the items might get destroyed twice. Make sure you know what you are doing when copying a pointer vector with an item destructor, or unset the item destructor on one of the vectors later.

Arguments:

to: Pointer to an uninitialized pointer vector object.

from: A pointer vector object.

Returns:

Error code: `IGRAPH_ENOMEM` if out of memory

Time complexity: $O(n)$ if allocating memory for n elements can be done in $O(n)$ time.

`igraph_vector_ptr_destroy` — Destroys a pointer vector.

```
void igraph_vector_ptr_destroy(igraph_vector_ptr_t* v);
```

The destructor for pointer vectors.

Arguments:

v: Pointer to the pointer vector to destroy.

Time complexity: operating system dependent, the “time” required to deallocate $O(n)$ bytes, n is the number of elements allocated for the pointer vector (not necessarily the number of elements in the vector).

igraph_vector_ptr_free_all — Frees all the elements of a pointer vector.

```
void igraph_vector_ptr_free_all(igraph_vector_ptr_t* v);
```

If an item destructor is set for this pointer vector, this function will first call the destructor on all elements of the vector and then free all the elements using `igraph_free()`. If an item destructor is not set, the elements will simply be freed.

Arguments:

`v`: Pointer to the pointer vector whose elements will be freed.

Time complexity: operating system dependent, the “time” required to call the destructor n times and then deallocate $O(n)$ pointers, each pointing to a memory area of arbitrary size. n is the number of elements in the pointer vector.

igraph_vector_ptr_destroy_all — Frees all the elements and destroys the pointer vector.

```
void igraph_vector_ptr_destroy_all(igraph_vector_ptr_t* v);
```

This function is equivalent to `igraph_vector_ptr_free_all()` followed by `igraph_vector_ptr_destroy()`.

Arguments:

`v`: Pointer to the pointer vector to destroy.

Time complexity: operating system dependent, the “time” required to deallocate $O(n)$ pointers, each pointing to a memory area of arbitrary size, plus the “time” required to deallocate $O(n)$ bytes, n being the number of elements allocated for the pointer vector (not necessarily the number of elements in the vector).

igraph_vector_ptr_size — Gives the number of elements in the pointer vector.

```
igraph_integer_t igraph_vector_ptr_size(const igraph_vector_ptr_t* v);
```

Arguments:

`v`: The pointer vector object.

Returns:

The size of the object, i.e. the number of pointers stored.

Time complexity: $O(1)$.

igraph_vector_ptr_clear — Removes all elements from a pointer vector.

```
void igraph_vector_ptr_clear(igraph_vector_ptr_t* v);
```

This function resizes a pointer to vector to zero length. Note that the pointed objects are *not* deallocated, you should call `igraph_free()` on them, or make sure that their allocated memory is freed in some other way, you'll get memory leaks otherwise. If you have set up an item destructor earlier, the destructor will be called on every element.

Note that the current implementation of this function does *not* deallocate the memory required for storing the pointers, so making a pointer vector smaller this way does not give back any memory. This behavior might change in the future.

Arguments:

`v`: The pointer vector to clear.

Time complexity: $O(1)$.

igraph_vector_ptr_push_back — Appends an element to the back of a pointer vector.

```
igraph_error_t igraph_vector_ptr_push_back(igraph_vector_ptr_t* v, void* e);
```

Arguments:

`v`: The pointer vector.

`e`: The new element to include in the pointer vector.

Returns:

Error code.

See also:

`igraph_vector_push_back()` for the corresponding operation of the ordinary vector type.

Time complexity: $O(1)$ or $O(n)$, n is the number of elements in the vector. The pointer vector implementation ensures that n subsequent `push_back` operations need $O(n)$ time to complete.

igraph_vector_ptr_pop_back — Removes and returns the last element of a pointer vector.

```
void *igraph_vector_ptr_pop_back(igraph_vector_ptr_t *v);
```

It is an error to call this function with an empty vector.

Arguments:

v: The pointer vector.

Returns:

The removed last element.

Time complexity: $O(1)$.

igraph_vector_ptr_insert — Inserts a single element into a pointer vector.

```
igraph_error_t igraph_vector_ptr_insert(igraph_vector_ptr_t* v, igraph_integer_t pos, void* e)
```

Note that this function does not do range checking. Insertion will shift the elements from the position given to the end of the vector one position to the right, and the new element will be inserted in the empty space created at the given position. The size of the vector will increase by one.

Arguments:

v: The pointer vector object.

pos: The position where the new element is inserted.

e: The inserted element

igraph_vector_ptr_get — Access an element of a pointer vector.

```
void* igraph_vector_ptr_get(const igraph_vector_ptr_t* v, igraph_integer_t pos)
```

Arguments:

v: Pointer to a pointer vector.

pos: The index of the pointer to return.

Returns:

The pointer at *pos* position.

Time complexity: $O(1)$.

igraph_vector_ptr_set — Assign to an element of a pointer vector.

```
void igraph_vector_ptr_set(igraph_vector_ptr_t* v, igraph_integer_t pos, void* e)
```

Arguments:

v: Pointer to a pointer vector.

pos: The index of the pointer to update.

value: The new pointer to set in the vector.

Time complexity: $O(1)$.

igraph_vector_ptr_resize — Resizes a pointer vector.

```
igraph_error_t igraph_vector_ptr_resize(igraph_vector_ptr_t* v, igraph_integer_t newsize)
```

Note that if a vector is made smaller the pointed object are not deallocated by this function and the item destructor is not called on the extra elements.

Arguments:

v: A pointer vector.

newsize: The new size of the pointer vector.

Returns:

Error code.

Time complexity: $O(1)$ if the vector if made smaller. Operating system dependent otherwise, the amount of “time” needed to allocate the memory for the vector elements.

igraph_vector_ptr_sort — Sorts the pointer vector based on an external comparison function.

```
void igraph_vector_ptr_sort(igraph_vector_ptr_t *v, int (*compar)(const void*, const void*))
```

Sometimes it is necessary to sort the pointers in the vector based on the property of the element being referenced by the pointer. This function allows us to sort the vector based on an arbitrary external comparison function which accepts two `void *` pointers `p1` and `p2` and returns an integer less than, equal to or greater than zero if the first argument is considered to be respectively less than, equal to, or greater than the second. `p1` and `p2` will point to the pointer in the vector, so they have to be double-dereferenced if one wants to get access to the underlying object the address of which is stored in `v`.

Arguments:

v: The pointer vector to be sorted.

compar: A `qsort`-compatible comparison function. It must take pointers to the elements of the pointer vector. For example, if the pointer vector contains `igraph_vector_t *` pointers, then the comparison function must interpret its arguments as `igraph_vector_t **`.

igraph_vector_ptr_sort_ind — Return a permutation of indices that sorts a vector of pointers

```
igraph_error_t igraph_vector_ptr_sort_ind(igraph_vector_ptr_t *v,  
                                          igraph_vector_int_t *inds, cmp_t *cmp);
```

Takes an unsorted array *v* as input and computes an array of indices *inds* such that *v[inds[i]]*, with *i* increasing from 0, is an ordered array (either ascending or descending, depending on *v* order). The order of indices for identical elements is not defined.

Arguments:

v: the array to be sorted

inds: the output array of indices. This must be initialized, but will be resized

cmp: a comparator function that takes two elements of the pointer vector being sorted (these are constant pointers on their own) and returns a negative value if the item "pointed to" by the first pointer is smaller than the item "pointed to" by the second pointer, a positive value if it is larger, or zero if the two items are equal

Returns:

Error code.

This routine uses the C library `qsort` routine. Algorithm: 1) create an array of pointers to the elements of *v*. 2) Pass this array to `qsort`. 3) after sorting the difference between the pointer value and the first pointer value gives its original position in the array. Use this to set the values of *inds*.

igraph_vector_ptr_permute — Permutes the elements of a pointer vector in place according to an index vector.

```
igraph_error_t igraph_vector_ptr_permute(igraph_vector_ptr_t* v, const igraph_v
```

This function takes a vector *v* and a corresponding index vector *ind*, and permutes the elements of *v* such that *v[ind[i]]* is moved to become *v[i]* after the function is executed.

It is an error to call this function with an index vector that does not represent a valid permutation. Each element in the index vector must be between 0 and the length of the vector minus one (inclusive), and each such element must appear only once. The function does not attempt to validate the index vector.

The index vector that this function takes is compatible with the index vector returned from `igraph_vector_ptr_sort_ind()`; passing in the index vector from `igraph_vector_ptr_sort_ind()` will sort the original vector.

As a special case, this function allows the index vector to be *shorter* than the vector being permuted, in which case the elements whose indices do not occur in the index vector will be removed from the vector.

Arguments:

v: the vector to permute

ind: the index vector

Returns:

Error code: `IGRAPH_ENOMEM` if there is not enough memory.

Time complexity: $O(n)$, the size of the vector.

igraph_vector_ptr_get_item_destructor — Gets the current item destructor for this pointer vector.

```
igraph_finally_func_t* igraph_vector_ptr_get_item_destructor(const igraph_vector_ptr_t v);
```

The item destructor is a function which will be called on every non-null pointer stored in this vector when `igraph_vector_ptr_destroy()`, `igraph_vector_ptr_destroy_all()` or `igraph_vector_ptr_free_all()` is called.

Returns:

The current item destructor.

Time complexity: $O(1)$.

igraph_vector_ptr_set_item_destructor — Sets the item destructor for this pointer vector.

```
igraph_finally_func_t* igraph_vector_ptr_set_item_destructor(igraph_vector_ptr_t v, igraph_finally_func_t *func);
```

The item destructor is a function which will be called on every non-null pointer stored in this vector when `igraph_vector_ptr_destroy()`, `igraph_vector_ptr_destroy_all()` or `igraph_vector_ptr_free_all()` is called.

Returns:

The old item destructor.

Time complexity: $O(1)$.

IGRAPH_VECTOR_PTR_SET_ITEM_DESTRUCTOR — Sets the item destructor for this pointer vector (macro version).

```
#define IGRAPH_VECTOR_PTR_SET_ITEM_DESTRUCTOR(v, func)
```

This macro is expanded to `igraph_vector_ptr_set_item_destructor()`, the only difference is that the second argument is automatically cast to an `igraph_finally_func_t*`. The cast is necessary in most cases as the destructor functions we use (such as `igraph_vector_destroy()`) take a pointer to some concrete igraph data type, while `igraph_finally_func_t` expects `void*`.

Deprecated functions

igraph_vector_copy — Initializes a vector from another vector object (deprecated alias).

```
igraph_error_t igraph_vector_copy(igraph_vector_t *to,  
                                  const igraph_vector_t *from);
```

Warning

Deprecated since version 0.10. Please do not use this function in new code; use `igraph_vector_init_copy()` instead.

igraph_vector_e — Access an element of a vector (deprecated alias).

```
igraph_real_t igraph_vector_e(const igraph_vector_t* v, igraph_integer_t pos);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_vector_get()` instead.

igraph_vector_e_ptr — Get the address of an element of a vector

```
igraph_real_t* igraph_vector_e_ptr(const igraph_vector_t* v, igraph_integer_t pos);
```

Arguments:

v: The `igraph_vector_t` object.

pos: The position of the element, the position of the first element is zero.

Returns:

Pointer to the desired element.

See also:

`igraph_vector_get()` and the `VECTOR` macro.

Time complexity: $O(1)$.

igraph_vector_init_seq — Initializes a vector with a sequence, inclusive endpoints (deprecated).

```
igraph_error_t igraph_vector_init_seq(igraph_vector_t *v, igraph_real_t from, igraph_real_t to);
```

The vector will contain the numbers *from*, *from*+1, ..., *to*. Note that both endpoints are *inclusive*, contrary to typical usage of ranges in C.

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_vector_init_range()` instead.

Arguments:

v: Pointer to an uninitialized vector object.
from: The lower limit in the sequence (inclusive).
to: The upper limit in the sequence (inclusive).

Returns:

Error code: `IGRAPH_ENOMEM`: out of memory.

Time complexity: $O(n)$, the number of elements in the vector.

`igraph_vector_ptr_copy` — Initializes a pointer vector from another one (deprecated alias).

```
igraph_error_t igraph_vector_ptr_copy(igraph_vector_ptr_t *to, const igraph_vec
```

Warning

Deprecated since version 0.10. Please do not use this function in new code; use `igraph_vector_ptr_init_copy()` instead.

`igraph_vector_ptr_e` — Access an element of a pointer vector (deprecated alias).

```
void *igraph_vector_ptr_e(const igraph_vector_ptr_t* v, igraph_integer_t pos);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_vector_ptr_get()` instead.

Matrices

About `igraph_matrix_t` objects

This type is just an interface to `igraph_vector_t`.

The `igraph_matrix_t` type usually stores n elements in $O(n)$ space, but not always. See the documentation of the vector type.

Matrix constructors and destructors

igraph_matrix_init — Initializes a matrix.

```
igraph_error_t igraph_matrix_init(
    igraph_matrix_t *m, igraph_integer_t nrow, igraph_integer_t ncol);
```

Every matrix needs to be initialized before using it. This is done by calling this function. A matrix has to be destroyed if it is not needed any more; see `igraph_matrix_destroy()`.

Arguments:

m: Pointer to a not yet initialized matrix object to be initialized.

nrow: The number of rows in the matrix.

ncol: The number of columns in the matrix.

Returns:

Error code.

Time complexity: usually $O(n)$, n is the number of elements in the matrix.

igraph_matrix_init_copy — Copies a matrix.

```
igraph_error_t igraph_matrix_init_copy(igraph_matrix_t *to, const igraph_matrix_t *from);
```

Creates a matrix object by copying from an existing matrix.

Arguments:

to: Pointer to an uninitialized matrix object.

from: The initialized matrix object to copy.

Returns:

Error code, `IGRAPH_ENOMEM` if there isn't enough memory to allocate the new matrix.

Time complexity: $O(n)$, the number of elements in the matrix.

igraph_matrix_destroy — Destroys a matrix object.

```
void igraph_matrix_destroy(igraph_matrix_t *m);
```

This function frees all the memory allocated for a matrix object. The destroyed object needs to be reinitialized before using it again.

Arguments:

m: The matrix to destroy.

Time complexity: operating system dependent.

Initializing elements

igraph_matrix_null — Sets all elements in a matrix to zero.

```
void igraph_matrix_null(igraph_matrix_t *m);
```

Arguments:

m: Pointer to an initialized matrix object.

Time complexity: $O(n)$, n is the number of elements in the matrix.

igraph_matrix_fill — Fill with an element.

```
void igraph_matrix_fill(igraph_matrix_t *m, igraph_real_t e);
```

Set the matrix to a constant matrix.

Arguments:

m: The input matrix.

e: The element to set.

Time complexity: $O(mn)$, the number of elements.

Accessing elements of a matrix

MATRIX — Accessing an element of a matrix.

```
#define MATRIX(m,i,j)
```

Note that there are no range checks right now. This functionality might be redefined as a proper function later.

Arguments:

m: The matrix object.

i: The index of the row, starting with zero.

j: The index of the column, starting with zero.

Time complexity: $O(1)$.

igraph_matrix_get — Extract an element from a matrix.


```
igraph_real_t igraph_matrix_get(const igraph_matrix_t *m,
                                igraph_integer_t row, igraph_integer_t col);
```

Use this if you need a function for some reason and cannot use the `MATRIX` macro. Note that no range checking is performed.

Arguments:

m: The input matrix.
row: The row index.
col: The column index.

Returns:

The element in the given row and column.

Time complexity: $O(1)$.

igraph_matrix_get_ptr — Pointer to an element of a matrix.

```
igraph_real_t* igraph_matrix_get_ptr(const igraph_matrix_t *m,
                                       igraph_integer_t row, igraph_integer_t col);
```

The function returns a pointer to an element. No range checking is performed.

Arguments:

m: The input matrix.
row: The row index.
col: The column index.

Returns:

Pointer to the element in the given row and column.

Time complexity: $O(1)$.

igraph_matrix_set — Set an element.

```
void igraph_matrix_set(
    igraph_matrix_t* m, igraph_integer_t row, igraph_integer_t col,
    igraph_real_t value);
```

Set an element of a matrix. No range checking is performed.

Arguments:

m: The input matrix.
row: The row index.
col: The column index.

value: The new value of the element.

Time complexity: $O(1)$.

Matrix views

igraph_matrix_view — Creates a matrix view into an existing array.

```
const igraph_matrix_t* igraph_matrix_view(  
    const igraph_matrix_t *m, const igraph_real_t *data,  
    igraph_integer_t nrow, igraph_integer_t ncol);
```

This function lets you treat an existing C array as a matrix. The elements of the matrix are assumed to be stored in column-major order in the array, i.e. the elements of the first column are stored first, followed by the second column and so on.

Since this function creates a view into an existing array, you must *not* destroy the `igraph_matrix_t` object when you are done with it. Similarly, you must *not* call any function on it that may attempt to modify the size of the matrix. Modifying an element in the matrix will modify the underlying array as the two share the same memory block.

Arguments:

m: Pointer to a not yet initialized matrix object where the view will be created.

data: The array that the matrix provides a view into.

nrow: The number of rows in the matrix.

ncol: The number of columns in the matrix.

Returns:

Pointer to the matrix object, the same as the *m* parameter, for convenience.

Time complexity: $O(1)$.

igraph_matrix_view_from_vector — Creates a matrix view that treats an existing vector as a matrix.

```
const igraph_matrix_t *igraph_matrix_view_from_vector(  
    const igraph_matrix_t *m, const igraph_vector_t *v,  
    igraph_integer_t nrow  
);
```

This function lets you treat an existing igraph vector as a matrix. The elements of the matrix are assumed to be stored in column-major order in the vector, i.e. the elements of the first column are stored first, followed by the second column and so on.

Since this function creates a view into an existing vector, you must *not* destroy the `igraph_matrix_t` object when you are done with it. Similarly, you must *not* call any function on it that may

attempt to modify the size of the vector. Modifying an element in the matrix will modify the underlying vector as the two share the same memory block.

Additionally, you must *not* attempt to grow the underlying vector by any vector operation as that may result in a re-allocation of the backing memory block of the vector, and the matrix view will not be informed about the re-allocation so it will point to an invalid memory area afterwards.

Arguments:

m: Pointer to a not yet initialized matrix object where the view will be created.

v: The vector that the matrix will provide a view into.

nrow: The number of rows in the matrix. The number of columns will be derived implicitly from the size of the vector. If the number of items in the vector is not divisible by the number of rows, the last few elements of the vector will not be covered by the view.

Returns:

Error code.

Time complexity: $O(1)$.

Copying matrices

igraph_matrix_copy_to — Copies a matrix to a regular C array.

```
void igraph_matrix_copy_to(const igraph_matrix_t *m, igraph_real_t *to);
```

The matrix is copied columnwise, as this is the format most programs and languages use. The C array should be of sufficient size; there are (of course) no range checks.

Arguments:

m: Pointer to an initialized matrix object.

to: Pointer to a C array; the place to copy the data to.

Returns:

Error code.

Time complexity: $O(n)$, n is the number of elements in the matrix.

igraph_matrix_update — Update from another matrix.

```
igraph_error_t igraph_matrix_update(igraph_matrix_t *to,  
                                     const igraph_matrix_t *from);
```

This function replicates *from* in the matrix *to*. Note that *to* must be already initialized.

Arguments:

to: The result matrix.

from: The matrix to replicate; it is left unchanged.

Returns:

Error code.

Time complexity: $O(mn)$, the number of elements.

igraph_matrix_swap — Swap two matrices.

```
igraph_error_t igraph_matrix_swap(igraph_matrix_t *m1, igraph_matrix_t *m2);
```

The contents of the two matrices will be swapped.

Arguments:

m1: The first matrix.

m2: The second matrix.

Returns:

Error code.

Time complexity: $O(1)$.

Operations on rows and columns

igraph_matrix_get_row — Extract a row.

```
igraph_error_t igraph_matrix_get_row(const igraph_matrix_t *m,  
                                     igraph_vector_t *res, igraph_integer_t index);
```

Extract a row from a matrix and return it as a vector.

Arguments:

m: The input matrix.

res: Pointer to an initialized vector; it will be resized if needed.

index: The index of the row to select.

Returns:

Error code.

Time complexity: $O(n)$, the number of columns in the matrix.

igraph_matrix_get_col — Select a column.

```
igraph_error_t igraph_matrix_get_col(const igraph_matrix_t *m,
```

```
igraph_vector_t *res,  
igraph_integer_t index);
```

Extract a column of a matrix and return it as a vector.

Arguments:

m: The input matrix.

res: The result will be stored in this vector. It should be initialized and will be resized as needed.

index: The index of the column to select.

Returns:

Error code.

Time complexity: $O(n)$, the number of rows in the matrix.

igraph_matrix_set_row — Set a row from a vector.

```
igraph_error_t igraph_matrix_set_row(igraph_matrix_t *m,  
                                     const igraph_vector_t *v, igraph_integer_t
```

Sets the elements of a row with the given vector. This has the effect of setting row *index* to have the elements in the vector *v*. The length of the vector and the number of columns in the matrix must match, otherwise an error is triggered.

Arguments:

m: The input matrix.

v: The vector containing the new elements of the row.

index: Index of the row to set.

Returns:

Error code.

Time complexity: $O(n)$, the number of columns in the matrix.

igraph_matrix_set_col — Set a column from a vector.

```
igraph_error_t igraph_matrix_set_col(igraph_matrix_t *m,  
                                     const igraph_vector_t *v, igraph_integer_t
```

Sets the elements of a column with the given vector. In effect, column *index* will be set with elements from the vector *v*. The length of the vector and the number of rows in the matrix must match, otherwise an error is triggered.

Arguments:

m: The input matrix.

v: The vector containing the new elements of the column.

index: Index of the column to set.

Returns:

Error code.

Time complexity: $O(m)$, the number of rows in the matrix.

igraph_matrix_swap_rows — Swap two rows.

```
igraph_error_t igraph_matrix_swap_rows(igraph_matrix_t *m,  
                                       igraph_integer_t i, igraph_integer_t j);
```

Swap two rows in the matrix.

Arguments:

m: The input matrix.

i: The index of the first row.

j: The index of the second row.

Returns:

Error code.

Time complexity: $O(n)$, the number of columns.

igraph_matrix_swap_cols — Swap two columns.

```
igraph_error_t igraph_matrix_swap_cols(igraph_matrix_t *m,  
                                       igraph_integer_t i, igraph_integer_t j);
```

Swap two columns in the matrix.

Arguments:

m: The input matrix.

i: The index of the first column.

j: The index of the second column.

Returns:

Error code.

Time complexity: $O(m)$, the number of rows.

igraph_matrix_select_rows — Select some rows of a matrix.

```
igraph_error_t igraph_matrix_select_rows(const igraph_matrix_t *m,
                                         igraph_matrix_t *res,
                                         const igraph_vector_int_t *rows);
```

This function selects some rows of a matrix and returns them in a new matrix. The result matrix should be initialized before calling the function.

Arguments:

m: The input matrix.

res: The result matrix. It should be initialized and will be resized as needed.

rows: Vector; it contains the row indices (starting with zero) to extract. Note that no range checking is performed.

Returns:

Error code.

Time complexity: $O(nm)$, n is the number of rows, m the number of columns of the result matrix.

igraph_matrix_select_cols — Select some columns of a matrix.

```
igraph_error_t igraph_matrix_select_cols(const igraph_matrix_t *m,
                                         igraph_matrix_t *res,
                                         const igraph_vector_int_t *cols);
```

This function selects some columns of a matrix and returns them in a new matrix. The result matrix should be initialized before calling the function.

Arguments:

m: The input matrix.

res: The result matrix. It should be initialized and will be resized as needed.

cols: Vector; it contains the column indices (starting with zero) to extract. Note that no range checking is performed.

Returns:

Error code.

Time complexity: $O(nm)$, n is the number of rows, m the number of columns of the result matrix.

igraph_matrix_select_rows_cols — Select some rows and columns of a matrix.

```
igraph_error_t igraph_matrix_select_rows_cols(const igraph_matrix_t *m,
                                              igraph_matrix_t *res,
                                              const igraph_vector_int_t *rows,
                                              const igraph_vector_int_t *cols);
```

This function selects some rows and columns of a matrix and returns them in a new matrix. The result matrix should be initialized before calling the function.

Arguments:

m: The input matrix.

res: The result matrix. It should be initialized and will be resized as needed.

rows: Vector; it contains the row indices (starting with zero) to extract. Note that no range checking is performed.

cols: Vector; it contains the column indices (starting with zero) to extract. Note that no range checking is performed.

Returns:

Error code.

Time complexity: $O(nm)$, n is the number of rows, m the number of columns of the result matrix.

Matrix operations

igraph_matrix_add_constant — Add a constant to every element.

```
void igraph_matrix_add_constant(igraph_matrix_t *m, igraph_real_t plus);
```

Arguments:

m: The input matrix.

plus: The constant to add.

Time complexity: $O(mn)$, the number of elements.

igraph_matrix_scale — Multiplies each element of the matrix by a constant.

```
void igraph_matrix_scale(igraph_matrix_t *m, igraph_real_t by);
```

Arguments:

m: The matrix.

by: The constant.

Added in version 0.2.

Time complexity: $O(n)$, the number of elements in the matrix.

igraph_matrix_add — Add two matrices.


```
igraph_error_t igraph_matrix_add(igraph_matrix_t *m1,  
                                const igraph_matrix_t *m2);
```

Add $m2$ to $m1$, and store the result in $m1$. The dimensions of the matrices must match.

Arguments:

$m1$: The first matrix; the result will be stored here.

$m2$: The second matrix; it is left unchanged.

Returns:

Error code.

Time complexity: $O(mn)$, the number of elements.

igraph_matrix_sub — Difference of two matrices.

```
igraph_error_t igraph_matrix_sub(igraph_matrix_t *m1,  
                                const igraph_matrix_t *m2);
```

Subtract $m2$ from $m1$ and store the result in $m1$. The dimensions of the two matrices must match.

Arguments:

$m1$: The first matrix; the result is stored here.

$m2$: The second matrix; it is left unchanged.

Returns:

Error code.

Time complexity: $O(mn)$, the number of elements.

igraph_matrix_mul_elements — Elementwise multiplication.

```
igraph_error_t igraph_matrix_mul_elements(igraph_matrix_t *m1,  
                                           const igraph_matrix_t *m2);
```

Multiply $m1$ by $m2$ elementwise and store the result in $m1$. The dimensions of the two matrices must match.

Arguments:

$m1$: The first matrix; the result is stored here.

$m2$: The second matrix; it is left unchanged.

Returns:

Error code.

Time complexity: $O(mn)$, the number of elements.

igraph_matrix_div_elements — Elementwise division.

```
igraph_error_t igraph_matrix_div_elements(igraph_matrix_t *m1,  
                                           const igraph_matrix_t *m2);
```

Divide $m1$ by $m2$ elementwise and store the result in $m1$. The dimensions of the two matrices must match.

Arguments:

$m1$: The dividend. The result is store here.

$m2$: The divisor. It is left unchanged.

Returns:

Error code.

Time complexity: $O(mn)$, the number of elements.

igraph_matrix_sum — Sum of elements.

```
igraph_real_t igraph_matrix_sum(const igraph_matrix_t *m);
```

Returns the sum of the elements of a matrix.

Arguments:

m : The input matrix.

Returns:

The sum of the elements.

Time complexity: $O(mn)$, the number of elements in the matrix.

igraph_matrix_prod — Product of the elements.

```
igraph_real_t igraph_matrix_prod(const igraph_matrix_t *m);
```

Note this function can result in overflow easily, even for not too big matrices.

Arguments:

m : The input matrix.

Returns:

The product of the elements.

Time complexity: $O(mn)$, the number of elements.

igraph_matrix_rowsum — Rowwise sum.

```
igraph_error_t igraph_matrix_rowsum(const igraph_matrix_t *m,  
                                     igraph_vector_t *res);
```

Calculate the sum of the elements in each row.

Arguments:

m: The input matrix.

res: Pointer to an initialized vector; the result is stored here. It will be resized if necessary.

Returns:

Error code.

Time complexity: $O(mn)$, the number of elements in the matrix.

igraph_matrix_colsum — Columnwise sum.

```
igraph_error_t igraph_matrix_colsum(const igraph_matrix_t *m,  
                                     igraph_vector_t *res);
```

Calculate the sum of the elements in each column.

Arguments:

m: The input matrix.

res: Pointer to an initialized vector; the result is stored here. It will be resized if necessary.

Returns:

Error code.

Time complexity: $O(mn)$, the number of elements in the matrix.

igraph_matrix_transpose — Transpose a matrix.

```
igraph_error_t igraph_matrix_transpose(igraph_matrix_t *m);
```

Calculate the transpose of a matrix. Note that the function reallocates the memory used for the matrix.

Arguments:

m: The input (and output) matrix.

Returns:

Error code.

Time complexity: $O(mn)$, the number of elements in the matrix.

Matrix comparisons

igraph_matrix_all_e — Are all elements equal?

```
igraph_bool_t igraph_matrix_all_e(const igraph_matrix_t *lhs,
                                   const igraph_matrix_t *rhs);
```

Checks element-wise equality of two matrices. For matrices containing floating point values, consider using `igraph_matrix_all_almost_e()`.

Arguments:

lhs: The first matrix.

rhs: The second matrix.

Returns:

Positive integer (=true) if the elements in the *lhs* are all equal to the corresponding elements in *rhs*. Returns 0 (=false) if the dimensions of the matrices don't match.

Time complexity: $O(nm)$, the size of the matrices.

igraph_matrix_all_almost_e — Are all elements almost equal?

```
igraph_bool_t igraph_matrix_all_almost_e(const igraph_matrix_t *lhs,
                                           const igraph_matrix_t *rhs,
                                           igraph_real_t eps);
```

Checks if the elements of two matrices are equal within a relative tolerance.

Arguments:

lhs: The first matrix.

rhs: The second matrix.

eps: Relative tolerance, see `igraph_almost_equals()` for details.

Returns:

True if the two matrices are almost equal, false if there is at least one differing element or if the matrices are not of the same dimensions.

igraph_matrix_all_l — Are all elements less?

```
igraph_bool_t igraph_matrix_all_l(const igraph_matrix_t *lhs,
                                   const igraph_matrix_t *rhs);
```

Arguments:

lhs: The first matrix.

rhs: The second matrix.

Returns:

Positive integer (=true) if the elements in the *lhs* are all less than the corresponding elements in *rhs*. Returns 0 (=false) if the dimensions of the matrices don't match.

Time complexity: $O(nm)$, the size of the matrices.

igraph_matrix_all_g — Are all elements greater?

```
igraph_bool_t igraph_matrix_all_g(const igraph_matrix_t *lhs,
                                   const igraph_matrix_t *rhs);
```

Arguments:

lhs: The first matrix.

rhs: The second matrix.

Returns:

Positive integer (=true) if the elements in the *lhs* are all greater than the corresponding elements in *rhs*. Returns 0 (=false) if the dimensions of the matrices don't match.

Time complexity: $O(nm)$, the size of the matrices.

igraph_matrix_all_le — Are all elements less or equal?

```
igraph_bool_t
igraph_matrix_all_le(const igraph_matrix_t *lhs,
                     const igraph_matrix_t *rhs);
```

Arguments:

lhs: The first matrix.

rhs: The second matrix.

Returns:

Positive integer (=true) if the elements in the *lhs* are all less than or equal to the corresponding elements in *rhs*. Returns 0 (=false) if the dimensions of the matrices don't match.

Time complexity: $O(nm)$, the size of the matrices.

igraph_matrix_all_ge — Are all elements greater or equal?

```
igraph_bool_t  
igraph_matrix_all_ge(const igraph_matrix_t *lhs,  
                    const igraph_matrix_t *rhs);
```

Arguments:

lhs: The first matrix.

rhs: The second matrix.

Returns:

Positive integer (=true) if the elements in the *lhs* are all greater than or equal to the corresponding elements in *rhs*. Returns 0 (=false) if the dimensions of the matrices don't match.

Time complexity: $O(nm)$, the size of the matrices.

igraph_matrix_zapsmall — Replaces small elements of a matrix by exact zeros.

```
igraph_error_t igraph_matrix_zapsmall(igraph_matrix_t *m, igraph_real_t tol);
```

Matrix elements which are smaller in magnitude than the given absolute tolerance will be replaced by exact zeros. The default tolerance corresponds to two-thirds of the representable digits of `igraph_real_t`, i.e. $\text{DBL_EPSILON}^{(2/3)}$ which is approximately 10^{-10} .

Arguments:

m: The matrix to process, it will be changed in-place.

tol: Tolerance value. Numbers smaller than this in magnitude will be replaced by zeros. Pass in zero to use the default tolerance. Must not be negative.

Returns:

Error code.

See also:

`igraph_matrix_all_almost_e()` and `igraph_almost_equals()` to perform comparisons with relative tolerances.

Combining matrices

igraph_matrix_rbind — Combine two matrices rowwise.

```
igraph_error_t igraph_matrix_rbind(igraph_matrix_t *to,  
                                   const igraph_matrix_t *from);
```

This function places the rows of *from* below the rows of *to* and stores the result in *to*. The number of columns in the two matrices must match.

Arguments:

to: The upper matrix; the result is also stored here.

from: The lower matrix. It is left unchanged.

Returns:

Error code.

Time complexity: $O(mn)$, the number of elements in the newly created matrix.

igraph_matrix_cbind — Combine matrices columnwise.

```
igraph_error_t igraph_matrix_cbind(igraph_matrix_t *to,  
                                   const igraph_matrix_t *from);
```

This function places the columns of *from* on the right of *to*, and stores the result in *to*.

Arguments:

to: The left matrix; the result is stored here too.

from: The right matrix. It is left unchanged.

Returns:

Error code.

Time complexity: $O(mn)$, the number of elements on the new matrix.

Finding minimum and maximum

igraph_matrix_min — Smallest element of a matrix.

```
igraph_real_t igraph_matrix_min(const igraph_matrix_t *m);
```

The matrix must be non-empty.

Arguments:

m: The input matrix.

Returns:

The smallest element of *m*, or NaN if any element is NaN.

Time complexity: $O(mn)$, the number of elements in the matrix.

igraph_matrix_max — Largest element of a matrix.

```
igraph_real_t igraph_matrix_max(const igraph_matrix_t *m);
```

If the matrix is empty, an arbitrary number is returned.

Arguments:

m: The matrix object.

Returns:

The maximum element of *m*, or NaN if any element is NaN.

Added in version 0.2.

Time complexity: $O(mn)$, the number of elements in the matrix.

igraph_matrix_which_min — Indices of the smallest element.

```
void igraph_matrix_which_min(  
    const igraph_matrix_t *m, igraph_integer_t *i, igraph_integer_t *j);
```

The matrix must be non-empty. If the smallest element is not unique, then the indices of the first such element are returned. If the matrix contains NaN values, the indices of the first NaN value are returned.

Arguments:

m: The matrix.

i: Pointer to an `igraph_integer_t`. The row index of the minimum is stored here.

j: Pointer to an `igraph_integer_t`. The column index of the minimum is stored here.

Time complexity: $O(mn)$, the number of elements.

igraph_matrix_which_max — Indices of the largest element.

```
void igraph_matrix_which_max(  
    const igraph_matrix_t *m, igraph_integer_t *i, igraph_integer_t *j);
```

The matrix must be non-empty. If the largest element is not unique, then the indices of the first such element are returned. If the matrix contains NaN values, the indices of the first NaN value are returned.

Arguments:

m: The matrix.

i: Pointer to an `igraph_integer_t`. The row index of the maximum is stored here.

j: Pointer to an `igraph_integer_t`. The column index of the maximum is stored here.

Time complexity: $O(mn)$, the number of elements.

igraph_matrix_minmax — Minimum and maximum elements of a matrix.


```
void igraph_matrix_minmax(const igraph_matrix_t *m,
                          igraph_real_t *min, igraph_real_t *max);
```

Handy if you want to have both the smallest and largest element of a matrix. The matrix is only traversed once. The matrix must be non-empty. If a matrix contains at least one NaN, both `min` and `max` will be NaN.

Arguments:

m: The input matrix. It must contain at least one element.

min: Pointer to a base type variable. The minimum is stored here.

max: Pointer to a base type variable. The maximum is stored here.

Time complexity: $O(mn)$, the number of elements.

igraph_matrix_which_minmax — Indices of the minimum and maximum elements

```
void igraph_matrix_which_minmax(const igraph_matrix_t *m,
                                igraph_integer_t *imin, igraph_integer_t *jmin,
                                igraph_integer_t *imax, igraph_integer_t *jmax);
```

Handy if you need the indices of the smallest and largest elements. The matrix is traversed only once. The matrix must be non-empty. If the minimum or maximum is not unique, the index of the first minimum or the first maximum is returned, respectively. If a matrix contains at least one NaN, both `which_min` and `which_max` will point to the first NaN value.

Arguments:

m: The input matrix.

imin: Pointer to an `igraph_integer_t`, the row index of the minimum is stored here.

jmin: Pointer to an `igraph_integer_t`, the column index of the minimum is stored here.

imax: Pointer to an `igraph_integer_t`, the row index of the maximum is stored here.

jmax: Pointer to an `igraph_integer_t`, the column index of the maximum is stored here.

Time complexity: $O(mn)$, the number of elements.

Matrix properties

igraph_matrix_empty — Check for an empty matrix.

```
igraph_bool_t igraph_matrix_empty(const igraph_matrix_t *m);
```

It is possible to have a matrix with zero rows or zero columns, or even both. This functions checks for these.

Arguments:

m: The input matrix.

Returns:

Boolean, `true` if the matrix contains zero elements, and `false` otherwise.

Time complexity: $O(1)$.

`igraph_matrix_isnull` — Check for a null matrix.

```
igraph_bool_t igraph_matrix_isnull(const igraph_matrix_t *m);
```

Checks whether all elements are zero.

Arguments:

m: The input matrix.

Returns:

Boolean, `true` if *m* contains only zeros and `false` otherwise.

Time complexity: $O(mn)$, the number of elements.

`igraph_matrix_size` — The number of elements in a matrix.

```
igraph_integer_t igraph_matrix_size(const igraph_matrix_t *m);
```

Arguments:

m: Pointer to an initialized matrix object.

Returns:

The size of the matrix.

Time complexity: $O(1)$.

`igraph_matrix_capacity` — Returns the number of elements allocated for a matrix.

```
igraph_integer_t igraph_matrix_capacity(const igraph_matrix_t *m);
```

Note that this might be different from the size of the matrix (as queried by `igraph_matrix_size()`), and specifies how many elements the matrix can hold, without reallocation.

Arguments:

v: Pointer to the (previously initialized) matrix object to query.

Returns:

The allocated capacity.

See also:

`igraph_matrix_size()`, `igraph_matrix_nrow()`, `igraph_matrix_ncol()`.

Time complexity: $O(1)$.

`igraph_matrix_nrow` — The number of rows in a matrix.

```
igraph_integer_t igraph_matrix_nrow(const igraph_matrix_t *m);
```

Arguments:

m: Pointer to an initialized matrix object.

Returns:

The number of rows in the matrix.

Time complexity: $O(1)$.

`igraph_matrix_ncol` — The number of columns in a matrix.

```
igraph_integer_t igraph_matrix_ncol(const igraph_matrix_t *m);
```

Arguments:

m: Pointer to an initialized matrix object.

Returns:

The number of columns in the matrix.

Time complexity: $O(1)$.

`igraph_matrix_is_symmetric` — Check for symmetric matrix.

```
igraph_bool_t igraph_matrix_is_symmetric(const igraph_matrix_t *m);
```

A non-square matrix is not symmetric by definition.

Arguments:

m: The input matrix.

Returns:

Boolean, `true` if the matrix is square and symmetric, `false` otherwise.

Time complexity: $O(mn)$, the number of elements. $O(1)$ for non-square matrices.

igraph_matrix_maxdifference — Maximum absolute difference between two matrices.

```
igraph_real_t igraph_matrix_maxdifference(const igraph_matrix_t *m1,  
                                           const igraph_matrix_t *m2);
```

Calculate the maximum absolute difference of two matrices. Both matrices must be non-empty. If their dimensions differ then a warning is given and the comparison is performed by vectors columnwise from both matrices. The remaining elements in the larger vector are ignored.

Arguments:

m1: The first matrix.

m2: The second matrix.

Returns:

The element with the largest absolute value in $m1 - m2$.

Time complexity: $O(mn)$, the elements in the smaller matrix.

Searching for elements

igraph_matrix_contains — Search for an element.

```
igraph_bool_t igraph_matrix_contains(const igraph_matrix_t *m,  
                                     igraph_real_t e);
```

Search for the given element in the matrix.

Arguments:

m: The input matrix.

e: The element to search for.

Returns:

Boolean, true if the matrix contains *e*, false otherwise.

Time complexity: $O(mn)$, the number of elements.

igraph_matrix_search — Search from a given position.

```
igraph_bool_t igraph_matrix_search(const igraph_matrix_t *m,  
                                   igraph_integer_t from, igraph_real_t what, igraph_integer_t *pos,  
                                   igraph_integer_t *row, igraph_integer_t *col);
```

Search for an element in a matrix and start the search from the given position. The search is performed columnwise.

Arguments:

- m*: The input matrix.
- from*: The position to search from, the positions are enumerated columnwise.
- what*: The element to search for.
- pos*: Pointer to an `igraph_integer_t`. If the element is found, then this is set to the position of its first appearance.
- row*: Pointer to an `igraph_integer_t`. If the element is found, then this is set to its row index.
- col*: Pointer to an `igraph_integer_t`. If the element is found, then this is set to its column index.

Returns:

Boolean, `true` if the element is found, `false` otherwise.

Time complexity: $O(mn)$, the number of elements.

Resizing operations

`igraph_matrix_resize` — Resizes a matrix.

```
igraph_error_t igraph_matrix_resize(igraph_matrix_t *m, igraph_integer_t nrow,
```

This function resizes a matrix by adding more elements to it. The matrix contains arbitrary data after resizing it. That is, after calling this function you cannot expect that element (i,j) in the matrix remains the same as before.

Arguments:

- m*: Pointer to an already initialized matrix object.
- nrow*: The number of rows in the resized matrix.
- ncol*: The number of columns in the resized matrix.

Returns:

Error code.

Time complexity: $O(1)$ if the matrix gets smaller, usually $O(n)$ if it gets larger, n is the number of elements in the resized matrix.

`igraph_matrix_resize_min` — Deallocates unused memory for a matrix.

```
void igraph_matrix_resize_min(igraph_matrix_t *m);
```

This function attempts to deallocate the unused reserved storage of a matrix.

Arguments:

m: Pointer to an initialized matrix.

See also:

`igraph_matrix_resize()`.

Time complexity: operating system dependent, $O(n)$ at worst.

igraph_matrix_add_rows — Adds rows to a matrix.

```
igraph_error_t igraph_matrix_add_rows(igraph_matrix_t *m, igraph_integer_t n);
```

Arguments:

m: The matrix object.

n: The number of rows to add.

Returns:

Error code, `IGRAPH_ENOMEM` if there isn't enough memory for the operation.

Time complexity: linear with the number of elements of the new, resized matrix.

igraph_matrix_add_cols — Adds columns to a matrix.

```
igraph_error_t igraph_matrix_add_cols(igraph_matrix_t *m, igraph_integer_t n);
```

Arguments:

m: The matrix object.

n: The number of columns to add.

Returns:

Error code, `IGRAPH_ENOMEM` if there is not enough memory to perform the operation.

Time complexity: linear with the number of elements of the new, resized matrix.

igraph_matrix_remove_row — Remove a row.

```
igraph_error_t igraph_matrix_remove_row(igraph_matrix_t *m, igraph_integer_t row);
```

A row is removed from the matrix.

Arguments:

m: The input matrix.

row: The index of the row to remove.

Returns:

Error code.

Time complexity: $O(mn)$, the number of elements in the matrix.

igraph_matrix_remove_col — Removes a column from a matrix.

```
igraph_error_t igraph_matrix_remove_col(igraph_matrix_t *m, igraph_integer_t col);
```

Arguments:

m: The matrix object.

col: The column to remove.

Returns:

Error code, always returns with success.

Time complexity: linear with the number of elements of the new, resized matrix.

Complex matrix operations

igraph_matrix_complex_real — Gives the real part of a complex matrix.

```
igraph_error_t igraph_matrix_complex_real(const igraph_matrix_complex_t *m,  
                                           igraph_matrix_t *real);
```

Arguments:

m: Pointer to a complex matrix.

real: Pointer to an initialized matrix. The result will be stored here.

Returns:

Error code.

Time complexity: $O(n)$, n is the number of elements in the matrix.

igraph_matrix_complex_imag — Gives the imaginary part of a complex matrix.

```
igraph_error_t igraph_matrix_complex_imag(const igraph_matrix_complex_t *m,  
                                           igraph_matrix_t *imag);
```

Arguments:

m: Pointer to a complex matrix.

imag: Pointer to an initialized matrix. The result will be stored here.

Returns:

Error code.

Time complexity: $O(n)$, n is the number of elements in the matrix.

igraph_matrix_complex_realimag — Gives the real and imaginary parts of a complex matrix.

```
igraph_error_t igraph_matrix_complex_realimag(const igraph_matrix_complex_t *m,  
                                              igraph_matrix_t *real,  
                                              igraph_matrix_t *imag);
```

Arguments:

m: Pointer to a complex matrix.

real: Pointer to an initialized matrix. The real part will be stored here.

imag: Pointer to an initialized matrix. The imaginary part will be stored here.

Returns:

Error code.

Time complexity: $O(n)$, n is the number of elements in the matrix.

igraph_matrix_complex_create — Creates a complex matrix from a real and imaginary part.

```
igraph_error_t igraph_matrix_complex_create(igraph_matrix_complex_t *m,  
                                             const igraph_matrix_t *real,  
                                             const igraph_matrix_t *imag);
```

Arguments:

m: Pointer to an uninitialized complex matrix.

real: Pointer to the real part of the complex matrix.

imag: Pointer to the imaginary part of the complex matrix.

Returns:

Error code.

Time complexity: $O(n)$, n is the number of elements in the matrix.

igraph_matrix_complex_create_polar — Creates a complex matrix from a magnitude and an angle.

```
igraph_error_t igraph_matrix_complex_create_polar(igraph_matrix_complex_t *m,  
                                                  const igraph_matrix_t *r,  
                                                  const igraph_matrix_t *theta);
```

Arguments:

m: Pointer to an uninitialized complex matrix.

r: Pointer to a real matrix containing magnitudes.

theta: Pointer to a real matrix containing arguments (phase angles).

Returns:

Error code.

Time complexity: $O(n)$, n is the number of elements in the matrix.

igraph_matrix_complex_all_almost_e — Are all elements almost equal?

```
igraph_bool_t igraph_matrix_complex_all_almost_e(igraph_matrix_complex_t *lhs,  
                                                  igraph_matrix_complex_t *rhs,  
                                                  igraph_real_t eps);
```

Checks if the elements of two complex matrices are equal within a relative tolerance.

Arguments:

lhs: The first matrix.

rhs: The second matrix.

eps: Relative tolerance, see `igraph_complex_almost_equals()` for details.

Returns:

True if the two matrices are almost equal, false if there is at least one differing element or if the matrices are not of the same dimensions.

igraph_matrix_complex_zapsmall — Replaces small elements of a complex matrix by exact zeros.

```
igraph_error_t igraph_matrix_complex_zapsmall(igraph_matrix_complex_t *m, igraph_real_t eps);
```

Similarly to `igraph_matrix_zapsmall()`, small elements will be replaced by zeros. The operation is performed separately on the real and imaginary parts of the numbers. This way, complex

numbers with a large real part and tiny imaginary part will effectively be transformed to real numbers. The default tolerance corresponds to two-thirds of the representable digits of `igraph_real_t`, i.e. $\text{DBL_EPSILON}^{(2/3)}$ which is approximately 10^{-10} .

Arguments:

- m*: The matrix to process, it will be changed in-place.
- tol*: Tolerance value. Real and imaginary parts smaller than this in magnitude will be replaced by zeros. Pass in zero to use the default tolerance. Must not be negative.

Returns:

Error code.

See also:

`igraph_matrix_complex_all_almost_e()` and `igraph_complex_almost_equals()` to perform comparisons with relative tolerances.

Deprecated functions

`igraph_matrix_copy` — Copies a matrix (deprecated alias).

```
igraph_error_t igraph_matrix_copy(igraph_matrix_t *to, const igraph_matrix_t *from)
```

Warning

Deprecated since version 0.10. Please do not use this function in new code; use `igraph_matrix_init_copy()` instead.

`igraph_matrix_e` — Extract an element from a matrix (deprecated alias).

```
igraph_real_t igraph_matrix_e(const igraph_matrix_t *m,  
                              igraph_integer_t row, igraph_integer_t col);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_matrix_get()` instead.

`igraph_matrix_e_ptr` — Pointer to an element of a matrix.

```
igraph_real_t* igraph_matrix_e_ptr(const igraph_matrix_t *m,  
                                   igraph_integer_t row, igraph_integer_t col)
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_matrix_get_ptr()` instead.

Sparse matrices

About sparse matrices

The `igraph_sparsemat_t` data type stores sparse matrices, i.e. matrices in which the majority of the elements are zero.

The data type is essentially a wrapper to some of the functions in the CXSparse library, by Tim Davis, see <http://faculty.cse.tamu.edu/davis/suitesparse.html>

Matrices can be stored in two formats: triplet and column-compressed. The triplet format is intended for sparse matrix initialization, as it is easy to add new (non-zero) elements to it. Most of the computations are done on sparse matrices in column-compressed format, after the user has converted the triplet matrix to column-compressed, via `igraph_sparsemat_compress()`.

Both formats are dynamic, in the sense that new elements can be added to them, possibly resulting the allocation of more memory.

Row and column indices follow the C convention and are zero-based.

Example 7.4. File `examples/simple/igraph_sparsemat.c`

Example 7.5. File `examples/simple/igraph_sparsemat3.c`

Example 7.6. File `examples/simple/igraph_sparsemat4.c`

Example 7.7. File `examples/simple/igraph_sparsemat6.c`

Example 7.8. File `examples/simple/igraph_sparsemat7.c`

Example 7.9. File `examples/simple/igraph_sparsemat8.c`

Creating sparse matrix objects

`igraph_sparsemat_init` — Initializes a sparse matrix, in triplet format.

```
igraph_error_t igraph_sparsemat_init(igraph_sparsemat_t *A, igraph_integer_t rows,
                                     igraph_integer_t cols, igraph_integer_t nzmax);
```

This is the most common way to create a sparse matrix, together with the `igraph_sparsemat_entry()` function, which can be used to add the non-zero elements one by one. Once done, the

user can call `igraph_sparsemat_compress()` to convert the matrix to column-compressed, to allow computations with it.

The user must call `igraph_sparsemat_destroy()` on the matrix to deallocate the memory, once the matrix is no more needed.

Arguments:

A: Pointer to a not yet initialized sparse matrix.

rows: The number of rows in the matrix.

cols: The number of columns.

nzmax: The maximum number of non-zero elements in the matrix. It is not compulsory to get this right, but it is useful for the allocation of the proper amount of memory.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_init_copy — Copies a sparse matrix.

```
igraph_error_t igraph_sparsemat_init_copy(  
    igraph_sparsemat_t *to, const igraph_sparsemat_t *from  
);
```

Create a sparse matrix object, by copying another one. The source matrix can be either in triplet or column-compressed format.

Exactly the same amount of memory will be allocated to the copy matrix, as it is currently for the original one.

Arguments:

to: Pointer to an uninitialized sparse matrix, the copy will be created here.

from: The sparse matrix to copy.

Returns:

Error code.

Time complexity: $O(n+nzmax)$, the number of columns plus the maximum number of non-zero elements.

igraph_sparsemat_init_diag — Creates a sparse diagonal matrix.

```
igraph_error_t igraph_sparsemat_init_diag(  
    igraph_sparsemat_t *A, igraph_integer_t nzmax, const igraph_vector_t *values,  
    igraph_bool_t compress  
);
```

Arguments:

- A*: An uninitialized sparse matrix, the result is stored here.
- nzmax*: The maximum number of non-zero elements, this essentially gives the amount of memory that will be allocated for matrix elements.
- values*: The values to store in the diagonal, the size of the matrix defined by the length of this vector.
- compress*: Whether to create a column-compressed matrix. If false, then a triplet matrix is created.

Returns:

Error code.

Time complexity: $O(n)$, the length of the diagonal vector.

igraph_sparsemat_init_eye — Creates a sparse identity matrix.

```
igraph_error_t igraph_sparsemat_init_eye(
    igraph_sparsemat_t *A, igraph_integer_t n, igraph_integer_t nzmax,
    igraph_real_t value, igraph_bool_t compress
);
```

Arguments:

- A*: An uninitialized sparse matrix, the result is stored here.
- n*: The number of rows and number of columns in the matrix.
- nzmax*: The maximum number of non-zero elements, this essentially gives the amount of memory that will be allocated for matrix elements.
- value*: The value to store in the diagonal.
- compress*: Whether to create a column-compressed matrix. If false, then a triplet matrix is created.

Returns:

Error code.

Time complexity: $O(n)$.

igraph_sparsemat_realloc — Allocates more (or less) memory for a sparse matrix.

```
igraph_error_t igraph_sparsemat_realloc(igraph_sparsemat_t *A, igraph_integer_t
```

Sparse matrices automatically allocate more memory, as needed. To control memory allocation, the user can call this function, to allocate memory for a given number of non-zero elements.

Arguments:

A: The sparse matrix, it can be in triplet or column-compressed format.

***nzmax*:** The new maximum number of non-zero elements.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_destroy — Deallocates memory used by a sparse matrix.

```
void igraph_sparsemat_destroy(igraph_sparsemat_t *A);
```

One destroyed, the sparse matrix must be initialized again, before calling any other operation on it.

Arguments:

A: The sparse matrix to destroy.

Time complexity: $O(1)$.

igraph_sparsemat_view — Initialize a sparse matrix and set all parameters.

```
igraph_error_t igraph_sparsemat_view(igraph_sparsemat_t *A, igraph_integer_t nzmax,  
                                     igraph_integer_t *p, igraph_integer_t *i, igraph_real_t *x);
```

This function can be used to temporarily handle existing sparse matrix data, usually created by another software library, as an `igraph_sparsemat_t` object, and thus avoid unnecessary copying. It supports data stored in either the compressed sparse column format, or the (i, j, x) triplet format where i and j are the matrix indices of a non-zero element, and x is its value.

The compressed sparse column (or row) format is commonly used to represent sparse matrix data. It consists of three vectors, the p column pointers, the i row indices, and the x values. $p[k]$ is the number of non-zero entries in matrix columns $k-1$ and lower. $p[0]$ is always zero and $p[n]$ is always the total number of non-zero entries in the matrix. $i[1]$ is the row index of the 1-th stored element, while $x[1]$ is its value. If a matrix element with indices (j, k) is explicitly stored, it must be located between positions $p[k]$ and $p[k+1] - 1$ (inclusive) in the i and x vectors.

Do not call `igraph_sparsemat_destroy()` on a sparse matrix created with this function. Instead, `igraph_free()` must be called on the `cs` field of A to free the storage allocated by this function.

Warning: Matrices created with this function must not be used with functions that may reallocate the underlying storage, such as `igraph_sparsemat_entry()`.

Arguments:

A: The non-initialized sparse matrix.

***nzmax*:** The maximum number of entries, typically the actual number of entries.

<i>m</i> :	The number of matrix rows.
<i>n</i> :	The number of matrix columns.
<i>p</i> :	For a compressed matrix, this is the column pointer vector, and must be of size $n+1$. For a triplet format matrix, it is a vector of column indices and must be of size <i>nzmax</i> .
<i>i</i> :	The row vector. This should contain the row indices of the elements in <i>x</i> . It must be of size <i>nzmax</i> .
<i>x</i> :	The values of the non-zero elements of the sparse matrix. It must be of size <i>nzmax</i> .
<i>nz</i> :	For a compressed matrix, it must be -1. For a triplet format matrix, it must contain the number of entries.

Returns:

Error code.

Time complexity: $O(1)$.

Query properties of a sparse matrix

igraph_sparsemat_index — Extracts a submatrix or a single element.

```
igraph_error_t igraph_sparsemat_index(const igraph_sparsemat_t *A,
                                      const igraph_vector_int_t *p,
                                      const igraph_vector_int_t *q,
                                      igraph_sparsemat_t *res,
                                      igraph_real_t *constres);
```

This function indexes into a sparse matrix. It serves two purposes. First, it can extract submatrices from a sparse matrix. Second, as a special case, it can extract a single element from a sparse matrix.

Arguments:

<i>A</i> :	The input matrix, it must be in column-compressed format.
<i>p</i> :	An integer vector, or a null pointer. The selected row index or indices. A null pointer selects all rows.
<i>q</i> :	An integer vector, or a null pointer. The selected column index or indices. A null pointer selects all columns.
<i>res</i> :	Pointer to an uninitialized sparse matrix, or a null pointer. If not a null pointer, then the selected submatrix is stored here.
<i>constres</i> :	Pointer to a real variable or a null pointer. If not a null pointer, then the first non-zero element in the selected submatrix is stored here, if there is one. Otherwise zero is stored here. This behavior is handy if one wants to select a single entry from the matrix.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_nrow — Number of rows.

```
igraph_integer_t igraph_sparsemat_nrow(const igraph_sparsemat_t *A);
```

Arguments:

A: The input matrix, in triplet or column-compressed format.

Returns:

The number of rows in the *A* matrix.

Time complexity: $O(1)$.

igraph_sparsemat_ncol — Number of columns.

```
igraph_integer_t igraph_sparsemat_ncol(const igraph_sparsemat_t *A);
```

Arguments:

A: The input matrix, in triplet or column-compressed format.

Returns:

The number of columns in the *A* matrix.

Time complexity: $O(1)$.

igraph_sparsemat_type — Type of a sparse matrix (triplet or column-compressed).

```
igraph_sparsemat_type_t igraph_sparsemat_type(const igraph_sparsemat_t *A);
```

Gives whether a sparse matrix is stored in the triplet format or in column-compressed format.

Arguments:

A: The input matrix.

Returns:

Either `IGRAPH_SPARSEMAT_CC` or `IGRAPH_SPARSEMAT_TRIPLET`.

Time complexity: $O(1)$.

igraph_sparsemat_is_triplet — Is this sparse matrix in triplet format?


```
igraph_bool_t igraph_sparsemat_is_triplet(const igraph_sparsemat_t *A);
```

Decides whether a sparse matrix is in triplet format.

Arguments:

A: The input matrix.

Returns:

One if the input matrix is in triplet format, zero otherwise.

Time complexity: $O(1)$.

igraph_sparsemat_is_cc — Is this sparse matrix in column-compressed format?

```
igraph_bool_t igraph_sparsemat_is_cc(const igraph_sparsemat_t *A);
```

Decides whether a sparse matrix is in column-compressed format.

Arguments:

A: The input matrix.

Returns:

One if the input matrix is in column-compressed format, zero otherwise.

Time complexity: $O(1)$.

igraph_sparsemat_is_symmetric — Returns whether a sparse matrix is symmetric.

```
igraph_error_t igraph_sparsemat_is_symmetric(const igraph_sparsemat_t *A, igraph_bool_t *result);
```

Arguments:

A: The input matrix

result: Pointer to an `igraph_bool_t`; the result is provided here.

Returns:

Error code.

igraph_sparsemat_get — Return the value of a single element from a sparse matrix.

```
igraph_real_t igraph_sparsemat_get(  
    const igraph_sparsemat_t *A, igraph_integer_t row, igraph_integer_t col  
);
```

Arguments:

A: The input matrix, in triplet or column-compressed format.

row: The row index

col: The column index

Returns:

The value of the cell with the given row and column indices in the matrix; zero if the indices are out of bounds.

Time complexity: TODO.

igraph_sparsemat_getelements — Returns all elements of a sparse matrix

```
igraph_error_t igraph_sparsemat_getelements(const igraph_sparsemat_t *A,  
                                             igraph_vector_int_t *i,  
                                             igraph_vector_int_t *j,  
                                             igraph_vector_t *x);
```

This function will return the elements of a sparse matrix in three vectors. Two vectors will indicate where the elements are located, and one will specify the elements themselves.

Arguments:

A: A sparse matrix in either triplet or compressed form.

i: An initialized integer vector. This will store the rows of the returned elements.

j: An initialized integer vector. For a triplet matrix this will store the columns of the returned elements. For a compressed matrix, if the column index is k , then $j[k]$ is the index in x of the start of the k -th column, and the last element of j is the total number of elements. The total number of elements in the k -th column is therefore $j[k+1] - j[k]$. For example, if there is one element in the first column, and five in the second, j will be set to $\{0, 1, 6\}$.

x: An initialized vector. The elements will be placed here.

Returns:

Error code.

Time complexity: $O(n)$, the number of stored elements in the sparse matrix.

igraph_sparsemat_getelements_sorted — Returns all elements of a sparse matrix, sorted by row and column indices.

```
igraph_error_t igraph_sparsemat_getelements_sorted(const igraph_sparsemat_t *A,  
                                                    igraph_vector_int_t *i,  
                                                    igraph_vector_int_t *j,  
                                                    igraph_vector_t *x);
```

This function will sort a sparse matrix and return the elements in three vectors. Two vectors will indicate where the elements are located, and one will specify the elements themselves.

Sorting is done based on the *indices* of the elements, not their numeric values. The returned entries will be sorted by column indices; entries in the same column are then sorted by row indices.

Arguments:

- A: A sparse matrix in either triplet or compressed form.
- i: An initialized integer vector. This will store the rows of the returned elements.
- j: An initialized integer vector. For a triplet matrix this will store the columns of the returned elements. For a compressed matrix, if the column index is k , then $j[k]$ is the index in x of the start of the k -th column, and the last element of j is the total number of elements. The total number of elements in the k -th column is therefore $j[k+1] - j[k]$. For example, if there is one element in the first column, and five in the second, j will be set to $\{0, 1, 6\}$.
- x: An initialized vector. The elements will be placed here.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_min — Minimum of a sparse matrix.

```
igraph_real_t igraph_sparsemat_min(igraph_sparsemat_t *A);
```

Arguments:

- A: The input matrix, column-compressed.

Returns:

The minimum in the input matrix, or IGRAPH_POSINFINITY if the matrix has zero elements.

Time complexity: TODO.

igraph_sparsemat_max — Maximum of a sparse matrix.

```
igraph_real_t igraph_sparsemat_max(igraph_sparsemat_t *A);
```

Arguments:

- A: The input matrix, column-compressed.

Returns:

The maximum in the input matrix, or `IGRAPH_NEGINFINITY` if the matrix has zero elements.

Time complexity: TODO.

`igraph_sparsemat_minmax` — Minimum and maximum of a sparse matrix.

```
igraph_error_t igraph_sparsemat_minmax(igraph_sparsemat_t *A,  
                                       igraph_real_t *min, igraph_real_t *max);
```

Arguments:

A: The input matrix, column-compressed.

min: The minimum in the input matrix is stored here, or `IGRAPH_POSINFINITY` if the matrix has zero elements.

max: The maximum in the input matrix is stored here, or `IGRAPH_NEGINFINITY` if the matrix has zero elements.

Returns:

Error code.

Time complexity: TODO.

`igraph_sparsemat_count_nonzero` — Counts nonzero elements of a sparse matrix.

```
igraph_integer_t igraph_sparsemat_count_nonzero(igraph_sparsemat_t *A);
```

Arguments:

A: The input matrix, column-compressed.

Returns:

Error code.

Time complexity: TODO.

`igraph_sparsemat_count_nonzerotol` — Counts nonzero elements of a sparse matrix, ignoring elements close to zero.

```
igraph_integer_t igraph_sparsemat_count_nonzerotol(igraph_sparsemat_t *A,  
                                                    igraph_real_t tol);
```

Count the number of matrix entries that are closer to zero than *tol*.

Arguments:

The: input matrix, column-compressed.

Real: scalar, the tolerance.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_rowsums — Row-wise sums.

```
igraph_error_t igraph_sparsemat_rowsums(const igraph_sparsemat_t *A,  
                                         igraph_vector_t *res);
```

Arguments:

A: The input matrix, in triplet or column-compressed format.

res: An initialized vector, the result is stored here. It will be resized as needed.

Returns:

Error code.

Time complexity: $O(nz)$, the number of non-zero elements.

igraph_sparsemat_colsums — Column-wise sums.

```
igraph_error_t igraph_sparsemat_colsums(const igraph_sparsemat_t *A,  
                                         igraph_vector_t *res);
```

Arguments:

A: The input matrix, in triplet or column-compressed format.

res: An initialized vector, the result is stored here. It will be resized as needed.

Returns:

Error code.

Time complexity: $O(nz)$ for triplet matrices, $O(nz+n)$ for column-compressed ones, nz is the number of non-zero elements, n is the number of columns.

igraph_sparsemat_nonzero_storage — Returns number of stored entries of a sparse matrix.

```
igraph_integer_t igraph_sparsemat_nonzero_storage(const igraph_sparsemat_t *A);
```

This function will return the number of stored entries of a sparse matrix. These entries can be zero, and multiple entries can be at the same position. Use `igraph_sparsemat_dupl()` to sum duplicate entries, and `igraph_sparsemat_dropzeros()` to remove zeros.

Arguments:

A: A sparse matrix in either triplet or compressed form.

Returns:

Number of stored entries.

Time complexity: $O(1)$.

Operations on sparse matrices

`igraph_sparsemat_entry` — Adds an element to a sparse matrix.

```
igraph_error_t igraph_sparsemat_entry(igraph_sparsemat_t *A,
                                       igraph_integer_t row, igraph_integer_t col, igraph_real_t elem);
```

This function can be used to add the entries to a sparse matrix, after initializing it with `igraph_sparsemat_init()`. If you add multiple entries in the same position, they will all be saved, and the resulting value is the sum of all entries in that position.

Arguments:

A: The input matrix, it must be in triplet format.

row: The row index of the entry to add.

col: The column index of the entry to add.

elem: The value of the entry.

Returns:

Error code.

Time complexity: $O(1)$ on average.

`igraph_sparsemat_fkeep` — Filters the elements of a sparse matrix.

```
igraph_error_t igraph_sparsemat_fkeep(
    igraph_sparsemat_t *A,
    igraph_integer_t (*fkeep)(igraph_integer_t, igraph_integer_t, igraph_real_t,
    void *other
);
```

This function can be used to filter the (non-zero) elements of a sparse matrix. For all entries, it calls the supplied function and depending on the return values either keeps, or deleted the element from the matrix.

Arguments:

- A*: The input matrix, in column-compressed format.
- fkeep*: The filter function. It must take four arguments: the first is an `igraph_integer_t`, the row index of the entry, the second is another `igraph_integer_t`, the column index. The third is `igraph_real_t`, the value of the entry. The fourth element is a `void` pointer, the *other* argument is passed here. The function must return an `int`. If this is zero, then the entry is deleted, otherwise it is kept.
- other*: A `void` pointer that is passed to the filtering function.

Returns:

Error code.

Time complexity: TODO.

`igraph_sparsemat_dropzeros` — Drops the zero elements from a sparse matrix.

```
igraph_error_t igraph_sparsemat_dropzeros(igraph_sparsemat_t *A);
```

As a result of matrix operations, some of the entries in a sparse matrix might be zero. This function removes these entries.

Arguments:

- A*: The input matrix, it must be in column-compressed format.

Returns:

Error code.

Time complexity: TODO.

`igraph_sparsemat_droptol` — Drops the almost zero elements from a sparse matrix.

```
igraph_error_t igraph_sparsemat_droptol(igraph_sparsemat_t *A, igraph_real_t tol);
```

This function is similar to `igraph_sparsemat_dropzeros()`, but it also drops entries that are closer to zero than the given tolerance threshold.

Arguments:

- A*: The input matrix, it must be in column-compressed format.
- tol*: Real number, giving the tolerance threshold.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_scale — Scales a sparse matrix.

```
igraph_error_t igraph_sparsemat_scale(igraph_sparsemat_t *A, igraph_real_t by),
```

Multiplies all elements of a sparse matrix, by the given scalar.

Arguments:

A: The input matrix.

by: The scaling factor.

Returns:

Error code.

Time complexity: $O(nz)$, the number of non-zero elements in the matrix.

igraph_sparsemat_permute — Permutes the rows and columns of a sparse matrix.

```
igraph_error_t igraph_sparsemat_permute(const igraph_sparsemat_t *A,  
                                         const igraph_vector_int_t *p,  
                                         const igraph_vector_int_t *q,  
                                         igraph_sparsemat_t *res);
```

Arguments:

A: The input matrix, it must be in column-compressed format.

p: Integer vector, giving the permutation of the rows.

q: Integer vector, the permutation of the columns.

res: Pointer to an uninitialized sparse matrix, the result is stored here.

Returns:

Error code.

Time complexity: $O(m+n+nz)$, the number of rows plus the number of columns plus the number of non-zero elements in the matrix.

igraph_sparsemat_transpose — Transposes a sparse matrix.

```
igraph_error_t igraph_sparsemat_transpose(  
    const igraph_sparsemat_t *A, igraph_sparsemat_t *res  
);
```


Arguments:

A: The input matrix, column-compressed or triple format.

res: Pointer to an uninitialized sparse matrix, the result is stored here.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_add — Sum of two sparse matrices.

```
igraph_error_t igraph_sparsemat_add(const igraph_sparsemat_t *A,
                                     const igraph_sparsemat_t *B,
                                     igraph_real_t alpha,
                                     igraph_real_t beta,
                                     igraph_sparsemat_t *res);
```

Arguments:

A: The first input matrix, in column-compressed format.

B: The second input matrix, in column-compressed format.

alpha: Real scalar, *A* is multiplied by *alpha* before the addition.

beta: Real scalar, *B* is multiplied by *beta* before the addition.

res: Pointer to an uninitialized sparse matrix, the result is stored here.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_multiply — Matrix multiplication.

```
igraph_error_t igraph_sparsemat_multiply(const igraph_sparsemat_t *A,
                                          const igraph_sparsemat_t *B,
                                          igraph_sparsemat_t *res);
```

Multiplies two sparse matrices.

Arguments:

A: The first input matrix (left hand side), in column-compressed format.

B: The second input matrix (right hand side), in column-compressed format.

res: Pointer to an uninitialized sparse matrix, the result is stored here.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_gaxpy — Matrix-vector product, added to another vector.

```
igraph_error_t igraph_sparsemat_gaxpy(const igraph_sparsemat_t *A,  
                                       const igraph_vector_t *x,  
                                       igraph_vector_t *res);
```

Arguments:

A: The input matrix, in column-compressed format.

x: The input vector, its size must match the number of columns in *A*.

res: This vector is added to the matrix-vector product and it is overwritten by the result.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_add_rows — Adds rows to a sparse matrix.

```
igraph_error_t igraph_sparsemat_add_rows(igraph_sparsemat_t *A, igraph_integer_t n);
```

The current matrix elements are retained and all elements in the new rows are zero.

Arguments:

A: The input matrix, in triplet or column-compressed format.

n: The number of rows to add.

Returns:

Error code.

Time complexity: $O(1)$.

igraph_sparsemat_add_cols — Adds columns to a sparse matrix.

```
igraph_error_t igraph_sparsemat_add_cols(igraph_sparsemat_t *A, igraph_integer_t n);
```

The current matrix elements are retained, and all elements in the new columns are zero.

Arguments:

- A*: The input matrix, in triplet or column-compressed format.
- n*: The number of columns to add.

Returns:

- Error code.
- Time complexity: TODO.

igraph_sparsemat_resize — Resizes a sparse matrix and clears all the elements.

```
igraph_error_t igraph_sparsemat_resize(igraph_sparsemat_t *A, igraph_integer_t nrow,  
                                       igraph_integer_t ncol, igraph_integer_t nzmax);
```

This function resizes a sparse matrix. The resized sparse matrix will become empty, even if it contained nonzero entries.

Arguments:

- A*: The initialized sparse matrix to resize.
- nrow*: The new number of rows.
- ncol*: The new number of columns.
- nzmax*: The new maximum number of elements.

Returns:

- Error code.
- Time complexity: $O(nzmax)$, the maximum number of non-zero elements.

igraph_sparsemat_sort — Sorts all elements of a sparse matrix by row and column indices.

```
igraph_error_t igraph_sparsemat_sort(const igraph_sparsemat_t *A,  
                                     igraph_sparsemat_t *sorted);
```

This function will sort the elements of a sparse matrix such that iterating over the entries will return them sorted by column indices; elements in the same column are then sorted by row indices.

Arguments:

- A*: A sparse matrix in either triplet or compressed form.
- sorted*: An uninitialized sparse matrix; the result will be returned here. The result will be in triplet form if the input was in triplet form, otherwise it will be in compressed form. Note that sorting is more efficient when the matrix is already in compressed form.

Returns:

Error code.

Time complexity: TODO

Operations on sparse matrix iterators

igraph_sparsemat_iterator_init — Initialize a sparse matrix iterator.

```
igraph_error_t igraph_sparsemat_iterator_init(
    igraph_sparsemat_iterator_t *it, const igraph_sparsemat_t *sparsemat
);
```

Arguments:

it: A pointer to an uninitialized sparse matrix iterator.

sparsemat: Pointer to the sparse matrix.

Returns:

Error code. This will always return IGRAPH_SUCCESS

Time complexity: $O(n)$, the number of columns of the sparse matrix.

igraph_sparsemat_iterator_reset — Reset a sparse matrix iterator to the first element.

```
igraph_error_t igraph_sparsemat_iterator_reset(igraph_sparsemat_iterator_t *it)
```

Arguments:

it: A pointer to the sparse matrix iterator.

Returns:

Error code. This will always return IGRAPH_SUCCESS

Time complexity: $O(n)$, the number of columns of the sparse matrix.

igraph_sparsemat_iterator_end — Query if the iterator is past the last element.

```
igraph_bool_t
igraph_sparsemat_iterator_end(const igraph_sparsemat_iterator_t *it);
```

Arguments:

it: A pointer to the sparse matrix iterator.

Returns:

true if the iterator is past the last element, false if it points to an element in a sparse matrix.

Time complexity: $O(1)$.

igraph_sparsemat_iterator_row — Return the row of the iterator.

```
igraph_integer_t igraph_sparsemat_iterator_row(const igraph_sparsemat_iterator_t
```

Arguments:

it: A pointer to the sparse matrix iterator.

Returns:

The row of the element at the current iterator position.

Time complexity: $O(1)$.

igraph_sparsemat_iterator_col — Return the column of the iterator.

```
igraph_integer_t igraph_sparsemat_iterator_col(const igraph_sparsemat_iterator_t
```

Arguments:

it: A pointer to the sparse matrix iterator.

Returns:

The column of the element at the current iterator position.

Time complexity: $O(1)$.

igraph_sparsemat_iterator_get — Return the element at the current iterator position.

```
igraph_real_t  
igraph_sparsemat_iterator_get(const igraph_sparsemat_iterator_t *it);
```

Arguments:

it: A pointer to the sparse matrix iterator.

Returns:

The value of the element at the current iterator position.

Time complexity: $O(1)$.

igraph_sparsemat_iterator_next — Let a sparse matrix iterator go to the next element.

```
igraph_integer_t igraph_sparsemat_iterator_next(igraph_sparsemat_iterator_t *it)
```

Arguments:

it: A pointer to the sparse matrix iterator.

Returns:

The position of the iterator in the element vector.

Time complexity: $O(n)$, the number of columns of the sparse matrix.

igraph_sparsemat_iterator_idx — Returns the element vector index of a sparse matrix iterator.

```
igraph_integer_t igraph_sparsemat_iterator_idx(const igraph_sparsemat_iterator_t *it)
```

Arguments:

it: A pointer to the sparse matrix iterator.

Returns:

The position of the iterator in the element vector.

Time complexity: $O(1)$.

Operations that change the internal representation

igraph_sparsemat_compress — Converts a sparse matrix to column-compressed format.

```
igraph_error_t igraph_sparsemat_compress(const igraph_sparsemat_t *A,
                                          igraph_sparsemat_t *res);
```

Converts a sparse matrix from triplet format to column-compressed format. Almost all sparse matrix operations require that the matrix is in column-compressed format.

Arguments:

A: The input matrix, it must be in triplet format.

res: Pointer to an uninitialized sparse matrix object, the compressed version of *A* is stored here.

Returns:

Error code.

Time complexity: $O(nz)$ where nz is the number of non-zero elements.

igraph_sparsemat_dupl — Removes duplicate elements from a sparse matrix.

```
igraph_error_t igraph_sparsemat_dupl(igraph_sparsemat_t *A);
```

It is possible that a column-compressed sparse matrix stores a single matrix entry in multiple pieces. The entry is then the sum of all its pieces. (Some functions create matrices like this.) This function eliminates the multiple pieces.

Arguments:

A: The input matrix, in column-compressed format.

Returns:

Error code.

Time complexity: TODO.

Decompositions and solving linear systems

igraph_sparsemat_symblu — Symbolic LU decomposition.

```
igraph_error_t igraph_sparsemat_symblu(igraph_integer_t order, const igraph_sparsemat_t *A,
                                       igraph_sparsemat_symbolic_t *dis);
```

LU decomposition of sparse matrices involves two steps, the first is calling this function, and then `igraph_sparsemat_lu()`.

Arguments:

order: The ordering to use: 0 means natural ordering, 1 means minimum degree ordering of $A + A'$, 2 is minimum degree ordering of $A'A$ after removing the dense rows from A , and 3 is the minimum degree ordering of $A'A$.

A: The input matrix, in column-compressed format.

dis: The result of the symbolic analysis is stored here. Once not needed anymore, it must be destroyed by calling `igraph_sparsemat_symbolic_destroy()`.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_symbqr — Symbolic QR decomposition.

```
igraph_error_t igraph_sparsemat_symbqr(igraph_integer_t order, const igraph_sparsemat_t *A,
                                       igraph_sparsemat_symbolic_t *dis);
```

QR decomposition of sparse matrices involves two steps, the first is calling this function, and then `igraph_sparsemat_qr()`.

Arguments:

order: The ordering to use: 0 means natural ordering, 1 means minimum degree ordering of $A + A'$, 2 is minimum degree ordering of $A'A$ after removing the dense rows from A , and 3 is the minimum degree ordering of $A'A$.

A: The input matrix, in column-compressed format.

dis: The result of the symbolic analysis is stored here. Once not needed anymore, it must be destroyed by calling `igraph_sparsemat_symbolic_destroy()`.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_lsolve — Solves a lower-triangular linear system.

```
igraph_error_t igraph_sparsemat_lsolve(const igraph_sparsemat_t *L,
                                       const igraph_vector_t *b,
                                       igraph_vector_t *res);
```

Solve the $Lx=b$ linear equation system, where the L coefficient matrix is square and lower-triangular, with a zero-free diagonal.

Arguments:

L: The input matrix, in column-compressed format.

b: The right hand side of the linear system.

res: An initialized vector, the result is stored here.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_ltsolve — Solves an upper-triangular linear system.


```
igraph_error_t igraph_sparsemat_ltsolve(const igraph_sparsemat_t *L,
                                         const igraph_vector_t *b,
                                         igraph_vector_t *res);
```

Solve the $Lx=b$ linear equation system, where the L matrix is square and lower-triangular, with a zero-free diagonal.

Arguments:

L: The input matrix, in column-compressed format.

b: The right hand side of the linear system.

res: An initialized vector, the result is stored here.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_usolve — Solves an upper-triangular linear system.

```
igraph_error_t igraph_sparsemat_usolve(const igraph_sparsemat_t *U,
                                         const igraph_vector_t *b,
                                         igraph_vector_t *res);
```

Solves the $Ux=b$ upper triangular system.

Arguments:

U: The input matrix, in column-compressed format.

b: The right hand side of the linear system.

res: An initialized vector, the result is stored here.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_utsolve — Solves a lower-triangular linear system.

```
igraph_error_t igraph_sparsemat_utsolve(const igraph_sparsemat_t *U,
                                         const igraph_vector_t *b,
                                         igraph_vector_t *res);
```

This is the same as `igraph_sparsemat_usolve()`, but $U'x=b$ is solved, where the apostrophe denotes the transpose.

Arguments:

- U*: The input matrix, in column-compressed format.
- b*: The right hand side of the linear system.
- res*: An initialized vector, the result is stored here.

Returns:

- Error code.
- Time complexity: TODO.

igraph_sparsemat_cholsol — Solves a symmetric linear system via Cholesky decomposition.

```
igraph_error_t igraph_sparsemat_cholsol(const igraph_sparsemat_t *A,
                                         const igraph_vector_t *b,
                                         igraph_vector_t *res,
                                         igraph_integer_t order);
```

Solve $Ax=b$, where A is a symmetric positive definite matrix.

Arguments:

- A*: The input matrix, in column-compressed format.
- v*: The right hand side.
- res*: An initialized vector, the result is stored here.
- order*: An integer giving the ordering method to use for the factorization. Zero is the natural ordering; if it is one, then the fill-reducing minimum-degree ordering of $A+A'$ is used.

Returns:

- Error code.
- Time complexity: TODO.

igraph_sparsemat_lusol — Solves a linear system via LU decomposition.

```
igraph_error_t igraph_sparsemat_lusol(const igraph_sparsemat_t *A,
                                       const igraph_vector_t *b,
                                       igraph_vector_t *res,
                                       igraph_integer_t order,
                                       igraph_real_t tol);
```

Solve $Ax=b$, via LU factorization of A .

Arguments:

- A*: The input matrix, in column-compressed format.

- b*: The right hand side of the equation.
- res*: An initialized vector, the result is stored here.
- order*: The ordering method to use, zero means the natural ordering, one means the fill-reducing minimum-degree ordering of $A+A'$, two means the ordering of $A'*A$, after removing the dense rows from A . Three means the ordering of $A'*A$.
- tol*: Real number, the tolerance limit to use for the numeric LU factorization.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_lu — LU decomposition of a sparse matrix.

```
igraph_error_t igraph_sparsemat_lu(const igraph_sparsemat_t *A,
                                   const igraph_sparsemat_symbolic_t *dis,
                                   igraph_sparsemat_numeric_t *din, double tol);
```

Performs numeric sparse LU decomposition of a matrix.

Arguments:

- A*: The input matrix, in column-compressed format.
- dis*: The symbolic analysis for LU decomposition, coming from a call to the `igraph_sparsemat_symlu()` function.
- din*: The numeric decomposition, the result is stored here. It can be used to solve linear systems with changing right hand side vectors, by calling `igraph_sparsemat_luresol()`. Once not needed any more, it must be destroyed by calling `igraph_sparsemat_symbolic_destroy()` on it.
- tol*: The tolerance for the numeric LU decomposition.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_qr — QR decomposition of a sparse matrix.

```
igraph_error_t igraph_sparsemat_qr(const igraph_sparsemat_t *A,
                                   const igraph_sparsemat_symbolic_t *dis,
                                   igraph_sparsemat_numeric_t *din);
```

Numeric QR decomposition of a sparse matrix.

Arguments:

- A*: The input matrix, in column-compressed format.

dis: The result of the symbolic QR analysis, from the function `igraph_sparsemat_sym-bqr()`.

din: The result of the decomposition is stored here, it can be used to solve many linear systems with the same coefficient matrix and changing right hand sides, using the `igraph_sparsemat_qrresol()` function. Once not needed any more, one should call `igraph_sparsemat_numeric_destroy()` on it to free the allocated memory.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_luresol — Solves a linear system using a precomputed LU decomposition.

```
igraph_error_t igraph_sparsemat_luresol(const igraph_sparsemat_symbolic_t *dis,
                                         const igraph_sparsemat_numeric_t *din,
                                         const igraph_vector_t *b,
                                         igraph_vector_t *res);
```

Uses the LU decomposition of a matrix to solve linear systems.

Arguments:

dis: The symbolic analysis of the coefficient matrix, the result of `igraph_sparsemat_sym-blu()`.

din: The LU decomposition, the result of a call to `igraph_sparsemat_lu()`.

b: A vector that defines the right hand side of the linear equation system.

res: An initialized vector, the solution of the linear system is stored here.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_qrresol — Solves a linear system using a precomputed QR decomposition.

```
igraph_error_t igraph_sparsemat_qrresol(const igraph_sparsemat_symbolic_t *dis,
                                         const igraph_sparsemat_numeric_t *din,
                                         const igraph_vector_t *b,
                                         igraph_vector_t *res);
```

Solves a linear system using a QR decomposition of its coefficient matrix.

Arguments:

dis: Symbolic analysis of the coefficient matrix, the result of `igraph_sparsemat_sym-bqr()`.

din: The QR decomposition of the coefficient matrix, the result of `igraph_sparsemat_qr()`.

b: Vector, giving the right hand side of the linear equation system.

res: An initialized vector, the solution is stored here. It is resized as needed.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_symbolic_destroy — Deallocates memory after a symbolic decomposition.

```
void igraph_sparsemat_symbolic_destroy(igraph_sparsemat_symbolic_t *dis);
```

Frees the memory allocated by `igraph_sparsemat_symbqr()` or `igraph_sparsemat_symb lu()`.

Arguments:

dis: The symbolic analysis.

Time complexity: O(1).

igraph_sparsemat_numeric_destroy — Deallocates memory after a numeric decomposition.

```
void igraph_sparsemat_numeric_destroy(igraph_sparsemat_numeric_t *din);
```

Frees the memory allocated by `igraph_sparsemat_qr()` or `igraph_sparsemat_lu()`.

Arguments:

din: The LU or QR decomposition.

Time complexity: O(1).

Eigenvalues and eigenvectors

igraph_sparsemat_arpack_rssolve — Eigenvalues and eigenvectors of a symmetric sparse matrix via ARPACK.

```
igraph_error_t igraph_sparsemat_arpack_rssolve(const igraph_sparsemat_t *A,
                                                igraph_arpack_options_t *options,
                                                igraph_arpack_storage_t *storage,
                                                igraph_vector_t *values,
                                                igraph_matrix_t *vectors,
                                                igraph_sparsemat_solve_t solvemethod);
```

Arguments:

<i>The:</i>	input matrix, must be column-compressed.	
<i>options:</i>	It is passed to <code>igraph_arnpack_rssolve()</code> . Supply <code>NULL</code> here to use the defaults. See <code>igraph_arnpack_options_t</code> for the details. If mode is 1, then ARPACK uses regular mode, if mode is 3, then shift and invert mode is used and the <code>sigma</code> structure member defines the shift.	
<i>storage:</i>	Storage for ARPACK. See <code>igraph_arnpack_rssolve()</code> and <code>igraph_arnpack_storage_t</code> for details.	
<i>values:</i>	An initialized vector or a null pointer, the eigenvalues are stored here.	
<i>vectors:</i>	An initialised matrix, or a null pointer, the eigenvectors are stored here, in the columns.	
<i>solvemethod:</i>	The method to solve the linear system, if mode is 3, i.e. the shift and invert mode is used. Possible values:	
	IGRAPH_SPARSE-MAT_SOLVE_LU	The linear system is solved using LU decomposition.
	IGRAPH_SPARSE-MAT_SOLVE_QR	The linear system is solved using QR decomposition.

Returns:

Error code.

Time complexity: TODO.

igraph_sparsemat_arnpack_rnsolve — Eigenvalues and eigenvectors of a nonsymmetric sparse matrix via ARPACK.

```
igraph_error_t igraph_sparsemat_arnpack_rnsolve(const igraph_sparsemat_t *A,
                                                igraph_arnpack_options_t *options,
                                                igraph_arnpack_storage_t *storage,
                                                igraph_matrix_t *values,
                                                igraph_matrix_t *vectors);
```

Eigenvalues and/or eigenvectors of a nonsymmetric sparse matrix.

Arguments:

<i>A:</i>	The input matrix, in column-compressed mode.	
<i>options:</i>	ARPACK options, it is passed to <code>igraph_arnpack_rnsolve()</code> . Supply <code>NULL</code> here to use the defaults. See also <code>igraph_arnpack_options_t</code> for details.	
<i>storage:</i>	Storage for ARPACK, this is passed to <code>igraph_arnpack_rnsolve()</code> . See <code>igraph_arnpack_storage_t</code> for details.	
<i>values:</i>	An initialized matrix, or a null pointer. If not a null pointer, then the eigenvalues are stored here, the first column is the real part, the second column is the imaginary part.	
<i>vectors:</i>	An initialized matrix, or a null pointer. If not a null pointer, then the eigenvectors are stored here, please see <code>igraph_arnpack_rnsolve()</code> for the format.	

Returns:

Error code.

Time complexity: TODO.

Conversion to other data types

igraph_sparsemat — Creates an igraph graph from a sparse matrix.

```
igraph_error_t igraph_sparsemat(igraph_t *graph, const igraph_sparsemat_t *A,
                                igraph_bool_t directed);
```

One edge is created for each non-zero entry in the matrix. If you have a symmetric matrix, and want to create an undirected graph, then delete the entries in the upper diagonal first, or call `igraph_simplify()` on the result graph to eliminate the multiple edges.

Arguments:

graph: Pointer to an uninitialized `igraph_t` object, the graph is stored here.

A: The input matrix, in triplet or column-compressed format.

directed: Boolean scalar, whether to create a directed graph.

Returns:

Error code.

Time complexity: TODO.

igraph_matrix_as_sparsemat — Converts a dense matrix to a sparse matrix.

```
igraph_error_t igraph_matrix_as_sparsemat(igraph_sparsemat_t *res,
                                           const igraph_matrix_t *mat,
                                           igraph_real_t tol);
```

Arguments:

res: An uninitialized sparse matrix, the result is stored here.

mat: The dense input matrix.

tol: Real scalar, the tolerance. Values closer than *tol* to zero are considered as zero, and will not be included in the sparse matrix.

Returns:

Error code.

Time complexity: $O(mn)$, the number of elements in the dense matrix.

igraph_sparsemat_as_matrix — Converts a sparse matrix to a dense matrix.

```
igraph_error_t igraph_sparsemat_as_matrix(igraph_matrix_t *res,
                                          const igraph_sparsemat_t *spmat);
```

Arguments:

res: Pointer to an initialized matrix, the result is stored here. It will be resized to the required size.

spmat: The input sparse matrix, in triplet or column-compressed format.

Returns:

Error code.

Time complexity: $O(mn)$, the number of elements in the dense matrix.

Writing to a file, or to the screen

igraph_sparsemat_print — Prints a sparse matrix to a file.

```
igraph_error_t igraph_sparsemat_print(const igraph_sparsemat_t *A,
                                       FILE *ostream);
```

Only the non-zero entries are printed. This function serves more as a debugging utility, as currently there is no function that could read back the printed matrix from the file.

Arguments:

A: The input matrix, triplet or column-compressed format.

ostream: The stream to print it to.

Returns:

Error code.

Time complexity: $O(nz)$ for triplet matrices, $O(n+nz)$ for column-compressed matrices. nz is the number of non-zero elements, n is the number columns in the matrix.

Deprecated functions

igraph_sparsemat_copy — Copies a sparse matrix (deprecated alias).


```
igraph_error_t igraph_sparsemat_copy(
    igraph_sparsemat_t *to, const igraph_sparsemat_t *from
);
```

Warning

Deprecated since version 0.10. Please do not use this function in new code; use `igraph_sparsemat_init_copy()` instead.

igraph_sparsemat_diag — Creates a sparse diagonal matrix (deprecated alias).

```
igraph_error_t igraph_sparsemat_diag(
    igraph_sparsemat_t *A, igraph_integer_t nzmax, const igraph_vector_t *values,
    igraph_bool_t compress
);
```

Warning

Deprecated since version 0.10. Please do not use this function in new code; use `igraph_sparsemat_init_diag()` instead.

igraph_sparsemat_eye — Creates a sparse identity matrix (deprecated alias).

```
igraph_error_t igraph_sparsemat_eye(
    igraph_sparsemat_t *A, igraph_integer_t n, igraph_integer_t nzmax,
    igraph_real_t value, igraph_bool_t compress
);
```

Warning

Deprecated since version 0.10. Please do not use this function in new code; use `igraph_sparsemat_init_eye()` instead.

Stacks

igraph_stack_init — Initializes a stack.

```
igraph_error_t igraph_stack_init(igraph_stack_t* s, igraph_integer_t size);
```

The initialized stack is always empty.

Arguments:

s: Pointer to an uninitialized stack.

size: The number of elements to allocate memory for.

Returns:

Error code.

Time complexity: $O(size)$.

igraph_stack_destroy — Destroys a stack object.

```
void igraph_stack_destroy(igraph_stack_t* s);
```

Deallocate the memory used for a stack. It is possible to reinitialize a destroyed stack again by `igraph_stack_init()`.

Arguments:

s: The stack to destroy.

Time complexity: $O(1)$.

igraph_stack_reserve — Reserve memory.

```
igraph_error_t igraph_stack_reserve(igraph_stack_t* s, igraph_integer_t capacity);
```

Reserve memory for future use. The actual size of the stack is unchanged.

Arguments:

s: The stack object.

size: The number of elements to reserve memory for. If it is not bigger than the current size then nothing happens.

Returns:

Error code.

Time complexity: should be around $O(n)$, the new allocated size of the stack.

igraph_stack_empty — Decides whether a stack object is empty.

```
igraph_bool_t igraph_stack_empty(igraph_stack_t* s);
```

Arguments:

s: The stack object.

Returns:

Boolean, true if the stack is empty, false otherwise.

Time complexity: $O(1)$.

igraph_stack_size — Returns the number of elements in a stack.

```
igraph_integer_t igraph_stack_size(const igraph_stack_t* s);
```

Arguments:

s: The stack object.

Returns:

The number of elements in the stack.

Time complexity: $O(1)$.

igraph_stack_clear — Removes all elements from a stack.

```
void igraph_stack_clear(igraph_stack_t* s);
```

Arguments:

s: The stack object.

Time complexity: $O(1)$.

igraph_stack_push — Places an element on the top of a stack.

```
igraph_error_t igraph_stack_push(igraph_stack_t* s, igraph_real_t elem);
```

The capacity of the stack is increased, if needed.

Arguments:

s: The stack object.

elem: The element to push.

Returns:

Error code.

Time complexity: $O(1)$ if no reallocation is needed, $O(n)$ otherwise, but it is ensured that n push operations are performed in $O(n)$ time.

igraph_stack_pop — Removes and returns an element from the top of a stack.

```
igraph_real_t igraph_stack_pop(igraph_stack_t* s);
```

The stack must contain at least one element, call `igraph_stack_empty()` to make sure of this.

Arguments:

s: The stack object.

Returns:

The removed top element.

Time complexity: $O(1)$.

igraph_stack_top — Query top element.

```
igraph_real_t igraph_stack_top(const igraph_stack_t* s);
```

Returns the top element of the stack, without removing it. The stack must be non-empty.

Arguments:

s: The stack.

Returns:

The top element.

Time complexity: $O(1)$.

Double-ended queues

This is the classic data type of the double ended queue. Most of the time it is used if a First-In-First-Out (FIFO) behavior is needed. See the operations below.

Example 7.10. File `examples/simple/dqueue.c`

igraph_dqueue_init — Initialize a double ended queue (deque).

```
igraph_error_t igraph_dqueue_init(igraph_dqueue_t* q, igraph_integer_t capacity)
```

The queue will be always empty.

Arguments:

q: Pointer to an uninitialized deque.
capacity: How many elements to allocate memory for.

Returns:

Error code.
Time complexity: $O(\text{capacity})$.

igraph_dqueue_destroy — Destroy a double ended queue.

```
void igraph_dqueue_destroy(igraph_dqueue_t* q);
```

Arguments:

q: The queue to destroy
Time complexity: $O(1)$.

igraph_dqueue_empty — Decide whether the queue is empty.

```
igraph_bool_t igraph_dqueue_empty(const igraph_dqueue_t* q);
```

Arguments:

q: The queue.

Returns:

Boolean, true if *q* contains at least one element, false otherwise.
Time complexity: $O(1)$.

igraph_dqueue_full — Check whether the queue is full.

```
igraph_bool_t igraph_dqueue_full(igraph_dqueue_t* q);
```

If a queue is full the next `igraph_dqueue_push()` operation will allocate more memory.

Arguments:

q: The queue.

Returns:

true if q is full, false otherwise.

Time complexity: $O(1)$.

igraph_dqueue_clear — Remove all elements from the queue.

```
void igraph_dqueue_clear(igraph_dqueue_t* q);
```

Arguments:

q : The queue.

Time complexity: $O(1)$.

igraph_dqueue_size — Number of elements in the queue.

```
igraph_integer_t igraph_dqueue_size(const igraph_dqueue_t* q);
```

Arguments:

q : The queue.

Returns:

Integer, the number of elements currently in the queue.

Time complexity: $O(1)$.

igraph_dqueue_head — Head of the queue.

```
igraph_real_t igraph_dqueue_head(const igraph_dqueue_t* q);
```

The queue must contain at least one element.

Arguments:

q : The queue.

Returns:

The first element in the queue.

Time complexity: $O(1)$.

igraph_dqueue_back — Tail of the queue.

```
igraph_real_t igraph_dqueue_back(const igraph_dqueue_t* q);
```

The queue must contain at least one element.

Arguments:

q: The queue.

Returns:

The last element in the queue.

Time complexity: $O(1)$.

igraph_dqueue_pop — Remove the head.

```
igraph_real_t igraph_dqueue_pop(igraph_dqueue_t* q);
```

Removes and returns the first element in the queue. The queue must be non-empty.

Arguments:

q: The input queue.

Returns:

The first element in the queue.

Time complexity: $O(1)$.

igraph_dqueue_pop_back — Remove the tail

```
igraph_real_t igraph_dqueue_pop_back(igraph_dqueue_t* q);
```

Removes and returns the last element in the queue. The queue must be non-empty.

Arguments:

q: The queue.

Returns:

The last element in the queue.

Time complexity: $O(1)$.

igraph_dqueue_push — Appends an element.

```
igraph_error_t igraph_dqueue_push(igraph_dqueue_t* q, igraph_real_t elem);
```

Append an element to the end of the queue.

Arguments:

q: The queue.

elem: The element to append.

Returns:

Error code.

Time complexity: $O(1)$ if no memory allocation is needed, $O(n)$, the number of elements in the queue otherwise. But note that by allocating always twice as much memory as the current size of the queue we ensure that n push operations can always be done in at most $O(n)$ time. (Assuming memory allocation is at most linear.)

Maximum and minimum heaps

igraph_heap_init — Initializes an empty heap object.

```
igraph_error_t igraph_heap_init(igraph_heap_t* h, igraph_integer_t capacity);
```

Creates an *empty* heap, and also allocates memory for some elements.

Arguments:

h: Pointer to an uninitialized heap object.

capacity: Number of elements to allocate memory for.

Returns:

Error code.

Time complexity: $O(\text{alloc_size})$, assuming memory allocation is a linear operation.

igraph_heap_init_array — Build a heap from an array.

```
igraph_error_t igraph_heap_init_array(igraph_heap_t *h, igraph_real_t* data, ig
```

Initializes a heap object from an array. The heap is also built of course (constructor).

Arguments:

h: Pointer to an uninitialized heap object.

data: Pointer to an array of base data type.

len: The length of the array at *data*.

Returns:

Error code.

Time complexity: $O(n)$, the number of elements in the heap.

igraph_heap_destroy — Destroys an initialized heap object.

```
void igraph_heap_destroy(igraph_heap_t* h);
```

Arguments:

h: The heap object.

Time complexity: $O(1)$.

igraph_heap_clear — Removes all elements from a heap.

```
void igraph_heap_clear(igraph_heap_t* h);
```

This function simply sets the size of the heap to zero, it does not free any allocated memory. For that you have to call `igraph_heap_destroy()`.

Arguments:

h: The heap object.

Time complexity: $O(1)$.

igraph_heap_empty — Decides whether a heap object is empty.

```
igraph_bool_t igraph_heap_empty(const igraph_heap_t* h);
```

Arguments:

h: The heap object.

Returns:

`true` if the heap is empty, `false` otherwise.

Time complexity: $O(1)$.

igraph_heap_push — Add an element.

```
igraph_error_t igraph_heap_push(igraph_heap_t* h, igraph_real_t elem);
```

Adds an element to the heap.

Arguments:

h: The heap object.

elem: The element to add.

Returns:

Error code.

Time complexity: $O(\log n)$, n is the number of elements in the heap if no reallocation is needed, $O(n)$ otherwise. It is ensured that n push operations are performed in $O(n \log n)$ time.

igraph_heap_top — Top element.

```
igraph_real_t igraph_heap_top(const igraph_heap_t* h);
```

For maximum heaps this is the largest, for minimum heaps the smallest element of the heap.

Arguments:

h: The heap object.

Returns:

The top element.

Time complexity: $O(1)$.

igraph_heap_delete_top — Removes and returns the top element.

```
igraph_real_t igraph_heap_delete_top(igraph_heap_t* h);
```

Removes and returns the top element of the heap. For maximum heaps this is the largest, for minimum heaps the smallest element.

Arguments:

h: The heap object.

Returns:

The top element.

Time complexity: $O(\log n)$, n is the number of elements in the heap.

igraph_heap_size — Number of elements in the heap.

```
igraph_integer_t igraph_heap_size(const igraph_heap_t* h);
```

Gives the number of elements in a heap.

Arguments:

h: The heap object.

Returns:

The number of elements in the heap.

Time complexity: $O(1)$.

igraph_heap_reserve — Reserves memory for a heap.

```
igraph_error_t igraph_heap_reserve(igraph_heap_t* h, igraph_integer_t capacity)
```

Allocates memory for future use. The size of the heap is unchanged. If the heap is larger than the *capacity* parameter then nothing happens.

Arguments:

h: The heap object.

capacity: The number of elements to allocate memory for.

Returns:

Error code.

Time complexity: $O(capacity)$ if *capacity* is larger than the current number of elements. $O(1)$ otherwise.

String vectors

The `igraph_strvector_t` type is a vector of null-terminated strings. It is used internally for storing graph attribute names as well as string attributes in the C attribute handler.

This container automatically manages the memory of its elements. The strings within an `igraph_strvector_t` should be considered constant, and not modified directly. Functions that add new elements always make copies of the string passed to them.

Example 7.11. File `examples/simple/igraph_strvector.c`

igraph_strvector_init — Initializes a string vector.

```
igraph_error_t igraph_strvector_init(igraph_strvector_t *sv, igraph_integer_t s
```

Reserves memory for the string vector, a string vector must be first initialized before calling other functions on it. All elements of the string vector are set to the empty string.

Arguments:

sv: Pointer to an initialized string vector.

len: The (initial) length of the string vector.

Returns:

Error code.

Time complexity: $O(len)$.

igraph_strvector_init_copy — Initialization by copying.

```
igraph_error_t igraph_strvector_init_copy(igraph_strvector_t *to,
                                           const igraph_strvector_t *from);
```

Initializes a string vector by copying another string vector.

Arguments:

to: Pointer to an uninitialized string vector.

from: The other string vector, to be copied.

Returns:

Error code.

Time complexity: $O(l)$, the total length of the strings in *from*.

igraph_strvector_destroy — Frees the memory allocated for the string vector.

```
void igraph_strvector_destroy(igraph_strvector_t *sv);
```

Destroy a string vector. It may be reinitialized with `igraph_strvector_init()` later.

Arguments:

sv: The string vector.

Time complexity: $O(l)$, the total length of the strings, maybe less depending on the memory manager.

STR — Indexing string vectors.

```
#define STR(sv,i)
```

This is a macro that allows to query the elements of a string vector, just like `igraph_strvector_get()`, but without the overhead of a function call. Note this macro cannot be used to set an element. Use `igraph_strvector_set()` to set an element instead.

Arguments:

sv: The string vector

i: The the index of the element.

Returns:

The element at position *i*.

Time complexity: $O(1)$.

igraph_strvector_get — Retrieves an element of the string vector.

```
const char* igraph_strvector_get(const igraph_strvector_t *sv, igraph_integer_t
```

Query an element of a string vector. See also the `STR` macro for an easier way.

Arguments:

sv: The input string vector.

idx: The index of the element to query.

Time complexity: $O(1)$.

igraph_strvector_set — Takes elements at given positions from a string vector.

```
igraph_error_t igraph_strvector_index(const igraph_strvector_t *sv,  
                                       igraph_strvector_t *newv,  
                                       const igraph_vector_int_t *idx);
```

Arguments:

sv: The string vector.

newv: An initialized string vector, it will be resized as needed.

idx: An integer vector of indices to take from *sv*.

Returns:

Error code.

igraph_strvector_set_len — Sets an element of the string vector given a buffer and its size.

```
igraph_error_t igraph_strvector_set_len(igraph_strvector_t *sv, igraph_integer_t  
                                       const char *value, size_t len);
```

This is almost the same as `igraph_strvector_set`, but the new value is not a zero terminated string, but its length is given.

Arguments:

sv: The string vector.
idx: The position to set.
value: The new value.
len: The length of the new value.

Returns:

Error code.

Time complexity: $O(l)$, the length of the new string. Maybe more, depending on the memory management, if reallocation is needed.

igraph_strvector_push_back — Adds an element to the back of a string vector.

```
igraph_error_t igraph_strvector_push_back(igraph_strvector_t *sv, const char *v)
```

Arguments:

sv: The string vector.
value: The string to add; it will be copied.

Returns:

Error code.

Time complexity: $O(n+l)$, n is the total number of strings, l is the length of the new string.

igraph_strvector_push_back_len — Adds a string of the given length to the back of a string vector.

```
igraph_error_t igraph_strvector_push_back_len(
```

```
igraph_strvector_t *sv,  
const char *value, igraph_integer_t len);
```

Arguments:

sv: The string vector.
value: The start of the string to add. At most *len* characters will be copied.
len: The length of the string.

Returns:

Error code.

Time complexity: $O(n+l)$, n is the total number of strings, l is the length of the new string.

igraph_strvector_remove — Removes a single element from a string vector.

```
void igraph_strvector_remove(igraph_strvector_t *sv, igraph_integer_t elem);
```

The string will be one shorter.

Arguments:

sv: The string vector.
elem: The index of the element to remove.

Time complexity: $O(n)$, the length of the string.

igraph_strvector_remove_section — Removes a section from a string vector.

```
void igraph_strvector_remove_section(  
    igraph_strvector_t *sv, igraph_integer_t from, igraph_integer_t to);
```

This function removes the range [*from*, *to*) from the string vector.

Arguments:

sv: The string vector.
from: The position of the first element to remove.
to: The position of the first element *not* to remove.

igraph_strvector_append — Concatenates two string vectors.

```
igraph_error_t igraph_strvector_append(igraph_strvector_t *to,  
                                       const igraph_strvector_t *from);
```

Appends the contents of the *from* vector to the *to* vector. If the *from* vector is no longer needed after this operation, use `igraph_strvector_merge()` for better performance.

Arguments:

to: The first string vector, the result is stored here.

from: The second string vector, it is kept unchanged.

Returns:

Error code.

See also:

`igraph_strvector_merge()`

Time complexity: $O(n+l_2)$, n is the number of strings in the new string vector, l_2 is the total length of strings in the *from* string vector.

igraph_strvector_merge — Moves the contents of a string vector to the end of another.

```
igraph_error_t igraph_strvector_merge(igraph_strvector_t *to, igraph_strvector_t *from);
```

Transfers the contents of the *from* vector to the end of *to*, clearing *from* in the process. If this operation fails, both vectors are left intact. This function does not copy or reallocate individual strings, therefore it performs better than `igraph_strvector_append()`.

Arguments:

to: The target vector. The contents of *from* will be appended to it.

from: The source vector. It will be cleared.

Returns:

Error code.

See also:

`igraph_strvector_append()`

Time complexity: $O(l_2)$ if *to* has sufficient capacity, $O(2*l_1+l_2)$ otherwise, where l_1 and l_2 are the lengths of *to* and *from* respectively.

igraph_strvector_clear — Removes all elements from a string vector.


```
void igraph_strvector_clear(igraph_strvector_t *sv);
```

After this operation the string vector will be empty.

Arguments:

sv: The string vector.

Time complexity: $O(l)$, the total length of strings, maybe less, depending on the memory manager.

igraph_strvector_resize — Resizes a string vector.

```
igraph_error_t igraph_strvector_resize(igraph_strvector_t *sv, igraph_integer_t
```

If the new size is bigger then empty strings are added, if it is smaller then the unneeded elements are removed.

Arguments:

sv: The string vector.

newsize: The new size.

Returns:

Error code.

Time complexity: $O(n)$, the number of strings if the vector is made bigger, $O(l)$, the total length of the deleted strings if it is made smaller, maybe less, depending on memory management.

igraph_strvector_reserve — Reserves memory for a string vector.

```
igraph_error_t igraph_strvector_reserve(igraph_strvector_t *sv, igraph_integer_t
```

igraph string vectors are flexible, they can grow and shrink. Growing however occasionally needs the data in the vector to be copied. In order to avoid this, you can call this function to reserve space for future growth of the vector.

Note that this function does *not* change the size of the string vector. Let us see a small example to clarify things: if you reserve space for 100 strings and the size of your vector was (and still is) 60, then you can surely add additional 40 strings to your vector before it will be copied.

Arguments:

sv: The string vector object.

capacity: The new *allocated* size of the string vector.

Returns:

Error code: IGRAPH_ENOMEM if there is not enough memory.

Time complexity: operating system dependent, should be around $O(n)$, n is the new allocated size of the vector.

igraph_strvector_resize_min — Deallocates the unused memory of a string vector.

```
void igraph_strvector_resize_min(igraph_strvector_t *sv);
```

This function attempts to deallocate the unused reserved storage of a string vector. If it succeeds, `igraph_strvector_size()` and `igraph_strvector_capacity()` will be the same. The data in the string vector is always preserved, even if deallocation is not successful.

Arguments:

sv: The string vector.

Time complexity: Operating system dependent, at most $O(n)$.

igraph_strvector_size — Returns the size of a string vector.

```
igraph_integer_t igraph_strvector_size(const igraph_strvector_t *sv);
```

Arguments:

sv: The string vector.

Returns:

The length of the string vector.

Time complexity: $O(1)$.

igraph_strvector_capacity — Returns the capacity of a string vector.

```
igraph_integer_t igraph_strvector_capacity(const igraph_strvector_t *sv);
```

Arguments:

sv: The string vector.

Returns:

The capacity of the string vector.

Time complexity: $O(1)$.

Deprecated functions

igraph_strvector_copy — Initialization by copying (deprecated alias).

```
igraph_error_t igraph_strvector_copy(igraph_strvector_t *to,  
                                     const igraph_strvector_t *from);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_strvector_init_copy()` instead.

igraph_strvector_add — Adds an element to the back of a string vector (deprecated alias).

```
igraph_error_t igraph_strvector_add(igraph_strvector_t *sv, const char *value);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_strvector_push_back()` instead.

igraph_strvector_set2 — Sets an element of the string vector given a buffer and its size (deprecated alias).

```
igraph_error_t igraph_strvector_set2(  
    igraph_strvector_t *sv, igraph_integer_t idx, const char *value, size_t len  
);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_strvector_set_len()` instead.

Lists of vectors, matrices and graphs

About igraph_vector_list_t objects

The `igraph_vector_list_t` data type is essentially a list of `igraph_vector_t` objects with automatic memory management. It is something similar to (but much simpler than) the `vector` template in the C++ standard library where the elements are vectors themselves.

There are multiple variants of `igraph_vector_list_t`; the basic variant stores vectors of doubles (i.e. each item is an `igraph_vector_t`), but there is also `igraph_vector_int_list_t` for integers (where each item is an `igraph_vector_int_t`), `igraph_matrix_list_t` for matrices of doubles and so on. The following list summarizes the variants that are currently available in the library:

- `igraph_vector_list_t` for lists of vectors of floating-point numbers (`igraph_vector_t`)
- `igraph_vector_int_list_t` for lists of integer vectors (`igraph_vector_int_t`)
- `igraph_matrix_list_t` for lists of matrices of floating-point numbers (`igraph_matrix_t`)
- `igraph_graph_list_t` for lists of graphs (`igraph_t`)

Lists of vectors are used in **igraph** in many cases, e.g., when returning lists of paths, cliques or vertex sets. Functions that expect or return a list of numeric vectors typically use `igraph_vector_list_t` or `igraph_vector_int_list_t` to achieve this. Lists of integer vectors are used when the vectors in the list are supposed to hold vertex or edge identifiers, while lists of floating-point vectors are used when the vectors are expected to hold fractional numbers or infinities.

The elements in an `igraph_vector_list_t` object and its variants are indexed from zero, we follow the usual C convention here.

Almost all of the functions described below for `igraph_vector_list_t` also exist for all the other vector list variants. These variants are not documented separately; you can simply replace `vector_list` with, say, `vector_int_list` if you need a function for another variant. For instance, to initialize a list of integer vectors, you need to use `igraph_vector_int_list_init()` and not `igraph_vector_list_init()`.

Before diving into a detailed description of the functions related to lists of vectors, we must also talk about the *ownership* rules of these objects. The most important rule is that the vectors in the list are owned by the list itself, meaning that the user is *not* responsible for allocating memory for the vectors or for freeing the memory associated to the vectors. It is the responsibility of the list to allocate and initialize the vectors when new items are created in the list, and it is also the responsibility of the list to destroy the items when they are removed from the list without passing on their ownership to the user. As a consequence, the list may not contain "uninitialized" or "null" items; each item is initialized when it comes to existence. If you create a list containing one million vectors, you are not only allocating memory for one million `igraph_vector_t` object but you are also initializing one million vectors. Also, if you have a list containing one million vectors and you clear the list by calling `igraph_vector_list_clear()`, the list will implicitly destroy these lists, and any pointers that you may hold to the items become invalid at once.

Speaking about pointers, the typical way of working with vectors in a list is to obtain a pointer to one of the items via the `igraph_vector_list_get_ptr()` method and then passing this pointer onwards to functions that manipulate `igraph_vector_t` objects. However, note that the pointers are *ephemeral* in the sense that they may be invalidated any time when the list is modified because a modification may involve the re-allocation of the internal storage of the list if more space is needed, and the pointers that you obtained will not follow the reallocation. This limitation does not appear often in real-world usage of `igraph_vector_list_t` and in general, the advantages of the automatic memory management outweigh this limitation.

Constructors and destructors

`igraph_vector_list_t` objects have to be initialized before using them, this is analogous to calling a constructor on them. `igraph_vector_list_init()` is the basic constructor; it creates a list of the given length and also initializes each vector in the newly created list to zero length.

If an `igraph_vector_list_t` object is not needed any more, it should be destroyed to free its allocated memory by calling the `igraph_vector_list_t` destructor, `igraph_vector_list_destroy()`. Calling the destructor also destroys all the vectors inside the vector list due to the own-

ership rules. If you want to keep a few of the vectors in the vector list, you need to copy them with `igraph_vector_init_copy()` or `igraph_vector_update()`, or you need to remove them from the list and take ownership by calling `igraph_vector_list_pop_back()`, `igraph_vector_list_remove()` or `igraph_vector_list_remove_fast()`.

igraph_vector_list_init — Initializes a list of vectors (constructor).

```
igraph_error_t igraph_vector_list_init(igraph_vector_list_t* v, igraph_integer_t
```

This function constructs a list of vectors of the given size, and initializes each vector in the newly created list to become an empty vector.

Vector objects initialized by this function are *owned* by the list, and they will be destroyed automatically when the list is destroyed with `igraph_vector_list_destroy()`.

Arguments:

v: Pointer to a not yet initialized list of vectors.

size: The size of the list.

Returns:

error code: `IGRAPH_ENOMEM` if there is not enough memory.

Time complexity: operating system dependent, the amount of “time” required to allocate $O(n)$ elements and initialize the corresponding vectors; n is the number of elements.

igraph_vector_list_destroy — Destroys a list of vectors object.

```
void igraph_vector_list_destroy(igraph_vector_list_t* v);
```

All lists initialized by `igraph_vector_list_init()` should be properly destroyed by this function. A destroyed list of vectors needs to be reinitialized by `igraph_vector_list_init()` if you want to use it again.

Vectors that are in the list when it is destroyed are also destroyed implicitly.

Arguments:

v: Pointer to the (previously initialized) list object to destroy.

Time complexity: operating system dependent.

Accessing elements

Elements of a vector list may be accessed with the `igraph_vector_list_get_ptr()` function. The function returns a *pointer* to the vector with a given index inside the list, and you may then pass this pointer onwards to other functions that can query or manipulate vectors. The pointer itself is guaranteed to stay valid as long as the list itself is not modified; however, *any* modification to the

list will invalidate the pointer, even modifications that are seemingly unrelated to the vector that the pointer points to (such as adding a new vector at the end of the list). This is because the list data structure may be forced to re-allocate its internal storage if a new element does not fit into the already allocated space, and there are no guarantees that the re-allocated block remains at the same memory location (typically it gets moved elsewhere).

Note that the standard `VECTOR` macro that works for ordinary vectors does not work for lists of vectors to access the *i*-th element (but of course you can use it to index into an existing vector that you retrieved from the vector list with `igraph_vector_list_get_ptr()`). This is because the macro notation would allow one to overwrite the vector in the list with another one without the list knowing about it, so the list would not be able to destroy the vector that was overwritten by a new one.

`igraph_vector_list_tail_ptr()` returns a pointer to the last vector in the list, or `NULL` if the list is empty. There is no `igraph_vector_list_head_ptr()`, however, as it is easy to write `igraph_vector_list_get_ptr(v, 0)` instead.

`igraph_vector_list_get_ptr` — Retrieve the address of a vector in the vector list.

```
igraph_vector_t* igraph_vector_list_get_ptr(const igraph_vector_list_t* v, igraph_int_t pos);
```

Arguments:

v: The list object.

pos: The position of the vector in the list. The position of the first vector is zero.

Returns:

A pointer to the vector. It remains valid as long as the underlying list of vectors is not modified.

Time complexity: $O(1)$.

`igraph_vector_list_tail_ptr` — Retrieve the address of the last vector in the vector list.

```
igraph_vector_t* igraph_vector_list_tail_ptr(const igraph_vector_list_t *v);
```

Arguments:

v: The list object.

Returns:

A pointer to the last vector in the list, or `NULL` if the list is empty.

Time complexity: $O(1)$.

`igraph_vector_list_set` — Sets the vector at the given index in the list.

```
void igraph_vector_list_set(igraph_vector_list_t* v, igraph_integer_t pos, igraph_vector_t e);
```

This function destroys the vector that is already at the given index *pos* in the list, and replaces it with the vector pointed to by *e*. The ownership of the vector pointed to by *e* is taken by the list so the user is not responsible for destroying *e* any more; it will be destroyed when the list itself is destroyed or if *e* gets removed from the list without passing on the ownership to somewhere else.

Arguments:

v: The list object.

pos: The index to modify in the list.

e: The vector to set in the list.

Time complexity: $O(1)$.

igraph_vector_list_replace — Replaces the vector at the given index in the list with another one.

```
void igraph_vector_list_replace(igraph_vector_list_t* v, igraph_integer_t pos, igraph_vector_t e);
```

This function replaces the vector that is already at the given index *pos* in the list with the vector pointed to by *e*. The ownership of the vector pointed to by *e* is taken by the list so the user is not responsible for destroying *e* any more. At the same time, the ownership of the vector that *was* in the list at position *pos* will be transferred to the caller and *e* will be updated to point to it, so the caller becomes responsible for destroying it when it does not need the vector any more.

Arguments:

v: The list object.

pos: The index to modify in the list.

e: The vector to swap with the one already in the list.

Time complexity: $O(1)$.

Vector properties

igraph_vector_list_empty — Decides whether the size of the list is zero.

```
igraph_bool_t igraph_vector_list_empty(const igraph_vector_list_t* v);
```

Arguments:

v: The list object.

Returns:

Non-zero number (true) if the size of the list is zero and zero (false) otherwise.

Time complexity: $O(1)$.

igraph_vector_list_size — Returns the size (=length) of the vector.

```
igraph_integer_t igraph_vector_list_size(const igraph_vector_list_t* v);
```

Arguments:

v: The list object

Returns:

The size of the list.

Time complexity: $O(1)$.

igraph_vector_list_capacity — Returns the allocated capacity of the list.

```
igraph_integer_t igraph_vector_list_capacity(const igraph_vector_list_t* v);
```

Note that this might be different from the size of the list (as queried by `igraph_vector_list_size()`), and specifies how many vectors the list can hold, without reallocation.

Arguments:

v: Pointer to the (previously initialized) list object to query.

Returns:

The allocated capacity.

See also:

`igraph_vector_list_size()`.

Time complexity: $O(1)$.

Resizing operations

igraph_vector_list_clear — Removes all elements from a list of vectors.

```
void igraph_vector_list_clear(igraph_vector_list_t* v);
```


This function sets the size of the list to zero, and it also destroys all the vectors that were placed in the list before clearing it.

Arguments:

`v`: The list object.

Time complexity: $O(n)$, n is the number of items being deleted.

igraph_vector_list_reserve — Reserves memory for a list.

```
igraph_error_t igraph_vector_list_reserve(igraph_vector_list_t* v, igraph_integ
```

igraph lists are flexible, they can grow and shrink. Growing however occasionally needs the data in the list to be copied. In order to avoid this, you can call this function to reserve space for future growth of the list.

Note that this function does *not* change the size of the list, neither does it initialize any new vectors. Let us see a small example to clarify things: if you reserve space for 100 elements and the size of your list was (and still is) 60, then you can surely add additional 40 new vectors to your list before it will be copied.

Arguments:

`v`: The list object.

`capacity`: The new *allocated* size of the list.

Returns:

Error code: `IGRAPH_ENOMEM` if there is not enough memory.

Time complexity: operating system dependent, should be around $O(n)$, n is the new allocated size of the list.

igraph_vector_list_resize — Resize the list of vectors.

```
igraph_error_t igraph_vector_list_resize(igraph_vector_list_t* v, igraph_integ
```

Note that this function does not free any memory, just sets the size of the list to the given one. It can on the other hand allocate more memory if the new size is larger than the previous one.

When the new size is larger than the current size, the newly added vectors in the list are initialized to empty vectors. When the new size is smaller than the current size, the vectors that were removed from the end of the list are destroyed automatically.

Arguments:

`v`: The list object

`new_size`: The new size of the list.

Returns:

Error code, `IGRAPH_ENOMEM` if there is not enough memory. Note that this function *never* returns an error if the list is made smaller.

See also:

`igraph_vector_list_reserve()` for allocating memory for future extensions of a list.

Time complexity: $O(m)$ if the new size is smaller (m is the number of items that were removed from the list), operating system dependent if the new size is larger. In the latter case it is usually around $O(n)$, where n is the new size of the vector.

`igraph_vector_list_push_back` — Append an existing vector to the list, transferring ownership.

```
igraph_error_t igraph_vector_list_push_back(igraph_vector_list_t* v, igraph_vec
```

This function resizes the list to be one element longer, and sets the very last element in the list to the specified vector e . The list takes ownership of the vector so the user is not responsible for freeing e any more; the vector will be destroyed when the list itself is destroyed or if e gets removed from the list without passing on the ownership to somewhere else.

Arguments:

v : The list object.

e : Pointer to the vector to append to the list.

Returns:

Error code: `IGRAPH_ENOMEM`: not enough memory.

Time complexity: operating system dependent. What is important is that a sequence of n subsequent calls to this function has time complexity $O(n)$, even if there hadn't been any space reserved for the new elements by `igraph_vector_list_reserve()`. This is implemented by a trick similar to the C++ vector class: each time more memory is allocated for a vector, the size of the additionally allocated memory is the same as the vector's current length. (We assume here that the time complexity of memory allocation is at most linear).

`igraph_vector_list_push_back_copy` — Append the copy of a vector to the list.

```
igraph_error_t igraph_vector_list_push_back_copy(igraph_vector_list_t* v, const
```

This function resizes the list to be one element longer, and copies the specified vector given as an argument to the last element. The newly added element is owned by the list, but the ownership of the original vector is retained at the caller.

Arguments:

v : The list object.

e : Pointer to the vector to copy to the end of the list.

Returns:

Error code: IGRAPH_ENOMEM: not enough memory.

Time complexity: same as `igraph_vector_list_push_back()` plus the time needed to copy the vector (which is $O(n)$ for n elements in the vector).

igraph_vector_list_push_back_new — Append a new vector to the list.

```
igraph_error_t igraph_vector_list_push_back_new(igraph_vector_list_t* v, igraph_
```

This function resizes the list to be one element longer. The newly added element will be an empty vector that is owned by the list. A pointer to the newly added element is returned in the last argument if it is not `NULL`.

Arguments:

v: The list object.

result: Pointer to a vector pointer; this will be updated to point to the newly added vector. May be `NULL` if you do not need a pointer to the newly added vector.

Returns:

Error code: IGRAPH_ENOMEM: not enough memory.

Time complexity: same as `igraph_vector_list_push_back()`.

igraph_vector_list_pop_back — Remove the last item from the vector list and transfer ownership to the caller.

```
igraph_vector_t igraph_vector_list_pop_back(igraph_vector_list_t* v);
```

This function removes the last vector from the list. The vector that was removed from the list is returned and its ownership is passed back to the caller; in other words, the caller becomes responsible for destroying the vector when it is not needed any more.

It is an error to call this function with an empty vector.

Arguments:

v: The list object.

result: Pointer to an `igraph_vector_t` object; it will be updated to the item that was removed from the list. Ownership of this vector is passed on to the caller.

Time complexity: $O(1)$.

igraph_vector_list_insert — Insert an existing vector into the list, transferring ownership.

```
igraph_error_t igraph_vector_list_insert(igraph_vector_list_t* v, igraph_intege
```

This function inserts e into the list at the given index, moving other items towards the end of the list as needed. The list takes ownership of the vector so the user is not responsible for freeing e any more; the vector will be destroyed when the list itself is destroyed or if e gets removed from the list without passing on the ownership to somewhere else.

Arguments:

v : The list object.

pos : The position where the new element is to be inserted.

e : Pointer to the vector to insert into the list.

Returns:

Error code: IGRAPH_ENOMEM: not enough memory.

Time complexity: $O(n)$.

igraph_vector_list_insert_copy — Insert the copy of a vector to the list.

```
igraph_error_t igraph_vector_list_insert_copy(igraph_vector_list_t* v, igraph_in
```

This function inserts a copy of e into the list at the given index, moving other items towards the end of the list as needed. The newly added element is owned by the list, but the ownership of the original vector is retained at the caller.

Arguments:

v : The list object.

pos : The position where the new element is to be inserted.

e : Pointer to the vector to copy to the end of the list.

Returns:

Error code: IGRAPH_ENOMEM: not enough memory.

Time complexity: same as `igraph_vector_list_insert()` plus the time needed to copy the vector (which is $O(n)$ for n elements in the vector).

igraph_vector_list_insert_new — Insert a new vector into the list.

```
igraph_error_t igraph_vector_list_insert_new(igraph_vector_list_t* v, igraph_in
```

This function inserts a newly created empty vector into the list at the given index, moving other items towards the end of the list as needed. The newly added vector is owned by the list. A pointer to the new element is returned in the last argument if it is not `NULL`.

Arguments:

v: The list object.

pos: The position where the new element is to be inserted.

result: Pointer to a vector pointer; this will be updated to point to the newly added vector. May be `NULL` if you do not need a pointer to the newly added vector.

Returns:

Error code: `IGRAPH_ENOMEM`: not enough memory.

Time complexity: same as `igraph_vector_list_push_back()`.

`igraph_vector_list_remove` — Remove the item at the given index from the vector list and transfer ownership to the caller.

```
igraph_error_t igraph_vector_list_remove(igraph_vector_list_t* v, igraph_intege
```

This function removes the vector at the given index from the list, and moves all subsequent items in the list by one slot to the left to fill the gap. The vector that was removed from the list is returned in *e* and its ownership is passed back to the caller; in other words, the caller becomes responsible for destroying the vector when it is not needed any more.

Arguments:

v: The list object.

index: Index of the item to be removed.

result: Pointer to an `igraph_vector_t` object; it will be updated to the item that was removed from the list. Ownership of this vector is passed on to the caller. It is an error to supply a null pointer here.

See also:

`igraph_vector_list_discard()` if you are not interested in the item that was removed,
`igraph_vector_list_remove_fast()` if you do not care about the order of the items in the list.

Time complexity: $O(n)$, where n is the number of items in the list.

`igraph_vector_list_remove_fast` — Remove the item at the given index in the vector list, move the last item to its place and transfer ownership to the caller.

```
igraph_error_t igraph_vector_list_remove_fast(igraph_vector_list_t* v, igraph_i
```

This function removes the vector at the given index from the list, moves the last item in the list to *index* to fill the gap, and then transfers ownership of the removed vector back to the caller; in other words, the caller becomes responsible for destroying the vector when it is not needed any more.

Arguments:

v: The list object.

index: Index of the item to be removed.

result: Pointer to an `igraph_vector_t` object; it will be updated to the item that was removed from the list. Ownership of this vector is passed on to the caller. It is an error to supply a null pointer here.

See also:

`igraph_vector_list_remove()` if you want to preserve the order of the items in the list, `igraph_vector_list_discard_fast()` if you are not interested in the item that was removed.

Time complexity: $O(1)$.

`igraph_vector_list_discard` — Discard the item at the given index in the vector list.

```
void igraph_vector_list_discard(igraph_vector_list_t* v, igraph_integer_t index)
```

This function removes the vector at the given index from the list, and moves all subsequent items in the list by one slot to the left to fill the gap. The vector that was removed from the list is destroyed automatically.

Arguments:

v: The list object.

index: Index of the item to be discarded and destroyed.

See also:

`igraph_vector_list_discard_fast()` if you do not care about the order of the items in the list, `igraph_vector_list_remove()` if you want to gain ownership of the item that was removed instead of destroying it.

Time complexity: $O(n)$, where n is the number of items in the list.

`igraph_vector_list_discard_back` — Discard the last item in the vector list.

```
void igraph_vector_list_discard_back(igraph_vector_list_t* v);
```

This function removes the last vector from the list and destroys it.

Arguments:

v: The list object.

Time complexity: $O(1)$.

igraph_vector_list_discard_fast — Discard the item at the given index in the vector list and move the last item to its place.

```
void igraph_vector_list_discard_fast(igraph_vector_list_t* v, igraph_integer_t index)
```

This function removes the vector at the given index from the list, and moves the last item in the list to *index* to fill the gap. The vector that was removed from the list is destroyed automatically.

Arguments:

v: The list object.

index: Index of the item to be discarded and destroyed.

See also:

`igraph_vector_list_discard()` if you want to preserve the order of the items in the list,
`igraph_vector_list_remove_fast()` if you want to gain ownership of the item that was removed instead of destroying it.

Time complexity: $O(1)$.

Sorting and reordering

igraph_vector_list_permute — Permutes the elements of a list in place according to an index vector.

```
igraph_error_t igraph_vector_list_permute(igraph_vector_list_t* v, const igraph_integer_t* index)
```

This function takes a list *v* and a corresponding index vector *index*, and permutes the elements of *v* such that *v*[*index*[*i*]] is moved to become *v*[*i*] after the function is executed.

It is an error to call this function with an index vector that does not represent a valid permutation. Each element in the index vector must be between 0 and the length of the list minus one (inclusive), and each such element must appear only once. The function does not attempt to validate the index vector. Memory may be leaked if the index vector does not satisfy these conditions.

The index vector that this function takes is compatible with the index vector returned from `igraph_vector_list_sort_ind()`; passing in the index vector from `igraph_vector_list_sort_ind()` will sort the original vector.

Arguments:

v: the list to permute

index: the index vector

Time complexity: $O(n)$, the number of items in the list.

igraph_vector_list_sort — Sorts the elements of the list into ascending order.

```
void igraph_vector_list_sort(igraph_vector_list_t *v, int (*cmp)(const igraph_v
```

Arguments:

v: Pointer to an initialized list object.

cmp: A comparison function that takes pointers to two vectors and returns zero if the two vectors are considered equal, any negative number if the first vector is smaller and any positive number if the second vector is smaller.

Returns:

Error code.

Time complexity: $O(n \log n)$ for n elements.

igraph_vector_list_sort_ind — Return a permutation of indices that sorts the list

```
igraph_error_t igraph_vector_list_sort_ind(  
    igraph_vector_list_t *v, igraph_vector_int_t *inds,  
    int (*cmp)(const igraph_vector_t*, const igraph_vector_t*)  
);
```

Takes an unsorted list *v* as input and computes an array of indices *inds* such that *v*[*inds*[*i*]], with *i* increasing from 0, is an ordered array according to the comparison function *cmp*. The order of indices for identical elements is not defined.

Arguments:

v: the list to be sorted

inds: the output array of indices. This must be initialized, but will be resized

cmp: A comparison function that takes pointers to two vectors and returns zero if the two vectors are considered equal, any negative number if the first vector is smaller and any positive number if the second vector is smaller.

Returns:

Error code.

Time complexity: $O(n \log n)$ for n elements.

igraph_vector_list_swap — Swaps all elements of two vector lists.

```
igraph_error_t igraph_vector_list_swap(igraph_vector_list_t *v1, igraph_vector_
```


Arguments:

`v1`: The first list.

`v2`: The second list.

Returns:

Error code.

Time complexity: $O(1)$.

`igraph_vector_list_swap_elements` — Swap two elements in a vector list.

```
igraph_error_t igraph_vector_list_swap_elements(igraph_vector_list_t *v1, igraph_error_t *err)
```

Note that currently no range checking is performed.

Arguments:

`v`: The input list.

`i`: Index of the first element.

`j`: Index of the second element (may be the same as the first one).

Returns:

Error code, currently always `IGRAPH_SUCCESS`.

Time complexity: $O(1)$.

Adjacency lists

Sometimes it is easier to work with a graph which is in adjacency list format: a list of vectors; each vector contains the neighbor vertices or incident edges of a given vertex. Typically, this representation is good if we need to iterate over the neighbors of all vertices many times. E.g. when finding the shortest paths between all pairs of vertices or calculating closeness centrality for all the vertices.

The `igraph_adjlist_t` stores the adjacency lists of a graph. After creation it is independent of the original graph, it can be modified freely with the usual vector operations, the graph is not affected. E.g. the adjacency list can be used to rewire the edges of a graph efficiently. If one used the straightforward `igraph_delete_edges()` and `igraph_add_edges()` combination for this that needs $O(|V|+|E|)$ time for every single deletion and insertion operation, it is thus very slow if many edges are rewired. Extracting the graph into an adjacency list, do all the rewiring operations on the vectors of the adjacency list and then creating a new graph needs (depending on how exactly the rewiring is done) typically $O(|V|+|E|)$ time for the whole rewiring process.

Lazy adjacency lists are a bit different. When creating a lazy adjacency list, the neighbors of the vertices are not queried, only some memory is allocated for the vectors. When `igraph_lazy_adjlist_get()` is called for vertex `v` the first time, the neighbors of `v` are queried and stored in a vector of the adjacency list, so they don't need to be queried again. Lazy adjacency lists are handy if you have an at least linear operation (because initialization is generally linear in terms of the number of vertices), but you don't know how many vertices you will visit during the computation.

Example 7.12. File `examples/simple/adjlist.c`

Adjacent vertices

`igraph_adjlist_init` — Constructs an adjacency list of vertices from an incidence list.

```
igraph_error_t igraph_adjlist_init_from_inclist(  
    const igraph_t *graph, igraph_adjlist_t *al, const igraph_inclist_t *il);
```

In some algorithms it is useful to have an adjacency list *and* an incidence list representation of the same graph, and in many cases it is the most useful if they are consistent with each other, i.e. if can be guaranteed that the vertex ID in the i -th entry of the adjacency list of vertex v is the *other* endpoint of the edge in the i -th entry of the incidence list of the same vertex. This function creates such an adjacency list from the corresponding incidence list by looking up the endpoints of each edge in the incidence list and constructing the corresponding adjacency vectors.

The adjacency list is independent of the graph or the incidence list after creation; in other words, modifications that are made to the graph or the incidence list are not reflected in the adjacency list.

Arguments:

graph: The input graph.

al: Pointer to an uninitialized `igraph_adjlist_t` object.

il: Pointer to an *initialized* `igraph_inclist_t` object that will be converted into an adjacency list.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

`igraph_adjlist_init_empty` — Initializes an empty adjacency list.

```
igraph_error_t igraph_adjlist_init_empty(igraph_adjlist_t *al, igraph_integer_t
```

Creates a list of vectors, one for each vertex. This is useful when you are *constructing* a graph using an adjacency list representation as it does not require your graph to exist yet.

Arguments:

no_of_nodes: The number of vertices

al: Pointer to an uninitialized `igraph_adjlist_t` object.

Returns:

Error code.

Time complexity: $O(|V|)$, linear in the number of vertices.

igraph_adjlist_init_complementer — Adjacency lists for the complementer graph.

```
igraph_error_t igraph_adjlist_init_complementer(const igraph_t *graph,
                                                igraph_adjlist_t *al,
                                                igraph_neimode_t mode,
                                                igraph_bool_t loops);
```

This function creates adjacency lists for the complementer of the input graph. In the complementer graph all edges are present which are not present in the original graph. Multiple edges in the input graph are ignored.

Arguments:

graph: The input graph.

al: Pointer to a not yet initialized adjacency list.

mode: Constant specifying whether outgoing (IGRAPH_OUT), incoming (IGRAPH_IN), or both (IGRAPH_ALL) types of neighbors (in the complementer graph) to include in the adjacency list. It is ignored for undirected networks.

loops: Whether to consider loop edges.

Returns:

Error code.

Time complexity: $O(|V|^2+|E|)$, quadratic in the number of vertices.

igraph_adjlist_destroy — Deallocates an adjacency list.

```
void igraph_adjlist_destroy(igraph_adjlist_t *al);
```

Free all memory allocated for an adjacency list.

Arguments:

al: The adjacency list to destroy.

Time complexity: depends on memory management.

igraph_adjlist_get — Query a vector in an adjacency list.

```
#define igraph_adjlist_get(al,no)
```

Returns a pointer to an `igraph_vector_int_t` object from an adjacency list. The vector can be modified as desired.

Arguments:

al: The adjacency list object.

no: The vertex whose adjacent vertices will be returned.

Returns:

Pointer to the `igraph_vector_int_t` object.

Time complexity: $O(1)$.

igraph_adjlist_size — Returns the number of vertices in an adjacency list.

```
igraph_integer_t igraph_adjlist_size(const igraph_adjlist_t *al);
```

Arguments:

al: The adjacency list.

Returns:

The number of vertices in the adjacency list.

Time complexity: $O(1)$.

igraph_adjlist_clear — Removes all edges from an adjacency list.

```
void igraph_adjlist_clear(igraph_adjlist_t *al);
```

Arguments:

al: The adjacency list. Time complexity: depends on memory management, typically $O(n)$, where n is the total number of elements in the adjacency list.

igraph_adjlist_sort — Sorts each vector in an adjacency list.

```
void igraph_adjlist_sort(igraph_adjlist_t *al);
```

Sorts every vector of the adjacency list.

Arguments:

al: The adjacency list.

Time complexity: $O(n \log n)$, n is the total number of elements in the adjacency list.

igraph_adjlist_simplify — Simplifies an adjacency list.

```
igraph_error_t igraph_adjlist_simplify(igraph_adjlist_t *al);
```

Simplifies an adjacency list, i.e. removes loop and multiple edges.

Arguments:

al: The adjacency list.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of edges and vertices.

Incident edges

igraph_inclist_init — Initializes an incidence list.

```
igraph_error_t igraph_inclist_init(const igraph_t *graph,
                                   igraph_inclist_t *il,
                                   igraph_neimode_t mode,
                                   igraph_loops_t loops);
```

Creates a list of vectors containing the incident edges for all vertices. The incidence list is independent of the graph after creation, subsequent changes of the graph object do not update the incidence list, and changes to the incidence list do not update the graph.

When *mode* is `IGRAPH_IN` or `IGRAPH_OUT`, each edge ID will appear in the incidence list *once*. When *mode* is `IGRAPH_ALL`, each edge ID will appear in the incidence list *twice*, once for the source vertex and once for the target edge. It also means that the edge IDs of loop edges may potentially appear *twice* for the *same* vertex. Use the *loops* argument to control whether this will be the case (`IGRAPH_LOOPS_TWICE`) or not (`IGRAPH_LOOPS_ONCE` or `IGRAPH_NO_LOOPS`).

Arguments:

graph: The input graph.

il: Pointer to an uninitialized incidence list.

mode: Constant specifying whether incoming edges (`IGRAPH_IN`), outgoing edges (`IGRAPH_OUT`) or both (`IGRAPH_ALL`) to include in the incidence lists of directed graphs. It is ignored for undirected graphs.

loops: Specifies how to treat loop edges. `IGRAPH_NO_LOOPS` removes loop edges from the incidence list. `IGRAPH_LOOPS_ONCE` makes each loop edge appear only once in the incidence list of the corresponding vertex. `IGRAPH_LOOPS_TWICE` makes loop edges appear *twice* in the incidence list of the corresponding vertex, but only if the graph is undirected or *mode* is set to `IGRAPH_ALL`.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

igraph_inclist_destroy — Frees all memory allocated for an incidence list.

```
void igraph_inclist_destroy(igraph_inclist_t *il);
```

Arguments:

il: The incidence list to destroy.

Time complexity: depends on memory management.

igraph_inclist_get — Query a vector in an incidence list.

```
#define igraph_inclist_get(il,no)
```

Returns a pointer to an `igraph_vector_int_t` object from an incidence list containing edge IDs. The vector can be modified, resized, etc. as desired.

Arguments:

il: Pointer to the incidence list.

no: The vertex for which the incident edges are returned.

Returns:

Pointer to an `igraph_vector_int_t` object.

Time complexity: $O(1)$.

igraph_inclist_size — Returns the number of vertices in an incidence list.

```
igraph_integer_t igraph_inclist_size(const igraph_inclist_t *il);
```

Arguments:

il: The incidence list.

Returns:

The number of vertices in the incidence list.

Time complexity: $O(1)$.

igraph_inclist_clear — Removes all edges from an incidence list.

```
void igraph_inclist_clear(igraph_inclist_t *il);
```

Arguments:

il: The incidence list.

Time complexity: depends on memory management, typically $O(n)$, where n is the total number of elements in the incidence list.

Lazy adjacency list for vertices

igraph_lazy_adjlist_init — Initialized a lazy adjacency list.

```
igraph_error_t igraph_lazy_adjlist_init(const igraph_t *graph,
                                         igraph_lazy_adjlist_t *al,
                                         igraph_neimode_t mode,
                                         igraph_loops_t loops,
                                         igraph_multiple_t multiple);
```

Create a lazy adjacency list for vertices. This function only allocates some memory for storing the vectors of an adjacency list, but the neighbor vertices are not queried, only at the `igraph_lazy_adjlist_get()` calls.

Arguments:

graph: The input graph.

al: Pointer to an uninitialized adjacency list object.

mode: Constant, it gives whether incoming edges (`IGRAPH_IN`), outgoing edges (`IGRAPH_OUT`) or both types of edges (`IGRAPH_ALL`) are considered. It is ignored for undirected graphs.

simplify: Constant, it gives whether to simplify the vectors in the adjacency list (`IGRAPH_SIMPLIFY`) or not (`IGRAPH_DONT_SIMPLIFY`).

Returns:

Error code.

Time complexity: $O(|V|)$, the number of vertices, possibly, but depends on the underlying memory management too.

igraph_lazy_adjlist_destroy — Deallocate a lazy adjacency list.

```
void igraph_lazy_adjlist_destroy(igraph_lazy_adjlist_t *al);
```

Free all allocated memory for a lazy adjacency list.

Arguments:

al: The adjacency list to deallocate.

Time complexity: depends on the memory management.

igraph_lazy_adjlist_get — Query neighbor vertices.

```
#define igraph_lazy_adjlist_get(al,no)
```

If the function is called for the first time for a vertex then the result is stored in the adjacency list and no further query operations are needed when the neighbors of the same vertex are queried again.

Arguments:

al: The lazy adjacency list.

no: The vertex ID to query.

Returns:

Pointer to a vector, or NULL upon error. It is safe to modify this vector, modification does not affect the original graph.

Time complexity: $O(d)$, the number of neighbor vertices for the first time, $O(1)$ for subsequent calls.

igraph_lazy_adjlist_size — Returns the number of vertices in a lazy adjacency list.

```
igraph_integer_t igraph_lazy_adjlist_size(const igraph_lazy_adjlist_t *al);
```

Arguments:

al: The lazy adjacency list.

Returns:

The number of vertices in the lazy adjacency list.

Time complexity: $O(1)$.

igraph_lazy_adjlist_clear — Removes all edges from a lazy adjacency list.

```
void igraph_lazy_adjlist_clear(igraph_lazy_adjlist_t *al);
```

Arguments:

al: The lazy adjacency list. Time complexity: depends on memory management, typically $O(n)$, where n is the total number of elements in the adjacency list.

Lazy incidence list for edges

igraph_lazy_inclist_init — Initializes a lazy incidence list of edges.

```
igraph_error_t igraph_lazy_inclist_init(const igraph_t *graph,
```



```
igraph_lazy_inclist_t *il,  
igraph_neimode_t mode,  
igraph_loops_t loops);
```

Create a lazy incidence list for edges. This function only allocates some memory for storing the vectors of an incidence list, but the incident edges are not queried, only when `igraph_lazy_inclist_get()` is called.

When *mode* is `IGRAPH_IN` or `IGRAPH_OUT`, each edge ID will appear in the incidence list *once*. When *mode* is `IGRAPH_ALL`, each edge ID will appear in the incidence list *twice*, once for the source vertex and once for the target edge. It also means that the edge IDs of loop edges will appear *twice* for the *same* vertex.

Arguments:

graph: The input graph.

al: Pointer to an uninitialized incidence list.

mode: Constant, it gives whether incoming edges (`IGRAPH_IN`), outgoing edges (`IGRAPH_OUT`) or both types of edges (`IGRAPH_ALL`) are considered. It is ignored for undirected graphs.

loops: Specifies how to treat loop edges. `IGRAPH_NO_LOOPS` removes loop edges from the incidence list. `IGRAPH_LOOPS_ONCE` makes each loop edge appear only once in the incidence list of the corresponding vertex. `IGRAPH_LOOPS_TWICE` makes loop edges appear *twice* in the incidence list of the corresponding vertex, but only if the graph is undirected or *mode* is set to `IGRAPH_ALL`.

Returns:

Error code.

Time complexity: $O(|V|)$, the number of vertices, possibly. But it also depends on the underlying memory management.

igraph_lazy_inclist_destroy — Deallocates a lazy incidence list.

```
void igraph_lazy_inclist_destroy(igraph_lazy_inclist_t *il);
```

Frees all allocated memory for a lazy incidence list.

Arguments:

al: The incidence list to deallocate.

Time complexity: depends on memory management.

igraph_lazy_inclist_get — Query incident edges.

```
#define igraph_lazy_inclist_get(al,no)
```

If the function is called for the first time for a vertex, then the result is stored in the incidence list and no further query operations are needed when the incident edges of the same vertex are queried again.

Arguments:

al: The lazy incidence list object.

no: The vertex ID to query.

Returns:

Pointer to a vector, or NULL upon error. It is safe to modify this vector, modification does not affect the original graph.

Time complexity: $O(d)$, the number of incident edges for the first time, $O(1)$ for subsequent calls with the same *no* argument.

igraph_lazy_inclist_size — Returns the number of vertices in a lazy incidence list.

```
igraph_integer_t igraph_lazy_inclist_size(const igraph_lazy_inclist_t *il);
```

Arguments:

il: The lazy incidence list.

Returns:

The number of vertices in the lazy incidence list.

Time complexity: $O(1)$.

igraph_lazy_inclist_clear — Removes all edges from a lazy incidence list.

```
void igraph_lazy_inclist_clear(igraph_lazy_inclist_t *il);
```

Arguments:

il: The lazy incidence list.

Time complexity: depends on memory management, typically $O(n)$, where n is the total number of elements in the incidence list.

Partial prefix sum trees

The `igraph_psumtree_t` data type represents a partial prefix sum tree. A partial prefix sum tree is a data structure that can be used to draw samples from a discrete probability distribution with dynamic probabilities that are updated frequently. This is achieved by creating a binary tree where the leaves are the items. Each leaf contains the probability corresponding to the items. Intermediate nodes of the tree always contain the sum of its two children. When the value of a leaf node is updated, the values of its ancestors are also updated accordingly.

Samples can be drawn from the probability distribution represented by the tree by generating a uniform random number between 0 (inclusive) and the value of the root of the tree (exclusive), and then

following the branches of the tree as follows. In each step, the value in the current node is compared with the generated number. If the value in the node is larger, the left branch of the tree is taken; otherwise the generated number is decreased by the value in the node and the right branch of the tree is taken, until a leaf node is reached.

Note that the sampling process works only if all the values in the tree are non-negative. This is enforced by the object; in particular, trying to set a negative value for an item will produce an igraph error.

igraph_psumtree_init — Initializes a partial prefix sum tree.

```
igraph_error_t igraph_psumtree_init(igraph_psumtree_t *t, igraph_integer_t size)
```

The tree is initialized with a fixed number of elements. After initialization, the value corresponding to each element is zero.

Arguments:

t: The tree to initialize.

size: The number of elements in the tree. It must be at least one.

Returns:

Error code, typically `IGRAPH_ENOMEM` if there is not enough memory.

Time complexity: $O(n)$ for a tree containing n elements

igraph_psumtree_destroy — Destroys a partial prefix sum tree.

```
void igraph_psumtree_destroy(igraph_psumtree_t *t);
```

All partial prefix sum trees initialized by `igraph_psumtree_init()` should be properly destroyed by this function. A destroyed tree needs to be reinitialized by `igraph_psumtree_init()` if you want to use it again.

Arguments:

t: Pointer to the (previously initialized) tree to destroy.

Time complexity: operating system dependent.

igraph_psumtree_size — Returns the size of the tree.

```
igraph_integer_t igraph_psumtree_size(const igraph_psumtree_t *t);
```

Arguments:

t: The tree object

Returns:

The number of discrete items in the tree.

Time complexity: $O(1)$.

igraph_psumtree_get — Retrieves the value corresponding to an item in the tree.

```
igraph_real_t igraph_psumtree_get(const igraph_psumtree_t *t, igraph_integer_t idx);
```

Arguments:

t: The tree to query.

idx: The index of the item whose value is to be retrieved.

Returns:

The value corresponding to the item with the given index.

Time complexity: $O(1)$

igraph_psumtree_sum — Returns the sum of the values of the leaves in the tree.

```
igraph_real_t igraph_psumtree_sum(const igraph_psumtree_t *t);
```

Arguments:

t: The tree object

Returns:

The sum of the values of the leaves in the tree.

Time complexity: $O(1)$.

igraph_psumtree_search — Finds an item in the tree, given a value.

```
igraph_error_t igraph_psumtree_search(const igraph_psumtree_t *t, igraph_integer_t value);
```

```
igraph_real_t search);
```

This function finds the item with the lowest index where it holds that the sum of all the items with a *lower* index is less than or equal to the given value and that the sum of all the items with a lower index plus the item itself is larger than the given value.

If you think about the partial prefix sum tree as a tool to sample from a discrete probability distribution, then calling this function repeatedly with uniformly distributed random numbers in the range 0 (inclusive) to the sum of all values in the tree (exclusive) will sample the items in the tree with a probability that is proportional to their associated values.

Arguments:

t: The tree to query.

idx: The index of the item is returned here.

search: The value to use for the search. Must be in the interval $[0, \text{sum})$, where *sum* is the sum of all elements (leaves) in the tree.

Returns:

Error code; currently the search always succeeds.

Time complexity: $O(\log n)$, where *n* is the number of items in the tree.

igraph_psumtree_update — Updates the value associated to an item in the tree.

```
igraph_error_t igraph_psumtree_update(igraph_psumtree_t *t, igraph_integer_t idx,  
                                      igraph_real_t new_value);
```

Arguments:

t: The tree to query.

idx: The index of the item to update.

new_value: The new value of the item.

Returns:

Error code, `IGRAPH_EINVAL` if the new value is negative or NaN, `IGRAPH_SUCCESS` if the operation was successful.

Time complexity: $O(\log n)$, where *n* is the number of items in the tree.

Chapter 8. Random numbers

About random numbers in igraph

Some algorithms in igraph, such as sampling from random graph models, require random number generators (RNGs). igraph includes a flexible RNG framework that allows hooking up arbitrary random number generators, and comes with several ready-to-use generators. This framework is used in igraph's high-level interfaces to integrate with the host language's own RNG.

The default random number generator

igraph_rng_default — Query the default random number generator.

```
igraph_rng_t *igraph_rng_default(void);
```

Returns:

A pointer to the default random number generator.

See also:

```
igraph_rng_set_default()
```

igraph_rng_set_default — Set the default igraph random number generator.

```
void igraph_rng_set_default(igraph_rng_t *rng);
```

This function *copies* the internal structure of the given `igraph_rng_t` object to igraph's internal default RNG structure. The structure itself contains two pointers only, one to the "methods" of the RNG and one to the memory buffer holding the internal state of the RNG. This means that if you keep on generating random numbers from the RNG after setting it as the default, it will affect the state of the default RNG as well because the two share the same state pointer. However, do *not* expect `igraph_rng_default()` to return the same pointer as the one you passed in here - the state is shared, but the entire structure is not.

Arguments:

rng: The random number generator to use as default from now on. Calling `igraph_rng_destroy()` on it, while it is still being used as the default will result in crashes and/or unpredictable results.

Time complexity: $O(1)$.

Creating random number generators

igraph_rng_init — Initializes a random number generator.

```
igraph_error_t igraph_rng_init(igraph_rng_t *rng, const igraph_rng_type_t *type)
```

This function allocates memory for a random number generator, with the given type, and sets its seed to the default.

Arguments:

rng: Pointer to an uninitialized RNG.

type: The type of the RNG, such as `igraph_rngtype_mt19937`, `igraph_rngtype_glibc2`, `igraph_rngtype_pcg32` or `igraph_rngtype_pcg64`.

Returns:

Error code.

igraph_rng_destroy — Deallocates memory associated with a random number generator.

```
void igraph_rng_destroy(igraph_rng_t *rng);
```

Arguments:

rng: The RNG to destroy. Do not destroy an RNG that is used as the default igraph RNG.

Time complexity: $O(1)$.

igraph_rng_seed — Seeds a random number generator.

```
igraph_error_t igraph_rng_seed(igraph_rng_t *rng, igraph_uint_t seed);
```

Arguments:

rng: The RNG.

seed: The new seed.

Returns:

Error code.

Time complexity: usually $O(1)$, but may depend on the type of the RNG.

igraph_rng_bits — The number of random bits that a random number generator can produce in a single round.

```
igraph_integer_t igraph_rng_bits(const igraph_rng_t* rng);
```

Arguments:

rng: The RNG.

Returns:

The number of random bits that can be generated in a single round with the RNG.

Time complexity: $O(1)$.

igraph_rng_max — The maximum possible integer for a random number generator.

```
igraph_uint_t igraph_rng_max(const igraph_rng_t *rng);
```

Note that this number is only for informational purposes; it returns the maximum possible integer that can be generated with the RNG with a single call to its internals. It is derived directly from the number of random *bits* that the RNG can generate in a single round. When this is smaller than what would be needed by other RNG functions like `igraph_rng_get_integer()`, igraph will call the RNG multiple times to generate more random bits.

Arguments:

rng: The RNG.

Returns:

The largest possible integer that can be generated in a single round with the RNG.

Time complexity: $O(1)$.

igraph_rng_name — The type of a random number generator.

```
const char *igraph_rng_name(const igraph_rng_t *rng);
```

Arguments:

rng: The RNG.

Returns:

The name of the type of the generator. Do not deallocate or change the returned string.

Time complexity: $O(1)$.

Generating random numbers

igraph_rng_get_integer — Generate an integer random number from an interval.

```
igraph_integer_t igraph_rng_get_integer(  
    igraph_rng_t *rng, igraph_integer_t l, igraph_integer_t h  
);
```

Arguments:

rng: Pointer to the RNG to use for the generation. Use `igraph_rng_default()` here to use the default igraph RNG.

l: Lower limit, inclusive, it can be negative as well.

h: Upper limit, inclusive, it can be negative as well, but it should be at least *l*.

Returns:

The generated random integer.

Time complexity: $O(\log_2(h-l) / \text{bits})$ where bits is the value of `igraph_rng_bits(rng)`.

igraph_rng_get_unif01 — Samples uniformly from the unit interval.

```
igraph_real_t igraph_rng_get_unif01(igraph_rng_t *rng);
```

Generates uniformly distributed real numbers from the $[0, 1)$ half-open interval.

Arguments:

rng: Pointer to the RNG to use. Use `igraph_rng_default()` here to use the default igraph RNG.

Returns:

The generated uniformly distributed random number.

Time complexity: depends on the type of the RNG.

igraph_rng_get_unif — Samples real numbers from a given interval.

```
igraph_real_t igraph_rng_get_unif(igraph_rng_t *rng,  
                                  igraph_real_t l, igraph_real_t h);
```

Generates uniformly distributed real numbers from the $[l, h)$ half-open interval.

Arguments:

rng: Pointer to the RNG to use. Use `igraph_rng_default()` here to use the default igraph RNG.

l: The lower bound, it can be negative.

h: The upper bound, it can be negative, but it has to be larger than the lower bound.

Returns:

The generated uniformly distributed random number.

Time complexity: depends on the type of the RNG.

igraph_rng_get_normal — Samples from a normal distribution.

```
igraph_real_t igraph_rng_get_normal(igraph_rng_t *rng,  
                                     igraph_real_t m, igraph_real_t s);
```

Generates random variates from a normal distribution with probability density

$\exp(- (x - m)^2 / (2 s^2))$.

Arguments:

rng: Pointer to the RNG to use. Use `igraph_rng_default()` here to use the default igraph RNG.

m: The mean.

s: The standard deviation.

Returns:

The generated normally distributed random number.

Time complexity: depends on the type of the RNG.

igraph_rng_get_exp — Samples from an exponential distribution.

```
igraph_real_t igraph_rng_get_exp(igraph_rng_t *rng, igraph_real_t rate);
```

Generates random variates from an exponential distribution with probability density proportional to

```
exp(-rate x).
```

Arguments:

rng: Pointer to the RNG to use. Use `igraph_rng_default()` here to use the default igraph RNG.

rate: Rate parameter.

Returns:

The generated sample.

Time complexity: depends on the RNG.

igraph_rng_get_gamma — Samples from a gamma distribution.

```
igraph_real_t igraph_rng_get_gamma(igraph_rng_t *rng, igraph_real_t shape,  
                                   igraph_real_t scale);
```

Generates random variates from a gamma distribution with probability density proportional to

$x^{(\text{shape}-1)} \exp(-x / \text{scale})$.

Arguments:

rng: Pointer to the RNG to use. Use `igraph_rng_default()` here to use the default igraph RNG.

shape: Shape parameter.

scale: Scale parameter.

Returns:

The generated sample.

Time complexity: depends on the RNG.

igraph_rng_get_binom — Samples from a binomial distribution.

```
igraph_real_t igraph_rng_get_binom(igraph_rng_t *rng, igraph_integer_t n, igraph_real_t p);
```

Generates random variates from a binomial distribution. The number k is generated with probability

$\binom{n}{k} p^k (1-p)^{(n-k)}$, $k = 0, 1, \dots, n$.

Arguments:

rng: Pointer to the RNG to use. Use `igraph_rng_default()` here to use the default igraph RNG.

n: Number of observations.

p: Probability of an event.

Returns:

The generated binomially distributed random number.

Time complexity: depends on the RNG.

igraph_rng_get_geom — Samples from a geometric distribution.

```
igraph_real_t igraph_rng_get_geom(igraph_rng_t *rng, igraph_real_t p);
```

Generates random variates from a geometric distribution. The number *k* is generated with probability

$(1 - p)^k p, k = 0, 1, 2, \dots$

Arguments:

rng: Pointer to the RNG to use. Use `igraph_rng_default()` here to use the default igraph RNG.

p: The probability of success in each trial. Must be larger than zero and smaller or equal to 1.

Returns:

The generated geometrically distributed random number.

Time complexity: depends on the RNG.

igraph_rng_get_pois — Samples from a Poisson distribution.

```
igraph_real_t igraph_rng_get_pois(igraph_rng_t *rng, igraph_real_t rate);
```

Generates random variates from a Poisson distribution. The number *k* is generated with probability

$\text{rate}^k * \exp(-\text{rate}) / k!, k = 0, 1, 2, \dots$

Arguments:

rng: Pointer to the RNG to use. Use `igraph_rng_default()` here to use the default igraph RNG.

rate: The rate parameter of the Poisson distribution. Must not be negative.

Returns:

The generated geometrically distributed random number.

Time complexity: depends on the RNG.

Supported random number generators

By default igraph uses the MT19937 generator. Prior to igraph version 0.6, the generator supplied by the standard C library was used. This means the GLIBC2 generator on GNU libc 2 systems, and maybe the BSD RAND generator on others. The RAND generator was removed due to poor statistical properties in version 0.10. The PCG32 generator was added in version 0.10.

igraph_rngtype_mt19937 — The MT19937 random number generator.

```
const igraph_rng_type_t igraph_rngtype_mt19937 = {
    /* name= */      "MT19937",
    /* bits= */      32,
    /* init= */      igraph_rng_mt19937_init,
    /* destroy= */    igraph_rng_mt19937_destroy,
    /* seed= */      igraph_rng_mt19937_seed,
    /* get= */       igraph_rng_mt19937_get,
    /* get_int= */    0,
    /* get_real= */   0,
    /* get_norm= */   0,
    /* get_geom= */   0,
    /* get_binom= */  0,
    /* get_exp= */    0,
    /* get_gamma= */  0,
    /* get_pois= */   0
};
```

The MT19937 generator of Makoto Matsumoto and Takuji Nishimura is a variant of the twisted generalized feedback shift-register algorithm, and is known as the “Mersenne Twister” generator. It has a Mersenne prime period of $2^{19937} - 1$ (about 10^{6000}) and is equi-distributed in 623 dimensions. It has passed the diehard statistical tests. It uses 624 words of state per generator and is comparable in speed to the other generators. The original generator used a default seed of 4357 and choosing `s` equal to zero in `igraph_rng_mt19937_seed()` reproduces this. Later versions switched to 5489 as the default seed, you can choose this explicitly via `igraph_rng_seed()` instead if you require it.

For more information see, Makoto Matsumoto and Takuji Nishimura, “Mersenne Twister: A 623-dimensionally equidistributed uniform pseudorandom number generator”. ACM Transactions on Modeling and Computer Simulation, Vol. 8, No. 1 (Jan. 1998), Pages 3–30

The generator `igraph_rngtype_mt19937` uses the second revision of the seeding procedure published by the two authors above in 2002. The original seeding procedures could cause spurious artifacts for some seed values.

This generator was ported from the GNU Scientific Library.

igraph_rngtype_glibc2 — The random number generator introduced in GNU libc 2.

```
const igraph_rng_type_t igraph_rngtype_glibc2 = {
    /* name= */      "LIBC",
    /* bits= */      31,
    /* init= */      igraph_rng_glibc2_init,
```

```
/* destroy= */    igraph_rng_glibc2_destroy,  
/* seed= */      igraph_rng_glibc2_seed,  
/* get= */       igraph_rng_glibc2_get,  
/* get_int= */   0,  
/* get_real= */  0,  
/* get_norm= */  0,  
/* get_geom= */  0,  
/* get_binom= */ 0,  
/* get_exp= */   0,  
/* get_gamma= */ 0,  
/* get_pois= */  0  
};
```

This is a linear feedback shift register generator with a 128-byte buffer. This generator was the default prior to igraph version 0.6, at least on systems relying on GNU libc. This generator was ported from the GNU Scientific Library. It is a reimplement and does not call the system glibc generator.

igraph_rngtype_pcg32 — The PCG random number generator (32-bit version).

```
const igraph_rng_type_t igraph_rngtype_pcg32 = {  
    /* name= */      "PCG32",  
    /* bits= */      32,  
    /* init= */      igraph_rng_pcg32_init,  
    /* destroy= */    igraph_rng_pcg32_destroy,  
    /* seed= */      igraph_rng_pcg32_seed,  
    /* get= */       igraph_rng_pcg32_get,  
    /* get_int= */   0,  
    /* get_real= */  0,  
    /* get_norm= */  0,  
    /* get_geom= */  0,  
    /* get_binom= */ 0,  
    /* get_exp= */   0,  
    /* get_gamma= */ 0,  
    /* get_pois= */  0  
};
```

This is an implementation of the PCG random number generator; see <https://www.pcg-random.org> for more details. This implementation returns 32 random bits in a single iteration.

The generator was ported from the original source code published by the authors at <https://github.com/imneme/pcg-c>.

igraph_rngtype_pcg64 — The PCG random number generator (64-bit version).

```
const igraph_rng_type_t igraph_rngtype_pcg64 = {  
    /* name= */      "PCG64",  
    /* bits= */      64,  
    /* init= */      igraph_rng_pcg64_init,  
    /* destroy= */    igraph_rng_pcg64_destroy,  
    /* seed= */      igraph_rng_pcg64_seed,  
};
```

```
/* get= */      igraph_rng_pcg64_get,  
/* get_int= */  0,  
/* get_real= */ 0,  
/* get_norm= */ 0,  
/* get_geom= */ 0,  
/* get_binom= */ 0,  
/* get_exp= */  0,  
/* get_gamma= */ 0,  
/* get_pois= */ 0  
};
```

This is an implementation of the PCG random number generator; see <https://www.pcg-random.org> for more details. This implementation returns 64 random bits in a single iteration. It is only available on 64-bit platforms with compilers that provide the `__uint128_t` type.

PCG64 typically provides better performance than PCG32 when sampling floating point numbers or very large integers, as it can provide twice as many random bits in a single generation round.

The generator was ported from the original source code published by the authors at <https://github.com/inneme/pcg-c>.

Use cases

Normal (default) use

If the user does not use any of the RNG functions explicitly, but calls some of the randomized igraph functions, then a default RNG is set up the first time an igraph function needs random numbers. The seed of this RNG is the output of the `time(0)` function call, using the `time` function from the standard C library. This ensures that igraph creates a different random graph, each time the C program is called.

The created default generator is stored internally and can be queried with the `igraph_rng_default()` function.

Reproducible simulations

If reproducible results are needed, then the user should set the seed of the default random number generator explicitly, using the `igraph_rng_seed()` function on the default generator, `igraph_rng_default()`. When setting the seed to the same number, igraph generates exactly the same random graph (or series of random graphs).

Changing the default generator

By default igraph uses the `igraph_rng_default()` random number generator. This can be changed any time by calling `igraph_rng_set_default()`, with an already initialized random number generator. Note that the old (replaced) generator is not destroyed, so no memory is deallocated.

Using multiple generators

igraph also provides functions to set up multiple random number generators, using the `igraph_rng_init()` function, and then generating random numbers from them, e.g. with `igraph_rng_get_integer()` and/or `igraph_rng_get_unif()` calls.

Note that initializing a new random number generator is independent of the generator that the igraph functions themselves use. If you want to replace that, then please use `igraph_rng_set_default()`.

Example

Example 8.1. File `examples/simple/random_seed.c`

Chapter 9. Graph generators

Graph generators create graphs.

Almost all functions which create graph objects are documented here. The exceptions are `igraph_induced_subgraph()` and alike, these create graphs based on another graph.

Deterministic graph generators

`igraph_create` — Creates a graph with the specified edges.

```
igraph_error_t igraph_create(igraph_t *graph, const igraph_vector_int_t *edges,
                             igraph_integer_t n, igraph_bool_t directed);
```

Arguments:

- graph*: An uninitialized graph object.
- edges*: The edges to add, the first two elements are the first edge, etc.
- n*: The number of vertices in the graph, if smaller or equal to the highest vertex ID in the *edges* vector it will be increased automatically. So it is safe to give 0 here.
- directed*: Boolean, whether to create a directed graph or not. If yes, then the first edge points from the first vertex ID in *edges* to the second, etc.

Returns:

Error code: `IGRAPH_EINVEVECTOR`: invalid edges vector (odd number of vertices).
`IGRAPH_EINVVID`: invalid (negative) vertex ID.

Time complexity: $O(|V|+|E|)$, $|V|$ is the number of vertices, $|E|$ the number of edges in the graph.

Example 9.1. File `examples/simple/igraph_create.c`

`igraph_small` — Shorthand to create a small graph, giving the edges as arguments.

```
igraph_error_t igraph_small(igraph_t *graph, igraph_integer_t n, igraph_bool_t directed,
                             int first, ...);
```

This function is handy when a relatively small graph needs to be created. Instead of giving the edges as a vector, they are given simply as arguments and a `-1` needs to be given after the last meaningful edge argument.

Note that only graphs which have vertices less than the highest value of the 'int' type can be created this way. If you give larger values then the result is undefined.

Arguments:

- graph*: Pointer to an uninitialized graph object. The result will be stored here.
- n*: The number of vertices in the graph; a nonnegative integer.
- directed*: Logical constant; gives whether the graph should be directed. Supported values are:
- | | |
|--------------------------------|---|
| <code>IGRAPH_DIRECTED</code> | The graph to be created will be <i>directed</i> . |
| <code>IGRAPH_UNDIRECTED</code> | The graph to be created will be <i>undirected</i> . |
- ...:* The additional arguments giving the edges of the graph. Don't forget to supply an additional '-1' after the last (meaningful) argument. The *first* parameter is present for technical reasons and represents the first variadic argument.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges in the graph to create.

Example 9.2. File `examples/simple/igraph_small.c`

igraph_adjacency — Creates a graph from an adjacency matrix.

```
igraph_error_t igraph_adjacency(  
    igraph_t *graph, const igraph_matrix_t *adjmatrix, igraph_adjacency_t mode,  
    igraph_loops_t loops  
);
```

The order of the vertices in the matrix is preserved, i.e. the vertex corresponding to the first row/column will be vertex with id 0, the next row is for vertex 1, etc.

Arguments:

- graph*: Pointer to an uninitialized graph object.
- adjmatrix*: The adjacency matrix. How it is interpreted depends on the *mode* argument.
- mode*: Constant to specify how the given matrix is interpreted as an adjacency matrix. Possible values ($A(i,j)$ is the element in row i and column j in the adjacency matrix *adjmatrix*):
- | | |
|------------------------------------|---|
| <code>IGRAPH_ADJ_DIRECTED</code> | the graph will be directed and an element gives the number of edges between two vertices. |
| <code>IGRAPH_ADJ_UNDIRECTED</code> | this is the same as <code>IGRAPH_ADJ_MAX</code> , for convenience. |
| <code>IGRAPH_ADJ_MAX</code> | undirected graph will be created and the number of edges between vertices i and j is $\max(A(i,j), A(j,i))$. |
| <code>IGRAPH_ADJ_MIN</code> | undirected graph will be created with $\min(A(i,j), A(j,i))$ edges between vertices i and j . |

	IGRAPH_ADJ_PLUS	undirected graph will be created with $A(i,j)+A(j,i)$ edges between vertices i and j .
	IGRAPH_ADJ_UPPER	undirected graph will be created, only the upper right triangle (including the diagonal) is used for the number of edges.
	IGRAPH_ADJ_LOWER	undirected graph will be created, only the lower left triangle (including the diagonal) is used for creating the edges.
<i>loops:</i>	Constant to specify how the diagonal of the matrix should be treated when creating loop edges.	
	IGRAPH_NO_LOOPS	Ignore the diagonal of the input matrix and do not create loops.
	IGRAPH_LOOPS_ONCE	Treat the diagonal entries as the number of loop edges incident on the corresponding vertex.
	IGRAPH_LOOPS_TWICE	Treat the diagonal entries as <i>twice</i> the number of loop edges incident on the corresponding vertex. Odd numbers in the diagonal will return an error code.

Returns:

Error code, IGRAPH_NONSQUARE: non-square matrix. IGRAPH_EINVAL: Negative entry was found in adjacency matrix, or an odd number was found in the diagonal with IGRAPH_LOOPS_TWICE

Time complexity: $O(|V||V|)$, $|V|$ is the number of vertices in the graph.

Example 9.3. File `examples/simple/igraph_adjacency.c`

igraph_weighted_adjacency — Creates a graph from a weighted adjacency matrix.

```
igraph_error_t igraph_weighted_adjacency(  
    igraph_t *graph, const igraph_matrix_t *adjmatrix, igraph_adjacency_t mode,  
    igraph_vector_t *weights, igraph_loops_t loops  
);
```

The order of the vertices in the matrix is preserved, i.e. the vertex corresponding to the first row/column will be vertex with id 0, the next row is for vertex 1, etc.

Arguments:

<i>graph:</i>	Pointer to an uninitialized graph object.
<i>adjmatrix:</i>	The weighted adjacency matrix. How it is interpreted depends on the <i>mode</i> argument. The common feature is that edges with zero weights are considered nonexistent (however, negative weights are permitted).
<i>mode:</i>	Constant to specify how the given matrix is interpreted as an adjacency matrix. Possible values ($A(i,j)$ is the element in row i and column j in the adjacency matrix <i>adjmatrix</i>):

IGRAPH_ADJ_DIRECTED	the graph will be directed and an element gives the weight of the edge between two vertices.
IGRAPH_ADJ_UNDIRECTED	this is the same as IGRAPH_ADJ_MAX, for convenience.
IGRAPH_ADJ_MAX	undirected graph will be created and the weight of the edge between vertices i and j is $\max(A(i,j), A(j,i))$.
IGRAPH_ADJ_MIN	undirected graph will be created with edge weight $\min(A(i,j), A(j,i))$ between vertices i and j .
IGRAPH_ADJ_PLUS	undirected graph will be created with edge weight $A(i,j)+A(j,i)$ between vertices i and j .
IGRAPH_ADJ_UPPER	undirected graph will be created, only the upper right triangle (including the diagonal) is used for the edge weights.
IGRAPH_ADJ_LOWER	undirected graph will be created, only the lower left triangle (including the diagonal) is used for the edge weights.
<i>weights:</i>	Pointer to an initialized vector, the weights will be stored here.
<i>loops:</i>	Constant to specify how the diagonal of the matrix should be treated when creating loop edges.
IGRAPH_NO_LOOPS	Ignore the diagonal of the input matrix and do not create loops.
IGRAPH_LOOPS_ONCE	Treat the diagonal entries as the weight of the loop edge incident on the corresponding vertex.
IGRAPH_LOOPS_TWICE	Treat the diagonal entries as <i>twice</i> the weight of the loop edge incident on the corresponding vertex.

Returns:

Error code, IGRAPH_NONSQUARE: non-square matrix.

Time complexity: $O(|V||V|)$, $|V|$ is the number of vertices in the graph.

Example 9.4. File `examples/simple/igraph_weighted_adjacency.c`

igraph_sparse_adjacency — Creates a graph from a sparse adjacency matrix.

```
igraph_error_t igraph_sparse_adjacency(igraph_t *graph, igraph_sparsemat_t *adjmat,
                                     igraph_adjacency_t mode, igraph_loops_t loops);
```

This has the same functionality as `igraph_adjacency()`, but uses a column-compressed adjacency matrix. Time complexity: $O(|E|)$, where $|E|$ is the number of edges in the graph.

igraph_sparse_weighted_adjacency — Creates a graph from a weighted sparse adjacency matrix.

```
igraph_error_t igraph_sparse_weighted_adjacency(  
    igraph_t *graph, igraph_sparsemat_t *adjmatrix, igraph_adjacency_t mode,  
    igraph_vector_t *weights, igraph_loops_t loops  
);
```

This has the same functionality as `igraph_weighted_adjacency()`, but uses a column-compressed adjacency matrix. Time complexity: $O(|E|)$, where $|E|$ is the number of edges in the graph.

igraph_adjlist — Creates a graph from an adjacency list.

```
igraph_error_t igraph_adjlist(igraph_t *graph, const igraph_adjlist_t *adjlist,  
    igraph_neimode_t mode, igraph_bool_t duplicate);
```

An adjacency list is a list of vectors, containing the neighbors of all vertices. For operations that involve many changes to the graph structure, it is recommended that you convert the graph into an adjacency list via `igraph_adjlist_init()`, perform the modifications (these are cheap for an adjacency list) and then recreate the igraph graph via this function.

Arguments:

- graph*: Pointer to an uninitialized graph object.
- adjlist*: The adjacency list.
- mode*: Whether or not to create a directed graph. `IGRAPH_ALL` means an undirected graph, `IGRAPH_OUT` means a directed graph from an out-adjacency list (i.e. each list contains the successors of the corresponding vertices), `IGRAPH_IN` means a directed graph from an in-adjacency list
- duplicate*: Logical, for undirected graphs this specified whether each edge is included twice, in the vectors of both adjacent vertices. If this is false (0), then it is assumed that every edge is included only once. This argument is ignored for directed graphs.

Returns:

Error code.

See also:

`igraph_adjlist_init()` for the opposite operation.

Time complexity: $O(|V|+|E|)$.

igraph_star — Creates a *star* graph, every vertex connects only to the center.

```
igraph_error_t igraph_star(igraph_t *graph, igraph_integer_t n, igraph_star_mode_t
                           igraph_integer_t center);
```

Arguments:

graph: Pointer to an uninitialized graph object, this will be the result.

n: Integer constant, the number of vertices in the graph.

mode: Constant, gives the type of the star graph to create. Possible values:

IGRAPH_STAR_OUT	directed star graph, edges point <i>from</i> the center to the other vertices.
IGRAPH_STAR_IN	directed star graph, edges point <i>to</i> the center from the other vertices.
IGRAPH_STAR_MUTUAL	directed star graph with mutual edges.
IGRAPH_STAR_UNDIRECTED	an undirected star graph is created.

center: Id of the vertex which will be the center of the graph.

Returns:

Error code:

IGRAPH_EINVALVID invalid number of vertices.

IGRAPH_EINVAL invalid center vertex.

IGRAPH_EINVMODE invalid mode argument.

Time complexity: $O(|V|)$, the number of vertices in the graph.

See also:

`igraph_square_lattice()`, `igraph_ring()`, `igraph_kary_tree()` for creating other regular structures.

Example 9.5. File `examples/simple/igraph_star.c`

`igraph_wheel` — Creates a *wheel* graph, a union of a star and a cycle graph.

```
igraph_error_t igraph_wheel(igraph_t *graph, igraph_integer_t n, igraph_wheel_mode_t
                           igraph_integer_t center);
```

A wheel graph on n vertices can be thought of as a wheel with $n - 1$ spokes. The cycle graph part makes up the rim, while the star graph part adds the spokes.

Note that the two and three-vertex wheel graphs are non-simple: The two-vertex wheel graph contains a self-loop, while the three-vertex wheel graph contains parallel edges (a 1-cycle and a 2-cycle, respectively).

Arguments:

graph: Pointer to an uninitialized graph object, this will be the result.

n: Integer constant, the number of vertices in the graph.

mode: Constant, gives the type of the star graph to create. Possible values:

IGRAPH_WHEEL_OUT	directed wheel graph, edges point <i>from</i> the center to the other vertices.
IGRAPH_WHEEL_IN	directed wheel graph, edges point <i>to</i> the center from the other vertices.
IGRAPH_WHEEL_MUTUAL	directed wheel graph with mutual edges.
IGRAPH_WHEEL_UNDIRECTED	an undirected wheel graph is created.

center: Id of the vertex which will be the center of the graph.

Returns:

Error code:

IGRAPH_EINVVID invalid number of vertices.

IGRAPH_EINVAL invalid center vertex.

IGRAPH_EINVMODE invalid mode argument.

Time complexity: $O(|V|)$, the number of vertices in the graph.

See also:

`igraph_square_lattice()`, `igraph_ring()`, `igraph_star()`,
`igraph_kary_tree()` for creating other regular structures.

igraph_square_lattice — Arbitrary dimensional square lattices.

```
igraph_error_t igraph_square_lattice(  
    igraph_t *graph, const igraph_vector_int_t *dimvector, igraph_integer_t nei,  
    igraph_bool_t directed, igraph_bool_t mutual, const igraph_vector_bool_t *p  
);
```

Creates d-dimensional square lattices of the given size. Optionally, the lattice can be made periodic, and the neighbors within a given graph distance can be connected.

In the zero-dimensional case, the singleton graph is returned.

The vertices of the resulting graph are ordered such that the index of the vertex at position $(i_0, i_1, i_2, \dots, i_d)$ in a lattice of size (n_0, n_1, \dots, n_d) will be $i_0 + n_0 * i_1 + n_0 * n_1 * i_2 + \dots$

Arguments:

graph: An uninitialized graph object.

dimvector: Vector giving the sizes of the lattice in each of its dimensions. The dimension of the lattice will be the same as the length of this vector.

<i>nei</i> :	Integer value giving the distance (number of steps) within which two vertices will be connected.
<i>directed</i> :	Boolean, whether to create a directed graph. If the <code>mutual</code> and <code>circular</code> arguments are not set to true, edges will be directed from lower-index vertices towards higher-index ones.
<i>mutual</i> :	Boolean, if the graph is directed this gives whether to create all connections as mutual.
<i>periodic</i> :	Boolean vector, defines whether the generated lattice is periodic along each dimension. The length of this vector must match the length of <i>dimvector</i> . This parameter may also be NULL, which implies that the lattice will not be periodic.

Returns:

Error code: IGRAPH_EINVAL: invalid (negative) dimension vector or mismatch between the length of the dimension vector and the periodicity vector.

Time complexity: If *nei* is less than two then it is $O(|V|+|E|)$ (as far as I remember), $|V|$ and $|E|$ are the number of vertices and edges in the generated graph. Otherwise it is $O(|V|*d^k+|E|)$, d is the average degree of the graph, k is the *nei* argument.

igraph_ring — Creates a *cycle* graph or a *path* graph.

```
igraph_error_t igraph_ring(igraph_t *graph, igraph_integer_t n, igraph_bool_t directed,
                           igraph_bool_t mutual, igraph_bool_t circular);
```

A circular ring on n vertices is commonly known in graph theory as the cycle graph, and often denoted by C_n . Removing a single edge from the cycle graph C_n results in the path graph P_n . This function can generate both.

When n is 1 or 2, the result may not be a simple graph: the one-cycle contains a self-loop and the undirected or reciprocally connected directed two-cycle contains parallel edges.

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph object.
<i>n</i> :	The number of vertices in the graph.
<i>directed</i> :	Logical, whether to create a directed graph. All edges will be oriented in the same direction along the cycle or path.
<i>mutual</i> :	Logical, whether to create mutual edges in directed graphs. It is ignored for undirected graphs.
<i>circular</i> :	Logical, whether to create a closed ring (a cycle) or an open path.

Returns:

Error code: IGRAPH_EINVAL: invalid number of vertices.

Time complexity: $O(|V|)$, the number of vertices in the graph.

See also:

`igraph_lattice()` for generating more general lattices.

Example 9.6. File `examples/simple/igraph_ring.c`

`igraph_kary_tree` — Creates a k-ary tree in which almost all vertices have k children.

```
igraph_error_t igraph_kary_tree(igraph_t *graph, igraph_integer_t n, igraph_integer_t children,
                                igraph_tree_mode_t type);
```

To obtain a completely symmetric tree with l layers, where each vertex has precisely *children* descendants, use $n = (\text{children}^{(l+1)} - 1) / (\text{children} - 1)$. Such trees are often called k-ary trees, where k refers to the number of children.

Note that for $n=0$, the null graph is returned, which is not considered to be a tree by `igraph_is_tree()`.

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph object.	
<i>n</i> :	Integer, the number of vertices in the graph.	
<i>children</i> :	Integer, the number of children of a vertex in the tree.	
<i>type</i> :	Constant, gives whether to create a directed tree, and if this is the case, also its orientation. Possible values:	
	<code>IGRAPH_TREE_OUT</code>	directed tree, the edges point from the parents to their children,
	<code>IGRAPH_TREE_IN</code>	directed tree, the edges point from the children to their parents.
	<code>IGRAPH_TREE_UNDIRECTED</code>	undirected tree.

Returns:

Error code: `IGRAPH_EINVAL`: invalid number of vertices. `IGRAPH_INVMODE`: invalid mode argument.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges in the graph.

See also:

`igraph_lattice()`, `igraph_star()` for creating other regular structures; `igraph_from_prufer()` for creating arbitrary trees; `igraph_tree_game()` for uniform random sampling of trees.

Example 9.7. File `examples/simple/igraph_kary_tree.c`

`igraph_symmetric_tree` — Creates a symmetric tree with the specified number of branches at each level.

```
igraph_error_t igraph_symmetric_tree(igraph_t *graph, const igraph_vector_int_t  
                                     igraph_tree_mode_t type);
```

This function creates a tree in which all vertices at distance d from the root have *branching_counts*[d] children.

Arguments:

graph: Pointer to an uninitialized graph object.

branches: Vector detailing the number of branches at each level.

type: Constant, gives whether to create a directed tree, and if this is the case, also its orientation. Possible values:

IGRAPH_TREE_OUT	directed tree, the edges point from the parents to their children,
IGRAPH_TREE_IN	directed tree, the edges point from the children to their parents.
IGRAPH_TREE_UNDIRECTED	undirected tree.

Returns:

Error code: IGRAPH_INVMODE: invalid mode argument. IGRAPH_EINVAL: invalid number of children.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges in the graph.

See also:

`igraph_kary_tree()`, `igraph_regular_tree()` and `igraph_star()` for creating other regular tree structures; `igraph_from_prufer()` for creating arbitrary trees; `igraph_tree_game()` for uniform random sampling of trees.

Example 9.8. File `examples/simple/igraph_symmetric_tree.c`

igraph_regular_tree — Creates a regular tree.

```
igraph_error_t igraph_regular_tree(igraph_t *graph, igraph_integer_t h, igraph_
```

All vertices of a regular tree, except its leaves, have the same total degree k . This is different from a k -ary tree (`igraph_kary_tree()`), where all vertices have the same number of children, thus the degree of the root is one less than the degree of the other internal vertices. Regular trees are also referred to as Bethe lattices.

Arguments:

graph: Pointer to an uninitialized graph object.

h: The height of the tree, i.e. the distance between the root and the leaves.

k: The degree of the regular tree.

type: Constant, gives whether to create a directed tree, and if this is the case, also its orientation. Possible values:

IGRAPH_TREE_OUT	directed tree, the edges point from the parents to their children,
IGRAPH_TREE_IN	directed tree, the edges point from the children to their parents.
IGRAPH_TREE_UNDIRECTED	undirected tree.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges in the graph.

See also:

`igraph_kary_tree()` to create k-ary tree where each vertex has the same number of children, i.e. out-degree, instead of the same total degree. `igraph_symmetric_tree()` to use a different number of children at each level.

Example 9.9. File `examples/simple/igraph_regular_tree.c`

`igraph_full` — Creates a full graph (directed or undirected, with or without loops).

```
igraph_error_t igraph_full(igraph_t *graph, igraph_integer_t n, igraph_bool_t directed,  
                           igraph_bool_t loops);
```

In a full graph every possible edge is present, every vertex is connected to every other vertex. A full graph in `igraph` should be distinguished from the concept of complete graphs as used in graph theory. If n is a positive integer, then the complete graph K_n on n vertices is the undirected simple graph with the following property. For any distinct pair (u,v) of vertices in K_n , uv (or equivalently vu) is an edge of K_n . In `igraph`, a full graph on n vertices can be K_n , a directed version of K_n , or K_n with at least one loop edge. In any case, if F is a full graph on n vertices as generated by `igraph`, then K_n is a subgraph of the undirected version of F .

Arguments:

graph: Pointer to an uninitialized graph object.

n: Integer, the number of vertices in the graph.

directed: Logical, whether to create a directed graph.

loops: Logical, whether to include self-edges (loops).

Returns:

Error code: IGRAPH_EINVAL: invalid number of vertices.

Time complexity: $O(|V|+|E|)$, $|V|$ is the number of vertices, $|E|$ the number of edges in the graph. Of course this is the same as $O(|E|)=O(|V||V|)$ here.

See also:

`igraph_square_lattice()`, `igraph_star()`, `igraph_kary_tree()` for creating other regular structures.

Example 9.10. File `examples/simple/igraph_full.c`

`igraph_full_citation` — Creates a full citation graph.

```
igraph_error_t igraph_full_citation(igraph_t *graph, igraph_integer_t n,
                                     igraph_bool_t directed);
```

This is a directed graph, where every $i \rightarrow j$ edge is present if and only if $j < i$. If the `directed` argument is zero then an undirected graph is created, and it is just a full graph.

Arguments:

graph: Pointer to an uninitialized graph object, the result is stored here.

n: The number of vertices.

directed: Whether to create a directed graph. If zero an undirected graph is created.

Returns:

Error code.

Time complexity: $O(|V|^2)$, as we have many edges.

`igraph_full_multipartite` — Create a full multipartite graph.

```
igraph_error_t igraph_full_multipartite(igraph_t *graph,
                                         igraph_vector_int_t *types,
                                         const igraph_vector_int_t *n,
                                         igraph_bool_t directed,
                                         igraph_neimode_t mode);
```

A multipartite graph contains two or more types of vertices and connections are only possible between two vertices of different types. This function creates a complete multipartite graph.

Arguments:

graph: Pointer to an `igraph_t` object, the graph will be created here.

types: Pointer to an integer vector. If not a null pointer, the type of each vertex will be stored here.

n: Pointer to an integer vector, the number of vertices of each type.

directed: Boolean, whether to create a directed graph.

mode: A constant that gives the type of connections for directed graphs. If `IGRAPH_OUT`, then edges point from vertices of low-index vertices to high-index vertices; if

IGRAPH_IN, then the opposite direction is realized; if IGRAPH_ALL, then mutual edges will be created.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

See also:

`igraph_full_bipartite()` for full bipartite graphs.

igraph_turan — Create a Turán graph.

```
igraph_error_t igraph_turan(igraph_t *graph,
                             igraph_vector_int_t *types,
                             igraph_integer_t n,
                             igraph_integer_t r);
```

Turán graphs are complete multipartite graphs with the property that the sizes of the partitions are as close to equal as possible. This function generates undirected graphs. The null graph is returned when the number of vertices is zero. A complete graph is returned if the number of partitions is greater than the number of vertices.

Arguments:

graph: Pointer to an `igraph_t` object, the graph will be created here.

types: Pointer to an integer vector. If not a null pointer, the type (partition index) of each vertex will be stored here.

n: Integer, the number of vertices in the graph.

r: Integer, the number of partitions of the graph, must be positive.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

See also:

`igraph_full_multipartite()` for full multipartite graphs.

igraph_realize_degree_sequence — Generates a graph with the given degree sequence.

```
igraph_error_t igraph_realize_degree_sequence(
    igraph_t *graph,
    const igraph_vector_int_t *outdeg, const igraph_vector_int_t *indeg,
```

```
igraph_edge_type_sw_t allowed_edge_types,  
igraph_realize_degseq_t method);
```

This function generates an undirected graph that realizes a given degree sequence, or a directed graph that realized a given pair of out- and in-degree sequences.

Simple undirected graphs are constructed using the Havel-Hakimi algorithm (undirected case), or the analogous Kleitman-Wang algorithm (directed case). These algorithms work by choosing an arbitrary vertex and connecting all its stubs to other vertices of highest degree. In the directed case, the "highest" (in, out) degree pairs are determined based on lexicographic ordering. This step is repeated until all degrees have been connected up.

Loopless multigraphs are generated using an analogous algorithm: an arbitrary vertex is chosen, and it is connected with a single connection to a highest remaining degree vertex. If self-loops are also allowed, the same algorithm is used, but if a non-zero vertex remains at the end of the procedure, the graph is completed by adding self-loops to it. Thus, the result will contain at most one vertex with self-loops.

The `method` parameter controls the order in which the vertices to be connected are chosen.

References:

V. Havel, Poznámka o existenci konečných grafů (A remark on the existence of finite graphs), *Časopis pro pěstování matematiky* 80, 477-480 (1955). <http://eudml.org/doc/19050>

S. L. Hakimi, On Realizability of a Set of Integers as Degrees of the Vertices of a Linear Graph, *Journal of the SIAM* 10, 3 (1962). <https://www.jstor.org/stable/2098770>

D. J. Kleitman and D. L. Wang, Algorithms for Constructing Graphs and Digraphs with Given Valences and Factors, *Discrete Mathematics* 6, 1 (1973). [https://doi.org/10.1016/0012-365X\(73\)90037-X](https://doi.org/10.1016/0012-365X(73)90037-X)

Sz. Horvát and C. D. Modes, Connectivity matters: Construction and exact random sampling of connected graphs (2020). <https://arxiv.org/abs/2009.03747>

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph object.								
<i>outdeg</i> :	The degree sequence of an undirected graph (if <i>indeg</i> is NULL), or the out-degree sequence of a directed graph (if <i>indeg</i> is given).								
<i>indeg</i> :	The in-degree sequence of a directed graph. Pass NULL to generate an undirected graph.								
<i>allowed_edge_types</i> :	The types of edges to allow in the graph. For directed graphs, only IGRAPH_SIMPLE_SW is implemented at this moment. For undirected graphs, the following values are valid: <table><tr><td>IGRAPH_SIMPLE_SW</td><td>simple graphs (i.e. no self-loops or multi-edges allowed).</td></tr><tr><td>IGRAPH_LOOPS_SW</td><td>single self-loops are allowed, but not multi-edges; currently not implemented.</td></tr><tr><td>IGRAPH_MULTI_SW</td><td>multi-edges are allowed, but not self-loops.</td></tr><tr><td>IGRAPH_LOOPS_SW IGRAPH_MULTI_SW</td><td>both self-loops and multi-edges are allowed.</td></tr></table>	IGRAPH_SIMPLE_SW	simple graphs (i.e. no self-loops or multi-edges allowed).	IGRAPH_LOOPS_SW	single self-loops are allowed, but not multi-edges; currently not implemented.	IGRAPH_MULTI_SW	multi-edges are allowed, but not self-loops.	IGRAPH_LOOPS_SW IGRAPH_MULTI_SW	both self-loops and multi-edges are allowed.
IGRAPH_SIMPLE_SW	simple graphs (i.e. no self-loops or multi-edges allowed).								
IGRAPH_LOOPS_SW	single self-loops are allowed, but not multi-edges; currently not implemented.								
IGRAPH_MULTI_SW	multi-edges are allowed, but not self-loops.								
IGRAPH_LOOPS_SW IGRAPH_MULTI_SW	both self-loops and multi-edges are allowed.								

method:

The method to generate the graph. Possible values:

IGRAPH_REALIZE_DEGSEQ_SMALLEST	The vertex with smallest remaining degree is selected first. The result is usually a graph with high negative degree assortativity. In the undirected case, this method is guaranteed to generate a connected graph, regardless of whether multi-edges are allowed, provided that a connected realization exists (see Horvát and Modes, 2020, as well as http://szhorvat.net/pelican/hh-connected-graphs.html). In the directed case it tends to generate weakly connected graphs, but this is not guaranteed.
IGRAPH_REALIZE_DEGSEQ_LARGEST	The vertex with the largest remaining degree is selected first. The result is usually a graph with high positive degree assortativity, and is often disconnected.
IGRAPH_REALIZE_DEGSEQ_INDEX	The vertices are selected in order of their index (i.e. their position in the degree vector). Note that sorting the degree vector and using the INDEX method is not equivalent to the SMALLEST method above, as SMALLEST uses the smallest <i>remaining</i> degree for selecting vertices, not the smallest <i>initial</i> degree.

Returns:

Error code:

IGRAPH_UNIMPLEMENTED	The requested method is not implemented.
IGRAPH_ENOMEM	There is not enough memory to perform the operation.
IGRAPH_EINVAL	Invalid method parameter, or invalid in- and/or out-degree vectors. The degree vectors should be non-negative, the length and sum of <i>outdeg</i> and <i>indeg</i> should match for directed graphs.

See also:

`igraph_is_graphical()` to test graphicality without generating a graph; `igraph_degree_sequence_game()` to generate random graphs with a given degree sequence; `igraph_k_regular_game()` to generate random regular graphs; `igraph_rewire()` to randomly rewire the edges of a graph while preserving its degree sequence.

Example	9.11.	File	examples/simple/ igraph_realize_degree_sequence.c
----------------	--------------	-------------	--

igraph_famous — Create a famous graph by simply providing its name.

```
igraph_error_t igraph_famous(igraph_t *graph, const char *name);
```

The name of the graph can be simply supplied as a string. Note that this function creates graphs which don't take any parameters, there are separate functions for graphs with parameters, e.g. `igraph_full()` for creating a full graph.

The following graphs are supported:

Bull	The bull graph, 5 vertices, 5 edges, resembles the head of a bull if drawn properly.
Chvatal	This is the smallest triangle-free graph that is both 4-chromatic and 4-regular. According to the Grunbaum conjecture there exists an m -regular, m -chromatic graph with n vertices for every $m > 1$ and $n > 2$. The Chvatal graph is an example for $m=4$ and $n=12$. It has 24 edges.
Coxeter	A non-Hamiltonian cubic symmetric graph with 28 vertices and 42 edges.
Cubical	The Platonic graph of the cube. A convex regular polyhedron with 8 vertices and 12 edges.
Diamond	A graph with 4 vertices and 5 edges, resembles a schematic diamond if drawn properly.
Dodecahedral, Dodecahedron	Another Platonic solid with 20 vertices and 30 edges.
Folkman	The semisymmetric graph with minimum number of vertices, 20 and 40 edges. A semisymmetric graph is regular, edge transitive and not vertex transitive.
Franklin	This is a graph whose embedding to the Klein bottle can be colored with six colors, it is a counterexample to the necessity of the Heawood conjecture on a Klein bottle. It has 12 vertices and 18 edges.
Frucht	The Frucht Graph is the smallest cubical graph whose automorphism group consists only of the identity element. It has 12 vertices and 18 edges.
Grotzsch	The Grötzsch graph is a triangle-free graph with 11 vertices, 20 edges, and chromatic number 4. It is named after German mathematician Herbert Grötzsch, and its existence demonstrates that the assumption of planarity is necessary in Grötzsch's theorem that every triangle-free planar graph is 3-colorable.
Heawood	The Heawood graph is an undirected graph with 14 vertices and 21 edges. The graph is cubic, and all cycles in the graph have

	six or more edges. Every smaller cubic graph has shorter cycles, so this graph is the 6-cage, the smallest cubic graph of girth 6.
Herschel	The Herschel graph is the smallest nonhamiltonian polyhedral graph. It is the unique such graph on 11 nodes, and has 18 edges.
House	The house graph is a 5-vertex, 6-edge graph, the schematic draw of a house if drawn properly, basically a triangle on top of a square.
HouseX	The same as the house graph with an X in the square. 5 vertices and 8 edges.
Icosahedral, Icosahedron	A Platonic solid with 12 vertices and 30 edges.
Krackhardt_Kite	A social network with 10 vertices and 18 edges. Krackhardt, D. Assessing the Political Landscape: Structure, Cognition, and Power in Organizations. Admin. Sci. Quart. 35, 342-369, 1990.
Levi	The graph is a 4-arc transitive cubic graph, it has 30 vertices and 45 edges.
McGee	The McGee graph is the unique 3-regular 7-cage graph, it has 24 vertices and 36 edges.
Meredith	The Meredith graph is a quartic graph on 70 nodes and 140 edges that is a counterexample to the conjecture that every 4-regular 4-connected graph is Hamiltonian.
Noperfectmatching	A connected graph with 16 vertices and 27 edges containing no perfect matching. A matching in a graph is a set of pairwise non-incident edges; that is, no two edges share a common vertex. A perfect matching is a matching which covers all vertices of the graph.
Nonline	A graph whose connected components are the 9 graphs whose presence as a vertex-induced subgraph in a graph makes a non-line graph. It has 50 vertices and 72 edges.
Octahedral, Octahedron	Platonic solid with 6 vertices and 12 edges.
Petersen	A 3-regular graph with 10 vertices and 15 edges. It is the smallest hypohamiltonian graph, i.e. it is non-hamiltonian but removing any single vertex from it makes it Hamiltonian.
Robertson	The unique (4,5)-cage graph, i.e. a 4-regular graph of girth 5. It has 19 vertices and 38 edges.
Smallestcyclicgroup	A smallest nontrivial graph whose automorphism group is cyclic. It has 9 vertices and 15 edges.
Tetrahedral, Tetrahedron	Platonic solid with 4 vertices and 6 edges.
Thomassen	The smallest hypotractable graph, on 34 vertices and 52 edges. A hypotractable graph does not contain a Hamiltonian path but after removing any single vertex from it the remainder always contains a Hamiltonian path. A graph containing a Hamiltonian path is called traceable.
Tutte	Tait's Hamiltonian graph conjecture states that every 3-connected 3-regular planar graph is Hamiltonian. This graph is a counterexample. It has 46 vertices and 69 edges.

Uniquely3colorable	Returns a 12-vertex, triangle-free graph with chromatic number 3 that is uniquely 3-colorable.
Walther	An identity graph with 25 vertices and 31 edges. An identity graph has a single graph automorphism, the trivial one.
Zachary	Social network of friendships between 34 members of a karate club at a US university in the 1970s. See W. W. Zachary, An information flow model for conflict and fission in small groups, Journal of Anthropological Research 33, 452-473 (1977).

Arguments:

graph: Pointer to an uninitialized graph object.

name: Character constant, the name of the graph to be created, it is case insensitive.

Returns:

Error code, IGRAPH_EINVAL if there is no graph with the given name.

See also:

Other functions for creating graph structures: `igraph_ring()`, `igraph_kary_tree()`, `igraph_square_lattice()`, `igraph_full()`.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges in the graph.

igraph_lcf — Creates a graph from LCF notation.

```
igraph_error_t igraph_lcf(igraph_t *graph, igraph_integer_t n, ...);
```

LCF is short for Lederberg-Coxeter-Frucht, it is a concise notation for 3-regular Hamiltonian graphs. It consists of three parameters: the number of vertices in the graph, a list of shifts giving additional edges to a cycle backbone, and another integer giving how many times the shifts should be performed. See <http://mathworld.wolfram.com/LCFNotation.html> for details.

Arguments:

graph: Pointer to an uninitialized graph object.

n: Integer, the number of vertices in the graph.

...: The shifts and the number of repeats for the shifts, plus an additional 0 to mark the end of the arguments.

Returns:

Error code.

See also:

See `igraph_lcf_vector()` for a similar function using a `vector_t` instead of the variable length argument list.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

Example 9.12. File `examples/simple/igraph_lcf.c`

igraph_lcf_vector — Creates a graph from LCF notation.

```
igraph_error_t igraph_lcf_vector(igraph_t *graph, igraph_integer_t n,
                                const igraph_vector_int_t *shifts,
                                igraph_integer_t repeats);
```

This function is essentially the same as `igraph_lcf()`, only the way for giving the arguments is different. See `igraph_lcf()` for details.

Arguments:

graph: Pointer to an uninitialized graph object.
n: Integer constant giving the number of vertices.
shifts: A vector giving the shifts.
repeats: An integer constant giving the number of repeats for the shifts.

Returns:

Error code.

See also:

`igraph_lcf()`, `igraph_extended_chordal_ring()`

Time complexity: $O(|V|+|E|)$, linear in the number of vertices plus the number of edges.

igraph_from_prufer — Generates a tree from a Prüfer sequence.

```
igraph_error_t igraph_from_prufer(igraph_t *graph, const igraph_vector_int_t *p
```

A Prüfer sequence is a unique sequence of integers associated with a labelled tree. A tree on n vertices can be represented by a sequence of $n-2$ integers, each between 0 and $n-1$ (inclusive). The algorithm used by this function is based on Paulius Micikevičius, Saverio Caminiti, Narsingh Deo: Linear-time Algorithms for Encoding Trees as Sequences of Node Labels

Arguments:

graph: Pointer to an uninitialized graph object.
prufer: The Prüfer sequence

Returns:

Error code:

IGRAPH_ENOMEM there is not enough memory to perform the operation.

IGRAPH_EINVAL invalid Prüfer sequence given

See also:

`igraph_to_prufer()`, `igraph_kary_tree()`, `igraph_tree_game()`

igraph_atlas — Create a small graph from the “Graph Atlas”.

```
igraph_error_t igraph_atlas(igraph_t *graph, igraph_integer_t number);
```

The number of the graph is given as a parameter. The graphs are listed:

1. in increasing order of number of nodes;
2. for a fixed number of nodes, in increasing order of the number of edges;
3. for fixed numbers of nodes and edges, in increasing order of the degree sequence, for example $111223 < 112222$;
4. for fixed degree sequence, in increasing number of automorphisms.

The data was converted from the NetworkX software package, see <http://networkx.github.io>.

See *An Atlas of Graphs* by Ronald C. Read and Robin J. Wilson, Oxford University Press, 1998.

Arguments:

graph: Pointer to an uninitialized graph object.

number: The number of the graph to generate.

Added in version 0.2.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

Example 9.13. File `examples/simple/igraph_atlas.c`

igraph_de_bruijn — Generate a de Bruijn graph.

```
igraph_error_t igraph_de_bruijn(igraph_t *graph, igraph_integer_t m, igraph_int_t n);
```

A de Bruijn graph represents relationships between strings. An alphabet of m letters are used and strings of length n are considered. A vertex corresponds to every possible string and there is a directed edge from vertex v to vertex w if the string of v can be transformed into the string of w by removing its first letter and appending a letter to it.

Please note that the graph will have m to the power n vertices and even more edges, so probably you don't want to supply too big numbers for m and n .

De Bruijn graphs have some interesting properties, please see another source, e.g. Wikipedia for details.

Arguments:

graph: Pointer to an uninitialized graph object, the result will be stored here.

m: Integer, the number of letters in the alphabet.

n: Integer, the length of the strings.

Returns:

Error code.

See also:

`igraph_kautz()`.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

igraph_kautz — Generate a Kautz graph.

```
igraph_error_t igraph_kautz(igraph_t *graph, igraph_integer_t m, igraph_integer_t n)
```

A Kautz graph is a labeled graph, vertices are labeled by strings of length $n+1$ above an alphabet with $m+1$ letters, with the restriction that every two consecutive letters in the string must be different. There is a directed edge from a vertex v to another vertex w if it is possible to transform the string of v into the string of w by removing the first letter and appending a letter to it. For string length 1 the new letter cannot equal the old letter, so there are no loops.

Kautz graphs have some interesting properties, see e.g. Wikipedia for details.

Vincent Matossian wrote the first version of this function in R, thanks.

Arguments:

graph: Pointer to an uninitialized graph object, the result will be stored here.

m: Integer, $m+1$ is the number of letters in the alphabet.

n: Integer, $n+1$ is the length of the strings.

Returns:

Error code.

See also:

`igraph_de_bruijn()`.

Time complexity: $O(|V| * [(m+1)/m]^n + |E|)$, in practice it is more like $O(|V|+|E|)$. $|V|$ is the number of vertices, $|E|$ is the number of edges and m and n are the corresponding arguments.

igraph_circulant — Creates a circulant graph.

```
igraph_error_t igraph_circulant(igraph_t *graph, igraph_integer_t n, const igraph_integer_t *shifts)
```

A circulant graph $G(n, \text{shifts})$ consists of n vertices $v_0, \dots, v_{(n-1)}$ such that for each s_i in the list of offsets *shifts*, v_j is connected to $v_{(j + s_i) \bmod n}$ for all j .

The function can generate either directed or undirected graphs. It does not generate multi-edges or self-loops.

Arguments:

graph: Pointer to an uninitialized graph object, the result will be stored here.

n: Integer, the number of vertices in the circulant graph.

shifts: Integer vector, a list of the offsets within the circulant graph.

directed: Boolean, whether to create a directed graph.

Returns:

Error code.

See also:

`igraph_ring()`, `igraph_generalized_petersen()`, `igraph_extended_chordal_ring()`

Time complexity: $O(|V||\text{shifts}|)$, the number of vertices in the graph times the number of shifts.

igraph_generalized_petersen — Creates a Generalized Petersen graph.

```
igraph_error_t igraph_generalized_petersen(igraph_t *graph, igraph_integer_t n, igraph_integer_t k)
```

The generalized Petersen graph $G(n, k)$ consists of n vertices v_0, \dots, v_{n-1} forming an "outer" cycle graph, and n additional vertices u_0, \dots, u_{n-1} forming an "inner" circulant graph where u_i is connected to $u_{(i + k) \bmod n}$. Additionally, all v_i are connected to u_i .

$G(n, k)$ has $2n$ vertices and $3n$ edges. The Petersen graph itself is $G(5, 2)$.

Reference:

M. E. Watkins, A Theorem on Tait Colorings with an Application to the Generalized Petersen Graphs, Journal of Combinatorial Theory 6, 152-164 (1969). <https://doi.org/10.1016%2FS0021-9800%2869%2980116-X>

Arguments:

graph: Pointer to an uninitialized graph object, the result will be stored here.

n: Integer, n is the number of vertices in the inner and outer cycle/circulant graphs. It must be at least 3.

k: Integer, k is the shift of the circulant graph. It must be positive and less than $n/2$.

Returns:

Error code.

See also:

`igraph_famous()` for the original Petersen graph.

Time complexity: $O(|V|)$, the number of vertices in the graph.

`igraph_extended_chordal_ring` — Create an extended chordal ring.

```
igraph_error_t igraph_extended_chordal_ring(  
    igraph_t *graph, igraph_integer_t nodes, const igraph_matrix_int_t *W,  
    igraph_bool_t directed);
```

An extended chordal ring is a cycle graph with additional chords connecting its vertices. Each row L of the matrix W specifies a set of chords to be inserted, in the following way: vertex i will connect to a vertex $L[(i \bmod p)]$ steps ahead of it along the cycle, where p is the length of L . In other words, vertex i will be connected to vertex $(i + L[(i \bmod p)]) \bmod nodes$. If multiple edges are defined in this way, this will output a non-simple graph. The result can be simplified using `igraph_simplify()`.

See also Kotsis, G: Interconnection Topologies for Parallel Processing Systems, PARS Mitteilungen 11, 1-6, 1993. The `igraph` extended chordal rings are not identical to the ones in the paper. In `igraph` the matrix specifies which edges to add. In the paper, a condition is specified which should simultaneously hold between two endpoints and the reverse endpoints.

Arguments:

graph: Pointer to an uninitialized graph object, the result will be stored here.

nodes: Integer constant, the number of vertices in the graph. It must be at least 3.

W: The matrix specifying the extra edges. The number of columns should divide the number of total vertices. The elements are allowed to be negative.

directed: Whether the graph should be directed.

Returns:

Error code.

See also:

`igraph_ring()`, `igraph_lcf()`, `igraph_lcf_vector()`.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

Games: Randomized graph generators

Games are randomized graph generators. Randomization means that they generate a different graph every time you call them.

igraph_grg_game — Generates a geometric random graph.

```
igraph_error_t igraph_grg_game(igraph_t *graph, igraph_integer_t nodes,
                               igraph_real_t radius, igraph_bool_t torus,
                               igraph_vector_t *x, igraph_vector_t *y);
```

A geometric random graph is created by dropping points (i.e. vertices) randomly on the unit square and then connecting all those pairs which are strictly less than `radius` apart in Euclidean distance.

Original code contributed by Keith Briggs, thanks Keith.

Arguments:

- graph*: Pointer to an uninitialized graph object.
- nodes*: The number of vertices in the graph.
- radius*: The radius within which the vertices will be connected.
- torus*: Logical constant. If true, periodic boundary conditions will be used, i.e. the vertices are assumed to be on a torus instead of a square.
- x*: An initialized vector or NULL. If not NULL, the points' x coordinates will be returned here.
- y*: An initialized vector or NULL. If not NULL, the points' y coordinates will be returned here.

Returns:

Error code.

Time complexity: TODO, less than $O(|V|^2+|E|)$.

Example 9.14. File `examples/simple/igraph_grg_game.c`

igraph_barabasi_game — Generates a graph based on the Barabási-Albert model.

```
igraph_error_t igraph_barabasi_game(igraph_t *graph, igraph_integer_t n,
                                     igraph_real_t power,
                                     igraph_integer_t m,
                                     const igraph_vector_int_t *outseq,
                                     igraph_bool_t outpref,
                                     igraph_real_t A,
                                     igraph_bool_t directed,
                                     igraph_barabasi_algorithm_t algo,
                                     const igraph_t *start_from);
```

Arguments:

- graph*: An uninitialized graph object.

<i>n</i> :	The number of vertices in the graph.	
<i>power</i> :	Power of the preferential attachment. The probability that a vertex is cited is proportional to $d^{\text{power}+A}$, where d is its degree (see also the <i>outpref</i> argument), <i>power</i> and <i>A</i> are given by arguments. In the classic preferential attachment model <i>power</i> =1.	
<i>m</i> :	The number of outgoing edges generated for each vertex. (Only if <i>outseq</i> is NULL.)	
<i>outseq</i> :	Gives the (out-)degrees of the vertices. If this is constant, this can be a NULL pointer or an empty (but initialized!) vector, in this case <i>m</i> contains the constant out-degree. The very first vertex has by definition no outgoing edges, so the first number in this vector is ignored.	
<i>outpref</i> :	Boolean, if true not only the in- but also the out-degree of a vertex increases its citation probability. I.e., the citation probability is determined by the total degree of the vertices. Ignored and assumed to be true if the graph being generated is undirected.	
<i>A</i> :	The probability that a vertex is cited is proportional to $d^{\text{power}+A}$, where d is its degree (see also the <i>outpref</i> argument), <i>power</i> and <i>A</i> are given by arguments. In the previous versions of the function this parameter was implicitly set to one.	
<i>directed</i> :	Boolean, whether to generate a directed graph.	
<i>algo</i> :	The algorithm to use to generate the network. Possible values:	
	IGRAPH_BARABASI_BAG	This is the algorithm that was previously (before version 0.6) solely implemented in igraph. It works by putting the IDs of the vertices into a bag (multiset, really), exactly as many times as their (in-)degree, plus once more. Then the required number of cited vertices are drawn from the bag, with replacement. This method might generate multiple edges. It only works if <i>power</i> =1 and <i>A</i> =1.
	IGRAPH_BARABASI_PSUMTREE	This algorithm uses a partial prefix-sum tree to generate the graph. It does not generate multiple edges and works for any <i>power</i> and <i>A</i> values.
	IGRAPH_BARABASI_PSUMTREE_MULTIPLE	This algorithm also uses a partial prefix-sum tree to generate the graph. The difference is, that now multiple edges are allowed. This method was implemented under the name <i>igraph_non-linear_barabasi_game</i> before version 0.6.
<i>start_from</i> :	Either a null pointer, or a graph. In the former case, the starting configuration is a clique of size <i>m</i> . In the latter case, the graph is a starting configuration. The graph must be non-empty, i.e. it must have at least one vertex. If a graph is supplied here and the <i>outseq</i> argument is also given, then <i>outseq</i> should only contain information on the vertices that are not in the <i>start_from</i> graph.	

Returns:

Error code: IGRAPH_EINVAL: invalid n , m or *outseq* parameter.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

Example 9.15. File `examples/simple/igraph_barabasi_game.c`

Example 9.16. File `examples/simple/igraph_barabasi_game2.c`

igraph_erdos_renyi_game — Generates a random (Erdős-Rényi) graph.

```
igraph_error_t igraph_erdos_renyi_game(igraph_t *graph, igraph_erdos_renyi_t type,
                                       igraph_integer_t n, igraph_real_t p_or_m,
                                       igraph_bool_t directed, igraph_bool_t loops);
```

Arguments:

graph: Pointer to an uninitialized graph object.

type: The type of the random graph, possible values:

IGRAPH_ERDOS_RENYI_GNM $G(n,m)$ graph, m edges are selected uniformly randomly in a graph with n vertices.

IGRAPH_ERDOS_RENYI_GNP $G(n,p)$ graph, every possible edge is included in the graph with probability p .

n: The number of vertices in the graph.

p_or_m: This is the p parameter for $G(n,p)$ graphs and the m parameter for $G(n,m)$ graphs.

directed: Logical, whether to generate a directed graph.

loops: Logical, whether to generate loops (self) edges.

Returns:

Error code: IGRAPH_EINVAL: invalid *type*, n , p or m parameter. IGRAPH_ENOMEM: there is not enough memory for the operation.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges in the graph.

See also:

`igraph_barabasi_game()`, `igraph_growing_random_game()`

Example 9.17. File `examples/simple/igraph_erdos_renyi_game.c`

igraph_watts_strogatz_game — The Watts-Strogatz small-world model.

```
igraph_error_t igraph_watts_strogatz_game(igraph_t *graph, igraph_integer_t dim,
                                           igraph_integer_t size, igraph_integer_t nei,
                                           igraph_real_t p, igraph_bool_t loops,
                                           igraph_bool_t multiple);
```

This function generates a graph according to the Watts-Strogatz model of small-world networks. The graph is obtained by creating a circular undirected lattice and then rewiring the edges randomly with a constant probability.

See also: Duncan J Watts and Steven H Strogatz: Collective dynamics of “small world” networks, Nature 393, 440-442, 1998.

Arguments:

graph: The graph to initialize.

dim: The dimension of the lattice.

size: The size of the lattice along each dimension.

nei: The size of the neighborhood for each vertex. This is the same as the *nei* argument of `igraph_connect_neighborhood()`.

p: The rewiring probability. A real number between zero and one (inclusive).

loops: Logical, whether to generate loop edges.

multiple: Logical, whether to allow multiple edges in the generated graph.

Returns:

Error code.

See also:

`igraph_square_lattice()`, `igraph_connect_neighborhood()` and `igraph_rewire_edges()` can be used if more flexibility is needed, e.g. a different type of lattice.

Time complexity: $O(|V| \cdot d^o + |E|)$, $|V|$ and $|E|$ are the number of vertices and edges, d is the average degree, o is the *nei* argument.

igraph_rewire_edges — Rewires the edges of a graph with constant probability.

```
igraph_error_t igraph_rewire_edges(igraph_t *graph, igraph_real_t prob,
                                   igraph_bool_t loops, igraph_bool_t multiple);
```

This function rewires the edges of a graph with a constant probability. More precisely each end point of each edge is rewired to a uniformly randomly chosen vertex with constant probability *prob*.

Note that this function modifies the input *graph*, call `igraph_copy()` if you want to keep it.

Arguments:

graph: The input graph, this will be rewired, it can be directed or undirected.

prob: The rewiring probability a constant between zero and one (inclusive).
loops: Boolean, whether loop edges are allowed in the new graph, or not.
multiple: Boolean, whether multiple edges are allowed in the new graph.

Returns:

Error code.

See also:

`igraph_watts_strogatz_game()` uses this function for the rewiring.

Time complexity: $O(|V|+|E|)$.

igraph_rewire_directed_edges — Rewires the chosen endpoint of directed edges.

```
igraph_error_t igraph_rewire_directed_edges(igraph_t *graph, igraph_real_t prob,
                                             igraph_bool_t loops, igraph_neimode_t mode);
```

This function rewires either the start or end of directed edges in a graph with a constant probability. Correspondingly, either the in-degree sequence or the out-degree sequence of the graph will be preserved.

Note that this function modifies the input *graph*, call `igraph_copy()` if you want to keep it.

This function can produce multiple edges between two vertices.

Arguments:

graph: The input graph, this will be rewired, it can be directed or undirected. If it is undirected or *mode* is set to `IGRAPH_ALL`, `igraph_rewire_edges()` will be called.

prob: The rewiring probability, a constant between zero and one (inclusive).

loops: Boolean, whether loop edges are allowed in the new graph, or not.

mode: The endpoints of directed edges to rewire. It is ignored for undirected graphs. Possible values:

`IGRAPH_OUT` rewire the end of each directed edge

`IGRAPH_IN` rewire the start of each directed edge

`IGRAPH_ALL` rewire both endpoints of each edge

Returns:

Error code.

See also:

`igraph_rewire_edges()`, `igraph_rewire()`

Time complexity: $O(|E|)$.

igraph_degree_sequence_game — Generates a random graph with a given degree sequence.

```
igraph_error_t igraph_degree_sequence_game(igraph_t *graph, const igraph_vector_t *out_deg,
const igraph_vector_int_t *in_deg,
igraph_degseq_t method);
```

Arguments:

- graph*: Pointer to an uninitialized graph object.
- out_deg*: The degree sequence for an undirected graph (if *in_seq* is NULL or of length zero), or the out-degree sequence of a directed graph (if *in_deg* is not of length zero).
- in_deg*: It is either a zero-length vector or NULL (if an undirected graph is generated), or the in-degree sequence.
- method*: The method to generate the graph. Possible values:
- | | |
|------------------------------------|---|
| IGRAPH_DEGSEQ_CONFIGURATION | This method implements the configuration model. For undirected graphs, it puts all vertex IDs in a bag such that the multiplicity of a vertex in the bag is the same as its degree. Then it draws pairs from the bag until the bag becomes empty. This method may generate both loop (self) edges and multiple edges. For directed graphs, the algorithm is basically the same, but two separate bags are used for the in- and out-degrees. Undirected graphs are generated with probability proportional to $(\prod_{i < j} A_{ij} \prod_i A_{ii}!)^{-1}$, where A denotes the adjacency matrix and $!!$ denotes the double factorial. Here A is assumed to have twice the number of self-loops on its diagonal. The corresponding expression for directed graphs is $(\prod_{i, j} A_{ij}!)^{-1}$. Thus the probability of all simple graphs (which only have 0s and 1s in the adjacency matrix) is the same, while that of non-simple ones depends on their edge and self-loop multiplicities. |
| IGRAPH_DEGSEQ_CONFIGURATION_SIMPLE | This method is identical to IGRAPH_DEGSEQ_CONFIGURATION, but if the generated graph is not simple, it rejects it and re-starts the generation. It generates all simple graphs with the same probability. |
| IGRAPH_DEGSEQ_FAST_HEUR_SIMPLE | This method generates simple graphs. It is similar to IGRAPH_DEGSEQ_CONFIGURATION but tries to avoid multiple and loop edges and restarts the generation from scratch if it gets stuck. It can generate all simple realizations of a degree sequence, but it is not guaranteed to sample them uniformly. This method is relative- |

ly fast and it will eventually succeed if the provided degree sequence is graphical, but there is no upper bound on the number of iterations.

IGRAPH_DEGSEQ_EDGE_SWITCHING_SIMPLE

This is an MCMC sampler based on degree-preserving edge switches. It generates simple undirected or directed graphs. It uses `igraph_realize_degree_sequence()` to construct an initial graph, then rewires it using `igraph_rewire()`.

IGRAPH_DEGSEQ_VL

This method samples undirected *connected* graphs approximately uniformly. It is a Monte Carlo method based on degree-preserving edge switches. This generator should be favoured if undirected and connected graphs are to be generated and execution time is not a concern. `igraph` uses the original implementation of Fabien Viger; for the algorithm, see <https://www-complexnetworks.lip6.fr/~latapy/FV/generation.html> and the paper <https://arxiv.org/abs/cs/0502085>

Returns:

Error code: IGRAPH_ENOMEM: there is not enough memory to perform the operation.
IGRAPH_EINVAL: invalid method parameter, or invalid in- and/or out-degree vectors. The degree vectors should be non-negative, *out_deg* should sum up to an even integer for undirected graphs; the length and sum of *out_deg* and *in_deg* should match for directed graphs.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges for IGRAPH_DEGSEQ_EDGE_SWITCHING_SIMPLE. The time complexity of the other modes is not known.

See also:

`igraph_barabasi_game()`, `igraph_erdos_renyi_game()`, `igraph_is_graphical()`

Example	9.18.	File	examples/simple/
igraph_degree_sequence_game.c			

igraph_k_regular_game — Generates a random graph where each vertex has the same degree.

```
igraph_error_t igraph_k_regular_game(igraph_t *graph,
                                     igraph_integer_t no_of_nodes, igraph_integer_t k,
                                     igraph_bool_t directed, igraph_bool_t multiple);
```

This game generates a directed or undirected random graph where the degrees of vertices are equal to a predefined constant *k*. For undirected graphs, at least one of *k* and the number of vertices must be even.

Currently, this game simply uses `igraph_degree_sequence_game` with the SIMPLE_NO_MULTIPLE method and appropriately constructed degree sequences. Therefore, it does not sample uniformly: while it can generate all *k*-regular graphs with the given number of vertices, it does not generate each one with the same probability.

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph object.
<i>no_of_nodes</i> :	The number of nodes in the generated graph.
<i>k</i> :	The degree of each vertex in an undirected graph, or the out-degree and in-degree of each vertex in a directed graph.
<i>directed</i> :	Whether the generated graph will be directed.
<i>multiple</i> :	Whether to allow multiple edges in the generated graph.

Returns:

Error code: IGRAPH_EINVAL: invalid parameter; e.g., negative number of nodes, or odd number of nodes and odd *k* for undirected graphs. IGRAPH_ENOMEM: there is not enough memory for the operation.

Time complexity: $O(|V|+|E|)$ if *multiple* is true, otherwise not known.

igraph_static_fitness_game — Non-growing random graph with edge probabilities proportional to node fitness scores.

```
igraph_error_t igraph_static_fitness_game(igraph_t *graph, igraph_integer_t no_of_nodes,
                                          const igraph_vector_t *fitness_out, const igraph_vector_t *fitness_in,
                                          igraph_bool_t loops, igraph_bool_t multiple);
```

This game generates a directed or undirected random graph where the probability of an edge between vertices *i* and *j* depends on the fitness scores of the two vertices involved. For undirected graphs, each vertex has a single fitness score. For directed graphs, each vertex has an out- and an in-fitness, and the probability of an edge from *i* to *j* depends on the out-fitness of vertex *i* and the in-fitness of vertex *j*.

The generation process goes as follows. We start from *N* disconnected nodes (where *N* is given by the length of the fitness vector). Then we randomly select two vertices *i* and *j*, with probabilities proportional to their fitnesses. (When the generated graph is directed, *i* is selected according to the out-fitnesses and *j* is selected according to the in-fitnesses). If the vertices are not connected yet (or if multiple edges are allowed), we connect them; otherwise we select a new pair. This is repeated until the desired number of links are created.

It can be shown that the *expected* degree of each vertex will be proportional to its fitness, although the actual, observed degree will not be. If you need to generate a graph with an exact degree sequence, consider `igraph_degree_sequence_game` instead.

This model is commonly used to generate static scale-free networks. To achieve this, you have to draw the fitness scores from the desired power-law distribution. Alternatively, you may use `igraph_static_power_law_game` which generates the fitnesses for you with a given exponent.

Reference: Goh K-I, Kahng B, Kim D: Universal behaviour of load distribution in scale-free networks. Phys Rev Lett 87(27):278701, 2001.

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph object.
----------------	---

fitness_out: A numeric vector containing the fitness of each vertex. For directed graphs, this specifies the out-fitness of each vertex.

fitness_in: If NULL, the generated graph will be undirected. If not NULL, this argument specifies the in-fitness of each vertex.

no_of_edges: The number of edges in the generated graph.

loops: Whether to allow loop edges in the generated graph.

multiple: Whether to allow multiple edges in the generated graph.

Returns:

Error code: IGRAPH_EINVAL: invalid parameter IGRAPH_ENOMEM: there is not enough memory for the operation.

Time complexity: $O(|V| + |E| \log |E|)$.

igraph_static_power_law_game — Generates a non-growing random graph with expected power-law degree distributions.

```
igraph_error_t igraph_static_power_law_game(igraph_t *graph,
                                             igraph_integer_t no_of_nodes, igraph_integer_t exponent_out,
                                             igraph_real_t exponent_in, igraph_real_t exponent_out,
                                             igraph_bool_t loops, igraph_bool_t multiple,
                                             igraph_bool_t finite_size_correction);
```

This game generates a directed or undirected random graph where the degrees of vertices follow power-law distributions with prescribed exponents. For directed graphs, the exponents of the in- and out-degree distributions may be specified separately.

The game simply uses `igraph_static_fitness_game` with appropriately constructed fitness vectors. In particular, the fitness of vertex i is $i^{-\alpha}$, where $\alpha = 1/(\gamma-1)$ and γ is the exponent given in the arguments.

To remove correlations between in- and out-degrees in case of directed graphs, the in-fitness vector will be shuffled after it has been set up and before `igraph_static_fitness_game` is called.

Note that significant finite size effects may be observed for exponents smaller than 3 in the original formulation of the game. This function provides an argument that lets you remove the finite size effects by assuming that the fitness of vertex i is $(i+i_0-1)^{-\alpha}$, where i_0 is a constant chosen appropriately to ensure that the maximum degree is less than the square root of the number of edges times the average degree; see the paper of Chung and Lu, and Cho et al for more details.

References:

Goh K-I, Kahng B, Kim D: Universal behaviour of load distribution in scale-free networks. Phys Rev Lett 87(27):278701, 2001.

Chung F and Lu L: Connected components in a random graph with given degree sequences. Annals of Combinatorics 6, 125-145, 2002.

Cho YS, Kim JS, Park J, Kahng B, Kim D: Percolation transitions in scale-free networks under the Achlioptas process. Phys Rev Lett 103:135702, 2009.

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph object.
<i>no_of_nodes</i> :	The number of nodes in the generated graph.
<i>no_of_edges</i> :	The number of edges in the generated graph.
<i>exponent_out</i> :	The power law exponent of the degree distribution. For directed graphs, this specifies the exponent of the out-degree distribution. It must be greater than or equal to 2. If you pass <code>IGRAPH_INFINITY</code> here, you will get back an Erdos-Renyi random network.
<i>exponent_in</i> :	If negative, the generated graph will be undirected. If greater than or equal to 2, this argument specifies the exponent of the in-degree distribution. If non-negative but less than 2, an error will be generated.
<i>loops</i> :	Whether to allow loop edges in the generated graph.
<i>multiple</i> :	Whether to allow multiple edges in the generated graph.
<i>finite_size_correction</i> :	Whether to use the proposed finite size correction of Cho et al.

Returns:

Error code: `IGRAPH_EINVAL`: invalid parameter `IGRAPH_ENOMEM`: there is not enough memory for the operation.

Time complexity: $O(|V| + |E| \log |E|)$.

`igraph_forest_fire_game` — Generates a network according to the “forest fire game”.

```
igraph_error_t igraph_forest_fire_game(igraph_t *graph, igraph_integer_t nodes,
                                         igraph_real_t fw_prob, igraph_real_t bw_factor,
                                         igraph_integer_t pambs, igraph_bool_t directed);
```

The forest fire model intends to reproduce the following network characteristics, observed in real networks:

- Heavy-tailed in-degree distribution.
- Heavy-tailed out-degree distribution.
- Communities.
- Densification power-law. The network is densifying in time, according to a power-law rule.
- Shrinking diameter. The diameter of the network decreases in time.

The network is generated in the following way. One vertex is added at a time. This vertex connects to (cites) *ambs* vertices already present in the network, chosen uniformly random. Now, for each cited vertex *v* we do the following procedure:

1. We generate two random numbers, *x* and *y*, that are geometrically distributed with means $p/(1-p)$ and $rp/(1-rp)$. (*p* is *fw_prob*, *r* is *bw_factor*.) The new vertex cites *x* outgoing

neighbors and y incoming neighbors of v , from those which are not yet cited by the new vertex. If there are less than x or y such vertices available then we cite all of them.

2. The same procedure is applied to all the newly cited vertices.

See also: Jure Leskovec, Jon Kleinberg and Christos Faloutsos. Graphs over time: densification laws, shrinking diameters and possible explanations. *KDD '05: Proceeding of the eleventh ACM SIGKDD international conference on Knowledge discovery in data mining*, 177--187, 2005.

Note however, that the version of the model in the published paper is incorrect in the sense that it cannot generate the kind of graphs the authors claim. A corrected version is available from <http://cs.stanford.edu/people/jure/pubs/powergrowth-tkdd.pdf>, our implementation is based on this.

Arguments:

graph: Pointer to an uninitialized graph object.

nodes: The number of vertices in the graph.

fw_prob: The forward burning probability.

bw_factor: The backward burning ratio. The backward burning probability is calculated as `bw_factor * fw_prob`.

pambs: The number of ambassador vertices.

directed: Whether to create a directed graph.

Returns:

Error code.

Time complexity: TODO.

igraph_rewire — Randomly rewires a graph while preserving its degree sequence.

```
igraph_error_t igraph_rewire(igraph_t *graph, igraph_integer_t n, igraph_rewiring_t mode)
```

This function generates a new graph based on the original one by randomly rewiring edges while preserving the original graph's degree sequence. The rewiring is done "in place", so no new graph will be allocated. If you would like to keep the original graph intact, use `igraph_copy()` beforehand. All graph attributes will be lost.

Arguments:

graph: The graph object to be rewired.

n: Number of rewiring trials to perform.

mode: The rewiring algorithm to be used. It can be one of the following flags:

<code>IGRAPH_REWIRING_SIMPLE</code>	Simple rewiring algorithm which chooses two arbitrary edges in each step (namely (a,b) and (c,d)) and substitutes them with (a,d) and (c,b) if they don't exist. The method will neither destroy nor create self-loops.
-------------------------------------	---

IGRAPH_REWIRING_SIMPLE_LOOPS

Same as IGRAPH_REWIRING_SIMPLE but allows the creation or destruction of self-loops.

Returns:

Error code:

IGRAPH_EINVMODE Invalid rewiring mode.

IGRAPH_EINVAL Graph unsuitable for rewiring (e.g. it has less than 4 nodes in case of IGRAPH_REWIRING_SIMPLE)

IGRAPH_ENOMEM Not enough memory for temporary data.

Time complexity: TODO.

igraph_growing_random_game — Generates a growing random graph.

```
igraph_error_t igraph_growing_random_game(igraph_t *graph, igraph_integer_t n,
                                           igraph_integer_t m, igraph_bool_t directed,
                                           igraph_bool_t citation);
```

This function simulates a growing random graph. We start out with one vertex. In each step a new vertex is added and a number of new edges are also added. These graphs are known to be different from standard (not growing) random graphs.

Arguments:

graph: Uninitialized graph object.

n: The number of vertices in the graph.

m: The number of edges to add in a time step (i.e. after adding a vertex).

directed: Boolean, whether to generate a directed graph.

citation: Boolean, if `true`, the edges always originate from the most recently added vertex and are connected to a previous vertex.

Returns:

Error code: IGRAPH_EINVAL: invalid *n* or *m* parameter.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

igraph_callaway_traits_game — Simulates a growing network with vertex types.

```
igraph_error_t igraph_callaway_traits_game(igraph_t *graph, igraph_integer_t no,
                                           igraph_integer_t types, igraph_integer_t edges_
```

```
const igraph_vector_t *type_dist,  
const igraph_matrix_t *pref_matrix,  
igraph_bool_t directed,  
igraph_vector_int_t *node_type_vec);
```

The different types of vertices prefer to connect other types of vertices with a given probability.

The simulation goes like this: in each discrete time step a new vertex is added to the graph. The type of this vertex is generated based on *type_dist*. Then two vertices are selected uniformly randomly from the graph. The probability that they will be connected depends on the types of these vertices and is taken from *pref_matrix*. Then another two vertices are selected and this is repeated *edges_per_step* times in each time step.

References:

D. S. Callaway, J. E. Hopcroft, J. M. Kleinberg, M. E. J. Newman, and S. H. Strogatz, Are randomly grown graphs really random? Phys. Rev. E 64, 041902 (2001). <https://doi.org/10.1103/PhysRevE.64.041902>

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph.
<i>nodes</i> :	The number of nodes in the graph.
<i>types</i> :	Number of node types.
<i>edges_per_step</i> :	The number of connections tried in each time step.
<i>type_dist</i> :	Vector giving the distribution of the vertex types. If NULL, the distribution is assumed to be uniform.
<i>pref_matrix</i> :	Matrix giving the connection probabilities for the vertex types.
<i>directed</i> :	Logical, whether to generate a directed graph.
<i>node_type_vec</i> :	An initialized vector or NULL. If not NULL, the type of each node will be stored here.

Returns:

Error code.

Added in version 0.2.

Time complexity: $O(|V|*k*\log(|V|))$, $|V|$ is the number of vertices, k is *edges_per_step*.

igraph_establishment_game — Generates a graph with a simple growing model with vertex types.

```
igraph_error_t igraph_establishment_game(igraph_t *graph, igraph_integer_t nodes,  
igraph_integer_t types, igraph_integer_t k,  
const igraph_vector_t *type_dist,  
const igraph_matrix_t *pref_matrix,  
igraph_bool_t directed,
```

```
igraph_vector_int_t *node_type_vec);
```

The simulation goes like this: a single vertex is added at each time step. This new vertex tries to connect to k vertices in the graph. The probability that such a connection is realized depends on the types of the vertices involved.

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph.
<i>nodes</i> :	The number of vertices in the graph.
<i>types</i> :	The number of vertex types.
<i>k</i> :	The number of connections tried in each time step.
<i>type_dist</i> :	Vector giving the distribution of vertex types. If NULL, the distribution is assumed to be uniform.
<i>pref_matrix</i> :	Matrix giving the connection probabilities for different vertex types.
<i>directed</i> :	Logical, whether to generate a directed graph.
<i>node_type_vec</i> :	An initialized vector or NULL. If not NULL, the type of each node will be stored here.

Returns:

Error code.

Added in version 0.2.

Time complexity: $O(|V|*k*\log(|V|))$, $|V|$ is the number of vertices and k is the k parameter.

igraph_preference_game — Generates a graph with vertex types and connection preferences.

```
igraph_error_t igraph_preference_game(igraph_t *graph, igraph_integer_t nodes,
                                     igraph_integer_t types,
                                     const igraph_vector_t *type_dist,
                                     igraph_bool_t fixed_sizes,
                                     const igraph_matrix_t *pref_matrix,
                                     igraph_vector_int_t *node_type_vec,
                                     igraph_bool_t directed,
                                     igraph_bool_t loops);
```

This is practically the nongrowing variant of `igraph_establishment_game()`. A given number of vertices are generated. Every vertex is assigned to a vertex type according to the given type probabilities. Finally, every vertex pair is evaluated and an edge is created between them with a probability depending on the types of the vertices involved.

In other words, this function generates a graph according to a block-model. Vertices are divided into groups (or blocks), and the probability the two vertices are connected depends on their groups only.

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph.
<i>nodes</i> :	The number of vertices in the graph.
<i>types</i> :	The number of vertex types.
<i>type_dist</i> :	Vector giving the distribution of vertex types. If NULL, all vertex types will have equal probability. See also the <i>fixed_sizes</i> argument.
<i>fixed_sizes</i> :	Boolean. If true, then the number of vertices with a given vertex type is fixed and the <i>type_dist</i> argument gives these numbers for each vertex type. If true, and <i>type_dist</i> is NULL, then the function tries to make vertex groups of the same size. If this is not possible, then some groups will have an extra vertex.
<i>pref_matrix</i> :	Matrix giving the connection probabilities for different vertex types. This should be symmetric if the requested graph is undirected.
<i>node_type_vec</i> :	A vector where the individual generated vertex types will be stored. If NULL, the vertex types won't be saved.
<i>directed</i> :	Logical, whether to generate a directed graph. If undirected graphs are requested, only the lower left triangle of the preference matrix is considered.
<i>loops</i> :	Logical, whether loop edges are allowed.

Returns:

Error code.

Added in version 0.3.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges in the graph.

See also:

```
igraph_asymmetric_preference_game(),    igraph_establishment_game(),  
igraph_callaway_traits_game()
```

igraph_asymmetric_preference_game — Generates a graph with asymmetric vertex types and connection preferences.

```
igraph_error_t igraph_asymmetric_preference_game(igraph_t *graph, igraph_integer_t no_out_types,  
                                                  igraph_integer_t no_in_types,  
                                                  const igraph_matrix_t *type_dist_matrix,  
                                                  const igraph_matrix_t *pref_matrix,  
                                                  igraph_vector_int_t *node_type_out_vec,  
                                                  igraph_vector_int_t *node_type_in_vec,  
                                                  igraph_bool_t loops);
```

This is the asymmetric variant of `igraph_preference_game()`. A given number of vertices are generated. Every vertex is assigned to an "outgoing" and an "incoming" vertex type according

to the given joint type probabilities. Finally, every vertex pair is evaluated and a directed edge is created between them with a probability depending on the "outgoing" type of the source vertex and the "incoming" type of the target vertex.

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph.
<i>nodes</i> :	The number of vertices in the graph.
<i>no_out_types</i> :	The number of vertex out-types.
<i>no_in_types</i> :	The number of vertex in-types.
<i>type_dist_matrix</i> :	Matrix of size <code>out_types * in_types</code> , giving the joint distribution of vertex types. If <code>NULL</code> , incoming and outgoing vertex types are independent and uniformly distributed.
<i>pref_matrix</i> :	Matrix of size <code>out_types * in_types</code> , giving the connection probabilities for different vertex types.
<i>node_type_out_vec</i> :	A vector where the individual generated "outgoing" vertex types will be stored. If <code>NULL</code> , the vertex types won't be saved.
<i>node_type_in_vec</i> :	A vector where the individual generated "incoming" vertex types will be stored. If <code>NULL</code> , the vertex types won't be saved.
<i>loops</i> :	Logical, whether loop edges are allowed.

Returns:

Error code.

Added in version 0.3.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges in the graph.

See also:

`igraph_preference_game()`

igraph_recent_degree_game — Stochastic graph generator based on the number of incident edges a node has gained recently.

```
igraph_error_t igraph_recent_degree_game(igraph_t *graph, igraph_integer_t nodes,
                                         igraph_real_t power,
                                         igraph_integer_t time_window,
                                         igraph_integer_t m,
                                         const igraph_vector_int_t *outseq,
                                         igraph_bool_t outpref,
                                         igraph_real_t zero_appeal,
                                         igraph_bool_t directed);
```

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph object.
<i>nodes</i> :	The number of vertices in the graph, this is the same as the number of time steps.
<i>power</i> :	The exponent, the probability that a node gains a new edge is proportional to the number of edges it has gained recently (in the last <i>window</i> time steps) to <i>power</i> .
<i>time_window</i> :	Integer constant, the size of the time window to use to count the number of recent edges.
<i>m</i> :	Integer constant, the number of edges to add per time step if the <i>outseq</i> parameter is a null pointer or a zero-length vector.
<i>outseq</i> :	The number of edges to add in each time step. This argument is ignored if it is a null pointer or a zero length vector. In this case the constant <i>m</i> parameter is used.
<i>outpref</i> :	Logical constant, if true the edges originated by a vertex also count as recent incident edges. For most applications it is reasonable to set it to false.
<i>zero_appeal</i> :	Constant giving the attractiveness of the vertices which haven't gained any edge recently.
<i>directed</i> :	Logical constant, whether to generate a directed graph.

Returns:

Error code.

Time complexity: $O(|V| \cdot \log(|V| + |E|))$, $|V|$ is the number of vertices, $|E|$ is the number of edges in the graph.

igraph_barabasi_aging_game — Preferential attachment with aging of vertices.

```
igraph_error_t igraph_barabasi_aging_game(igraph_t *graph,
                                           igraph_integer_t nodes,
                                           igraph_integer_t m,
                                           const igraph_vector_int_t *outseq,
                                           igraph_bool_t outpref,
                                           igraph_real_t pa_exp,
                                           igraph_real_t aging_exp,
                                           igraph_integer_t aging_bins,
                                           igraph_real_t zero_deg_appeal,
                                           igraph_real_t zero_age_appeal,
                                           igraph_real_t deg_coef,
                                           igraph_real_t age_coef,
                                           igraph_bool_t directed);
```

This game starts with one vertex (if *nodes* > 0). In each step a new node is added, and it is connected to *m* existing nodes. Existing nodes to connect to are chosen with probability dependent on their (in-)degree (*k*) and age (*l*). The degree-dependent part is `deg_coef * kpa_exp + zero_deg_appeal`, while the age-dependent part is `age_coef * laging_exp + zero_age_appeal`, which are summed to obtain the final weight.

The age *l* is based on the number of vertices in the network and the *aging_bins* argument: the age of a node is incremented by 1 after each `floor(nodes / aging_bins) + 1` time steps.

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph object.
<i>nodes</i> :	The number of vertices in the graph.
<i>m</i> :	The number of edges to add in each time step. Ignored if <i>outseq</i> is a non-zero length vector.
<i>outseq</i> :	The number of edges to add in each time step. If it is NULL or a zero-length vector then it is ignored and the <i>m</i> argument is used instead.
<i>outpref</i> :	Logical constant, whether the edges initiated by a vertex contribute to the probability to gain a new edge.
<i>pa_exp</i> :	The exponent of the preferential attachment, a small positive number usually, the value 1 yields the classic linear preferential attachment.
<i>aging_exp</i> :	The exponent of the aging, this is a negative number usually.
<i>aging_bins</i> :	Integer constant, the number of age bins to use.
<i>zero_deg_appeal</i> :	The degree dependent part of the attractiveness of the zero degree vertices.
<i>zero_age_appeal</i> :	The age dependent part of the attractiveness of the vertices of age zero. This parameter is usually zero.
<i>deg_coef</i> :	The coefficient for the degree.
<i>age_coef</i> :	The coefficient for the age.
<i>directed</i> :	Logical constant, whether to generate a directed graph.

Returns:

Error code.

Time complexity: $O((|V|+|V|/\text{aging_bins})\log(|V|+|E|))$. $|V|$ is the number of vertices, $|E|$ the number of edges.

igraph_recent_degree_aging_game — Preferential attachment based on the number of edges gained recently, with aging of vertices.

```
igraph_error_t igraph_recent_degree_aging_game(igraph_t *graph,
                                                igraph_integer_t nodes,
                                                igraph_integer_t m,
                                                const igraph_vector_int_t *outseq,
                                                igraph_bool_t outpref,
                                                igraph_real_t pa_exp,
                                                igraph_real_t aging_exp,
                                                igraph_integer_t aging_bins,
                                                igraph_integer_t time_window,
                                                igraph_real_t zero_appeal,
                                                igraph_bool_t directed);
```

This game is very similar to `igraph_barabasi_aging_game()`, except that instead of the total number of incident edges the number of edges gained in the last `time_window` time steps are counted.

The degree dependent part of the attractiveness is given by k to the power of `pa_exp` plus `zero_appeal`; the age dependent part is l to the power to `aging_exp`. k is the number of edges gained in the last `time_window` time steps, l is the age of the vertex.

Arguments:

<code>graph</code> :	Pointer to an uninitialized graph object.
<code>nodes</code> :	The number of vertices in the graph.
<code>m</code> :	The number of edges to add in each time step. If the <code>outseq</code> argument is not a null vector or a zero-length vector then it is ignored.
<code>outseq</code> :	Vector giving the number of edges to add in each time step. If it is a null pointer or a zero-length vector then it is ignored and the <code>m</code> argument is used.
<code>outpref</code> :	Logical constant, if true the edges initiated by a vertex are also counted. Normally it is false.
<code>pa_exp</code> :	The exponent for the preferential attachment.
<code>aging_exp</code> :	The exponent for the aging, normally it is negative: old vertices gain edges with less probability.
<code>aging_bins</code> :	Integer constant, the number of age bins to use.
<code>time_window</code> :	The time window to use to count the number of incident edges for the vertices.
<code>zero_appeal</code> :	The degree dependent part of the attractiveness for zero degree vertices.
<code>directed</code> :	Logical constant, whether to create a directed graph.

Returns:

Error code.

Time complexity: $O((|V|+|V|/\text{aging_bins})\log(|V|+|E|))$. $|V|$ is the number of vertices, $|E|$ the number of edges.

`igraph_lastcit_game` — Simulates a citation network, based on time passed since the last citation.

```
igraph_error_t igraph_lastcit_game(igraph_t *graph,
                                   igraph_integer_t nodes, igraph_integer_t edges_per_node,
                                   igraph_integer_t agebins,
                                   const igraph_vector_t *preference,
                                   igraph_bool_t directed);
```

This is a quite special stochastic graph generator, it models an evolving graph. In each time step a single vertex is added to the network and it cites a number of other vertices (as specified by the `edges_per_step` argument). The cited vertices are selected based on the last time they were cited. Time is measured by the addition of vertices and it is binned into `agebins` bins. So if the current time step is t and the last citation to a given i vertex was made in time step t_0 , then $\lfloor (t-t_0)/\text{binwidth} \rfloor$

is calculated where $\text{binwidth} = \text{nodes}/\text{agebins}+1$, in the last expression $'/'$ denotes integer division, so the fraction part is omitted.

The *preference* argument specifies the preferences for the citation lags, i.e. its first elements contains the attractivity of the very recently cited vertices, etc. The last element is special, it contains the attractivity of the vertices which were never cited. This element should be bigger than zero.

Note that this function generates networks with multiple edges if *edges_per_step* is bigger than one, call `igraph_simplify()` on the result to get rid of these edges.

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph object, the result will be stored here.
<i>node</i> :	The number of vertices in the network.
<i>edges_per_node</i> :	The number of edges to add in each time step.
<i>agebins</i> :	The number of age bins to use.
<i>preference</i> :	Pointer to an initialized vector of length $\text{agebins}+1$. This contains the 'attractivity' of the various age bins, the last element is the attractivity of the vertices which were never cited, and it should be greater than zero. It is a good idea to have all positive values in this vector. Preferences cannot be negative.
<i>directed</i> :	Logical constant, whether to create directed networks.

Returns:

Error code.

See also:

`igraph_barabasi_aging_game()`.

Time complexity: $O(|V|*a+|E|*\log|V|)$, $|V|$ is the number of vertices, $|E|$ is the total number of edges, a is the *agebins* parameter.

igraph_cited_type_game — Simulates a citation based on vertex types.

```
igraph_error_t igraph_cited_type_game(igraph_t *graph, igraph_integer_t nodes,
                                       const igraph_vector_int_t *types,
                                       const igraph_vector_t *pref,
                                       igraph_integer_t edges_per_step,
                                       igraph_bool_t directed);
```

Function to create a network based on some vertex categories. This function creates a citation network: in each step a single vertex and *edges_per_step* citing edges are added. Nodes with different categories may have different probabilities to get cited, as given by the *pref* vector.

Note that this function might generate networks with multiple edges if *edges_per_step* is greater than one. You might want to call `igraph_simplify()` on the result to remove multiple edges.

Arguments:

graph: Pointer to an uninitialized graph object.

<i>nodes</i> :	The number of vertices in the network.
<i>types</i> :	Numeric vector giving the categories of the vertices, so it should contain <i>nodes</i> non-negative integer numbers. Types are numbered from zero.
<i>pref</i> :	The attractivity of the different vertex categories in a vector. Its length should be the maximum element in <i>types</i> plus one (types are numbered from zero).
<i>edges_per_step</i> :	Integer constant, the number of edges to add in each time step.
<i>directed</i> :	Logical constant, whether to create a directed network.

Returns:

Error code.

See also:

`igraph_citing_cited_type_game()` for a bit more general game.

Time complexity: $O((|V|+|E|)\log|V|)$, $|V|$ and $|E|$ are number of vertices and edges, respectively.

igraph_citing_cited_type_game — Simulates a citation network based on vertex types.

```
igraph_error_t igraph_citing_cited_type_game(igraph_t *graph, igraph_integer_t nodes,
                                              const igraph_vector_int_t *types,
                                              const igraph_matrix_t *pref,
                                              igraph_integer_t edges_per_step,
                                              igraph_bool_t directed);
```

This game is similar to `igraph_cited_type_game()` but here the category of the citing vertex is also considered.

An evolving citation network is modeled here, a single vertex and its *edges_per_step* citation are added in each time step. The odds the a given vertex is cited by the new vertex depends on the category of both the citing and the cited vertex and is given in the *pref* matrix. The categories of the citing vertex correspond to the rows, the categories of the cited vertex to the columns of this matrix. I.e. the element in row *i* and column *j* gives the probability that a *j* vertex is cited, if the category of the citing vertex is *i*.

Note that this function might generate networks with multiple edges if *edges_per_step* is greater than one. You might want to call `igraph_simplify()` on the result to remove multiple edges.

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph object.
<i>nodes</i> :	The number of vertices in the network.
<i>types</i> :	A numeric vector of length <i>nodes</i> , containing the categories of the vertices. The categories are numbered from zero.
<i>pref</i> :	The preference matrix, a square matrix is required, both the number of rows and columns should be the maximum element in <i>types</i> plus one (types are numbered from zero).

edges_per_step: Integer constant, the number of edges to add in each time step.

directed: Logical constant, whether to create a directed network.

Returns:

Error code.

Time complexity: $O((|V|+|E|)\log|V|)$, $|V|$ and $|E|$ are number of vertices and edges, respectively.

igraph_sbm_game — Sample from a stochastic block model.

```
igraph_error_t igraph_sbm_game(igraph_t *graph, igraph_integer_t n,
                                const igraph_matrix_t *pref_matrix,
                                const igraph_vector_int_t *block_sizes,
                                igraph_bool_t directed, igraph_bool_t loops);
```

This function samples graphs from a stochastic block model by (doing the equivalent of) Bernoulli trials for each potential edge with the probabilities given by the Bernoulli rate matrix, *pref_matrix*. See Faust, K., & Wasserman, S. (1992a). Blockmodels: Interpretation and evaluation. Social Networks, 14, 5–61.

The order of the vertex IDs in the generated graph corresponds to the *block_sizes* argument.

Arguments:

graph: The output graph. This should be a pointer to an uninitialized graph.

n: Number of vertices.

pref_matrix: The matrix giving the Bernoulli rates. This is a $K \times K$ matrix, where K is the number of groups. The probability of creating an edge between vertices from groups i and j is given by element (i,j) .

block_sizes: An integer vector giving the number of vertices in each group.

directed: Boolean, whether to create a directed graph. If this argument is false, then *pref_matrix* must be symmetric.

loops: Boolean, whether to create self-loops.

Returns:

Error code.

Time complexity: $O(|V|+|E|+K^2)$, where $|V|$ is the number of vertices, $|E|$ is the number of edges, and K is the number of groups.

See also:

`igraph_erdos_renyi_game()` for a simple Bernoulli graph.

igraph_hsbm_game — Hierarchical stochastic block model.

```
igraph_error_t igraph_hsbm_game(igraph_t *graph, igraph_integer_t n,
                                igraph_integer_t m, const igraph_vector_t *rho,
                                const igraph_matrix_t *C, igraph_real_t p);
```

The function generates a random graph according to the hierarchical stochastic block model.

Arguments:

- graph*: The generated graph is stored here.
- n*: The number of vertices in the graph.
- m*: The number of vertices per block. n/m must be integer.
- rho*: The fraction of vertices per cluster, within a block. Must sum up to 1, and $\rho * m$ must be integer for all elements of *rho*.
- C*: A square, symmetric numeric matrix, the Bernoulli rates for the clusters within a block. Its size must match the size of the *rho* vector.
- p*: The Bernoulli rate of connections between vertices in different blocks.

Returns:

Error code.

See also:

`igraph_sbm_game()` for the classic stochastic block model, `igraph_hsbm_list_game()` for a more general version.

igraph_hsbm_list_game — Hierarchical stochastic block model, more general version.

```
igraph_error_t igraph_hsbm_list_game(igraph_t *graph, igraph_integer_t n,
                                      const igraph_vector_int_t *mlist,
                                      const igraph_vector_list_t *rholist,
                                      const igraph_matrix_list_t *Clist,
                                      igraph_real_t p);
```

The function generates a random graph according to the hierarchical stochastic block model.

Arguments:

- graph*: The generated graph is stored here.
- n*: The number of vertices in the graph.
- mlist*: An integer vector of block sizes.
- rholist*: A list of rho vectors (`igraph_vector_t` objects), one for each block.
- Clist*: A list of square matrices (`igraph_matrix_t` objects), one for each block, specifying the Bernoulli rates of connections within the block.
- p*: The Bernoulli rate of connections between vertices in different blocks.

Returns:

Error code.

See also:

`igraph_sbm_game()` for the classic stochastic block model, `igraph_hsbm_game()` for a simpler general version.

`igraph_dot_product_game` — Generates a random dot product graph.

```
igraph_error_t igraph_dot_product_game(igraph_t *graph, const igraph_matrix_t *
                                     igraph_bool_t directed);
```

In this model, each vertex is represented by a latent position vector. Probability of an edge between two vertices are given by the dot product of their latent position vectors.

See also Christine Leigh Myers Nickel: Random dot product graphs, a model for social networks. Dissertation, Johns Hopkins University, Maryland, USA, 2006.

Arguments:

graph: The output graph is stored here.

vecs: A matrix in which each latent position vector is a column. The dot product of the latent position vectors should be in the $[0,1]$ interval, otherwise a warning is given. For negative dot products, no edges are added; dot products that are larger than one always add an edge.

directed: Should the generated graph be directed?

Returns:

Error code.

Time complexity: $O(n*n*m)$, where n is the number of vertices, and m is the length of the latent vectors.

See also:

`igraph_sample_dirichlet()`, `igraph_sample_sphere_volume()`, `igraph_sample_sphere_surface()` for functions to generate the latent vectors.

`igraph_tree_game` — Generates a random tree with the given number of nodes.

```
igraph_error_t igraph_tree_game(igraph_t *graph, igraph_integer_t n, igraph_bool_t
```

This function samples uniformly from the set of labelled trees, i.e. it generates each labelled tree with the same probability.

Note that for $n=0$, the null graph is returned, which is not considered to be a tree by `igraph_is_tree()`.

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph object.	
<i>n</i> :	The number of nodes in the tree.	
<i>directed</i> :	Whether to create a directed tree. The edges are oriented away from the root.	
<i>method</i> :	The algorithm to use to generate the tree. Possible values:	
	IGRAPH_RANDOM_TREE_PRUFER	This algorithm samples Prüfer sequences uniformly, then converts them to trees. Directed trees are not currently supported.
	IGRAPH_RANDOM_LERW	This algorithm effectively performs a loop-erased random walk on the complete graph to uniformly sample its spanning trees (Wilson's algorithm).

Returns:

Error code: IGRAPH_ENOMEM: there is not enough memory to perform the operation.
IGRAPH_EINVAL: invalid tree size

See also:

`igraph_from_prufer()`

`igraph_correlated_game` — Generates a random graph correlated to an existing graph.

```
igraph_error_t igraph_correlated_game(const igraph_t *old_graph, igraph_t *new_graph,  
                                     igraph_real_t corr, igraph_real_t p,  
                                     const igraph_vector_int_t *permutation);
```

Sample a new graph by perturbing the adjacency matrix of a given simple graph and shuffling its vertices.

Arguments:

<i>old_graph</i> :	The original graph, it must be simple.
<i>new_graph</i> :	The new graph will be stored here.
<i>corr</i> :	A scalar in the unit interval $[0,1]$, the target Pearson correlation between the adjacency matrices of the original and the generated graph (the adjacency matrix being used as a vector).
<i>p</i> :	A numeric scalar, the probability of an edge between two vertices, it must in the open $(0,1)$ interval. Typically, the density of <i>old_graph</i> .
<i>permutation</i> :	A permutation to apply to the vertices of the generated graph. It can also be a null pointer, in which case the vertices will not be permuted.

Returns:

Error code

See also:

`igraph_correlated_pair_game()` for generating a pair of correlated random graphs in one go.

`igraph_correlated_pair_game` — Generates pairs of correlated random graphs.

```
igraph_error_t igraph_correlated_pair_game(igraph_t *graph1, igraph_t *graph2,  
                                             igraph_integer_t n, igraph_real_t corr, igraph_  
                                             igraph_bool_t directed,  
                                             const igraph_vector_int_t *permutation);
```

Sample two random graphs, with given correlation.

Arguments:

<i>graph1</i> :	The first graph will be stored here.
<i>graph2</i> :	The second graph will be stored here.
<i>n</i> :	The number of vertices in both graphs.
<i>corr</i> :	A scalar in the unit interval, the target Pearson correlation between the adjacency matrices of the original the generated graph (the adjacency matrix being used as a vector).
<i>p</i> :	A numeric scalar, the probability of an edge between two vertices, it must in the open (0,1) interval.
<i>directed</i> :	Whether to generate directed graphs.
<i>permutation</i> :	A permutation to apply to the vertices of the second graph. It can also be a null pointer, in which case the vertices will not be permuted.

Returns:

Error code

See also:

`igraph_correlated_game()` for generating a correlated pair to a given graph.

`igraph_simple_interconnected_islands_game` — Generates a random graph made of several interconnected islands, each island being a random graph.

```
igraph_error_t igraph_simple_interconnected_islands_game(  
    igraph_t *graph,  
    igraph_integer_t islands_n,  
    igraph_integer_t islands_size,  
    igraph_real_t islands_pin,  
    igraph_integer_t n_inter);
```

All islands are of the same size. Within an island, each edge is generated with the same probability. A fixed number of additional edges are then generated for each unordered pair of islands to connect them. The generated graph is guaranteed to be simple.

Arguments:

graph: Pointer to an uninitialized graph object.

islands_n: The number of islands in the graph.

islands_size: The size of islands in the graph.

islands_pin: The probability to create each possible edge within islands.

n_inter: The number of edges to create between two islands. It may be larger than *islands_size* squared, but in this case it is assumed to be *islands_size* squared.

Returns:

Error code: IGRAPH_EINVAL: invalid parameter IGRAPH_ENOMEM: there is not enough memory for the operation.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges in the graph.

Deprecated functions

igraph_lattice — Arbitrary dimensional square lattices (deprecated).

```
igraph_error_t igraph_lattice(igraph_t *graph, const igraph_vector_int_t *dimvec,  
    igraph_integer_t nei, igraph_bool_t directed, igraph_bool_t t,  
    igraph_bool_t circular);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_square_lattice()` instead.

igraph_tree — Creates a k-ary tree in which almost all vertices have k children (deprecated alias).

```
igraph_error_t igraph_tree(igraph_t *graph, igraph_integer_t n, igraph_integer_t  
                           igraph_tree_mode_t type);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_kary_tree()` instead.

Chapter 10. Games on graphs

Microscopic update rules

`igraph_deterministic_optimal_imitation` — Adopt a strategy via deterministic optimal imitation.

```
igraph_error_t igraph_deterministic_optimal_imitation(const igraph_t *graph,
    igraph_integer_t vid,
    igraph_optimal_t optimality,
    const igraph_vector_t *quantities,
    igraph_vector_int_t *strategies,
    igraph_neimode_t mode);
```

A simple deterministic imitation strategy where a vertex revises its strategy to that which yields a local optimum. Here "local" is with respect to the immediate neighbours of the vertex. The vertex retains its current strategy where this strategy yields a locally optimal quantity. The quantity in this case could be a measure such as fitness.

Arguments:

- graph*: The graph object representing the game network. This cannot be the empty or trivial graph, but must have at least two vertices and one edge. If *graph* has one vertex, then no strategy update would take place. Furthermore, if *graph* has at least two vertices but zero edges, then strategy update would also not take place.
- vid*: The vertex whose strategy is to be updated. It is assumed that *vid* represents a vertex in *graph*. No checking is performed and it is your responsibility to ensure that *vid* is indeed a vertex of *graph*. If an isolated vertex is provided, i.e. the input vertex has degree 0, then no strategy update would take place and *vid* would retain its current strategy. Strategy update would also not take place if the local neighbourhood of *vid* are its in-neighbours (respectively out-neighbours), but *vid* has zero in-neighbours (respectively out-neighbours). Loops are ignored in computing the degree (in, out, all) of *vid*.
- optimality*: Logical; controls the type of optimality to be used. Supported values are:
- | | |
|-----------------------------|---|
| <code>IGRAPH_MAXIMUM</code> | Use maximum deterministic imitation, where the strategy of the vertex with maximum quantity (e.g. fitness) would be adopted. We update the strategy of <i>vid</i> to that which yields a local maximum. |
| <code>IGRAPH_MINIMUM</code> | Use minimum deterministic imitation. That is, the strategy of the vertex with minimum quantity would be imitated. In other words, update to the strategy that yields a local minimum. |
- quantities*: A vector of quantities providing the quantity of each vertex in *graph*. Think of each entry of the vector as being generated by a function such as the fitness function for the game. So if the vector represents fitness quantities, then each vector entry is the fitness of some vertex. The length of this vector must be the same as the number of vertices in the vertex set of *graph*.
- strategies*: A vector of the current strategies for the vertex population. The updated strategy for *vid* would be stored here. Each strategy is identified with a nonnegative integer,

whose interpretation depends on the payoff matrix of the game. Generally we use the strategy ID as a row or column index of the payoff matrix. The length of this vector must be the same as the number of vertices in the vertex set of *graph*.

mode: Defines the sort of neighbourhood to consider for *vid*. If *graph* is undirected, then we use all the immediate neighbours of *vid*. Thus if you know that *graph* is undirected, then it is safe to pass the value *IGRAPH_ALL* here. Supported values are:

IGRAPH_OUT Use the out-neighbours of *vid*. This option is only relevant when *graph* is a directed graph.

IGRAPH_IN Use the in-neighbours of *vid*. Again this option is only relevant when *graph* is a directed graph.

IGRAPH_ALL Use both the in- and out-neighbours of *vid*. This option is only relevant if *graph* is a digraph. Also use this value if *graph* is undirected.

Returns:

The error code *IGRAPH_EINVAL* is returned in each of the following cases: (1) Any of the parameters *graph*, *quantities*, or *strategies* is a null pointer. (2) The vector *quantities* or *strategies* has a length different from the number of vertices in *graph*. (3) The parameter *graph* is the empty or null graph, i.e. the graph with zero vertices and edges.

Time complexity: $O(2d)$, where d is the degree of the vertex *vid*.

Example 10.1. File **examples/simple/igraph_deterministic_optimal_imitation.c**

igraph_moran_process — The Moran process in a network setting.

```
igraph_error_t igraph_moran_process(const igraph_t *graph,
                                   const igraph_vector_t *weights,
                                   igraph_vector_t *quantities,
                                   igraph_vector_int_t *strategies,
                                   igraph_neimode_t mode);
```

This is an extension of the classic Moran process to a network setting. The Moran process is a model of haploid (asexual) reproduction within a population having a fixed size. In the network setting, the Moran process operates on a weighted graph. At each time step a vertex *a* is chosen for reproduction and another vertex *b* is chosen for death. Vertex *a* gives birth to an identical clone *c*, which replaces *b*. Vertex *c* is a clone of *a* in that *c* inherits both the current quantity (e.g. fitness) and current strategy of *a*.

The graph *G* representing the game network is assumed to be simple, i.e. free of loops and without multiple edges. If, on the other hand, *G* has a loop incident on some vertex *v*, then it is possible that when *v* is chosen for reproduction it would forgo this opportunity. In particular, when *v* is chosen for reproduction and *v* is also chosen for death, the clone of *v* would be *v* itself with its current vertex ID. In effect *v* forgoes its chance for reproduction.

Arguments:

graph: The graph object representing the game network. This cannot be the empty or trivial graph, but must have at least two vertices and one edge. The Moran process will

not take place in each of the following cases: (1) If *graph* has one vertex. (2) If *graph* has at least two vertices but zero edges.

weights: A vector of all edge weights for *graph*. Thus *weights*[*i*] means the weight of the edge with edge ID *i*. For the purpose of the Moran process, each weight is assumed to be positive; it is your responsibility to ensure this condition holds. The length of this vector must be the same as the number of edges in *graph*.

quantities: A vector of quantities providing the quantity of each vertex in *graph*. The quantity of the new clone will be stored here. Think of each entry of the vector as being generated by a function such as the fitness function for the game. So if the vector represents fitness quantities, then each vector entry is the fitness of some vertex. The length of this vector must be the same as the number of vertices in the vertex set of *graph*. For the purpose of the Moran process, each vector entry is assumed to be nonnegative; no checks will be performed for this. It is your responsibility to ensure that at least one entry is positive. Furthermore, this vector cannot be a vector of zeros; this condition will be checked.

strategies: A vector of the current strategies for the vertex population. The strategy of the new clone will be stored here. Each strategy is identified with a nonnegative integer, whose interpretation depends on the payoff matrix of the game. Generally we use the strategy ID as a row or column index of the payoff matrix. The length of this vector must be the same as the number of vertices in the vertex set of *graph*.

mode: Defines the sort of neighbourhood to consider for the vertex a chosen for reproduction. This is only relevant if *graph* is directed. If *graph* is undirected, then it is safe to pass the value *IGRAPH_ALL* here. Supported values are:

IGRAPH_OUT Use the out-neighbours of *a*. This option is only relevant when *graph* is directed.

IGRAPH_IN Use the in-neighbours of *a*. Again this option is only relevant when *graph* is directed.

IGRAPH_ALL Use both the in- and out-neighbours of *a*. This option is only relevant if *graph* is directed. Also use this value if *graph* is undirected.

Returns:

The error code *IGRAPH_EINVAL* is returned in each of the following cases: (1) Any of the parameters *graph*, *weights*, *quantities* or *strategies* is a null pointer. (2) The vector *quantities* or *strategies* has a length different from the number of vertices in *graph*. (3) The vector *weights* has a length different from the number of edges in *graph*. (4) The parameter *graph* is the empty or null graph, i.e. the graph with zero vertices and edges. (5) The vector *weights*, or the combination of interest, sums to zero. (6) The vector *quantities*, or the combination of interest, sums to zero.

Time complexity: depends on the random number generator, but is usually $O(n)$ where *n* is the number of vertices in *graph*.

References:

- (Lieberman et al. 2005) E. Lieberman, C. Hauert, and M. A. Nowak. Evolutionary dynamics on graphs. *Nature*, 433(7023):312--316, 2005.
- (Moran 1958) P. A. P. Moran. Random processes in genetics. *Mathematical Proceedings of the Cambridge Philosophical Society*, 54(1):60--71, 1958.

igraph_roulette_wheel_imitation — Adopt a strategy via roulette wheel selection.

```
igraph_error_t igraph_roulette_wheel_imitation(const igraph_t *graph,
                                              igraph_integer_t vid,
                                              igraph_bool_t islocal,
                                              const igraph_vector_t *quantities,
                                              igraph_vector_int_t *strategies,
                                              igraph_neimode_t mode);
```

A simple stochastic imitation strategy where a vertex revises its strategy to that of a vertex *u* chosen proportionate to *u*'s quantity (e.g. fitness). This is a special case of stochastic imitation, where a candidate is not chosen uniformly at random but proportionate to its quantity.

Arguments:

- graph*: The graph object representing the game network. This cannot be the empty or trivial graph, but must have at least two vertices and one edge. If *graph* has one vertex, then no strategy update would take place. Furthermore, if *graph* has at least two vertices but zero edges, then strategy update would also not take place.
- vid*: The vertex whose strategy is to be updated. It is assumed that *vid* represents a vertex in *graph*. No checking is performed and it is your responsibility to ensure that *vid* is indeed a vertex of *graph*. If an isolated vertex is provided, i.e. the input vertex has degree 0, then no strategy update would take place and *vid* would retain its current strategy. Strategy update would also not take place if the local neighbourhood of *vid* are its in-neighbours (respectively out-neighbours), but *vid* has zero in-neighbours (respectively out-neighbours). Loops are ignored in computing the degree (in, out, all) of *vid*.
- islocal*: Boolean; this flag controls which perspective to use in computing the relative quantity. If true then we use the local perspective; otherwise we use the global perspective. The local perspective for *vid* is the set of all immediate neighbours of *vid*. In contrast, the global perspective for *vid* is the vertex set of *graph*.
- quantities*: A vector of quantities providing the quantity of each vertex in *graph*. Think of each entry of the vector as being generated by a function such as the fitness function for the game. So if the vector represents fitness quantities, then each vector entry is the fitness of some vertex. The length of this vector must be the same as the number of vertices in the vertex set of *graph*. For the purpose of roulette wheel selection, each vector entry is assumed to be nonnegative; no checks will be performed for this. It is your responsibility to ensure that at least one entry is nonzero. Furthermore, this vector cannot be a vector of zeros; this condition will be checked.
- strategies*: A vector of the current strategies for the vertex population. The updated strategy for *vid* would be stored here. Each strategy is identified with a nonnegative integer, whose interpretation depends on the payoff matrix of the game. Generally we use the strategy ID as a row or column index of the payoff matrix. The length of this vector must be the same as the number of vertices in the vertex set of *graph*.
- mode*: Defines the sort of neighbourhood to consider for *vid*. This is only relevant if we are considering the local perspective, i.e. if *islocal* is true. If we are considering the global perspective, then it is safe to pass the value `IGRAPH_ALL` here. If *graph* is undirected, then we use all the immediate neighbours of *vid*. Thus if you know that *graph* is undirected, then it is safe to pass the value `IGRAPH_ALL` here. Supported values are:

IGRAPH_OUT	Use the out-neighbours of <i>vid</i> . This option is only relevant when <i>graph</i> is a digraph and we are considering the local perspective.
IGRAPH_IN	Use the in-neighbours of <i>vid</i> . Again this option is only relevant when <i>graph</i> is a directed graph and we are considering the local perspective.
IGRAPH_ALL	Use both the in- and out-neighbours of <i>vid</i> . This option is only relevant if <i>graph</i> is a digraph. Also use this value if <i>graph</i> is undirected or we are considering the global perspective.

Returns:

The error code `IGRAPH_EINVAL` is returned in each of the following cases: (1) Any of the parameters *graph*, *quantities*, or *strategies* is a null pointer. (2) The vector *quantities* or *strategies* has a length different from the number of vertices in *graph*. (3) The parameter *graph* is the empty or null graph, i.e. the graph with zero vertices and edges. (4) The vector *quantities* sums to zero.

Time complexity: $O(n)$ where n is the number of vertices in the perspective to consider. If we consider the global perspective, then n is the number of vertices in the vertex set of *graph*. On the other hand, for the local perspective n is the degree of *vid*, excluding loops.

Reference:

(Yu & Gen 2010) X. Yu and M. Gen. *Introduction to Evolutionary Algorithms*. Springer, 2010, pages 18--20.

Example	10.2.	File	examples/simple/
		igraph_roulette_wheel_imitation.c	

igraph_stochastic_imitation — Adopt a strategy via stochastic imitation with uniform selection.

```
igraph_error_t igraph_stochastic_imitation(const igraph_t *graph,
                                           igraph_integer_t vid,
                                           igraph_imitate_algorithm_t algo,
                                           const igraph_vector_t *quantities,
                                           igraph_vector_int_t *strategies,
                                           igraph_neimode_t mode);
```

A simple stochastic imitation strategy where a vertex revises its strategy to that of a vertex chosen uniformly at random from its local neighbourhood. This is called stochastic imitation via uniform selection, where the strategy to imitate is chosen via some random process. For the purposes of this function, we use uniform selection from a pool of candidates.

Arguments:

<i>graph</i> :	The graph object representing the game network. This cannot be the empty or trivial graph, but must have at least two vertices and one edge. If <i>graph</i> has one vertex, then no strategy update would take place. Furthermore, if <i>graph</i> has at least two vertices but zero edges, then strategy update would also not take place.
<i>vid</i> :	The vertex whose strategy is to be updated. It is assumed that <i>vid</i> represents a vertex in <i>graph</i> . No checking is performed and it is your responsibility to ensure

that *vid* is indeed a vertex of *graph*. If an isolated vertex is provided, i.e. the input vertex has degree 0, then no strategy update would take place and *vid* would retain its current strategy. Strategy update would also not take place if the local neighbourhood of *vid* are its in-neighbours (respectively out-neighbours), but *vid* has zero in-neighbours (respectively out-neighbours). Loops are ignored in computing the degree (in, out, all) of *vid*.

algo: This flag controls which algorithm to use in stochastic imitation. Supported values are:

`IGRAPH_IMITATE_AUGMENTED` Augmented imitation. Vertex *vid* imitates the strategy of the chosen vertex *u* provided that doing so would increase the quantity (e.g. fitness) of *vid*. Augmented imitation can be thought of as "imitate if better".

`IGRAPH_IMITATE_BLIND` Blind imitation. Vertex *vid* blindly imitates the strategy of the chosen vertex *u*, regardless of whether doing so would increase or decrease the quantity of *vid*.

`IGRAPH_IMITATE_CONTRACTED` Contracted imitation. Here vertex *vid* imitates the strategy of the chosen vertex *u* if doing so would decrease the quantity of *vid*. Think of contracted imitation as "imitate if worse".

quantities: A vector of quantities providing the quantity of each vertex in *graph*. Think of each entry of the vector as being generated by a function such as the fitness function for the game. So if the vector represents fitness quantities, then each vector entry is the fitness of some vertex. The length of this vector must be the same as the number of vertices in the vertex set of *graph*.

strategies: A vector of the current strategies for the vertex population. The updated strategy for *vid* would be stored here. Each strategy is identified with a nonnegative integer, whose interpretation depends on the payoff matrix of the game. Generally we use the strategy ID as a row or column index of the payoff matrix. The length of this vector must be the same as the number of vertices in the vertex set of *graph*.

mode: Defines the sort of neighbourhood to consider for *vid*. If *graph* is undirected, then we use all the immediate neighbours of *vid*. Thus if you know that *graph* is undirected, then it is safe to pass the value `IGRAPH_ALL` here. Supported values are:

`IGRAPH_OUT` Use the out-neighbours of *vid*. This option is only relevant when *graph* is a directed graph.

`IGRAPH_IN` Use the in-neighbours of *vid*. Again this option is only relevant when *graph* is a directed graph.

`IGRAPH_ALL` Use both the in- and out-neighbours of *vid*. This option is only relevant if *graph* is a digraph. Also use this value if *graph* is undirected.

Returns:

The error code `IGRAPH_EINVAL` is returned in each of the following cases: (1) Any of the parameters *graph*, *quantities*, or *strategies* is a null pointer. (2) The vector *quantities* or *strategies* has a length different from the number of vertices in *graph*. (3) The parameter

graph is the empty or null graph, i.e. the graph with zero vertices and edges. (4) The parameter *algo* refers to an unsupported stochastic imitation algorithm.

Time complexity: depends on the uniform random number generator, but should usually be $O(1)$.

Example	10.3.	File	examples/simple/
igraph_stochastic_imitation.c			

Epidemic models

igraph_sir — Performs a number of SIR epidemics model runs on a graph.

```
igraph_error_t igraph_sir(const igraph_t *graph, igraph_real_t beta,
                          igraph_real_t gamma, igraph_integer_t no_sim,
                          igraph_vector_ptr_t *result);
```

The SIR model is a simple model from epidemiology. The individuals of the population might be in three states: susceptible, infected and recovered. Recovered people are assumed to be immune to the disease. Susceptibles become infected with a rate that depends on their number of infected neighbors. Infected people become recovered with a constant rate. See these parameters below.

This function runs multiple simulations, all starting with a single uniformly randomly chosen infected individual. A simulation is stopped when no infected individuals are left.

Arguments:

<i>graph</i> :	The graph to perform the model on. For directed graphs edge directions are ignored and a warning is given.
<i>beta</i> :	The rate of infection of an individual that is susceptible and has a single infected neighbor. The infection rate of a susceptible individual with n infected neighbors is n times β . Formally this is the rate parameter of an exponential distribution.
<i>gamma</i> :	The rate of recovery of an infected individual. Formally, this is the rate parameter of an exponential distribution.
<i>no_sim</i> :	The number of simulation runs to perform.
<i>result</i> :	The result of the simulation is stored here, in a list of <code>igraph_sir_t</code> objects. To deallocate memory, the user needs to call <code>igraph_sir_destroy</code> on each element, before destroying the pointer vector itself using <code>igraph_vector_ptr_destroy_all()</code> .

Returns:

Error code.

Time complexity: $O(\text{no_sim} * (|V| + |E| \log(|V|)))$.

igraph_sir_t — The result of one SIR model simulation.

```
typedef struct igraph_sir_t {  
    igraph_vector_t times;  
    igraph_vector_int_t no_s, no_i, no_r;  
} igraph_sir_t;
```

Data structure to store the results of one simulation of the SIR (susceptible-infected-recovered) model on a graph. It has the following members. They are all (real or integer) vectors, and they are of the same length.

Values:

`times`: A vector, the times of the events are stored here.

`no_s`: An integer vector, the number of susceptibles in each time step is stored here.

`no_i`: An integer vector, the number of infected individuals at each time step, is stored here.

`no_r`: An integer vector, the number of recovered individuals is stored here at each time step.

igraph_sir_destroy — Deallocates memory associated with a SIR simulation run.

```
void igraph_sir_destroy(igraph_sir_t *sir);
```

Arguments:

`sir`: The `igraph_sir_t` object storing the simulation.

Chapter 11. Vertex and edge selectors and sequences, iterators

About selectors, iterators

Everything about vertices and vertex selectors also applies to edges and edge selectors unless explicitly noted otherwise.

The vertex (and edge) selector notion was introduced in igraph 0.2. It is a way to reference a sequence of vertices or edges independently of the graph.

While this might sound quite mysterious, it is actually very simple. For example, all vertices of a graph can be selected by `igraph_vs_all()` and the graph independence means that `igraph_vs_all()` is not parametrized by a graph object. That is, `igraph_vs_all()` is the general *concept* of selecting all vertices of a graph. A vertex selector is then a way to specify the class of vertices to be visited. The selector might specify that all vertices of a graph or all the neighbours of a vertex are to be visited. A vertex selector is a way of saying that you want to visit a bunch of vertices, as opposed to a vertex iterator which is a concrete plan for visiting each of the chosen vertices of a specific graph.

To determine the actual vertex IDs implied by a vertex selector, you need to apply the concept of selecting vertices to a specific graph object. This can be accomplished by instantiating a vertex iterator using a specific vertex selection concept and a specific graph object. The notion of vertex iterators can be thought of in the following way. Given a specific graph object and the class of vertices to be visited, a vertex iterator is a road map, plan or route for how to visit the chosen vertices.

Some vertex selectors have *immediate* versions. These have the prefix `igraph_vss` instead of `igraph_vs`, e.g. `igraph_vss_all()` instead of `igraph_vs_all()`. The immediate versions are to be used in the parameter list of the igraph functions, such as `igraph_degree()`. These functions are not associated with any `igraph_vs_t` object, so they have no separate constructors and destructors (destroy functions).

Vertex selector constructors

Vertex selectors are created by vertex selector constructors, can be instantiated with `igraph_vit_create()`, and are destroyed with `igraph_vs_destroy()`.

`igraph_vs_all` — Vertex set, all vertices of a graph.

```
igraph_error_t igraph_vs_all(igraph_vs_t *vs);
```

Arguments:

`vs`: Pointer to an uninitialized `igraph_vs_t` object.

Returns:

Error code.

See also:

`igraph_vss_all()`, `igraph_vs_destroy()`

This selector includes all vertices of a given graph in increasing vertex ID order.

Time complexity: $O(1)$.

igraph_vs_adj — Adjacent vertices of a vertex.

```
igraph_error_t igraph_vs_adj(igraph_vs_t *vs,  
                             igraph_integer_t vid, igraph_neimode_t mode);
```

All neighboring vertices of a given vertex are selected by this selector. The *mode* argument controls the type of the neighboring vertices to be selected. The vertices are visited in increasing vertex ID order, as of igraph version 0.4.

Arguments:

vs: Pointer to an uninitialized vertex selector object.

vid: Vertex ID, the center of the neighborhood.

mode: Decides the type of the neighborhood for directed graphs. This parameter is ignored for undirected graphs. Possible values:

IGRAPH_OUT All vertices to which there is a directed edge from *vid*. That is, all the out-neighbors of *vid*.

IGRAPH_IN All vertices from which there is a directed edge to *vid*. In other words, all the in-neighbors of *vid*.

IGRAPH_ALL All vertices to which or from which there is a directed edge from/to *vid*. That is, all the neighbors of *vid* considered as if the graph is undirected.

Returns:

Error code.

See also:

`igraph_vs_destroy()`

Time complexity: $O(1)$.

igraph_vs_nonadj — Non-adjacent vertices of a vertex.

```
igraph_error_t igraph_vs_nonadj(igraph_vs_t *vs, igraph_integer_t vid,  
                                igraph_neimode_t mode);
```

All non-neighboring vertices of a given vertex. The *mode* argument controls the type of neighboring vertices *not* to select. Instead of selecting immediate neighbors of *vid* as is done by `igraph_vs_adj()`, the current function selects vertices that are *not* immediate neighbors of *vid*.

Arguments:

vs: Pointer to an uninitialized vertex selector object.

vid: Vertex ID, the “center” of the non-neighborhood.

mode: The type of neighborhood not to select in directed graphs. Possible values:

IGRAPH_OUT	All vertices will be selected except those to which there is a directed edge from <i>vid</i> . That is, we select all vertices excluding the out-neighbors of <i>vid</i> .
IGRAPH_IN	All vertices will be selected except those from which there is a directed edge to <i>vid</i> . In other words, we select all vertices but the in-neighbors of <i>vid</i> .
IGRAPH_ALL	All vertices will be selected except those from or to which there is a directed edge to or from <i>vid</i> . That is, we select all vertices of <i>vid</i> except for its immediate neighbors.

Returns:

Error code.

See also:

`igraph_vs_destroy()`

Time complexity: $O(1)$.

Example 11.1. File `examples/simple/igraph_vs_nonadj.c`

igraph_vs_none — Empty vertex set.

```
igraph_error_t igraph_vs_none(igraph_vs_t *vs);
```

Creates an empty vertex selector.

Arguments:

vs: Pointer to an uninitialized vertex selector object.

Returns:

Error code.

See also:

`igraph_vss_none()`, `igraph_vs_destroy()`

Time complexity: $O(1)$.

igraph_vs_1 — Vertex set with a single vertex.

```
igraph_error_t igraph_vs_1(igraph_vs_t *vs, igraph_integer_t vid);
```

This vertex selector selects a single vertex.

Arguments:

vs: Pointer to an uninitialized vertex selector object.

vid: The vertex ID to be selected.

Returns:

Error Code.

See also:

`igraph_vss_l()`, `igraph_vs_destroy()`

Time complexity: $O(1)$.

`igraph_vs_vector` — Vertex set based on a vector.

```
igraph_error_t igraph_vs_vector(igraph_vs_t *vs,  
                                const igraph_vector_int_t *v);
```

This function makes it possible to handle an `igraph_vector_int_t` temporarily as a vertex selector. The vertex selector should be thought of as a *view* into the vector. If you make changes to the vector that also affects the vertex selector. Destroying the vertex selector does not destroy the vector. Do not destroy the vector before destroying the vertex selector, or you might get strange behavior. Since selectors are not tied to any specific graph, this function does not check whether the vertex IDs in the vector are valid.

Arguments:

vs: Pointer to an uninitialized vertex selector.

v: Pointer to a `igraph_vector_int_t` object.

Returns:

Error code.

See also:

`igraph_vss_vector()`, `igraph_vs_destroy()`

Time complexity: $O(1)$.

Example 11.2. File `examples/simple/igraph_vs_vector.c`

`igraph_vs_vector_small` — Create a vertex set by giving its elements.

```
igraph_error_t igraph_vs_vector_small(igraph_vs_t *vs, ...);
```

This function can be used to create a vertex selector with a few of vertices. Do not forget to include a -1 after the last vertex ID. The behavior of the function is undefined if you don't use a -1 properly.

Note that the vertex IDs supplied will be parsed as value of type int so you cannot supply arbitrarily large (too large for int) vertex IDs here.

Arguments:

`vs`: Pointer to an uninitialized vertex selector object.

`...`: Additional parameters, these will be the vertex IDs to be included in the vertex selector. Supply a -1 after the last vertex ID.

Returns:

Error code.

See also:

`igraph_vs_destroy()`

Time complexity: $O(n)$, the number of vertex IDs supplied.

`igraph_vs_vector_copy` — Vertex set based on a vector, with copying.

```
igraph_error_t igraph_vs_vector_copy(igraph_vs_t *vs, const igraph_vector_int_t
```

This function makes it possible to handle an `igraph_vector_int_t` permanently as a vertex selector. The vertex selector creates a copy of the original vector, so the vector can safely be destroyed after creating the vertex selector. Changing the original vector will not affect the vertex selector. The vertex selector is responsible for deleting the copy made by itself. Since selectors are not tied to any specific graph, this function does not check whether the vertex IDs in the vector are valid.

Arguments:

`vs`: Pointer to an uninitialized vertex selector.

`v`: Pointer to a `igraph_vector_int_t` object.

Returns:

Error code.

See also:

`igraph_vs_destroy()`

Time complexity: $O(1)$.

`igraph_vs_range` — Vertex set, an interval of vertices.


```
igraph_error_t igraph_vs_range(igraph_vs_t *vs, igraph_integer_t start, igraph_
```

Creates a vertex selector containing all vertices with vertex ID equal to or bigger than *from* and smaller than *to*. Note that the interval is closed from the left and open from the right, following C conventions.

Arguments:

vs: Pointer to an uninitialized vertex selector object.

start: The first vertex ID to be included in the vertex selector.

end: The first vertex ID *not* to be included in the vertex selector.

Returns:

Error code.

See also:

```
igraph_vss_range(), igraph_vs_destroy()
```

Time complexity: $O(1)$.

Example 11.3. File `examples/simple/igraph_vs_seq.c`

Generic vertex selector operations

igraph_vs_copy — Creates a copy of a vertex selector.

```
igraph_error_t igraph_vs_copy(igraph_vs_t* dest, const igraph_vs_t* src);
```

Arguments:

src: The selector being copied.

dest: An uninitialized selector that will contain the copy.

igraph_vs_destroy — Destroy a vertex set.

```
void igraph_vs_destroy(igraph_vs_t *vs);
```

This function should be called for all vertex selectors when they are not needed. The memory allocated for the vertex selector will be deallocated. Do not call this function on vertex selectors created with the immediate versions of the vertex selector constructors (starting with `igraph_vss`).

Arguments:

vs: Pointer to a vertex selector object.

Time complexity: operating system dependent, usually $O(1)$.

igraph_vs_is_all — Check whether all vertices are included.

```
igraph_bool_t igraph_vs_is_all(const igraph_vs_t *vs);
```

This function checks whether the vertex selector object was created by `igraph_vs_all()` or `igraph_vss_all()`. Note that the vertex selector might contain all vertices in a given graph but if it wasn't created by the two constructors mentioned here the return value will be `false`.

Arguments:

vs: Pointer to a vertex selector object.

Returns:

`true` if the vertex selector contains all vertices and `false` otherwise.

Time complexity: $O(1)$.

igraph_vs_size — Returns the size of the vertex selector.

```
igraph_error_t igraph_vs_size(const igraph_t *graph, const igraph_vs_t *vs,  
                             igraph_integer_t *result);
```

The size of the vertex selector is the number of vertices it will yield when it is iterated over.

Arguments:

graph: The graph over which we will iterate.

result: The result will be returned here.

igraph_vs_type — Returns the type of the vertex selector.

```
igraph_vs_type_t igraph_vs_type(const igraph_vs_t *vs);
```

Immediate vertex selectors

igraph_vss_all — All vertices of a graph (immediate version).

```
igraph_vs_t igraph_vss_all(void);
```

Immediate vertex selector for all vertices in a graph. It can be used conveniently when some vertex property (e.g. betweenness, degree, etc.) should be calculated for all vertices.

Returns:

A vertex selector for all vertices in a graph.

See also:

```
igraph_vs_all()
```

Time complexity: $O(1)$.

igraph_vss_none — Empty vertex set (immediate version).

```
igraph_vs_t igraph_vss_none(void);
```

The immediate version of the empty vertex selector.

Returns:

An empty vertex selector.

See also:

```
igraph_vs_none()
```

Time complexity: $O(1)$.

igraph_vss_1 — Vertex set with a single vertex (immediate version).

```
igraph_vs_t igraph_vss_1(igraph_integer_t vid);
```

The immediate version of the single-vertex selector.

Arguments:

vid: The vertex to be selected.

Returns:

A vertex selector containing a single vertex.

See also:

```
igraph_vs_1()
```

Time complexity: $O(1)$.

igraph_vss_vector — Vertex set based on a vector (immediate version).

```
igraph_vs_t igraph_vss_vector(const igraph_vector_int_t *v);
```

This is the immediate version of `igraph_vs_vector`.

Arguments:

v: Pointer to a `igraph_vector_int_t` object.

Returns:

A vertex selector object containing the vertices in the vector.

See also:

```
igraph_vs_vector()
```

Time complexity: $O(1)$.

igraph_vss_range — An interval of vertices (immediate version).

```
igraph_vs_t igraph_vss_range(igraph_integer_t start, igraph_integer_t end);
```

The immediate version of `igraph_vs_range()`.

Arguments:

start: The first vertex ID to be included in the vertex selector.

end: The first vertex ID *not* to be included in the vertex selector.

Returns:

Error code.

See also:

```
igraph_vs_range()
```

Time complexity: $O(1)$.

Vertex iterators

igraph_vit_create — Creates a vertex iterator from a vertex selector.

```
igraph_error_t igraph_vit_create(const igraph_t *graph,  
                                igraph_vs_t vs, igraph_vit_t *vit);
```

This function instantiates a vertex selector object with a given graph. This is the step when the actual vertex IDs are created from the *logical* notion of the vertex selector based on the graph. E.g. a vertex selector created with `igraph_vs_all()` contains knowledge that *all* vertices are included in a (yet indefinite) graph. When instantiating it a vertex iterator object is created, this contains the actual vertex IDs in the graph supplied as a parameter.

The same vertex selector object can be used to instantiate any number vertex iterators.

Arguments:

graph: An `igraph_t` object, a graph.

vs: A vertex selector object.

vit: Pointer to an uninitialized vertex iterator object.

Returns:

Error code.

See also:

`igraph_vit_destroy()`.

Time complexity: it depends on the vertex selector type. $O(1)$ for vertex selectors created with `igraph_vs_all()`, `igraph_vs_none()`, `igraph_vs_1`, `igraph_vs_vector`, `igraph_vs_range()`, `igraph_vs_vector()`, `igraph_vs_vector_small()`. $O(d)$ for `igraph_vs_adj()`, d is the number of vertex IDs to be included in the iterator. $O(|V|)$ for `igraph_vs_nonadj()`, $|V|$ is the number of vertices in the graph.

igraph_vit_destroy — Destroys a vertex iterator.

```
void igraph_vit_destroy(const igraph_vit_t *vit);
```

Deallocates memory allocated for a vertex iterator.

Arguments:

vit: Pointer to an initialized vertex iterator object.

See also:

`igraph_vit_create()`

Time complexity: operating system dependent, usually $O(1)$.

Stepping over the vertices

After creating an iterator with `igraph_vit_create()`, it points to the first vertex in the vertex determined by the vertex selector (if there is any). The `IGRAPH_VIT_NEXT()` macro steps to the next vertex, `IGRAPH_VIT_END()` checks whether there are more vertices to vis-

it, `IGRAPH_VIT_SIZE()` gives the total size of the vertices visited so far and to be visited. `IGRAPH_VIT_RESET()` resets the iterator, it will point to the first vertex again. Finally `IGRAPH_VIT_GET()` gives the current vertex pointed to by the iterator (call this only if `IGRAPH_VIT_END()` is false).

Here is an example on how to step over the neighbors of vertex 0:

```
igraph_vs_t vs;
igraph_vit_t vit;
...
igraph_vs_adj(&vs, 0, IGRAPH_ALL);
igraph_vit_create(&graph, vs, &vit);
while (!IGRAPH_VIT_END(vit)) {
    printf(" %" IGRAPH_PRId, IGRAPH_VIT_GET(vit));
    IGRAPH_VIT_NEXT(vit);
}
printf("\n");
...
igraph_vit_destroy(&vit);
igraph_vs_destroy(&vs);
```

IGRAPH_VIT_NEXT — Next vertex.

```
#define IGRAPH_VIT_NEXT(vit)
```

Steps the iterator to the next vertex. Only call this function if `IGRAPH_VIT_END()` returns false.

Arguments:

vit: The vertex iterator to step.

Time complexity: $O(1)$.

IGRAPH_VIT_END — Are we at the end?

```
#define IGRAPH_VIT_END(vit)
```

Checks whether there are more vertices to step to.

Arguments:

vit: The vertex iterator to check.

Returns:

Logical value, if true there are no more vertices to step to.

Time complexity: $O(1)$.

IGRAPH_VIT_SIZE — Size of a vertex iterator.

```
#define IGRAPH_VIT_SIZE(vit)
```

Gives the number of vertices in a vertex iterator.

Arguments:

vit: The vertex iterator.

Returns:

The number of vertices.

Time complexity: $O(1)$.

IGRAPH_VIT_RESET — Reset a vertex iterator.

```
#define IGRAPH_VIT_RESET(vit)
```

Resets a vertex iterator. After calling this macro the iterator will point to the first vertex.

Arguments:

vit: The vertex iterator.

Time complexity: $O(1)$.

IGRAPH_VIT_GET — Query the current position.

```
#define IGRAPH_VIT_GET(vit)
```

Gives the vertex ID of the current vertex pointed to by the iterator.

Arguments:

vit: The vertex iterator.

Returns:

The vertex ID of the current vertex.

Time complexity: $O(1)$.

Edge selector constructors

igraph_es_all — Edge set, all edges.

```
igraph_error_t igraph_es_all(igraph_es_t *es,  
                             igraph_edgeorder_type_t order);
```

Arguments:

es: Pointer to an uninitialized edge selector object.

order: Constant giving the order in which the edges will be included in the selector. Possible values: `IGRAPH_EDGEORDER_ID`, edge ID order. `IGRAPH_EDGEORDER_FROM`, vertex ID order, the id of the *source* vertex counts for directed graphs. The order of the incident edges of a given vertex is arbitrary. `IGRAPH_EDGEORDER_TO`, vertex ID order, the ID of the *target* vertex counts for directed graphs. The order of the incident edges of a given vertex is arbitrary. For undirected graph the latter two is the same.

Returns:

Error code.

See also:

`igraph_ess_all()`, `igraph_es_destroy()`

Time complexity: $O(1)$.

`igraph_es_incident` — Edges incident on a given vertex.

```
igraph_error_t igraph_es_incident(igraph_es_t *es,  
                                igraph_integer_t vid, igraph_neimode_t mode);
```

Arguments:

es: Pointer to an uninitialized edge selector object.

vid: Vertex ID, of which the incident edges will be selected.

mode: Constant giving the type of the incident edges to select. This is ignored for undirected graphs. Possible values: `IGRAPH_OUT`, outgoing edges; `IGRAPH_IN`, incoming edges; `IGRAPH_ALL`, all edges.

Returns:

Error code.

See also:

`igraph_es_destroy()`

Time complexity: $O(1)$.

`igraph_es_none` — Empty edge selector.

```
igraph_error_t igraph_es_none(igraph_es_t *es);
```

Arguments:

es: Pointer to an uninitialized edge selector object to initialize.

Returns:

Error code.

See also:

`igraph_ess_none()`, `igraph_es_destroy()`

Time complexity: $O(1)$.

`igraph_es_1` — Edge selector containing a single edge.

```
igraph_error_t igraph_es_1(igraph_es_t *es, igraph_integer_t eid);
```

Arguments:

es: Pointer to an uninitialized edge selector object.

eid: Edge ID of the edge to select.

Returns:

Error code.

See also:

`igraph_ess_1()`, `igraph_es_destroy()`

Time complexity: $O(1)$.

`igraph_es_vector` — Handle a vector as an edge selector.

```
igraph_error_t igraph_es_vector(igraph_es_t *es, const igraph_vector_int_t *v);
```

Creates an edge selector which serves as a view into a vector containing edge IDs. Do not destroy the vector before destroying the edge selector. Since selectors are not tied to any specific graph, this function does not check whether the edge IDs in the vector are valid.

Arguments:

es: Pointer to an uninitialized edge selector.

v: Vector containing edge IDs.

Returns:

Error code.

See also:

```
igraph_ess_vector(),igraph_es_destroy()
```

Time complexity: $O(1)$.

igraph_es_range — Edge selector, a sequence of edge IDs.

```
igraph_error_t igraph_es_range(igraph_es_t *es, igraph_integer_t start, igraph_
```

Creates an edge selector containing all edges with edge ID equal to or bigger than *from* and smaller than *to*. Note that the interval is closed from the left and open from the right, following C conventions.

Arguments:

vs: Pointer to an uninitialized edge selector object.

start: The first edge ID to be included in the edge selector.

end: The first edge ID *not* to be included in the edge selector.

Returns:

Error code.

See also:

```
igraph_ess_range(),igraph_es_destroy()
```

Time complexity: $O(1)$.

igraph_es_pairs — Edge selector, multiple edges defined by their endpoints in a vector.

```
igraph_error_t igraph_es_pairs(igraph_es_t *es, const igraph_vector_int_t *v,  
                               igraph_bool_t directed);
```

The edges between the given pairs of vertices will be included in the edge selection. The vertex pairs must be defined in the vector *v*, the first element of the vector is the first vertex of the first edge to be selected, the second element is the second vertex of the first edge, the third element is the first vertex of the second edge and so on.

Arguments:

es: Pointer to an uninitialized edge selector object.

v: The vector containing the endpoints of the edges.

directed: Whether the graph is directed or not.

Returns:

Error code.

See also:

```
igraph_es_pairs_small(), igraph_es_destroy()
```

Time complexity: $O(n)$, the number of edges being selected.

Example 11.4. File `examples/simple/igraph_es_pairs.c`

igraph_es_pairs_small — Edge selector, multiple edges defined by their endpoints as arguments.

```
igraph_error_t igraph_es_pairs_small(igraph_es_t *es, igraph_bool_t directed, ...)
```

The edges between the given pairs of vertices will be included in the edge selection. The vertex pairs must be given as the arguments of the function call, the third argument is the first vertex of the first edge, the fourth argument is the second vertex of the first edge, the fifth is the first vertex of the second edge and so on. The last element of the argument list must be -1 to denote the end of the argument list.

Note that the vertex IDs supplied will be parsed as `int`'s so you cannot supply arbitrarily large (too large for `int`) vertex IDs here.

Arguments:

es: Pointer to an uninitialized edge selector object.

directed: Whether the graph is directed or not.

...: The additional arguments give the edges to be included in the selector, as pairs of vertex IDs. The last argument must be -1. The *first* parameter is present for technical reasons and represents the first variadic argument.

Returns:

Error code.

See also:

```
igraph_es_pairs(), igraph_es_destroy()
```

Time complexity: $O(n)$, the number of edges being selected.

igraph_es_path — Edge selector, edge IDs on a path.

```
igraph_error_t igraph_es_path(igraph_es_t *es, const igraph_vector_int_t *v,  
                              igraph_bool_t directed);
```

This function takes a vector of vertices and creates a selector of edges between those vertices. Vector `{0, 3, 4, 7}` will select edges `(0 -> 3)`, `(3 -> 4)`, `(4 -> 7)`. If these edges don't exist then trying to create an iterator using this selector will fail.

Arguments:

es: Pointer to an uninitialized edge selector object.

v: Pointer to a vector of vertex IDs along the path.

directed: If edge directions should be taken into account. This will be ignored if the graph to select from is undirected.

Returns:

Error code.

See also:

`igraph_es_destroy()`

Time complexity: $O(n)$, the number of vertices.

igraph_es_vector_copy — Edge set, based on a vector, with copying.

```
igraph_error_t igraph_es_vector_copy(igraph_es_t *es, const igraph_vector_int_t
```

This function makes it possible to handle an `igraph_vector_int_t` permanently as an edge selector. The edge selector creates a copy of the original vector, so the vector can safely be destroyed after creating the edge selector. Changing the original vector will not affect the edge selector. The edge selector is responsible for deleting the copy made by itself. Since selectors are not tied to any specific graph, this function does not check whether the edge IDs in the vector are valid.

Arguments:

es: Pointer to an uninitialized edge selector.

v: Pointer to a `igraph_vector_int_t` object.

Returns:

Error code.

See also:

`igraph_es_destroy()`

Time complexity: $O(1)$.

Immediate edge selectors

igraph_ess_all — Edge set, all edges (immediate version)

```
igraph_es_t igraph_ess_all(igraph_edgeorder_type_t order);
```

The immediate version of the all-edges selector.

Arguments:

order: Constant giving the order of the edges in the edge selector. See `igraph_es_all()` for the possible values.

Returns:

The edge selector.

See also:

`igraph_es_all()`

Time complexity: $O(1)$.

`igraph_ess_none` — Immediate empty edge selector.

```
igraph_es_t igraph_ess_none(void);
```

Immediate version of the empty edge selector.

Returns:

Initialized empty edge selector.

See also:

`igraph_es_none()`

Time complexity: $O(1)$.

`igraph_ess_1` — Immediate version of the single edge edge selector.

```
igraph_es_t igraph_ess_1(igraph_integer_t eid);
```

Arguments:

eid: The ID of the edge.

Returns:

The edge selector.

See also:

`igraph_es_1()`

Time complexity: $O(1)$.

igraph_ess_vector — Immediate vector view edge selector.

```
igraph_es_t igraph_ess_vector(const igraph_vector_int_t *v);
```

This is the immediate version of the vector of edge IDs edge selector.

Arguments:

v: The vector of edge IDs.

Returns:

Edge selector, initialized.

See also:

```
igraph_es_vector()
```

Time complexity: $O(1)$.

igraph_ess_range — Immediate version of the sequence edge selector.

```
igraph_es_t igraph_ess_range(igraph_integer_t start, igraph_integer_t end);
```

Arguments:

start: The first edge ID to be included in the edge selector.

end: The first edge ID *not* to be included in the edge selector.

Returns:

The initialized edge selector.

See also:

```
igraph_es_range()
```

Time complexity: $O(1)$.

Generic edge selector operations

igraph_es_as_vector — Transform edge selector into vector.

```
igraph_error_t igraph_es_as_vector(const igraph_t *graph, igraph_es_t es,
                                   igraph_vector_int_t *v);
```

Call this function on an edge selector to transform it into a vector. This is only implemented for sequence and vector selectors. If the edges do not exist in the graph, this will result in an error.

Arguments:

graph: Pointer to a graph to check if the edges in the selector exist.

es: An edge selector object.

v: Pointer to initialized vector. The result will be stored here.

Time complexity: $O(n)$, the number of edges in the selector.

igraph_es_copy — Creates a copy of an edge selector.

```
igraph_error_t igraph_es_copy(igraph_es_t* dest, const igraph_es_t* src);
```

Arguments:

src: The selector being copied.

dest: An uninitialized selector that will contain the copy.

See also:

```
igraph_es_destroy()
```

igraph_es_destroy — Destroys an edge selector object.

```
void igraph_es_destroy(igraph_es_t *es);
```

Call this function on an edge selector when it is not needed any more. Do *not* call this function on edge selectors created by immediate constructors, those don't need to be destroyed.

Arguments:

es: Pointer to an edge selector object.

Time complexity: operating system dependent, usually $O(1)$.

igraph_es_is_all — Check whether an edge selector includes all edges.

```
igraph_bool_t igraph_es_is_all(const igraph_es_t *es);
```

Arguments:

es: Pointer to an edge selector object.

Returns:

true if *es* was created with `igraph_es_all()` or `igraph_ess_all()`, and false otherwise.

Time complexity: $O(1)$.

igraph_es_size — Returns the size of the edge selector.

```
igraph_error_t igraph_es_size(const igraph_t *graph, const igraph_es_t *es,  
                             igraph_integer_t *result);
```

The size of the edge selector is the number of edges it will yield when it is iterated over.

Arguments:

graph: The graph over which we will iterate.

result: The result will be returned here.

igraph_es_type — Returns the type of the edge selector.

```
igraph_es_type_t igraph_es_type(const igraph_es_t *es);
```

Edge iterators

igraph_eit_create — Creates an edge iterator from an edge selector.

```
igraph_error_t igraph_eit_create(const igraph_t *graph,  
                                igraph_es_t es, igraph_eit_t *eit);
```

This function creates an edge iterator based on an edge selector and a graph.

The same edge selector can be used to create many edge iterators, also for different graphs.

Arguments:

graph: An `igraph_t` object for which the edge selector will be instantiated.

es: The edge selector to instantiate.

eit: Pointer to an uninitialized edge iterator.

Returns:

Error code.

See also:

`igraph_eit_destroy()`

Time complexity: depends on the type of the edge selector. For edge selectors created by `igraph_es_all()`, `igraph_es_none()`, `igraph_es_l()`, `igraph_es_vector()`, `igraph_es_seq()` it is $O(1)$. For `igraph_es_incident()` it is $O(d)$ where d is the number of incident edges of the vertex.

`igraph_eit_destroy` — Destroys an edge iterator.

```
void igraph_eit_destroy(const igraph_eit_t *eit);
```

Arguments:

eit: Pointer to an edge iterator to destroy.

See also:

`igraph_eit_create()`

Time complexity: operating system dependent, usually $O(1)$.

Stepping over the edges

Just like for vertex iterators, macros are provided for stepping over a sequence of edges: `IGRAPH_EIT_NEXT()` goes to the next edge, `IGRAPH_EIT_END()` checks whether there are more edges to visit, `IGRAPH_EIT_SIZE()` gives the number of edges in the edge sequence, `IGRAPH_EIT_RESET()` resets the iterator to the first edge and `IGRAPH_EIT_GET()` returns the id of the current edge.

`IGRAPH_EIT_NEXT` — Next edge.

```
#define IGRAPH_EIT_NEXT(eit)
```

Steps the iterator to the next edge. Call this function only if `IGRAPH_EIT_END()` returns false.

Arguments:

eit: The edge iterator to step.

Time complexity: $O(1)$.

IGRAPH_EIT_END — Are we at the end?

```
#define IGRAPH_EIT_END(eit)
```

Checks whether there are more edges to step to.

Arguments:

wit: The edge iterator to check.

Returns:

Logical value, if true there are no more edges to step to.

Time complexity: $O(1)$.

IGRAPH_EIT_SIZE — Number of edges in the iterator.

```
#define IGRAPH_EIT_SIZE(eit)
```

Gives the number of edges in an edge iterator.

Arguments:

eit: The edge iterator.

Returns:

The number of edges.

Time complexity: $O(1)$.

IGRAPH_EIT_RESET — Reset an edge iterator.

```
#define IGRAPH_EIT_RESET(eit)
```

Resets an edge iterator. After calling this macro the iterator will point to the first edge.

Arguments:

eit: The edge iterator.

Time complexity: $O(1)$.

IGRAPH_EIT_GET — Query an edge iterator.

```
#define IGRAPH_EIT_GET(eit)
```

Gives the edge ID of the current edge pointed to by an iterator.

Arguments:

eit: The edge iterator.

Returns:

The id of the current edge.

Time complexity: $O(1)$.

Deprecated functions

igraph_es_seq — Edge selector, a sequence of edge IDs, with inclusive endpoints (deprecated).

```
igraph_error_t igraph_es_seq(igraph_es_t *es, igraph_integer_t from, igraph_int
```

All edge IDs between *from* and *to* (inclusive) will be included in the edge selection.

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_es_range()` instead.

Arguments:

es: Pointer to an uninitialized edge selector object.

from: The first edge ID to be included.

to: The last edge ID to be included.

Returns:

Error code.

See also:

`igraph_ess_seq()`, `igraph_es_destroy()`

Time complexity: $O(1)$.

igraph_ess_seq — Immediate version of the sequence edge selector, with inclusive endpoints.

```
igraph_es_t igraph_ess_seq(igraph_integer_t from, igraph_integer_t to);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_ess_range()` instead.

Arguments:

from: The first edge ID to include.

to: The last edge ID to include.

Returns:

The initialized edge selector.

See also:

`igraph_es_seq()`

Time complexity: $O(1)$.

`igraph_vs_seq` — Vertex set, an interval of vertices with inclusive endpoints (deprecated).

```
igraph_error_t igraph_vs_seq(igraph_vs_t *vs, igraph_integer_t from, igraph_int
```

Creates a vertex selector containing all vertices with vertex ID equal to or bigger than *from* and equal to or smaller than *to*. Note that both endpoints are inclusive, contrary to C conventions.

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_vs_range()` instead.

Arguments:

vs: Pointer to an uninitialized vertex selector object.

from: The first vertex ID to be included in the vertex selector.

to: The last vertex ID to be included in the vertex selector.

Returns:

Error code.

See also:

`igraph_vs_range()`, `igraph_vss_seq()`, `igraph_vs_destroy()`

Time complexity: $O(1)$.

Example 11.5. File `examples/simple/igraph_vs_seq.c`

`igraph_vss_seq` — An interval of vertices with inclusive endpoints (immediate version, deprecated).

```
igraph_vs_t igraph_vss_seq(igraph_integer_t from, igraph_integer_t to);
```

The immediate version of `igraph_vs_seq()`.

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_vss_range()` instead.

Arguments:

from: The first vertex ID to be included in the vertex selector.

to: The last vertex ID to be included in the vertex selector.

Returns:

Error code.

See also:

`igraph_vss_range()`, `igraph_vs_seq()`

Time complexity: $O(1)$.

Chapter 12. Graph, vertex and edge attributes

Attributes are numbers or strings (or basically any kind of data) associated with the vertices or edges of a graph, or with the graph itself. E.g. you may label vertices with symbolic names or attach numeric weights to the edges of a graph.

igraph attributes are designed to be flexible and extensible. In igraph attributes are implemented via an interface abstraction: any type implementing the functions in the interface, can be used for storing vertex, edge and graph attributes. This means that different attribute implementations can be used together with igraph. This is reasonable: if igraph is used from Python attributes can be of any Python type, from GNU R all R types are allowed. There is an experimental attribute implementation to be used when programming in C, but by default it is currently turned off.

First we briefly look over how attribute handlers can be implemented. This is not something a user does every day. It is rather typically the job of the high level interface writers. (But it is possible to write an interface without implementing attributes.) Then we show the experimental C attribute handler.

The Attribute Handler Interface

It is possible to attach an attribute handling interface to **igraph**. This is simply a table of functions, of type `igraph_attribute_table_t`. These functions are invoked to notify the attribute handling code about the structural changes in a graph. See the documentation of this type for details.

By default there is no attribute interface attached to **igraph**, to attach one, call `igraph_set_attribute_table` with your new table.

`igraph_attribute_table_t` — Table of functions to perform operations on attributes

```
typedef struct igraph_attribute_table_t {
    igraph_error_t (*init)(igraph_t *graph, igraph_vector_ptr_t *attr);
    void (*destroy)(igraph_t *graph);
    igraph_error_t (*copy)(igraph_t *to, const igraph_t *from, igraph_bool_t ga,
                           igraph_bool_t va, igraph_bool_t ea);
    igraph_error_t (*add_vertices)(igraph_t *graph, igraph_integer_t nv, igraph_t *newgraph);
    igraph_error_t (*permute_vertices)(const igraph_t *graph,
                                       igraph_t *newgraph,
                                       const igraph_vector_int_t *idx);
    igraph_error_t (*combine_vertices)(const igraph_t *graph,
                                       igraph_t *newgraph,
                                       const igraph_vector_int_list_t *merges,
                                       const igraph_attribute_combination_t *comb);
    igraph_error_t (*add_edges)(igraph_t *graph, const igraph_vector_int_t *edges,
                               igraph_t *newgraph, igraph_vector_ptr_t *attr);
    igraph_error_t (*permute_edges)(const igraph_t *graph,
                                    igraph_t *newgraph, const igraph_vector_int_t *idx);
    igraph_error_t (*combine_edges)(const igraph_t *graph,
                                    igraph_t *newgraph,
                                    const igraph_vector_int_list_t *merges,
                                    const igraph_attribute_combination_t *comb);
    igraph_error_t (*get_info)(const igraph_t *graph,
```

```
igraph_strvector_t *gnames, igraph_vector_int_t
igraph_strvector_t *vnames, igraph_vector_int_t
igraph_strvector_t *enames, igraph_vector_int_t
igraph_bool_t (*has_attr)(const igraph_t *graph, igraph_attribute_element_t
const char *name);
igraph_error_t (*gettype)(const igraph_t *graph, igraph_attribute_type_t *t
igraph_attribute_element_t elemtype, const char
igraph_error_t (*get_numeric_graph_attr)(const igraph_t *graph, const char
igraph_vector_t *value);
igraph_error_t (*get_string_graph_attr)(const igraph_t *graph, const char *n
igraph_strvector_t *value);
igraph_error_t (*get_bool_graph_attr)(const igraph_t *igraph, const char *n
igraph_vector_bool_t *value);
igraph_error_t (*get_numeric_vertex_attr)(const igraph_t *graph, const char
igraph_vs_t vs,
igraph_vector_t *value);
igraph_error_t (*get_string_vertex_attr)(const igraph_t *graph, const char
igraph_vs_t vs,
igraph_strvector_t *value);
igraph_error_t (*get_bool_vertex_attr)(const igraph_t *graph, const char *n
igraph_vs_t vs,
igraph_vector_bool_t *value);
igraph_error_t (*get_numeric_edge_attr)(const igraph_t *graph, const char *n
igraph_es_t es,
igraph_vector_t *value);
igraph_error_t (*get_string_edge_attr)(const igraph_t *graph, const char *n
igraph_es_t es,
igraph_strvector_t *value);
igraph_error_t (*get_bool_edge_attr)(const igraph_t *graph, const char *n
igraph_es_t es,
igraph_vector_bool_t *value);
} igraph_attribute_table_t;
```

This type collects the functions defining an attribute handler. It has the following members:

Values:

init:	This function is called whenever a new graph object is created, right after it is created but before any vertices or edges are added. It is supposed to set the attr member of the igraph_t object. It is expected to return an error code.
destroy:	This function is called whenever the graph object is destroyed, right before freeing the allocated memory.
copy:	This function is called when copying a graph with igraph_copy, after the structure of the graph has been already copied. It is expected to return an error code.
add_vertices:	Called when vertices are added to a graph, before adding the vertices themselves. The number of vertices to add is supplied as an argument. Expected to return an error code.
permute_vertices:	Typically called when a new graph is created based on an existing one, e.g. if vertices are removed from a graph. The supplied index vector defines which old vertex a new vertex corresponds to. Its length must be the same as the number of vertices in the new graph.

<code>combine_vertices:</code>	This function is called when the creation of a new graph involves a merge (contraction, etc.) of vertices from another graph. The function is after the new graph was created. An argument specifies how several vertices from the old graph map to a single vertex in the new graph.
<code>add_edges:</code>	Called when new edges have been added. The number of new edges are supplied as well. It is expected to return an error code.
<code>permute_edges:</code>	Typically called when a new graph is created and some of the new edges should carry the attributes of some of the old edges. The <code>idx</code> vector shows the mapping between the old edges and the new ones. Its length is the same as the number of edges in the new graph, and for each edge it gives the id of the old edge (the edge in the old graph).
<code>combine_edges:</code>	This function is called when the creation of a new graph involves a merge (contraction, etc.) of edges from another graph. The function is after the new graph was created. An argument specifies how several edges from the old graph map to a single edge in the new graph.
<code>get_info:</code>	Query the attributes of a graph, the names and types should be returned.
<code>has_attr:</code>	Check whether a graph has the named graph/vertex/edge attribute.
<code>gettype:</code>	Query the type of a graph/vertex/edge attribute.
<code>get_numeric_graph_attr:</code>	Query a numeric graph attribute. The value should be placed as the first element of the <i>value</i> vector.
<code>get_string_graph_attr:</code>	Query a string graph attribute. The value should be placed as the first element of the <i>value</i> string vector.
<code>get_bool_graph_attr:</code>	Query a boolean graph attribute. The value should be placed as the first element of the <i>value</i> boolean vector.
<code>get_numeric_vertex_attr:</code>	Query a numeric vertex attribute, for the vertices included in <i>vs</i> .
<code>get_string_vertex_attr:</code>	Query a string vertex attribute, for the vertices included in <i>vs</i> .
<code>get_bool_vertex_attr:</code>	Query a boolean vertex attribute, for the vertices included in <i>vs</i> .
<code>get_numeric_edge_attr:</code>	Query a numeric edge attribute, for the edges included in <i>es</i> .
<code>get_string_edge_attr:</code>	Query a string edge attribute, for the edges included in <i>es</i> .
<code>get_bool_edge_attr:</code>	Query a boolean edge attribute, for the edges included in <i>es</i> .

Note that the `get_*_*_attr` are allowed to convert the attributes to numeric or string. E.g. if a vertex attribute is a GNU R complex data type, then `get_string_vertex_attribute` may serialize it into a string, but this probably makes sense only if `add_vertices` is able to deserialize it.

igraph_set_attribute_table — Attach an attribute table.


```
igraph_attribute_table_t *  
igraph_set_attribute_table(const igraph_attribute_table_t * table);
```

This function attaches attribute handling code to the igraph library. Note that the attribute handler table is *not* thread-local even if igraph is compiled in thread-local mode. In the vast majority of cases, this is not a significant restriction.

Arguments:

table: Pointer to an `igraph_attribute_table_t` object containing the functions for attribute manipulation. Supply NULL here if you don't want attributes.

Returns:

Pointer to the old attribute handling table.

Time complexity: $O(1)$.

`igraph_attribute_type_t` — The possible types of the attributes.

```
typedef enum { IGRAPH_ATTRIBUTE_UNSPECIFIED = 0,  
               IGRAPH_ATTRIBUTE_DEFAULT IGRAPH_DEPRECATED_ENUMVAL = IGRAPH_ATTR  
               IGRAPH_ATTRIBUTE_NUMERIC = 1,  
               IGRAPH_ATTRIBUTE_BOOLEAN = 2,  
               IGRAPH_ATTRIBUTE_STRING = 3,  
               IGRAPH_ATTRIBUTE_OBJECT = 127  
             } igraph_attribute_type_t;
```

Note that this is only the type communicated by the attribute interface towards igraph functions. E.g. in the R attribute handler, it is safe to say that all complex R object attributes are strings, as long as this interface is able to serialize them into strings. See also `igraph_attribute_table_t`.

Values:

<code>IGRAPH_ATTRIBUTE_UNSPECIFIED</code> :	Currently used internally as a "null value" or "placeholder value" in some algorithms. Attribute records with this type must not be passed to igraph functions.
<code>IGRAPH_ATTRIBUTE_NUMERIC</code> :	Numeric attribute.
<code>IGRAPH_ATTRIBUTE_BOOLEAN</code> :	Logical values, true or false.
<code>IGRAPH_ATTRIBUTE_STRING</code> :	Attribute that can be converted to a string.
<code>IGRAPH_ATTRIBUTE_OBJECT</code> :	Custom attribute type, to be used for special data types by client applications. The R and Python interfaces use this for attributes that hold R or Python objects. Usually ignored by igraph functions.

Handling attribute combination lists

Several graph operations may collapse multiple vertices or edges into a single one. Attribute combination lists are used to indicate to the attribute handler how to combine the attributes of the original

vertices or edges and how to derive the final attribute value that is to be assigned to the collapsed vertex or edge. For example, `igraph_simplify()` removes loops and combines multiple edges into a single one; in case of a graph with an edge attribute named `weight` the attribute combination list can tell the attribute handler whether the weight of a collapsed edge should be the sum, the mean or some other function of the weights of the original edges that were collapsed into one.

One attribute combination list may contain several attribute combination records, one for each vertex or edge attribute that is to be handled during the operation.

`igraph_attribute_combination_init` — Initialize attribute combination list.

```
igraph_error_t igraph_attribute_combination_init(igraph_attribute_combination_t
```

Arguments:

comb: The uninitialized attribute combination list.

Returns:

Error code.

Time complexity: $O(1)$

`igraph_attribute_combination_add` — Add combination record to attribute combination list.

```
igraph_error_t igraph_attribute_combination_add(igraph_attribute_combination_t  
                                                const char *name,  
                                                igraph_attribute_combination_type_t type,  
                                                igraph_function_pointer_t func);
```

Arguments:

comb: The attribute combination list.

name: The name of the attribute. If the name already exists the attribute combination record will be replaced. Use `NULL` to add a default combination record for all attributes not in the list.

type: The type of the attribute combination. See `igraph_attribute_combination_type_t` for the options.

func: Function to be used if *type* is `IGRAPH_ATTRIBUTE_COMBINE_FUNCTION`.

Returns:

Error code.

Time complexity: $O(n)$, where n is the number of current attribute combinations.

igraph_attribute_combination_remove — Remove a record from an attribute combination list.

```
igraph_error_t igraph_attribute_combination_remove(igraph_attribute_combination_t *comb,  
                                                    const char *name);
```

Arguments:

comb: The attribute combination list.

name: The attribute name of the attribute combination record to remove. It will be ignored if the named attribute does not exist. It can be NULL to remove the default combination record.

Returns:

Error code. This currently always returns IGRAPH_SUCCESS.

Time complexity: $O(n)$, where n is the number of records in the attribute combination list.

igraph_attribute_combination_destroy — Destroy attribute combination list.

```
void igraph_attribute_combination_destroy(igraph_attribute_combination_t *comb)
```

Arguments:

comb: The attribute combination list.

Time complexity: $O(n)$, where n is the number of records in the attribute combination list.

igraph_attribute_combination_type_t — The possible types of attribute combinations.

```
typedef enum {  
    IGRAPH_ATTRIBUTE_COMBINE_IGNORE = 0,  
    IGRAPH_ATTRIBUTE_COMBINE_DEFAULT = 1,  
    IGRAPH_ATTRIBUTE_COMBINE_FUNCTION = 2,  
    IGRAPH_ATTRIBUTE_COMBINE_SUM = 3,  
    IGRAPH_ATTRIBUTE_COMBINE_PROD = 4,  
    IGRAPH_ATTRIBUTE_COMBINE_MIN = 5,  
    IGRAPH_ATTRIBUTE_COMBINE_MAX = 6,  
    IGRAPH_ATTRIBUTE_COMBINE_RANDOM = 7,  
    IGRAPH_ATTRIBUTE_COMBINE_FIRST = 8,  
    IGRAPH_ATTRIBUTE_COMBINE_LAST = 9,  
    IGRAPH_ATTRIBUTE_COMBINE_MEAN = 10,  
    IGRAPH_ATTRIBUTE_COMBINE_MEDIAN = 11,  
    IGRAPH_ATTRIBUTE_COMBINE_CONCAT = 12  
}
```

```
} igraph_attribute_combination_type_t;
```

Values:

IGRAPH_ATTRIBUTE_COMBINE_IGNORE:	Ignore old attributes, use an empty value.
IGRAPH_ATTRIBUTE_COMBINE_DEFAULT:	Use the default way to combine attributes (decided by the attribute handler implementation).
IGRAPH_ATTRIBUTE_COMBINE_FUNCTION:	Supply your own function to combine attributes.
IGRAPH_ATTRIBUTE_COMBINE_SUM:	Take the sum of the attributes.
IGRAPH_ATTRIBUTE_COMBINE_PROD:	Take the product of the attributes.
IGRAPH_ATTRIBUTE_COMBINE_MIN:	Take the minimum attribute.
IGRAPH_ATTRIBUTE_COMBINE_MAX:	Take the maximum attribute.
IGRAPH_ATTRIBUTE_COMBINE_RANDOM:	Take a random attribute.
IGRAPH_ATTRIBUTE_COMBINE_FIRST:	Take the first attribute.
IGRAPH_ATTRIBUTE_COMBINE_LAST:	Take the last attribute.
IGRAPH_ATTRIBUTE_COMBINE_MEAN:	Take the mean of the attributes.
IGRAPH_ATTRIBUTE_COMBINE_MEDIAN:	Take the median of the attributes.
IGRAPH_ATTRIBUTE_COMBINE_CONCAT:	Concatenate the attributes.

Accessing attributes from C

There is an experimental attribute handler that can be used from C code. In this section we show how this works. This attribute handler is by default not attached (the default is no attribute handler), so we first need to attach it:

```
igraph_set_attribute_table(&igraph_cattribute_table);
```

Now the attribute functions are available. Please note that the attribute handler must be attached before you call any other igraph functions, otherwise you might end up with graphs without attributes and an active attribute handler, which might cause unexpected program behaviour. The rule is that you attach the attribute handler in the beginning of your `main()` and never touch it again. Detaching the attribute handler might lead to memory leaks.

It is not currently possible to have attribute handlers on a per-graph basis. All graphs in an application must be managed with the same attribute handler. This also applies to the default case when there is no attribute handler at all.

The C attribute handler supports attaching real numbers, boolean values and character strings as attributes. No vector values are allowed. For example, vertices have a `name` attribute holding a single string value for each vertex, but it is not possible to have a `coords` attribute which is a vector of numbers per vertex.

The functions documented in this section are specific to the C attribute handler. Code using these functions will not function when a different attribute handler is attached.

Example 12.1. File `examples/simple/cattributes.c`

Example 12.2. File `examples/simple/cattributes2.c`

Example 12.3. File `examples/simple/cattributes3.c`

Example 12.4. File `examples/simple/cattributes4.c`

Query attributes

`igraph_cattribute_list` — List all attributes.

```
igraph_error_t igraph_cattribute_list(const igraph_t *graph,
                                     igraph_strvector_t *gnames, igraph_vector_int_t *gtypes,
                                     igraph_strvector_t *vnames, igraph_vector_int_t *vtypes,
                                     igraph_strvector_t *enames, igraph_vector_int_t *etypes)
```

See `igraph_attribute_type_t` for the various attribute types.

Arguments:

graph: The input graph.

gnames: String vector, the names of the graph attributes.

gtypes: Numeric vector, the types of the graph attributes.

vnames: String vector, the names of the vertex attributes.

vtypes: Numeric vector, the types of the vertex attributes.

enames: String vector, the names of the edge attributes.

etypes: Numeric vector, the types of the edge attributes.

Returns:

Error code.

Naturally, the string vector with the attribute names and the numeric vector with the attribute types are in the right order, i.e. the first name corresponds to the first type, etc. Time complexity: $O(A_g + A_v + A_e)$, the number of all attributes.

igraph_cattribute_has_attr — Checks whether a (graph, vertex or edge) attribute exists.

```
igraph_bool_t igraph_cattribute_has_attr(const igraph_t *graph,
                                         igraph_attribute_element_t type,
                                         const char *name);
```

Arguments:

graph: The graph.

type: The type of the attribute, IGRAPH_ATTRIBUTE_GRAPH, IGRAPH_ATTRIBUTE_VERTEX or IGRAPH_ATTRIBUTE_EDGE.

name: Character constant, the name of the attribute.

Returns:

Logical value, true if the attribute exists, false otherwise.

Time complexity: $O(A)$, the number of (graph, vertex or edge) attributes, assuming attribute names are not too long.

igraph_cattribute_GAN — Query a numeric graph attribute.

```
igraph_real_t igraph_cattribute_GAN(const igraph_t *graph, const char *name);
```

Returns the value of the given numeric graph attribute. If the attribute does not exist, a warning is issued and NaN is returned.

Arguments:

graph: The input graph.

name: The name of the attribute to query.

Returns:

The value of the attribute.

See also:

GAN for a simpler interface.

Time complexity: $O(A_g)$, the number of graph attributes.

GAN — Query a numeric graph attribute.

```
#define GAN(graph,n)
```

This is shorthand for `igraph_cattribute_GAN()`.

Arguments:

graph: The graph.
n: The name of the attribute.

Returns:

The value of the attribute.

igraph_cattribute_GAB — Query a boolean graph attribute.

```
igraph_bool_t igraph_cattribute_GAB(const igraph_t *graph, const char *name);
```

Returns the value of the given boolean graph attribute. If the attribute does not exist, a warning is issued and false is returned.

Arguments:

graph: The input graph.
name: The name of the attribute to query.

Returns:

The value of the attribute.

See also:

GAB for a simpler interface.

Time complexity: $O(A_g)$, the number of graph attributes.

GAB — Query a boolean graph attribute.

```
#define GAB(graph,n)
```

This is shorthand for `igraph_cattribute_GAB()`.

Arguments:

graph: The graph.
n: The name of the attribute.

Returns:

The value of the attribute.

igraph_cattribute_GAS — Query a string graph attribute.

```
const char *igraph_cattribute_GAS(const igraph_t *graph, const char *name);
```

Returns a const pointer to the string graph attribute specified in *name*. The value must not be modified. If the attribute does not exist, a warning is issued and an empty string is returned.

Arguments:

graph: The input graph.

name: The name of the attribute to query.

Returns:

The value of the attribute.

See also:

GAS for a simpler interface.

Time complexity: $O(A_g)$, the number of graph attributes.

GAS — Query a string graph attribute.

```
#define GAS(graph,n)
```

This is shorthand for `igraph_cattribute_GAS()`.

Arguments:

graph: The graph.

n: The name of the attribute.

Returns:

The value of the attribute.

igraph_cattribute_VAN — Query a numeric vertex attribute.

```
igraph_real_t igraph_cattribute_VAN(const igraph_t *graph, const char *name,  
                                     igraph_integer_t vid);
```

If the attribute does not exist, a warning is issued and NaN is returned. See `igraph_cattribute_VANV()` for an error-checked version.

Arguments:

graph: The input graph.

name: The name of the attribute.

vid: The id of the queried vertex.

Returns:

The value of the attribute.

See also:

`VAN` macro for a simpler interface.

Time complexity: $O(A_v)$, the number of vertex attributes.

`VAN` — Query a numeric vertex attribute.

```
#define VAN(graph,n,v)
```

This is shorthand for `igraph_cattribute_VAN()`.

Arguments:

graph: The graph.

n: The name of the attribute.

v: The id of the vertex.

Returns:

The value of the attribute.

`igraph_cattribute_VANV` — Query a numeric vertex attribute for many vertices.

```
igraph_error_t igraph_cattribute_VANV(const igraph_t *graph, const char *name,  
                                       igraph_vs_t vids, igraph_vector_t *result);
```

Arguments:

graph: The input graph.

name: The name of the attribute.

vids: The vertices to query.

result: Pointer to an initialized vector, the result is stored here. It will be resized, if needed.

Returns:

Error code.

Time complexity: $O(v)$, where v is the number of vertices in 'vids'.

`VANV` — Query a numeric vertex attribute for all vertices.

```
#define VANV(graph,n,vec)
```

This is a shorthand for `igraph_cattribute_VANV()`.

Arguments:

graph: The graph.

n: The name of the attribute.

vec: Pointer to an initialized vector, the result is stored here. It will be resized, if needed.

Returns:

Error code.

igraph_cattribute_VAB — Query a boolean vertex attribute.

```
igraph_bool_t igraph_cattribute_VAB(const igraph_t *graph, const char *name,  
                                     igraph_integer_t vid);
```

If the vertex attribute does not exist, a warning is issued and false is returned. See `igraph_cattribute_VABV()` for an error-checked version.

Arguments:

graph: The input graph.

name: The name of the attribute.

vid: The id of the queried vertex.

Returns:

The value of the attribute.

See also:

VAB macro for a simpler interface.

Time complexity: $O(A_v)$, the number of vertex attributes.

VAB — Query a boolean vertex attribute.

```
#define VAB(graph,n,v)
```

This is shorthand for `igraph_cattribute_VAB()`.

Arguments:

graph: The graph.

n: The name of the attribute.

v: The id of the vertex.

Returns:

The value of the attribute.

igraph_cattribute_VABV — Query a boolean vertex attribute for many vertices.

```
igraph_error_t igraph_cattribute_VABV(const igraph_t *graph, const char *name,
                                       igraph_vs_t vids, igraph_vector_bool_t *result);
```

Arguments:

graph: The input graph.

name: The name of the attribute.

vids: The vertices to query.

result: Pointer to an initialized boolean vector, the result is stored here. It will be resized, if needed.

Returns:

Error code.

Time complexity: $O(v)$, where v is the number of vertices in 'vids'.

VABV — Query a boolean vertex attribute for all vertices.

```
#define VABV(graph,n,vec)
```

This is a shorthand for `igraph_cattribute_VABV()`.

Arguments:

graph: The graph.

n: The name of the attribute.

vec: Pointer to an initialized boolean vector, the result is stored here. It will be resized, if needed.

Returns:

Error code.

igraph_cattribute_VAS — Query a string vertex attribute.

```
const char *igraph_cattribute_VAS(const igraph_t *graph, const char *name,
                                  igraph_integer_t vid);
```

Returns a const pointer to the string vertex attribute specified in *name*. The value must not be modified. If the vertex attribute does not exist, a warning is issued and an empty string is returned. See `igraph_cattribute_VASV()` for an error-checked version.

Arguments:

graph: The input graph.
name: The name of the attribute.
vid: The id of the queried vertex.

Returns:

The value of the attribute.

See also:

The macro `VAS` for a simpler interface.

Time complexity: $O(A_v)$, the number of vertex attributes.

VAS — Query a string vertex attribute.

```
#define VAS(graph,n,v)
```

This is shorthand for `igraph_cattribute_VAS()`.

Arguments:

graph: The graph.
n: The name of the attribute.
v: The id of the vertex.

Returns:

The value of the attribute.

igraph_cattribute_VASV — Query a string vertex attribute for many vertices.

```
igraph_error_t igraph_cattribute_VASV(const igraph_t *graph, const char *name,
                                       igraph_vs_t vids, igraph_strvector_t *result);
```

Arguments:

graph: The input graph.

name: The name of the attribute.

vids: The vertices to query.

result: Pointer to an initialized string vector, the result is stored here. It will be resized, if needed.

Returns:

Error code.

Time complexity: $O(v)$, where v is the number of vertices in 'vids'. (We assume that the string attributes have a bounded length.)

VASV — Query a string vertex attribute for all vertices.

```
#define VASV(graph,n,vec)
```

This is a shorthand for `igraph_cattribute_VASV()`.

Arguments:

graph: The graph.

n: The name of the attribute.

vec: Pointer to an initialized string vector, the result is stored here. It will be resized, if needed.

Returns:

Error code.

igraph_cattribute_EAN — Query a numeric edge attribute.

```
igraph_real_t igraph_cattribute_EAN(const igraph_t *graph, const char *name,  
                                   igraph_integer_t eid);
```

If the attribute does not exist, a warning is issued and NaN is returned. See `igraph_cattribute_EANV()` for an error-checked version.

Arguments:

graph: The input graph.

name: The name of the attribute.

eid: The id of the queried edge.

Returns:

The value of the attribute.

See also:

EAN for an easier interface.

Time complexity: $O(A_e)$, the number of edge attributes.

EAN — Query a numeric edge attribute.

```
#define EAN(graph,n,e)
```

This is shorthand for `igraph_cattribute_EAN()`.

Arguments:

graph: The graph.

n: The name of the attribute.

e: The id of the edge.

Returns:

The value of the attribute.

igraph_cattribute_EANV — Query a numeric edge attribute for many edges.

```
igraph_error_t igraph_cattribute_EANV(const igraph_t *graph, const char *name,  
                                     igraph_es_t eids, igraph_vector_t *result);
```

Arguments:

graph: The input graph.

name: The name of the attribute.

eids: The edges to query.

result: Pointer to an initialized vector, the result is stored here. It will be resized, if needed.

Returns:

Error code.

Time complexity: $O(e)$, where e is the number of edges in 'eids'.

EANV — Query a numeric edge attribute for all edges.

```
#define EANV(graph,n,vec)
```

This is a shorthand for `igraph_cattribute_EANV()`.

Arguments:

graph: The graph.

n: The name of the attribute.

vec: Pointer to an initialized vector, the result is stored here. It will be resized, if needed.

Returns:

Error code.

igraph_cattribute_EAB — Query a boolean edge attribute.

```
igraph_bool_t igraph_cattribute_EAB(const igraph_t *graph, const char *name,
                                     igraph_integer_t eid);
```

If the edge attribute does not exist, a warning is issued and false is returned. See `igraph_cattribute_EABV()` for an error-checked version.

Arguments:

graph: The input graph.

name: The name of the attribute.

eid: The id of the queried edge.

Returns:

The value of the attribute.

See also:

EAB for an easier interface.

Time complexity: $O(A_e)$, the number of edge attributes.

EAB — Query a boolean edge attribute.

```
#define EAB(graph,n,e)
```

This is shorthand for `igraph_cattribute_EAB()`.

Arguments:

graph: The graph.

n: The name of the attribute.

e: The id of the edge.

Returns:

The value of the attribute.

igraph_cattribute_EABV — Query a boolean edge attribute for many edges.

```
igraph_error_t igraph_cattribute_EABV(const igraph_t *graph, const char *name,
                                       igraph_es_t eids, igraph_vector_bool_t *result);
```

Arguments:

graph: The input graph.

name: The name of the attribute.

eids: The edges to query.

result: Pointer to an initialized boolean vector, the result is stored here. It will be resized, if needed.

Returns:

Error code.

Time complexity: $O(e)$, where e is the number of edges in 'eids'.

EABV — Query a boolean edge attribute for all edges.

```
#define EABV(graph,n,vec)
```

This is a shorthand for `igraph_cattribute_EABV()`.

Arguments:

graph: The graph.

n: The name of the attribute.

vec: Pointer to an initialized vector, the result is stored here. It will be resized, if needed.

Returns:

Error code.

igraph_cattribute_EAS — Query a string edge attribute.

```
const char *igraph_cattribute_EAS(const igraph_t *graph, const char *name,
                                   igraph_integer_t eid);
```

Returns a const pointer to the string edge attribute specified in *name*. The value must not be modified. If the edge attribute does not exist, a warning is issued and an empty string is returned. See `igraph_cattribute_EASV()` for an error-checked version.

Arguments:

graph: The input graph.
name: The name of the attribute.
eid: The id of the queried edge.

Returns:

The value of the attribute.

\se EAS if you want to type less. Time complexity: $O(Ae)$, the number of edge attributes.

EAS — Query a string edge attribute.

```
#define EAS(graph,n,e)
```

This is shorthand for `igraph_cattribute_EAS()`.

Arguments:

graph: The graph.
n: The name of the attribute.
e: The id of the edge.

Returns:

The value of the attribute.

igraph_cattribute_EASV — Query a string edge attribute for many edges.

```
igraph_error_t igraph_cattribute_EASV(const igraph_t *graph, const char *name,  
                                     igraph_es_t eids, igraph_strvector_t *result);
```

Arguments:

graph: The input graph.
name: The name of the attribute.
vids: The edges to query.
result: Pointer to an initialized string vector, the result is stored here. It will be resized, if needed.

Returns:

Error code.

Time complexity: $O(e)$, where e is the number of edges in 'eids'. (We assume that the string attributes have a bounded length.)

EASV — Query a string edge attribute for all edges.

```
#define EASV(graph,n,vec)
```

This is a shorthand for `igraph_cattribute_EASV()`.

Arguments:

graph: The graph.

n: The name of the attribute.

vec: Pointer to an initialized string vector, the result is stored here. It will be resized, if needed.

Returns:

Error code.

Set attributes

igraph_cattribute_GAN_set — Set a numeric graph attribute.

```
igraph_error_t igraph_cattribute_GAN_set(igraph_t *graph, const char *name,  
                                         igraph_real_t value);
```

Arguments:

graph: The graph.

name: Name of the graph attribute. If there is no such attribute yet, then it will be added.

value: The (new) value of the graph attribute.

Returns:

Error code.

\se SETGAN if you want to type less. Time complexity: O(1).

SETGAN — Set a numeric graph attribute

```
#define SETGAN(graph,n,value)
```

This is a shorthand for `igraph_cattribute_GAN_set()`.

Arguments:

graph: The graph.

n: The name of the attribute.

value: The new value of the attribute.

Returns:

Error code.

igraph_cattribute_GAB_set — Set a boolean graph attribute.

```
igraph_error_t igraph_cattribute_GAB_set(igraph_t *graph, const char *name,
                                          igraph_bool_t value);
```

Arguments:

graph: The graph.

name: Name of the graph attribute. If there is no such attribute yet, then it will be added.

value: The (new) value of the graph attribute.

Returns:

Error code.

\se SETGAB if you want to type less. Time complexity: O(1).

SETGAB — Set a boolean graph attribute

```
#define SETGAB(graph,n,value)
```

This is a shorthand for `igraph_cattribute_GAB_set()`.

Arguments:

graph: The graph.

n: The name of the attribute.

value: The new value of the attribute.

Returns:

Error code.

igraph_cattribute_GAS_set — Set a string graph attribute.

```
igraph_error_t igraph_cattribute_GAS_set(igraph_t *graph, const char *name,
                                          const char *value);
```

Arguments:

graph: The graph.

name: Name of the graph attribute. If there is no such attribute yet, then it will be added.

value: The (new) value of the graph attribute. It will be copied.

Returns:

Error code.

\se SETGAS if you want to type less. Time complexity: O(1).

SETGAS — Set a string graph attribute

```
#define SETGAS(graph,n,value)
```

This is a shorthand for `igraph_cattribute_GAS_set()`.

Arguments:

graph: The graph.

n: The name of the attribute.

value: The new value of the attribute.

Returns:

Error code.

igraph_cattribute_VAN_set — Set a numeric vertex attribute.

```
igraph_error_t igraph_cattribute_VAN_set(igraph_t *graph, const char *name,  
                                         igraph_integer_t vid, igraph_real_t value);
```

The attribute will be added if not present already. If present it will be overwritten. The same *value* is set for all vertices included in *vid*.

Arguments:

graph: The graph.

name: Name of the attribute.

vid: Vertices for which to set the attribute.

value: The (new) value of the attribute.

Returns:

Error code.

See also:

SETVAN for a simpler way.

Time complexity: $O(n)$, the number of vertices if the attribute is new, $O(|vid|)$ otherwise.

SETVAN — Set a numeric vertex attribute

```
#define SETVAN(graph,n,vid,value)
```

This is a shorthand for `igraph_cattribute_VAN_set()`.

Arguments:

graph: The graph.

n: The name of the attribute.

vid: Ids of the vertices to set.

value: The new value of the attribute.

Returns:

Error code.

igraph_cattribute_VAB_set — Set a boolean vertex attribute.

```
igraph_error_t igraph_cattribute_VAB_set(igraph_t *graph, const char *name,  
                                         igraph_integer_t vid, igraph_bool_t value);
```

The attribute will be added if not present already. If present it will be overwritten. The same *value* is set for all vertices included in *vid*.

Arguments:

graph: The graph.

name: Name of the attribute.

vid: Vertices for which to set the attribute.

value: The (new) value of the attribute.

Returns:

Error code.

See also:

SETVAB for a simpler way.

Time complexity: $O(n)$, the number of vertices if the attribute is new, $O(|vid|)$ otherwise.

SETVAB — Set a boolean vertex attribute

```
#define SETVAB(graph,n,vid,value)
```

This is a shorthand for `igraph_cattribute_VAB_set()`.

Arguments:

graph: The graph.
n: The name of the attribute.
vid: Ids of the vertices to set.
value: The new value of the attribute.

Returns:

Error code.

igraph_cattribute_VAS_set — Set a string vertex attribute.

```
igraph_error_t igraph_cattribute_VAS_set(igraph_t *graph, const char *name,  
                                         igraph_integer_t vid, const char *value);
```

The attribute will be added if not present already. If present it will be overwritten. The same *value* is set for all vertices included in *vid*.

Arguments:

graph: The graph.
name: Name of the attribute.
vid: Vertices for which to set the attribute.
value: The (new) value of the attribute.

Returns:

Error code.

See also:

SETVAS for a simpler way.

Time complexity: $O(n \cdot l)$, n is the number of vertices, l is the length of the string to set. If the attribute is not new then only $O(|vid| \cdot l)$.

SETVAS — Set a string vertex attribute

```
#define SETVAS(graph,n,vid,value)
```

This is a shorthand for `igraph_cattribute_VAS_set()`.

Arguments:

graph: The graph.

n: The name of the attribute.
vid: Ids of the vertices to set.
value: The new value of the attribute.

Returns:

Error code.

igraph_cattribute_EAN_set — Set a numeric edge attribute.

```
igraph_error_t igraph_cattribute_EAN_set(igraph_t *graph, const char *name,  
                                         igraph_integer_t eid, igraph_real_t value);
```

The attribute will be added if not present already. If present it will be overwritten. The same *value* is set for all edges included in *vid*.

Arguments:

graph: The graph.
name: Name of the attribute.
eid: Edges for which to set the attribute.
value: The (new) value of the attribute.

Returns:

Error code.

See also:

SETEAN for a simpler way.

Time complexity: $O(e)$, the number of edges if the attribute is new, $O(|eid|)$ otherwise.

SETEAN — Set a numeric edge attribute

```
#define SETEAN(graph,n,eid,value)
```

This is a shorthand for `igraph_cattribute_EAN_set()`.

Arguments:

graph: The graph.
n: The name of the attribute.
eid: Ids of the edges to set.
value: The new value of the attribute.

Returns:

Error code.

igraph_cattribute_EAB_set — Set a boolean edge attribute.

```
igraph_error_t igraph_cattribute_EAB_set(igraph_t *graph, const char *name,
                                          igraph_integer_t eid, igraph_bool_t value);
```

The attribute will be added if not present already. If present it will be overwritten. The same *value* is set for all edges included in *eid*.

Arguments:

graph: The graph.
name: Name of the attribute.
eid: Edges for which to set the attribute.
value: The (new) value of the attribute.

Returns:

Error code.

See also:

SETEAB for a simpler way.

Time complexity: $O(e)$, the number of edges if the attribute is new, $O(|eid|)$ otherwise.

SETEAB — Set a boolean edge attribute

```
#define SETEAB(graph,n,eid,value)
```

This is a shorthand for `igraph_cattribute_EAB_set()`.

Arguments:

graph: The graph.
n: The name of the attribute.
eid: Ids of the edges to set.
value: The new value of the attribute.

Returns:

Error code.

igraph_cattribute_EAS_set — Set a string edge attribute.


```
igraph_error_t igraph_cattribute_EAS_set(igraph_t *graph, const char *name,
                                         igraph_integer_t eid, const char *value);
```

The attribute will be added if not present already. If present it will be overwritten. The same *value* is set for all edges included in *vid*.

Arguments:

graph: The graph.

name: Name of the attribute.

eid: Edges for which to set the attribute.

value: The (new) value of the attribute.

Returns:

Error code.

See also:

SETEAS for a simpler way.

Time complexity: $O(e \cdot l)$, n is the number of edges, l is the length of the string to set. If the attribute is not new then only $O(|eid| \cdot l)$.

SETEAS — Set a string edge attribute

```
#define SETEAS(graph,n,eid,value)
```

This is a shorthand for `igraph_cattribute_EAS_set()`.

Arguments:

graph: The graph.

n: The name of the attribute.

eid: Ids of the edges to set.

value: The new value of the attribute.

Returns:

Error code.

igraph_cattribute_VAN_setv — Set a numeric vertex attribute for all vertices.

```
igraph_error_t igraph_cattribute_VAN_setv(igraph_t *graph, const char *name,
                                           const igraph_vector_t *v);
```

The attribute will be added if not present yet.

Arguments:

graph: The graph.

name: Name of the attribute.

v: The new attribute values. The length of this vector must match the number of vertices.

Returns:

Error code.

See also:

SETVANV for a simpler way.

Time complexity: $O(n)$, the number of vertices.

SETVANV — Set a numeric vertex attribute for all vertices

```
#define SETVANV(graph,n,v)
```

This is a shorthand for `igraph_cattribute_VAN_setv()`.

Arguments:

graph: The graph.

n: The name of the attribute.

v: Vector containing the new values of the attributes.

Returns:

Error code.

igraph_cattribute_VAB_setv — Set a boolean vertex attribute for all vertices.

```
igraph_error_t igraph_cattribute_VAB_setv(igraph_t *graph, const char *name,  
                                           const igraph_vector_bool_t *v);
```

The attribute will be added if not present yet.

Arguments:

graph: The graph.

name: Name of the attribute.

v: The new attribute values. The length of this boolean vector must match the number of vertices.

Returns:

Error code.

See also:

SETVANV for a simpler way.

Time complexity: $O(n)$, the number of vertices.

SETVABV — Set a boolean vertex attribute for all vertices

```
#define SETVABV(graph,n,v)
```

This is a shorthand for `igraph_cattribute_VAB_setv()`.

Arguments:

graph: The graph.

n: The name of the attribute.

v: Vector containing the new values of the attributes.

Returns:

Error code.

igraph_cattribute_VAS_setv — Set a string vertex attribute for all vertices.

```
igraph_error_t igraph_cattribute_VAS_setv(igraph_t *graph, const char *name,  
                                           const igraph_strvector_t *sv);
```

The attribute will be added if not present yet.

Arguments:

graph: The graph.

name: Name of the attribute.

sv: String vector, the new attribute values. The length of this vector must match the number of vertices.

Returns:

Error code.

See also:

SETVASV for a simpler way.

Time complexity: $O(n+l)$, n is the number of vertices, l is the total length of the strings.

SETVASV — Set a string vertex attribute for all vertices

```
#define SETVASV(graph,n,v)
```

This is a shorthand for `igraph_cattribute_VAS_setv()`.

Arguments:

graph: The graph.

n: The name of the attribute.

v: Vector containing the new values of the attributes.

Returns:

Error code.

igraph_cattribute_EAN_setv — Set a numeric edge attribute for all edges.

```
igraph_error_t igraph_cattribute_EAN_setv(igraph_t *graph, const char *name,  
                                           const igraph_vector_t *v);
```

The attribute will be added if not present yet.

Arguments:

graph: The graph.

name: Name of the attribute.

v: The new attribute values. The length of this vector must match the number of edges.

Returns:

Error code.

See also:

SETEANV for a simpler way.

Time complexity: $O(e)$, the number of edges.

SETEANV — Set a numeric edge attribute for all edges

```
#define SETEANV(graph,n,v)
```

This is a shorthand for `igraph_cattribute_EAN_setv()`.

Arguments:

graph: The graph.
n: The name of the attribute.
v: Vector containing the new values of the attributes.

igraph_cattribute_EAB_setv — Set a boolean edge attribute for all edges.

```
igraph_error_t igraph_cattribute_EAB_setv(igraph_t *graph, const char *name,  
                                           const igraph_vector_bool_t *v);
```

The attribute will be added if not present yet.

Arguments:

graph: The graph.
name: Name of the attribute.
v: The new attribute values. The length of this vector must match the number of edges.

Returns:

Error code.

See also:

SETEABV for a simpler way.

Time complexity: $O(e)$, the number of edges.

SETEABV — Set a boolean edge attribute for all edges

```
#define SETEABV(graph,n,v)
```

This is a shorthand for `igraph_cattribute_EAB_setv()`.

Arguments:

graph: The graph.
n: The name of the attribute.
v: Vector containing the new values of the attributes.

igraph_cattribute_EAS_setv — Set a string edge attribute for all edges.

```
igraph_error_t igraph_cattribute_EAS_setv(igraph_t *graph, const char *name,
                                           const igraph_strvector_t *sv);
```

The attribute will be added if not present yet.

Arguments:

graph: The graph.

name: Name of the attribute.

sv: String vector, the new attribute values. The length of this vector must match the number of edges.

Returns:

Error code.

See also:

SETEASV for a simpler way.

Time complexity: $O(e+l)$, e is the number of edges, l is the total length of the strings.

SETEASV — Set a string edge attribute for all edges

```
#define SETEASV(graph,n,v)
```

This is a shorthand for `igraph_cattribute_EAS_setv()`.

Arguments:

graph: The graph.

n: The name of the attribute.

v: Vector containing the new values of the attributes.

Remove attributes

igraph_cattribute_remove_g — Remove a graph attribute.

```
void igraph_cattribute_remove_g(igraph_t *graph, const char *name);
```

Arguments:

graph: The graph object.

name: Name of the graph attribute to remove.

See also:

DELGA for a simpler way.

DELGA — Remove a graph attribute.

```
#define DELGA(graph,n)
```

A shorthand for `igraph_cattribute_remove_g()`.

Arguments:

graph: The graph.

n: The name of the attribute to remove.

igraph_cattribute_remove_v — Remove a vertex attribute.

```
void igraph_cattribute_remove_v(igraph_t *graph, const char *name);
```

Arguments:

graph: The graph object.

name: Name of the vertex attribute to remove.

See also:

DELVA for a simpler way.

DELVA — Remove a vertex attribute.

```
#define DELVA(graph,n)
```

A shorthand for `igraph_cattribute_remove_v()`.

Arguments:

graph: The graph.

n: The name of the attribute to remove.

igraph_cattribute_remove_e — Remove an edge attribute.

```
void igraph_cattribute_remove_e(igraph_t *graph, const char *name);
```

Arguments:

graph: The graph object.

name: Name of the edge attribute to remove.

See also:

DELEA for a simpler way.

DELEA — Remove an edge attribute.

```
#define DELEA(graph,n)
```

A shorthand for `igraph_cattribute_remove_e()`.

Arguments:

graph: The graph.

n: The name of the attribute to remove.

igraph_cattribute_remove_all — Remove all graph/vertex/edge attributes.

```
void igraph_cattribute_remove_all(igraph_t *graph, igraph_bool_t g,  
                                igraph_bool_t v, igraph_bool_t e);
```

Arguments:

graph: The graph object.

g: Boolean, whether to remove graph attributes.

v: Boolean, whether to remove vertex attributes.

e: Boolean, whether to remove edge attributes.

See also:

DELGAS, DELVAS, DELEAS, DELALL for simpler ways.

DELGAS — Remove all graph attributes.

```
#define DELGAS(graph)
```

Calls `igraph_cattribute_remove_all()`.

Arguments:

graph: The graph.

DELVAS — Remove all vertex attributes.


```
#define DELVAS(graph)
```

Calls `igraph_cattribute_remove_all()`.

Arguments:

graph: The graph.

DELEAS — Remove all edge attributes.

```
#define DELEAS(graph)
```

Calls `igraph_cattribute_remove_all()`.

Arguments:

graph: The graph.

DELALL — Remove all attributes.

```
#define DELALL(graph)
```

All graph, vertex and edges attributes will be removed. Calls `igraph_cattribute_remove_all()`.

Arguments:

graph: The graph.

Chapter 13. Structural properties of graphs

These functions usually calculate some structural property of a graph, like its diameter, the degree of the nodes, etc.

Basic properties

igraph_are_connected — Decides whether two vertices are connected

```
igraph_error_t igraph_are_connected(const igraph_t *graph,
                                     igraph_integer_t v1, igraph_integer_t v2,
                                     igraph_bool_t *res);
```

Arguments:

graph: The graph object.

v1: The first vertex.

v2: The second vertex.

res: Boolean, true if there is an edge from *v1* to *v2*, false otherwise.

Returns:

The error code IGRAPH_EINVVID is returned if an invalid vertex ID is given.

The function is of course symmetric for undirected graphs.

Time complexity: $O(\min(\log(d1), \log(d2)))$, *d1* is the (out-)degree of *v1* and *d2* is the (in-)degree of *v2*.

Sparsifiers

igraph_spanner — Calculates a spanner of a graph with a given stretch factor.

```
igraph_error_t igraph_spanner(const igraph_t *graph, igraph_vector_int_t *spanner,
                               igraph_real_t stretch, const igraph_vector_t *weights);
```

A spanner of a graph $G = (V, E)$ with a stretch t is a subgraph $H = (V, E_s)$ such that E_s is a subset of E and the distance between any pair of nodes in H is at most t times the distance in G . The returned graph is always a spanner of the given graph with the specified stretch. For weighted graphs the number of edges in the spanner is $O(k * n^{1 + 1/k})$, where $k = (stretch + 1) / 2$, m is the number of edges and n is the number of nodes in G . For unweighted graphs the number of edges is $O(n^{1 + 1/k} + kn)$.

This function is based on the algorithm of Baswana and Sen: "A Simple and Linear Time Randomized Algorithm for Computing Sparse Spanners in Weighted Graphs"

Arguments:

- graph*: An undirected connected graph object. If the graph is directed, the directions of the edges will be ignored.
- spanenr*: An initialized vector, the IDs of the edges that constitute the calculated spanner will be returned here. Use `igraph_subgraph_edges()` to extract the spanner as a separate graph object.
- stretch*: The stretch factor of the spanner.
- weights*: The edge weights or NULL.

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for temporary data.

Time complexity: The algorithm is a randomized Las Vegas algorithm. The expected running time is $O(km)$ where k is the value mentioned above.

(Shortest)-path related functions

igraph_distances — Length of the shortest paths between vertices.

```
igraph_error_t igraph_distances(const igraph_t *graph, igraph_matrix_t *res,
                                const igraph_vs_t from, const igraph_vs_t to,
                                igraph_neimode_t mode);
```

Arguments:

- graph*: The graph object.
- res*: The result of the calculation, a matrix. A pointer to an initialized matrix, to be more precise. The matrix will be resized if needed. It will have the same number of rows as the length of the *from* argument, and its number of columns is the number of vertices in the *to* argument. One row of the matrix shows the distances from/to a given vertex to the ones in *to*. For the unreachable vertices IGRAPH_INFINITY is returned.
- from*: The source vertices.
- to*: The target vertices. It is not allowed to include a vertex twice or more.
- mode*: The type of shortest paths to be used for the calculation in directed graphs. Possible values:
- IGRAPH_OUT the lengths of the outgoing paths are calculated.
 - IGRAPH_IN the lengths of the incoming paths are calculated.
 - IGRAPH_ALL the directed graph is considered as an undirected one for the computation.

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for temporary data.

IGRAPH_EINVAL invalid vertex ID passed.

IGRAPH_EINVMODE invalid mode argument.

Time complexity: $O(n(|V|+|E|))$, n is the number of vertices to calculate, $|V|$ and $|E|$ are the number of vertices and edges in the graph.

See also:

`igraph_get_shortest_paths()` to get the paths themselves, `igraph_distances_dijkstra()` for the weighted version with non-negative weights, `igraph_distances_bellman_ford()` if you also have negative weights.

`igraph_distances_dijkstra` — Weighted shortest path lengths between vertices.

```
igraph_error_t igraph_distances_dijkstra(const igraph_t *graph,
                                         igraph_matrix_t *res,
                                         const igraph_vs_t from,
                                         const igraph_vs_t to,
                                         const igraph_vector_t *weights,
                                         igraph_neimode_t mode);
```

This function implements Dijkstra's algorithm, which can find the weighted shortest path lengths from a source vertex to all other vertices. This function allows specifying a set of source and target vertices. The algorithm is run independently for each source and the results are retained only for the specified targets. This implementation uses a binary heap for efficiency.

Arguments:

graph: The input graph, can be directed.

res: The result, a matrix. A pointer to an initialized matrix should be passed here. The matrix will be resized as needed. Each row contains the distances from a single source, to the vertices given in the *to* argument. Unreachable vertices has distance IGRAPH_INFINITY.

from: The source vertices.

to: The target vertices. It is not allowed to include a vertex twice or more.

weights: The edge weights. All edge weights must be non-negative for Dijkstra's algorithm to work. Additionally, no edge weight may be NaN. If either case does not hold, an error is returned. If this is a null pointer, then the unweighted version, `igraph_distances()` is called.

mode: For directed graphs; whether to follow paths along edge directions (IGRAPH_OUT), or the opposite (IGRAPH_IN), or ignore edge directions completely (IGRAPH_ALL). It is ignored for undirected graphs.

Returns:

Error code.

Time complexity: $O(s*|E|\log|E|+|V|)$, where $|V|$ is the number of vertices, $|E|$ the number of edges and s the number of sources.

See also:

`igraph_distances()` for a (slightly) faster unweighted version or `igraph_distances_bellman_ford()` for a weighted variant that works in the presence of negative edge weights (but no negative loops)

Example 13.1. File `examples/simple/dijkstra.c`

`igraph_distances_bellman_ford` — Weighted shortest path lengths between vertices, allowing negative weights.

```
igraph_error_t igraph_distances_bellman_ford(const igraph_t *graph,
                                             igraph_matrix_t *res,
                                             const igraph_vs_t from,
                                             const igraph_vs_t to,
                                             const igraph_vector_t *weights,
                                             igraph_neimode_t mode);
```

This function implements the Bellman-Ford algorithm to find the weighted shortest paths to all vertices from a single source, allowing negative weights. It is run independently for the given sources. If there are no negative weights, you are better off with `igraph_distances_dijkstra()`.

Arguments:

- graph*: The input graph, can be directed.
- res*: The result, a matrix. A pointer to an initialized matrix should be passed here, the matrix will be resized if needed. Each row contains the distances from a single source, to all vertices in the graph, in the order of vertex IDs. For unreachable vertices the matrix contains `IGRAPH_INFINITY`.
- from*: The source vertices.
- to*: The target vertices.
- weights*: The edge weights. There must not be any closed loop in the graph that has a negative total weight (since this would allow us to decrease the weight of any path containing at least a single vertex of this loop infinitely). Additionally, no edge weight may be NaN. If either case does not hold, an error is returned. If this is a null pointer, then the unweighted version, `igraph_distances()` is called.
- mode*: For directed graphs; whether to follow paths along edge directions (`IGRAPH_OUT`), or the opposite (`IGRAPH_IN`), or ignore edge directions completely (`IGRAPH_ALL`). It is ignored for undirected graphs.

Returns:

Error code.

Time complexity: $O(s*|E|*|V|)$, where $|V|$ is the number of vertices, $|E|$ the number of edges and s the number of sources.

See also:

`igraph_distances()` for a faster unweighted version or `igraph_distances_dijkstra()` if you do not have negative edge weights.

Example 13.2. File `examples/simple/bellman_ford.c`

`igraph_distances_johnson` — Weighted shortest path lengths between vertices, using Johnson's algorithm.

```
igraph_error_t igraph_distances_johnson(const igraph_t *graph,
                                       igraph_matrix_t *res,
                                       const igraph_vs_t from,
                                       const igraph_vs_t to,
                                       const igraph_vector_t *weights);
```

See Wikipedia at http://en.wikipedia.org/wiki/Johnson's_algorithm for Johnson's algorithm. This algorithm works even if the graph contains negative edge weights, and it is worth using it if we calculate the shortest paths from many sources.

If no edge weights are supplied, then the unweighted version, `igraph_distances()` is called.

If all the supplied edge weights are non-negative, then Dijkstra's algorithm is used by calling `igraph_distances_dijkstra()`.

Arguments:

graph: The input graph. If negative weights are present, it should be directed.

res: Pointer to an initialized matrix, the result will be stored here, one line for each source vertex, one column for each target vertex.

from: The source vertices.

to: The target vertices. It is not allowed to include a vertex twice or more.

weights: Optional edge weights. If it is a null-pointer, then the unweighted breadth-first search based `igraph_distances()` will be called.

Returns:

Error code.

Time complexity: $O(s|V|\log|V|+|V||E|)$, $|V|$ and $|E|$ are the number of vertices and edges, s is the number of source vertices.

See also:

`igraph_distances()` for a faster unweighted version, `igraph_distances_dijkstra()` if you do not have negative edge weights, `igraph_distances_bellman_ford()` if you only need to calculate shortest paths from a couple of sources.

igraph_get_shortest_paths — Shortest paths from a vertex.

```
igraph_error_t igraph_get_shortest_paths(const igraph_t *graph,
                                         igraph_vector_int_list_t *vertices,
                                         igraph_vector_int_list_t *edges,
                                         igraph_integer_t from, const igraph_vs_t to,
                                         igraph_neimode_t mode,
                                         igraph_vector_int_t *parents,
                                         igraph_vector_int_t *inbound_edges);
```

If there is more than one geodesic between two vertices, this function gives only one of them.

Arguments:

<i>graph</i> :	The graph object.
<i>vertices</i> :	The result, the IDs of the vertices along the paths. This is a list of integer vectors where each element is an <code>igraph_vector_int_t</code> object. The list will be resized as needed. Supply a null pointer here if you don't need these vectors.
<i>edges</i> :	The result, the IDs of the edges along the paths. This is a list of integer vectors where each element is an <code>igraph_vector_int_t</code> object. The list will be resized as needed. Supply a null pointer here if you don't need these vectors.
<i>from</i> :	The id of the vertex from/to which the geodesics are calculated.
<i>to</i> :	Vertex sequence with the IDs of the vertices to/from which the shortest paths will be calculated. A vertex might be given multiple times.
<i>mode</i> :	The type of shortest paths to be used for the calculation in directed graphs. Possible values: IGRAPH_OUT the outgoing paths are calculated. IGRAPH_IN the incoming paths are calculated. IGRAPH_ALL the directed graph is considered as an undirected one for the computation.
<i>parents</i> :	A pointer to an initialized igraph vector or null. If not null, a vector containing the parent of each vertex in the single source shortest path tree is returned here. The parent of vertex <i>i</i> in the tree is the vertex from which vertex <i>i</i> was reached. The parent of the start vertex (in the <i>from</i> argument) is -1. If the parent is -2, it means that the given vertex was not reached from the source during the search. Note that the search terminates if all the vertices in <i>to</i> are reached.
<i>inbound_edges</i> :	A pointer to an initialized igraph vector or null. If not null, a vector containing the inbound edge of each vertex in the single source shortest path tree is returned here. The inbound edge of vertex <i>i</i> in the tree is the edge via which vertex <i>i</i> was reached. The start vertex and vertices that were not reached during the search will have -1 in the corresponding entry of the vector. Note that the search terminates if all the vertices in <i>to</i> are reached.

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for temporary data.

IGRAPH_EINVVID *from* is invalid vertex ID

IGRAPH_EINVMODE invalid mode argument.

Time complexity: $O(|V|+|E|)$, $|V|$ is the number of vertices, $|E|$ the number of edges in the graph.

See also:

`igraph_distances()` if you only need the path lengths but not the paths themselves.

Example	13.3.	File	examples/simple/
<code>igraph_get_shortest_paths.c</code>			

`igraph_get_shortest_path` — Shortest path from one vertex to another one.

```
igraph_error_t igraph_get_shortest_path(const igraph_t *graph,
                                         igraph_vector_int_t *vertices,
                                         igraph_vector_int_t *edges,
                                         igraph_integer_t from,
                                         igraph_integer_t to,
                                         igraph_neimode_t mode);
```

Calculates and returns a single unweighted shortest path from a given vertex to another one. If there are more than one shortest paths between the two vertices, then an arbitrary one is returned.

This function is a wrapper to `igraph_get_shortest_paths()`, for the special case when only one target vertex is considered.

Arguments:

<i>graph</i> :	The input graph, it can be directed or undirected. Directed paths are considered in directed graphs.
<i>vertices</i> :	Pointer to an initialized vector or a null pointer. If not a null pointer, then the vertex IDs along the path are stored here, including the source and target vertices.
<i>edges</i> :	Pointer to an initialized vector or a null pointer. If not a null pointer, then the edge IDs along the path are stored here.
<i>from</i> :	The id of the source vertex.
<i>to</i> :	The id of the target vertex.
<i>mode</i> :	A constant specifying how edge directions are considered in directed graphs. Valid modes are: IGRAPH_OUT, follows edge directions; IGRAPH_IN, follows the opposite directions; and IGRAPH_ALL, ignores edge directions. This argument is ignored for undirected graphs.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges in the graph.

See also:

`igraph_get_shortest_paths()` for the version with more target vertices.

igraph_get_shortest_paths_dijkstra — Weighted shortest paths from a vertex.

```
igraph_error_t igraph_get_shortest_paths_dijkstra(const igraph_t *graph,
                                                  igraph_vector_int_list_t *vertices,
                                                  igraph_vector_int_list_t *edges,
                                                  igraph_integer_t from,
                                                  igraph_vs_t to,
                                                  const igraph_vector_t *weights,
                                                  igraph_neimode_t mode,
                                                  igraph_vector_int_t *parents,
                                                  igraph_vector_int_t *inbound_edges);
```

If there is more than one path with the smallest weight between two vertices, this function gives only one of them.

Arguments:

<i>graph</i> :	The graph object.
<i>vertices</i> :	The result, the IDs of the vertices along the paths. This is a list of integer vectors where each element is an <code>igraph_vector_int_t</code> object. The list will be resized as needed. Supply a null pointer here if you don't need these vectors.
<i>edges</i> :	The result, the IDs of the edges along the paths. This is a list of integer vectors where each element is an <code>igraph_vector_int_t</code> object. The list will be resized as needed. Supply a null pointer here if you don't need these vectors.
<i>from</i> :	The id of the vertex from/to which the geodesics are calculated.
<i>to</i> :	Vertex sequence with the IDs of the vertices to/from which the shortest paths will be calculated. A vertex might be given multiple times. *
<i>weights</i> :	The edge weights. All edge weights must be non-negative for Dijkstra's algorithm to work. Additionally, no edge weight may be NaN. If either case does not hold, an error is returned. If this is a null pointer, then the unweighted version, <code>igraph_get_shortest_paths()</code> is called.
<i>mode</i> :	The type of shortest paths to be use for the calculation in directed graphs. Possible values: <code>IGRAPH_OUT</code> the outgoing paths are calculated. <code>IGRAPH_IN</code> the incoming paths are calculated. <code>IGRAPH_ALL</code> the directed graph is considered as an undirected one for the computation.
<i>parents</i> :	A pointer to an initialized <code>igraph</code> vector or null. If not null, a vector containing the parent of each vertex in the single source shortest path tree is returned here.

The parent of vertex *i* in the tree is the vertex from which vertex *i* was reached. The parent of the start vertex (in the *from* argument) is -1. If the parent is -2, it means that the given vertex was not reached from the source during the search. Note that the search terminates if all the vertices in *to* are reached.

inbound_edges: A pointer to an initialized igraph vector or null. If not null, a vector containing the inbound edge of each vertex in the single source shortest path tree is returned here. The inbound edge of vertex *i* in the tree is the edge via which vertex *i* was reached. The start vertex and vertices that were not reached during the search will have -1 in the corresponding entry of the vector. Note that the search terminates if all the vertices in *to* are reached.

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for temporary data.

IGRAPH_EINVAL *from* is invalid vertex ID

IGRAPH_EINVMODE invalid mode argument.

Time complexity: $O(|E|\log|E|+|V|)$, where $|V|$ is the number of vertices and $|E|$ is the number of edges

See also:

`igraph_distances_dijkstra()` if you only need the path length but not the paths themselves, `igraph_get_shortest_paths()` if all edge weights are equal.

Example 13.4. File examples/simple/
igraph_get_shortest_paths_dijkstra.c

igraph_get_shortest_path_dijkstra — Weighted shortest path from one vertex to another one.

```
igraph_error_t igraph_get_shortest_path_dijkstra(const igraph_t *graph,
                                                igraph_vector_int_t *vertices,
                                                igraph_vector_int_t *edges,
                                                igraph_integer_t from,
                                                igraph_integer_t to,
                                                const igraph_vector_t *weights,
                                                igraph_neimode_t mode);
```

Calculates a single (positively) weighted shortest path from a single vertex to another one, using Dijkstra's algorithm.

This function is a special case (and a wrapper) to `igraph_get_shortest_paths_dijkstra()`.

Arguments:

graph: The input graph, it can be directed or undirected.

vertices: Pointer to an initialized vector or a null pointer. If not a null pointer, then the vertex IDs along the path are stored here, including the source and target vertices.

<i>edges:</i>	Pointer to an initialized vector or a null pointer. If not a null pointer, then the edge IDs along the path are stored here.
<i>from:</i>	The id of the source vertex.
<i>to:</i>	The id of the target vertex.
<i>weights:</i>	The edge weights. All edge weights must be non-negative for Dijkstra's algorithm to work. Additionally, no edge weight may be NaN. If either case does not hold, an error is returned. If this is a null pointer, then the unweighted version, <code>igraph_get_shortest_paths()</code> is called.
<i>mode:</i>	A constant specifying how edge directions are considered in directed graphs. <code>IGRAPH_OUT</code> follows edge directions, <code>IGRAPH_IN</code> follows the opposite directions, and <code>IGRAPH_ALL</code> ignores edge directions. This argument is ignored for undirected graphs.

Returns:

Error code.

Time complexity: $O(|E|\log|E|+|V|)$, $|V|$ is the number of vertices, $|E|$ is the number of edges in the graph.

See also:

`igraph_get_shortest_paths_dijkstra()` for the version with more target vertices.

`igraph_get_shortest_paths_bellman_ford` — Weighted shortest paths from a vertex, allowing negative weights.

```
igraph_error_t igraph_get_shortest_paths_bellman_ford(const igraph_t *graph,
                                                    igraph_vector_int_list_t *vertices,
                                                    igraph_vector_int_list_t *edges,
                                                    igraph_integer_t from,
                                                    igraph_vs_t to,
                                                    const igraph_vector_t *weights,
                                                    igraph_neimode_t mode,
                                                    igraph_vector_int_t *parents,
                                                    igraph_vector_int_t *inbound_edges);
```

This function calculates weighted shortest paths from or to a single vertex, and allows negative weights. When there is more than one shortest path between two vertices, only one of them is returned. If there are no negative weights, you are better off with `igraph_get_shortest_paths_dijkstra()`.

Arguments:

<i>graph:</i>	The input graph, can be directed.
<i>vertices:</i>	The result, the IDs of the vertices along the paths. This is a list of integer vectors where each element is an <code>igraph_vector_int_t</code> object. The list will be resized as needed. Supply a null pointer here if you don't need these vectors.

<i>edges:</i>	The result, the IDs of the edges along the paths. This is a list of integer vectors where each element is an <code>igraph_vector_int_t</code> object. The list will be resized as needed. Supply a null pointer here if you don't need these vectors.
<i>from:</i>	The id of the vertex from/to which the geodesics are calculated.
<i>to:</i>	Vertex sequence with the IDs of the vertices to/from which the shortest paths will be calculated. A vertex might be given multiple times.
<i>weights:</i>	The edge weights. There must not be any closed loop in the graph that has a negative total weight (since this would allow us to decrease the weight of any path containing at least a single vertex of this loop infinitely). If this is a null pointer, then the unweighted version, <code>igraph_get_shortest_paths()</code> is called.
<i>mode:</i>	For directed graphs; whether to follow paths along edge directions (<code>IGRAPH_OUT</code>), or the opposite (<code>IGRAPH_IN</code>), or ignore edge directions completely (<code>IGRAPH_ALL</code>). It is ignored for undirected graphs.
<i>parents:</i>	A pointer to an initialized <code>igraph</code> vector or null. If not null, a vector containing the parent of each vertex in the single source shortest path tree is returned here. The parent of vertex <i>i</i> in the tree is the vertex from which vertex <i>i</i> was reached. The parent of the start vertex (in the <i>from</i> argument) is -1. If the parent is -2, it means that the given vertex was not reached from the source during the search. Note that the search terminates if all the vertices in <i>to</i> are reached.
<i>inbound_edges:</i>	A pointer to an initialized <code>igraph</code> vector or null. If not null, a vector containing the inbound edge of each vertex in the single source shortest path tree is returned here. The inbound edge of vertex <i>i</i> in the tree is the edge via which vertex <i>i</i> was reached. The start vertex and vertices that were not reached during the search will have -1 in the corresponding entry of the vector. Note that the search terminates if all the vertices in <i>to</i> are reached.

Returns:

Error code:

<code>IGRAPH_ENOMEM</code>	Not enough memory for temporary data.
<code>IGRAPH_EINVAL</code>	The weight vector doesn't match the number of edges.
<code>IGRAPH_EINVVID</code>	<i>from</i> is invalid vertex ID
<code>IGRAPH_ENEGLOOP</code>	Bellman-ford algorithm encountered a negative loop.

Time complexity: $O(|E|*|V|)$, where $|V|$ is the number of vertices, $|E|$ the number of edges.

See also:

`igraph_get_shortest_paths()` for a faster unweighted version or `igraph_get_shortest_paths_dijkstra()` if you do not have negative edge weights.

`igraph_get_shortest_path_bellman_ford` — Weighted shortest path from one vertex to another one.

```
igraph_error_t igraph_get_shortest_path_bellman_ford(const igraph_t *graph,
                                                    igraph_vector_int_t *vertices,
                                                    igraph_vector_int_t *edges,
                                                    igraph_integer_t from,
                                                    igraph_integer_t to,
                                                    const igraph_vector_t *weights,
                                                    igraph_neimode_t mode);
```

Calculates a single (positively) weighted shortest path from a single vertex to another one, using Bellman-Ford algorithm.

This function is a special case (and a wrapper) to `igraph_get_shortest_paths_bellman_ford()`.

Arguments:

- graph*: The input graph, it can be directed or undirected.
- vertices*: Pointer to an initialized vector or a null pointer. If not a null pointer, then the vertex IDs along the path are stored here, including the source and target vertices.
- edges*: Pointer to an initialized vector or a null pointer. If not a null pointer, then the edge IDs along the path are stored here.
- from*: The id of the source vertex.
- to*: The id of the target vertex.
- weights*: The edge weights. There must not be any closed loop in the graph that has a negative total weight (since this would allow us to decrease the weight of any path containing at least a single vertex of this loop infinitely). If this is a null pointer, then the unweighted version is called.
- mode*: A constant specifying how edge directions are considered in directed graphs. `IGRAPH_OUT` follows edge directions, `IGRAPH_IN` follows the opposite directions, and `IGRAPH_ALL` ignores edge directions. This argument is ignored for undirected graphs.

Returns:

Error code.

Time complexity: $O(|E|\log|E|+|V|)$, $|V|$ is the number of vertices, $|E|$ is the number of edges in the graph.

See also:

`igraph_get_shortest_paths_bellman_ford()` for the version with more target vertices.

igraph_get_all_shortest_paths — All shortest paths (geodesics) from a vertex.

```
igraph_error_t igraph_get_all_shortest_paths(const igraph_t *graph,
                                              igraph_vector_int_list_t *vertices,
                                              igraph_vector_int_list_t *edges,
                                              igraph_vector_int_t *nrgeo,
                                              igraph_integer_t from, const igraph_vs_t to,
```

```
igraph_neimode_t mode);
```

When there is more than one shortest path between two vertices, all of them will be returned.

Arguments:

- graph*: The graph object.
- vertices*: The result, the IDs of the vertices along the paths. This is a list of integer vectors where each element is an `igraph_vector_int_t` object. Each vector object contains the vertices along a shortest path from *from* to another vertex. The vectors are ordered according to their target vertex: first the shortest paths to vertex 0, then to vertex 1, etc. No data is included for unreachable vertices. The list will be resized as needed. Supply a null pointer here if you don't need these vectors.
- edges*: The result, the IDs of the edges along the paths. This is a list of integer vectors where each element is an `igraph_vector_int_t` object. Each vector object contains the edges along a shortest path from *from* to another vertex. The vectors are ordered according to their target vertex: first the shortest paths to vertex 0, then to vertex 1, etc. No data is included for unreachable vertices. The list will be resized as needed. Supply a null pointer here if you don't need these vectors.
- nrgeo*: Pointer to an initialized `igraph_vector_int_t` object or NULL. If not NULL the number of shortest paths from *from* are stored here for every vertex in the graph. Note that the values will be accurate only for those vertices that are in the target vertex sequence (see *to*), since the search terminates as soon as all the target vertices have been found.
- from*: The id of the vertex from/to which the geodesics are calculated.
- to*: Vertex sequence with the IDs of the vertices to/from which the shortest paths will be calculated. A vertex might be given multiple times.
- mode*: The type of shortest paths to be use for the calculation in directed graphs. Possible values:
- | | |
|-------------------------|--|
| <code>IGRAPH_OUT</code> | the lengths of the outgoing paths are calculated. |
| <code>IGRAPH_IN</code> | the lengths of the incoming paths are calculated. |
| <code>IGRAPH_ALL</code> | the directed graph is considered as an undirected one for the computation. |

Returns:

Error code:

- | | |
|------------------------------|---------------------------------------|
| <code>IGRAPH_ENOMEM</code> | not enough memory for temporary data. |
| <code>IGRAPH_EINVAL</code> | <i>from</i> is invalid vertex ID. |
| <code>IGRAPH_EINVMODE</code> | invalid mode argument. |

Added in version 0.2.

Time complexity: $O(|V|+|E|)$ for most graphs, $O(|V|^2)$ in the worst case.

`igraph_get_all_shortest_paths_dijkstra` — All weighted shortest paths (geodesics) from a vertex.

```
igraph_error_t igraph_get_all_shortest_paths_dijkstra(const igraph_t *graph,
    igraph_vector_int_list_t *vertices,
    igraph_vector_int_list_t *edges,
    igraph_vector_int_t *nrgeo,
    igraph_integer_t from, igraph_vs_t to,
    const igraph_vector_t *weights,
    igraph_neimode_t mode);
```

Arguments:

- graph*: The graph object.
- vertices*: Pointer to an initialized integer vector list or NULL. If not NULL, then each vector object contains the vertices along a shortest path from *from* to another vertex. The vectors are ordered according to their target vertex: first the shortest paths to vertex 0, then to vertex 1, etc. No data is included for unreachable vertices.
- edges*: Pointer to an initialized integer vector list or NULL. If not NULL, then each vector object contains the edges along a shortest path from *from* to another vertex. The vectors are ordered according to their target vertex: first the shortest paths to vertex 0, then to vertex 1, etc. No data is included for unreachable vertices.
- nrgeo*: Pointer to an initialized `igraph_vector_int_t` object or NULL. If not NULL the number of shortest paths from *from* are stored here for every vertex in the graph. Note that the values will be accurate only for those vertices that are in the target vertex sequence (see *to*), since the search terminates as soon as all the target vertices have been found.
- from*: The id of the vertex from/to which the geodesics are calculated.
- to*: Vertex sequence with the IDs of the vertices to/from which the shortest paths will be calculated. A vertex might be given multiple times.
- weights*: The edge weights. All edge weights must be non-negative for Dijkstra's algorithm to work. Additionally, no edge weight may be NaN. If either case does not hold, an error is returned. If this is a null pointer, then the unweighted version, `igraph_get_all_shortest_paths()` is called.
- mode*: The type of shortest paths to be use for the calculation in directed graphs. Possible values:
- `IGRAPH_OUT` the outgoing paths are calculated.
 - `IGRAPH_IN` the incoming paths are calculated.
 - `IGRAPH_ALL` the directed graph is considered as an undirected one for the computation.

Returns:

Error code:

- `IGRAPH_ENOMEM` not enough memory for temporary data.
- `IGRAPH_EINVVID` *from* is an invalid vertex ID
- `IGRAPH_EINVMODE` invalid mode argument.

Time complexity: $O(|E|\log|E|+|V|)$, where $|V|$ is the number of vertices and $|E|$ is the number of edges

See also:

`igraph_distances_dijkstra()` if you only need the path length but not the paths themselves, `igraph_get_all_shortest_paths()` if all edge weights are equal.

Example **13.5.** **File** **examples/simple/**
igraph_get_all_shortest_paths_dijkstra.c

igraph_get_k_shortest_paths — k shortest paths between two vertices.

```
igraph_error_t igraph_get_k_shortest_paths(  
    const igraph_t *graph, const igraph_vector_t *weights,  
    igraph_vector_int_list_t *vertex_paths,  
    igraph_vector_int_list_t *edge_paths,  
    igraph_integer_t k, igraph_integer_t from, igraph_integer_t to,  
    igraph_neimode_t mode  
);
```

Arguments:

<i>graph</i> :	The graph object.
<i>weights</i> :	The edge weights of the graph. Can be NULL for an unweighted graph. Infinite weights will be treated as missing edges.
<i>vertex_paths</i> :	Pointer to an initialized list of integer vectors, the result will be stored here in <code>igraph_vector_int_t</code> objects. Each vector object contains the vertex IDs along the <i>k</i> th shortest path between <i>from</i> and <i>to</i> , where <i>k</i> is the vector list index. May be NULL if the vertex paths are not needed.
<i>edge_paths</i> :	Pointer to an initialized list of integer vectors, the result will be stored here in <code>igraph_vector_int_t</code> objects. Each vector object contains the edge IDs along the <i>k</i> th shortest path between <i>from</i> and <i>to</i> , where <i>k</i> is the vector list index. May be NULL if the edge paths are not needed.
<i>k</i> :	The number of paths.
<i>from</i> :	The ID of the vertex from which the paths are calculated.
<i>to</i> :	The ID of the vertex to which the paths are calculated.
<i>mode</i> :	The type of paths to be used for the calculation in directed graphs. Possible values: IGRAPH_OUT The outgoing paths of <i>from</i> are calculated. IGRAPH_IN The incoming paths of <i>from</i> are calculated. IGRAPH_ALL The directed graph is considered as an undirected one for the computation.

Returns:

Error code:

IGRAPH_ENOMEM	Not enough memory for temporary data.
IGRAPH_EINVAL	<i>from</i> or <i>to</i> is an invalid vertex id.
IGRAPH_EINVMODE	Invalid mode argument.
IGRAPH_EINVAL	Invalid argument.

Time complexity: $k |V| (|V| \log |V| + |E|)$, where $|V|$ is the number of vertices, and $|E|$ is the number of edges.

igraph_get_all_simple_paths — List all simple paths from one source.

```
igraph_error_t igraph_get_all_simple_paths(const igraph_t *graph,
                                           igraph_vector_int_t *res,
                                           igraph_integer_t from,
                                           const igraph_vs_t to,
                                           igraph_integer_t cutoff,
                                           igraph_neimode_t mode);
```

A path is simple if its vertices are unique, i.e. no vertex is visited more than once.

Note that potentially there are exponentially many paths between two vertices of a graph, and you may run out of memory when using this function, if your graph is lattice-like.

This function currently ignored multiple and loop edges.

Arguments:

<i>graph</i> :	The input graph.
<i>res</i> :	Initialized integer vector, all paths are returned here, separated by -1 markers. The paths are included in arbitrary order, as they are found.
<i>from</i> :	The start vertex.
<i>to</i> :	The target vertices.
<i>cutoff</i> :	Maximum length of path that is considered. If negative, paths of all lengths are considered.
<i>mode</i> :	The type of the paths to consider, it is ignored for undirected graphs.

Returns:

Error code.

Time complexity: $O(n!)$ in the worst case, n is the number of vertices.

igraph_average_path_length — Calculates the average unweighted shortest path length between all vertex pairs.

```
igraph_error_t igraph_average_path_length(const igraph_t *graph,
                                           igraph_real_t *res, igraph_real_t *unconn_pairs,
                                           igraph_bool_t directed, igraph_bool_t unconn);
```

If no vertex pairs can be included in the calculation, for example because the graph has fewer than two vertices, or if the graph has no edges and `unconn` is set to `true`, NaN is returned.

Arguments:

graph: The graph object.

res: Pointer to a real number, this will contain the result.

unconn_pairs: Pointer to a real number. If not a null pointer, the number of ordered vertex pairs where the second vertex is unreachable from the first one will be stored here.

directed: Boolean, whether to consider directed paths. Ignored for undirected graphs.

unconn: What to do if the graph is not connected. If `true`, only those vertex pairs will be included in the calculation between which there is a path. If `false`, `IGRAPH_INFINITY` is returned for disconnected graphs.

Returns:

Error code: `IGRAPH_ENOMEM`, not enough memory for data structures

Time complexity: $O(|V| |E|)$, the number of vertices times the number of edges.

See also:

`igraph_average_path_length_dijkstra()` for the weighted version.

Example	13.6.	File	examples/simple/
igraph_average_path_length.c			

igraph_average_path_length_dijkstra — Cal- culates the average weighted shortest path length be- tween all vertex pairs.

```
igraph_error_t igraph_average_path_length_dijkstra(const igraph_t *graph,
                                                    igraph_real_t *res, igraph_real_t *unconn_pairs,
                                                    const igraph_vector_t *weights,
                                                    igraph_bool_t directed, igraph_bool_t unconn);
```

If no vertex pairs can be included in the calculation, for example because the graph has fewer than two vertices, or if the graph has no edges and `unconn` is set to `true`, NaN is returned.

All distinct ordered vertex pairs are taken into account.

Arguments:

graph: The graph object.

<i>res</i> :	Pointer to a real number, this will contain the result.
<i>unconn_pairs</i> :	Pointer to a real number. If not a null pointer, the number of ordered vertex pairs where the second vertex is unreachable from the first one will be stored here.
<i>weights</i> :	The edge weights. All edge weights must be non-negative for Dijkstra's algorithm to work. Additionally, no edge weight may be NaN. If either case does not hold, an error is returned. If this is a null pointer, then the unweighted version, <code>igraph_average_path_length()</code> is called.
<i>directed</i> :	Boolean, whether to consider directed paths. Ignored for undirected graphs.
<i>unconn</i> :	If <code>true</code> , only those pairs are considered for the calculation between which there is a path. If <code>false</code> , <code>IGRAPH_INFINITY</code> is returned for disconnected graphs.

Returns:

Error code:

`IGRAPH_ENOMEM` not enough memory for data structures

`IGRAPH_EINVAL` invalid weight vector

Time complexity: $O(|V| |E| \log |E| + |V|)$, where $|V|$ is the number of vertices and $|E|$ is the number of edges.

See also:

`igraph_average_path_length()` for a slightly faster unweighted version.

Example 13.7. File `examples/simple/igraph_grg_game.c`

igraph_path_length_hist — Create a histogram of all shortest path lengths.

```
igraph_error_t igraph_path_length_hist(const igraph_t *graph, igraph_vector_t *,
                                       igraph_real_t *unconnected, igraph_bool_t directed)
```

This function calculates a histogram, by calculating the shortest path length between each pair of vertices. For directed graphs both directions might be considered and then every pair of vertices appears twice in the histogram.

Arguments:

<i>graph</i> :	The input graph.
<i>res</i> :	Pointer to an initialized vector, the result is stored here. The first (i.e. zeroth) element contains the number of shortest paths of length 1, etc. The supplied vector is resized as needed.
<i>unconnected</i> :	Pointer to a real number, the number of pairs for which the second vertex is not reachable from the first is stored here.
<i>directed</i> :	Whether to consider directed paths in a directed graph (if not zero). This argument is ignored for undirected graphs.

Returns:

Error code.

Time complexity: $O(|V||E|)$, the number of vertices times the number of edges.

See also:

`igraph_average_path_length()` and `igraph_distances()`

igraph_diameter — Calculates the diameter of a graph (longest geodesic).

```
igraph_error_t igraph_diameter(const igraph_t *graph, igraph_real_t *res,
                               igraph_integer_t *from, igraph_integer_t *to,
                               igraph_vector_int_t *vertex_path, igraph_vector_int_t *edge_path,
                               igraph_bool_t directed, igraph_bool_t unconn);
```

The diameter of a graph is the length of the longest shortest path it has. This function computes both the diameter, as well as the corresponding path. The diameter of the null graph is considered be infinity by convention. If the graph has no vertices, `IGRAPH_NAN` is returned.

Arguments:

<i>graph</i> :	The graph object.
<i>res</i> :	Pointer to a real number, if not <code>NULL</code> then it will contain the diameter (the actual distance).
<i>from</i> :	Pointer to an integer, if not <code>NULL</code> it will be set to the source vertex of the diameter path. If the graph has no diameter path, it will be set to -1.
<i>to</i> :	Pointer to an integer, if not <code>NULL</code> it will be set to the target vertex of the diameter path. If the graph has no diameter path, it will be set to -1.
<i>vertex_path</i> :	Pointer to an initialized vector. If not <code>NULL</code> the actual longest geodesic path in terms of vertices will be stored here. The vector will be resized as needed.
<i>edge_path</i> :	Pointer to an initialized vector. If not <code>NULL</code> the actual longest geodesic path in terms of edges will be stored here. The vector will be resized as needed.
<i>directed</i> :	Boolean, whether to consider directed paths. Ignored for undirected graphs.
<i>unconn</i> :	What to do if the graph is not connected. If <code>true</code> the longest geodesic within a component will be returned, otherwise <code>IGRAPH_INFINITY</code> is returned.

Returns:

Error code: `IGRAPH_ENOMEM`, not enough memory for temporary data.

Time complexity: $O(|V||E|)$, the number of vertices times the number of edges.

See also:

`igraph_diameter_dijkstra()`

Example 13.8. File `examples/simple/igraph_diameter.c`**`igraph_diameter_dijkstra` — Calculates the weighted diameter of a graph using Dijkstra's algorithm.**

```
igraph_error_t igraph_diameter_dijkstra(const igraph_t *graph,
                                       const igraph_vector_t *weights,
                                       igraph_real_t *res,
                                       igraph_integer_t *from,
                                       igraph_integer_t *to,
                                       igraph_vector_int_t *vertex_path,
                                       igraph_vector_int_t *edge_path,
                                       igraph_bool_t directed,
                                       igraph_bool_t unconn);
```

This function computes the weighted diameter of a graph. If the graph has no vertices, `IGRAPH_NAN` is returned.

Arguments:

<i>graph</i> :	The input graph, can be directed or undirected.
<i>weights</i> :	The edge weights of the graph. Can be <code>NULL</code> for an unweighted graph.
<i>res</i> :	Pointer to a real number, if not <code>NULL</code> then it will contain the diameter (the actual distance).
<i>from</i> :	Pointer to an integer, if not <code>NULL</code> it will be set to the source vertex of the diameter path. If the graph has no diameter path, it will be set to -1.
<i>to</i> :	Pointer to an integer, if not <code>NULL</code> it will be set to the target vertex of the diameter path. If the graph has no diameter path, it will be set to -1.
<i>vertex_path</i> :	Pointer to an initialized vector. If not <code>NULL</code> the actual longest geodesic path in terms of vertices will be stored here. The vector will be resized as needed.
<i>edge_path</i> :	Pointer to an initialized vector. If not <code>NULL</code> the actual longest geodesic path in terms of edges will be stored here. The vector will be resized as needed.
<i>directed</i> :	Boolean, whether to consider directed paths. Ignored for undirected graphs.
<i>unconn</i> :	What to do if the graph is not connected. If <code>true</code> the longest geodesic within a component will be returned, otherwise <code>IGRAPH_INFINITY</code> is returned.

Returns:

Error code.

Time complexity: $O(|V||E|\log|E|)$, $|V|$ is the number of vertices, $|E|$ is the number of edges.

See also:

`igraph_diameter()`

igraph_girth — The girth of a graph is the length of the shortest cycle in it.

```
igraph_error_t igraph_girth(const igraph_t *graph, igraph_real_t *girth,  
                             igraph_vector_int_t *circle);
```

The current implementation works for undirected graphs only, directed graphs are treated as undirected graphs. Self-loops and multiple edges are ignored.

For graphs that contain no cycles, and only for such graphs, infinity is returned.

This implementation is based on Alon Itai and Michael Rodeh: Finding a minimum circuit in a graph *Proceedings of the ninth annual ACM symposium on Theory of computing*, 1-10, 1977. The first implementation of this function was done by Keith Briggs, thanks Keith.

Arguments:

graph: The input graph.

girth: Pointer to an `igraph_real_t`, if not NULL then the result will be stored here.

circle: Pointer to an initialized vector, the vertex IDs in the shortest circle will be stored here. If NULL then it is ignored.

Returns:

Error code.

Time complexity: $O((|V|+|E|)^2)$, $|V|$ is the number of vertices, $|E|$ is the number of edges in the general case. If the graph has no cycles at all then the function needs $O(|V|+|E|)$ time to realize this and then it stops.

Example 13.9. File `examples/simple/igraph_girth.c`

igraph_eccentricity — Eccentricity of some vertices.

```
igraph_error_t igraph_eccentricity(const igraph_t *graph,  
                                   igraph_vector_t *res,  
                                   igraph_vs_t vids,  
                                   igraph_neimode_t mode);
```

The eccentricity of a vertex is calculated by measuring the shortest distance from (or to) the vertex, to (or from) all vertices in the graph, and taking the maximum.

This implementation ignores vertex pairs that are in different components. Isolated vertices have eccentricity zero.

Arguments:

graph: The input graph, it can be directed or undirected.

res: Pointer to an initialized vector, the result is stored here.

vids: The vertices for which the eccentricity is calculated.

mode: What kind of paths to consider for the calculation: `IGRAPH_OUT`, paths that follow edge directions; `IGRAPH_IN`, paths that follow the opposite directions; and `IGRAPH_ALL`, paths that ignore edge directions. This argument is ignored for undirected graphs.

Returns:

Error code.

Time complexity: $O(v*(|V|+|E|))$, where $|V|$ is the number of vertices, $|E|$ is the number of edges and v is the number of vertices for which eccentricity is calculated.

See also:

`igraph_radius()`.

Example 13.10. File `examples/simple/igraph_eccentricity.c`

`igraph_eccentricity_dijkstra` — Eccentricity of some vertices, using weighted edges.

```
igraph_error_t igraph_eccentricity_dijkstra(const igraph_t *graph,
                                           const igraph_vector_t *weights,
                                           igraph_vector_t *res,
                                           igraph_vs_t vids,
                                           igraph_neimode_t mode);
```

The eccentricity of a vertex is calculated by measuring the shortest distance from (or to) the vertex, to (or from) all vertices in the graph, and taking the maximum.

This implementation ignores vertex pairs that are in different components. Isolated vertices have eccentricity zero.

Arguments:

graph: The input graph, it can be directed or undirected.

weights: The edge weights. All edge weights must be non-negative for Dijkstra's algorithm to work. Additionally, no edge weight may be NaN. If either case does not hold, an error is returned. If this is a null pointer, then the unweighted version, `igraph_eccentricity()` is called.

res: Pointer to an initialized vector, the result is stored here.

vids: The vertices for which the eccentricity is calculated.

mode: What kind of paths to consider for the calculation: `IGRAPH_OUT`, paths that follow edge directions; `IGRAPH_IN`, paths that follow the opposite directions; and `IGRAPH_ALL`, paths that ignore edge directions. This argument is ignored for undirected graphs.

Returns:

Error code.

igraph_graph_center — Central vertices of a graph.

```
igraph_error_t igraph_graph_center(  
    const igraph_t *graph, igraph_vector_int_t *res, igraph_neimode_t mode  
);
```

The central vertices of a graph are calculated by finding the vertices with the minimum eccentricity. This concept is typically applied to connected graphs. In undirected disconnected graphs, the calculation is effectively done per connected component.

Arguments:

graph: The input graph, it can be directed or undirected.

res: Pointer to an initialized vector, the result is stored here.

mode: What kind of paths to consider for the calculation: IGRAPH_OUT, paths that follow edge directions; IGRAPH_IN, paths that follow the opposite directions; and IGRAPH_ALL, paths that ignore edge directions. This argument is ignored for undirected graphs.

Returns:

Error code.

Time complexity: $O(|V| (|V|+|E|))$, where $|V|$ is the number of vertices and $|E|$ is the number of edges.

See also:

`igraph_eccentricity()`.

igraph_radius — Radius of a graph.

```
igraph_error_t igraph_radius(const igraph_t *graph, igraph_real_t *radius,  
                             igraph_neimode_t mode);
```

The radius of a graph is defined as the minimum eccentricity of its vertices, see `igraph_eccentricity()`.

Arguments:

graph: The input graph, it can be directed or undirected.

radius: Pointer to a real variable, the result is stored here.

mode: What kind of paths to consider for the calculation: IGRAPH_OUT, paths that follow edge directions; IGRAPH_IN, paths that follow the opposite directions; and IGRAPH_ALL, paths that ignore edge directions. This argument is ignored for undirected graphs.

Returns:

Error code.

Time complexity: $O(|V|(|V|+|E|))$, where $|V|$ is the number of vertices and $|E|$ is the number of edges.

See also:

`igraph_eccentricity()`.

Example 13.11. File `examples/simple/igraph_radius.c`

`igraph_pseudo_diameter` — Approximation and lower bound of diameter.

```
igraph_error_t igraph_pseudo_diameter(const igraph_t *graph,
                                       igraph_real_t *diameter,
                                       igraph_integer_t vid_start,
                                       igraph_integer_t *from,
                                       igraph_integer_t *to,
                                       igraph_bool_t directed,
                                       igraph_bool_t unconn);
```

This algorithm finds a pseudo-peripheral vertex and returns its eccentricity. This value can be used as an approximation and lower bound of the diameter of a graph.

A pseudo-peripheral vertex is a vertex v , such that for every vertex u which is as far away from v as possible, v is also as far away from u as possible. The process of finding one depends on where the search starts, and for a disconnected graph the maximum diameter found will be that of the component `vid_start` is in.

Arguments:

- graph*: The input graph, if it is directed, its edge directions are ignored.
- diameter*: Pointer to a real variable, the result is stored here.
- vid_start*: Id of the starting vertex. If this is negative, a random starting vertex is chosen.
- from*: Pointer to an integer, if not NULL it will be set to the source vertex of the diameter path. If *unconn* is false, and a disconnected graph is detected, this is set to -1.
- to*: Pointer to an integer, if not NULL it will be set to the target vertex of the diameter path. If *unconn* is false, and a disconnected graph is detected, this is set to -1.
- directed*: Boolean, whether to consider directed paths. Ignored for undirected graphs.
- unconn*: What to do if the graph is not connected. If true the longest geodesic within a component will be returned, otherwise `IGRAPH_INFINITY` is returned.

Returns:

Error code.

Time complexity: $O(|V||E|)$, where $|V|$ is the number of vertices and $|E|$ is the number of edges.

See also:

`igraph_eccentricity()`, `igraph_diameter()`.

igraph_vertex_path_from_edge_path — Converts a path of edge IDs to the traversed vertex IDs.

```
igraph_error_t igraph_vertex_path_from_edge_path(  
    const igraph_t *graph, igraph_integer_t start,  
    const igraph_vector_int_t *edge_path, igraph_vector_int_t *vertex_path,  
    igraph_neimode_t mode  
);
```

This function is useful when you have a sequence of edge IDs representing a continuous path in a graph and you would like to obtain the vertex IDs that the path traverses. The function is used implicitly by several shortest path related functions to convert a path of edge IDs to the corresponding representation that describes the path in terms of vertex IDs instead.

Arguments:

graph: the graph that the edge IDs refer to
start: the start vertex of the path
edge_path: the sequence of edge IDs that describe the path
vertex_path: the sequence of vertex IDs traversed will be returned here

Returns:

Error code: `IGRAPH_ENOMEM` if there is not enough memory, `IGRAPH_EINVAL` if the edge path does not start at the given vertex or if there is at least one edge whose start vertex does not match the end vertex of the previous edge

Widest-path related functions

igraph_get_widest_path — Widest path from one vertex to another one.

```
igraph_error_t igraph_get_widest_path(const igraph_t *graph,  
                                     igraph_vector_int_t *vertices,  
                                     igraph_vector_int_t *edges,  
                                     igraph_integer_t from,  
                                     igraph_integer_t to,  
                                     const igraph_vector_t *weights,  
                                     igraph_neimode_t mode);
```

Calculates a single widest path from a single vertex to another one, using Dijkstra's algorithm.

This function is a special case (and a wrapper) to `igraph_get_widest_paths()`.

Arguments:

graph: The input graph, it can be directed or undirected.

vertices: Pointer to an initialized vector or a null pointer. If not a null pointer, then the vertex IDs along the path are stored here, including the source and target vertices.

edges: Pointer to an initialized vector or a null pointer. If not a null pointer, then the edge IDs along the path are stored here.

from: The id of the source vertex.

to: The id of the target vertex.

weights: The edge weights. Edge weights can be negative. If this is a null pointer or if any edge weight is NaN, then an error is returned.

mode: A constant specifying how edge directions are considered in directed graphs. IGRAPH_OUT follows edge directions, IGRAPH_IN follows the opposite directions, and IGRAPH_ALL ignores edge directions. This argument is ignored for undirected graphs.

Returns:

Error code.

Time complexity: $O(|E|\log|E|+|V|)$, $|V|$ is the number of vertices, $|E|$ is the number of edges in the graph.

See also:

`igraph_get_widest_paths()` for the version with more target vertices.

igraph_get_widest_paths — Widest paths from a single vertex.

```
igraph_error_t igraph_get_widest_paths(const igraph_t *graph,
                                       igraph_vector_int_list_t *vertices,
                                       igraph_vector_int_list_t *edges,
                                       igraph_integer_t from,
                                       igraph_vs_t to,
                                       const igraph_vector_t *weights,
                                       igraph_neimode_t mode,
                                       igraph_vector_int_t *parents,
                                       igraph_vector_int_t *inbound_edges);
```

Calculates the widest paths from a single node to all other specified nodes, using a modified Dijkstra's algorithm. If there is more than one path with the largest width between two vertices, this function gives only one of them.

Arguments:

graph: The graph object.

vertices: The result, the IDs of the vertices along the paths. This is a list of integer vectors where each element is an `igraph_vector_int_t` object. The list will be resized as needed. Supply a null pointer here if you don't need these vectors.

edges: The result, the IDs of the edges along the paths. This is a list of integer vectors where each element is an `igraph_vector_int_t` object. The list will be resized as needed. Supply a null pointer here if you don't need these vectors.

<i>from</i> :	The id of the vertex from/to which the widest paths are calculated.
<i>to</i> :	Vertex sequence with the IDs of the vertices to/from which the widest paths will be calculated. A vertex might be given multiple times.
<i>weights</i> :	The edge weights. Edge weights can be negative. If this is a null pointer or if any edge weight is NaN, then an error is returned.
<i>mode</i> :	The type of widest paths to be used for the calculation in directed graphs. Possible values: <div> <div>IGRAPH_OUT the outgoing paths are calculated.</div> <div>IGRAPH_IN the incoming paths are calculated.</div> <div>IGRAPH_ALL the directed graph is considered as an undirected one for the computation.</div> </div>
<i>parents</i> :	A pointer to an initialized igraph vector or null. If not null, a vector containing the parent of each vertex in the single source widest path tree is returned here. The parent of vertex <i>i</i> in the tree is the vertex from which vertex <i>i</i> was reached. The parent of the start vertex (in the <i>from</i> argument) is -1. If the parent is -2, it means that the given vertex was not reached from the source during the search. Note that the search terminates if all the vertices in <i>to</i> are reached.
<i>inbound_edges</i> :	A pointer to an initialized igraph vector or null. If not null, a vector containing the inbound edge of each vertex in the single source widest path tree is returned here. The inbound edge of vertex <i>i</i> in the tree is the edge via which vertex <i>i</i> was reached. The start vertex and vertices that were not reached during the search will have -1 in the corresponding entry of the vector. Note that the search terminates if all the vertices in <i>to</i> are reached.

Returns:

Error code:

IGRAPH_ENOMEM	not enough memory for temporary data.
IGRAPH_EINVVID	<i>from</i> is invalid vertex ID
IGRAPH_EINVMODE	invalid mode argument.

Time complexity: $O(|E|\log|E|+|V|)$, where $|V|$ is the number of vertices in the graph and $|E|$ is the number of edges

See also:

`igraph_widest_path_widths_dijkstra()` or `igraph_widest_path_widths_floyd_warshall()` if you only need the widths of the paths but not the paths themselves.

igraph_widest_path_widths_dijkstra — Widths of widest paths between vertices.

```
igraph_error_t igraph_widest_path_widths_dijkstra(const igraph_t *graph,
                                                  igraph_matrix_t *res,
                                                  const igraph_vs_t from,
```

```
const igraph_vs_t to,  
const igraph_vector_t *weights,  
igraph_neimode_t mode);
```

This function implements a modified Dijkstra's algorithm, which can find the widest path widths from a source vertex to all other vertices. This function allows specifying a set of source and target vertices. The algorithm is run independently for each source and the results are retained only for the specified targets. This implementation uses a binary heap for efficiency.

Arguments:

graph: The input graph, can be directed.

res: The result, a matrix. A pointer to an initialized matrix should be passed here. The matrix will be resized as needed. Each row contains the widths from a single source, to the vertices given in the *to* argument. Unreachable vertices have width `IGRAPH_NEGINFINITY`, and vertices have a width of `IGRAPH_POSINFINITY` to themselves.

from: The source vertices.

to: The target vertices. It is not allowed to include a vertex twice or more.

weights: The edge weights. Edge weights can be negative. If this is a null pointer or if any edge weight is NaN, then an error is returned.

mode: For directed graphs; whether to follow paths along edge directions (`IGRAPH_OUT`), or the opposite (`IGRAPH_IN`), or ignore edge directions completely (`IGRAPH_ALL`). It is ignored for undirected graphs.

Returns:

Error code.

Time complexity: $O(s \cdot (|E| \log |E| + |V|))$, where $|V|$ is the number of vertices in the graph, $|E|$ the number of edges and s the number of sources.

See also:

`igraph_widest_path_widths_floyd_warshall()` for a variant that runs faster on dense graphs.

`igraph_widest_path_widths_floyd_warshall` — Widths of widest paths between vertices.

```
igraph_error_t igraph_widest_path_widths_floyd_warshall(const igraph_t *graph,  
                                                         igraph_matrix_t *res,  
                                                         const igraph_vs_t from,  
                                                         const igraph_vs_t to,  
                                                         const igraph_vector_t *weights,  
                                                         igraph_neimode_t mode);
```

This function implements a modified Floyd Warshalls algorithm, to find the widest path widths from a set of source vertices to all other target vertices.

Arguments:

graph: The input graph, can be directed.

res: The result, a matrix. A pointer to an initialized matrix should be passed here. The matrix will be resized as needed. Each row contains the widths from a single source, to the vertices given in the *to* argument. Unreachable vertices have width `IGRAPH_NEGINFINITY`, and vertices have a width of `IGRAPH_POSINFINITY` to themselves.

from: The source vertices.

to: The target vertices. It is not allowed to include a vertex twice or more.

weights: The edge weights. Edge weights can be negative. If this is a null pointer or if any edge weight is NaN, then an error is returned.

mode: For directed graphs; whether to follow paths along edge directions (`IGRAPH_OUT`), or the opposite (`IGRAPH_IN`), or ignore edge directions completely (`IGRAPH_ALL`). It is ignored for undirected graphs.

Returns:

Error code.

Time complexity: $O(|V|^3)$, where $|V|$ is the number of vertices in the graph.

See also:

`igraph_widest_path_widths_dijkstra()` for a variant that runs faster on sparse graphs.

Efficiency measures

`igraph_global_efficiency` — Calculates the global efficiency of a network.

```
igraph_error_t igraph_global_efficiency(const igraph_t *graph, igraph_real_t *res,
                                       const igraph_vector_t *weights,
                                       igraph_bool_t directed);
```

The global efficiency of a network is defined as the average of inverse distances between all pairs of vertices: $E_g = 1/(N*(N-1)) \sum_{i \neq j} 1/d_{ij}$, where N is the number of vertices. The inverse distance between pairs that are not reachable from each other is considered to be zero. For graphs with fewer than 2 vertices, NaN is returned.

Reference: V. Latora and M. Marchiori, Efficient Behavior of Small-World Networks, Phys. Rev. Lett. 87, 198701 (2001). <https://dx.doi.org/10.1103/PhysRevLett.87.198701>

Arguments:

graph: The graph object.

res: Pointer to a real number, this will contain the result.

weights: The edge weights. All edge weights must be non-negative for Dijkstra's algorithm to work. Additionally, no edge weight may be NaN. If either case does not hold, an error

is returned. If this is a null pointer, then the unweighted version, `igraph_average_path_length()` is used in calculating the global efficiency.

directed: Boolean, whether to consider directed paths. Ignored for undirected graphs.

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for data structures

IGRAPH_EINVAL invalid weight vector

Time complexity: $O(|V| |E| \log |E| + |V|)$ for weighted graphs and $O(|V| |E|)$ for unweighted ones. $|V|$ denotes the number of vertices and $|E|$ denotes the number of edges.

igraph_local_efficiency — Calculates the local efficiency around each vertex in a network.

```
igraph_error_t igraph_local_efficiency(const igraph_t *graph, igraph_vector_t *,
                                       const igraph_vs_t vids,
                                       const igraph_vector_t *weights,
                                       igraph_bool_t directed, igraph_neimode_t mode);
```

The local efficiency of a network around a vertex is defined as follows: We remove the vertex and compute the distances (shortest path lengths) between its neighbours through the rest of the network. The local efficiency around the removed vertex is the average of the inverse of these distances.

The inverse distance between two vertices which are not reachable from each other is considered to be zero. The local efficiency around a vertex with fewer than two neighbours is taken to be zero by convention.

Reference: I. Vragovi#, E. Louis, and A. Díaz-Guilera, Efficiency of informational transfer in regular and complex networks, Phys. Rev. E 71, 1 (2005). <http://dx.doi.org/10.1103/PhysRevE.71.036122>

Arguments:

graph: The graph object.

res: Pointer to an initialized vector, this will contain the result.

vids: The vertices around which the local efficiency will be calculated.

weights: The edge weights. All edge weights must be non-negative. Additionally, no edge weight may be NaN. If either case does not hold, an error is returned. If this is a null pointer, then the unweighted version, `igraph_average_path_length()` is called.

directed: Boolean, whether to consider directed paths. Ignored for undirected graphs.

mode: How to determine the local neighborhood of each vertex in directed graphs. Ignored in undirected graphs.

IGRAPH_ALL take both in- and out-neighbours; this is a reasonable default for high-level interfaces.

IGRAPH_OUT take only out-neighbours

IGRAPH_IN take only in-neighbours

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for data structures

IGRAPH_EINVAL invalid weight vector

Time complexity: $O(|E|^2 \log|E|)$ for weighted graphs and $O(|E|^2)$ for unweighted ones. $|E|$ denotes the number of edges.

See also:

`igraph_average_local_efficiency()`

igraph_average_local_efficiency — Calculates the average local efficiency in a network.

```
igraph_error_t igraph_average_local_efficiency(const igraph_t *graph, igraph_real_t *res,
                                              const igraph_vector_t *weights,
                                              igraph_bool_t directed, igraph_neimode_t mode)
```

For the null graph, zero is returned by convention.

Arguments:

graph: The graph object.

res: Pointer to a real number, this will contain the result.

weights: The edge weights. They must be all non-negative. If a null pointer is given, all weights are assumed to be 1.

directed: Boolean, whether to consider directed paths. Ignored for undirected graphs.

mode: How to determine the local neighborhood of each vertex in directed graphs. Ignored in undirected graphs.

IGRAPH_ALL take both in- and out-neighbours; this is a reasonable default for high-level interfaces.

IGRAPH_OUT take only out-neighbours

IGRAPH_IN take only in-neighbours

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for data structures

IGRAPH_EINVAL invalid weight vector

Time complexity: $O(|E|^2 \log|E|)$ for weighted graphs and $O(|E|^2)$ for unweighted ones. $|E|$ denotes the number of edges.

See also:

`igraph_local_efficiency()`

Neighborhood of a vertex

`igraph_neighborhood_size` — Calculates the size of the neighborhood of a given vertex.

```
igraph_error_t igraph_neighborhood_size(const igraph_t *graph, igraph_vector_int_t *res,
                                         igraph_vs_t vids, igraph_integer_t order,
                                         igraph_neimode_t mode,
                                         igraph_integer_t mindist);
```

The neighborhood of a given order of a vertex includes all vertices which are closer to the vertex than the order. I.e., order 0 is always the vertex itself, order 1 is the vertex plus its immediate neighbors, order 2 is order 1 plus the immediate neighbors of the vertices in order 1, etc.

This function calculates the size of the neighborhood of the given order for the given vertices.

Arguments:

- graph*: The input graph.
- res*: Pointer to an initialized vector, the result will be stored here. It will be resized as needed.
- vids*: The vertices for which the calculation is performed.
- order*: Integer giving the order of the neighborhood.
- mode*: Specifies how to use the direction of the edges if a directed graph is analyzed. For `IGRAPH_OUT` only the outgoing edges are followed, so all vertices reachable from the source vertex in at most *order* steps are counted. For `IGRAPH_IN` all vertices from which the source vertex is reachable in at most *order* steps are counted. `IGRAPH_ALL` ignores the direction of the edges. This argument is ignored for undirected graphs.
- mindist*: The minimum distance to include a vertex in the counting. Vertices reachable with a path shorter than this value are excluded. If this is one, then the starting vertex is not counted. If this is two, then its neighbors are not counted either, etc.

Returns:

Error code.

See also:

`igraph_neighborhood()` for calculating the actual neighborhood, `igraph_neighborhood_graphs()` for creating separate graphs from the neighborhoods.

Time complexity: $O(n*d*o)$, where n is the number vertices for which the calculation is performed, d is the average degree, o is the order.

igraph_neighborhood — Calculate the neighborhood of vertices.

```
igraph_error_t igraph_neighborhood(const igraph_t *graph, igraph_vector_int_list_t  
                                igraph_vs_t vids, igraph_integer_t order,  
                                igraph_neimode_t mode, igraph_integer_t mindist);
```

The neighborhood of a given order of a vertex includes all vertices which are closer to the vertex than the order. I.e., order 0 is always the vertex itself, order 1 is the vertex plus its immediate neighbors, order 2 is order 1 plus the immediate neighbors of the vertices in order 1, etc.

This function calculates the vertices within the neighborhood of the specified vertices.

Arguments:

- graph*: The input graph.
- res*: An initialized list of integer vectors. The result of the calculation will be stored here. The list will be resized as needed.
- vids*: The vertices for which the calculation is performed.
- order*: Integer giving the order of the neighborhood.
- mode*: Specifies how to use the direction of the edges if a directed graph is analyzed. For IGRAPH_OUT only the outgoing edges are followed, so all vertices reachable from the source vertex in at most *order* steps are included. For IGRAPH_IN all vertices from which the source vertex is reachable in at most *order* steps are included. IGRAPH_ALL ignores the direction of the edges. This argument is ignored for undirected graphs.
- mindist*: The minimum distance to include a vertex in the counting. Vertices reachable with a path shorter than this value are excluded. If this is one, then the starting vertex is not counted. If this is two, then its neighbors are not counted either, etc.

Returns:

Error code.

See also:

`igraph_neighborhood_size()` to calculate the size of the neighborhood,
`igraph_neighborhood_graphs()` for creating graphs from the neighborhoods.

Time complexity: $O(n*d*o)$, n is the number of vertices for which the calculation is performed, d is the average degree, o is the order.

igraph_neighborhood_graphs — Create graphs from the neighborhood(s) of some vertex/vertices.

```
igraph_error_t igraph_neighborhood_graphs(const igraph_t *graph, igraph_graph_list_t  
                                igraph_vs_t vids, igraph_integer_t order,
```

```
igraph_neimode_t mode,  
igraph_integer_t mindist);
```

The neighborhood of a given order of a vertex includes all vertices which are closer to the vertex than the order. I.e. order 0 is always the vertex itself, order 1 is the vertex plus its immediate neighbors, order 2 is order 1 plus the immediate neighbors of the vertices in order 1, etc.

This function finds every vertex in the neighborhood of a given parameter vertex and creates the induced subgraph from these vertices.

The first version of this function was written by Vincent Matossian, thanks Vincent.

Arguments:

- graph*: The input graph.
- res*: Pointer to a list of graphs, the result will be stored here. Each item in the list is an `igraph_t` object. The list will be resized as needed.
- vids*: The vertices for which the calculation is performed.
- order*: Integer giving the order of the neighborhood.
- mode*: Specifies how to use the direction of the edges if a directed graph is analyzed. For `IGRAPH_OUT` only the outgoing edges are followed, so all vertices reachable from the source vertex in at most *order* steps are counted. For `IGRAPH_IN` all vertices from which the source vertex is reachable in at most *order* steps are counted. `IGRAPH_ALL` ignores the direction of the edges. This argument is ignored for undirected graphs.
- mindist*: The minimum distance to include a vertex in the counting. Vertices reachable with a path shorter than this value are excluded. If this is one, then the starting vertex is not counted. If this is two, then its neighbors are not counted either, etc.

Returns:

Error code.

See also:

`igraph_neighborhood_size()` for calculating the neighborhood sizes only,
`igraph_neighborhood()` for calculating the neighborhoods (but not creating graphs).

Time complexity: $O(n*(|V|+|E|))$, where n is the number vertices for which the calculation is performed, $|V|$ and $|E|$ are the number of vertices and edges in the original input graph.

Local scan statistics

The scan statistic is a summary of the locality statistics that is computed from the local neighborhood of each vertex. For details, see Priebe, C. E., Conroy, J. M., Marchette, D. J., Park, Y. (2005). Scan Statistics on Enron Graphs. Computational and Mathematical Organization Theory.

"Us" statistics

`igraph_local_scan_0` — Local scan-statistics, $k=0$

```
igraph_error_t igraph_local_scan_0(const igraph_t *graph, igraph_vector_t *res,
```

```
const igraph_vector_t *weights,  
igraph_neimode_t mode);
```

K=0 scan-statistics is arbitrarily defined as the vertex degree for unweighted, and the vertex strength for weighted graphs. See `igraph_degree()` and `igraph_strength()`.

Arguments:

graph: The input graph

res: An initialized vector, the results are stored here.

weights: Weight vector for weighted graphs, null pointer for unweighted graphs.

mode: Type of the neighborhood, IGRAPH_OUT means outgoing, IGRAPH_IN means incoming and IGRAPH_ALL means all edges.

Returns:

Error code.

igraph_local_scan_1_ecount — Local scan-statistics, k=1, edge count and sum of weights

```
igraph_error_t igraph_local_scan_1_ecount(const igraph_t *graph, igraph_vector_t  
                                         const igraph_vector_t *weights,  
                                         igraph_neimode_t mode);
```

Count the number of edges or the sum the edge weights in the 1-neighborhood of vertices.

Arguments:

graph: The input graph

res: An initialized vector, the results are stored here.

weights: Weight vector for weighted graphs, null pointer for unweighted graphs.

mode: Type of the neighborhood, IGRAPH_OUT means outgoing, IGRAPH_IN means incoming and IGRAPH_ALL means all edges.

Returns:

Error code.

igraph_local_scan_k_ecount — Sum the number of edges or the weights in k-neighborhood of every vertex.

```
igraph_error_t igraph_local_scan_k_ecount(const igraph_t *graph, igraph_integer_t  
                                         igraph_vector_t *res,  
                                         const igraph_vector_t *weights,  
                                         igraph_neimode_t mode);
```

Arguments:

- graph*: The input graph.
- k*: The size of the neighborhood, non-negative integer. The *k*=0 case is special, see `igraph_local_scan_0()`.
- res*: An initialized vector, the results are stored here.
- weights*: Weight vector for weighted graphs, null pointer for unweighted graphs.
- mode*: Type of the neighborhood, `IGRAPH_OUT` means outgoing, `IGRAPH_IN` means incoming and `IGRAPH_ALL` means all edges.

Returns:

Error code.

"Them" statistics

`igraph_local_scan_0_them` — Local THEM scan-statistics, *k*=0

```
igraph_error_t igraph_local_scan_0_them(const igraph_t *us, const igraph_t *them,
                                         igraph_vector_t *res,
                                         const igraph_vector_t *weights_them,
                                         igraph_neimode_t mode);
```

K=0 scan-statistics is arbitrarily defined as the vertex degree for unweighted, and the vertex strength for weighted graphs. See `igraph_degree()` and `igraph_strength()`.

Arguments:

- us*: The input graph, to use to extract the neighborhoods.
- them*: The input graph to use for the actually counting.
- res*: An initialized vector, the results are stored here.
- weights_them*: Weight vector for weighted graphs, null pointer for unweighted graphs.
- mode*: Type of the neighborhood, `IGRAPH_OUT` means outgoing, `IGRAPH_IN` means incoming and `IGRAPH_ALL` means all edges.

Returns:

Error code.

`igraph_local_scan_1_ecount_them` — Local THEM scan-statistics, *k*=1, edge count and sum of weights

```
igraph_error_t igraph_local_scan_1_ecount_them(const igraph_t *us, const igraph_t *them,
                                                igraph_vector_t *res,
                                                const igraph_vector_t *weights_them,
```

```
igraph_neimode_t mode);
```

Count the number of edges or the sum the edge weights in the 1-neighborhood of vertices.

Arguments:

us: The input graph to extract the neighborhoods.
them: The input graph to perform the counting.
weights_them: Weight vector for weighted graphs, null pointer for unweighted graphs.
mode: Type of the neighborhood, IGRAPH_OUT means outgoing, IGRAPH_IN means incoming and IGRAPH_ALL means all edges.

Returns:

Error code.

See also:

`igraph_local_scan_1_ecount()` for the US statistics.

`igraph_local_scan_k_ecount_them` — Local THEM scan-statistics, edge count or sum of weights.

```
igraph_error_t igraph_local_scan_k_ecount_them(const igraph_t *us, const igraph_t *them,
                                                igraph_integer_t k, igraph_vector_t *res,
                                                const igraph_vector_t *weights_them,
                                                igraph_neimode_t mode);
```

Count the number of edges or the sum the edge weights in the k-neighborhood of vertices.

Arguments:

us: The input graph to extract the neighborhoods.
them: The input graph to perform the counting.
k: The size of the neighborhood, non-negative integer. The k=0 case is special, see `igraph_local_scan_0_them()`.
weights_them: Weight vector for weighted graphs, null pointer for unweighted graphs.
mode: Type of the neighborhood, IGRAPH_OUT means outgoing, IGRAPH_IN means incoming and IGRAPH_ALL means all edges.

Returns:

Error code.

See also:

`igraph_local_scan_1_ecount()` for the US statistics.

Pre-calculated subsets

igraph_local_scan_neighborhood_ecount — Local scan-statistics with pre-calculated neighborhoods

```
igraph_error_t igraph_local_scan_neighborhood_ecount(const igraph_t *graph,
                                                    igraph_vector_t *res,
                                                    const igraph_vector_t *weights,
                                                    const igraph_vector_int_list_t *neighborhoods);
```

Count the number of edges, or sum the edge weights in neighborhoods given as a parameter.

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_local_scan_subset_ecount()` instead.

Arguments:

graph: The graph to perform the counting/summing in.

res: Initialized vector, the result is stored here.

weights: Weight vector for weighted graphs, null pointer for unweighted graphs.

neighborhoods: List of `igraph_vector_int_t` objects, the neighborhoods, one for each vertex in the graph.

Returns:

Error code.

igraph_local_scan_subset_ecount — Local scan-statistics of subgraphs induced by subsets of vertices.

```
igraph_error_t igraph_local_scan_subset_ecount(const igraph_t *graph,
                                                igraph_vector_t *res,
                                                const igraph_vector_t *weights,
                                                const igraph_vector_int_list_t *subsets);
```

Count the number of edges, or sum the edge weights in induced subgraphs from vertices given as a parameter.

Arguments:

graph: The graph to perform the counting/summing in.

res: Initialized vector, the result is stored here.

weights: Weight vector for weighted graphs, null pointer for unweighted graphs.

subsets: List of `igraph_vector_int_t` objects, the vertex subsets.

Returns:

Error code.

Graph components

igraph_subcomponent — The vertices in the same component as a given vertex.

```
igraph_error_t igraph_subcomponent(  
    const igraph_t *graph, igraph_vector_int_t *res, igraph_integer_t vertex,  
    igraph_neimode_t mode  
);
```

Arguments:

graph: The graph object.

res: The result, vector with the IDs of the vertices in the same component.

vertex: The id of the vertex of which the component is searched.

mode: Type of the component for directed graphs, possible values:

IGRAPH_OUT the set of vertices reachable *from* the *vertex*,

IGRAPH_IN the set of vertices from which the *vertex* is reachable.

IGRAPH_ALL the graph is considered as an undirected graph. Note that this is *not* the same as the union of the previous two.

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for temporary data.

IGRAPH_EINVAL *vertex* is an invalid vertex ID

IGRAPH_EINVMODE invalid mode argument passed.

Time complexity: $O(|V|+|E|)$, $|V|$ and $|E|$ are the number of vertices and edges in the graph.

See also:

`igraph_induced_subgraph()` if you want a graph object consisting only a given set of vertices and the edges between them.

igraph_connected_components — Calculates the (weakly or strongly) connected components in a graph.


```
igraph_error_t igraph_connected_components(  
    const igraph_t *graph, igraph_vector_int_t *membership,  
    igraph_vector_int_t *csize, igraph_integer_t *no, igraph_connectedness_t mode  
);
```

Arguments:

graph: The graph object to analyze.

membership: First half of the result will be stored here. For every vertex the id of its component is given. The vector has to be preinitialized and will be resized. Alternatively this argument can be NULL, in which case it is ignored.

csize: The second half of the result. For every component it gives its size, the order is defined by the component ids. The vector has to be preinitialized and will be resized. Alternatively this argument can be NULL, in which case it is ignored.

no: Pointer to an integer, if not NULL then the number of clusters will be stored here.

mode: For directed graph this specifies whether to calculate weakly or strongly connected components. Possible values: IGRAPH_WEAK, IGRAPH_STRONG. This argument is ignored for undirected graphs.

Returns:

Error code: IGRAPH_EINVAL: invalid mode argument.

Time complexity: $O(|V|+|E|)$, $|V|$ and $|E|$ are the number of vertices and edges in the graph.

igraph_clusters — Calculates the (weakly or strongly) connected components in a graph (deprecated alias).

```
igraph_error_t igraph_clusters(const igraph_t *graph, igraph_vector_int_t *membership,  
    igraph_vector_int_t *csize, igraph_integer_t *no,  
    igraph_connectedness_t mode);
```

Warning

Deprecated since version 0.10. Please do not use this function in new code; use `igraph_connected_components()` instead.

igraph_is_connected — Decides whether the graph is (weakly or strongly) connected.

```
igraph_error_t igraph_is_connected(const igraph_t *graph, igraph_bool_t *res,  
    igraph_connectedness_t mode);
```

A graph is considered connected when any of its vertices is reachable from any other. A directed graph with this property is called *strongly* connected. A directed graph that would be connected when ignoring the directions of its edges is called *weakly* connected.

A graph with zero vertices (i.e. the null graph) is *not* connected by definition. This behaviour changed in igraph 0.9; earlier versions assumed that the null graph is connected. See the following issue on Github for the argument that led us to change the definition: <https://github.com/igraph/igraph/issues/1539>

The return value of this function is cached in the graph itself, separately for weak and strong connectivity. Calling the function multiple times with no modifications to the graph in between will return a cached value in $O(1)$ time.

Arguments:

- graph*: The graph object to analyze.
- res*: Pointer to a logical variable, the result will be stored here.
- mode*: For a directed graph this specifies whether to calculate weak or strong connectedness. Possible values: IGRAPH_WEAK, IGRAPH_STRONG. This argument is ignored for undirected graphs.

Returns:

Error code: IGRAPH_EINVAL: invalid mode argument.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges in the graph.

igraph_decompose — Decomposes a graph into connected components.

```
igraph_error_t igraph_decompose(const igraph_t *graph, igraph_graph_list_t *components,
                                igraph_connectedness_t mode,
                                igraph_integer_t maxcompno, igraph_integer_t minelements);
```

Creates a separate graph for each component of a graph. Note that the vertex IDs in the new graphs will be different than in the original graph, except when there is only a single component in the original graph.

Arguments:

- graph*: The original graph.
- components*: This list of graphs will contain the individual components. It should be initialized before calling this function and will be resized to hold the graphs.
- mode*: Either IGRAPH_WEAK or IGRAPH_STRONG for weakly and strongly connected components respectively.
- maxcompno*: The maximum number of components to return. The first *maxcompno* components will be returned (which hold at least *minelements* vertices, see the next parameter), the others will be ignored. Supply -1 here if you don't want to limit the number of components.
- minelements*: The minimum number of vertices a component should contain in order to place it in the *components* vector. Eg. supply 2 here to ignore isolated vertices.

Returns:

Error code, `IGRAPH_ENOMEM` if there is not enough memory to perform the operation.

Added in version 0.2.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

Example 13.12. File `examples/simple/igraph_decompose.c`

`igraph_decompose_destroy` — Frees the contents of a pointer vector holding graphs.

```
void igraph_decompose_destroy(igraph_vector_ptr_t *complist);
```

This function destroys and frees all `igraph_t` objects held in *complist*. However, it does not destroy *complist* itself. Use `igraph_vector_ptr_destroy()` to destroy *complist*.

Arguments:

complist: The list of graphs to destroy.

Time complexity: $O(n)$, n is the number of items.

Warning

Deprecated since version 0.10.0. Please do not use this function in new code.

`igraph_biconnected_components` — Calculates biconnected components.

```
igraph_error_t igraph_biconnected_components(const igraph_t *graph,
                                              igraph_integer_t *no,
                                              igraph_vector_int_list_t *tree_edges,
                                              igraph_vector_int_list_t *component_edges,
                                              igraph_vector_int_list_t *components,
                                              igraph_vector_int_t *articulation_points);
```

A graph is biconnected if the removal of any single vertex (and its incident edges) does not disconnect it.

A biconnected component of a graph is a maximal biconnected subgraph of it. The biconnected components of a graph can be given by the partition of its edges: every edge is a member of exactly one biconnected component. Note that this is not true for vertices: the same vertex can be part of many biconnected components.

Note that some authors do not consider the graph consisting of two connected vertices as biconnected, however, `igraph` does.

Somewhat arbitrarily, `igraph` does not consider components containing a single vertex only as being biconnected. Isolated vertices will not be part of any of the biconnected components.

Arguments:

<i>graph</i> :	The input graph.
<i>no</i> :	If not a NULL pointer, the number of biconnected components will be stored here.
<i>tree_edges</i> :	If not a NULL pointer, then the found components are stored here, in a list of vectors. Every vector in the list is a biconnected component, represented by its edges. More precisely, a spanning tree of the biconnected component is returned.
<i>component_edges</i> :	If not a NULL pointer, then the edges of the biconnected components are stored here, in the same form as for <i>tree_edges</i> .
<i>components</i> :	If not a NULL pointer, then the vertices of the biconnected components are stored here, in the same format as for the previous two arguments.
<i>articulation_points</i> :	If not a NULL pointer, then the articulation points of the graph are stored in this vector. A vertex is an articulation point if its removal increases the number of (weakly) connected components in the graph.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges, but only if you do not calculate *components* and *component_edges*. If you calculate *components*, then it is quadratic in the number of vertices. If you calculate *component_edges* as well, then it is cubic in the number of vertices.

See also:

`igraph_articulation_points()`, `igraph_clusters()`.

Example	13.13.	File	examples/simple/
igraph_biconnected_components.c			

igraph_articulation_points — Finds the articulation points in a graph.

```
igraph_error_t igraph_articulation_points(const igraph_t *graph, igraph_vector_t
```

A vertex is an articulation point if its removal increases the number of connected components in the graph.

Arguments:

<i>graph</i> :	The input graph.
<i>res</i> :	Pointer to an initialized vector, the articulation points will be stored here.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

See also:

`igraph_biconnected_components()`, `igraph_clusters()`, `igraph_bridges()`

igraph_bridges — Finds all bridges in a graph.

```
igraph_error_t igraph_bridges(const igraph_t *graph, igraph_vector_int_t *bridges)
```

An edge is a bridge if its removal increases the number of (weakly) connected components in the graph.

Arguments:

graph: The input graph.

res: Pointer to an initialized vector, the bridges will be stored here as edge indices.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

See also:

`igraph_articulation_points()`, `igraph_biconnected_components()`,
`igraph_clusters()`

Degree sequences

igraph_is_graphical — Is there a graph with the given degree sequence?

```
igraph_error_t igraph_is_graphical(const igraph_vector_int_t *out_degrees,  
                                   const igraph_vector_int_t *in_degrees,  
                                   const igraph_edge_type_sw_t allowed_edge_types,  
                                   igraph_bool_t *res);
```

Determines whether a sequence of integers can be the degree sequence of some graph. The classical concept of graphicality assumes simple graphs. This function can perform the check also when either self-loops, multi-edge, or both are allowed in the graph.

For simple undirected graphs, the Erdős-Gallai conditions are checked using the linear-time algorithm of Cloteaux. If both self-loops and multi-edges are allowed, it is sufficient to check that the sum of degrees is even. If only multi-edges are allowed, but not self-loops, there is an additional condition that the sum of degrees be no smaller than twice the maximum degree. If at most one self-loop is allowed per vertex, but no multi-edges, a modified version of the Erdős-Gallai conditions are used (see Cairns & Mendan).

For simple directed graphs, the Fulkerson-Chen-Anstee theorem is used with the relaxation by Berger. If both self-loops and multi-edges are allowed, then it is sufficient to check that the sum of in- and

out-degrees is the same. If only multi-edges are allowed, but not self loops, there is an additional condition that the sum of out-degrees (or equivalently, in-degrees) is no smaller than the maximum total degree. If single self-loops are allowed, but not multi-edges, the problem is equivalent to realizability as a simple bipartite graph, thus the Gale-Ryser theorem can be used; see `igraph_is_bigraphical()` for more information.

References:

P. Erdős and T. Gallai, Gráfok elírt fokú pontokkal, Matematikai Lapok 11, pp. 264–274 (1960). https://users.renyi.hu/~p_erdos/1961-05.pdf

Z Király, Recognizing graphic degree sequences and generating all realizations. TR-2011-11, Egerváry Research Group, H-1117, Budapest, Hungary. ISSN 1587-4451 (2012). <http://bolyai.cs.elte.hu/egres/tr/egres-11-11.pdf>

B. Cloteaux, Is This for Real? Fast Graphicality Testing, Comput. Sci. Eng. 17, 91 (2015). <https://dx.doi.org/10.1109/MCSE.2015.125>

A. Berger, A note on the characterization of digraphic sequences, Discrete Math. 314, 38 (2014). <https://dx.doi.org/10.1016/j.disc.2013.09.010>

G. Cairns and S. Mendan, Degree Sequence for Graphs with Loops (2013). <https://arxiv.org/abs/1303.2145v1>

Arguments:

<i>out_degrees</i> :	A vector of integers specifying the degree sequence for undirected graphs or the out-degree sequence for directed graphs.	
<i>in_degrees</i> :	A vector of integers specifying the in-degree sequence for directed graphs. For undirected graphs, it must be NULL.	
<i>allowed_edge_types</i> :	The types of edges to allow in the graph:	
	IGRAPH_SIMPLE_SW	simple graphs (i.e. no self-loops or multi-edges allowed).
	IGRAPH_LOOPS_SW	single self-loops are allowed, but not multi-edges.
	IGRAPH_MULTI_SW	multi-edges are allowed, but not self-loops.
	IGRAPH_LOOPS_SW IGRAPH_MULTI_SW	both self-loops and multi-edges are allowed.
<i>res</i> :	Pointer to a Boolean. The result will be stored here.	

Returns:

Error code.

See also:

`igraph_is_bigraphical()` to check if a bi-degree-sequence can be realized as a bipartite graph; `igraph_realize_degree_sequence()` to construct a graph with a given degree sequence.

Time complexity: $O(n^2)$ for simple directed graphs, $O(n \log n)$ for graphs with self-loops, and $O(n)$ for all other cases, where n is the length of the degree sequence(s).

igraph_is_bigraphical — Is there a bipartite graph with the given bi-degree-sequence?

```
igraph_error_t igraph_is_bigraphical(const igraph_vector_int_t *degrees1,
                                     const igraph_vector_int_t *degrees2,
                                     const igraph_edge_type_sw_t allowed_edge_types,
                                     igraph_bool_t *res);
```

Determines whether two sequences of integers can be the degree sequences of a bipartite graph. Such a pair of degree sequence is called *bigraphical*.

When multi-edges are allowed, it is sufficient to check that the sum of degrees is the same in the two partitions. For simple graphs, the Gale-Ryser theorem is used with Berger's relaxation.

References:

H. J. Ryser, Combinatorial Properties of Matrices of Zeros and Ones, Can. J. Math. 9, 371 (1957). <https://dx.doi.org/10.4153/cjm-1957-044-3>

D. Gale, A theorem on flows in networks, Pacific J. Math. 7, 1073 (1957). <https://dx.doi.org/10.2140/pjm.1957.7.1073>

A. Berger, A note on the characterization of digraphic sequences, Discrete Math. 314, 38 (2014). <https://dx.doi.org/10.1016/j.disc.2013.09.010>

Arguments:

<i>degrees1</i> :	A vector of integers specifying the degrees in the first partition
<i>degrees2</i> :	A vector of integers specifying the degrees in the second partition
<i>allowed_edge_types</i> :	The types of edges to allow in the graph: IGRAPH_SIMPLE_SW simple graphs (i.e. no multi-edges allowed). IGRAPH_MULTI_SW multi-edges are allowed.
<i>res</i> :	Pointer to a Boolean. The result will be stored here.

Returns:

Error code.

See also:

`igraph_is_graphical()`

Time complexity: $O(n \log n)$ for simple graphs, $O(n)$ for multigraphs, where n is the length of the larger degree sequence.

Centrality measures

igraph_closeness — Closeness centrality calculations for some vertices.

```
igraph_error_t igraph_closeness(const igraph_t *graph, igraph_vector_t *res,
                                igraph_vector_int_t *reachable_count, igraph_bool_t *all_reachable,
                                const igraph_vs_t vids, igraph_neimode_t mode,
                                const igraph_vector_t *weights,
                                igraph_bool_t normalized);
```

The closeness centrality of a vertex measures how easily other vertices can be reached from it (or the other way: how easily it can be reached from the other vertices). It is defined as the inverse of the mean distance to (or from) all other vertices.

Closeness centrality is meaningful only for connected graphs. If the graph is not connected, igraph computes the inverse of the mean distance to (or from) all *reachable* vertices. In undirected graphs, this is equivalent to computing the closeness separately in each connected component. The optional *all_reachable* output parameter is provided to help detect when the graph is disconnected.

While there is no universally adopted definition of closeness centrality for disconnected graphs, there have been some attempts for generalizing the concept to the disconnected case. One type of approach considers the mean distance only to reachable vertices, then re-scales the obtained centrality score by a factor that depends on the number of reachable vertices (i.e. the size of the component in the undirected case). To facilitate computing these generalizations of closeness centrality, the number of reachable vertices (not including the starting vertex) is returned in *reachable_count*.

In disconnected graphs, consider using the harmonic centrality, computable using `igraph_harmonic_centrality()`.

For isolated vertices, i.e. those having no associated paths, NaN is returned.

Arguments:

<i>graph</i> :	The graph object.						
<i>res</i> :	The result of the computation, a vector containing the closeness centrality scores for the given vertices.						
<i>reachable_count</i> :	If not NULL, this vector will contain the number of vertices reachable from each vertex for which the closeness is calculated (not including that vertex).						
<i>all_reachable</i> :	Pointer to a Boolean. If not NULL, it indicates if all vertices of the graph were reachable from each vertex in <i>vids</i> . If false, the graph is non-connected. If true, and the graph is undirected, or if the graph is directed and <i>vids</i> contains all vertices, then the graph is connected.						
<i>vids</i> :	The vertices for which the closeness centrality will be computed.						
<i>mode</i> :	The type of shortest paths to be used for the calculation in directed graphs. Possible values: <table border="0" style="margin-left: 20px;"> <tr> <td>IGRAPH_OUT</td><td>the lengths of the outgoing paths are calculated.</td></tr> <tr> <td>IGRAPH_IN</td><td>the lengths of the incoming paths are calculated.</td></tr> <tr> <td>IGRAPH_ALL</td><td>the directed graph is considered as an undirected one for the computation.</td></tr> </table>	IGRAPH_OUT	the lengths of the outgoing paths are calculated.	IGRAPH_IN	the lengths of the incoming paths are calculated.	IGRAPH_ALL	the directed graph is considered as an undirected one for the computation.
IGRAPH_OUT	the lengths of the outgoing paths are calculated.						
IGRAPH_IN	the lengths of the incoming paths are calculated.						
IGRAPH_ALL	the directed graph is considered as an undirected one for the computation.						
<i>weights</i> :	An optional vector containing edge weights for weighted closeness. No edge weight may be NaN. Supply a null pointer here for traditional, unweighted closeness.						
<i>normalized</i> :	If true, the inverse of the mean distance to reachable vertices is returned. If false, the inverse of the sum of distances is returned.						

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for temporary data.

IGRAPH_EINVAL invalid vertex ID passed.

IGRAPH_EINVMODE invalid mode argument.

Time complexity: $O(n|E|)$, n is the number of vertices for which the calculation is done and $|E|$ is the number of edges in the graph.

See also:

Other centrality types: `igraph_degree()`, `igraph_betweenness()`, `igraph_harmonic_centrality()`. See `igraph_closeness_cutoff()` for the range-limited closeness centrality.

`igraph_harmonic_centrality` — Harmonic centrality for some vertices.

```
igraph_error_t igraph_harmonic_centrality(const igraph_t *graph, igraph_vector_t *res,
                                           const igraph_vs_t vids, igraph_neimode_t mode,
                                           const igraph_vector_t *weights,
                                           igraph_bool_t normalized);
```

The harmonic centrality of a vertex is the mean inverse distance to all other vertices. The inverse distance to an unreachable vertex is considered to be zero.

References:

M. Marchiori and V. Latora, Harmony in the small-world, *Physica A* 285, pp. 539-546 (2000). <https://doi.org/10.1016/S0378-4371%2800%2900311-3>

Y. Rochat, Closeness Centrality Extended to Unconnected Graphs: the Harmonic Centrality Index, ASNA 2009. <https://infoscience.epfl.ch/record/200525>

S. Vigna and P. Boldi, Axioms for Centrality, *Internet Mathematics* 10, (2014). <https://doi.org/10.1080/15427951.2013.865686>

Arguments:

graph: The graph object.

res: The result of the computation, a vector containing the harmonic centrality scores for the given vertices.

vids: The vertices for which the harmonic centrality will be computed.

mode: The type of shortest paths to be used for the calculation in directed graphs. Possible values:

IGRAPH_OUT the lengths of the outgoing paths are calculated.

IGRAPH_IN the lengths of the incoming paths are calculated.

`IGRAPH_ALL` the directed graph is considered as an undirected one for the computation.

weights: An optional vector containing edge weights for weighted harmonic centrality. No edge weight may be NaN. If `NULL`, all weights are considered to be one.

normalized: Boolean, whether to normalize the result. If true, the result is the mean inverse path length to other vertices, i.e. it is normalized by the number of vertices minus one. If false, the result is the sum of inverse path lengths to other vertices.

Returns:

Error code:

`IGRAPH_ENOMEM` not enough memory for temporary data.

`IGRAPH_EINVVID` invalid vertex ID passed.

`IGRAPH_EINVMODE` invalid mode argument.

Time complexity: $O(n|E|)$, where n is the number of vertices for which the calculation is done and $|E|$ is the number of edges in the graph.

See also:

Other centrality types: `igraph_closeness()`, `igraph_degree()`, `igraph_betweenness()`.

`igraph_betweenness` — Betweenness centrality of some vertices.

```
igraph_error_t igraph_betweenness(const igraph_t *graph, igraph_vector_t *res,
                                   const igraph_vs_t vids, igraph_bool_t directed,
                                   const igraph_vector_t* weights);
```

The betweenness centrality of a vertex is the number of geodesics going through it. If there are more than one geodesic between two vertices, the value of these geodesics are weighted by one over the number of geodesics.

Arguments:

graph: The graph object.

res: The result of the computation, a vector containing the betweenness scores for the specified vertices.

vids: The vertices of which the betweenness centrality scores will be calculated.

directed: Logical, if true directed paths will be considered for directed graphs. It is ignored for undirected graphs.

weights: An optional vector containing edge weights for calculating weighted betweenness. No edge weight may be NaN. Supply a null pointer here for unweighted betweenness.

Returns:

Error code: `IGRAPH_ENOMEM`, not enough memory for temporary data. `IGRAPH_EINVVID`, invalid vertex ID passed in *vids*.

Time complexity: $O(|V||E|)$, $|V|$ and $|E|$ are the number of vertices and edges in the graph. Note that the time complexity is independent of the number of vertices for which the score is calculated.

See also:

Other centrality types: `igraph_degree()`, `igraph_closeness()`. See `igraph_edge_betweenness()` for calculating the betweenness score of the edges in a graph. See `igraph_betweenness_cutoff()` to calculate the range-limited betweenness of the vertices in a graph.

`igraph_edge_betweenness` — Betweenness centrality of the edges.

```
igraph_error_t igraph_edge_betweenness(const igraph_t *graph, igraph_vector_t *  
                                     igraph_bool_t directed,  
                                     const igraph_vector_t *weights);
```

The betweenness centrality of an edge is the number of geodesics going through it. If there are more than one geodesics between two vertices, the value of these geodesics are weighted by one over the number of geodesics.

Arguments:

graph: The graph object.

result: The result of the computation, vector containing the betweenness scores for the edges.

directed: Logical, if true directed paths will be considered for directed graphs. It is ignored for undirected graphs.

weights: An optional weight vector for weighted edge betweenness. No edge weight may be NaN. Supply a null pointer here for the unweighted version.

Returns:

Error code: `IGRAPH_ENOMEM`, not enough memory for temporary data.

Time complexity: $O(|V||E|)$, $|V|$ and $|E|$ are the number of vertices and edges in the graph.

See also:

Other centrality types: `igraph_degree()`, `igraph_closeness()`. See `igraph_edge_betweenness()` for calculating the betweenness score of the edges in a graph. See `igraph_edge_betweenness_cutoff()` to compute the range-limited betweenness score of the edges in a graph.

`igraph_pagerank_algo_t` — PageRank algorithm implementation

```
typedef enum {  
    IGRAPH_PAGERANK_ALGO_ARPACK = 1,  
    IGRAPH_PAGERANK_ALGO_PRPACK = 2  
} igraph_pagerank_algo_t;
```

Algorithms to calculate PageRank.

Values:

IGRAPH_PAGERANK_ALGO_ARPACK:	Use the ARPACK library, this was the PageRank implementation in igraph from version 0.5, until version 0.7.
IGRAPH_PAGERANK_ALGO_PRPACK:	Use the PRPACK library. Currently this implementation is recommended.

igraph_pagerank — Calculates the Google PageRank for the specified vertices.

```
igraph_error_t igraph_pagerank(const igraph_t *graph, igraph_pagerank_algo_t algo,  
                               igraph_vector_t *vector,  
                               igraph_real_t *value, const igraph_vs_t vids,  
                               igraph_bool_t directed, igraph_real_t damping,  
                               const igraph_vector_t *weights, igraph_arpack_options_t *options)
```

The PageRank centrality of a vertex is the fraction of time a random walker traversing the graph would spend on that vertex. The walker follows the out-edges with probabilities proportional to their weights. Additionally, in each step, it restarts the walk from a random vertex with probability $1 - \text{damping}$. If the random walker gets stuck in a sink vertex, it will also restart from a random vertex.

The PageRank centrality is mainly useful for directed graphs. In undirected graphs it converges to trivial values proportional to degrees as the damping factor approaches 1.

Starting from version 0.9, igraph has two PageRank implementations, and the user can choose between them. The first implementation is IGRAPH_PAGERANK_ALGO_ARPACK, based on the ARPACK library. This was the default before igraph version 0.7. The second and recommended implementation is IGRAPH_PAGERANK_ALGO_PRPACK. This is using the PRPACK package, see <https://github.com/dgleich/prpack>.

Note that the PageRank of a given vertex depends on the PageRank of all other vertices, so even if you want to calculate the PageRank for only some of the vertices, all of them must be calculated. Requesting the PageRank for only some of the vertices does not result in any performance increase at all.

References:

Sergey Brin and Larry Page: The Anatomy of a Large-Scale Hypertextual Web Search Engine. Proceedings of the 7th World-Wide Web Conference, Brisbane, Australia, April 1998.

Arguments:

<i>graph</i> :	The graph object.
<i>algo</i> :	The PageRank implementation to use. Possible values: IGRAPH_PAGERANK_ALGO_ARPACK, IGRAPH_PAGERANK_ALGO_PRPACK.
<i>vector</i> :	Pointer to an initialized vector, the result is stored here. It is resized as needed.

<i>value</i> :	Pointer to a real variable, the eigenvalue corresponding to the PageRank vector is stored here. It should be always exactly one.
<i>vids</i> :	The vertex IDs for which the PageRank is returned.
<i>directed</i> :	Boolean, whether to consider the directedness of the edges. This is ignored for undirected graphs.
<i>damping</i> :	The damping factor ("d" in the original paper). Must be a probability in the range [0, 1]. A commonly used value is 0.85.
<i>weights</i> :	Optional edge weights. May be a NULL pointer, meaning unweighted edges, or a vector of non-negative values of the same length as the number of edges.
<i>options</i> :	Options for the ARPACK method. See <code>igraph_arpack_options_t</code> for details. Supply NULL here to use the defaults. Note that the function overwrites the <code>n</code> (number of vertices), <code>nev</code> (1), <code>ncv</code> (3) and <code>which</code> (LM) parameters and it always starts the calculation from a non-random vector calculated based on the degree of the vertices.

Returns:

Error code: `IGRAPH_ENOMEM`, not enough memory for temporary data. `IGRAPH_EINVVID`, invalid vertex ID in *vids*.

Time complexity: depends on the input graph, usually it is $O(|E|)$, the number of edges.

See also:

`igraph_personalized_pagerank()` and `igraph_personalized_pagerank_vs()` for the personalized PageRank measure. See `igraph_arpack_rssolve()` and `igraph_arpack_rnsolve()` for the underlying machinery used by `IGRAPH_PAGERANK_ALGO_ARPACK`.

Example 13.14. File `examples/simple/igraph_pagerank.c`

`igraph_personalized_pagerank` — Calculates the personalized Google PageRank for the specified vertices.

```
igraph_error_t igraph_personalized_pagerank(const igraph_t *graph,
                                             igraph_pagerank_algo_t algo, igraph_vector_t *
                                             igraph_real_t *value, const igraph_vs_t vids,
                                             igraph_bool_t directed, igraph_real_t damping,
                                             const igraph_vector_t *reset,
                                             const igraph_vector_t *weights,
                                             igraph_arpack_options_t *options);
```

The personalized PageRank is similar to the original PageRank measure, but when the random walk is restarted, a new starting vertex is chosen non-uniformly, according to the distribution specified in *reset* (instead of the uniform distribution in the original PageRank measure). The *reset* distribution is used both when restarting randomly with probability $1 - \text{damping}$, and when the walker is forced to restart due to being stuck in a sink vertex (a vertex with no outgoing edges).

Note that the personalized PageRank of a given vertex depends on the personalized PageRank of all other vertices, so even if you want to calculate the personalized PageRank for only some of the vertices,

all of them must be calculated. Requesting the personalized PageRank for only some of the vertices does not result in any performance increase at all.

Arguments:

<i>graph</i> :	The graph object.
<i>algo</i> :	The PageRank implementation to use. Possible values: <code>IGRAPH_PAGERANK_ALGO_ARPACK</code> , <code>IGRAPH_PAGERANK_ALGO_PRPACK</code> .
<i>vector</i> :	Pointer to an initialized vector, the result is stored here. It is resized as needed.
<i>value</i> :	Pointer to a real variable, the eigenvalue corresponding to the PageRank vector is stored here. It should be always exactly one.
<i>vids</i> :	The vertex IDs for which the PageRank is returned.
<i>directed</i> :	Boolean, whether to consider the directedness of the edges. This is ignored for undirected graphs.
<i>damping</i> :	The damping factor ("d" in the original paper). Must be a probability in the range [0, 1]. A commonly used value is 0.85.
<i>reset</i> :	The probability distribution over the vertices used when resetting the random walk. It is either a <code>NULL</code> pointer (denoting a uniform choice that results in the original PageRank measure) or a vector of the same length as the number of vertices.
<i>weights</i> :	Optional edge weights. May be a <code>NULL</code> pointer, meaning unweighted edges, or a vector of non-negative values of the same length as the number of edges.
<i>options</i> :	Options for the ARPACK method. See <code>igraph_arpack_options_t</code> for details. Supply <code>NULL</code> here to use the defaults. Note that the function overwrites the <code>n</code> (number of vertices), <code>nev</code> (1), <code>ncv</code> (3) and <code>which</code> (LM) parameters and it always starts the calculation from a non-random vector calculated based on the degree of the vertices.

Returns:

Error code: `IGRAPH_ENOMEM`, not enough memory for temporary data. `IGRAPH_EINVVID`, invalid vertex ID in *vids* or an invalid reset vector in *reset*.

Time complexity: depends on the input graph, usually it is $O(|E|)$, the number of edges.

See also:

`igraph_pagerank()` for the non-personalized implementation, `igraph_personalized_pagerank_vs()` for a personalized implementation with resetting to specific vertices.

`igraph_personalized_pagerank_vs` — Calculates the personalized Google PageRank for the specified vertices.

```
igraph_error_t igraph_personalized_pagerank_vs(const igraph_t *graph,
                                              igraph_pagerank_algo_t algo, igraph_vector_t *vector,
                                              igraph_real_t *value, const igraph_vs_t vids);
```

```
igraph_bool_t directed, igraph_real_t damping,  
igraph_vs_t reset_vids,  
const igraph_vector_t *weights,  
igraph_arnpack_options_t *options);
```

The personalized PageRank is similar to the original PageRank measure, but when the random walk is restarted, a new starting vertex is chosen according to a specified distribution. This distribution is used both when restarting randomly with probability $1 - \text{damping}$, and when the walker is forced to restart due to being stuck in a sink vertex (a vertex with no outgoing edges).

This simplified interface takes a vertex sequence and resets the random walk to one of the vertices in the specified vertex sequence, chosen uniformly. A typical application of personalized PageRank is when the random walk is reset to the same vertex every time - this can easily be achieved using `igraph_vss_1()` which generates a vertex sequence containing only a single vertex.

Note that the personalized PageRank of a given vertex depends on the personalized PageRank of all other vertices, so even if you want to calculate the personalized PageRank for only some of the vertices, all of them must be calculated. Requesting the personalized PageRank for only some of the vertices does not result in any performance increase at all.

Arguments:

<i>graph</i> :	The graph object.
<i>algo</i> :	The PageRank implementation to use. Possible values: <code>IGRAPH_PAGERANK_ALGO_ARPACK</code> , <code>IGRAPH_PAGERANK_ALGO_PRPACK</code> .
<i>vector</i> :	Pointer to an initialized vector, the result is stored here. It is resized as needed.
<i>value</i> :	Pointer to a real variable, the eigenvalue corresponding to the PageRank vector is stored here. It should be always exactly one.
<i>vids</i> :	The vertex IDs for which the PageRank is returned.
<i>directed</i> :	Boolean, whether to consider the directedness of the edges. This is ignored for undirected graphs.
<i>damping</i> :	The damping factor ("d" in the original paper). Must be a probability in the range [0, 1]. A commonly used value is 0.85.
<i>reset_vids</i> :	IDs of the vertices used when resetting the random walk.
<i>weights</i> :	Optional edge weights, it is either a null pointer, then the edges are not weighted, or a vector of the same length as the number of edges.
<i>options</i> :	Options for the ARPACK method. See <code>igraph_arnpack_options_t</code> for details. Supply NULL here to use the defaults. Note that the function overwrites the <code>n</code> (number of vertices), <code>nev</code> (1), <code>ncv</code> (3) and <code>which</code> (LM) parameters and it always starts the calculation from a non-random vector calculated based on the degree of the vertices.

Returns:

Error code: `IGRAPH_ENOMEM`, not enough memory for temporary data. `IGRAPH_EINVVID`, invalid vertex ID in *vids* or an empty reset vertex sequence in *vids_reset*.

Time complexity: depends on the input graph, usually it is $O(|E|)$, the number of edges.

See also:

`igraph_pagerank()` for the non-personalized implementation.

igraph_constraint — Burt's constraint scores.

```
igraph_error_t igraph_constraint(const igraph_t *graph, igraph_vector_t *res,
                                igraph_vs_t vids, const igraph_vector_t *weights);
```

This function calculates Burt's constraint scores for the given vertices, also known as structural holes.

Burt's constraint is higher if ego has less, or mutually stronger related (i.e. more redundant) contacts. Burt's measure of constraint, $C[i]$, of vertex i 's ego network $V[i]$, is defined for directed and valued graphs,

$$C[i] = \text{sum}(\text{sum}(p[i,q] p[q,j])^2, q \in V[i], q \neq i, j \in V, j \neq i)$$

for a graph of order (i.e. number of vertices) N , where proportional tie strengths are defined as

$$p[i,j] = (a[i,j] + a[j,i]) / \text{sum}(a[i,k] + a[k,i], k \in V[i], k \neq i),$$

$a[i,j]$ are elements of A and the latter being the graph adjacency matrix. For isolated vertices, constraint is undefined.

Burt, R.S. (2004). Structural holes and good ideas. *American Journal of Sociology* 110, 349-399.

The first R version of this function was contributed by Jeroen Bruggeman.

Arguments:

graph: A graph object.

res: Pointer to an initialized vector, the result will be stored here. The vector will be resized to have the appropriate size for holding the result.

vids: Vertex selector containing the vertices for which the constraint should be calculated.

weights: Vector giving the weights of the edges. If it is `NULL` then each edge is supposed to have the same weight.

Returns:

Error code.

Time complexity: $O(|V|+E|+n*d^2)$, n is the number of vertices for which the constraint is calculated and d is the average degree, $|V|$ is the number of vertices, $|E|$ the number of edges in the graph. If the *weights* argument is `NULL` then the time complexity is $O(|V|+n*d^2)$.

igraph_maxdegree — The maximum degree in a graph (or set of vertices).

```
igraph_error_t igraph_maxdegree(const igraph_t *graph, igraph_integer_t *res,
                                igraph_vs_t vids, igraph_neimode_t mode,
```



```
igraph_bool_t loops);
```

The largest in-, out- or total degree of the specified vertices is calculated. If the graph has no vertices, or *vids* is empty, 0 is returned, as this is the smallest possible value for degrees.

Arguments:

graph: The input graph.

res: Pointer to an integer (`igraph_integer_t`), the result will be stored here.

vids: Vector giving the vertex IDs for which the maximum degree will be calculated.

mode: Defines the type of the degree. `IGRAPH_OUT`, out-degree, `IGRAPH_IN`, in-degree, `IGRAPH_ALL`, total degree (sum of the in- and out-degree). This parameter is ignored for undirected graphs.

loops: Boolean, gives whether the self-loops should be counted.

Returns:

Error code: `IGRAPH_EINVVID`: invalid vertex ID. `IGRAPH_EINVMODE`: invalid mode argument.

Time complexity: $O(v)$ if *loops* is true, and $O(v*d)$ otherwise. *v* is the number of vertices for which the degree will be calculated, and *d* is their (average) degree.

igraph_strength — Strength of the vertices, also called weighted vertex degree.

```
igraph_error_t igraph_strength(const igraph_t *graph, igraph_vector_t *res,
                              const igraph_vs_t vids, igraph_neimode_t mode,
                              igraph_bool_t loops, const igraph_vector_t *weights);
```

In a weighted network the strength of a vertex is the sum of the weights of all incident edges. In a non-weighted network this is exactly the vertex degree.

Arguments:

graph: The input graph.

res: Pointer to an initialized vector, the result is stored here. It will be resized as needed.

vids: The vertices for which the calculation is performed.

mode: Gives whether to count only outgoing (`IGRAPH_OUT`), incoming (`IGRAPH_IN`) edges or both (`IGRAPH_ALL`).

loops: A logical scalar, whether to count loop edges as well.

weights: A vector giving the edge weights. If this is a NULL pointer, then `igraph_degree()` is called to perform the calculation.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number vertices and edges.

See also:

`igraph_degree()` for the traditional, non-weighted version.

igraph_eigenvector_centrality — Eigenvector centrality of the vertices.

```
igraph_error_t igraph_eigenvector_centrality(const igraph_t *graph,
                                             igraph_vector_t *vector,
                                             igraph_real_t *value,
                                             igraph_bool_t directed, igraph_bool_t scale,
                                             const igraph_vector_t *weights,
                                             igraph_arnpack_options_t *options);
```

Eigenvector centrality is a measure of the importance of a node in a network. It assigns relative scores to all nodes in the network based on the principle that connections from high-scoring nodes contribute more to the score of the node in question than equal connections from low-scoring nodes. Specifically, the eigenvector centrality of each vertex is proportional to the sum of eigenvector centralities of its neighbors. In practice, the centralities are determined by calculating the eigenvector corresponding to the largest positive eigenvalue of the adjacency matrix. In the undirected case, this function considers the diagonal entries of the adjacency matrix to be *twice* the number of self-loops on the corresponding vertex.

In the weighted case, the eigenvector centrality of a vertex is proportional to the weighted sum of centralities of its neighbours, i.e. $c_i = \sum_j w_{ij} c_j$, where w_{ij} is the weight of the edge connecting vertices i and j . The weights of parallel edges are added up.

The centrality scores returned by igraph can be normalized (using the `scale` parameter) such that the largest eigenvector centrality score is 1 (with one exception, see below).

In the directed case, the left eigenvector of the adjacency matrix is calculated. In other words, the centrality of a vertex is proportional to the sum of centralities of vertices pointing to it.

Eigenvector centrality is meaningful only for (strongly) connected graphs. Undirected graphs that are not connected should be decomposed into connected components, and the eigenvector centrality calculated for each separately. This function does not verify that the graph is connected. If it is not, in the undirected case the scores of all but one component will be zeros.

Also note that the adjacency matrix of a directed acyclic graph or the adjacency matrix of an empty graph does not possess positive eigenvalues, therefore the eigenvector centrality is not defined for these graphs. igraph will return an eigenvalue of zero in such cases. The eigenvector centralities will all be equal for an empty graph and will all be zeros for a directed acyclic graph. Such pathological cases can be detected by asking igraph to calculate the eigenvalue as well (using the `value` parameter, see below) and checking whether the eigenvalue is very close to zero.

Arguments:

<i>graph</i> :	The input graph. It may be directed.
<i>vector</i> :	Pointer to an initialized vector, it will be resized as needed. The result of the computation is stored here. It can be a null pointer, then it is ignored.
<i>value</i> :	If not a null pointer, then the eigenvalue corresponding to the found eigenvector is stored here.

- directed*: Boolean scalar, whether to consider edge directions in a directed graph. It is ignored for undirected graphs.
- scale*: If not zero then the result will be scaled such that the absolute value of the maximum centrality is one.
- weights*: A null pointer (indicating no edge weights), or a vector giving the weights of the edges. Weights should be positive to guarantee a meaningful result. The algorithm might produce complex numbers when some weights are negative and the graph is directed. In this case only the real part is reported.
- options*: Options to ARPACK. See `igraph_arpack_options_t` for details. Supply NULL here to use the defaults. Note that the function overwrites the `n` (number of vertices) parameter and it always starts the calculation from a non-random vector calculated based on the degree of the vertices.

Returns:

Error code.

Time complexity: depends on the input graph, usually it is $O(|V|+|E|)$.

See also:

`igraph_pagerank` and `igraph_personalized_pagerank` for modifications of eigenvector centrality.

Example 13.15. File `examples/simple/eigenvector_centrality.c`

igraph_hub_score — Kleinberg's hub scores.

```
igraph_error_t igraph_hub_score(const igraph_t *graph, igraph_vector_t *vector,
                                igraph_real_t *value, igraph_bool_t scale,
                                const igraph_vector_t *weights,
                                igraph_arpack_options_t *options);
```

The hub scores of the vertices are defined as the principal eigenvector of $A \cdot A^T$, where A is the adjacency matrix of the graph, A^T is its transposed.

See the following reference on the meaning of this score: J. Kleinberg. Authoritative sources in a hyperlinked environment. *Proc. 9th ACM-SIAM Symposium on Discrete Algorithms*, 1998. Extended version in *Journal of the ACM* 46(1999). Also appears as IBM Research Report RJ 10076, May 1997.

Arguments:

- graph*: The input graph. Can be directed and undirected.
- vector*: Pointer to an initialized vector, the result is stored here. If a null pointer then it is ignored.
- value*: If not a null pointer then the eigenvalue corresponding to the calculated eigenvector is stored here.
- scale*: If not zero then the result will be scaled such that the absolute value of the maximum centrality is one.
- weights*: A null pointer (=no edge weights), or a vector giving the weights of the edges.

options: Options to ARPACK. See `igraph_arpack_options_t` for details. Note that the function overwrites the `n` (number of vertices) parameter and it always starts the calculation from a non-random vector calculated based on the degree of the vertices.

Returns:

Error code.

Time complexity: depends on the input graph, usually it is $O(|V|)$, the number of vertices.

See also:

`igraph_authority_score()` for the companion measure, `igraph_pagerank()`, `igraph_personalized_pagerank()`, `igraph_eigenvector_centrality()` for similar measures.

igraph_authority_score — Kleinerg's authority scores.

```
igraph_error_t igraph_authority_score(const igraph_t *graph, igraph_vector_t *v,
                                     igraph_real_t *value, igraph_bool_t scale,
                                     const igraph_vector_t *weights,
                                     igraph_arpack_options_t *options);
```

The authority scores of the vertices are defined as the principal eigenvector of $A^T A$, where A is the adjacency matrix of the graph, A^T is its transposed.

See the following reference on the meaning of this score: J. Kleinberg. Authoritative sources in a hyperlinked environment. *Proc. 9th ACM-SIAM Symposium on Discrete Algorithms*, 1998. Extended version in *Journal of the ACM* 46(1999). Also appears as IBM Research Report RJ 10076, May 1997.

Arguments:

graph: The input graph. Can be directed and undirected.

vector: Pointer to an initialized vector, the result is stored here. If a null pointer then it is ignored.

value: If not a null pointer then the eigenvalue corresponding to the calculated eigenvector is stored here.

scale: If not zero then the result will be scaled such that the absolute value of the maximum centrality is one.

weights: A null pointer (=no edge weights), or a vector giving the weights of the edges.

options: Options to ARPACK. See `igraph_arpack_options_t` for details. Note that the function overwrites the `n` (number of vertices) parameter and it always starts the calculation from a non-random vector calculated based on the degree of the vertices.

Returns:

Error code.

Time complexity: depends on the input graph, usually it is $O(|V|)$, the number of vertices.

See also:

`igraph_hub_score()` for the companion measure, `igraph_pagerank()`, `igraph_personalized_pagerank()`, `igraph_eigenvector_centrality()` for similar measures.

igraph_convergence_degree — Calculates the convergence degree of each edge in a graph.

```
igraph_error_t igraph_convergence_degree(const igraph_t *graph, igraph_vector_t  
                                         igraph_vector_t *ins, igraph_vector_t *outs);
```

Let us define the input set of an edge (i, j) as the set of vertices where the shortest paths passing through (i, j) originate, and similarly, let us define the output set of an edge (i, j) as the set of vertices where the shortest paths passing through (i, j) terminate. The convergence degree of an edge is defined as the normalized value of the difference between the size of the input set and the output set, i.e. the difference of them divided by the sum of them. Convergence degrees are in the range $(-1, 1)$; a positive value indicates that the edge is *convergent* since the shortest paths passing through it originate from a larger set and terminate in a smaller set, while a negative value indicates that the edge is *divergent* since the paths originate from a small set and terminate in a larger set.

Note that the convergence degree as defined above does not make sense in undirected graphs as there is no distinction between the input and output set. Therefore, for undirected graphs, the input and output sets of an edge are determined by orienting the edge arbitrarily while keeping the remaining edges undirected, and then taking the absolute value of the convergence degree.

Arguments:

- graph*: The input graph, it can be either directed or undirected.
- result*: Pointer to an initialized vector; the convergence degrees of each edge will be stored here. May be NULL if we are not interested in the exact convergence degrees.
- ins*: Pointer to an initialized vector; the size of the input set of each edge will be stored here. May be NULL if we are not interested in the sizes of the input sets.
- outs*: Pointer to an initialized vector; the size of the output set of each edge will be stored here. May be NULL if we are not interested in the sizes of the output sets.

Returns:

Error code.

Time complexity: $O(|V||E|)$, the number of vertices times the number of edges.

Range-limited centrality measures

igraph_closeness_cutoff — Range limited closeness centrality.

```
igraph_error_t igraph_closeness_cutoff(const igraph_t *graph, igraph_vector_t *  
                                       igraph_vector_int_t *reachable_count, igraph_bool_t  
                                       const igraph_vs_t vids, igraph_neimode_t mode,
```

```
const igraph_vector_t *weights,
igraph_bool_t normalized,
igraph_real_t cutoff);
```

This function computes a range-limited version of closeness centrality by considering only those shortest paths whose length is no greater than the given cutoff value.

Arguments:

<i>graph</i> :	The graph object.
<i>res</i> :	The result of the computation, a vector containing the range-limited closeness centrality scores for the given vertices.
<i>reachable_count</i> :	If not NULL, this vector will contain the number of vertices reachable within the cutoff distance from each vertex for which the range-limited closeness is calculated (not including that vertex).
<i>all_reachable</i> :	Pointer to a Boolean. If not NULL, it indicates if all vertices of the graph were reachable from each vertex in <i>vids</i> within the given cutoff distance.
<i>vids</i> :	The vertices for which the range limited closeness centrality will be computed.
<i>mode</i> :	The type of shortest paths to be used for the calculation in directed graphs. Possible values: <div style="margin-left: 20px;"> IGRAPH_OUT the lengths of the outgoing paths are calculated. IGRAPH_IN the lengths of the incoming paths are calculated. IGRAPH_ALL the directed graph is considered as an undirected one for the computation. </div>
<i>weights</i> :	An optional vector containing edge weights for weighted closeness. No edge weight may be NaN. Supply a null pointer here for traditional, unweighted closeness.
<i>normalized</i> :	If true, the inverse of the mean distance to vertices reachable within the cutoff is returned. If false, the inverse of the sum of distances is returned.
<i>cutoff</i> :	The maximal length of paths that will be considered. If negative, the exact closeness will be calculated (no upper limit on path lengths).

Returns:

Error code:

IGRAPH_ENOMEM	not enough memory for temporary data.
IGRAPH_EINVVID	invalid vertex ID passed.
IGRAPH_EINVMODE	invalid mode argument.

Time complexity: $O(n|E|)$, n is the number of vertices for which the calculation is done and $|E|$ is the number of edges in the graph.

See also:

`igraph_closeness()` to calculate the exact closeness centrality.

igraph_harmonic_centrality_cutoff — Range limited harmonic centrality.

```
igraph_error_t igraph_harmonic_centrality_cutoff(const igraph_t *graph, igraph_vs_t vids,
                                                  const igraph_vs_t vids, igraph_neimode_t mode,
                                                  const igraph_vector_t *weights,
                                                  igraph_bool_t normalized,
                                                  igraph_real_t cutoff);
```

This function computes the range limited version of harmonic centrality: only those shortest paths are considered whose length is not above the given cutoff. The inverse distance to vertices not reachable within the cutoff is considered to be zero.

Arguments:

<i>graph</i> :	The graph object.
<i>res</i> :	The result of the computation, a vector containing the range limited harmonic centrality scores for the given vertices.
<i>vids</i> :	The vertices for which the harmonic centrality will be computed.
<i>mode</i> :	The type of shortest paths to be used for the calculation in directed graphs. Possible values: IGRAPH_OUT the lengths of the outgoing paths are calculated. IGRAPH_IN the lengths of the incoming paths are calculated. IGRAPH_ALL the directed graph is considered as an undirected one for the computation.
<i>weights</i> :	An optional vector containing edge weights for weighted harmonic centrality. No edge weight may be NaN. If NULL, all weights are considered to be one.
<i>normalized</i> :	Boolean, whether to normalize the result. If true, the result is the mean inverse path length to other vertices. i.e. it is normalized by the number of vertices minus one. If false, the result is the sum of inverse path lengths to other vertices.
<i>cutoff</i> :	The maximal length of paths that will be considered. The inverse distance to vertices that are not reachable within the cutoff path length is considered to be zero. Supply a negative value to compute the exact harmonic centrality, without any upper limit on the length of paths.

Returns:

Error code:

IGRAPH_ENOMEM	not enough memory for temporary data.
IGRAPH_EINVVID	invalid vertex ID passed.
IGRAPH_EINVMODE	invalid mode argument.

Time complexity: $O(n|E|)$, where n is the number of vertices for which the calculation is done and $|E|$ is the number of edges in the graph.

See also:

Other centrality types: `igraph_closeness()`, `igraph_betweenness()`.

`igraph_betweenness_cutoff` — Range-limited betweenness centrality.

```
igraph_error_t igraph_betweenness_cutoff(const igraph_t *graph, igraph_vector_t  
                                         const igraph_vs_t vids, igraph_bool_t directed,  
                                         const igraph_vector_t *weights, igraph_real_t cutoff)
```

This function computes a range-limited version of betweenness centrality by considering only those shortest paths whose length is no greater than the given cutoff value.

Arguments:

- graph*: The graph object.
- res*: The result of the computation, a vector containing the range-limited betweenness scores for the specified vertices.
- vids*: The vertices for which the range-limited betweenness centrality scores will be computed.
- directed*: Logical, if true directed paths will be considered for directed graphs. It is ignored for undirected graphs.
- weights*: An optional vector containing edge weights for calculating weighted betweenness. No edge weight may be NaN. Supply a null pointer here for unweighted betweenness.
- cutoff*: The maximal length of paths that will be considered. If negative, the exact betweenness will be calculated, and there will be no upper limit on path lengths.

Returns:

Error code: `IGRAPH_ENOMEM`, not enough memory for temporary data. `IGRAPH_EINVVID`, invalid vertex ID passed in *vids*.

Time complexity: $O(|V||E|)$, $|V|$ and $|E|$ are the number of vertices and edges in the graph. Note that the time complexity is independent of the number of vertices for which the score is calculated.

See also:

`igraph_betweenness()` to calculate the exact betweenness and `igraph_edge_betweenness_cutoff()` to calculate the range-limited edge betweenness.

`igraph_edge_betweenness_cutoff` — Range-limited betweenness centrality of the edges.

```
igraph_error_t igraph_edge_betweenness_cutoff(const igraph_t *graph, igraph_vec  
                                              igraph_bool_t directed,
```



```
const igraph_vector_t *weights, igraph_real_t
```

This function computes a range-limited version of edge betweenness centrality by considering only those shortest paths whose length is no greater than the given cutoff value.

Arguments:

- graph*: The graph object.
- result*: The result of the computation, vector containing the betweenness scores for the edges.
- directed*: Logical, if true directed paths will be considered for directed graphs. It is ignored for undirected graphs.
- weights*: An optional weight vector for weighted betweenness. No edge weight may be NaN. Supply a null pointer here for unweighted betweenness.
- cutoff*: The maximal length of paths that will be considered. If negative, the exact betweenness will be calculated (no upper limit on path lengths).

Returns:

Error code: IGRAPH_ENOMEM, not enough memory for temporary data.

Time complexity: $O(|V||E|)$, $|V|$ and $|E|$ are the number of vertices and edges in the graph.

See also:

`igraph_edge_betweenness()` to compute the exact edge betweenness and `igraph_betweenness_cutoff()` to compute the range-limited vertex betweenness.

Subset-limited Centrality Measures

`igraph_betweenness_subset` — Betweenness centrality for a subset of source and target vertices.

```
igraph_error_t igraph_betweenness_subset(const igraph_t *graph, igraph_vector_t  
                                         const igraph_vs_t vids, igraph_bool_t directed,  
                                         const igraph_vs_t sources, const igraph_vs_t targ  
                                         const igraph_vector_t *weights);
```

This function computes the subset-limited version of betweenness centrality by considering only those shortest paths that lie between vertices in a given source and target subset.

Arguments:

- graph*: The graph object.
- res*: The result of the computation, a vector containing the betweenness score for the subset of vertices.
- vids*: The vertices for which the subset-limited betweenness centrality scores will be computed.

- directed*: Logical, if true directed paths will be considered for directed graphs. It is ignored for undirected graphs.
- weights*: An optional vector containing edge weights for calculating weighted betweenness. No edge weight may be NaN. Supply a null pointer here for unweighted betweenness.
- sources*: A vertex selector for the sources of the shortest paths taken into consideration in the betweenness calculation.
- targets*: A vertex selector for the targets of the shortest paths taken into consideration in the betweenness calculation.

Returns:

Error code: IGRAPH_ENOMEM, not enough memory for temporary data. IGRAPH_EINVVID, invalid vertex ID passed in *vids*, *sources* or *targets*

Time complexity: $O(|S||E|)$, $|S|$ The number of vertices in the subset $|E|$ The number of edges in the graph

See also:

`igraph_betweenness()` to calculate the exact vertex betweenness and `igraph_betweenness_cutoff()` to calculate the range-limited vertex betweenness.

igraph_edge_betweenness_subset — Edge betweenness centrality for a subset of source and target vertices.

```
igraph_error_t igraph_edge_betweenness_subset(const igraph_t *graph, igraph_vector_t *res,
                                              const igraph_es_t eids, igraph_bool_t directed,
                                              const igraph_vs_t sources, const igraph_vs_t targets,
                                              const igraph_vector_t *weights);
```

This function computes the subset-limited version of edge betweenness centrality by considering only those shortest paths that lie between vertices in a given source and target subset.

Arguments:

- graph*: The graph object.
- res*: The result of the computation, vector containing the betweenness scores for the edges.
- eids*: The edges for which the subset-limited betweenness centrality scores will be computed.
- directed*: Logical, if true directed paths will be considered for directed graphs. It is ignored for undirected graphs.
- weights*: An optional weight vector for weighted betweenness. No edge weight may be NaN. Supply a null pointer here for unweighted betweenness.
- sources*: A vertex selector for the sources of the shortest paths taken into consideration in the betweenness calculation.

targets: A vertex selector for the targets of the shortest paths taken into consideration in the betweenness calculation.

Returns:

Error code: IGRAPH_ENOMEM, not enough memory for temporary data. IGRAPH_EINVVID, invalid vertex ID passed in *sources* or *targets*

Time complexity: $O(|S||E|)$, $|S|$ The number of vertices in the subset $|E|$ The number of edges in the graph

See also:

`igraph_edge_betweenness()` to compute the exact edge betweenness and `igraph_edge_betweenness_cutoff()` to compute the range-limited edge betweenness.

Centralization

`igraph_centralization` — Calculate the centralization score from the node level scores.

```
igraph_real_t igraph_centralization(const igraph_vector_t *scores,
                                    igraph_real_t theoretical_max,
                                    igraph_bool_t normalized);
```

For a centrality score defined on the vertices of a graph, it is possible to define a graph level centralization index, by calculating the sum of the deviation from the maximum centrality score. Consequently, the higher the centralization index of the graph, the more centralized the structure is.

In order to make graphs of different sizes comparable, the centralization index is usually normalized to a number between zero and one, by dividing the (unnormalized) centralization score of the most centralized structure with the same number of vertices.

For most centrality indices the most centralized structure is the star graph, a single center connected to all other nodes in the network. There are some variation depending on whether the graph is directed or not, whether loop edges are allowed, etc.

This function simply calculates the graph level index, if the node level scores and the theoretical maximum are given. It is called by all the measure-specific centralization functions.

Arguments:

scores: A vector containing the node-level centrality scores.

theoretical_max: The graph level centrality score of the most centralized graph with the same number of vertices. Only used if `normalized` set to true.

normalized: Boolean, whether to normalize the centralization by dividing the supplied theoretical maximum.

Returns:

The graph level index.

See also:

`igraph_centralization_degree()`, `igraph_centralization_betweenness()`, `igraph_centralization_closeness()`, and `igraph_centralization_eigenvector_centrality()` for specific centralization functions.

Time complexity: $O(n)$, the length of the score vector.

Example 13.16. File `examples/simple/centralization.c`

`igraph_centralization_degree` — Calculate vertex degree and graph centralization.

```
igraph_error_t igraph_centralization_degree(const igraph_t *graph, igraph_vector_t *centralization,
                                             igraph_neimode_t mode, igraph_bool_t loops,
                                             igraph_real_t *theoretical_max,
                                             igraph_bool_t normalized);
```

This function calculates the degree of the vertices by passing its arguments to `igraph_degree()`; and it calculates the graph level centralization index based on the results by calling `igraph_centralization()`.

Arguments:

<i>graph</i> :	The input graph.
<i>res</i> :	A vector if you need the node-level degree scores, or a null pointer otherwise.
<i>mode</i> :	Constant the specifies the type of degree for directed graphs. Possible values: <code>IGRAPH_IN</code> , <code>IGRAPH_OUT</code> and <code>IGRAPH_ALL</code> . This argument is ignored for undirected graphs.
<i>loops</i> :	Boolean, whether to consider loop edges when calculating the degree (and the centralization).
<i>centralization</i> :	Pointer to a real number, the centralization score is placed here.
<i>theoretical_max</i> :	Pointer to real number or a null pointer. If not a null pointer, then the theoretical maximum graph centrality score for a graph with the same number vertices is stored here.
<i>normalized</i> :	Boolean, whether to calculate a normalized centralization score. See <code>igraph_centralization()</code> for how the normalization is done.

Returns:

Error code.

See also:

`igraph_centralization()`, `igraph_degree()`.

Time complexity: the complexity of `igraph_degree()` plus $O(n)$, the number of vertices queried, for calculating the centralization score.

igraph_centralization_betweenness — Calculate vertex betweenness and graph centralization.

```
igraph_error_t igraph_centralization_betweenness(const igraph_t *graph,
                                                  igraph_vector_t *res,
                                                  igraph_bool_t directed,
                                                  igraph_real_t *centralization,
                                                  igraph_real_t *theoretical_max,
                                                  igraph_bool_t normalized);
```

This function calculates the betweenness centrality of the vertices by passing its arguments to `igraph_betweenness()`; and it calculates the graph level centralization index based on the results by calling `igraph_centralization()`.

Arguments:

<i>graph</i> :	The input graph.
<i>res</i> :	A vector if you need the node-level betweenness scores, or a null pointer otherwise.
<i>directed</i> :	Boolean, whether to consider directed paths when calculating betweenness.
<i>centralization</i> :	Pointer to a real number, the centralization score is placed here.
<i>theoretical_max</i> :	Pointer to real number or a null pointer. If not a null pointer, then the theoretical maximum graph centrality score for a graph with the same number vertices is stored here.
<i>normalized</i> :	Boolean, whether to calculate a normalized centralization score. See <code>igraph_centralization()</code> for how the normalization is done.

Returns:

Error code.

See also:

`igraph_centralization()`, `igraph_betweenness()`.

Time complexity: the complexity of `igraph_betweenness()` plus $O(n)$, the number of vertices queried, for calculating the centralization score.

igraph_centralization_closeness — Calculate vertex closeness and graph centralization.

```
igraph_error_t igraph_centralization_closeness(const igraph_t *graph,
                                                igraph_vector_t *res,
                                                igraph_neimode_t mode,
                                                igraph_real_t *centralization,
                                                igraph_real_t *theoretical_max,
                                                igraph_bool_t normalized);
```

This function calculates the closeness centrality of the vertices by passing its arguments to `igraph_closeness()`; and it calculates the graph level centralization index based on the results by calling `igraph_centralization()`.

Arguments:

<i>graph</i> :	The input graph.
<i>res</i> :	A vector if you need the node-level closeness scores, or a null pointer otherwise.
<i>mode</i> :	Constant that specifies the type of closeness for directed graphs. Possible values: <code>IGRAPH_IN</code> , <code>IGRAPH_OUT</code> and <code>IGRAPH_ALL</code> . This argument is ignored for undirected graphs. See <code>igraph_closeness()</code> argument with the same name for more.
<i>centralization</i> :	Pointer to a real number, the centralization score is placed here.
<i>theoretical_max</i> :	Pointer to real number or a null pointer. If not a null pointer, then the theoretical maximum graph centrality score for a graph with the same number of vertices is stored here.
<i>normalized</i> :	Boolean, whether to calculate a normalized centralization score. See <code>igraph_centralization()</code> for how the normalization is done.

Returns:

Error code.

See also:

`igraph_centralization()`, `igraph_closeness()`.

Time complexity: the complexity of `igraph_closeness()` plus $O(n)$, the number of vertices queried, for calculating the centralization score.

`igraph_centralization_eigenvector_centrality` — Calculate eigenvector centrality scores and graph centralization.

```
igraph_error_t igraph_centralization_eigenvector_centrality(
    const igraph_t *graph,
    igraph_vector_t *vector,
    igraph_real_t *value,
    igraph_bool_t directed,
    igraph_bool_t scale,
    igraph_arpack_options_t *options,
    igraph_real_t *centralization,
    igraph_real_t *theoretical_max,
    igraph_bool_t normalized);
```

This function calculates the eigenvector centrality of the vertices by passing its arguments to `igraph_eigenvector_centrality()`; and it calculates the graph level centralization index based on the results by calling `igraph_centralization()`.

Arguments:

<i>graph</i> :	The input graph.
<i>vector</i> :	A vector if you need the node-level eigenvector centrality scores, or a null pointer otherwise.
<i>value</i> :	If not a null pointer, then the leading eigenvalue is stored here.
<i>scale</i> :	If not zero then the result will be scaled, such that the absolute value of the maximum centrality is one.
<i>options</i> :	Options to ARPACK. See <code>igraph_arpack_options_t</code> for details. Note that the function overwrites the <code>n</code> (number of vertices) parameter and it always starts the calculation from a non-random vector calculated based on the degree of the vertices.
<i>centralization</i> :	Pointer to a real number, the centralization score is placed here.
<i>theoretical_max</i> :	Pointer to real number or a null pointer. If not a null pointer, then the theoretical maximum graph centrality score for a graph with the same number of vertices is stored here.
<i>normalized</i> :	Boolean, whether to calculate a normalized centralization score. See <code>igraph_centralization()</code> for how the normalization is done.

Returns:

Error code.

See also:

`igraph_centralization()`, `igraph_eigenvector_centrality()`.

Time complexity: the complexity of `igraph_eigenvector_centrality()` plus $O(|V|)$, the number of vertices for the calculating the centralization.

`igraph_centralization_degree_tmax` — Theoretical maximum for graph centralization based on degree.

```
igraph_error_t igraph_centralization_degree_tmax(const igraph_t *graph,
                                                igraph_integer_t nodes,
                                                igraph_neimode_t mode,
                                                igraph_bool_t loops,
                                                igraph_real_t *res);
```

This function returns the theoretical maximum graph centrality based on vertex degree.

There are two ways to call this function, the first is to supply a graph as the `graph` argument, and then the number of vertices is taken from this object, and its directedness is considered as well. The `nodes` argument is ignored in this case. The `mode` argument is also ignored if the supplied graph is undirected.

The other way is to supply a null pointer as the `graph` argument. In this case the `nodes` and `mode` arguments are considered.

The most centralized structure is the star. More specifically, for undirected graphs it is the star, for directed graphs it is the in-star or the out-star.

Arguments:

- graph*: A graph object or a null pointer, see the description above.
- nodes*: The number of nodes. This is ignored if the *graph* argument is not a null pointer.
- mode*: Constant, whether the calculation is based on in-degree (IGRAPH_IN), out-degree (IGRAPH_OUT) or total degree (IGRAPH_ALL). This is ignored if the *graph* argument is not a null pointer and the given graph is undirected.
- loops*: Boolean scalar, whether to consider loop edges in the calculation.
- res*: Pointer to a real variable, the result is stored here.

Returns:

Error code.

Time complexity: $O(1)$.

See also:

`igraph_centralization_degree()` and `igraph_centralization()`.

`igraph_centralization_betweenness_tmax` — Theoretical maximum for graph centralization based on betweenness.

```
igraph_error_t igraph_centralization_betweenness_tmax(const igraph_t *graph,  
    igraph_integer_t nodes,  
    igraph_bool_t directed,  
    igraph_real_t *res);
```

This function returns the theoretical maximum graph centrality based on vertex betweenness.

There are two ways to call this function, the first is to supply a graph as the *graph* argument, and then the number of vertices is taken from this object, and its directedness is considered as well. The *nodes* argument is ignored in this case. The *directed* argument is also ignored if the supplied graph is undirected.

The other way is to supply a null pointer as the *graph* argument. In this case the *nodes* and *directed* arguments are considered.

The most centralized structure is the star.

Arguments:

- graph*: A graph object or a null pointer, see the description above.
- nodes*: The number of nodes. This is ignored if the *graph* argument is not a null pointer.
- directed*: Boolean scalar, whether to use directed paths in the betweenness calculation. This argument is ignored if *graph* is not a null pointer and it is undirected.

res: Pointer to a real variable, the result is stored here.

Returns:

Error code.

Time complexity: $O(1)$.

See also:

`igraph_centralization_betweenness()` and `igraph_centralization()`.

`igraph_centralization_closeness_tmax` — Theoretical maximum for graph centralization based on closeness.

```
igraph_error_t igraph_centralization_closeness_tmax(const igraph_t *graph,
                                                    igraph_integer_t nodes,
                                                    igraph_neimode_t mode,
                                                    igraph_real_t *res);
```

This function returns the theoretical maximum graph centrality based on vertex closeness.

There are two ways to call this function, the first is to supply a graph as the `graph` argument, and then the number of vertices is taken from this object, and its directedness is considered as well. The `nodes` argument is ignored in this case. The `mode` argument is also ignored if the supplied graph is undirected.

The other way is to supply a null pointer as the `graph` argument. In this case the `nodes` and `mode` arguments are considered.

The most centralized structure is the star.

Arguments:

graph: A graph object or a null pointer, see the description above.

nodes: The number of nodes. This is ignored if the `graph` argument is not a null pointer.

mode: Constant, specifies what kind of distances to consider to calculate closeness. See the `mode` argument of `igraph_closeness()` for details. This argument is ignored if `graph` is not a null pointer and it is undirected.

res: Pointer to a real variable, the result is stored here.

Returns:

Error code.

Time complexity: $O(1)$.

See also:

`igraph_centralization_closeness()` and `igraph_centralization()`.

igraph_centralization_eigenvector_centrality_tmax — Theoretical maximum centralization for eigenvector centrality.

```
igraph_error_t igraph_centralization_eigenvector_centrality_tmax(  
    const igraph_t *graph,  
    igraph_integer_t nodes,  
    igraph_bool_t directed,  
    igraph_bool_t scale,  
    igraph_real_t *res);
```

This function returns the theoretical maximum graph centrality based on vertex eigenvector centrality.

There are two ways to call this function, the first is to supply a graph as the `graph` argument, and then the number of vertices is taken from this object, and its directedness is considered as well. The `nodes` argument is ignored in this case. The `directed` argument is also ignored if the supplied graph is undirected.

The other way is to supply a null pointer as the `graph` argument. In this case the `nodes` and `directed` arguments are considered.

The most centralized directed structure is the in-star. The most centralized undirected structure is the graph with a single edge.

Arguments:

graph: A graph object or a null pointer, see the description above.

nodes: The number of nodes. This is ignored if the `graph` argument is not a null pointer.

directed: Boolean scalar, whether to consider edge directions. This argument is ignored if graph is not a null pointer and it is undirected.

scale: Whether to rescale the node-level centrality scores to have a maximum of one.

res: Pointer to a real variable, the result is stored here.

Returns:

Error code.

Time complexity: $O(1)$.

See also:

`igraph_centralization_closeness()` and `igraph_centralization()`.

Similarity measures

igraph_bibcoupling — Bibliographic coupling.

```
igraph_error_t igraph_bibcoupling(const igraph_t *graph, igraph_matrix_t *res,  
    const igraph_vs_t vids);
```

The bibliographic coupling of two vertices is the number of other vertices they both cite, `igraph_bibcoupling()` calculates this. The bibliographic coupling score for each given vertex and all other vertices in the graph will be calculated.

Arguments:

graph: The graph object to analyze.

res: Pointer to a matrix, the result of the calculation will be stored here. The number of its rows is the same as the number of vertex IDs in *vids*, the number of columns is the number of vertices in the graph.

vids: The vertex IDs of the vertices for which the calculation will be done.

Returns:

Error code: `IGRAPH_EINVVID`: invalid vertex ID.

Time complexity: $O(|V|d^2)$, $|V|$ is the number of vertices in the graph, d is the (maximum) degree of the vertices in the graph.

See also:

`igraph_cocitation()`

Example 13.17. File `examples/simple/igraph_cocitation.c`

`igraph_cocitation` — Cocitation coupling.

```
igraph_error_t igraph_cocitation(const igraph_t *graph, igraph_matrix_t *res,
                                const igraph_vs_t vids);
```

Two vertices are cocited if there is another vertex citing both of them. `igraph_cocitation()` simply counts how many times two vertices are cocited. The cocitation score for each given vertex and all other vertices in the graph will be calculated.

Arguments:

graph: The graph object to analyze.

res: Pointer to a matrix, the result of the calculation will be stored here. The number of its rows is the same as the number of vertex IDs in *vids*, the number of columns is the number of vertices in the graph.

vids: The vertex IDs of the vertices for which the calculation will be done.

Returns:

Error code: `IGRAPH_EINVVID`: invalid vertex ID.

Time complexity: $O(|V|d^2)$, $|V|$ is the number of vertices in the graph, d is the (maximum) degree of the vertices in the graph.

See also:

`igraph_bibcoupling()`

Example 13.18. File `examples/simple/igraph_cocitation.c`

`igraph_similarity_jaccard` — Jaccard similarity coefficient for the given vertices.

```
igraph_error_t igraph_similarity_jaccard(const igraph_t *graph, igraph_matrix_t  
                                         const igraph_vs_t vids, igraph_neimode_t mode, ig
```

The Jaccard similarity coefficient of two vertices is the number of common neighbors divided by the number of vertices that are neighbors of at least one of the two vertices being considered. This function calculates the pairwise Jaccard similarities for some (or all) of the vertices.

Arguments:

graph: The graph object to analyze

res: Pointer to a matrix, the result of the calculation will be stored here. The number of its rows and columns is the same as the number of vertex IDs in *vids*.

vids: The vertex IDs of the vertices for which the calculation will be done.

mode: The type of neighbors to be used for the calculation in directed graphs. Possible values:

IGRAPH_OUT the outgoing edges will be considered for each node.

IGRAPH_IN the incoming edges will be considered for each node.

IGRAPH_ALL the directed graph is considered as an undirected one for the computation.

loops: Whether to include the vertices themselves in the neighbor sets.

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for temporary data.

IGRAPH_EINVVID invalid vertex ID passed.

IGRAPH_EINVMODE invalid mode argument.

Time complexity: $O(|V|^2 d)$, $|V|$ is the number of vertices in the vertex iterator given, d is the (maximum) degree of the vertices in the graph.

See also:

`igraph_similarity_dice()`, a measure very similar to the Jaccard coefficient

Example 13.19. File `examples/simple/igraph_similarity.c`

`igraph_similarity_jaccard_pairs` — Jaccard similarity coefficient for given vertex pairs.

```
igraph_error_t igraph_similarity_jaccard_pairs(const igraph_t *graph, igraph_vector_int_t *res,
                                              const igraph_vector_int_t *pairs, igraph_neimode_t mode,
                                              int loops);
```

The Jaccard similarity coefficient of two vertices is the number of common neighbors divided by the number of vertices that are neighbors of at least one of the two vertices being considered. This function calculates the pairwise Jaccard similarities for a list of vertex pairs.

Arguments:

- graph*: The graph object to analyze
- res*: Pointer to a vector, the result of the calculation will be stored here. The number of elements is the same as the number of pairs in *pairs*.
- pairs*: A vector that contains the pairs for which the similarity will be calculated. Each pair is defined by two consecutive elements, i.e. the first and second element of the vector specifies the first pair, the third and fourth element specifies the second pair and so on.
- mode*: The type of neighbors to be used for the calculation in directed graphs. Possible values:
- IGRAPH_OUT the outgoing edges will be considered for each node.
 - IGRAPH_IN the incoming edges will be considered for each node.
 - IGRAPH_ALL the directed graph is considered as an undirected one for the computation.
- loops*: Whether to include the vertices themselves in the neighbor sets.

Returns:

Error code:

- IGRAPH_ENOMEM not enough memory for temporary data.
- IGRAPH_EINVAL invalid vertex ID passed.
- IGRAPH_EINVALMODE invalid mode argument.

Time complexity: $O(nd)$, n is the number of pairs in the given vector, d is the (maximum) degree of the vertices in the graph.

See also:

`igraph_similarity_jaccard()` to calculate the Jaccard similarity between all pairs of a vertex set, or `igraph_similarity_dice()` and `igraph_similarity_dice_pairs()` for a measure very similar to the Jaccard coefficient

Example 13.20. File `examples/simple/igraph_similarity.c`

igraph_similarity_jaccard_es — Jaccard similarity coefficient for a given edge selector.

```
igraph_error_t igraph_similarity_jaccard_es(const igraph_t *graph, igraph_vector_int_t *res,
                                             const igraph_es_t es, igraph_neimode_t mode,
                                             int loops);
```

The Jaccard similarity coefficient of two vertices is the number of common neighbors divided by the number of vertices that are neighbors of at least one of the two vertices being considered. This function calculates the pairwise Jaccard similarities for the endpoints of edges in a given edge selector.

Arguments:

- graph*: The graph object to analyze
- res*: Pointer to a vector, the result of the calculation will be stored here. The number of elements is the same as the number of edges in *es*.
- es*: An edge selector that specifies the edges to be included in the result.
- mode*: The type of neighbors to be used for the calculation in directed graphs. Possible values:
- IGRAPH_OUT the outgoing edges will be considered for each node.
 - IGRAPH_IN the incoming edges will be considered for each node.
 - IGRAPH_ALL the directed graph is considered as an undirected one for the computation.
- loops*: Whether to include the vertices themselves in the neighbor sets.

Returns:

Error code:

- IGRAPH_ENOMEM not enough memory for temporary data.
- IGRAPH_EINVAL invalid vertex ID passed.
- IGRAPH_EINVMODE invalid mode argument.

Time complexity: $O(nd)$, n is the number of edges in the edge selector, d is the (maximum) degree of the vertices in the graph.

See also:

`igraph_similarity_jaccard()` and `igraph_similarity_jaccard_pairs()` to calculate the Jaccard similarity between all pairs of a vertex set or some selected vertex pairs, or `igraph_similarity_dice()`, `igraph_similarity_dice_pairs()` and `igraph_similarity_dice_es()` for a measure very similar to the Jaccard coefficient

Example 13.21. File `examples/simple/igraph_similarity.c`

igraph_similarity_dice — Dice similarity coefficient.

```
igraph_error_t igraph_similarity_dice(const igraph_t *graph, igraph_matrix_t *res,
                                     const igraph_vs_t vids, igraph_neimode_t mode, igraph_bool_t loops)
```

The Dice similarity coefficient of two vertices is twice the number of common neighbors divided by the sum of the degrees of the vertices. This function calculates the pairwise Dice similarities for some (or all) of the vertices.

Arguments:

graph: The graph object to analyze

res: Pointer to a matrix, the result of the calculation will be stored here. The number of its rows and columns is the same as the number of vertex IDs in *vids*.

vids: The vertex IDs of the vertices for which the calculation will be done.

mode: The type of neighbors to be used for the calculation in directed graphs. Possible values:

- IGRAPH_OUT the outgoing edges will be considered for each node.
- IGRAPH_IN the incoming edges will be considered for each node.
- IGRAPH_ALL the directed graph is considered as an undirected one for the computation.

loops: Whether to include the vertices themselves as their own neighbors.

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for temporary data.

IGRAPH_EINVVID invalid vertex ID passed.

IGRAPH_EINVMODE invalid mode argument.

Time complexity: $O(|V|^2 d)$, $|V|$ is the number of vertices in the vertex iterator given, d is the (maximum) degree of the vertices in the graph.

See also:

`igraph_similarity_jaccard()`, a measure very similar to the Dice coefficient

Example 13.22. File `examples/simple/igraph_similarity.c`

igraph_similarity_dice_pairs — Dice similarity coefficient for given vertex pairs.

```
igraph_error_t igraph_similarity_dice_pairs(const igraph_t *graph, igraph_vector_t *res,
                                           const igraph_vector_int_t *pairs, igraph_neimod_t mode)
```

The Dice similarity coefficient of two vertices is twice the number of common neighbors divided by the sum of the degrees of the vertices. This function calculates the pairwise Dice similarities for a list of vertex pairs.

Arguments:

graph: The graph object to analyze

res: Pointer to a vector, the result of the calculation will be stored here. The number of elements is the same as the number of pairs in *pairs*.

pairs: A vector that contains the pairs for which the similarity will be calculated. Each pair is defined by two consecutive elements, i.e. the first and second element of the vector specifies the first pair, the third and fourth element specifies the second pair and so on.

mode: The type of neighbors to be used for the calculation in directed graphs. Possible values:

- IGRAPH_OUT the outgoing edges will be considered for each node.
- IGRAPH_IN the incoming edges will be considered for each node.
- IGRAPH_ALL the directed graph is considered as an undirected one for the computation.

loops: Whether to include the vertices themselves as their own neighbors.

Returns:

Error code:

- IGRAPH_ENOMEM not enough memory for temporary data.
- IGRAPH_EINVVID invalid vertex ID passed.
- IGRAPH_EINVMODE invalid mode argument.

Time complexity: $O(nd)$, n is the number of pairs in the given vector, d is the (maximum) degree of the vertices in the graph.

See also:

`igraph_similarity_dice()` to calculate the Dice similarity between all pairs of a vertex set, or `igraph_similarity_jaccard()`, `igraph_similarity_jaccard_pairs()` and `igraph_similarity_jaccard_es()` for a measure very similar to the Dice coefficient

Example 13.23. File `examples/simple/igraph_similarity.c`

`igraph_similarity_dice_es` — Dice similarity coefficient for a given edge selector.

```
igraph_error_t igraph_similarity_dice_es(const igraph_t *graph, igraph_vector_t  
                                         const igraph_es_t es, igraph_neimode_t mode, igraph_res_t res)
```

The Dice similarity coefficient of two vertices is twice the number of common neighbors divided by the sum of the degrees of the vertices. This function calculates the pairwise Dice similarities for the endpoints of edges in a given edge selector.

Arguments:

graph: The graph object to analyze

res: Pointer to a vector, the result of the calculation will be stored here. The number of elements is the same as the number of edges in *es*.

es: An edge selector that specifies the edges to be included in the result.

mode: The type of neighbors to be used for the calculation in directed graphs. Possible values:

- IGRAPH_OUT the outgoing edges will be considered for each node.
- IGRAPH_IN the incoming edges will be considered for each node.
- IGRAPH_ALL the directed graph is considered as an undirected one for the computation.

loops: Whether to include the vertices themselves as their own neighbors.

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for temporary data.

IGRAPH_EINVVID invalid vertex ID passed.

IGRAPH_EINVMODE invalid mode argument.

Time complexity: $O(nd)$, n is the number of pairs in the given vector, d is the (maximum) degree of the vertices in the graph.

See also:

`igraph_similarity_dice()` and `igraph_similarity_dice_pairs()` to calculate the Dice similarity between all pairs of a vertex set or some selected vertex pairs, or `igraph_similarity_jaccard()`, `igraph_similarity_jaccard_pairs()` and `igraph_similarity_jaccard_es()` for a measure very similar to the Dice coefficient

Example 13.24. File `examples/simple/igraph_similarity.c`

`igraph_similarity_inverse_log_weighted` — Vertex similarity based on the inverse logarithm of vertex degrees.

```
igraph_error_t igraph_similarity_inverse_log_weighted(const igraph_t *graph,
                                                    igraph_matrix_t *res, const igraph_vs_t vids, igraph_neimode_t mode);
```

The inverse log-weighted similarity of two vertices is the number of their common neighbors, weighted by the inverse logarithm of their degrees. It is based on the assumption that two vertices should be considered more similar if they share a low-degree common neighbor, since high-degree common neighbors are more likely to appear even by pure chance.

Isolated vertices will have zero similarity to any other vertex. Self-similarities are not calculated.

See the following paper for more details: Lada A. Adamic and Eytan Adar: Friends and neighbors on the Web. *Social Networks*, 25(3):211-230, 2003.

Arguments:

graph: The graph object to analyze.

res: Pointer to a matrix, the result of the calculation will be stored here. The number of its rows is the same as the number of vertex IDs in *vids*, the number of columns is the number of vertices in the graph.

vids: The vertex IDs of the vertices for which the calculation will be done.

mode: The type of neighbors to be used for the calculation in directed graphs. Possible values:

IGRAPH_OUT the outgoing edges will be considered for each node. Nodes will be weighted according to their in-degree.

IGRAPH_IN	the incoming edges will be considered for each node. Nodes will be weighted according to their out-degree.
IGRAPH_ALL	the directed graph is considered as an undirected one for the computation. Every node is weighted according to its undirected degree.

Returns:

Error code: IGRAPH_EINVVID: invalid vertex ID.

Time complexity: $O(|V|d^2)$, $|V|$ is the number of vertices in the graph, d is the (maximum) degree of the vertices in the graph.

Example 13.25. File `examples/simple/igraph_similarity.c`

Trees and forests

`igraph_minimum_spanning_tree` — Calculates one minimum spanning tree of a graph.

```
igraph_error_t igraph_minimum_spanning_tree(  
    const igraph_t* graph, igraph_vector_int_t* res, const igraph_vector_t* weights  
);
```

If the graph has more minimum spanning trees (this is always the case, except if it is a forest) this implementation returns only the same one.

Directed graphs are considered as undirected for this computation.

If the graph is not connected then its minimum spanning forest is returned. This is the set of the minimum spanning trees of each component.

Arguments:

graph: The graph object.

res: An initialized vector, the IDs of the edges that constitute a spanning tree will be returned here. Use `igraph_subgraph_edges()` to extract the spanning tree as a separate graph object.

weights: A vector containing the weights of the edges in the same order as the simple edge iterator visits them (i.e. in increasing order of edge IDs).

Returns:

Error code: IGRAPH_ENOMEM, not enough memory for temporary data.

Time complexity: $O(|V|+|E|)$ for the unweighted case, $O(|E| \log |V|)$ for the weighted case. $|V|$ is the number of vertices, $|E|$ the number of edges in the graph.

See also:

`igraph_minimum_spanning_tree_unweighted()` and `igraph_minimum_spanning_tree_prim()` if you only need the tree as a separate graph object.

Example	13.26.	File	examples/simple/
igraph_minimum_spanning_tree.c			

igraph_minimum_spanning_tree_unweighted — Calculates one minimum spanning tree of an unweighted graph.

```
igraph_error_t igraph_minimum_spanning_tree_unweighted(const igraph_t *graph,
                                                       igraph_t *mst);
```

If the graph has more minimum spanning trees (this is always the case, except if it is a forest) this implementation returns only the same one.

Directed graphs are considered as undirected for this computation.

If the graph is not connected then its minimum spanning forest is returned. This is the set of the minimum spanning trees of each component.

Arguments:

graph: The graph object.

mst: The minimum spanning tree, another graph object. Do *not* initialize this object before passing it to this function, but be sure to call `igraph_destroy()` on it if you don't need it any more.

Returns:

Error code: `IGRAPH_ENOMEM`, not enough memory for temporary data.

Time complexity: $O(|V|+|E|)$, $|V|$ is the number of vertices, $|E|$ the number of edges in the graph.

See also:

`igraph_minimum_spanning_tree_prim()` for weighted graphs, `igraph_minimum_spanning_tree()` if you need the IDs of the edges that constitute the spanning tree.

igraph_minimum_spanning_tree_prim — Calculates one minimum spanning tree of a weighted graph.

```
igraph_error_t igraph_minimum_spanning_tree_prim(const igraph_t *graph, igraph_t *mst,
                                                  const igraph_vector_t *weights);
```

This function uses Prim's method for carrying out the computation, see Prim, R.C.: Shortest connection networks and some generalizations, Bell System Technical Journal, Vol. 36, 1957, 1389--1401.

If the graph has more than one minimum spanning tree, the current implementation returns always the same one.

Directed graphs are considered as undirected for this computation.

If the graph is not connected then its minimum spanning forest is returned. This is the set of the minimum spanning trees of each component.

Arguments:

graph: The graph object.

mst: The result of the computation, a graph object containing the minimum spanning tree of the graph. Do *not* initialize this object before passing it to this function, but be sure to call `igraph_destroy()` on it if you don't need it any more.

weights: A vector containing the weights of the edges in the same order as the simple edge iterator visits them (i.e. in increasing order of edge IDs).

Returns:

Error code: `IGRAPH_ENOMEM`, not enough memory. `IGRAPH_EINVAL`, length of weight vector does not match number of edges.

Time complexity: $O(|E| \log |V|)$, $|V|$ is the number of vertices, $|E|$ the number of edges in the graph.

See also:

`igraph_minimum_spanning_tree_unweighted()` for unweighted graphs, `igraph_minimum_spanning_tree()` if you need the IDs of the edges that constitute the spanning tree.

Example 13.27. File `examples/simple/igraph_minimum_spanning_tree.c`

`igraph_random_spanning_tree` — Uniformly sample the spanning trees of a graph

```
igraph_error_t igraph_random_spanning_tree(const igraph_t *graph, igraph_vector_t &res,
```

Performs a loop-erased random walk on the graph to uniformly sample its spanning trees. Edge directions are ignored.

Multi-graphs are supported, and edge multiplicities will affect the sampling frequency. For example, consider the 3-cycle graph $1=2-3-1$, with two edges between vertices 1 and 2. Due to these parallel edges, the trees $1-2-3$ and $3-1-2$ will be sampled with multiplicity 2, while the tree $2-3-1$ will be sampled with multiplicity 1.

Arguments:

graph: The input graph. Edge directions are ignored.

res: An initialized vector, the IDs of the edges that constitute a spanning tree will be returned here. Use `igraph_subgraph_edges()` to extract the spanning tree as a separate graph object.

vid: This parameter is relevant if the graph is not connected. If negative, a random spanning forest of all components will be generated. Otherwise, it should be the ID of a vertex. A random spanning tree of the component containing the vertex will be generated.

Returns:

Error code.

See also:

`igraph_minimum_spanning_tree()`, `igraph_random_walk()`

`igraph_is_tree` — Decides whether the graph is a tree.

```
igraph_error_t igraph_is_tree(const igraph_t *graph, igraph_bool_t *res, igraph_t *root, igraph_mode_t mode)
```

An undirected graph is a tree if it is connected and has no cycles.

In the directed case, a possible additional requirement is that all edges are oriented away from a root (out-tree or arborescence) or all edges are oriented towards a root (in-tree or anti-arborescence). This test can be controlled using the *mode* parameter.

By convention, the null graph (i.e. the graph with no vertices) is considered not to be a tree.

Arguments:

graph: The graph object to analyze.

res: Pointer to a logical variable, the result will be stored here.

root: If not NULL, the root node will be stored here. When *mode* is `IGRAPH_ALL` or the graph is undirected, any vertex can be the root and *root* is set to 0 (the first vertex). When *mode* is `IGRAPH_OUT` or `IGRAPH_IN`, the root is set to the vertex with zero in- or out-degree, respectively.

mode: For a directed graph this specifies whether to test for an out-tree, an in-tree or ignore edge directions. The respective possible values are: `IGRAPH_OUT`, `IGRAPH_IN`, `IGRAPH_ALL`. This argument is ignored for undirected graphs.

Returns:

Error code: `IGRAPH_EINVAL`: invalid mode argument.

Time complexity: At most $O(|V|+|E|)$, the number of vertices plus the number of edges in the graph.

See also:

`igraph_is_weakly_connected()`

Example 13.28. File `examples/simple/igraph_kary_tree.c`

`igraph_is_forest` — Decides whether the graph is a forest.

```
igraph_error_t igraph_is_forest(const igraph_t *graph, igraph_bool_t *res,
                                igraph_vector_int_t *roots, igraph_neimode_t mo
```

An undirected graph is a forest if it has no cycles.

In the directed case, a possible additional requirement is that edges in each tree are oriented away from the root (out-trees or arborescences) or all edges are oriented towards the root (in-trees or anti-arborescences). This test can be controlled using the *mode* parameter.

By convention, the null graph (i.e. the graph with no vertices) is considered to be a forest.

The *res* return value of this function is cached in the graph itself if *mode* is set to `IGRAPH_ALL` or if the graph is undirected. Calling the function multiple times with no modifications to the graph in between will return a cached value in $O(1)$ time if the roots are not asked for.

Arguments:

graph: The graph object to analyze.

res: Pointer to a logical variable. If not `NULL`, then the result will be stored here.

roots: If not `NULL`, the root nodes will be stored here. When *mode* is `IGRAPH_ALL` or the graph is undirected, any one vertex from each component can be the root. When *mode* is `IGRAPH_OUT` or `IGRAPH_IN`, all the vertices with zero in- or out-degree, respectively are considered as root nodes.

mode: For a directed graph this specifies whether to test for an out-forest, an in-forest or ignore edge directions. The respective possible values are: `IGRAPH_OUT`, `IGRAPH_IN`, `IGRAPH_ALL`. This argument is ignored for undirected graphs.

Returns:

Error code: `IGRAPH_EINVALMODE`: invalid mode argument.

Time complexity: At most $O(|V|+|E|)$, the number of vertices plus the number of edges in the graph.

igraph_to_prufer — Converts a tree to its Prüfer sequence

```
igraph_error_t igraph_to_prufer(const igraph_t *graph, igraph_vector_int_t* pr
```

A Prüfer sequence is a unique sequence of integers associated with a labelled tree. A tree on $n \geq 2$ vertices can be represented by a sequence of $n-2$ integers, each between 0 and $n-1$ (inclusive).

Arguments:

graph: Pointer to an initialized graph object which must be a tree on $n \geq 2$ vertices.

prufer: A pointer to the integer vector that should hold the Prüfer sequence; the vector must be initialized and will be resized to $n - 2$.

Returns:

Error code:

`IGRAPH_ENOMEM` there is not enough memory to perform the operation.

IGRAPH_EINVAL the graph is not a tree or it has less than vertices

See also:

`igraph_from_prufer()`

Transitivity or clustering coefficient

`igraph_transitivity_undirected` — Calculates the transitivity (clustering coefficient) of a graph.

```
igraph_error_t igraph_transitivity_undirected(const igraph_t *graph,
                                              igraph_real_t *res,
                                              igraph_transitivity_mode_t mode);
```

The transitivity measures the probability that two neighbors of a vertex are connected. More precisely, this is the ratio of the triangles and connected triples in the graph, the result is a single real number. Directed graphs are considered as undirected ones and multi-edges are ignored.

Note that this measure is different from the local transitivity measure (see `igraph_transitivity_local_undirected()`) as it calculates a single value for the whole graph.

Clustering coefficient is an alternative name for transitivity.

References:

S. Wasserman and K. Faust: Social Network Analysis: Methods and Applications. Cambridge: Cambridge University Press, 1994.

Arguments:

graph: The graph object. Edge directions and multiplicities are ignored.

res: Pointer to a real variable, the result will be stored here.

mode: Defines how to treat graphs with no connected triples. `IGRAPH_TRANSITIVITY_NAN` returns NaN in this case, `IGRAPH_TRANSITIVITY_ZERO` returns zero.

Returns:

Error code: `IGRAPH_ENOMEM`: not enough memory for temporary data.

See also:

`igraph_transitivity_local_undirected()`, `igraph_transitivity_avglocal_undirected()`.

Time complexity: $O(|V| \cdot d^2)$, $|V|$ is the number of vertices in the graph, d is the average node degree.

Example 13.29. File `examples/simple/igraph_transitivity.c`

igraph_transitivity_local_undirected — Calculates the local transitivity (clustering coefficient) of a graph.

```
igraph_error_t igraph_transitivity_local_undirected(const igraph_t *graph,
                                                    igraph_vector_t *res,
                                                    const igraph_vs_t vids,
                                                    igraph_transitivity_mode_t mode);
```

The transitivity measures the probability that two neighbors of a vertex are connected. In case of the local transitivity, this probability is calculated separately for each vertex.

Note that this measure is different from the global transitivity measure (see `igraph_transitivity_undirected()`) as it calculates a transitivity value for each vertex individually.

Clustering coefficient is an alternative name for transitivity.

References:

D. J. Watts and S. Strogatz: Collective dynamics of small-world networks. *Nature* 393(6684):440-442 (1998).

Arguments:

graph: The input graph. Edge directions and multiplicities are ignored.

res: Pointer to an initialized vector, the result will be stored here. It will be resized as needed.

vids: Vertex set, the vertices for which the local transitivity will be calculated.

mode: Defines how to treat vertices with degree less than two. `IGRAPH_TRANSITIVITY_NAN` returns NaN for these vertices, `IGRAPH_TRANSITIVITY_ZERO` returns zero.

Returns:

Error code.

See also:

```
igraph_transitivity_undirected(),      igraph_transitivity_avglocal_undirected().
```

Time complexity: $O(n*d^2)$, n is the number of vertices for which the transitivity is calculated, d is the average vertex degree.

igraph_transitivity_avglocal_undirected — Average local transitivity (clustering coefficient).

```
igraph_error_t igraph_transitivity_avglocal_undirected(const igraph_t *graph,
                                                        igraph_real_t *res,
                                                        igraph_transitivity_mode_t mode);
```


The transitivity measures the probability that two neighbors of a vertex are connected. In case of the average local transitivity, this probability is calculated for each vertex and then the average is taken. Vertices with less than two neighbors require special treatment, they will either be left out from the calculation or they will be considered as having zero transitivity, depending on the mode argument. Edge directions and edge multiplicities are ignored.

Note that this measure is different from the global transitivity measure (see `igraph_transitivity_undirected()`) as it simply takes the average local transitivity across the whole network.

Clustering coefficient is an alternative name for transitivity.

References:

D. J. Watts and S. Strogatz: Collective dynamics of small-world networks. Nature 393(6684):440-442 (1998).

Arguments:

graph: The input graph. Edge directions and multiplicities are ignored.

res: Pointer to a real variable, the result will be stored here.

mode: Defines how to treat vertices with degree less than two. `IGRAPH_TRANSITIVITY_NAN` leaves them out from averaging, `IGRAPH_TRANSITIVITY_ZERO` includes them with zero transitivity. The result will be NaN if the mode is `IGRAPH_TRANSITIVITY_NAN` and there are no vertices with more than one neighbor.

Returns:

Error code.

See also:

`igraph_transitivity_undirected()`, `igraph_transitivity_local_undirected()`.

Time complexity: $O(|V|*d^2)$, $|V|$ is the number of vertices in the graph and d is the average degree.

`igraph_transitivity_barrat` — Weighted transitivity, as defined by A. Barrat.

```
igraph_error_t igraph_transitivity_barrat(const igraph_t *graph,
                                          igraph_vector_t *res,
                                          const igraph_vs_t vids,
                                          const igraph_vector_t *weights,
                                          igraph_transitivity_mode_t mode);
```

This is a local transitivity, i.e. a vertex-level index. For a given vertex i , from all triangles in which it participates we consider the weight of the edges incident on i . The transitivity is the sum of these weights divided by twice the strength of the vertex (see `igraph_strength()`) and the degree of the vertex minus one. See Alain Barrat, Marc Barthélemy, Romualdo Pastor-Satorras, Alessandro Vespignani: The architecture of complex weighted networks, Proc. Natl. Acad. Sci. USA 101, 3747 (2004) at <http://arxiv.org/abs/cond-mat/0311416> for the exact formula.

Arguments:

graph: The input graph. Edge directions are ignored for directed graphs. Note that the function does *not* work for non-simple graphs.

res: Pointer to an initialized vector, the result will be stored here. It will be resized as needed.

vids: The vertices for which the calculation is performed.

weights: Edge weights. If this is a null pointer, then a warning is given and `igraph_transitivity_local_undirected()` is called.

mode: Defines how to treat vertices with zero strength. `IGRAPH_TRANSITIVITY_NAN` says that the transitivity of these vertices is NaN, `IGRAPH_TRANSITIVITY_ZERO` says it is zero.

Returns:

Error code.

Time complexity: $O(|V|*d^2)$, $|V|$ is the number of vertices in the graph, d is the average node degree.

See also:

`igraph_transitivity_undirected()`, `igraph_transitivity_local_undirected()` and `igraph_transitivity_avglocal_undirected()` for other kinds of (non-weighted) transitivity.

Directedness conversion

`igraph_to_directed` — Convert an undirected graph to a directed one

```
igraph_error_t igraph_to_directed(igraph_t *graph,
                                  igraph_to_directed_t mode);
```

If the supplied graph is directed, this function does nothing.

Arguments:

graph: The graph object to convert.

mode: Constant, specifies the details of how exactly the conversion is done. Possible values:

<code>IGRAPH_TO_DIRECTED_ARBITRARY</code>	The number of edges in the graph stays the same, an arbitrarily directed edge is created for each undirected edge.
<code>IGRAPH_TO_DIRECTED_MUTUAL</code>	Two directed edges are created for each undirected edge, one in each direction.
<code>IGRAPH_TO_DIRECTED_RANDOM</code>	Each undirected edge is converted to a randomly oriented directed one.
<code>IGRAPH_TO_DIRECTED_ACYCLIC</code>	Each undirected edge is converted to a directed edge oriented from a lower index vertex to a higher

index one. If no self-loops were present, then the result is a directed acyclic graph.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

igraph_to_undirected — Convert a directed graph to an undirected one.

```
igraph_error_t igraph_to_undirected(igraph_t *graph,  
                                     igraph_to_undirected_t mode,  
                                     const igraph_attribute_combination_t *edge_comb);
```

If the supplied graph is undirected, this function does nothing.

Arguments:

graph: The graph object to convert.

mode: Constant, specifies the details of how exactly the conversion is done. Possible values: `IGRAPH_TO_UNDIRECTED_EACH`: the number of edges remains constant, an undirected edge is created for each directed one, this version might create graphs with multiple edges; `IGRAPH_TO_UNDIRECTED_COLLAPSE`: one undirected edge will be created for each pair of vertices that are connected with at least one directed edge, no multiple edges will be created. `IGRAPH_TO_UNDIRECTED_MUTUAL` creates an undirected edge for each pair of mutual edges in the directed graph. Non-mutual edges are lost; loop edges are kept unconditionally. This mode might create multiple edges.

edge_comb: What to do with the edge attributes. See the igraph manual section about attributes for details. `NULL` means that the edge attributes are lost during the conversion, *except* when mode is `IGRAPH_TO_UNDIRECTED_EACH`, in which case the edge attributes are kept intact.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

Example 13.30. File `examples/simple/igraph_to_undirected.c`

Spectral properties

igraph_get_laplacian — Returns the Laplacian matrix of a graph.

```
igraph_error_t igraph_get_laplacian(  
    const igraph_t *graph, igraph_matrix_t *res, igraph_neimode_t mode,  
    igraph_laplacian_normalization_t normalization,  
    const igraph_vector_t *weights  
);
```

The Laplacian matrix L of a graph is defined as $L_{ij} = -A_{ij}$ when $i \neq j$ and $L_{ii} = d_i - A_{ii}$. Here A denotes the (possibly weighted) adjacency matrix and d_i is the degree (or strength, if weighted) of vertex i . In directed graphs, the *mode* parameter controls whether to use out- or in-degrees. Correspondingly, the rows or columns will sum to zero. In undirected graphs, A_{ii} is taken to be *twice* the number (or total weight) of self-loops, ensuring that $d_i = \sum_j A_{ij}$. Thus, the Laplacian of an undirected graph is the same as the Laplacian of a directed one obtained by replacing each undirected edge with two reciprocal directed ones.

More compactly, $L = D - A$ where the D is a diagonal matrix containing the degrees. The Laplacian matrix can also be normalized, with several conventional normalization methods. See `igraph_laplacian_normalization_t` for the methods available in `igraph`.

The first version of this function was written by Vincent Matossian.

Arguments:

<i>graph</i> :	Pointer to the graph to convert.
<i>res</i> :	Pointer to an initialized matrix object, the result is stored here. It will be resized if needed.
<i>mode</i> :	Controls whether to use out- or in-degrees in directed graphs. If set to <code>IGRAPH_ALL</code> , edge directions will be ignored.
<i>normalization</i> :	The normalization method to use when calculating the Laplacian matrix. See <code>igraph_laplacian_normalization_t</code> for possible values.
<i>weights</i> :	An optional vector containing non-negative edge weights, to calculate the weighted Laplacian matrix. Set it to a null pointer to calculate the unweighted Laplacian.

Returns:

Error code.

Time complexity: $O(|V|^2)$, $|V|$ is the number of vertices in the graph.

Example 13.31. File `examples/simple/igraph_get_laplacian.c`

`igraph_get_laplacian_sparse` — Returns the Laplacian of a graph in a sparse matrix format.

```
igraph_error_t igraph_get_laplacian_sparse(  
    const igraph_t *graph, igraph_sparsemat_t *sparseres, igraph_neimode_t mode,  
    igraph_laplacian_normalization_t normalization,  
    const igraph_vector_t *weights  
);
```

See `igraph_get_laplacian()` for the definition of the Laplacian matrix.

The first version of this function was written by Vincent Matossian.

Arguments:

<i>graph</i> :	Pointer to the graph to convert.
<i>sparse</i> :	Pointer to an initialized sparse matrix object, the result is stored here.
<i>mode</i> :	Controls whether to use out- or in-degrees in directed graphs. If set to <code>IGRAPH_ALL</code> , edge directions will be ignored.
<i>normalization</i> :	The normalization method to use when calculating the Laplacian matrix. See <code>igraph_laplacian_normalization_t</code> for possible values.
<i>weights</i> :	An optional vector containing non-negative edge weights, to calculate the weighted Laplacian matrix. Set it to a null pointer to calculate the unweighted Laplacian.

Returns:

Error code.

Time complexity: $O(|E|)$, $|E|$ is the number of edges in the graph.

Example 13.32. File `examples/simple/igraph_get_laplacian_sparse.c`

`igraph_laplacian_normalization_t` — Normalization methods for a Laplacian matrix.

```
typedef enum {
    IGRAPH_LAPLACIAN_UNNORMALIZED = 0,
    IGRAPH_LAPLACIAN_SYMMETRIC = 1,
    IGRAPH_LAPLACIAN_LEFT = 2,
    IGRAPH_LAPLACIAN_RIGHT = 3
} igraph_laplacian_normalization_t;
```

Normalization methods for `igraph_get_laplacian()` and `igraph_get_laplacian_sparse()`. In the following, A refers to the (possibly weighted) adjacency matrix and D is a diagonal matrix containing degrees (unweighted case) or strengths (weighted case). Out-, in- or total degrees are used according to the *mode* parameter.

Values:

<code>IGRAPH_LAPLACIAN_UNNORMALIZED</code> :	Unnormalized Laplacian, $L = D - A$.
<code>IGRAPH_LAPLACIAN_SYMMETRIC</code> :	Symmetric normalized Laplacian, $L = I - D^{-1/2} A D^{-1/2}$.
<code>IGRAPH_LAPLACIAN_LEFT</code> :	Left-stochastic normalized Laplacian, $L = I - D^{-1} A$.
<code>IGRAPH_LAPLACIAN_RIGHT</code> :	Right-stochastic normalized Laplacian, $L = I - A D^{-1}$.

Non-simple graphs: Multiple and loop edges

igraph_is_simple — Decides whether the input graph is a simple graph.

```
igraph_error_t igraph_is_simple(const igraph_t *graph, igraph_bool_t *res);
```

A graph is a simple graph if it does not contain loop edges and multiple edges.

Arguments:

graph: The input graph.

res: Pointer to a boolean constant, the result is stored here.

Returns:

Error code.

See also:

`igraph_is_loop()` and `igraph_is_multiple()` to find the loops and multiple edges, `igraph_simplify()` to get rid of them, or `igraph_has_multiple()` to decide whether there is at least one multiple edge.

Time complexity: $O(|V|+|E|)$.

igraph_is_loop — Find the loop edges in a graph.

```
igraph_error_t igraph_is_loop(const igraph_t *graph, igraph_vector_bool_t *res,
                              igraph_es_t es);
```

A loop edge is an edge from a vertex to itself.

Arguments:

graph: The input graph.

res: Pointer to an initialized boolean vector for storing the result, it will be resized as needed.

es: The edges to check, for all edges supply `igraph_ess_all()` here.

Returns:

Error code.

See also:

`igraph_simplify()` to get rid of loop edges.

Time complexity: $O(e)$, the number of edges to check.

Example 13.33. File `examples/simple/igraph_is_loop.c`

igraph_is_multiple — Find the multiple edges in a graph.

```
igraph_error_t igraph_is_multiple(const igraph_t *graph, igraph_vector_bool_t *res,
                                  igraph_es_t es);
```

An edge is a multiple edge if there is another edge with the same head and tail vertices in the graph.

Note that this function returns true only for the second or more appearances of the multiple edges.

Arguments:

graph: The input graph.

res: Pointer to a boolean vector, the result will be stored here. It will be resized as needed.

es: The edges to check. Supply `igraph_ess_all()` if you want to check all edges.

Returns:

Error code.

See also:

`igraph_count_multiple()`, `igraph_has_multiple()` and `igraph_simplify()`.

Time complexity: $O(e*d)$, e is the number of edges to check and d is the average degree (out-degree in directed graphs) of the vertices at the tail of the edges.

Example 13.34. File `examples/simple/igraph_is_multiple.c`

igraph_has_multiple — Check whether the graph has at least one multiple edge.

```
igraph_error_t igraph_has_multiple(const igraph_t *graph, igraph_bool_t *res);
```

An edge is a multiple edge if there is another edge with the same head and tail vertices in the graph.

The return value of this function is cached in the graph itself; calling the function multiple times with no modifications to the graph in between will return a cached value in $O(1)$ time.

Arguments:

graph: The input graph.

res: Pointer to a boolean variable, the result will be stored here.

Returns:

Error code.

See also:

`igraph_count_multiple()`, `igraph_is_multiple()` and `igraph_simplify()`.

Time complexity: $O(e*d)$, e is the number of edges to check and d is the average degree (out-degree in directed graphs) of the vertices at the tail of the edges.

Example 13.35. File `examples/simple/igraph_has_multiple.c`

`igraph_count_multiple` — Count the number of appearances of the edges in a graph.

```
igraph_error_t igraph_count_multiple(const igraph_t *graph, igraph_vector_int_t
```

If the graph has no multiple edges then the result vector will be filled with ones. (An edge is a multiple edge if there is another edge with the same head and tail vertices in the graph.)

Arguments:

graph: The input graph.

res: Pointer to a vector, the result will be stored here. It will be resized as needed.

es: The edges to check. Supply `igraph_ess_all()` if you want to check all edges.

Returns:

Error code.

See also:

`igraph_is_multiple()` and `igraph_simplify()`.

Time complexity: $O(E d)$, E is the number of edges to check and d is the average degree (out-degree in directed graphs) of the vertices at the tail of the edges.

Mixing patterns

`igraph_assortativity_nominal` — Assortativity of a graph based on vertex categories.

```
igraph_error_t igraph_assortativity_nominal(const igraph_t *graph,
                                             const igraph_vector_int_t *types,
                                             igraph_real_t *res,
                                             igraph_bool_t directed,
```



```
igraph_bool_t normalized);
```

Assuming the vertices of the input graph belong to different categories, this function calculates the assortativity coefficient of the graph. The assortativity coefficient is between minus one and one and it is one if all connections stay within categories, it is minus one, if the network is perfectly disassortative. For a randomly connected network it is (asymptotically) zero.

The unnormalized version, computed when *normalized* is set to false, is identical to the modularity, and is defined as follows for directed networks:

$$1/m \sum_{ij} (A_{ij} - k^{\text{out}}_i k^{\text{in}}_j / m) d(i, j),$$

where m denotes the number of edges, A_{ij} is the adjacency matrix, k^{out} and k^{in} are the out- and in-degrees, and $d(i, j)$ is one if vertices i and j are in the same category and zero otherwise.

The normalized assortativity coefficient is obtained by dividing the previous expression by

$$1/m \sum_{ij} (m - k^{\text{out}}_i k^{\text{in}}_j d(i, j) / m).$$

It can take any value within the interval $[-1, 1]$.

Undirected graphs are effectively treated as directed ones with all-reciprocal edges. Thus, self-loops are taken into account twice in undirected graphs.

References:

M. E. J. Newman: Mixing patterns in networks, Phys. Rev. E 67, 026126 (2003) <https://doi.org/10.1103/PhysRevE.67.026126>. See section II and equation (2) for the definition of the concept.

For an educational overview of assortativity, see M. E. J. Newman, Networks: An Introduction, Oxford University Press (2010). <https://doi.org/10.1093/acprof%3Aoso/9780199206650.001.0001>.

Arguments:

<i>graph</i> :	The input graph, it can be directed or undirected.
<i>types</i> :	Integer vector giving the vertex categories. The types are represented by integers starting at zero.
<i>res</i> :	Pointer to a real variable, the result is stored here.
<i>directed</i> :	Boolean, it gives whether to consider edge directions in a directed graph. It is ignored for undirected graphs.
<i>normalized</i> :	Boolean, whether to compute the usual normalized assortativity. The unnormalized version is identical to modularity. Supply true here to compute the standard assortativity.

Returns:

Error code.

Time complexity: $O(|E|+t)$, $|E|$ is the number of edges, t is the number of vertex types.

See also:

`igraph_assortativity()` for computing the assortativity based on continuous vertex values instead of discrete categories. `igraph_modularity()` to compute generalized modularity.

Example 13.36. File `examples/simple/igraph_assortativity_nominal.c`

igraph_assortativity — Assortativity based on numeric properties of vertices.

```
igraph_error_t igraph_assortativity(const igraph_t *graph,
                                   const igraph_vector_t *values,
                                   const igraph_vector_t *values_in,
                                   igraph_real_t *res,
                                   igraph_bool_t directed,
                                   igraph_bool_t normalized);
```

This function calculates the assortativity coefficient of a graph based on given values x_i for each vertex i . This type of assortativity coefficient equals the Pearson correlation of the values at the two ends of the edges.

The unnormalized covariance of values, computed when *normalized* is set to false, is defined as follows in a directed graph:

$$\text{cov}(x_{\text{out}}, x_{\text{in}}) = 1/m \sum_{ij} (A_{ij} - k^{\text{out}}_i k^{\text{in}}_j / m) x_i x_j,$$

where m denotes the number of edges, A_{ij} is the adjacency matrix, and k^{out} and k^{in} are the out- and in-degrees. x_{out} and x_{in} refer to the sets of vertex values at the start and end of the directed edges.

The normalized covariance, i.e. Pearson correlation, is obtained by dividing the previous expression by $\sqrt{\text{var}(x_{\text{out}})} \sqrt{\text{var}(x_{\text{in}})}$, where

$$\text{var}(x_{\text{out}}) = 1/m \sum_i k^{\text{out}}_i x_i^2 - (1/m \sum_i k^{\text{out}}_i x_i)^2$$

$$\text{var}(x_{\text{in}}) = 1/m \sum_j k^{\text{in}}_j x_j^2 - (1/m \sum_j k^{\text{in}}_j x_j)^2$$

Undirected graphs are effectively treated as directed graphs where all edges are reciprocal. Therefore, self-loops are effectively considered twice in undirected graphs.

References:

M. E. J. Newman: Mixing patterns in networks, Phys. Rev. E 67, 026126 (2003) <https://doi.org/10.1103/PhysRevE.67.026126>. See section III and equation (21) for the definition, and equation (26) for performing the calculation in directed graphs with the degrees as values.

M. E. J. Newman: Assortative mixing in networks, Phys. Rev. Lett. 89, 208701 (2002) <http://doi.org/10.1103/PhysRevLett.89.208701>. See equation (4) for performing the calculation in undirected graphs with the degrees as values.

For an educational overview of the concept of assortativity, see M. E. J. Newman, Networks: An Introduction, Oxford University Press (2010). <https://doi.org/10.1093/acprof:3Aoso/9780199206650.001.0001>.

Arguments:

- graph*: The input graph, it can be directed or undirected.
- values*: The vertex values, these can be arbitrary numeric values.
- values_in*: A second value vector to be used for the incoming edges when calculating assortativity for a directed graph. Supply NULL here if you want to use the same values for outgoing and incoming edges. This argument is ignored (with a warning) if it is not a null pointer and the undirected assortativity coefficient is being calculated.

res: Pointer to a real variable, the result is stored here.

directed: Boolean, whether to consider edge directions for directed graphs. It is ignored for undirected graphs.

normalized: Boolean, whether to compute the normalized covariance, i.e. Pearson correlation. Supply true here to compute the standard assortativity.

Returns:

Error code.

Time complexity: $O(|E|)$, linear in the number of edges of the graph.

See also:

`igraph_assortativity_nominal()` if you have discrete vertex categories instead of numeric labels, and `igraph_assortativity_degree()` for the special case of assortativity based on vertex degrees.

`igraph_assortativity_degree` — Assortativity of a graph based on vertex degree.

```
igraph_error_t igraph_assortativity_degree(const igraph_t *graph,
                                           igraph_real_t *res,
                                           igraph_bool_t directed);
```

Assortativity based on vertex degree, please see the discussion at the documentation of `igraph_assortativity()` for details. This function simply calls `igraph_assortativity()` with the degrees as the vertex values and normalization enabled. In the directed case, it uses out-degrees as out-values and in-degrees as in-values.

For regular graphs, i.e. graphs in which all vertices have the same degree, computing degree correlations is not meaningful, and this function returns NaN.

Arguments:

graph: The input graph, it can be directed or undirected.

res: Pointer to a real variable, the result is stored here.

directed: Boolean, whether to consider edge directions for directed graphs. This argument is ignored for undirected graphs. Supply true here to do the natural thing, i.e. use directed version of the measure for directed graphs and the undirected version for undirected graphs.

Returns:

Error code.

Time complexity: $O(|E|+|V|)$, $|E|$ is the number of edges, $|V|$ is the number of vertices.

See also:

`igraph_assortativity()` for the general function calculating assortativity for any kind of numeric vertex values.

Example **13.37.**
igraph_assortativity_degree.c

File **examples/simple/**

K-Cores and K-Trusses

igraph_coreness — Finding the coreness of the vertices in a network.

```
igraph_error_t igraph_coreness(const igraph_t *graph,  
                               igraph_vector_int_t *cores, igraph_neimode_t mode);
```

The k-core of a graph is a maximal subgraph in which each vertex has at least degree k. (Degree here means the degree in the subgraph of course.). The coreness of a vertex is the highest order of a k-core containing the vertex.

This function implements the algorithm presented in Vladimir Batagelj, Matjaz Zaversnik: An O(m) Algorithm for Cores Decomposition of Networks.

Arguments:

graph: The input graph.

cores: Pointer to an initialized vector, the result of the computation will be stored here. It will be resized as needed. For each vertex it contains the highest order of a core containing the vertex.

mode: For directed graph it specifies whether to calculate in-cores, out-cores or the undirected version. It is ignored for undirected graphs. Possible values: IGRAPH_ALL undirected version, IGRAPH_IN in-cores, IGRAPH_OUT out-cores.

Returns:

Error code.

Time complexity: $O(|E|)$, the number of edges.

igraph_trussness — Finding the "trussness" of the edges in a network.

```
igraph_error_t igraph_trussness(const igraph_t* graph, igraph_vector_int_t* trussness);
```

A k-truss is a subgraph in which every edge occurs in at least k-2 triangles in the subgraph. The trussness of an edge indicates the highest k-truss that the edge occurs in.

This function returns the highest k for each edge. If you are interested in a particular k-truss subgraph, you can subset the graph using to those eids which are $\geq k$ because each k-truss is a subgraph of a (k-1)-truss (thus to get all 4-trusses, take $k \geq 4$ because the 5-trusses, 6-trusses, etc need to be included).

The current implementation of this function iteratively decrements support of each edge using $O(|E|)$ space and $O(|E|^{1.5})$ time. The implementation does not support multigraphs; use `igraph_simplify()` to collapse edges before calling this function.

Arguments:

graph: The input graph. Loop edges are allowed; multigraphs are not.

truss: Pointer to initialized vector of truss values that will indicate the highest k-truss each edge occurs in. It will be resized as needed.

Returns:

Error code.

Time complexity: It should be $O(|E|^{1.5})$. See Algorithm 2 in: Wang, Jia, and James Cheng. "Truss decomposition in massive networks." Proceedings of the VLDB Endowment 5.9 (2012): 812-823.

Topological sorting, directed acyclic graphs

igraph_is_dag — Checks whether a graph is a directed acyclic graph (DAG).

```
igraph_error_t igraph_is_dag(const igraph_t* graph, igraph_bool_t *res);
```

A directed acyclic graph (DAG) is a directed graph with no cycles.

The return value of this function is cached in the graph itself; calling the function multiple times with no modifications to the graph in between will return a cached value in $O(1)$ time.

Arguments:

graph: The input graph.

res: Pointer to a boolean constant, the result is stored here.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, where $|V|$ and $|E|$ are the number of vertices and edges in the original input graph.

See also:

`igraph_topological_sorting()` to get a possible topological sorting of a DAG.

igraph_topological_sorting — Calculate a possible topological sorting of the graph.

```
igraph_error_t igraph_topological_sorting(  
    const igraph_t* graph, igraph_vector_int_t *res, igraph_neimode_t mode)
```

A topological sorting of a directed acyclic graph (DAG) is a linear ordering of its vertices where each vertex comes before all nodes to which it has edges. Every DAG has at least one topological sort, and may have many. This function returns one possible topological sort among them. If the graph contains any cycles that are not self-loops, an error is raised.

Arguments:

graph: The input graph.

res: Pointer to a vector, the result will be stored here. It will be resized if needed.

mode: Specifies how to use the direction of the edges. For `IGRAPH_OUT`, the sorting order ensures that each vertex comes before all vertices to which it has edges, so vertices with no incoming edges go first. For `IGRAPH_IN`, it is quite the opposite: each vertex comes before all vertices from which it receives edges. Vertices with no outgoing edges go first.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, where $|V|$ and $|E|$ are the number of vertices and edges in the original input graph.

See also:

`igraph_is_dag()` if you are only interested in whether a given graph is a DAG or not, or `igraph_feedback_arc_set()` to find a set of edges whose removal makes the graph acyclic.

Example	13.38.	File	examples/simple/
igraph_topological_sorting.c			

igraph_feedback_arc_set — Calculates a feedback arc set of the graph using different

```
igraph_error_t igraph_feedback_arc_set(const igraph_t *graph, igraph_vector_int_t *res,
                                       const igraph_vector_t *weights, igraph_fas_algorithm_t algorithm);
```

algorithms.

A feedback arc set is a set of edges whose removal makes the graph acyclic. We are usually interested in *minimum* feedback arc sets, i.e. sets of edges whose total weight is minimal among all the feedback arc sets.

For undirected graphs, the problem is simple: one has to find a maximum weight spanning tree and then remove all the edges not in the spanning tree. For directed graphs, this is an NP-hard problem, and various heuristics are usually used to find an approximate solution to the problem. This function implements a few of these heuristics.

Arguments:

graph: The graph object.

result: An initialized vector, the result will be returned here.

weights: Weight vector or NULL if no weights are specified.

<i>algo</i> :	The algorithm to use to solve the problem if the graph is directed. Possible values:	
	IGRAPH_FAS_EXACT_IP	Finds a <i>minimum</i> feedback arc set using integer programming (IP). The complexity of this algorithm is exponential of course.
	IGRAPH_FAS_APPROX_EADES	Finds a feedback arc set using the heuristic of Eades, Lin and Smyth (1993). This is guaranteed to be smaller than $ E /2 - V /6$, and it is linear in the number of edges (i.e. $O(E)$). For more details, see Eades P, Lin X and Smyth WF: A fast and effective heuristic for the feedback arc set problem. In: Proc Inf Process Lett 319-323, 1993.

Returns:

Error code: IGRAPH_EINVAL if an unknown method was specified or the weight vector is invalid.

Example 13.39. File `examples/simple/igraph_feedback_arc_set.c`

Example 13.40. File `examples/simple/igraph_feedback_arc_set_ip.c`

Time complexity: depends on *algo*, see the time complexities there.

Maximum cardinality search and chordal graphs

`igraph_maximum_cardinality_search` — Maximum cardinality search.

```
igraph_error_t igraph_maximum_cardinality_search(const igraph_t *graph,
                                                igraph_vector_int_t *alpha,
                                                igraph_vector_int_t *alpham1);
```

This function implements the maximum cardinality search algorithm. It computes a rank *alpha* for each vertex, such that visiting vertices in decreasing rank order corresponds to always choosing the vertex with the most already visited neighbors as the next one to visit.

Maximum cardinality search is useful in deciding the chordality of a graph. A graph is chordal if and only if any two neighbors of a vertex which are higher in rank than it are connected to each other.

References:

Robert E Tarjan and Mihalis Yannakakis: Simple linear-time algorithms to test chordality of graphs, test acyclicity of hypergraphs, and selectively reduce acyclic hypergraphs. SIAM Journal of Computation 13, 566--579, 1984. <https://doi.org/10.1137/0213035>

Arguments:

graph: The input graph. Edge directions will be ignored.

alpha: Pointer to an initialized vector, the result is stored here. It will be resized, as needed. Upon return it contains the rank of the each vertex in the range 0 to $n - 1$, where n is the number of vertices.

alpham1: Pointer to an initialized vector or a NULL pointer. If not NULL, then the inverse of *alpha* is stored here. In other words, the elements of *alpham1* are vertex IDs in reverse maximum cardinality search order.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in terms of the number of vertices and edges.

See also:

`igraph_is_chordal()`.

igraph_is_chordal — Decides whether a graph is chordal.

```
igraph_error_t igraph_is_chordal(const igraph_t *graph,
                                const igraph_vector_int_t *alpha,
                                const igraph_vector_int_t *alpham1,
                                igraph_bool_t *chordal,
                                igraph_vector_int_t *fill_in,
                                igraph_t *newgraph);
```

A graph is chordal if each of its cycles of four or more nodes has a chord, i.e. an edge joining two nodes that are not adjacent in the cycle. An equivalent definition is that any chordless cycles have at most three nodes. If either *alpha* or *alpham1* is given, then the other is calculated by taking simply the inverse. If neither are given, then `igraph_maximum_cardinality_search()` is called to calculate them.

Arguments:

graph: The input graph. Edge directions will be ignored.

alpha: Either an alpha vector coming from `igraph_maximum_cardinality_search()` (on the same graph), or a NULL pointer.

alpham1: Either an inverse alpha vector coming from `igraph_maximum_cardinality_search()` (on the same graph) or a NULL pointer.

chordal: Pointer to a boolean. If not NULL the result is stored here.

fill_in: Pointer to an initialized vector, or a NULL pointer. If not a NULL pointer, then the fill-in, also called the chordal completion of the graph is stored here. The chordal completion is a set of edges that are needed to make the graph chordal. The vector is resized as needed. Note that the chordal completion returned by this function may not be minimal, i.e. some of the returned fill-in edges may not be needed to make the graph chordal.

newgraph: Pointer to an uninitialized graph, or a NULL pointer. If not a null pointer, then a new triangulated graph is created here. This essentially means adding the fill-in edges to the original graph.

Returns:

Error code.

Time complexity: $O(n)$.

See also:

`igraph_maximum_cardinality_search()`.

Matchings

`igraph_is_matching` — Checks whether the given matching is valid for the given graph.

```
igraph_error_t igraph_is_matching(const igraph_t* graph,
                                   const igraph_vector_bool_t* types, const igraph_vector_int_t* matching,
                                   igraph_bool_t* result);
```

This function checks a matching vector and verifies whether its length matches the number of vertices in the given graph, its values are between -1 (inclusive) and the number of vertices (exclusive), and whether there exists a corresponding edge in the graph for every matched vertex pair. For bipartite graphs, it also verifies whether the matched vertices are in different parts of the graph.

Arguments:

- graph*: The input graph. It can be directed but the edge directions will be ignored.
- types*: If the graph is bipartite and you are interested in bipartite matchings only, pass the vertex types here. If the graph is non-bipartite, simply pass NULL.
- matching*: The matching itself. It must be a vector where element *i* contains the ID of the vertex that vertex *i* is matched to, or -1 if vertex *i* is unmatched.
- result*: Pointer to a boolean variable, the result will be returned here.

See also:

`igraph_is_maximal_matching()` if you are also interested in whether the matching is maximal (i.e. non-extendable).

Time complexity: $O(|V|+|E|)$ where $|V|$ is the number of vertices and $|E|$ is the number of edges.

Example **13.41.** **File** **`examples/simple/igraph_maximum_bipartite_matching.c`**

`igraph_is_maximal_matching` — Checks whether a matching in a graph is maximal.

```
igraph_error_t igraph_is_maximal_matching(const igraph_t* graph,
```

```
const igraph_vector_bool_t* types, const igraph_
igraph_bool_t* result);
```

A matching is maximal if and only if there exists no unmatched vertex in a graph such that one of its neighbors is also unmatched.

Arguments:

graph: The input graph. It can be directed but the edge directions will be ignored.

types: If the graph is bipartite and you are interested in bipartite matchings only, pass the vertex types here. If the graph is non-bipartite, simply pass NULL.

matching: The matching itself. It must be a vector where element *i* contains the ID of the vertex that vertex *i* is matched to, or -1 if vertex *i* is unmatched.

result: Pointer to a boolean variable, the result will be returned here.

See also:

`igraph_is_matching()` if you are only interested in whether a matching vector is valid for a given graph.

Time complexity: $O(|V|+|E|)$ where $|V|$ is the number of vertices and $|E|$ is the number of edges.

Example **13.42.** **File** **examples/simple/**
igraph_maximum_bipartite_matching.c

igraph_maximum_bipartite_matching — Calculates a maximum matching in a bipartite graph.

```
igraph_error_t igraph_maximum_bipartite_matching(const igraph_t* graph,
                                                  const igraph_vector_bool_t* types, igraph_
                                                  igraph_real_t* matching_weight, igraph_ve
                                                  const igraph_vector_t* weights, igraph_re
```

A matching in a bipartite graph is a partial assignment of vertices of the first kind to vertices of the second kind such that each vertex of the first kind is matched to at most one vertex of the second kind and vice versa, and matched vertices must be connected by an edge in the graph. The size (or cardinality) of a matching is the number of edges. A matching is a maximum matching if there exists no other matching with larger cardinality. For weighted graphs, a maximum matching is a matching whose edges have the largest possible total weight among all possible matchings.

Maximum matchings in bipartite graphs are found by the push-relabel algorithm with greedy initialization and a global relabeling after every $n/2$ steps where n is the number of vertices in the graph.

References: Cherkassky BV, Goldberg AV, Martin P, Setubal JC and Stolfi J: Augment or push: A computational study of bipartite matching and unit-capacity flow algorithms. ACM Journal of Experimental Algorithmics 3, 1998.

Kaya K, Langguth J, Manne F and Ucar B: Experiments on push-relabel-based maximum cardinality matching algorithms for bipartite graphs. Technical Report TR/PA/11/33 of the Centre Europeen de Recherche et de Formation Avancee en Calcul Scientifique, 2011.

Arguments:

<i>graph</i> :	The input graph. It can be directed but the edge directions will be ignored.
<i>types</i> :	Boolean vector giving the vertex types of the graph.
<i>matching_size</i> :	The size of the matching (i.e. the number of matched vertex pairs will be returned here). It may be NULL if you don't need this.
<i>matching_weight</i> :	The weight of the matching if the edges are weighted, or the size of the matching again if the edges are unweighted. It may be NULL if you don't need this.
<i>matching</i> :	The matching itself. It must be a vector where element <i>i</i> contains the ID of the vertex that vertex <i>i</i> is matched to, or -1 if vertex <i>i</i> is unmatched.
<i>weights</i> :	A null pointer (=no edge weights), or a vector giving the weights of the edges. Note that the algorithm is stable only for integer weights.
<i>eps</i> :	A small real number used in equality tests in the weighted bipartite matching algorithm. Two real numbers are considered equal in the algorithm if their difference is smaller than <i>eps</i> . This is required to avoid the accumulation of numerical errors. It is advised to pass a value derived from the DBL_EPSILON constant in <code>float.h</code> here. If you are running the algorithm with no <i>weights</i> vector, this argument is ignored.

Returns:

Error code.

Time complexity: $O(\sqrt{|V|} |E|)$ for unweighted graphs (according to the technical report referenced above), $O(|V||E|)$ for weighted graphs.

Example	13.43.	File	examples/simple/
igraph_maximum_bipartite_matching.c			

Unfolding a graph into a tree

igraph_unfold_tree — Unfolding a graph into a tree, by possibly multiplying its vertices.

```
igraph_error_t igraph_unfold_tree(const igraph_t *graph, igraph_t *tree,
                                   igraph_neimode_t mode, const igraph_vector_int_t *roots,
                                   igraph_vector_int_t *vertex_index);
```

A graph is converted into a tree (or forest, if it is unconnected), by performing a breadth-first search on it, and replicating vertices that were found a second, third, etc. time.

Arguments:

<i>graph</i> :	The input graph, it can be either directed or undirected.
<i>tree</i> :	Pointer to an uninitialized graph object, the result is stored here.
<i>mode</i> :	For directed graphs; whether to follow paths along edge directions (IGRAPH_OUT), or the opposite (IGRAPH_IN), or ignore edge directions completely (IGRAPH_ALL). It is ignored for undirected graphs.

roots: A numeric vector giving the root vertex, or vertices (if the graph is not connected), to start from.

vertex_index: Pointer to an initialized vector, or a null pointer. If not a null pointer, then a mapping from the vertices in the new graph to the ones in the original is created here.

Returns:

Error code.

Time complexity: $O(n+m)$, linear in the number vertices and edges.

Other operations

igraph_density — Calculate the density of a graph.

```
igraph_error_t igraph_density(const igraph_t *graph, igraph_real_t *res,  
                              igraph_bool_t loops);
```

The density of a graph is simply the ratio of the actual number of its edges and the largest possible number of edges it could have. The maximum number of edges depends on interpretation: are vertices allowed to have a connected to themselves? This is controlled by the *loops* parameter.

Note that density is ill-defined for graphs which have multiple edges between some pairs of vertices. Consider calling `igraph_simplify()` on such graphs.

Arguments:

graph: The input graph object.

res: Pointer to a real number, the result will be stored here.

loops: Logical constant, whether to include self-loops in the calculation. If this constant is `true` then loop edges are thought to be possible in the graph (this does not necessarily mean that the graph really contains any loops). If this is `false` then the result is only correct if the graph does not contain loops.

Returns:

Error code.

Time complexity: $O(1)$.

igraph_reciprocity — Calculates the reciprocity of a directed graph.

```
igraph_error_t igraph_reciprocity(const igraph_t *graph, igraph_real_t *res,  
                                  igraph_bool_t ignore_loops,  
                                  igraph_reciprocity_t mode);
```

The measure of reciprocity defines the proportion of mutual connections, in a directed graph. It is most commonly defined as the probability that the opposite counterpart of a directed edge is also included in the graph. In adjacency matrix notation: $\sum(i, j, (A \cdot A')_{ij}) / \sum(i, j, A_{ij})$, where $A \cdot A'$ is the element-wise product of matrix A and its transpose. This measure is calculated if the *mode* argument is `IGRAPH_RECIPROCITY_DEFAULT`.

Prior to igraph version 0.6, another measure was implemented, defined as the probability of mutual connection between a vertex pair if we know that there is a (possibly non-mutual) connection between them. In other words, (unordered) vertex pairs are classified into three groups: (1) disconnected, (2) non-reciprocally connected, (3) reciprocally connected. The result is the size of group (3), divided by the sum of group sizes (2)+(3). This measure is calculated if *mode* is `IGRAPH_RECIPROCITY_RATIO`.

Arguments:

graph: The graph object.

res: Pointer to an `igraph_real_t` which will contain the result.

ignore_loops: Whether to ignore loop edges.

mode: Type of reciprocity to calculate, possible values are `IGRAPH_RECIPROCITY_DEFAULT` and `IGRAPH_RECIPROCITY_RATIO`, please see their description above.

Returns:

Error code: `IGRAPH_EINVAL`: graph has no edges `IGRAPH_ENOMEM`: not enough memory for temporary data.

Time complexity: $O(|V|+|E|)$, $|V|$ is the number of vertices, $|E|$ is the number of edges.

Example 13.44. File `examples/simple/igraph_reciprocity.c`

igraph_diversity — Structural diversity index of the vertices

```
igraph_error_t igraph_diversity(const igraph_t *graph, const igraph_vector_t *w,
                                igraph_vector_t *res, const igraph_vs_t vids);
```

This measure was defined in Nathan Eagle, Michael Macy and Rob Claxton: Network Diversity and Economic Development, Science 328, 1029--1031, 2010.

It is simply the (normalized) Shannon entropy of the incident edges' weights. $D(i)=H(i)/\log(k[i])$, and $H(i) = -\sum(p[i,j] \log(p[i,j])), j=1..k[i])$, where $p[i,j]=w[i,j]/\sum(w[i,l], l=1..k[i])$, $k[i]$ is the (total) degree of vertex i , and $w[i,j]$ is the weight of the edge(s) between vertex i and j . The diversity of isolated vertices will be NaN (not-a-number), while that of vertices with a single connection will be zero.

The measure works only if the graph is undirected and has no multiple edges. If the graph has multiple edges, simplify it first using `igraph_simplify()`. If the graph is directed, convert it into an undirected graph with `igraph_to_undirected()`.

Arguments:

graph: The undirected input graph.

weights: The edge weights, in the order of the edge IDs, must have appropriate length. Weights must be non-negative.

res: An initialized vector, the results are stored here.

vids: Vertex selector that specifies the vertices which to calculate the measure.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear.

igraph_is_mutual — Check whether some edges of a directed graph are mutual.

```
igraph_error_t igraph_is_mutual(const igraph_t *graph, igraph_vector_bool_t *res)
```

An (A,B) non-loop directed edge is mutual if the graph contains the (B,A) edge too. Whether directed self-loops are considered mutual is controlled by the *loops* parameter.

An undirected graph only has mutual edges, by definition.

Edge multiplicity is not considered here, e.g. if there are two (A,B) edges and one (B,A) edge, then all three are considered to be mutual.

Arguments:

graph: The input graph.

res: Pointer to an initialized vector, the result is stored here.

es: The sequence of edges to check. Supply `igraph_ess_all()` to check all edges.

loops: Boolean, whether to consider directed self-loops to be mutual.

Returns:

Error code.

Time complexity: $O(n \log(d))$, n is the number of edges supplied, d is the maximum in-degree of the vertices that are targets of the supplied edges. An upper limit of the time complexity is $O(n \log(|E|))$, $|E|$ is the number of edges in the graph.

igraph_avg_nearest_neighbor_degree — Average neighbor degree.

```
igraph_error_t igraph_avg_nearest_neighbor_degree(const igraph_t *graph,
                                                    igraph_vs_t vids,
                                                    igraph_neimode_t mode,
                                                    igraph_neimode_t neighbor_degree_mode,
                                                    igraph_vector_t *knn,
                                                    igraph_vector_t *knnk,
```

```
const igraph_vector_t *weights);
```

Calculates the average degree of the neighbors for each vertex (*knn*), and optionally, the same quantity as a function of the vertex degree (*knnk*).

For isolated vertices *knn* is set to NaN. The same is done in *knnk* for vertex degrees that don't appear in the graph.

The weighted version computes a weighted average of the neighbor degrees as $k_{nn,u} = 1/s_u \sum_v w_{uv} k_v$, where $s_u = \sum_v w_{uv}$ is the sum of the incident edge weights of vertex *u*, i.e. its strength. The sum runs over the neighbors *v* of vertex *u* as indicated by *mode*. w_{uv} denotes the weighted adjacency matrix and k_v is the neighbors' degree, specified by *neighbor_degree_mode*.

Reference: A. Barrat, M. Barthélemy, R. Pastor-Satorras, and A. Vespignani, The architecture of complex weighted networks, Proc. Natl. Acad. Sci. USA 101, 3747 (2004). <https://dx.doi.org/10.1073/pnas.0400087101>

Arguments:

<i>graph</i> :	The input graph. It may be directed.
<i>vids</i> :	The vertices for which the calculation is performed.
<i>mode</i> :	The type of neighbors to consider in directed graphs. IGRAPH_OUT considers out-neighbors, IGRAPH_IN in-neighbors and IGRAPH_ALL ignores edge directions.
<i>neighbor_degree_mode</i> :	The type of degree to average in directed graphs. IGRAPH_OUT averages out-degrees, IGRAPH_IN averages in-degrees and IGRAPH_ALL ignores edge directions for the degree calculation.
<i>vids</i> :	The vertices for which the calculation is performed.
<i>knn</i> :	Pointer to an initialized vector, the result will be stored here. It will be resized as needed. Supply a NULL pointer here, if you only want to calculate <i>knnk</i> .
<i>knnk</i> :	Pointer to an initialized vector, the average neighbor degree as a function of the vertex degree is stored here. The first (zeroth) element is for degree one vertices, etc. Supply a NULL pointer here if you don't want to calculate this.
<i>weights</i> :	Optional edge weights. Supply a null pointer here for the non-weighted version.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

Example 13.45. File `examples/simple/igraph_knn.c`

igraph_get_adjacency — Returns the adjacency matrix of a graph

```
#define WEIGHT_OF(eid) (weights ? VECTOR(*weights)[eid] : 1)

igraph_error_t igraph_get_adjacency(
    const igraph_t *graph, igraph_matrix_t *res, igraph_get_adjacency_t type,
    const igraph_vector_t *weights, igraph_loops_t loops
);
```

The result is an adjacency matrix. Entry i, j of the matrix contains the number of edges connecting vertex i to vertex j in the unweighted case, or the total weight of edges connecting vertex i to vertex j in the weighted case.

Arguments:

- graph*: Pointer to the graph to convert
- res*: Pointer to an initialized matrix object, it will be resized if needed.
- type*: Constant specifying the type of the adjacency matrix to create for undirected graphs. It is ignored for directed graphs. Possible values:
- | | |
|----------------------------|--|
| IGRAPH_GET_ADJACENCY_UPPER | the upper right triangle of the matrix is used. |
| IGRAPH_GET_ADJACENCY_LOWER | the lower left triangle of the matrix is used. |
| IGRAPH_GET_ADJACENCY_BOTH | the whole matrix is used, a symmetric matrix is returned if the graph is undirected. |
- weights*: An optional vector containing the weight of each edge in the graph. Supply a null pointer here to make all edges have the same weight of 1.
- loops*: Constant specifying how loop edges should be handled. Possible values:
- | | |
|--------------------|---|
| IGRAPH_NO_LOOPS | loop edges are ignored and the diagonal of the matrix will contain zeros only |
| IGRAPH_LOOPS_ONCE | loop edges are counted once, i.e. a vertex with a single unweighted loop edge will have 1 in the corresponding diagonal entry |
| IGRAPH_LOOPS_TWICE | loop edges are counted twice in <i>undirected</i> graphs, i.e. a vertex with a single unweighted loop edge in an undirected graph will have 2 in the corresponding diagonal entry. Loop edges in directed graphs are still counted as 1. Essentially, this means that the function is counting the incident edge <i>stems</i> , which makes more sense when using the adjacency matrix in linear algebra. |

Returns:

Error code: IGRAPH_EINVAL invalid type argument.

See also:

`igraph_get_adjacency_sparse()` if you want a sparse matrix representation

Time complexity: $O(|V||V|)$, $|V|$ is the number of vertices in the graph.

igraph_get_adjacency_sparse — Returns the adjacency matrix of a graph in a sparse matrix format.

```
igraph_error_t igraph_get_adjacency_sparse(  
    const igraph_t *graph, igraph_sparsemat_t *res, igraph_get_adjacency_t type  
    const igraph_vector_t *weights, igraph_loops_t loops  
);
```

Arguments:

graph: The input graph.

res: Pointer to an *initialized* sparse matrix. The result will be stored here. The matrix will be resized as needed.

type: Constant specifying the type of the adjacency matrix to create for undirected graphs. It is ignored for directed graphs. Possible values:

IGRAPH_GET_ADJACENCY_UPPER — the upper right triangle of the matrix is used.

IGRAPH_GET_ADJACENCY_LOWER — the lower left triangle of the matrix is used.

IGRAPH_GET_ADJACENCY_BOTH — the whole matrix is used, a symmetric matrix is returned if the graph is undirected.

Returns:

Error code: IGRAPH_EINVAL invalid type argument.

See also:

igraph_get_adjacency(), the dense version of this function.

Time complexity: TODO.

igraph_get_stochastic — Stochastic adjacency matrix of a graph

```
igraph_error_t igraph_get_stochastic(  
    const igraph_t *graph, igraph_matrix_t *res, igraph_bool_t column_wise,  
    const igraph_vector_t *weights  
);
```

Stochastic matrix of a graph. The stochastic matrix of a graph is its adjacency matrix, normalized row-wise or column-wise, such that the sum of each row (or column) is one.

Arguments:

graph: The input graph.

res: Pointer to an initialized matrix, the result is stored here. It will be resized as needed.

column_wise: Whether to normalize column-wise.

Returns:

Error code.

Time complexity: $O(|V||V|)$, $|V|$ is the number of vertices in the graph.

See also:

`igraph_get_stochastic_sparse()`, the sparse version of this function.

`igraph_get_stochastic_sparse` — Stochastic adjacency matrix of a graph

```
igraph_error_t igraph_get_stochastic_sparse(  
    const igraph_t *graph, igraph_sparsemat_t *res, igraph_bool_t column_wise,  
    const igraph_vector_t *weights  
);
```

Stochastic matrix of a graph. The stochastic matrix of a graph is its adjacency matrix, normalized row-wise or column-wise, such that the sum of each row (or column) is one.

Arguments:

graph: The input graph.

res: Pointer to an *initialized* sparse matrix, the result is stored here. The matrix will be resized as needed.

column_wise: Whether to normalize column-wise.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

See also:

`igraph_get_stochastic()`, the dense version of this function.

`igraph_get_edgelist` — Returns the list of edges in a graph

```
igraph_error_t igraph_get_edgelist(const igraph_t *graph, igraph_vector_int_t *res);
```

The order of the edges is given by the edge IDs.

Arguments:

graph: Pointer to the graph object

res: Pointer to an initialized vector object, it will be resized.

bycol: Logical, if true, the edges will be returned columnwise, e.g. the first edge is `res[0] -> res[|E|]`, the second is `res[1] -> res[|E|+1]`, etc.

Returns:

Error code.

See also:

`igraph_edges()` to return the result only for some edge IDs.

Time complexity: $O(|E|)$, the number of edges in the graph.

igraph_is_acyclic — Checks whether a graph is acyclic or not.

```
igraph_error_t igraph_is_acyclic(const igraph_t *graph, igraph_bool_t *res);
```

This function checks whether a graph is acyclic or not.

Arguments:

graph: The input graph.

res: Pointer to a boolean constant, the result is stored here.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, where $|V|$ and $|E|$ are the number of vertices and edges in the original input graph.

Deprecated functions

igraph_shortest_paths — Length of the shortest paths between vertices.

```
igraph_error_t igraph_shortest_paths(const igraph_t *graph,
                                     igraph_matrix_t *res,
                                     const igraph_vs_t from,
                                     const igraph_vs_t to,
                                     igraph_neimode_t mode);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_distances()` instead.

igraph_shortest_paths_dijkstra — Weighted shortest path lengths between vertices (deprecated).

```
igraph_error_t igraph_shortest_paths_dijkstra(const igraph_t *graph,
                                              igraph_matrix_t *res,
                                              const igraph_vs_t from,
                                              const igraph_vs_t to,
                                              const igraph_vector_t *weights,
                                              igraph_neimode_t mode);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_distances_dijkstra()` instead.

igraph_shortest_paths_bellman_ford — Weighted shortest path lengths between vertices, allowing negative weights (deprecated).

```
igraph_error_t igraph_shortest_paths_bellman_ford(const igraph_t *graph,
                                                  igraph_matrix_t *res,
                                                  const igraph_vs_t from,
                                                  const igraph_vs_t to,
                                                  const igraph_vector_t *weights,
                                                  igraph_neimode_t mode);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_distances_bellman_ford()` instead.

igraph_shortest_paths_johnson — Weighted shortest path lengths between vertices, using Johnson's algorithm (deprecated).

```
igraph_error_t igraph_shortest_paths_johnson(const igraph_t *graph,
                                              igraph_matrix_t *res,
                                              const igraph_vs_t from,
```

```
const igraph_vs_t to,  
const igraph_vector_t *weights);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_distances_johnson()` instead.

igraph_get_stochastic_sparsemat — Stochastic adjacency matrix of a graph (deprecated).

```
igraph_error_t igraph_get_stochastic_sparsemat(const igraph_t *graph,  
                                              igraph_sparsemat_t *res,  
                                              igraph_bool_t column_wise);
```

This function is deprecated in favour of `igraph_get_stochastic_sparse()`, but does not work in an identical way. This function takes an *uninitialized* `igraph_sparsemat_t` while `igraph_get_stochastic_sparse()` takes an already initialized one.

Arguments:

graph: The input graph.

res: Pointer to an *uninitialized* sparse matrix, the result is stored here. The matrix will be resized as needed.

column_wise: Whether to normalize column-wise. For undirected graphs this argument does not have any effect.

Returns:

Error code.

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_get_stochastic_sparse()` instead.

igraph_get_sparsemat — Converts an igraph graph to a sparse matrix (deprecated).

```
igraph_error_t igraph_get_sparsemat(const igraph_t *graph, igraph_sparsemat_t *
```

If the graph is undirected, then a symmetric matrix is created.

This function is deprecated in favour of `igraph_get_adjacency_sparse()`, but does not work in an identical way. This function takes an *uninitialized* `igraph_sparsemat_t` while `igraph_get_adjacency_sparse()` takes an already initialized one.

Arguments:

graph: The input graph.

res: Pointer to an *uninitialized* sparse matrix. The result will be stored here.

Returns:

Error code.

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_get_adjacency_sparse()` instead.

igraph_laplacian — Returns the Laplacian matrix of a graph (deprecated).

```
igraph_error_t igraph_laplacian(  
    const igraph_t *graph, igraph_matrix_t *res, igraph_sparsemat_t *sparseres,  
    igraph_bool_t normalized, const igraph_vector_t *weights  
);
```

This function produces the Laplacian matrix of a graph in either dense or sparse format. When *normalized* is set to true, the type of normalization used depends on the directedness of the graph: symmetric normalization is used for undirected graphs and left stochastic normalization for directed graphs.

Arguments:

graph: Pointer to the graph to convert.

res: Pointer to an initialized matrix object or NULL. The dense matrix result will be stored here.

sparseres: Pointer to an initialized sparse matrix object or NULL. The sparse matrix result will be stored here.

mode: Controls whether to use out- or in-degrees in directed graphs. If set to `IGRAPH_ALL`, edge directions will be ignored.

normalized: Boolean, whether to normalize the result.

weights: An optional vector containing non-negative edge weights, to calculate the weighted Laplacian matrix. Set it to a null pointer to calculate the unweighted Laplacian.

Returns:

Error code.

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_get_laplacian()` instead.

Chapter 14. Graph cycles

Eulerian cycles and paths

These functions calculate whether an Eulerian path or cycle exists and if so, can find them.

igraph_is_eulerian — Checks whether an Eulerian path or cycle exists

```
igraph_error_t igraph_is_eulerian(const igraph_t *graph, igraph_bool_t *has_path,
```

An Eulerian path traverses each edge of the graph precisely once. A closed Eulerian path is referred to as an Eulerian cycle.

Arguments:

graph: The graph object.

has_path: Pointer to a Boolean, will be set to true if an Eulerian path exists.

has_cycle: Pointer to a Boolean, will be set to true if an Eulerian cycle exists.

Returns:

Error code: IGRAPH_ENOMEM, not enough memory for temporary data.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

igraph_eulerian_cycle — Finds an Eulerian cycle

```
igraph_error_t igraph_eulerian_cycle(const igraph_t *graph, igraph_vector_int_t
```

Finds an Eulerian cycle, if it exists. An Eulerian cycle is a closed path that traverses each edge precisely once.

This function uses Hierholzer's algorithm.

Arguments:

graph: The graph object.

edge_res: Pointer to an initialised vector. The indices of edges belonging to the cycle will be stored here. May be NULL if it is not needed by the caller.

vertex_res: Pointer to an initialised vector. The indices of vertices belonging to the cycle will be stored here. May be NULL if it is not needed by the caller.

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for temporary data.

IGRAPH_EINVVID graph does not have an Eulerian cycle.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

igraph_eulerian_path — Finds an Eulerian path

```
igraph_error_t igraph_eulerian_path(const igraph_t *graph, igraph_vector_int_t
```

Finds an Eulerian path, if it exists. An Eulerian path traverses each edge precisely once.

This function uses Hierholzer's algorithm.

Arguments:

graph: The graph object.

edge_res: Pointer to an initialised vector. The indices of edges belonging to the path will be stored here. May be NULL if it is not needed by the caller.

vertex_res: Pointer to an initialised vector. The indices of vertices belonging to the path will be stored here. May be NULL if it is not needed by the caller.

Returns:

Error code:

IGRAPH_ENOMEM not enough memory for temporary data.

IGRAPH_EINVVID graph does not have an Eulerian path.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

Chapter 15. Graph visitors

Breadth-first search

`igraph_bfs` — Breadth-first search

```
igraph_error_t igraph_bfs(const igraph_t *graph,
                          igraph_integer_t root, const igraph_vector_int_t *roots,
                          igraph_neimode_t mode, igraph_bool_t unreachable,
                          const igraph_vector_int_t *restricted,
                          igraph_vector_int_t *order, igraph_vector_int_t *rank,
                          igraph_vector_int_t *parents,
                          igraph_vector_int_t *pred, igraph_vector_int_t *succ,
                          igraph_vector_int_t *dist, igraph_bfshandler_t *callback,
                          void *extra);
```

A simple breadth-first search, with a lot of different results and the possibility to call a callback whenever a vertex is visited. It is allowed to supply null pointers as the output arguments the user is not interested in, in this case they will be ignored.

If not all vertices can be reached from the supplied root vertex, then additional root vertices will be used, in the order of their vertex IDs.

Consider using `igraph_bfs_simple` instead if you set most of the output arguments provided by this function to a null pointer.

Arguments:

<i>graph</i> :	The input graph.
<i>root</i> :	The id of the root vertex. It is ignored if the <i>roots</i> argument is not a null pointer.
<i>roots</i> :	Pointer to an initialized vector, or a null pointer. If not a null pointer, then it is a vector containing root vertices to start the BFS from. The vertices are considered in the order they appear. If a root vertex was already found while searching from another one, then no search is conducted from it.
<i>mode</i> :	For directed graphs, it defines which edges to follow. <code>IGRAPH_OUT</code> means following the direction of the edges, <code>IGRAPH_IN</code> means the opposite, and <code>IGRAPH_ALL</code> ignores the direction of the edges. This parameter is ignored for undirected graphs.
<i>unreachable</i> :	Logical scalar, whether the search should visit the vertices that are unreachable from the given root node(s). If true, then additional searches are performed until all vertices are visited.
<i>restricted</i> :	If not a null pointer, then it must be a pointer to a vector containing vertex IDs. The BFS is carried out only on these vertices.
<i>order</i> :	If not null pointer, then the vertex IDs of the graph are stored here, in the same order as they were visited.
<i>rank</i> :	If not a null pointer, then the rank of each vertex is stored here.
<i>parents</i> :	If not a null pointer, then the id of the parent of each vertex is stored here. When a vertex was not visited during the traversal, -2 will be stored as the ID of its parent.

When a vertex was visited during the traversal and it was one of the roots of the search trees, -1 will be stored as the ID of its parent.

pred: If not a null pointer, then the id of vertex that was visited before the current one is stored here. If there is no such vertex (the current vertex is the root of a search tree), then -1 is stored as the predecessor of the vertex. If the vertex was not visited at all, then -2 is stored for the predecessor of the vertex.

succ: If not a null pointer, then the id of the vertex that was visited after the current one is stored here. If there is no such vertex (the current one is the last in a search tree), then -1 is stored as the successor of the vertex. If the vertex was not visited at all, then -2 is stored for the successor of the vertex.

dist: If not a null pointer, then the distance from the root of the current search tree is stored here for each vertex. If a vertex was not reached during the traversal, its distance will be -1 in this vector.

callback: If not null, then it should be a pointer to a function of type `igraph_bfs_handler_t`. This function will be called, whenever a new vertex is visited.

extra: Extra argument to pass to the callback function.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

Example 15.1. File `examples/simple/igraph_bfs.c`

Example 15.2. File `examples/simple/igraph_bfs_callback.c`

igraph_bfs_simple — Breadth-first search, single-source version

```
igraph_error_t igraph_bfs_simple(  
    const igraph_t *graph, igraph_integer_t root, igraph_neimode_t mode,  
    igraph_vector_int_t *order, igraph_vector_int_t *layers,  
    igraph_vector_int_t *parents  
);
```

An alternative breadth-first search implementation to cater for the simpler use-cases when only a single breadth-first search has to be conducted from a source node and most of the output arguments from `igraph_bfs` are not needed. It is allowed to supply null pointers as the output arguments the user is not interested in, in this case they will be ignored.

Arguments:

graph: The input graph.

root: The id of the root vertex.

mode: For directed graphs, it defines which edges to follow. `IGRAPH_OUT` means following the direction of the edges, `IGRAPH_IN` means the opposite, and `IGRAPH_ALL` ignores the direction of the edges. This parameter is ignored for undirected graphs.

- order*: If not a null pointer, then an initialized vector must be passed here. The IDs of the vertices visited during the traversal will be stored here, in the same order as they were visited.
- layers*: If not a null pointer, then an initialized vector must be passed here. The *i*-th element of the vector will contain the index into *order* where the vertices that are at distance *i* from the root are stored. In other words, if you are interested in the vertices that are at distance *i* from the root, you need to look in the *order* vector from *layers*[*i*] to *layers*[*i*+1].
- parents*: If not a null pointer, then an initialized vector must be passed here. The vector will be resized so its length is equal to the number of nodes, and it will contain the index of the parent node for each *visited* node. The values in the vector are set to -2 for vertices that were *not* visited, and -1 for the root vertex.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

Example 15.3. File `examples/simple/igraph_bfs_simple.c`

igraph_bfshandler_t — Callback type for BFS function

```
typedef igraph_error_t igraph_bfshandler_t(const igraph_t *graph,
      igraph_integer_t vid,
      igraph_integer_t pred,
      igraph_integer_t succ,
      igraph_integer_t rank,
      igraph_integer_t dist,
      void *extra);
```

`igraph_bfs()` is able to call a callback function, whenever a new vertex is found, while doing the breadth-first search. This callback function must be of type `igraph_bfshandler_t`. It has the following arguments:

Arguments:

- graph*: The graph that that algorithm is working on. Of course this must not be modified.
- vid*: The id of the vertex just found by the breadth-first search.
- pred*: The id of the previous vertex visited. It is -1 if there is no previous vertex, because the current vertex is the root of a search tree.
- succ*: The id of the next vertex that will be visited. It is -1 if there is no next vertex, because the current vertex is the last one in a search tree.
- rank*: The rank of the current vertex, it starts with zero.
- dist*: The distance (number of hops) of the current vertex from the root of the current search tree.
- extra*: The extra argument that was passed to `igraph_bfs()`.

Returns:

IGRAPH_SUCCESS if the BFS should continue, IGRAPH_STOP if the BFS should stop and return to the caller normally. Any other value is treated as an igraph error code, terminating the search and returning to the caller with the same error code. If a BFS is terminated prematurely, then all elements of the result vectors that were not yet calculated at the point of the termination contain NaN.

See also:

`igraph_bfs()`

Depth-first search

`igraph_dfs` — Depth-first search

```
igraph_error_t igraph_dfs(const igraph_t *graph, igraph_integer_t root,
                          igraph_neimode_t mode, igraph_bool_t unreachable,
                          igraph_vector_int_t *order,
                          igraph_vector_int_t *order_out, igraph_vector_int_t *parents,
                          igraph_vector_int_t *dist, igraph_dfshandler_t *in_callback,
                          igraph_dfshandler_t *out_callback,
                          void *extra);
```

A simple depth-first search, with the possibility to call a callback whenever a vertex is discovered and/or whenever a subtree is finished. It is allowed to supply null pointers as the output arguments the user is not interested in, in this case they will be ignored.

If not all vertices can be reached from the supplied root vertex, then additional root vertices will be used, in the order of their vertex IDs.

Arguments:

<i>graph</i> :	The input graph.
<i>root</i> :	The id of the root vertex.
<i>mode</i> :	For directed graphs, it defines which edges to follow. IGRAPH_OUT means following the direction of the edges, IGRAPH_IN means the opposite, and IGRAPH_ALL ignores the direction of the edges. This parameter is ignored for undirected graphs.
<i>unreachable</i> :	Logical scalar, whether the search should visit the vertices that are unreachable from the given root node(s). If true, then additional searches are performed until all vertices are visited.
<i>order</i> :	If not null pointer, then the vertex IDs of the graph are stored here, in the same order as they were discovered. The tail of the vector will be padded with -1 to ensure that the length of the vector is the same as the number of vertices, even if some vertices were not visited during the traversal.
<i>order_out</i> :	If not a null pointer, then the vertex IDs of the graphs are stored here, in the order of the completion of their subtree. The tail of the vector will be padded with -1 to ensure that the length of the vector is the same as the number of vertices, even if some vertices were not visited during the traversal.

<i>parents:</i>	If not a null pointer, then the id of the parent of each vertex is stored here. -1 will be stored for the root of the search tree; -2 will be stored for vertices that were not visited.
<i>dist:</i>	If not a null pointer, then the distance from the root of the current search tree is stored here. -1 will be stored for vertices that were not visited.
<i>in_callback:</i>	If not null, then it should be a pointer to a function of type <code>igraph_dfshandler_t</code> . This function will be called, whenever a new vertex is discovered.
<i>out_callback:</i>	If not null, then it should be a pointer to a function of type <code>igraph_dfshandler_t</code> . This function will be called, whenever the subtree of a vertex is completed.
<i>extra:</i>	Extra argument to pass to the callback function(s).

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

`igraph_dfshandler_t` — Callback type for the DFS function

```
typedef igraph_error_t igraph_dfshandler_t(const igraph_t *graph,
      igraph_integer_t vid,
      igraph_integer_t dist,
      void *extra);
```

`igraph_dfs()` is able to call a callback function, whenever a new vertex is discovered, and/or whenever a subtree is completed. These callbacks must be of type `igraph_dfshandler_t`. They have the following arguments:

Arguments:

<i>graph:</i>	The graph that that algorithm is working on. Of course this must not be modified.
<i>vid:</i>	The id of the vertex just found by the depth-first search.
<i>dist:</i>	The distance (number of hops) of the current vertex from the root of the current search tree.
<i>extra:</i>	The extra argument that was passed to <code>igraph_dfs()</code> .

Returns:

`IGRAPH_SUCCESS` if the DFS should continue, `IGRAPH_STOP` if the DFS should stop and return to the caller normally. Any other value is treated as an igraph error code, terminating the search and returning to the caller with the same error code. If a BFS is terminated prematurely, then all elements of the result vectors that were not yet calculated at the point of the termination contain NaN.

See also:

`igraph_dfs()`

Random walks

igraph_random_walk — Performs a random walk on a graph.

```
igraph_error_t igraph_random_walk(const igraph_t *graph,
                                   const igraph_vector_t *weights,
                                   igraph_vector_int_t *vertices,
                                   igraph_vector_int_t *edges,
                                   igraph_integer_t start,
                                   igraph_neimode_t mode,
                                   igraph_integer_t steps,
                                   igraph_random_walk_stuck_t stuck);
```

Performs a random walk with a given length on a graph, from the given start vertex. Edge directions are (potentially) considered, depending on the *mode* argument.

Arguments:

- graph*: The input graph, it can be directed or undirected. Multiple edges are respected, so are loop edges.
- weights*: A vector of non-negative edge weights. It is assumed that at least one strictly positive weight is found among the outgoing edges of each vertex. Additionally, no edge weight may be NaN. If either case does not hold, an error is returned. If it is NULL, all edges are considered to have equal weight.
- vertices*: An allocated vector, the result is stored here as a list of vertex IDs. It will be resized as needed. It includes the vertex IDs of starting and ending vertices. Length of the vertices vector: *steps* + 1
- edges*: An initialized vector, the indices of traversed edges are stored here. It will be resized as needed. Length of the edges vector: *steps*
- start*: The start vertex for the walk.
- steps*: The number of steps to take. If the random walk gets stuck, then the *stuck* argument specifies what happens. *steps* is the number of edges to traverse during the walk.
- mode*: How to walk along the edges in directed graphs. IGRAPH_OUT means following edge directions, IGRAPH_IN means going opposite the edge directions, IGRAPH_ALL means ignoring edge directions. This argument is ignored for undirected graphs.
- stuck*: What to do if the random walk gets stuck. IGRAPH_RANDOM_WALK_STUCK_RETURN means that the function returns with a shorter walk; IGRAPH_RANDOM_WALK_STUCK_ERROR means that an IGRAPH_ERWSTUCK error is reported. In both cases, *vertices* and *edges* are truncated to contain the actual interrupted walk.

Returns:

Error code: IGRAPH_ERWSTUCK if the walk got stuck.

Time complexity: $O(l + d)$ for unweighted graphs and $O(l * \log(k) + d)$ for weighted graphs, where l is the length of the walk, d is the total degree of the visited nodes and k is the average degree of vertices of the given graph.

Deprecated functions

igraph_random_edge_walk — Performs a random walk on a graph and returns the traversed edges.

```
igraph_error_t igraph_random_edge_walk(
    const igraph_t *graph,
    const igraph_vector_t *weights,
    igraph_vector_int_t *edgewalk,
    igraph_integer_t start, igraph_neimode_t mode,
    igraph_integer_t steps,
    igraph_random_walk_stuck_t stuck);
```

Performs a random walk with a given length on a graph, from the given start vertex. Edge directions are (potentially) considered, depending on the *mode* argument.

Arguments:

- graph*: The input graph, it can be directed or undirected. Multiple edges are respected, so are loop edges.
- weights*: A vector of non-negative edge weights. It is assumed that at least one strictly positive weight is found among the outgoing edges of each vertex. Additionally, no edge weight may be NaN. If either case does not hold, an error is returned. If it is a NULL pointer, all edges are considered to have equal weight.
- edgewalk*: An initialized vector; the indices of traversed edges are stored here. It will be resized as needed.
- start*: The start vertex for the walk.
- steps*: The number of steps to take. If the random walk gets stuck, then the *stuck* argument specifies what happens.
- mode*: How to walk along the edges in directed graphs. IGRAPH_OUT means following edge directions, IGRAPH_IN means going opposite the edge directions, IGRAPH_ALL means ignoring edge directions. This argument is ignored for undirected graphs.
- stuck*: What to do if the random walk gets stuck. IGRAPH_RANDOM_WALK_STUCK_RETURN means that the function returns with a shorter walk; IGRAPH_RANDOM_WALK_STUCK_ERROR means that an IGRAPH_ERWSTUCK error is reported. In both cases, *edgewalk* is truncated to contain the actual interrupted walk.

Returns:

Error code.

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_random_walk()` instead.

Chapter 16. Cliques and independent vertex sets

These functions calculate various graph properties related to cliques and independent vertex sets.

Cliques

igraph_cliques — Finds all or some cliques in a graph.

```
igraph_error_t igraph_cliques(const igraph_t *graph, igraph_vector_int_list_t *res,
                              igraph_integer_t min_size, igraph_integer_t max_size);
```

Cliques are fully connected subgraphs of a graph.

If you are only interested in the size of the largest clique in the graph, use `igraph_clique_number()` instead.

The current implementation of this function uses version 1.21 of the Cliquer library by Sampo Niskanen and Patric R. J. Östergård, <http://users.aalto.fi/~pat/cliquer.html>

Arguments:

- graph*: The input graph.
- res*: Pointer to a list of integer vectors, the result will be stored here. The pointer vector will be resized if needed.
- min_size*: Integer specifying the minimum size of the cliques to be returned. If negative or zero, no lower bound will be used.
- max_size*: Integer specifying the maximum size of the cliques to be returned. If negative or zero, no upper bound will be used.

Returns:

Error code.

See also:

`igraph_largest_cliques()` and `igraph_clique_number()`.

Time complexity: Exponential

Example 16.1. File `examples/simple/igraph_cliques.c`

igraph_clique_size_hist — Counts cliques of each size in the graph.


```
igraph_error_t igraph_clique_size_hist(const igraph_t *graph, igraph_vector_t *h,
                                       igraph_integer_t min_size, igraph_integer_t max_size)
```

Cliques are fully connected subgraphs of a graph.

The current implementation of this function uses version 1.21 of the Cliquer library by Sampo Niskanen and Patric R. J. Östergård, <http://users.aalto.fi/~pat/cliquer.html>

Arguments:

graph: The input graph.

hist: Pointer to an initialized vector. The result will be stored here. The first element will store the number of size-1 cliques, the second element the number of size-2 cliques, etc. For cliques smaller than *min_size*, zero counts will be returned.

min_size: Integer specifying the minimum size of the cliques to be returned. If negative or zero, no lower bound will be used.

max_size: Integer specifying the maximum size of the cliques to be returned. If negative or zero, no upper bound will be used.

Returns:

Error code.

See also:

`igraph_cliques()` and `igraph_cliques_callback()`

Time complexity: Exponential

igraph_cliques_callback — Calls a function for each clique in the graph.

```
igraph_error_t igraph_cliques_callback(const igraph_t *graph,
                                       igraph_integer_t min_size, igraph_integer_t max_size,
                                       igraph_clique_handler_t *cliquehandler_fn, void *arg)
```

Cliques are fully connected subgraphs of a graph. This function enumerates all cliques within the given size range and calls *cliquehandler_fn* for each of them. The cliques are passed to the callback function as a pointer to an `igraph_vector_int_t`. Destroying and freeing this vector is left up to the user. Use `igraph_vector_int_destroy()` to destroy it first, then free it using `igraph_free()`.

The current implementation of this function uses version 1.21 of the Cliquer library by Sampo Niskanen and Patric R. J. Östergård, <http://users.aalto.fi/~pat/cliquer.html>

Arguments:

graph: The input graph.

min_size: Integer specifying the minimum size of the cliques to be returned. If negative or zero, no lower bound will be used.

max_size: Integer specifying the maximum size of the cliques to be returned. If negative or zero, no upper bound will be used.

cliquehandler_fn: Callback function to be called for each clique. See also `igraph_clique_handler_t`.

arg: Extra argument to supply to *cliquehandler_fn*.

Returns:

Error code.

See also:

`igraph_cliques()`

Time complexity: Exponential

`igraph_clique_handler_t` — Type of clique handler functions.

```
typedef igraph_error_t igraph_clique_handler_t(const igraph_vector_int_t *clique,
```

Callback type, called when a clique was found. See the details at the documentation of `igraph_cliques_callback()`.

Arguments:

clique: The current clique. The clique is owned by the clique search routine. You do not need to destroy or free it if you do not want to store it; however, if you want to hold on to it for a longer period of time, you need to make a copy of it on your own and store the copy itself.

arg: This extra argument was passed to `igraph_cliques_callback()` when it was called.

Returns:

Error code; `IGRAPH_SUCCESS` to continue the search or `IGRAPH_STOP` to stop the search without signaling an error.

`igraph_largest_cliques` — Finds the largest clique(s) in a graph.

```
igraph_error_t igraph_largest_cliques(const igraph_t *graph, igraph_vector_int_t
```

A clique is largest (quite intuitively) if there is no other clique in the graph which contains more vertices.

Note that this is not necessarily the same as a maximal clique, i.e. the largest cliques are always maximal but a maximal clique is not always largest.

The current implementation of this function searches for maximal cliques using `igraph_maximal_cliques_callback()` and drops those that are not the largest.

The implementation of this function changed between igraph 0.5 and 0.6, so the order of the cliques and the order of vertices within the cliques will almost surely be different between these two versions.

Arguments:

graph: The input graph.

res: Pointer to a list of integer vectors, the result will be stored here. The pointer vector will be resized if needed.

Returns:

Error code.

See also:

`igraph_cliques()`, `igraph_maximal_cliques()`

Time complexity: $O(3^{(|V|/3)})$ worst case.

igraph_maximal_cliques — Finds all maximal cliques in a graph.

```
igraph_error_t igraph_maximal_cliques(
    const igraph_t *graph, igraph_vector_int_list_t *res,
    igraph_integer_t min_size, igraph_integer_t max_size
);
```

A maximal clique is a clique which can't be extended any more by adding a new vertex to it.

If you are only interested in the size of the largest clique in the graph, use `igraph_clique_number()` instead.

The current implementation uses a modified Bron-Kerbosch algorithm to find the maximal cliques, see: David Eppstein, Maarten Löffler, Darren Strash: Listing All Maximal Cliques in Sparse Graphs in Near-Optimal Time. Algorithms and Computation, Lecture Notes in Computer Science Volume 6506, 2010, pp 403-414.

The implementation of this function changed between igraph 0.5 and 0.6 and also between 0.6 and 0.7, so the order of the cliques and the order of vertices within the cliques will almost surely be different between these three versions.

Arguments:

graph: The input graph.

res: Pointer to a pointer vector, the result will be stored here, i.e. *res* will contain pointers to `igraph_vector_int_t` objects which contain the indices of vertices involved in a clique. The pointer vector will be resized if needed but note that the objects in the pointer vector will not be freed. Note that vertices of a clique may be returned in arbitrary order.

min_size: Integer giving the minimum size of the cliques to be returned. If negative or zero, no lower bound will be used.

max_size: Integer giving the maximum size of the cliques to be returned. If negative or zero, no upper bound will be used.

Returns:

Error code.

See also:

`igraph_maximal_independent_vertex_sets()`, `igraph_clique_number()`

Time complexity: $O(d(n-d)3^{d/3})$ worst case, d is the degeneracy of the graph, this is typically small for sparse graphs.

Example 16.2. File `examples/simple/igraph_maximal_cliques.c`

`igraph_maximal_cliques_count` — Count the number of maximal cliques in a graph

```
igraph_error_t igraph_maximal_cliques_count(const igraph_t *graph,
                                             igraph_integer_t *res,
                                             igraph_integer_t min_size,
                                             igraph_integer_t max_size);
```

The current implementation uses a modified Bron-Kerbosch algorithm to find the maximal cliques, see: David Eppstein, Maarten Löffler, Darren Strash: Listing All Maximal Cliques in Sparse Graphs in Near-Optimal Time. Algorithms and Computation, Lecture Notes in Computer Science Volume 6506, 2010, pp 403-414.

Arguments:

graph: The input graph.

res: Pointer to an `igraph_integer_t`; the number of maximal cliques will be stored here.

min_size: Integer giving the minimum size of the cliques to be returned. If negative or zero, no lower bound will be used.

max_size: Integer giving the maximum size of the cliques to be returned. If negative or zero, no upper bound will be used.

Returns:

Error code.

See also:

`igraph_maximal_cliques()`.

Time complexity: $O(d(n-d)3^{(d/3)})$ worst case, d is the degeneracy of the graph, this is typically small for sparse graphs.

Example 16.3. File `examples/simple/igraph_maximal_cliques.c`

igraph_maximal_cliques_file — Find maximal cliques and write them to a file.

```
igraph_error_t igraph_maximal_cliques_file(const igraph_t *graph,
                                           FILE *outfile,
                                           igraph_integer_t min_size,
                                           igraph_integer_t max_size);
```

This function enumerates all maximal cliques and writes them to file.

Edge directions are ignored.

Arguments:

- graph*: The input graph.
- outfile*: Pointer to the output file, it should be writable.
- min_size*: Integer giving the minimum size of the cliques to be returned. If negative or zero, no lower bound will be used.
- max_size*: Integer giving the maximum size of the cliques to be returned. If negative or zero, no upper bound will be used.

Returns:

Error code.

See also:

`igraph_maximal_cliques()`.

Time complexity: $O(d(n-d)3^{(d/3)})$ worst case, d is the degeneracy of the graph, this is typically small for sparse graphs.*

igraph_maximal_cliques_subset — Maximal cliques for a subset of initial vertices

```
igraph_error_t igraph_maximal_cliques_subset(
    const igraph_t *graph, const igraph_vector_int_t *subset,
    igraph_vector_int_list_t *res, igraph_integer_t *no,
    FILE *outfile, igraph_integer_t min_size, igraph_integer_t max_size
);
```

This function enumerates all maximal cliques for a subset of initial vertices and writes them to file.

Edge directions are ignored.

Arguments:

graph: The input graph.

subset: Pointer to an `igraph_vector_int_t` containing the subset of initial vertices

res: Pointer to a list of integer vectors; the cliques will be stored here

no: Pointer to an `igraph_integer_t`; the number of maximal cliques will be stored here.

outfile: Pointer to an output file or NULL. When not NULL, the file should be writable.

min_size: Integer giving the minimum size of the cliques to be returned. If negative or zero, no lower bound will be used.

max_size: Integer giving the maximum size of the cliques to be returned. If negative or zero, no upper bound will be used.

Returns:

Error code.

See also:

`igraph_maximal_cliques()`.

Time complexity: $O(d(n-d)3^{(d/3)})$ worst case, d is the degeneracy of the graph, this is typically small for sparse graphs.

`igraph_maximal_cliques_hist` — Counts the number of maximal cliques of each size in a graph.

```
igraph_error_t igraph_maximal_cliques_hist(const igraph_t *graph,
                                           igraph_vector_t *hist,
                                           igraph_integer_t min_size,
                                           igraph_integer_t max_size);
```

This function counts how many maximal cliques of each size are present in the graph. Size-1 maximal cliques are simply isolated vertices.

Edge directions are ignored.

Arguments:

graph: The input graph.

hist: Pointer to an initialized vector. The result will be stored here. The first element will store the number of size-1 maximal cliques, the second element the number of size-2 maximal cliques, etc. For cliques smaller than *min_size*, zero counts will be returned.

min_size: Integer giving the minimum size of the cliques to be returned. If negative or zero, no lower bound will be used.

max_size: Integer giving the maximum size of the cliques to be returned. If negative or zero, no upper bound will be used.

Returns:

Error code.

See also:

`igraph_maximal_cliques()`.

Time complexity: $O(d(n-d)3^{(d/3)})$ worst case, d is the degeneracy of the graph, this is typically small for sparse graphs.

igraph_maximal_cliques_callback — Finds maximal cliques in a graph and calls a function for each one.

```
igraph_error_t igraph_maximal_cliques_callback(const igraph_t *graph,
                                              igraph_clique_handler_t *cliquehandler_fn,
                                              igraph_integer_t min_size, igraph_integer_t max_size);
```

This function enumerates all maximal cliques within the given size range and calls *cliquehandler_fn* for each of them. The cliques are passed to the callback function as a pointer to an `igraph_vector_int_t`. The vector is owned by the maximal clique search routine so users are expected to make a copy of the vector using `igraph_vector_int_init_copy()` if they want to hold on to it.

Edge directions are ignored.

Arguments:

graph: The input graph.

cliquehandler_fn: Callback function to be called for each clique. See also `igraph_clique_handler_t`.

arg: Extra argument to supply to *cliquehandler_fn*.

min_size: Integer giving the minimum size of the cliques to be returned. If negative or zero, no lower bound will be used.

max_size: Integer giving the maximum size of the cliques to be returned. If negative or zero, no upper bound will be used.

Returns:

Error code.

See also:

`igraph_maximal_cliques()`.

Time complexity: $O(d(n-d)3^{(d/3)})$ worst case, d is the degeneracy of the graph, this is typically small for sparse graphs.

igraph_clique_number — Finds the clique number of the graph.

```
igraph_error_t igraph_clique_number(const igraph_t *graph, igraph_integer_t *no
```

The clique number of a graph is the size of the largest clique.

The current implementation of this function searches for maximal cliques using `igraph_maximal_cliques_callback()` and keeps track of the size of the largest clique that was found.

Arguments:

graph: The input graph.

no: The clique number will be returned to the `igraph_integer_t` pointed by this variable.

Returns:

Error code.

See also:

`igraph_cliques()`, `igraph_largest_cliques()`.

Time complexity: $O(3^{(|V|/3)})$ worst case.

Weighted cliques

igraph_weighted_cliques — Finds all cliques in a given weight range in a vertex weighted graph.

```
igraph_error_t igraph_weighted_cliques(const igraph_t *graph,
                                       const igraph_vector_t *vertex_weights, igraph_vector_t *cliques,
                                       igraph_real_t min_weight, igraph_real_t max_weight,
```

Cliques are fully connected subgraphs of a graph. The weight of a clique is the sum of the weights of individual vertices within the clique.

The current implementation of this function uses version 1.21 of the Cliquer library by Sampo Niskanen and Patric R. J. Östergård, <http://users.aalto.fi/~pat/cliquer.html> Only positive integer vertex weights are supported.

Arguments:

graph: The input graph.

vertex_weights: A vector of vertex weights. The current implementation will truncate all weights to their integer parts. You may pass `NULL` here to make each vertex have a weight of 1.

res: Pointer to a list of integer vectors, the result will be stored here. The pointer vector will be resized if needed.

min_weight: Integer specifying the minimum weight of the cliques to be returned. If negative or zero, no lower bound will be used.

max_weight: Integer specifying the maximum weight of the cliques to be returned. If negative or zero, no upper bound will be used.

maximal: If true, only maximal cliques will be returned

Returns:

Error code.

See also:

`igraph_cliques()`, `igraph_maximal_cliques()`

Time complexity: Exponential

`igraph_largest_weighted_cliques` — Finds the largest weight clique(s) in a graph.

```
igraph_error_t igraph_largest_weighted_cliques(const igraph_t *graph,
                                              const igraph_vector_t *vertex_weights, igraph_vector_t *res);
```

Finds the clique(s) having the largest weight in the graph.

The current implementation of this function uses version 1.21 of the Cliquer library by Sampo Niskanen and Patric R. J. Östergård, <http://users.aalto.fi/~pat/cliquer.html> Only positive integer vertex weights are supported.

Arguments:

graph: The input graph.

vertex_weights: A vector of vertex weights. The current implementation will truncate all weights to their integer parts. You may pass NULL here to make each vertex have a weight of 1.

res: Pointer to a list of integer vectors, the result will be stored here. The pointer vector will be resized if needed.

Returns:

Error code.

See also:

`igraph_weighted_cliques()`, `igraph_weighted_clique_number()`,
`igraph_largest_cliques()`

Time complexity: TODO

igraph_weighted_clique_number — Finds the weight of the largest weight clique in the graph.

```
igraph_error_t igraph_weighted_clique_number(const igraph_t *graph,
                                             const igraph_vector_t *vertex_weights, igraph_t *res);
```

The current implementation of this function uses version 1.21 of the Cliquer library by Sampo Niskanen and Patric R. J. Östergård, <http://users.aalto.fi/~pat/cliquer.html> Only positive integer vertex weights are supported.

Arguments:

graph: The input graph.

vertex_weights: A vector of vertex weights. The current implementation will truncate all weights to their integer parts. You may pass NULL here to make each vertex have a weight of 1.

res: The largest weight will be returned to the `igraph_real_t` pointed to by this variable.

Returns:

Error code.

See also:

```
igraph_weighted_cliques(),      igraph_largest_weighted_cliques(),  
igraph_clique_number()
```

Time complexity: TODO

Independent vertex sets

igraph_independent_vertex_sets — Finds all independent vertex sets in a graph.

```
igraph_error_t igraph_independent_vertex_sets(const igraph_t *graph,
                                              igraph_vector_int_list_t *res,
                                              igraph_integer_t min_size,
                                              igraph_integer_t max_size);
```

A vertex set is considered independent if there are no edges between them.

If you are interested in the size of the largest independent vertex set, use `igraph_independence_number()` instead.

The current implementation was ported to igraph from the Very Nauty Graph Library by Keith Briggs and uses the algorithm from the paper S. Tsukiyama, M. Ide, H. Ariyoshi and I. Shirawaka. A new algorithm for generating all the maximal independent sets. SIAM J Computing, 6:505--517, 1977.

Arguments:

- graph*: The input graph.
- res*: Pointer to a list of integer vectors, the result will be stored here. The pointer vector will be resized if needed.
- min_size*: Integer specifying the minimum size of the sets to be returned. If negative or zero, no lower bound will be used.
- max_size*: Integer specifying the maximum size of the sets to be returned. If negative or zero, no upper bound will be used.

Returns:

Error code.

See also:

`igraph_largest_independent_vertex_sets()`, `igraph_independence_number()`.

Time complexity: TODO

Example 16.4. File `examples/simple/igraph_independent_sets.c`

`igraph_largest_independent_vertex_sets` — Finds the largest independent vertex set(s) in a graph.

```
igraph_error_t igraph_largest_independent_vertex_sets(const igraph_t *graph,
    igraph_vector_int_list_t *res);
```

An independent vertex set is largest if there is no other independent vertex set with more vertices in the graph.

The current implementation was ported to igraph from the Very Nauty Graph Library by Keith Briggs and uses the algorithm from the paper S. Tsukiyama, M. Ide, H. Ariyoshi and I. Shirawaka. A new algorithm for generating all the maximal independent sets. *SIAM J Computing*, 6:505--517, 1977.

Arguments:

- graph*: The input graph.
- res*: Pointer to a list of integer vectors, the result will be stored here. The pointer vector will be resized if needed.

Returns:

Error code.

See also:

`igraph_independent_vertex_sets()`, `igraph_maximal_independent_vertex_sets()`.

Time complexity: TODO

igraph_maximal_independent_vertex_sets — Finds all maximal independent vertex sets of a graph.

```
igraph_error_t igraph_maximal_independent_vertex_sets(const igraph_t *graph,
                                                       igraph_vector_int_list_t *res);
```

A maximal independent vertex set is an independent vertex set which can't be extended any more by adding a new vertex to it.

The algorithm used here is based on the following paper: S. Tsukiyama, M. Ide, H. Ariyoshi and I. Shirawaka. A new algorithm for generating all the maximal independent sets. *SIAM J Computing*, 6:505--517, 1977.

The implementation was originally written by Kevin O'Neill and modified by K M Briggs in the Very Nauty Graph Library. I simply re-wrote it to use igraph's data structures.

If you are interested in the size of the largest independent vertex set, use `igraph_independence_number()` instead.

Arguments:

graph: The input graph.

res: Pointer to a list of integer vectors, the result will be stored here. The pointer vector will be resized if needed.

Returns:

Error code.

See also:

`igraph_maximal_cliques()`, `igraph_independence_number()`

Time complexity: TODO.

igraph_independence_number — Finds the independence number of the graph.

```
igraph_error_t igraph_independence_number(const igraph_t *graph, igraph_integer_t *res);
```

The independence number of a graph is the cardinality of the largest independent vertex set.

The current implementation was ported to igraph from the Very Nauty Graph Library by Keith Briggs and uses the algorithm from the paper S. Tsukiyama, M. Ide, H. Ariyoshi and I. Shirawaka. A new algorithm for generating all the maximal independent sets. *SIAM J Computing*, 6:505--517, 1977.

Arguments:

graph: The input graph.

no: The independence number will be returned to the `igraph_integer_t` pointed by this variable.

Returns:

Error code.

See also:

`igraph_independent_vertex_sets()`.

Time complexity: TODO.

Chapter 17. Graph isomorphism

The simple interface

igraph provides four set of functions to deal with graph isomorphism problems.

The `igraph_isomorphic()` and `igraph_subisomorphic()` functions make up the first set (in addition with the `igraph_permute_vertices()` function). These functions choose the algorithm which is best for the supplied input graph. (The choice is not very sophisticated though, see their documentation for details.)

The VF2 graph (and subgraph) isomorphism algorithm is implemented in igraph, these functions are the second set. See `igraph_isomorphic_vf2()` and `igraph_subisomorphic_vf2()` for starters.

Functions for the Bliss algorithm constitute the third set, see `igraph_isomorphic_bliss()`.

Finally, the isomorphism classes of all directed graphs with three and four vertices and all undirected graphs with 3-6 vertices are precomputed and stored in igraph, so for these small graphs there is a separate fast path in the code that does not use more complex, generic isomorphism algorithms.

`igraph_isomorphic` — Decides whether two graphs are isomorphic

```
igraph_error_t igraph_isomorphic(const igraph_t *graph1, const igraph_t *graph2,
                                igraph_bool_t *iso);
```

In simple terms, two graphs are isomorphic if they become indistinguishable from each other once their vertex labels are removed (rendering the vertices within each graph indistinguishable). More precisely, two graphs are isomorphic if there is a one-to-one mapping from the vertices of the first one to the vertices of the second such that it transforms the edge set of the first graph into the edge set of the second. This mapping is called an *isomorphism*.

Currently, this function supports simple graphs and graphs with self-loops, but does not support multi-graphs.

This function decides which graph isomorphism algorithm to be used based on the input graphs. Right now it does the following:

1. If one graph is directed and the other undirected then an error is triggered.
2. If one of the graphs has multi-edges then an error is triggered.
3. If the two graphs does not have the same number of vertices and edges it returns with `false`.
4. Otherwise, if the `igraph_isoclass()` function supports both graphs (which is true for directed graphs with 3 and 4 vertices, and undirected graphs with 3-6 vertices), an $O(1)$ algorithm is used with precomputed data.
5. Otherwise Bliss is used, see `igraph_isomorphic_bliss()`.

Please call the VF2 and Bliss functions directly if you need something more sophisticated, e.g. you need the isomorphic mapping.

Arguments:

graph1: The first graph.

graph2: The second graph.

iso: Pointer to a logical variable, will be set to `true` if the two graphs are isomorphic, and `false` otherwise.

Returns:

Error code.

See also:

`igraph_isoclass()`, `igraph_isoclass_subgraph()`, `igraph_isoclass_create()`.

Time complexity: exponential.

`igraph_subisomorphic` — Decide subgraph isomorphism.

```
igraph_error_t igraph_subisomorphic(const igraph_t *graph1, const igraph_t *graph2,
                                     igraph_bool_t *iso);
```

Check whether *graph2* is isomorphic to a subgraph of *graph1*. Currently this function just calls `igraph_subisomorphic_vf2()` for all graphs.

Currently this function does not support non-simple graphs.

Arguments:

graph1: The first input graph, may be directed or undirected. This is supposed to be the bigger graph.

graph2: The second input graph, it must have the same directedness as *graph1*, or an error is triggered. This is supposed to be the smaller graph.

iso: Pointer to a boolean, the result is stored here.

Returns:

Error code.

Time complexity: exponential.

The BLISS algorithm

Bliss is a successor of the famous NAUTY algorithm and implementation. While using the same ideas in general, with better heuristics and data structures Bliss outperforms NAUTY on most graphs.

Bliss was developed and implemented by Tommi Junttila and Petteri Kaski at Helsinki University of Technology, Finland. For more information, see the Bliss homepage at <https://users.aalto.fi/~tjunttila/bliss/> and the following publication:

Tommi Junttila and Petteri Kaski: "Engineering an Efficient Canonical Labeling Tool for Large and Sparse Graphs" In ALENEX 2007, pages 135–149, 2007 <https://doi.org/10.1137/1.9781611972870.13>

Tommi Junttila and Petteri Kaski: "Conflict Propagation and Component Recursion for Canonical Labeling" in TAPAS 2011, pages 151–162, 2011. https://doi.org/10.1007/978-3-642-19754-3_16

Bliss works with both directed graphs and undirected graphs. It supports graphs with self-loops, but not graphs with multi-edges.

Bliss version 0.75 is included in igraph.

igraph_bliss_sh_t — Splitting heuristics for Bliss.

```
typedef enum { IGRAPH_BLISS_F = 0, IGRAPH_BLISS_FL,  
              IGRAPH_BLISS_FS, IGRAPH_BLISS_FM,  
              IGRAPH_BLISS_FLM, IGRAPH_BLISS_FSM  
            } igraph_bliss_sh_t;
```

IGRAPH_BLISS_FL provides good performance for many graphs, and is a reasonable default choice. IGRAPH_BLISS_FSM is recommended for graphs that have some combinatorial structure, and is the default of the Bliss library's command line tool.

Values:

IGRAPH_BLISS_F:	First non-singleton cell.
IGRAPH_BLISS_FL:	First largest non-singleton cell.
IGRAPH_BLISS_FS:	First smallest non-singleton cell.
IGRAPH_BLISS_FM:	First maximally non-trivially connected non-singleton cell.
IGRAPH_BLISS_FLM:	Largest maximally non-trivially connected non-singleton cell.
IGRAPH_BLISS_FSM:	Smallest maximally non-trivially connected non-singleton cell.

igraph_bliss_info_t — Information about a BLISS run

```
typedef struct igraph_bliss_info_t {  
    unsigned long nof_nodes;  
    unsigned long nof_leaf_nodes;  
    unsigned long nof_bad_nodes;  
    unsigned long nof_canupdates;  
    unsigned long nof_generators;  
    unsigned long max_level;  
    char *group_size;  
} igraph_bliss_info_t;
```

Some secondary information found by the BLISS algorithm is stored here. It is useful if you want to study the internal working of the algorithm.

Values:

<code>nof_nodes:</code>	The number of nodes in the search tree.
<code>nof_leaf_nodes:</code>	The number of leaf nodes in the search tree.
<code>nof_bad_nodes:</code>	Number of bad nodes.
<code>nof_canupdates:</code>	Number of canrep updates.
<code>nof_generators:</code>	Number of generators of the automorphism group.
<code>max_level:</code>	Maximum level.
<code>group_size:</code>	The size of the automorphism group of the graph, given as a string. It should be deallocated via <code>igraph_free()</code> if not needed any more.

See <http://www.tcs.hut.fi/Software/bliss/index.html> for details about the algorithm and these parameters.

`igraph_canonical_permutation` — Canonical permutation using Bliss.

```
igraph_error_t igraph_canonical_permutation(const igraph_t *graph, const igraph_vector_int_t *labeling, igraph_bliss_sh_t sh,
```

This function computes the vertex permutation which transforms the graph into a canonical form, using the Bliss algorithm. Two graphs have the same canonical form if and only if they are isomorphic. Use `igraph_is_same_graph()` to compare two canonical forms.

Arguments:

<i>graph</i> :	The input graph. Multiple edges between the same nodes are not supported and will cause an incorrect result to be returned.
<i>colors</i> :	An optional vertex color vector for the graph. Supply a null pointer if the graph is not colored.
<i>labeling</i> :	Pointer to a vector, the result is stored here. The permutation takes vertex 0 to the first element of the vector, vertex 1 to the second, etc. The vector will be resized as needed.
<i>sh</i> :	The splitting heuristics to be used in Bliss. See <code>igraph_bliss_sh_t</code> .
<i>info</i> :	If not NULL then information on Bliss internals is stored here. The memory used by this structure must be freed when no longer needed, see <code>igraph_bliss_info_t</code> .

Returns:

Error code.

See also:

`igraph_is_same_graph()`

Time complexity: exponential, in practice it is fast for many graphs.

igraph_isomorphic_bliss — Graph isomorphism via Bliss.

```
igraph_error_t igraph_isomorphic_bliss(const igraph_t *graph1, const igraph_t *graph2,
                                       const igraph_vector_int_t *colors1, const igraph_vector_int_t *colors2,
                                       igraph_bool_t *iso, igraph_vector_int_t *map12,
                                       igraph_vector_int_t *map21, igraph_bliss_sh_t sh,
                                       igraph_bliss_info_t *info1, igraph_bliss_info_t *info2)
```

This function uses the Bliss graph isomorphism algorithm, a successor of the famous NAUTY algorithm and implementation. Bliss is open source and licensed according to the GNU LGPL. See <https://users.aalto.fi/~tjunttil/bliss/> for details. Currently the 0.75 version of Bliss is included in igraph.

Isomorphism testing is implemented by producing the canonical form of both graphs using `igraph_canonical_permutation()` and comparing them.

Arguments:

- graph1*: The first input graph. Multiple edges between the same nodes are not supported and will cause an incorrect result to be returned.
- graph2*: The second input graph. Multiple edges between the same nodes are not supported and will cause an incorrect result to be returned.
- colors1*: An optional vertex color vector for the first graph. Supply a null pointer if your graph is not colored.
- colors2*: An optional vertex color vector for the second graph. Supply a null pointer if your graph is not colored.
- iso*: Pointer to a boolean, the result is stored here.
- map12*: A vector or NULL pointer. If not NULL then an isomorphic mapping from *graph1* to *graph2* is stored here. If the input graphs are not isomorphic then this vector is cleared, i.e. it will have length zero.
- map21*: Similar to *map12*, but for the mapping from *graph2* to *graph1*.
- sh*: Splitting heuristics to be used for the graphs. See `igraph_bliss_sh_t`.
- info1*: If not NULL, information about the canonization of the first input graph is stored here. Note that if the two graphs have different number of vertices or edges, then this is only partially filled. The memory used by this structure should be released when no longer needed, see `igraph_bliss_info_t` for details.
- info2*: Same as *info1*, but for the second graph.

Returns:

Error code.

Time complexity: exponential, but in practice it is quite fast.

igraph_automorphisms — Number of automorphisms using Bliss.

```
igraph_error_t igraph_automorphisms(const igraph_t *graph, const igraph_vector_int_t *
                                     igraph_bliss_sh_t sh, igraph_bliss_info_t *info);
```

The number of automorphisms of a graph is computed using Bliss. The result is returned as part of the *info* structure, in tag *group_size*. It is returned as a string, as it can be very high even for relatively small graphs. If the GNU MP library is used then this number is exact, otherwise a long double is used and it is only approximate. See also *igraph_bliss_info_t*.

Arguments:

- graph*: The input graph. Multiple edges between the same nodes are not supported and will cause an incorrect result to be returned.
- colors*: An optional vertex color vector for the graph. Supply a null pointer if the graph is not colored.
- sh*: The splitting heuristics to be used in Bliss. See *igraph_bliss_sh_t*.
- info*: The result is stored here, in particular in the *group_size* tag of *info*. The memory used by this structure must be released when no longer needed, see *igraph_bliss_info_t*.

Returns:

Error code.

Time complexity: exponential, in practice it is fast for many graphs.

igraph_automorphism_group — Automorphism group generators using Bliss.

```
igraph_error_t igraph_automorphism_group(
    const igraph_t *graph, const igraph_vector_int_t *colors, igraph_vector_int_t *
    igraph_bliss_sh_t sh, igraph_bliss_info_t *info);
```

The generators of the automorphism group of a graph are computed using Bliss. The generator set may not be minimal and may depend on the splitting heuristics. The generators are permutations represented using zero-based indexing.

Arguments:

- graph*: The input graph. Multiple edges between the same nodes are not supported and will cause an incorrect result to be returned.
- colors*: An optional vertex color vector for the graph. Supply a null pointer if the graph is not colored.
- generators*: Must be an initialized pointer vector. It will contain pointers to *igraph_vector_int_t* objects representing generators of the automorphism group.
- sh*: The splitting heuristics to be used in Bliss. See *igraph_bliss_sh_t*.
- info*: If not NULL then information on Bliss internals is stored here. The memory used by this structure must to be freed when no longer needed, see *igraph_bliss_info_t*.

Returns:

Error code.

Time complexity: exponential, in practice it is fast for many graphs.

The VF2 algorithm

The VF2 algorithm can search for a subgraph in a larger graph, or check if two graphs are isomorphic. See P. Foggia, C. Sansone, M. Vento, An Improved algorithm for matching large graphs, Proc. of the 3rd IAPR-TC-15 International Workshop on Graph-based Representations, Italy, 2001.

VF2 supports both vertex and edge-colored graphs, as well as custom vertex or edge compatibility functions.

VF2 works with both directed and undirected graphs. Only simple graphs are supported. Self-loops or multi-edges must not be present in the graphs. Currently, the VF2 functions do not check that the input graph is simple: it is the responsibility of the user to pass in valid input.

igraph_isomorphic_vf2 — Isomorphism via VF2

```
igraph_error_t igraph_isomorphic_vf2(const igraph_t *graph1, const igraph_t *graph2,
                                     const igraph_vector_int_t *vertex_color1,
                                     const igraph_vector_int_t *vertex_color2,
                                     const igraph_vector_int_t *edge_color1,
                                     const igraph_vector_int_t *edge_color2,
                                     igraph_bool_t *iso, igraph_vector_int_t *map12,
                                     igraph_vector_int_t *map21,
                                     igraph_isocompat_t *node_compat_fn,
                                     igraph_isocompat_t *edge_compat_fn,
                                     void *arg);
```

This function performs the VF2 algorithm via calling `igraph_get_isomorphism_s_vf2_callback()`.

Note that this function cannot be used for deciding subgraph isomorphism, use `igraph_subisomorphic_vf2()` for that.

Arguments:

<i>graph1</i> :	The first graph, may be directed or undirected.
<i>graph2</i> :	The second graph. It must have the same directedness as <i>graph1</i> , otherwise an error is reported.
<i>vertex_color1</i> :	An optional color vector for the first graph. If color vectors are given for both graphs, then the isomorphism is calculated on the colored graphs; i.e. two vertices can match only if their color also matches. Supply a null pointer here if your graphs are not colored.
<i>vertex_color2</i> :	An optional color vector for the second graph. See the previous argument for explanation.
<i>edge_color1</i> :	An optional edge color vector for the first graph. The matching edges in the two graphs must have matching colors as well. Supply a null pointer here if your graphs are not edge-colored.

<i>edge_color2</i> :	The edge color vector for the second graph.
<i>iso</i> :	Pointer to a logical constant, the result of the algorithm will be placed here.
<i>map12</i> :	Pointer to an initialized vector or a NULL pointer. If not a NULL pointer then the mapping from <i>graph1</i> to <i>graph2</i> is stored here. If the graphs are not isomorphic then the vector is cleared (i.e. has zero elements).
<i>map21</i> :	Pointer to an initialized vector or a NULL pointer. If not a NULL pointer then the mapping from <i>graph2</i> to <i>graph1</i> is stored here. If the graphs are not isomorphic then the vector is cleared (i.e. has zero elements).
<i>node_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two nodes are compatible.
<i>edge_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two edges are compatible.
<i>arg</i> :	Extra argument to supply to functions <i>node_compat_fn</i> and <i>edge_compat_fn</i> .

Returns:

Error code.

See also:

`igraph_subisomorphic_vf2()`, `igraph_count_isomorphisms_vf2()`,
`igraph_get_isomorphisms_vf2()`,

Time complexity: exponential, what did you expect?

Example 17.1. File `examples/simple/igraph_isomorphic_vf2.c`

igraph_count_isomorphisms_vf2 — Number of isomorphisms via VF2

```
igraph_error_t igraph_count_isomorphisms_vf2(const igraph_t *graph1, const igraph_t *graph2,
                                             const igraph_vector_int_t *vertex_color1,
                                             const igraph_vector_int_t *vertex_color2,
                                             const igraph_vector_int_t *edge_color1,
                                             const igraph_vector_int_t *edge_color2,
                                             igraph_integer_t *count,
                                             igraph_isocompat_t *node_compat_fn,
                                             igraph_isocompat_t *edge_compat_fn,
                                             void *arg);
```

This function counts the number of isomorphic mappings between two graphs. It uses the generic `igraph_get_isomorphisms_vf2_callback()` function.

Arguments:

<i>graph1</i> :	The first input graph, may be directed or undirected.
<i>graph2</i> :	The second input graph, it must have the same directedness as <i>graph1</i> , or an error will be reported.

<i>vertex_color1</i> :	An optional color vector for the first graph. If color vectors are given for both graphs, then the isomorphism is calculated on the colored graphs; i.e. two vertices can match only if their color also matches. Supply a null pointer here if your graphs are not colored.
<i>vertex_color2</i> :	An optional color vector for the second graph. See the previous argument for explanation.
<i>edge_color1</i> :	An optional edge color vector for the first graph. The matching edges in the two graphs must have matching colors as well. Supply a null pointer here if your graphs are not edge-colored.
<i>edge_color2</i> :	The edge color vector for the second graph.
<i>count</i> :	Point to an integer, the result will be stored here.
<i>node_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two nodes are compatible.
<i>edge_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two edges are compatible.
<i>arg</i> :	Extra argument to supply to functions <i>node_compat_fn</i> and <i>edge_compat_fn</i> .

Returns:

Error code.

Time complexity: exponential.

igraph_get_isomorphisms_vf2 — Collect all isomorphic mappings of two graphs.

```
igraph_error_t igraph_get_isomorphisms_vf2(const igraph_t *graph1,
                                           const igraph_t *graph2,
                                           const igraph_vector_int_t *vertex_color1,
                                           const igraph_vector_int_t *vertex_color2,
                                           const igraph_vector_int_t *edge_color1,
                                           const igraph_vector_int_t *edge_color2,
                                           igraph_vector_int_list_t *maps,
                                           igraph_isocompat_t *node_compat_fn,
                                           igraph_isocompat_t *edge_compat_fn,
                                           void *arg);
```

This function finds all the isomorphic mappings between two simple graphs. It uses the `igraph_get_isomorphisms_vf2_callback()` function. Call the function with the same graph as *graph1* and *graph2* to get automorphisms.

Arguments:

<i>graph1</i> :	The first input graph, may be directed or undirected.
<i>graph2</i> :	The second input graph, it must have the same directedness as <i>graph1</i> , or an error will be reported.
<i>vertex_color1</i> :	An optional color vector for the first graph. If color vectors are given for both graphs, then the isomorphism is calculated on the colored graphs; i.e. two

vertices can match only if their color also matches. Supply a null pointer here if your graphs are not colored.

<i>vertex_color2</i> :	An optional color vector for the second graph. See the previous argument for explanation.
<i>edge_color1</i> :	An optional edge color vector for the first graph. The matching edges in the two graphs must have matching colors as well. Supply a null pointer here if your graphs are not edge-colored.
<i>edge_color2</i> :	The edge color vector for the second graph.
<i>maps</i> :	Pointer to a list of integer vectors. On return it is empty if the input graphs are not isomorphic. Otherwise it contains pointers to <code>igraph_vector_int_t</code> objects, each vector is an isomorphic mapping of <i>graph2</i> to <i>graph1</i> .
<i>node_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two nodes are compatible.
<i>edge_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two edges are compatible.
<i>arg</i> :	Extra argument to supply to functions <i>node_compat_fn</i> and <i>edge_compat_fn</i> .

Returns:

Error code.

Time complexity: exponential.

igraph_get_isomorphisms_vf2_callback — The generic VF2 interface

```
igraph_error_t igraph_get_isomorphisms_vf2_callback(  
    const igraph_t *graph1, const igraph_t *graph2,  
    const igraph_vector_int_t *vertex_color1, const igraph_vector_int_t *vertex_color2,  
    const igraph_vector_int_t *edge_color1, const igraph_vector_int_t *edge_color2,  
    igraph_vector_int_t *map12, igraph_vector_int_t *map21,  
    igraph_isohandler_t *isohandler_fn, igraph_isocompat_t *node_compat_fn,  
    igraph_isocompat_t *edge_compat_fn, void *arg  
);
```

This function is an implementation of the VF2 isomorphism algorithm, see P. Foggia, C. Sansone, M. Vento, An Improved algorithm for matching large graphs, Proc. of the 3rd IAPR-TC-15 International Workshop on Graph-based Representations, Italy, 2001.

For using it you need to define a callback function of type `igraph_isohandler_t`. This function will be called whenever VF2 finds an isomorphism between the two graphs. The mapping between the two graphs will be also provided to this function. If the callback returns `IGRAPH_SUCCESS`, then the search is continued, otherwise it stops. `IGRAPH_STOP` as a return value can be used to indicate normal premature termination; any other return value will be treated as an `igraph` error code, making the caller function return the same error code as well. The callback function must not destroy the mapping vectors that are passed to it.

Arguments:

<i>graph1</i> :	The first input graph.
<i>graph2</i> :	The second input graph.
<i>vertex_color1</i> :	An optional color vector for the first graph. If color vectors are given for both graphs, then the isomorphism is calculated on the colored graphs; i.e. two vertices can match only if their color also matches. Supply a null pointer here if your graphs are not colored.
<i>vertex_color2</i> :	An optional color vector for the second graph. See the previous argument for explanation.
<i>edge_color1</i> :	An optional edge color vector for the first graph. The matching edges in the two graphs must have matching colors as well. Supply a null pointer here if your graphs are not edge-colored.
<i>edge_color2</i> :	The edge color vector for the second graph.
<i>map12</i> :	Pointer to an initialized vector or NULL. If not NULL and the supplied graphs are isomorphic then the permutation taking <i>graph1</i> to <i>graph2</i> is stored here. If not NULL and the graphs are not isomorphic then a zero-length vector is returned.
<i>map21</i> :	This is the same as <i>map12</i> , but for the permutation taking <i>graph2</i> to <i>graph1</i> .
<i>isohandler_fn</i> :	The callback function to be called if an isomorphism is found. See also <code>igraph_isohandler_t</code> .
<i>node_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two nodes are compatible.
<i>edge_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two edges are compatible.
<i>arg</i> :	Extra argument to supply to functions <i>isohandler_fn</i> , <i>node_compat_fn</i> and <i>edge_compat_fn</i> .

Returns:

Error code.

Time complexity: exponential.

`igraph_isohandler_t` — Callback type, called when an isomorphism was found

```
typedef igraph_error_t igraph_isohandler_t(const igraph_vector_int_t *map12,  
      const igraph_vector_int_t *map21, void *arg);
```

See the details at the documentation of `igraph_get_isomorphisms_vf2_callback()`.

Arguments:

map12: The mapping from the first graph to the second.

map21: The mapping from the second graph to the first, the inverse of *map12* basically.

arg: This extra argument was passed to `igraph_get_isomorphisms_vf2_callback()` when it was called.

Returns:

IGRAPH_SUCCESS to continue the search, IGRAPH_STOP to terminate the search. Any other return value is interpreted as an igraph error code, which will then abort the search and return the same error code from the caller function.

igraph_isocompat_t — Callback type, called to check whether two vertices or edges are compatible

```
typedef igraph_bool_t igraph_isocompat_t(const igraph_t *graph1,
    const igraph_t *graph2,
    const igraph_integer_t g1_num,
    const igraph_integer_t g2_num,
    void *arg);
```

VF2 (subgraph) isomorphism functions can be restricted by defining relations on the vertices and/or edges of the graphs, and then checking whether the vertices (edges) match according to these relations.

This feature is implemented by two callbacks, one for vertices, one for edges. Every time igraph tries to match a vertex (edge) of the first (sub)graph to a vertex of the second graph, the vertex (edge) compatibility callback is called. The callback returns a logical value, giving whether the two vertices match.

Both callback functions are of type `igraph_isocompat_t`.

Arguments:

graph1: The first graph.

graph2: The second graph.

g1_num: The id of a vertex or edge in the first graph.

g2_num: The id of a vertex or edge in the second graph.

arg: Extra argument to pass to the callback functions.

Returns:

Logical scalar, whether vertex (or edge) *g1_num* in *graph1* is compatible with vertex (or edge) *g2_num* in *graph2*.

igraph_subisomorphic_vf2 — Decide subgraph isomorphism using VF2

```
igraph_error_t igraph_subisomorphic_vf2(const igraph_t *graph1, const igraph_t *graph2,
    const igraph_vector_int_t *vertex_color1,
```

```
const igraph_vector_int_t *vertex_color2,  
const igraph_vector_int_t *edge_color1,  
const igraph_vector_int_t *edge_color2,  
igraph_bool_t *iso, igraph_vector_int_t *map12,  
igraph_vector_int_t *map21,  
igraph_isocompat_t *node_compat_fn,  
igraph_isocompat_t *edge_compat_fn,  
void *arg);
```

Decides whether a subgraph of *graph1* is isomorphic to *graph2*. It uses `igraph_get_subisomorphisms_vf2_callback()`.

Arguments:

<i>graph1</i> :	The first input graph, may be directed or undirected. This is supposed to be the larger graph.
<i>graph2</i> :	The second input graph, it must have the same directedness as <i>graph1</i> . This is supposed to be the smaller graph.
<i>vertex_color1</i> :	An optional color vector for the first graph. If color vectors are given for both graphs, then the subgraph isomorphism is calculated on the colored graphs; i.e. two vertices can match only if their color also matches. Supply a null pointer here if your graphs are not colored.
<i>vertex_color2</i> :	An optional color vector for the second graph. See the previous argument for explanation.
<i>edge_color1</i> :	An optional edge color vector for the first graph. The matching edges in the two graphs must have matching colors as well. Supply a null pointer here if your graphs are not edge-colored.
<i>edge_color2</i> :	The edge color vector for the second graph.
<i>iso</i> :	Pointer to a boolean. The result of the decision problem is stored here.
<i>map12</i> :	Pointer to a vector or NULL. If not NULL, then an isomorphic mapping from <i>graph1</i> to <i>graph2</i> is stored here.
<i>map21</i> :	Pointer to a vector or NULL. If not NULL, then an isomorphic mapping from <i>graph2</i> to <i>graph1</i> is stored here.
<i>node_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two nodes are compatible.
<i>edge_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two edges are compatible.
<i>arg</i> :	Extra argument to supply to functions <i>node_compat_fn</i> and <i>edge_compat_fn</i> .

Returns:

Error code.

Time complexity: exponential.

igraph_count_subisomorphisms_vf2 — Number of subgraph isomorphisms using VF2

```
igraph_error_t igraph_count_subisomorphisms_vf2(const igraph_t *graph1, const igraph_t *graph2,
                                                const igraph_vector_int_t *vertex_color1,
                                                const igraph_vector_int_t *vertex_color2,
                                                const igraph_vector_int_t *edge_color1,
                                                const igraph_vector_int_t *edge_color2,
                                                igraph_integer_t *count,
                                                igraph_isocompat_t *node_compat_fn,
                                                igraph_isocompat_t *edge_compat_fn,
                                                void *arg);
```

Count the number of isomorphisms between subgraphs of *graph1* and *graph2*. This function uses `igraph_get_subisomorphisms_vf2_callback()`.

Arguments:

<i>graph1</i> :	The first input graph, may be directed or undirected. This is supposed to be the larger graph.
<i>graph2</i> :	The second input graph, it must have the same directedness as <i>graph1</i> . This is supposed to be the smaller graph.
<i>vertex_color1</i> :	An optional color vector for the first graph. If color vectors are given for both graphs, then the subgraph isomorphism is calculated on the colored graphs; i.e. two vertices can match only if their color also matches. Supply a null pointer here if your graphs are not colored.
<i>vertex_color2</i> :	An optional color vector for the second graph. See the previous argument for explanation.
<i>edge_color1</i> :	An optional edge color vector for the first graph. The matching edges in the two graphs must have matching colors as well. Supply a null pointer here if your graphs are not edge-colored.
<i>edge_color2</i> :	The edge color vector for the second graph.
<i>count</i> :	Pointer to an integer. The number of subgraph isomorphisms is stored here.
<i>node_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two nodes are compatible.
<i>edge_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two edges are compatible.
<i>arg</i> :	Extra argument to supply to functions <i>node_compat_fn</i> and <i>edge_compat_fn</i> .

Returns:

Error code.

Time complexity: exponential.

igraph_get_subisomorphisms_vf2 — Return all subgraph isomorphic mappings.

```
igraph_error_t igraph_get_subisomorphisms_vf2(const igraph_t *graph1,
```

```
const igraph_t *graph2,  
const igraph_vector_int_t *vertex_color1,  
const igraph_vector_int_t *vertex_color2,  
const igraph_vector_int_t *edge_color1,  
const igraph_vector_int_t *edge_color2,  
igraph_vector_int_list_t *maps,  
igraph_isocompat_t *node_compat_fn,  
igraph_isocompat_t *edge_compat_fn,  
void *arg);
```

This function collects all isomorphic mappings of *graph2* to a subgraph of *graph1*. It uses the `igraph_get_subisomorphisms_vf2_callback()` function. The graphs should be simple.

Arguments:

<i>graph1</i> :	The first input graph, may be directed or undirected. This is supposed to be the larger graph.
<i>graph2</i> :	The second input graph, it must have the same directedness as <i>graph1</i> . This is supposed to be the smaller graph.
<i>vertex_color1</i> :	An optional color vector for the first graph. If color vectors are given for both graphs, then the subgraph isomorphism is calculated on the colored graphs; i.e. two vertices can match only if their color also matches. Supply a null pointer here if your graphs are not colored.
<i>vertex_color2</i> :	An optional color vector for the second graph. See the previous argument for explanation.
<i>edge_color1</i> :	An optional edge color vector for the first graph. The matching edges in the two graphs must have matching colors as well. Supply a null pointer here if your graphs are not edge-colored.
<i>edge_color2</i> :	The edge color vector for the second graph.
<i>maps</i> :	Pointer to a list of integer vectors. On return it contains pointers to <code>igraph_vector_int_t</code> objects, each vector is an isomorphic mapping of <i>graph2</i> to a subgraph of <i>graph1</i> .
<i>node_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two nodes are compatible.
<i>edge_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two edges are compatible.
<i>arg</i> :	Extra argument to supply to functions <i>node_compat_fn</i> and <i>edge_compat_fn</i> .

Returns:

Error code.

Time complexity: exponential.

igraph_get_subisomorphisms_vf2_callback — Generic VF2 function for subgraph isomorphism problems

```
igraph_error_t igraph_get_subisomorphisms_vf2_callback(  
    const igraph_t *graph1, const igraph_t *graph2,  
    const igraph_vector_int_t *vertex_color1, const igraph_vector_int_t *vertex_color2,  
    const igraph_vector_int_t *edge_color1, const igraph_vector_int_t *edge_color2,  
    igraph_vector_int_t *map12, igraph_vector_int_t *map21,  
    igraph_isohandler_t *isohandler_fn, igraph_isocompat_t *node_compat_fn,  
    igraph_isocompat_t *edge_compat_fn, void *arg  
);
```

This function is the pair of `igraph_get_isomorphisms_vf2_callback()`, for subgraph isomorphism problems. It searches for subgraphs of *graph1* which are isomorphic to *graph2*. When it finds an isomorphic mapping it calls the supplied callback *isohandler_fn*. The mapping (and its inverse) and the additional *arg* argument are supplied to the callback.

Arguments:

<i>graph1</i> :	The first input graph, may be directed or undirected. This is supposed to be the larger graph.
<i>graph2</i> :	The second input graph, it must have the same directedness as <i>graph1</i> . This is supposed to be the smaller graph.
<i>vertex_color1</i> :	An optional color vector for the first graph. If color vectors are given for both graphs, then the subgraph isomorphism is calculated on the colored graphs; i.e. two vertices can match only if their color also matches. Supply a null pointer here if your graphs are not colored.
<i>vertex_color2</i> :	An optional color vector for the second graph. See the previous argument for explanation.
<i>edge_color1</i> :	An optional edge color vector for the first graph. The matching edges in the two graphs must have matching colors as well. Supply a null pointer here if your graphs are not edge-colored.
<i>edge_color2</i> :	The edge color vector for the second graph.
<i>map12</i> :	Pointer to a vector or NULL. If not NULL, then an isomorphic mapping from <i>graph1</i> to <i>graph2</i> is stored here.
<i>map21</i> :	Pointer to a vector or NULL. If not NULL, then an isomorphic mapping from <i>graph2</i> to <i>graph1</i> is stored here.
<i>isohandler_fn</i> :	A pointer to a function of type <code>igraph_isohandler_t</code> . This will be called whenever a subgraph isomorphism is found. If the function returns <code>IGRAPH_SUCCESS</code> , then the search is continued. If the function returns <code>IGRAPH_STOP</code> , the search is terminated normally. Any other value is treated as an igraph error code.
<i>node_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two nodes are compatible.
<i>edge_compat_fn</i> :	A pointer to a function of type <code>igraph_isocompat_t</code> . This function will be called by the algorithm to determine whether two edges are compatible.
<i>arg</i> :	Extra argument to supply to functions <i>isohandler_fn</i> , <i>node_compat_fn</i> and <i>edge_compat_fn</i> .

Returns:

Error code.

Time complexity: exponential.

Deprecated aliases

igraph_isomorphic_function_vf2 — The generic VF2 interface (deprecated alias).

```
igraph_error_t igraph_isomorphic_function_vf2(
    const igraph_t *graph1, const igraph_t *graph2,
    const igraph_vector_int_t *vertex_color1, const igraph_vector_int_t *vertex_color2,
    const igraph_vector_int_t *edge_color1, const igraph_vector_int_t *edge_color2,
    igraph_vector_int_t *map12, igraph_vector_int_t *map21,
    igraph_isohandler_t *isohandler_fn, igraph_isocompat_t *node_compat_fn,
    igraph_isocompat_t *edge_compat_fn, void *arg
);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_get_isomorphisms_vf2_callback()` instead.

igraph_subisomorphic_function_vf2 — Generic VF2 function for subgraph isomorphism problems (deprecated alias).

```
igraph_error_t igraph_subisomorphic_function_vf2(
    const igraph_t *graph1, const igraph_t *graph2,
    const igraph_vector_int_t *vertex_color1, const igraph_vector_int_t *vertex_color2,
    const igraph_vector_int_t *edge_color1, const igraph_vector_int_t *edge_color2,
    igraph_vector_int_t *map12, igraph_vector_int_t *map21,
    igraph_isohandler_t *isohandler_fn, igraph_isocompat_t *node_compat_fn,
    igraph_isocompat_t *edge_compat_fn, void *arg
);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_get_subisomorphisms_vf2_callback()` instead.

The LAD algorithm

The LAD algorithm can search for a subgraph in a larger graph, or check if two graphs are isomorphic. See Christine Solnon: AllDifferent-based Filtering for Subgraph Isomorphism. Artificial Intelligence, 174(12-13):850-864, 2010. <https://doi.org/10.1016/j.artint.2010.05.002> as well as the homepage of the LAD library at <http://liris.cnrs.fr/csolnon/LAD.html> The implementation in igraph is based on LADv1, but it is modified to use igraph's own memory allocation and error handling.

LAD uses the concept of domains to indicate vertex compatibility when matching the pattern graph. Domains can be used to implement matching of colored vertices.

LAD works with both directed and undirected graphs. Graphs with multi-edges are not supported.

igraph_subisomorphic_lad — Check subgraph isomorphism with the LAD algorithm

```
igraph_error_t igraph_subisomorphic_lad(const igraph_t *pattern, const igraph_t
                                     const igraph_vector_int_list_t *domains,
                                     igraph_bool_t *iso, igraph_vector_int_t *map,
                                     igraph_vector_int_list_t *maps,
                                     igraph_bool_t induced, igraph_integer_t time_limit)
```

Check whether *pattern* is isomorphic to a subgraph of *target*. The original LAD implementation by Christine Solnon was used as the basis of this code.

See more about LAD at <http://liris.cnrs.fr/csolnon/LAD.html> and in Christine Solnon: AllDifferent-based Filtering for Subgraph Isomorphism. Artificial Intelligence, 174(12-13):850-864, 2010. <https://doi.org/10.1016/j.artint.2010.05.002>

Arguments:

<i>pattern</i> :	The smaller graph, it can be directed or undirected.
<i>target</i> :	The bigger graph, it can be directed or undirected.
<i>domains</i> :	A pointer vector, or a null pointer. If a pointer vector, then it must contain pointers to <code>igraph_vector_int_t</code> objects and the length of the vector must match the number of vertices in the <i>pattern</i> graph. For each vertex, the IDs of the compatible vertices in the target graph are listed.
<i>iso</i> :	Pointer to a boolean, or a null pointer. If not a null pointer, then the boolean is set to <code>true</code> if a subgraph isomorphism is found, and to <code>false</code> otherwise.
<i>map</i> :	Pointer to a vector or a null pointer. If not a null pointer and a subgraph isomorphism is found, the matching vertices from the target graph are listed here, for each vertex (in vertex ID order) from the pattern graph.
<i>maps</i> :	Pointer to a list of integer vectors or a null pointer. If not a null pointer, then all subgraph isomorphisms are stored in the vector list, in <code>igraph_vector_int_t</code> objects.
<i>induced</i> :	Boolean, whether to search for induced matching subgraphs.
<i>time_limit</i> :	Processor time limit in seconds. Supply zero here for no limit. If the time limit is over, then the function signals an error.

Returns:

Error code

See also:

`igraph_subisomorphic_vf2()` for the VF2 algorithm.

Time complexity: exponential.

Example 17.2. File `examples/simple/igraph_subisomorphic_lad.c`

Functions for small graphs

igraph_isoclass — Determine the isomorphism class of small graphs.

```
igraph_error_t igraph_isoclass(const igraph_t *graph, igraph_integer_t *isoclass)
```

All graphs with a given number of vertices belong to a number of isomorphism classes, with every graph in a given class being isomorphic to each other.

This function gives the isomorphism class (a number) of a graph. Two graphs have the same isomorphism class if and only if they are isomorphic.

The first isomorphism class is numbered zero and it contains the edgeless graph. The last isomorphism class contains the full graph. The number of isomorphism classes for directed graphs with three vertices is 16 (between 0 and 15), for undirected graph it is only 4. For graphs with four vertices it is 218 (directed) and 11 (undirected). For 5 and 6 vertex undirected graphs, it is 34 and 156, respectively. These values can also be retrieved using `igraph_graph_count()`. For more information, see <https://oeis.org/A000273> and <https://oeis.org/A000088>.

At the moment, 3- and 4-vertex directed graphs and 3 to 6 vertex undirected graphs are supported.

Multi-edges and self-loops are ignored by this function.

Arguments:

graph: The graph object.

isoclass: Pointer to an integer, the isomorphism class will be stored here.

Returns:

Error code.

See also:

`igraph_isomorphic()`, `igraph_isoclass_subgraph()`, `igraph_isoclass_create()`, `igraph_motifs_randesu()`.

Because of some limitations this function works only for graphs with three or four vertices.

Time complexity: $O(|E|)$, the number of edges in the graph.

igraph_isoclass_subgraph — The isomorphism class of a subgraph of a graph.

```
igraph_error_t igraph_isoclass_subgraph(const igraph_t *graph, const igraph_vector_t *vids, igraph_integer_t *isoclass);
```

This function identifies the isomorphism class of the subgraph induced the vertices specified in *vids*.

At the moment, 3- and 4-vertex directed graphs and 3 to 6 vertex undirected graphs are supported.

Multi-edges and self-loops are ignored by this function.

Arguments:

graph: The graph object.

vids: A vector containing the vertex IDs to be considered as a subgraph. Each vertex ID should be included at most once.

isoclass: Pointer to an integer, this will be set to the isomorphism class.

Returns:

Error code.

See also:

`igraph_isoclass()`, `igraph_isomorphic()`, `igraph_isoclass_create()`.

Time complexity: $O((d+n)*n)$, d is the average degree in the network, and n is the number of vertices in *vids*.

igraph_isoclass_create — Creates a graph from the given isomorphism class.

```
igraph_error_t igraph_isoclass_create(igraph_t *graph, igraph_integer_t size,
                                      igraph_integer_t number, igraph_bool_t directed);
```

This function creates the canonical representative graph of the given isomorphism class.

The isomorphism class is an integer between 0 and the number of unique unlabeled (i.e. non-isomorphic) graphs on the given number of vertices and give directedness. See <https://oeis.org/A000273> and <https://oeis.org/A000088> for the number of directed and undirected graphs on *size* nodes.

At the moment, 3- and 4-vertex directed graphs and 3 to 6 vertex undirected graphs are supported.

Arguments:

graph: Pointer to an uninitialized graph object.

size: The number of vertices to add to the graph.

number: The isomorphism class.

directed: Logical constant, whether to create a directed graph.

Returns:

Error code.

See also:

`igraph_isoclass()`, `igraph_isoclass_subgraph()`, `igraph_isomorphic()`.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges in the graph to create.

igraph_graph_count — The number of unlabelled graphs on the given number of vertices.

```
igraph_error_t igraph_graph_count(igraph_integer_t n, igraph_bool_t directed, igraph_integer_t *count);
```

Gives the number of unlabelled *simple* graphs on the specified number of vertices. The "isoclass" of a graph of this size is at most one less than this value.

This function is meant to be used in conjunction with `isoclass` and motif finder functions. It will only work for small n values for which the result is representable in an `igraph_integer_t`. For larger n values, an overflow error is raised.

Arguments:

n: The number of vertices.

directed: Boolean, whether to consider directed graphs.

count: Pointer to an integer, the result will be stored here.

Returns:

Error code.

See also:

`igraph_isoclass()`, `igraph_motifs_randesu_callback()`.

Time complexity: $O(1)$.

Utility functions

igraph_permute_vertices — Permute the vertices.

```
igraph_error_t igraph_permute_vertices(const igraph_t *graph, igraph_t *res,
                                       const igraph_vector_int_t *permutation);
```

This function creates a new graph from the input graph by permuting its vertices according to the specified mapping. Call this function with the output of `igraph_canonical_permutation()` to create the canonical form of a graph.

Arguments:

graph: The input graph.

res: Pointer to an uninitialized graph object. The new graph is created here.

permutation: The permutation to apply. Vertex 0 is mapped to the first element of the vector, vertex 1 to the second, etc.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in terms of the number of vertices and edges.

igraph_simplify_and_colorize — Simplify the graph and compute self-loop and edge multiplicities.

```
igraph_error_t igraph_simplify_and_colorize(  
    const igraph_t *graph, igraph_t *res,  
    igraph_vector_int_t *vertex_color, igraph_vector_int_t *edge_color);
```

This function creates a vertex and edge colored simple graph from the input graph. The vertex colors are computed as the number of incident self-loops to each vertex in the input graph. The edge colors are computed as the number of parallel edges in the input graph that were merged to create each edge in the simple graph.

The resulting colored simple graph is suitable for use by isomorphism checking algorithms such as VF2, which only support simple graphs, but can consider vertex and edge colors.

Arguments:

graph: The graph object, typically having self-loops or multi-edges.
res: An uninitialized graph object. The result will be stored here
vertex_color: Computed vertex colors corresponding to self-loop multiplicities.
edge_color: Computed edge colors corresponding to edge multiplicities

Returns:

Error code.

See also:

`igraph_simplify()`, `igraph_isomorphic_vf2()`, `igraph_subisomorphic_vf2()`

Deprecated functions

igraph_isomorphic_34 — Graph isomorphism for 3-4 vertices (deprecated alias).

```
igraph_error_t igraph_isomorphic_34(  
    const igraph_t *graph1, const igraph_t *graph2, igraph_bool_t *iso  
);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_isomorphic()` instead.

If you really care about performance and you *know* for sure that your input graphs are simple and have either 3 or 4 vertices for directed graphs, or 3-6 vertices for undirected graphs, you can compare their isomorphism classes obtained from `igraph_isoclass()` directly instead of calling `igraph_isomorphic()`; this saves the cost of checking whether the graphs do not contain multiple edges or self-loops.

Arguments:

graph1: The first input graph.

graph2: The second input graph. Must have the same directedness as *graph1*.

iso: Pointer to a boolean, the result is stored here.

Returns:

Error code.

Time complexity: $O(1)$.

Chapter 18. Graph coloring

igraph_vertex_coloring_greedy — Computes a vertex coloring using a greedy algorithm.

```
igraph_error_t igraph_vertex_coloring_greedy(const igraph_t *graph, igraph_vector_t &colors)
```

This function assigns a "color"—represented as a non-negative integer—to each vertex of the graph in such a way that neighboring vertices never have the same color. The obtained coloring is not necessarily minimal.

Vertices are colored one by one, choosing the smallest color index that differs from that of already colored neighbors. Colors are represented with non-negative integers 0, 1, 2, ...

Arguments:

graph: The input graph.

colors: Pointer to an initialized integer vector. The vertex colors will be stored here.

heuristic: The vertex ordering heuristic to use during greedy coloring. See `igraph_coloring_greedy_t`

Returns:

Error code.

Example 18.1. File `examples/simple/igraph_coloring.c`

igraph_coloring_greedy_t — Ordering heuristics for greedy graph coloring.

```
typedef enum {  
    IGRAPH_COLORING_GREEDY_COLORED_NEIGHBORS = 0  
} igraph_coloring_greedy_t;
```

Ordering heuristics for `igraph_vertex_coloring_greedy()`.

Values:

<code>IGRAPH_COLORING_GREEDY_COLORED_NEIGHBORS</code> :	Choose vertex with largest number of already colored neighbors.
---	---

igraph_is_perfect — Checks if the graph is perfect.

```
igraph_error_t igraph_is_perfect(const igraph_t *graph, igraph_bool_t *perfect)
```

A perfect graph is an undirected graph in which the chromatic number of every induced subgraph equals the order of the largest clique of that subgraph. The chromatic number of a graph G is the smallest number of colors needed to color the vertices of G so that no two adjacent vertices share the same color.

Warning: This function may create the complement of the graph internally, which consumes a lot of memory. For moderately sized graphs, consider decomposing them into biconnected components and running the check separately on each component.

This implementation is based on the strong perfect graph theorem which was conjectured by Claude Berge and proved by Maria Chudnovsky, Neil Robertson, Paul Seymour, and Robin Thomas.

Arguments:

graph: The input graph. It is expected to be undirected and simple.

perfect: Pointer to an integer, the result will be stored here.

Returns:

Error code.

Time complexity: worst case exponential, often faster in practice.

Chapter 19. Graph motifs, dyad census and triad census

This section deals with functions which find small induced subgraphs in a graph. These were first defined for subgraphs of two and three vertices by Holland and Leinhardt, and named dyad census and triad census.

igraph_dyad_census — Calculating the dyad census as defined by Holland and Leinhardt.

```
igraph_error_t igraph_dyad_census(const igraph_t *graph, igraph_real_t *mut,
                                   igraph_real_t *asym, igraph_real_t *null);
```

Dyad census means classifying each pair of vertices of a directed graph into three categories: mutual (there is at least one edge from a to b and also from b to a); asymmetric (there is at least one edge either from a to b or from b to a, but not the other way) and null (no edges between a and b in either direction).

Holland, P.W. and Leinhardt, S. (1970). A Method for Detecting Structure in Sociometric Data. American Journal of Sociology, 70, 492-513.

Arguments:

graph: The input graph. For an undirected graph, there are no asymmetric connections.

mut: Pointer to a real, the number of mutual dyads is stored here.

asym: Pointer to a real, the number of asymmetric dyads is stored here.

null: Pointer to a real, the number of null dyads is stored here.

Returns:

Error code.

See also:

`igraph_reciprocity()`, `igraph_triad_census()`.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

igraph_triad_census — Triad census, as defined by Davis and Leinhardt

```
igraph_error_t igraph_triad_census(const igraph_t *graph, igraph_vector_t *res)
```

Calculating the triad census means classifying every triple of vertices in a directed graph. A triple can be in one of 16 states:

- 003 A, B, C, the empty graph.
- 012 A->B, C, a graph with a single directed edge.
- 102 A<->B, C, a graph with a mutual connection between two vertices.
- 021D A<-B->C, the binary out-tree.
- 021U A->B<-C, the binary in-tree.
- 021C A->B->C, the directed line.
- 111D A<->B<-C.
- 111U A<->B->C.
- 030T A->B<-C, A->C.
- 030C A<-B<-C, A->C.
- 201 A<->B<->C.
- 120D A<-B->C, A<->C.
- 120U A->B<-C, A<->C.
- 120C A->B->C, A<->C.
- 210 A->B<->C, A<->C.
- 300 A<->B<->C, A<->C, the complete graph.

See also Davis, J.A. and Leinhardt, S. (1972). The Structure of Positive Interpersonal Relations in Small Groups. In J. Berger (Ed.), Sociological Theories in Progress, Volume 2, 218-251. Boston: Houghton Mifflin.

This function calls `igraph_motifs_randesu()` which is an implementation of the FANMOD motif finder tool, see `igraph_motifs_randesu()` for details. Note that the order of the triads is not the same for `igraph_triad_census()` and `igraph_motifs_randesu()`.

Arguments:

- graph*: The input graph. A warning is given for undirected graphs, as the result is undefined for those.
- res*: Pointer to an initialized vector, the result is stored here in the same order as given in the list above. Note that this order is different than the one used by `igraph_motifs_randesu()`.

Returns:

Error code.

See also:

`igraph_motifs_randesu()`, `igraph_dyad_census()`.

Time complexity: TODO.

Finding triangles

igraph_adjacent_triangles — Count the number of triangles a vertex is part of.

```
igraph_error_t igraph_adjacent_triangles(const igraph_t *graph,
                                         igraph_vector_t *res,
                                         const igraph_vs_t vids);
```

Arguments:

graph: The input graph. Edge directions and multiplicities are ignored.

res: Initilized vector, the results are stored here.

vids: The vertices to perform the calculation for.

Returns:

Error mode.

See also:

`igraph_list_triangles()` to list them.

Time complexity: $O(d^2 n)$, d is the average vertex degree of the queried vertices, n is their number.

igraph_list_triangles — Find all triangles in a graph.

```
igraph_error_t igraph_list_triangles(const igraph_t *graph,
                                     igraph_vector_int_t *res);
```

The triangles are reported as a long list of vertex ID triplets. Use the `int` variant of `igraph_matrix_view_from_vector()` to create a matrix view into the vector where each triangle is stored in a column of the matrix (see the example).

Arguments:

graph: The input graph, edge directions are ignored. Multiple edges are ignored.

res: Pointer to an initialized integer vector, the result is stored here, in a long list of triples of vertex IDs. Each triple is a triangle in the graph. Each triangle is listed exactly once.

Returns:

Error code.

See also:

`igraph_transitivity_undirected()` to count the triangles, `igraph_adjacent_triangles()` to count the triangles a vertex participates in.

Time complexity: $O(d^2 n)$, d is the average degree, n is the number of vertices.

Example 19.1. File `examples/simple/igraph_list_triangles.c`

Graph motifs

`igraph_motifs_randesu` — Count the number of motifs in a graph.

```
igraph_error_t igraph_motifs_randesu(const igraph_t *graph, igraph_vector_t *hist,
                                     igraph_integer_t size, const igraph_vector_t *cut_prob)
```

Motifs are small weakly connected induced subgraphs of a given structure in a graph. It is argued that the motif profile (i.e. the number of different motifs in the graph) is characteristic for different types of networks and network function is related to the motifs in the graph.

This function is able to find directed motifs of sizes three and four and undirected motifs of sizes three to six (i.e. the number of different subgraphs with three to six vertices in the network).

In a big network the total number of motifs can be very large, so it takes a lot of time to find all of them. In this case, a sampling method can be used. This function is capable of doing sampling via the `cut_prob` argument. This argument gives the probability that a branch of the motif search tree will not be explored. See S. Wernicke and F. Rasche: FANMOD: a tool for fast network motif detection, *Bioinformatics* 22(9), 1152--1153, 2006 for details. <https://doi.org/10.1093/bioinformatics/btl038>

Set the `cut_prob` argument to a zero vector for finding all motifs.

Directed motifs will be counted in directed graphs and undirected motifs in undirected graphs.

Arguments:

- graph*: The graph to find the motifs in.
- hist*: The result of the computation, it gives the number of motifs found for each isomorphism class. See `igraph_isoclass()` for help about isomorphism classes. Note that this function does *not* count isomorphism classes that are not connected and will report NaN (more precisely `IGRAPH_NAN`) for them.
- size*: The size of the motifs to search for. For directed graphs, only 3 and 4 are implemented, for undirected, 3 to 6. The limitation is not in the motif finding code, but the graph isomorphism code.
- cut_prob*: Vector of probabilities for cutting the search tree at a given level. The first element is the first level, etc. Supply all zeros here (of length *size*) to find all motifs in a graph.

Returns:

Error code.

See also:

`igraph_motifs_randesu_estimate()` for estimating the number of motifs in a graph, this can help to set the `cut_prob` parameter; `igraph_motifs_randesu_no()` to calculate the total number of motifs of a given size in a graph; `igraph_motifs_randesu_callback()` for calling a callback function for every motif found; `igraph_subisomorphic_lad()` for finding subgraphs on more than 4 (directed) or 6 (undirected) vertices; `igraph_graph_count()` to find the number of graph on a given number of vertices, i.e. the length of the `hist` vector.

Time complexity: TODO.

Example 19.2. File `examples/simple/igraph_motifs_randesu.c`

`igraph_motifs_randesu_no` — Count the total number of motifs in a graph.

```
igraph_error_t igraph_motifs_randesu_no(const igraph_t *graph, igraph_integer_t
                                         igraph_integer_t size, const igraph_vector_t *cut_
```

This function counts the total number of motifs in a graph, i.e. the number of of (weakly) connected triplets or quadruplets, without assigning isomorphism classes to them.

Arguments:

graph: The graph object to study.

no: Pointer to an integer type, the result will be stored here.

size: The size of the motifs to count.

cut_prob: Vector giving the probabilities that a branch of the search tree will be cut at a given level.

Returns:

Error code.

See also:

`igraph_motifs_randesu()`, `igraph_motifs_randesu_estimate()`.

Time complexity: TODO.

`igraph_motifs_randesu_estimate` — Estimate the total number of motifs in a graph.

```
igraph_error_t igraph_motifs_randesu_estimate(const igraph_t *graph, igraph_int
                                              igraph_integer_t size, const igraph_vector_t
                                              igraph_integer_t sample_size,
```

```
const igraph_vector_int_t *parsample);
```

This function estimates the total number of weakly connected induced subgraphs, called motifs, of a fixed number of vertices. For example, an undirected complete graph on n vertices will have one motif of size n , and n motifs of size $n - 1$. As another example, one triangle and a separate vertex will have zero motifs of size four.

This function is useful for large graphs for which it is not feasible to count all the different motifs, because there are very many of them.

The total number of motifs is estimated by taking a sample of vertices and counts all motifs in which these vertices are included. (There is also a *cut_prob* parameter which gives the probabilities to cut a branch of the search tree.)

Directed motifs will be counted in directed graphs and undirected motifs in undirected graphs.

Arguments:

<i>graph</i> :	The graph object to study.
<i>est</i> :	Pointer to an integer type, the result will be stored here.
<i>size</i> :	The size of the motifs to look for.
<i>cut_prob</i> :	Vector giving the probabilities to cut a branch of the search tree and omit counting the motifs in that branch. It contains a probability for each level. Supply <i>size</i> zeros here to count all the motifs in the sample.
<i>sample_size</i> :	The number of vertices to use as the sample. This parameter is only used if the <i>parsample</i> argument is a null pointer.
<i>parsample</i> :	Either pointer to an initialized vector or a null pointer. If a vector then the vertex IDs in the vector are used as a sample. If a null pointer then the <i>sample_size</i> argument is used to create a sample of vertices drawn with uniform probability.

Returns:

Error code.

See also:

`igraph_motifs_randesu()`, `igraph_motifs_randesu_no()`.

Time complexity: TODO.

igraph_motifs_randesu_callback — Finds motifs in a graph and calls a function for each of them.

```
igraph_error_t igraph_motifs_randesu_callback(const igraph_t *graph, igraph_int_t size,
                                              const igraph_vector_t *cut_prob, igraph_motif_cb_t cb,
                                              void* extra);
```

Similarly to `igraph_motifs_randesu()`, this function is able to find directed motifs of sizes three and four and undirected motifs of sizes three to six (i.e. the number of different subgraphs with three to six vertices in the network). However, instead of counting them, the function will call a callback function for each motif found to allow further tests or post-processing.

The `cut_prob` argument also allows sampling the motifs, just like for `igraph_motifs_randesu()`. Set the `cut_prob` argument to a zero vector for finding all motifs.

Arguments:

- graph*: The graph to find the motifs in.
- size*: The size of the motifs to search for. Only three and four are implemented currently. The limitation is not in the motif finding code, but the graph isomorphism code.
- cut_prob*: Vector of probabilities for cutting the search tree at a given level. The first element is the first level, etc. Supply all zeros here (of length `size`) to find all motifs in a graph.
- callback*: A pointer to a function of type `igraph_motifs_handler_t`. This function will be called whenever a new motif is found.
- extra*: Extra argument to pass to the callback function.

Returns:

Error code.

Time complexity: TODO.

Example 19.3. File `examples/simple/igraph_motifs_randesu.c`

igraph_motifs_handler_t — Callback type for igraph_motifs_randesu_callback

```
typedef igraph_error_t igraph_motifs_handler_t(const igraph_t *graph,
        igraph_vector_int_t *vids,
        igraph_integer_t isoclass,
        void* extra);
```

`igraph_motifs_randesu_callback()` calls a specified callback function whenever a new motif is found during a motif search. This callback function must be of type `igraph_motifs_handler_t`. It has the following arguments:

Arguments:

- graph*: The graph that that algorithm is working on. Of course this must not be modified.
- vids*: The IDs of the vertices in the motif that has just been found. This vector is owned by the motif search algorithm, so do not modify or destroy it; make a copy of it if you need it later.
- isoclass*: The isomorphism class of the motif that has just been found. Use `igraph_graph_count()` to find the maximum possible isoclass for graphs of a given size. See `igraph_isoclass` and `igraph_isoclass_subgraph` for more information.
- extra*: The extra argument that was passed to `igraph_motifs_randesu_callback()`.

Returns:

IGRAPH_SUCCESS to continue the motif search, IGRAPH_STOP to stop the motif search and return to the caller normally. Any other return value is interpreted as an igraph error code, which will terminate the search and return the same error code to the caller.

See also:

`igraph_motifs_randesu_callback()`

Chapter 20. Generating layouts for graph drawing

2D layout generators

Layout generator functions (or at least most of them) try to place the vertices and edges of a graph on a 2D plane or in 3D space in a way which visually pleases the human eye.

They take a graph object and a number of parameters as arguments and return an `igraph_matrix_t`, in which each row gives the coordinates of a vertex.

`igraph_layout_random` — Places the vertices uniformly randomly on a plane.

```
igraph_error_t igraph_layout_random(const igraph_t *graph, igraph_matrix_t *res)
```

Arguments:

graph: Pointer to an initialized graph object.

res: Pointer to an initialized matrix object. This will contain the result and will be resized as needed.

Returns:

Error code. The current implementation always returns with success.

Time complexity: $O(|V|)$, the number of vertices.

`igraph_layout_circle` — Places the vertices uniformly on a circle, in the order of vertex IDs.

```
igraph_error_t igraph_layout_circle(const igraph_t *graph, igraph_matrix_t *res,
                                     igraph_vs_t order);
```

Arguments:

graph: Pointer to an initialized graph object.

res: Pointer to an initialized matrix object. This will contain the result and will be resized as needed.

order: The order of the vertices on the circle. The vertices not included here, will be placed at (0,0). Supply `igraph_vss_all()` here for all vertices, in the order of their vertex IDs.

Returns:

Error code.

Time complexity: $O(|V|)$, the number of vertices.

igraph_layout_star — Generates a star-like layout.

```
igraph_error_t igraph_layout_star(const igraph_t *graph, igraph_matrix_t *res,  
                                igraph_integer_t center, const igraph_vector_int_t *order);
```

Arguments:

- graph*: The input graph. Its edges are ignored by this function.
- res*: Pointer to an initialized matrix object. This will contain the result and will be resized as needed.
- center*: The id of the vertex to put in the center. You can set it to any arbitrary value for the special case when the input graph has no vertices; otherwise it must be between 0 and the number of vertices minus 1.
- order*: A numeric vector giving the order of the vertices (including the center vertex!). If a null pointer, then the vertices are placed in increasing vertex ID order.

Returns:

Error code.

Time complexity: $O(|V|)$, linear in the number of vertices.

See also:

`igraph_layout_circle()` and other layout generators.

igraph_layout_grid — Places the vertices on a regular grid on the plane.

```
igraph_error_t igraph_layout_grid(const igraph_t *graph, igraph_matrix_t *res, igraph_integer_t width);
```

Arguments:

- graph*: Pointer to an initialized graph object.
- res*: Pointer to an initialized matrix object. This will contain the result and will be resized as needed.
- width*: The number of vertices in a single row of the grid. When zero or negative, the width of the grid will be the square root of the number of vertices, rounded up if needed.

Returns:

Error code. The current implementation always returns with success.

Time complexity: $O(|V|)$, the number of vertices.

igraph_layout_graphopt — Optimizes vertex layout via the graphopt algorithm.

```
igraph_error_t igraph_layout_graphopt(const igraph_t *graph, igraph_matrix_t *res,
                                      igraph_integer_t niter,
                                      igraph_real_t node_charge, igraph_real_t node_mass,
                                      igraph_real_t spring_length,
                                      igraph_real_t spring_constant,
                                      igraph_real_t max_sa_movement,
                                      igraph_bool_t use_seed);
```

This is a port of the graphopt layout algorithm by Michael Schmuhl. graphopt version 0.4.1 was rewritten in C and the support for layers was removed (might be added later) and a code was a bit reorganized to avoid some unnecessary steps is the node charge (see below) is zero.

Graphopt uses physical analogies for defining attracting and repelling forces among the vertices and then the physical system is simulated until it reaches an equilibrium. (There is no simulated annealing or anything like that, so a stable fixed point is not guaranteed.)

See also <http://www.schmuhl.org/graphopt/> for the original graphopt.

Arguments:

<i>graph</i> :	The input graph.
<i>res</i> :	Pointer to an initialized matrix, the result will be stored here and its initial contents are used as the starting point of the simulation if the <i>use_seed</i> argument is true. Note that in this case the matrix should have the proper size, otherwise a warning is issued and the supplied values are ignored. If no starting positions are given (or they are invalid) then a random starting position is used. The matrix will be resized if needed.
<i>niter</i> :	Integer constant, the number of iterations to perform. Should be a couple of hundred in general. If you have a large graph then you might want to only do a few iterations and then check the result. If it is not good enough you can feed it in again in the <i>res</i> argument. The original graphopt default is 500.
<i>node_charge</i> :	The charge of the vertices, used to calculate electric repulsion. The original graphopt default is 0.001.
<i>node_mass</i> :	The mass of the vertices, used for the spring forces. The original graphopt defaults to 30.
<i>spring_length</i> :	The length of the springs. The original graphopt defaults to zero.
<i>spring_constant</i> :	The spring constant, the original graphopt defaults to one.
<i>max_sa_movement</i> :	Real constant, it gives the maximum amount of movement allowed in a single step along a single axis. The original graphopt default is 5.
<i>use_seed</i> :	Logical scalar, whether to use the positions in <i>res</i> as a starting configuration. See also <i>res</i> above.

Returns:

Error code.

Time complexity: $O(n(|V|^2+|E|))$, n is the number of iterations, $|V|$ is the number of vertices, $|E|$ the number of edges. If *node_charge* is zero then it is only $O(n|E|)$.

igraph_layout_bipartite — Simple layout for bipartite graphs.

```
igraph_error_t igraph_layout_bipartite(const igraph_t *graph,
                                       const igraph_vector_bool_t *types,
                                       igraph_matrix_t *res, igraph_real_t hgap,
                                       igraph_real_t vgap, igraph_integer_t maxiter);
```

The layout is created by first placing the vertices in two rows, according to their types. Then the positions within the rows are optimized to minimize edge crossings, by calling `igraph_layout_sugiyama()`.

Arguments:

- graph*: The input graph.
- types*: A boolean vector containing ones and zeros, the vertex types. Its length must match the number of vertices in the graph.
- res*: Pointer to an initialized matrix, the result, the x and y coordinates are stored here.
- hgap*: The preferred minimum horizontal gap between vertices in the same layer (i.e. vertices of the same type).
- vgap*: The distance between layers.
- maxiter*: Maximum number of iterations in the crossing minimization stage. 100 is a reasonable default; if you feel that you have too many edge crossings, increase this.

Returns:

Error code.

See also:

`igraph_layout_sugiyama()`.

The DrL layout generator

DrL is a sophisticated layout generator developed and implemented by Shawn Martin et al. As of October 2012 the original DrL homepage is unfortunately not available. You can read more about this algorithm in the following technical report: Martin, S., Brown, W.M., Klavans, R., Boyack, K.W., DrL: Distributed Recursive (Graph) Layout. SAND Reports, 2008. 2936: p. 1-10.

Only a subset of the complete DrL functionality is included in igraph, parallel runs and recursive, multi-level layouting is not supported.

The parameters of the layout are stored in an `igraph_layout_drl_options_t` structure, this can be initialized by calling the function `igraph_layout_drl_options_init()`. The fields

of this structure can then be adjusted by hand if needed. The layout is calculated by an `igraph_layout_drl()` call.

igraph_layout_drl_options_t — Parameters for the DrL layout generator

```
typedef struct igraph_layout_drl_options_t {
    igraph_real_t    edge_cut;
    igraph_integer_t init_iterations;
    igraph_real_t    init_temperature;
    igraph_real_t    init_attraction;
    igraph_real_t    init_damping_mult;
    igraph_integer_t liquid_iterations;
    igraph_real_t    liquid_temperature;
    igraph_real_t    liquid_attraction;
    igraph_real_t    liquid_damping_mult;
    igraph_integer_t expansion_iterations;
    igraph_real_t    expansion_temperature;
    igraph_real_t    expansion_attraction;
    igraph_real_t    expansion_damping_mult;
    igraph_integer_t cooldown_iterations;
    igraph_real_t    cooldown_temperature;
    igraph_real_t    cooldown_attraction;
    igraph_real_t    cooldown_damping_mult;
    igraph_integer_t crunch_iterations;
    igraph_real_t    crunch_temperature;
    igraph_real_t    crunch_attraction;
    igraph_real_t    crunch_damping_mult;
    igraph_integer_t simmer_iterations;
    igraph_real_t    simmer_temperature;
    igraph_real_t    simmer_attraction;
    igraph_real_t    simmer_damping_mult;
} igraph_layout_drl_options_t;
```

Values:

<code>edge_cut</code> :	The edge cutting parameter. Edge cutting is done in the late stages of the algorithm in order to achieve less dense layouts. Edges are cut if there is a lot of stress on them (a large value in the objective function sum). The edge cutting parameter is a value between 0 and 1 with 0 representing no edge cutting and 1 representing maximal edge cutting. The default value is 32/40.
<code>init_iterations</code> :	Number of iterations, initial phase.
<code>init_temperature</code> :	Start temperature, initial phase.
<code>init_attraction</code> :	Attraction, initial phase.
<code>init_damping_mult</code> :	Damping factor, initial phase.
<code>liquid_iterations</code> :	Number of iterations in the liquid phase.
<code>liquid_temperature</code> :	Start temperature in the liquid phase.
<code>liquid_attraction</code> :	Attraction in the liquid phase.

<code>liquid_damping_mult:</code>	Multiplicatie damping factor, liquid phase.
<code>expansion_iterations:</code>	Number of iterations in the expansion phase.
<code>expansion_temperature:</code>	Start temperature in the expansion phase.
<code>expansion_attraction:</code>	Attraction, expansion phase.
<code>expansion_damping_mult:</code>	Damping factor, expansion phase.
<code>cooldown_iterations:</code>	Number of iterations in the cooldown phase.
<code>cooldown_temperature:</code>	Start temperature in the cooldown phase.
<code>cooldown_attraction:</code>	Attraction in the cooldown phase.
<code>cooldown_damping_mult:</code>	Damping fact int the cooldown phase.
<code>crunch_iterations:</code>	Number of iterations in the crunch phase.
<code>crunch_temperature:</code>	Start temperature in the crunch phase.
<code>crunch_attraction:</code>	Attraction in the crunch phase.
<code>crunch_damping_mult:</code>	Damping factor in the crunch phase.
<code>simmer_iterations:</code>	Number of iterations in the simmer phase.
<code>simmer_temperature:</code>	Start temperature in te simmer phase.
<code>simmer_attraction:</code>	Attraction in the simmer phase.
<code>simmer_damping_mult:</code>	Multiplicative damping factor in the simmer phase.

igraph_layout_drl_default_t — Predefined parameter templates for the DrL layout generator

```
typedef enum { IGRAPH_LAYOUT_DRL_DEFAULT = 0,
               IGRAPH_LAYOUT_DRL_COARSEN,
               IGRAPH_LAYOUT_DRL_COARSEST,
               IGRAPH_LAYOUT_DRL_REFINE,
               IGRAPH_LAYOUT_DRL_FINAL
             } igraph_layout_drl_default_t;
```

These constants can be used to initialize a set of DrL parameters. These can then be modified according to the user's needs.

Values:

<code>IGRAPH_LAYOUT_DRL_DEFAULT:</code>	The deafult parameters.
<code>IGRAPH_LAYOUT_DRL_COARSEN:</code>	Slightly modified parameters to get a coarser layout.
<code>IGRAPH_LAYOUT_DRL_COARSEST:</code>	An even coarser layout.

IGRAPH_LAYOUT_DRL_REFINE: Refine an already calculated layout.

IGRAPH_LAYOUT_DRL_FINAL: Finalize an already refined layout.

igraph_layout_drl_options_init — Initialize parameters for the DrL layout generator

```
igraph_error_t igraph_layout_drl_options_init(igraph_layout_drl_options_t *options,
                                              igraph_layout_drl_default_t templ);
```

This function can be used to initialize the struct holding the parameters for the DrL layout generator. There are a number of predefined templates available, it is a good idea to start from one of these by modifying some parameters.

Arguments:

options: The struct to initialize.

templ: The template to use. Currently the following templates are supplied: IGRAPH_LAYOUT_DRL_DEFAULT, IGRAPH_LAYOUT_DRL_COARSEN, IGRAPH_LAYOUT_DRL_COARSEST, IGRAPH_LAYOUT_DRL_REFINE and IGRAPH_LAYOUT_DRL_FINAL.

Returns:

Error code.

Time complexity: $O(1)$.

igraph_layout_drl — The DrL layout generator

```
igraph_error_t igraph_layout_drl(const igraph_t *graph, igraph_matrix_t *res,
                                igraph_bool_t use_seed,
                                const igraph_layout_drl_options_t *options,
                                const igraph_vector_t *weights);
```

This function implements the force-directed DrL layout generator. Please see more in the following technical report: Martin, S., Brown, W.M., Klavans, R., Boyack, K.W., DrL: Distributed Recursive (Graph) Layout. SAND Reports, 2008. 2936: p. 1-10.

Arguments:

graph: The input graph.

use_seed: Logical scalar, if true, then the coordinates supplied in the *res* argument are used as starting points.

res: Pointer to a matrix, the result layout is stored here. It will be resized as needed.

options: The parameters to pass to the layout generator.

weights: Edge weights, pointer to a vector. If this is a null pointer then every edge will have the same weight.

Returns:

Error code.

Time complexity: ???.

igraph_layout_drl_3d — The DrL layout generator, 3d version.

```
igraph_error_t igraph_layout_drl_3d(const igraph_t *graph, igraph_matrix_t *res,
                                     igraph_bool_t use_seed,
                                     const igraph_layout_drl_options_t *options,
                                     const igraph_vector_t *weights);
```

This function implements the force-directed DrL layout generator. Please see more in the technical report: Martin, S., Brown, W.M., Klavans, R., Boyack, K.W., DrL: Distributed Recursive (Graph) Layout. SAND Reports, 2008. 2936: p. 1-10.

This function uses a modified DrL generator that does the layout in three dimensions.

Arguments:

graph: The input graph.

use_seed: Logical scalar, if true, then the coordinates supplied in the *res* argument are used as starting points.

res: Pointer to a matrix, the result layout is stored here. It will be resized as needed.

options: The parameters to pass to the layout generator.

weights: Edge weights, pointer to a vector. If this is a null pointer then every edge will have the same weight.

Returns:

Error code.

Time complexity: ???.

See also:

`igraph_layout_drl()` for the standard 2d version.

igraph_layout_fruchterman_reingold — Places the vertices on a plane according to the Fruchterman-Reingold algorithm.

```
igraph_error_t igraph_layout_fruchterman_reingold(const igraph_t *graph,
                                                    igraph_matrix_t *res,
                                                    igraph_bool_t use_seed,
                                                    igraph_integer_t niter,
                                                    igraph_real_t start_temp,
```

```
igraph_layout_grid_t grid,
const igraph_vector_t *weight,
const igraph_vector_t *minx,
const igraph_vector_t *maxx,
const igraph_vector_t *miny,
const igraph_vector_t *maxy);
```

This is a force-directed layout that simulates an attractive force f_a between connected vertex pairs and a repulsive force f_r between all vertex pairs. The forces are computed as a function of the distance d between the two vertices as

$$f_a(d) = -w * d^2 \text{ and } f_r(d) = 1/d,$$

where w represents the edge weight. The equilibrium distance of two connected vertices is thus $1/w^3$, assuming no other forces acting on them.

In disconnected graphs, `igraph` effectively inserts a weak connection of weight $n^{(-3/2)}$ between all pairs of vertices, where n is the vertex count. This ensures that components are kept near each other.

Reference:

Fruchterman, T.M.J. and Reingold, E.M.: Graph Drawing by Force-directed Placement. *Software -- Practice and Experience*, 21/11, 1129--1164, 1991. <https://doi.org/10.1002/spe.4380211102>

Arguments:

- graph*: Pointer to an initialized graph object.
- res*: Pointer to an initialized matrix object. This will contain the result and will be re-sized as needed.
- use_seed*: Logical, if true the supplied values in the *res* argument are used as an initial layout, if false a random initial layout is used.
- niter*: The number of iterations to do. A reasonable default value is 500.
- start_temp*: Start temperature. This is the maximum amount of movement allowed along one axis, within one step, for a vertex. Currently it is decreased linearly to zero during the iteration.
- grid*: Whether to use the (fast but less accurate) grid based version of the algorithm. Possible values: `IGRAPH_LAYOUT_GRID`, `IGRAPH_LAYOUT_NOGRID`, `IGRAPH_LAYOUT_AUTOGRID`. The last one uses the grid based version only for large graphs, currently the ones with more than 1000 vertices.
- weight*: Pointer to a vector containing edge weights, the attraction along the edges will be multiplied by these. Weights must be positive. It will be ignored if it is a null-pointer.
- minx*: Pointer to a vector, or a NULL pointer. If not a NULL pointer then the vector gives the minimum “x” coordinate for every vertex.
- maxx*: Same as *minx*, but the maximum “x” coordinates.
- miny*: Pointer to a vector, or a NULL pointer. If not a NULL pointer then the vector gives the minimum “y” coordinate for every vertex.
- maxy*: Same as *miny*, but the maximum “y” coordinates.

Returns:

Error code.

Time complexity: $O(|V|^2)$ in each iteration, $|V|$ is the number of vertices in the graph.

igraph_layout_kamada_kawai — Places the vertices on a plane according to the Kamada-Kawai algorithm.

```
igraph_error_t igraph_layout_kamada_kawai(const igraph_t *graph, igraph_matrix_t *res,
                                          igraph_bool_t use_seed, igraph_integer_t maxiter,
                                          igraph_real_t epsilon, igraph_real_t kkconst,
                                          const igraph_vector_t *weights,
                                          const igraph_vector_t *minx, const igraph_vector_t *miny,
                                          const igraph_vector_t *maxx, const igraph_vector_t *maxy)
```

This is a force-directed layout. A spring is inserted between all pairs of vertices, both those which are directly connected and those that are not. The unstretched length of springs is chosen based on the undirected graph distance between the corresponding pair of vertices. Thus, in a weighted graph, increasing the weight between two vertices pushes them apart. The Young modulus of springs is inversely proportional to the graph distance, ensuring that springs between far-apart vertices will have a smaller effect on the layout.

This layout works particularly well for locally connected spatial networks such as lattices.

This layout algorithm is not suitable for large graphs. The memory requirements are of the order $O(|V|^2)$.

Reference:

Kamada, T. and Kawai, S.: An Algorithm for Drawing General Undirected Graphs. Information Processing Letters, 31/1, 7--15, 1989. [https://doi.org/10.1016/0020-0190\(89\)90102-6](https://doi.org/10.1016/0020-0190(89)90102-6)

Arguments:

<i>graph</i> :	A graph object.
<i>res</i> :	Pointer to an initialized matrix object. This will contain the result (x-positions in column zero and y-positions in column one) and will be resized if needed.
<i>use_seed</i> :	Boolean, whether to use the values supplied in the <i>res</i> argument as the initial configuration. If zero and there are any limits on the X or Y coordinates, then a random initial configuration is used. Otherwise the vertices are placed on a circle of radius 1 as the initial configuration.
<i>maxiter</i> :	The maximum number of iterations to perform. A reasonable default value is at least ten (or more) times the number of vertices.
<i>epsilon</i> :	Stop the iteration, if the maximum delta value of the algorithm is smaller than still. It is safe to leave it at zero, and then <i>maxiter</i> iterations are performed.
<i>kkconst</i> :	The Kamada-Kawai vertex attraction constant. Typical value: number of vertices.
<i>weights</i> :	Edge weights, larger values will result longer edges. Weights must be positive. Pass NULL to assume unit weights for all edges.
<i>minx</i> :	Pointer to a vector, or a NULL pointer. If not a NULL pointer then the vector gives the minimum “x” coordinate for every vertex.

maxx: Same as *minx*, but the maximum “x” coordinates.

miny: Pointer to a vector, or a NULL pointer. If not a NULL pointer then the vector gives the minimum “y” coordinate for every vertex.

maxy: Same as *miny*, but the maximum “y” coordinates.

Returns:

Error code.

Time complexity: $O(|V|)$ for each iteration, after an $O(|V|^2 \log|V|)$ initialization step. $|V|$ is the number of vertices in the graph.

igraph_layout_gem — Layout graph according to GEM algorithm.

```
igraph_error_t igraph_layout_gem(const igraph_t *graph, igraph_matrix_t *res,
                                igraph_bool_t use_seed, igraph_integer_t maxiter,
                                igraph_real_t temp_max, igraph_real_t temp_min,
                                igraph_real_t temp_init);
```

The GEM layout algorithm, as described in Arne Frick, Andreas Ludwig, Heiko Mehldau: A Fast Adaptive Layout Algorithm for Undirected Graphs, Proc. Graph Drawing 1994, LNCS 894, pp. 388-403, 1995.

Arguments:

graph: The input graph. Edge directions are ignored in directed graphs.

res: The result is stored here. If the *use_seed* argument is true (non-zero), then this matrix is also used as the starting point of the algorithm.

use_seed: Boolean, whether to use the supplied coordinates in *res* as the starting point. If false (zero), then a uniform random starting point is used.

maxiter: The maximum number of iterations to perform. Updating a single vertex counts as an iteration. A reasonable default is $40 * n * n$, where n is the number of vertices. The original paper suggests $4 * n * n$, but this usually only works if the other parameters are set up carefully.

temp_max: The maximum allowed local temperature. A reasonable default is the number of vertices.

temp_min: The global temperature at which the algorithm terminates (even before reaching *maxiter* iterations). A reasonable default is 1/10.

temp_init: Initial local temperature of all vertices. A reasonable default is the square root of the number of vertices.

Returns:

Error code.

Time complexity: $O(t * n * (n+e))$, where n is the number of vertices, e is the number of edges and t is the number of time steps performed.

igraph_layout_davidson_harel — Davidson-Harel layout algorithm

```
igraph_error_t igraph_layout_davidson_harel(const igraph_t *graph, igraph_matrix_t *res,
                                             igraph_bool_t use_seed, igraph_integer_t maxiter,
                                             igraph_integer_t fineiter, igraph_real_t cool_fact,
                                             igraph_real_t weight_node_dist, igraph_real_t weight_border,
                                             igraph_real_t weight_edge_lengths,
                                             igraph_real_t weight_edge_crossings,
                                             igraph_real_t weight_node_edge_dist);
```

This function implements the algorithm by Davidson and Harel, see Ron Davidson, David Harel: Drawing Graphs Nicely Using Simulated Annealing. ACM Transactions on Graphics 15(4), pp. 301-331, 1996.

The algorithm uses simulated annealing and a sophisticated energy function, which is unfortunately hard to parameterize for different graphs. The original publication did not disclose any parameter values, and the ones below were determined by experimentation.

The algorithm consists of two phases, an annealing phase, and a fine-tuning phase. There is no simulated annealing in the second phase.

Our implementation tries to follow the original publication, as much as possible. The only major difference is that coordinates are explicitly kept within the bounds of the rectangle of the layout.

Arguments:

<i>graph</i> :	The input graph, edge directions are ignored.
<i>res</i> :	A matrix, the result is stored here. It can be used to supply start coordinates, see <i>use_seed</i> .
<i>use_seed</i> :	Boolean, whether to use the supplied <i>res</i> as start coordinates.
<i>maxiter</i> :	The maximum number of annealing iterations. A reasonable value for smaller graphs is 10.
<i>fineiter</i> :	The number of fine tuning iterations. A reasonable value is $\max(10, \log_2(n))$ where n is the number of vertices.
<i>cool_fact</i> :	Cooling factor. A reasonable value is 0.75.
<i>weight_node_dist</i> :	Weight for the node-node distances component of the energy function. Reasonable value: 1.0.
<i>weight_border</i> :	Weight for the distance from the border component of the energy function. It can be set to zero, if vertices are allowed to sit on the border.
<i>weight_edge_lengths</i> :	Weight for the edge length component of the energy function, a reasonable value is the density of the graph divided by 10.
<i>weight_edge_crossings</i> :	Weight for the edge crossing component of the energy function, a reasonable default is 1 minus the square root of the density of the graph.
<i>weight_node_edge_dist</i> :	Weight for the node-edge distance component of the energy function. A reasonable value is 1 minus the density, divided by 5.

Returns:

Error code.

Time complexity: one first phase iteration has time complexity $O(n^2+m^2)$, one fine tuning iteration has time complexity $O(mn)$. Time complexity might be smaller if some of the weights of the components of the energy function are set to zero.

igraph_layout_mds — Place the vertices on a plane using multidimensional scaling.

```
igraph_error_t igraph_layout_mds(const igraph_t* graph, igraph_matrix_t *res,  
                                const igraph_matrix_t *dist, igraph_integer_t dim);
```

This layout requires a distance matrix, where the intersection of row i and column j specifies the desired distance between vertex i and vertex j . The algorithm will try to place the vertices in a space having a given number of dimensions in a way that approximates the distance relations prescribed in the distance matrix. igraph uses the classical multidimensional scaling by Torgerson; for more details, see Cox & Cox: Multidimensional Scaling (1994), Chapman and Hall, London.

If the input graph is disconnected, igraph will decompose it first into its subgraphs, lay out the subgraphs one by one using the appropriate submatrices of the distance matrix, and then merge the layouts using `igraph_layout_merge_dla`. Since `igraph_layout_merge_dla` works for 2D layouts only, you cannot run the MDS layout on disconnected graphs for more than two dimensions.

Warning: if the graph is symmetric to the exchange of two vertices (as is the case with leaves of a tree connecting to the same parent), classical multidimensional scaling may assign the same coordinates to these vertices.

Arguments:

graph: A graph object.

res: Pointer to an initialized matrix object. This will contain the result and will be resized if needed.

dist: The distance matrix. It must be symmetric and this function does not check whether the matrix is indeed symmetric. Results are unspecified if you pass a non-symmetric matrix here. You can set this parameter to null; in this case, the shortest path lengths between vertices will be used as distances.

dim: The number of dimensions in the embedding space. For 2D layouts, supply 2 here.

Returns:

Error code.

Added in version 0.6.

Time complexity: usually around $O(|V|^2 \dim)$.

igraph_layout_lgl — Force based layout algorithm for large graphs.

```
igraph_error_t igraph_layout_lgl(const igraph_t *graph, igraph_matrix_t *res,
                                igraph_integer_t maxit, igraph_real_t maxdelta,
                                igraph_real_t area, igraph_real_t coolexp,
                                igraph_real_t repulserad, igraph_real_t cellsize,
                                igraph_integer_t proot);
```

This is a layout generator similar to the Large Graph Layout algorithm and program (<http://lgl.sourceforge.net/>). But unlike LGL, this version uses a Fruchterman-Reingold style simulated annealing algorithm for placing the vertices. The speedup is achieved by placing the vertices on a grid and calculating the repulsion only for vertices which are closer to each other than a limit.

Arguments:

<i>graph</i> :	The (initialized) graph object to place. It must be connected; disconnected graphs are not handled by the algorithm.
<i>res</i> :	Pointer to an initialized matrix object to hold the result. It will be resized if needed.
<i>maxit</i> :	The maximum number of cooling iterations to perform for each layout step. A reasonable default is 150.
<i>maxdelta</i> :	The maximum length of the move allowed for a vertex in a single iteration. A reasonable default is the number of vertices.
<i>area</i> :	This parameter gives the area of the square on which the vertices will be placed. A reasonable default value is the number of vertices squared.
<i>coolexp</i> :	The cooling exponent. A reasonable default value is 1.5.
<i>repulserad</i> :	Determines the radius at which vertex-vertex repulsion cancels out attraction of adjacent vertices. A reasonable default value is <i>area</i> times the number of vertices.
<i>cellsize</i> :	The size of the grid cells, one side of the square. A reasonable default value is the fourth root of <i>area</i> (or the square root of the number of vertices if <i>area</i> is also left at its default value).
<i>proot</i> :	The root vertex, this is placed first, its neighbors in the first iteration, second neighbors in the second, etc. If negative then a random vertex is chosen.

Returns:

Error code.

Added in version 0.2.

Time complexity: ideally $O(\text{dia} \cdot \text{maxit} \cdot (|V| + |E|))$, $|V|$ is the number of vertices, dia is the diameter of the graph, worst case complexity is still $O(\text{dia} \cdot \text{maxit} \cdot (|V|^2 + |E|))$, this is the case when all vertices happen to be in the same grid cell.

Layouts for trees and acyclic graphs

igraph_layout_reingold_tilford — Reingold-Tilford layout for tree graphs

```
igraph_error_t igraph_layout_reingold_tilford(const igraph_t *graph,
```

```
igraph_matrix_t *res,  
igraph_neimode_t mode,  
const igraph_vector_int_t *roots,  
const igraph_vector_int_t *rootlevel);
```

Arranges the nodes in a tree where the given node is used as the root. The tree is directed downwards and the parents are centered above its children. For the exact algorithm, see:

Reingold, E and Tilford, J: Tidier drawing of trees. IEEE Trans. Softw. Eng., SE-7(2):223--228, 1981. <https://doi.org/10.1109/TSE.1981.234519>

If the given graph is not a tree, a breadth-first search is executed first to obtain a possible spanning tree.

Arguments:

- graph*: The graph object.
- res*: The result, the coordinates in a matrix. The parameter should point to an initialized matrix object and will be resized.
- mode*: Specifies which edges to consider when building the tree. If it is `IGRAPH_OUT` then only the outgoing, if it is `IGRAPH_IN` then only the incoming edges of a parent are considered. If it is `IGRAPH_ALL` then all edges are used (this was the behavior in igraph 0.5 and before). This parameter also influences how the root vertices are calculated, if they are not given. See the *roots* parameter.
- roots*: The index of the root vertex or root vertices. The set of roots should be specified so that all vertices of the graph are reachable from them. Simply put, in the undirected case, one root should be given from each connected component. If *roots* is `NULL` or a pointer to an empty vector, then the roots will be selected automatically. Currently, automatic root selection prefers low eccentricity vertices in graphs with fewer than 500 vertices, and high degree vertices (according to *mode*) in larger graphs. The root selection heuristic may change without notice. To ensure a consistent output, please specify the roots manually. The `igraph_roots_for_tree_layout()` function gives more control over automatic root selection.
- rootlevel*: This argument can be useful when drawing forests which are not trees (i.e. they are unconnected and have tree components). It specifies the level of the root vertices for every tree in the forest. It is only considered if not a null pointer and the *roots* argument is also given (and it is not a null pointer of an empty vector).

Returns:

Error code.

Added in version 0.2.

See also:

`igraph_layout_reingold_tilford_circular()`, `igraph_roots_for_tree_layout()`

Example	20.1.	File	examples/simple/
igraph_layout_reingold_tilford.c			

`igraph_layout_reingold_tilford_circular` — Circular Reingold-Tilford layout for trees

```
igraph_error_t igraph_layout_reingold_tilford_circular(const igraph_t *graph,
    igraph_matrix_t *res,
    igraph_neimode_t mode,
    const igraph_vector_int_t *roots,
    const igraph_vector_int_t *rootlevel);
```

This layout is almost the same as `igraph_layout_reingold_tilford()`, but the tree is drawn in a circular way, with the root vertex in the center.

Arguments:

- graph*: The graph object.
- res*: The result, the coordinates in a matrix. The parameter should point to an initialized matrix object and will be resized.
- mode*: Specifies which edges to consider when building the tree. If it is `IGRAPH_OUT` then only the outgoing, if it is `IGRAPH_IN` then only the incoming edges of a parent are considered. If it is `IGRAPH_ALL` then all edges are used (this was the behavior in igraph 0.5 and before). This parameter also influences how the root vertices are calculated, if they are not given. See the *roots* parameter.
- roots*: The index of the root vertex or root vertices. The set of roots should be specified so that all vertices of the graph are reachable from them. Simply put, in the undirected case, one root should be given from each connected component. If *roots* is `NULL` or a pointer to an empty vector, then the roots will be selected automatically. Currently, automatic root selection prefers low eccentricity vertices in graphs with fewer than 500 vertices, and high degree vertices (according to *mode*) in larger graphs. The root selection heuristic may change without notice. To ensure a consistent output, please specify the roots manually.
- rootlevel*: This argument can be useful when drawing forests which are not trees (i.e. they are unconnected and have tree components). It specifies the level of the root vertices for every tree in the forest. It is only considered if not a null pointer and the *roots* argument is also given (and it is not a null pointer or an empty vector).

Returns:

Error code.

See also:

`igraph_layout_reingold_tilford()`.

igraph_roots_for_tree_layout — Roots suitable for a nice tree layout.

```
igraph_error_t igraph_roots_for_tree_layout(
    const igraph_t *graph,
    igraph_neimode_t mode,
    igraph_vector_int_t *roots,
    igraph_root_choice_t heuristic);
```

This function chooses a root, or a set of roots suitable for visualizing a tree, or a tree-like graph. It is typically used with `igraph_layout_reingold_tilford()`. The principle is to select a minimal set of roots so that all other vertices will be reachable from them.

In the undirected case, one root is chosen from each connected component. In the directed case, one root is chosen from each strongly connected component that has no incoming (or outgoing) edges (depending on 'mode'). When more than one root choice is possible, vertices are prioritized based on the given *heuristic*.

Arguments:

<i>graph</i> :	The graph, typically a tree, but any graph is accepted.				
<i>mode</i> :	Whether to interpret the input as undirected, a directed out-tree or in-tree.				
<i>roots</i> :	An initialized integer vector, the roots will be returned here.				
<i>heuristic</i> :	The heuristic to use for breaking ties when multiple root choices are possible.				
	<table> <tr> <td>IGRAPH_ROOT_CHOICE_DEGREE</td><td>Choose the vertices with the highest degree (out- or in-degree in directed mode). This simple heuristic is fast even in large graphs.</td></tr> <tr> <td>IGRAPH_ROOT_CHOICE_ECCENTRICITY</td><td>Choose the vertices with the lowest eccentricity. This usually results in a "wide and shallow" tree layout. While this heuristic produces high-quality results, it is slow for large graphs: computing the eccentricities has quadratic complexity in the number of vertices.</td></tr> </table>	IGRAPH_ROOT_CHOICE_DEGREE	Choose the vertices with the highest degree (out- or in-degree in directed mode). This simple heuristic is fast even in large graphs.	IGRAPH_ROOT_CHOICE_ECCENTRICITY	Choose the vertices with the lowest eccentricity. This usually results in a "wide and shallow" tree layout. While this heuristic produces high-quality results, it is slow for large graphs: computing the eccentricities has quadratic complexity in the number of vertices.
IGRAPH_ROOT_CHOICE_DEGREE	Choose the vertices with the highest degree (out- or in-degree in directed mode). This simple heuristic is fast even in large graphs.				
IGRAPH_ROOT_CHOICE_ECCENTRICITY	Choose the vertices with the lowest eccentricity. This usually results in a "wide and shallow" tree layout. While this heuristic produces high-quality results, it is slow for large graphs: computing the eccentricities has quadratic complexity in the number of vertices.				

Returns:

Error code.

Time complexity: depends on the heuristic.

igraph_layout_sugiyama — Sugiyama layout algorithm for layered directed acyclic graphs.

```
igraph_error_t igraph_layout_sugiyama(const igraph_t *graph, igraph_matrix_t *res,
                                     igraph_t *extd_graph, igraph_vector_int_t *extd_to_o,
                                     const igraph_vector_int_t* layers, igraph_real_t hgap,
                                     igraph_integer_t maxiter, const igraph_vector_t *weights)
```

This layout algorithm is designed for directed acyclic graphs where each vertex is assigned to a layer. Layers are indexed from zero, and vertices of the same layer will be placed on the same horizontal line. The X coordinates of vertices within each layer are decided by the heuristic proposed by Sugiyama et al to minimize edge crossings.

You can also try to lay out undirected graphs, graphs containing cycles, or graphs without an a priori layered assignment with this algorithm. `igraph` will try to eliminate cycles and assign vertices to layers, but there is no guarantee on the quality of the layout in such cases.

The Sugiyama layout may introduce "bends" on the edges in order to obtain a visually more pleasing layout. This is achieved by adding dummy nodes to edges spanning more than one layer. The resulting

layout assigns coordinates not only to the nodes of the original graph but also to the dummy nodes. The layout algorithm will also return the extended graph with the dummy nodes. An edge in the original graph may either be mapped to a single edge in the extended graph or a *path* that starts and ends in the original source and target vertex and passes through multiple dummy vertices. In such cases, the user may also request the mapping of the edges of the extended graph back to the edges of the original graph.

For more details, see K. Sugiyama, S. Tagawa and M. Toda, "Methods for Visual Understanding of Hierarchical Systems". IEEE Transactions on Systems, Man and Cybernetics 11(2):109-125, 1981.

Arguments:

<i>graph</i> :	Pointer to an initialized graph object.
<i>res</i> :	Pointer to an initialized matrix object. This will contain the result and will be resized as needed. The first $ V $ rows of the layout will contain the coordinates of the original graph, the remaining rows contain the positions of the dummy nodes. Therefore, you can use the result both with <i>graph</i> or with <i>extended_graph</i> .
<i>extended_graph</i> :	Pointer to an uninitialized graph object or NULL. The extended graph with the added dummy nodes will be returned here. In this graph, each edge points downwards to lower layers, spans exactly one layer and the first $ V $ vertices coincide with the vertices of the original graph.
<i>extd_to_orig_eids</i> :	Pointer to a vector or NULL. If not NULL, the mapping from the edge IDs of the extended graph back to the edge IDs of the original graph will be stored here.
<i>layers</i> :	The layer index for each vertex or NULL if the layers should be determined automatically by igraph.
<i>hgap</i> :	The preferred minimum horizontal gap between vertices in the same layer.
<i>vgap</i> :	The distance between layers.
<i>maxiter</i> :	Maximum number of iterations in the crossing minimization stage. 100 is a reasonable default; if you feel that you have too many edge crossings, increase this.
<i>weights</i> :	Weights of the edges. These are used only if the graph contains cycles; igraph will tend to reverse edges with smaller weights when breaking the cycles.

igraph_layout_umap — Layout using Uniform Manifold Approximation and Projection for Dimension Reduction

```
igraph_error_t igraph_layout_umap(const igraph_t *graph,
                                  igraph_matrix_t *res,
                                  igraph_bool_t use_seed,
                                  const igraph_vector_t *distances,
                                  igraph_real_t min_dist,
                                  igraph_integer_t epochs,
                                  igraph_real_t sampling_prob);
```


UMAP is a mostly used to embed high-dimensional vectors in a low-dimensional space (most commonly by far, 2D). The algorithm is probabilistic and introduces nonlinearities, unlike e.g. PCA and similar to T-distributed Stochastic Neighbor Embedding (t-SNE). Nonlinearity helps "cluster" very similar vectors together without imposing a global geometry on the embedded space (e.g. a rigid rotation + compression in PCA).

However, UMAP uses a graph with distances associated to the edges as a key intermediate representation of the high-dimensional space, so it is also useful as a general graph layouting algorithm, hence its inclusion in *igraph*.

Importantly, the edge-associated distances are derived from a similarity metric between the high-dimensional vectors, often Pearson correlation:

```
corr(v1, v2) = v1 x v2 / [ sqrt(v1 x v1) * sqrt(v2 x v2) ]
```

In this case, the associated distance is usually defined as:

```
d(v1, v2) = 1 - corr(v1, v2)
```

This implementation can also work with unweighted similarity graphs, in which case the distance parameter should be a null pointer and all edges beget a similarity score of 1 (a distance of 0).

While all similarity graphs are theoretically embeddable, UMAP's stochastic gradient descent approach really shines when the graph is sparse. In practice, most people feed a k-nearest neighbor (either computed exactly or approximated) similarity graph with some additional cutoff to exclude "quasi-neighbors" that lie beyond a certain distance (e.g. correlation less than 0.2).

Therefore, if you are trying to use this function to embed high-dimensional vectors, the steps are:

1. Compute a sparse similarity graph (either exact or approximate) from your vectors, weighted or unweighted. If unsure, compute a knn.
2. If you keep the weights, convert them into distances or store them as a "weight" edge attribute and use a null pointer for the distances. If using similarity weights instead of distances, make sure they do not exceed 1.
3. Feed the graph (and distances, if you have them) into this function.

Note: Step 1 above involves deciding if two high-dimensional vectors "look similar" which, because of the curse of dimensionality, is in many cases a highly subjective and potentially controversial operation: thread with care and at your own risk. Two high-dimensional vectors might look similar or extremely different depending on the point of view/angle, and there are a lot of viewpoints when the dimensionality ramps up.

References:

Leland McInnes, John Healy, and James Melville. <https://arxiv.org/abs/1802.03426>

Arguments:

<i>graph</i> :	Pointer to the similarity graph to find a layout for (i.e. to embed).
<i>res</i> :	Pointer to the n by 2 matrix where the layout coordinates will be stored.
<i>use_seed</i> :	Logical, if true the supplied values in the <i>res</i> argument are used as an initial layout, if false a random initial layout is used.
<i>distances</i> :	Pointer to a vector of edge lengths. Similarity graphs for UMAP are often originally meant in terms of similarity weights (e.g. correlation between high-dimensional vectors) and converted into distances by crude $\text{dist} := 1 - \text{corr}$. That is fine here too. If this argument is a NULL pointer (NULL), all lengths are assumed equal.

<i>min_dist</i> :	A fudge parameter that decides how close two unconnected vertices can be in the embedding before feeling a repulsive force. It should be positive. Typically, 0.01 is a good number.
<i>epochs</i> :	Number of iterations of the main stochastic gradient descent loop on the cross-entropy. Usually, 500 epochs can be used if the graph is small (less than 50k edges), 50 epochs are used for larger graphs.
<i>sampling_prob</i> :	The fraction of vertices moved at each iteration of the stochastic gradient descent (epoch). At fixed number of epochs, a higher fraction makes the algorithm slower. Vice versa, a too low number will converge very slowly, possibly too slowly.

Returns:

Error code.

Warning

This function is experimental and its signature is not considered final yet. We reserve the right to change the function signature without changing the major version of igraph. Use it at your own risk.

3D layout generators

igraph_layout_random_3d — Places the vertices uniform randomly in a cube.

```
igraph_error_t igraph_layout_random_3d(const igraph_t *graph, igraph_matrix_t *
```

Vertex coordinates range from -1 to 1, and are placed in 3 columns of a matrix, with a row for each vertex.

Arguments:

graph: The graph to place.

res: Pointer to an initialized matrix object. It will be resized to hold the result.

Returns:

Error code. The current implementation always returns with success.

Added in version 0.2.

Time complexity: $O(|V|)$, the number of vertices.

igraph_layout_sphere — Places vertices (more or less) uniformly on a sphere.

```
igraph_error_t igraph_layout_sphere(const igraph_t *graph, igraph_matrix_t *res
```

The algorithm was described in the following paper: Distributing many points on a sphere by E.B. Saff and A.B.J. Kuijlaars, *Mathematical Intelligencer* 19.1 (1997) 5--11.

Arguments:

graph: Pointer to an initialized graph object.

res: Pointer to an initialized matrix object. This will contain the result and will be resized as needed.

Returns:

Error code. The current implementation always returns with success.

Added in version 0.2.

Time complexity: $O(|V|)$, the number of vertices in the graph.

igraph_layout_grid_3d — Places the vertices on a regular grid in the 3D space.

```
igraph_error_t igraph_layout_grid_3d(const igraph_t *graph, igraph_matrix_t *res,  
                                     igraph_integer_t width, igraph_integer_t height);
```

Arguments:

graph: Pointer to an initialized graph object.

res: Pointer to an initialized matrix object. This will contain the result and will be resized as needed.

width: The number of vertices in a single row of the grid. When zero or negative, the width is determined automatically.

height: The number of vertices in a single column of the grid. When zero or negative, the height is determined automatically.

Returns:

Error code. The current implementation always returns with success.

Time complexity: $O(|V|)$, the number of vertices.

igraph_layout_fruchterman_reingold_3d — 3D Fruchterman-Reingold algorithm.

```
igraph_error_t igraph_layout_fruchterman_reingold_3d(const igraph_t *graph,  
                                                      igraph_matrix_t *res,  
                                                      igraph_bool_t use_seed,  
                                                      igraph_integer_t niter,
```

```
igraph_real_t start_temp,  
const igraph_vector_t *weight,  
const igraph_vector_t *minx,  
const igraph_vector_t *maxx,  
const igraph_vector_t *miny,  
const igraph_vector_t *maxy,  
const igraph_vector_t *minz,  
const igraph_vector_t *maxz);
```

This is the 3D version of the force based Fruchterman-Reingold layout. See `igraph_layout_fruchterman_reingold()` for the 2D version.

Arguments:

- graph*: Pointer to an initialized graph object.
- res*: Pointer to an initialized matrix object. This will contain the result and will be re-sized as needed.
- use_seed*: Logical, if true the supplied values in the *res* argument are used as an initial layout, if false a random initial layout is used.
- niter*: The number of iterations to do. A reasonable default value is 500.
- start_temp*: Start temperature. This is the maximum amount of movement allowed along one axis, within one step, for a vertex. Currently it is decreased linearly to zero during the iteration.
- weight*: Pointer to a vector containing edge weights, the attraction along the edges will be multiplied by these. Weights must be positive. It will be ignored if it is a null-pointer.
- minx*: Pointer to a vector, or a NULL pointer. If not a NULL pointer then the vector gives the minimum “x” coordinate for every vertex.
- maxx*: Same as *minx*, but the maximum “x” coordinates.
- miny*: Pointer to a vector, or a NULL pointer. If not a NULL pointer then the vector gives the minimum “y” coordinate for every vertex.
- maxy*: Same as *miny*, but the maximum “y” coordinates.
- minz*: Pointer to a vector, or a NULL pointer. If not a NULL pointer then the vector gives the minimum “z” coordinate for every vertex.
- maxz*: Same as *minz*, but the maximum “z” coordinates.

Returns:

Error code.

Added in version 0.2.

Time complexity: $O(|V|^2)$ in each iteration, $|V|$ is the number of vertices in the graph.

`igraph_layout_kamada_kawai_3d` — 3D version of the Kamada-Kawai layout generator.

```
igraph_error_t igraph_layout_kamada_kawai_3d(const igraph_t *graph, igraph_matrix_t *res,
                                             igraph_bool_t use_seed, igraph_integer_t maxiter,
                                             igraph_real_t epsilon, igraph_real_t kkconst,
                                             const igraph_vector_t *weights,
                                             const igraph_vector_t *minx, const igraph_vector_t *maxx,
                                             const igraph_vector_t *miny, const igraph_vector_t *maxy,
                                             const igraph_vector_t *minz, const igraph_vector_t *maxz)
```

This is the 3D version of `igraph_layout_kamada_kawai()`. See the documentation of that function for more information.

This layout algorithm is not suitable for large graphs. The memory requirements are of the order $O(|V|^2)$.

Arguments:

- graph*: A graph object.
- res*: Pointer to an initialized matrix object. This will contain the result (x-, y- and z-positions in columns one through three) and will be resized if needed.
- use_seed*: Boolean, whether to use the values supplied in the *res* argument as the initial configuration. If zero and there are any limits on the z, y or z coordinates, then a random initial configuration is used. Otherwise the vertices are placed uniformly on a sphere of radius 1 as the initial configuration.
- maxiter*: The maximum number of iterations to perform. A reasonable default value is at least ten (or more) times the number of vertices.
- epsilon*: Stop the iteration, if the maximum delta value of the algorithm is smaller than still. It is safe to leave it at zero, and then *maxiter* iterations are performed.
- kkconst*: The Kamada-Kawai vertex attraction constant. Typical value: number of vertices.
- weights*: Edge weights, larger values will result longer edges. Weights must be positive. Pass NULL to assume unit weights for all edges.
- minx*: Pointer to a vector, or a NULL pointer. If not a NULL pointer then the vector gives the minimum “x” coordinate for every vertex.
- maxx*: Same as *minx*, but the maximum “x” coordinates.
- miny*: Pointer to a vector, or a NULL pointer. If not a NULL pointer then the vector gives the minimum “y” coordinate for every vertex.
- maxy*: Same as *miny*, but the maximum “y” coordinates.
- minz*: Pointer to a vector, or a NULL pointer. If not a NULL pointer then the vector gives the minimum “z” coordinate for every vertex.
- maxz*: Same as *minz*, but the maximum “z” coordinates.

Returns:

Error code.

Time complexity: $O(|V|)$ for each iteration, after an $O(|V|^2 \log|V|)$ initialization step. $|V|$ is the number of vertices in the graph.

igraph_layout_umap_3d — 3D layout using UMAP.

```
igraph_error_t igraph_layout_umap_3d(const igraph_t *graph,
                                     igraph_matrix_t *res,
                                     igraph_bool_t use_seed,
                                     const igraph_vector_t *distances,
                                     igraph_real_t min_dist,
                                     igraph_integer_t epochs,
                                     igraph_real_t sampling_prob);
```

This is the 3D version of the UMAP algorithm (see `igraph_layout_umap()` for the 2D version).

Arguments:

<i>graph</i> :	Pointer to the similarity graph to find a layout for (i.e. to embed).
<i>res</i> :	Pointer to the n by 3 matrix where the layout coordinates will be stored.
<i>use_seed</i> :	Logical, if true the supplied values in the <i>res</i> argument are used as an initial layout, if false a random initial layout is used.
<i>distances</i> :	Pointer to a vector of edge lengths. Similarity graphs for UMAP are often originally meant in terms of similarity weights (e.g. correlation between high-dimensional vectors) and converted into distances by crude $\text{dist} := 1 - \text{corr}$. That is fine here too. If this argument is a NULL pointer (NULL), all lengths are assumed equal.
<i>min_dist</i> :	A fudge parameter that decides how close two unconnected vertices can be in the embedding before feeling a repulsive force. It should be positive. Typically, 0.01 is a good number.
<i>epochs</i> :	Number of iterations of the main stochastic gradient descent loop on the cross-entropy. Usually, 500 epochs can be used if the graph is small (less than 50k edges), 50 epochs are used for larger graphs.
<i>sampling_prob</i> :	The fraction of vertices moved at each iteration of the stochastic gradient descent (epoch). At fixed number of epochs, a higher fraction makes the algorithm slower. Vice versa, a too low number will converge very slowly, possibly too slowly.

Returns:

Error code.

Warning

This function is experimental and its signature is not considered final yet. We reserve the right to change the function signature without changing the major version of igraph. Use it at your own risk.

Merging layouts

`igraph_layout_merge_dla` — Merge multiple layouts by using a DLA algorithm

```
igraph_error_t igraph_layout_merge_dla(  
    const igraph_vector_ptr_t *thegraphs, const igraph_matrix_list_t *coords,  
    igraph_matrix_t *res  
);
```

First each layout is covered by a circle. Then the layout of the largest graph is placed at the origin. Then the other layouts are placed by the DLA algorithm, larger ones first and smaller ones last.

Arguments:

thegraphs: Pointer vector containing the graph objects of which the layouts will be merged.

coords: List of matrices with the 2D layouts of the graphs in *thegraphs*.

res: Pointer to an initialized matrix object, the result will be stored here. It will be resized if needed.

Returns:

Error code.

Added in version 0.2. This function is experimental.

Time complexity: TODO.

Chapter 21. Reading and writing graphs from and to files

These functions can write a graph to a file, or read a graph from a file.

They assume that the current locale uses a decimal point and not a decimal comma. See `igraph_enter_safelocale()` and `igraph_exit_safelocale()` for more information.

Note that as **igraph** uses the traditional C streams, it is possible to read/write files from/to memory, at least on GNU operating systems supporting “non-standard” streams.

Simple edge list and similar formats

`igraph_read_graph_edgelist` — Reads an edge list from a file and creates a graph.

```
igraph_error_t igraph_read_graph_edgelist(igraph_t *graph, FILE *instream,
                                          igraph_integer_t n, igraph_bool_t directed);
```

This format is simply a series of an even number of non-negative integers separated by whitespace. The integers represent vertex IDs. Placing each edge (i.e. pair of integers) on a separate line is not required, but it is recommended for readability. Edges of directed graphs are assumed to be in “from, to” order.

Arguments:

- graph*: Pointer to an uninitialized graph object.
- instream*: Pointer to a stream, it should be readable.
- n*: The number of vertices in the graph. If smaller than the largest integer in the file it will be ignored. It is thus safe to supply zero here.
- directed*: Logical, if true the graph is directed, if false it will be undirected.

Returns:

Error code: `IGRAPH_PARSEERROR`: if there is a problem reading the file, or the file is syntactically incorrect.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges. It is assumed that reading an integer requires $O(1)$ time.

`igraph_write_graph_edgelist` — Writes the edge list of a graph to a file.

```
igraph_error_t igraph_write_graph_edgelist(const igraph_t *graph, FILE *outstream);
```

Edges are represented as pairs of 0-based vertex indices. One edge is written per line, separated by a single space. For directed graphs edges are written in from, to order.

Arguments:

graph: The graph object to write.

ostream: Pointer to a stream, it should be writable.

Returns:

Error code: `IGRAPH_EFILE` if there is an error writing the file.

Time complexity: $O(|E|)$, the number of edges in the graph. It is assumed that writing an integer to the file requires $O(1)$ time.

igraph_read_graph_ncol — Reads an .ncol file used by LGL.

```
igraph_error_t igraph_read_graph_ncol(igraph_t *graph, FILE *istream,
                                       const igraph_strvector_t *predefnames,
                                       igraph_bool_t names,
                                       igraph_add_weights_t weights,
                                       igraph_bool_t directed);
```

Also useful for creating graphs from “named” (and optionally weighted) edge lists.

This format is used by the Large Graph Layout program (<http://lgl.sourceforge.net>), and it is simply a symbolic weighted edge list. It is a simple text file with one edge per line. An edge is defined by two symbolic vertex names separated by whitespace. The vertex names themselves cannot contain whitespace. They may be followed by an optional number, the weight of the edge; the number can be negative and can be in scientific notation. If there is no weight specified to an edge it is assumed to be zero.

The resulting graph is always undirected. LGL cannot deal with files which contain multiple or loop edges, this is however not checked here, as **igraph** is happy with these.

Arguments:

graph: Pointer to an uninitialized graph object.

istream: Pointer to a stream, it should be readable.

predefnames: Pointer to the symbolic names of the vertices in the file. If `NULL` is given here then vertex IDs will be assigned to vertex names in the order of their appearance in the .ncol file. If it is not `NULL` and some unknown vertex names are found in the .ncol file then new vertex ids will be assigned to them.

names: Logical value, if `true` the symbolic names of the vertices will be added to the graph as a vertex attribute called “name”.

weights: Whether to add the weights of the edges to the graph as an edge attribute called “weight”. `IGRAPH_ADD_WEIGHTS_YES` adds the weights (even if they are not present in the file, in this case they are assumed to be zero). `IGRAPH_ADD_WEIGHTS_NO` does not add any edge attribute. `IGRAPH_ADD_WEIGHTS_IF_PRESENT` adds the attribute if and only if there is at least one explicit edge weight in the input file.

directed: Whether to create a directed graph. As this format was originally used only for undirected graphs there is no information in the file about the directedness of the

`graph`. Set this parameter to `IGRAPH_DIRECTED` or `IGRAPH_UNDIRECTED` to create a directed or undirected graph.

Returns:

Error code: `IGRAPH_PARSEERROR`: if there is a problem reading the file, or the file is syntactically incorrect.

Time complexity: $O(|V|+|E|\log(|V|))$ if we neglect the time required by the parsing. As usual $|V|$ is the number of vertices, while $|E|$ is the number of edges.

See also:

`igraph_read_graph_lgl()`, `igraph_write_graph_ncol()`

`igraph_write_graph_ncol` — Writes the graph to a file in `.ncol` format.

```
igraph_error_t igraph_write_graph_ncol(const igraph_t *graph, FILE *outstream,
                                       const char *names, const char *weights);
```

`.ncol` is a format used by LGL, see `igraph_read_graph_ncol()` for details.

Note that having multiple or loop edges in an `.ncol` file breaks the LGL software but **igraph** does not check for this condition.

This format cannot represent zero-degree vertices.

Arguments:

graph: The graph to write.

outstream: The stream object to write to, it should be writable.

names: The name of a string vertex attribute, if symbolic names are to be written to the file. Supply `NULL` to write vertex ids instead.

weights: The name of a numerical edge attribute, which will be written as weights to the file. Supply `NULL` to skip writing edge weights.

Returns:

Error code: `IGRAPH_EFILE` if there is an error writing the file.

Time complexity: $O(|E|)$, the number of edges. All file operations are expected to have time complexity $O(1)$.

See also:

`igraph_read_graph_ncol()`, `igraph_write_graph_lgl()`

`igraph_read_graph_lgl` — Reads a graph from an `.lgl` file

```
igraph_error_t igraph_read_graph_lgl(igraph_t *graph, FILE *instream,
                                     igraph_bool_t names,
                                     igraph_add_weights_t weights,
                                     igraph_bool_t directed);
```

The `.lgl` format is used by the Large Graph Layout visualization software (<http://lgl.sourceforge.net>), it can describe undirected optionally weighted graphs. From the LGL manual:

The second format is the LGL file format (`.lgl` file suffix). This is yet another graph file format that tries to be as stingy as possible with space, yet keeping the edge file in a human readable (not binary) format. The format itself is like the following:

```
# vertex1name
vertex2name [optionalWeight]
vertex3name [optionalWeight]
```

Here, the first vertex of an edge is preceded with a pound sign '#'. Then each vertex that shares an edge with that vertex is listed one per line on subsequent lines.

LGL cannot handle loop and multiple edges or directed graphs, but in **igraph** it is not an error to have multiple and loop edges.

Arguments:

- graph*: Pointer to an uninitialized graph object.
- instream*: A stream, it should be readable.
- names*: Logical value, if `true` the symbolic names of the vertices will be added to the graph as a vertex attribute called "name".
- weights*: Whether to add the weights of the edges to the graph as an edge attribute called "weight". `IGRAPH_ADD_WEIGHTS_YES` adds the weights (even if they are not present in the file, in this case they are assumed to be zero). `IGRAPH_ADD_WEIGHTS_NO` does not add any edge attribute. `IGRAPH_ADD_WEIGHTS_IF_PRESENT` adds the attribute if and only if there is at least one explicit edge weight in the input file.
- directed*: Whether to create a directed graph. As this format was originally used only for undirected graphs there is no information in the file about the directedness of the graph. Set this parameter to `IGRAPH_DIRECTED` or `IGRAPH_UNDIRECTED` to create a directed or undirected graph.

Returns:

Error code: `IGRAPH_PARSEERROR`: if there is a problem reading the file, or the file is syntactically incorrect.

Time complexity: $O(|V|+|E|\log(|V|))$ if we neglect the time required by the parsing. As usual $|V|$ is the number of vertices, while $|E|$ is the number of edges.

See also:

```
igraph_read_graph_ncol(), igraph_write_graph_lgl()
```

Example 21.1. File `examples/simple/igraph_read_graph_lgl.c`

igraph_write_graph_lgl — Writes the graph to a file in .lgl format

```
igraph_error_t igraph_write_graph_lgl(const igraph_t *graph, FILE *outstream,  
                                     const char *names, const char *weights,  
                                     igraph_bool_t isolates);
```

.lgl is a format used by LGL, see `igraph_read_graph_lgl()` for details.

Note that having multiple or loop edges in an .lgl file breaks the LGL software but **igraph** does not check for this condition.

Arguments:

graph: The graph to write.

outstream: The stream object to write to, it should be writable.

names: The name of a string vertex attribute, if symbolic names are to be written to the file. Supply NULL to write vertex ids instead.

weights: The name of a numerical edge attribute, which will be written as weights to the file. Supply NULL to skip writing edge weights.

isolates: Logical, if `true` isolated vertices are also written to the file. If `false` they will be omitted.

Returns:

Error code: `IGRAPH_EFILE` if there is an error writing the file.

Time complexity: $O(|E|)$, the number of edges if *isolates* is `false`, $O(|V|+|E|)$ otherwise. All file operations are expected to have time complexity $O(1)$.

See also:

`igraph_read_graph_lgl()`, `igraph_write_graph_ncol()`

Example 21.2. File `examples/simple/igraph_write_graph_lgl.c`

igraph_read_graph_dimacs_flow — Read a graph in DIMACS format.

```
igraph_error_t igraph_read_graph_dimacs_flow(igraph_t *graph, FILE *instream,  
                                             igraph_strvector_t *problem,  
                                             igraph_vector_int_t *label,  
                                             igraph_integer_t *source,  
                                             igraph_integer_t *target,  
                                             igraph_vector_t *capacity,  
                                             igraph_bool_t directed);
```

This function reads the DIMACS file format, more specifically the version for network flow problems, see the files at <ftp://dimacs.rutgers.edu/pub/netflow/general-info/>

This is a line-oriented text file (ASCII) format. The first character of each line defines the type of the line. If the first character is `c` the line is a comment line and it is ignored. There is one problem line (`p` in the file, it must appear before any node and arc descriptor lines. The problem line has three fields separated by spaces: the problem type (`min`, `max` or `asn`), the number of vertices and number of edges in the graph. Exactly two node identification lines are expected (`n`), one for the source, one for the target vertex. These have two fields: the id of the vertex and the type of the vertex, either `s` (=source) or `t` (=target). Arc lines start with `a` and have three fields: the source vertex, the target vertex and the edge capacity.

Vertex IDs are numbered from 1.

Arguments:

- graph*: Pointer to an uninitialized graph object.
- istream*: The file to read from.
- source*: Pointer to an integer, the id of the source node will be stored here. (The igraph vertex ID, which is one less than the actual number in the file.) It is ignored if NULL.
- target*: Pointer to an integer, the (igraph) id of the target node will be stored here. It is ignored if NULL.
- capacity*: Pointer to an initialized vector, the capacity of the edges will be stored here if not NULL.
- directed*: Boolean, whether to create a directed graph.

Returns:

Error code.

Time complexity: $O(|V|+|E|+c)$, the number of vertices plus the number of edges, plus the size of the file in characters.

See also:

`igraph_write_graph_dimacs()`

igraph_write_graph_dimacs_flow — Write a graph in DIMACS format.

```
igraph_error_t igraph_write_graph_dimacs_flow(const igraph_t *graph, FILE *outs,
                                              igraph_integer_t source, igraph_integer_t target,
                                              const igraph_vector_t *capacity);
```

This function writes a graph to an output stream in DIMACS format, describing a maximum flow problem. See <ftp://dimacs.rutgers.edu/pub/netflow/general-info/>

This file format is discussed in the documentation of `igraph_read_graph_dimacs_flow()`, see that for more information.

Arguments:

graph: The graph to write to the stream.

ostream: The stream.

source: Integer, the id of the source vertex for the maximum flow.

target: Integer, the id of the target vertex.

capacity: Pointer to an initialized vector containing the edge capacity values.

Returns:

Error code.

Time complexity: $O(|E|)$, the number of edges in the graph.

See also:

`igraph_read_graph_dimacs_flow()`

Binary formats

`igraph_read_graph_graphdb` — Read a graph in the binary graph database format.

```
igraph_error_t igraph_read_graph_graphdb(igraph_t *graph, FILE *instream,
                                          igraph_bool_t directed);
```

This is a binary format, used in the graph database for isomorphism testing. From the (now defunct) graph database homepage:

The graphs are stored in a compact binary format, one graph per file. The file is composed of 16 bit words, which are represented using the so-called little-endian convention, i.e. the least significant byte of the word is stored first.

Then, for each node, the file contains the list of edges coming out of the node itself. The list is represented by a word encoding its length, followed by a word for each edge, representing the destination node of the edge. Node numeration is 0-based, so the first node of the graph has index 0.

Only unlabelled graphs are implemented.

Arguments:

graph: Pointer to an uninitialized graph object.

instream: The stream to read from.

directed: Logical scalar, whether to create a directed graph.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

Example	21.3.	File	examples/simple/ igraph_read_graph_graphdb.c
----------------	--------------	-------------	---

GraphML format

igraph_read_graph_graphml — Reads a graph from a GraphML file.

```
igraph_error_t igraph_read_graph_graphml(igraph_t *graph, FILE *instream, igraph_index_t index)
```

GraphML is an XML-based file format for representing various types of graphs. Currently only the most basic import functionality is implemented in igraph: it can read GraphML files without nested graphs and hyperedges. Attributes of the graph are loaded only if an attribute interface is attached, see `igraph_set_attribute_table()`. String attribute values are returned in UTF-8 encoding.

Graph attribute names are taken from the `attr.name` attributes of the key tags in the GraphML file. Since `attr.name` is not mandatory, igraph will fall back to the `id` attribute of the key tag if `attr.name` is missing.

Arguments:

graph: Pointer to an uninitialized graph object.

instream: A stream, it should be readable.

index: If the GraphML file contains more than one graph, the one specified by this index will be loaded. Indices start from zero, so supply zero here if your GraphML file contains only a single graph.

Returns:

Error code: `IGRAPH_PARSEERROR`: if there is a problem reading the file, or the file is syntactically incorrect. `IGRAPH_UNIMPLEMENTED`: the GraphML functionality was disabled at compile-time

Example 21.4. File `examples/simple/graphml.c`

igraph_write_graph_graphml — Writes the graph to a file in GraphML format.

```
igraph_error_t igraph_write_graph_graphml(const igraph_t *graph, FILE *outstream, igraph_bool_t prefixattr);
```

GraphML is an XML-based file format for representing various types of graphs. See the GraphML Primer (<http://graphml.graphdrawing.org/primer/graphml-primer.html>) for detailed format description.

When a numerical attribute value is NaN, it will be omitted from the file.

Arguments:

<i>graph</i> :	The graph to write.
<i>ostream</i> :	The stream object to write to, it should be writable.
<i>prefixattr</i> :	Logical value, whether to put a prefix in front of the attribute names to ensure uniqueness if the graph has vertex and edge (or graph) attributes with the same name.

Returns:

Error code: `IGRAPH_EFILE` if there is an error writing the file.

Time complexity: $O(|V|+|E|)$ otherwise. All file operations are expected to have time complexity $O(1)$.

Example 21.5. File `examples/simple/graphml.c`

GML format

`igraph_read_graph_gml` — Read a graph in GML format.

```
igraph_error_t igraph_read_graph_gml(igraph_t *graph, FILE *instream);
```

GML is a simple textual format, see <https://web.archive.org/web/20190207140002/http://www.fim.uni-passau.de/index.php?id=17297%26L=1> for details.

Although all syntactically correct GML can be parsed, we implement only a subset of this format. Some attributes might be ignored. Here is a list of all the differences:

1. Only attributes with a simple type are used: integer, real or string. If an attribute is composite, i.e. an array or a record, then it is ignored. When some values of the attribute are simple and some compound, the composite ones are replaced with a default value (NaN for numeric, " " for string).
2. `comment` fields are not ignored. They are treated as any other field and converted to attributes.
3. Top level attributes except for `Version` and the first graph attribute are completely ignored.
4. There is no maximum line length or maximum keyword length.
5. Only the `quot`, `amp`, `apos`, `lt` and `gt` character entities are supported. Any other entity is passed through unchanged by the reader after issuing a warning, and is expected to be decoded by the user.
6. We allow `inf`, `-inf` and `nan` (not a number) as a real number. This is case insensitive, so `nan`, `NaN` and `NAN` are equivalent.

Please contact us if you cannot live with these limitations of the GML parser.

Arguments:

<i>graph</i> :	Pointer to an uninitialized graph object.
<i>istream</i> :	The stream to read the GML file from.

Returns:

Error code.

Time complexity: should be proportional to the length of the file.

See also:

`igraph_read_graph_graphml()` for a more modern format,
`igraph_write_graph_gml()` for writing GML files.

Example 21.6. File `examples/simple/gml.c`

`igraph_write_graph_gml` — Write the graph to a stream in GML format.

```
igraph_error_t igraph_write_graph_gml(const igraph_t *graph, FILE *outstream,  
                                     igraph_write_gml_sw_t options,  
                                     const igraph_vector_t *id, const char *cr)
```

GML is a quite general textual format, see <https://web.archive.org/web/20190207140002/http://www.fim.uni-passau.de/index.php?id=17297%26L=1> for details.

The graph, vertex and edges attributes are written to the file as well, if they are numeric or string. Boolean attributes are converted to numeric, with 0 and 1 used for false and true, respectively. NaN values of numeric attributes are skipped, as NaN is not part of the GML specification and other software may not be able to read files containing them. This is consistent with `igraph_read_graph_gml()`, which produces NaN when an attribute value is missing. In contrast with NaN, infinite values are retained. Ensure that none of the numeric attributes values are infinite to produce a conformant GML file that can be read by other software.

As `igraph` is more forgiving about attribute names, it might be necessary to simplify the them before writing to the GML file. This way we'll have a syntactically correct GML file. The following simple procedure is performed on each attribute name: first the alphanumeric characters are extracted, the others are ignored. Then if the first character is not a letter then the attribute name is prefixed with “igraph”. Note that this might result identical names for two attributes, `igraph` does not check this.

The “id” vertex attribute is treated specially. If the `id` argument is not `NULL` then it should be a numeric vector with the vertex IDs and the “id” vertex attribute is ignored (if there is one). If `id` is `NULL` and there is a numeric “id” vertex attribute, it will be used instead. If ids are not specified in either way then the regular `igraph` vertex IDs are used. If some of the supplied id values are invalid (non-integer or NaN), all supplied id are ignored and `igraph` vertex IDs are used instead.

Note that whichever way vertex IDs are specified, their uniqueness is not checked.

If the graph has edge attributes that become “source” or “target” after encoding, or the graph has an attribute that becomes “directed”, they will be ignored with a warning. GML uses these attributes to specify the edge endpoints, and the graph directedness, so we cannot write them to the file. Rename them before calling this function if you want to preserve them.

Arguments:

graph: The graph to write to the stream.

outstream: The stream to write the file to.

options: Set of | -combinable boolean flags for writing the GML file.

0 All options turned off.

IGRAPH_WRITE_GML_DEFAULT_SW Default options, currently equivalent to 0. May change in future versions.

IGRAPH_WRITE_GML_ENCODE_ONLY_QUOT_SW Do not encode any other characters than " as entities. Specifically, this option prevents the encoding of &. Useful when re-exporting a graph that was read from a GML file in which igraph could not interpret all entities, and thus passed them through without decoding.

id: Either NULL or a numeric vector with the vertex IDs. See details above.

creator: An optional string to write to the stream in the creator line. If NULL, the igraph version with the current date and time is added. If "", the creator line is omitted. Otherwise, the supplied string is used verbatim.

Returns:

Error code.

Time complexity: should be proportional to the number of characters written to the file.

See also:

`igraph_read_graph_gml()` for reading GML files, `igraph_read_graph_graphml()` for a more modern format.

Example 21.7. File `examples/simple/gml.c`

Pajek format

`igraph_read_graph_pajek` — Reads a file in Pajek format

```
igraph_error_t igraph_read_graph_pajek(igraph_t *graph, FILE *instream);
```

Arguments:

graph: Pointer to an uninitialized graph object.

file: An already opened file handler.

Returns:

Error code.

Only a subset of the Pajek format is implemented. This is partially because this format is not very well documented, but also because **igraph** does not support some Pajek features, like multigraphs.

Starting from version 0.6.1 igraph reads bipartite (two-mode) graphs from Pajek files and add the `type` vertex attribute for them. Warnings are given for invalid edges, i.e. edges connecting vertices of the same type.

The list of the current limitations:

1. Only .net files are supported, Pajek project files (.paj) are not. These might be supported in the future if there is need for it.
2. Time events networks are not supported.
3. Hypergraphs (i.e. graphs with non-binary edges) are not supported.
4. Graphs with both directed and non-directed edges are not supported, are they cannot be represented in **igraph**.
5. Only Pajek networks are supported, permutations, hierarchies, clusters and vectors are not.
6. Graphs with multiple edge sets are not supported.

If there are attribute handlers installed, **igraph** also reads the vertex and edge attributes from the file. Most attributes are renamed to be more informative: `color` instead of `c`, `xfact` instead of `x_fact`, `yfact` instead of `y_fact`, `labeldist` instead of `lr`, `labeldegree2` instead of `lphi`, `framewidth` instead of `bw`, `fontsize` instead of `fos`, `rotation` instead of `phi`, `radius` instead of `r`, `diamondratio` instead of `q`, `labeldegree` instead of `la`, `vertexsize` instead of `size`, `color` instead of `ic`, `framecolor` instead of `bc`, `labelcolor` instead of `lc`, these belong to vertices.

Edge attributes are also renamed, `s` to `arrowsize`, `w` to `edgewidth`, `h1` to `hook1`, `h2` to `hook2`, `a1` to `angle1`, `a2` to `angle2`, `k1` to `velocity1`, `k2` to `velocity2`, `ap` to `arrowpos`, `lp` to `labelpos`, `lr` to `labelangle`, `lphi` to `labelangle2`, `la` to `labeldegree`, `fos` to `font-size`, `a` to `arrowtype`, `p` to `linepattern`, `l` to `label`, `lc` to `labelcolor`, `c` to `color`.

In addition the following vertex attributes might be added: `id` if there are vertex IDs in the file, `x` and `y` or `x` and `y` and `z` if there are vertex coordinates in the file.

The `weight` edge attribute might be added if there are edge weights present.

See the pajek homepage: <http://vlado.fmf.uni-lj.si/pub/networks/pajek/> for more info on Pajek and the Pajek manual: <http://vlado.fmf.uni-lj.si/pub/networks/pajek/doc/pajekman.pdf> for information on the Pajek file format.

Time complexity: $O(|V|+|E|+|A|)$, $|V|$ is the number of vertices, $|E|$ the number of edges, $|A|$ the number of attributes (vertex + edge) in the graph if there are attribute handlers installed.

See also:

`igraph_write_graph_pajek()` for writing Pajek files,
`igraph_read_graph_graphml()` for reading GraphML files.

Example 21.8. File `examples/simple/foreign.c`

igraph_write_graph_pajek — Writes a graph to a file in Pajek format.

```
igraph_error_t igraph_write_graph_pajek(const igraph_t *graph, FILE *outstream)
```

The Pajek vertex and edge parameters (like `color`) are determined by the attributes of the vertices and edges, of course this requires an attribute handler to be installed. The names of the corresponding

vertex and edge attributes are listed at `igraph_read_graph_pajek()`, e.g. the `color` vertex attributes determines the color (`c` in Pajek) parameter.

As of version 0.6.1 `igraph` writes bipartite graphs into Pajek files correctly, i.e. they will be also bipartite when read into Pajek. As Pajek is less flexible for bipartite graphs (the numeric IDs of the vertices must be sorted according to vertex type), `igraph` might need to reorder the vertices when writing a bipartite Pajek file. This effectively means that numeric vertex IDs usually change when a bipartite graph is written to a Pajek file, and then read back into `igraph`.

Early versions of Pajek supported only Windows-style line endings in Pajek files, but recent versions support both Windows and Unix line endings. `igraph` therefore uses the platform-native line endings when the input file is opened in text mode, and uses Unix-style line endings when the input file is opened in binary mode. If you are using an old version of Pajek, you are on Unix and you are having problems reading files written by `igraph` on a Windows machine, convert the line endings manually with a text editor or with `unix2dos` or `iconv` from the command line).

Arguments:

graph: The graph object to write.

ostream: The file to write to. It should be opened and writable. Make sure that you open the file in binary format if you use MS Windows, otherwise end of line characters will be messed up. (`igraph` will be able to read back these messed up files, but Pajek won't.)

Returns:

Error code.

Time complexity: $O(|V|+|E|+|A|)$, $|V|$ is the number of vertices, $|E|$ is the number of edges, $|A|$ the number of attributes (vertex + edge) in the graph if there are attribute handlers installed.

See also:

`igraph_read_graph_pajek()` for reading Pajek graphs,
`igraph_write_graph_graphml()` for writing a graph in GraphML format, this suites **igraph** graphs better.

Example 21.9. File `examples/simple/igraph_write_graph_pajek.c`

UCINET's DL file format

`igraph_read_graph_dl` — Read a file in the DL format of UCINET

```
igraph_error_t igraph_read_graph_dl(igraph_t *graph, FILE *instream,  
                                     igraph_bool_t directed);
```

This is a simple textual file format used by UCINET. See <http://www.analytictech.com/networks/dataentry.htm> for examples. All the forms described here are supported by `igraph`. Vertex names and edge weights are also supported and they are added as attributes. (If an attribute handler is attached.)

Note the specification does not mention whether the format is case sensitive or not. For `igraph` DL files are case sensitive, i.e. `Larry` and `larry` are not the same.

Arguments:

graph: Pointer to an uninitialized graph object.

instream: The stream to read the DL file from.

directed: Logical scalar, whether to create a directed file.

Returns:

Error code.

Time complexity: linear in terms of the number of edges and vertices, except for the matrix format, which is quadratic in the number of vertices.

Example 21.10. File `examples/simple/igraph_read_graph_dl.c`

Graphviz format

`igraph_write_graph_dot` — Write the graph to a stream in DOT format

```
igraph_error_t igraph_write_graph_dot(const igraph_t *graph, FILE* outstream);
```

DOT is the format used by the widely known GraphViz software, see <http://www.graphviz.org> for details. The grammar of the DOT format can be found here: <http://www.graphviz.org/doc/info/lang.html>

This is only a preliminary implementation, no visualization information is written.

Arguments:

graph: The graph to write to the stream.

outstream: The stream to write the file to.

Time complexity: should be proportional to the number of characters written to the file.

See also:

`igraph_write_graph_graphml()` for a more modern format.

Example 21.11. File `examples/simple/dot.c`

Convenience functions for locale change

`igraph_enter_safelocale` — Temporarily set the C locale.

```
igraph_error_t igraph_enter_safelocale(igraph_safelocale_t *loc);
```

Warning

This function is experimental and its signature is not considered final yet. We reserve the right to change the function signature without changing the major version of igraph. Use it at your own risk.

igraph's foreign format readers and writers require a locale that uses a decimal point instead of a decimal comma. This is a convenience function that temporarily sets the C locale so that readers and writer would work correctly. It *must* be paired with a call to `igraph_exit_safelocale()`, otherwise a memory leak will occur.

This function tries to set the locale for the current thread only on a best-effort basis. Restricting the locale change to a single thread is not supported on all platforms. In these cases, this function falls back to using the standard `setlocale()` function, which affects the entire process and is not safe to use from concurrent threads.

It is generally recommended to run igraph within a thread that has been permanently set to the C locale using system-specific means. This is a convenience function for situations when this is not easily possible because the programmer is not in control of the process, such as when developing plugins/extensions. Note that processes start up in the C locale by default, thus nothing needs to be done unless the locale has been changed away from the default.

Arguments:

loc: Pointer to a variable of type `igraph_safelocale_t`. The current locale will be stored here, so that it can be restored using `igraph_exit_safelocale()`.

Returns:

Error code.

Example 21.12. File `examples/simple/safelocale.c`

igraph_exit_safelocale — Temporarily set the C locale.

```
void igraph_exit_safelocale(igraph_safelocale_t *loc);
```

Warning

This function is experimental and its signature is not considered final yet. We reserve the right to change the function signature without changing the major version of igraph. Use it at your own risk.

Restores a locale saved by `igraph_enter_safelocale()` and deallocates all associated data. This function *must* be paired with a call to `igraph_enter_safelocale()`.

Arguments:

loc: A variable of type `igraph_safelocale_t`, originally set by `igraph_enter_safelocale()`.

Deprecated functions

igraph_read_graph_dimacs — Read a graph in DIMACS format (deprecated alias).

```
igraph_error_t igraph_read_graph_dimacs(igraph_t *graph, FILE *instream,  
                                         igraph_strvector_t *problem,  
                                         igraph_vector_int_t *label,  
                                         igraph_integer_t *source,  
                                         igraph_integer_t *target,  
                                         igraph_vector_t *capacity,  
                                         igraph_bool_t directed);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_read_graph_dimacs_flow()` instead.

igraph_write_graph_dimacs — Write a graph in DIMACS format (deprecated alias).

```
igraph_error_t igraph_write_graph_dimacs(const igraph_t *graph, FILE *outstream,  
                                         igraph_integer_t source, igraph_integer_t target,  
                                         const igraph_vector_t *capacity);
```

Warning

Deprecated since version 0.10.0. Please do not use this function in new code; use `igraph_write_graph_dimacs_flow()` instead.

Chapter 22. Maximum flows, minimum cuts and related measures

Maximum flows

`igraph_maxflow` — Maximum network flow between a pair of vertices

```
igraph_error_t igraph_maxflow(const igraph_t *graph, igraph_real_t *value,
                              igraph_vector_t *flow, igraph_vector_int_t *cut,
                              igraph_vector_int_t *partition, igraph_vector_int_t *partition2,
                              igraph_integer_t source, igraph_integer_t target,
                              const igraph_vector_t *capacity,
                              igraph_maxflow_stats_t *stats);
```

This function implements the Goldberg-Tarjan algorithm for calculating value of the maximum flow in a directed or undirected graph. The algorithm was given in Andrew V. Goldberg, Robert E. Tarjan: A New Approach to the Maximum-Flow Problem, Journal of the ACM, 35(4), 921-940, 1988.

The input of the function is a graph, a vector of real numbers giving the capacity of the edges and two vertices of the graph, the source and the target. A flow is a function assigning positive real numbers to the edges and satisfying two requirements: (1) the flow value is less than the capacity of the edge and (2) at each vertex except the source and the target, the incoming flow (i.e. the sum of the flow on the incoming edges) is the same as the outgoing flow (i.e. the sum of the flow on the outgoing edges). The value of the flow is the incoming flow at the target vertex. The maximum flow is the flow with the maximum value.

Arguments:

<i>graph</i> :	The input graph, either directed or undirected.
<i>value</i> :	Pointer to a real number, the value of the maximum will be placed here, unless it is a null pointer.
<i>flow</i> :	If not a null pointer, then it must be a pointer to an initialized vector. The vector will be resized, and the flow on each edge will be placed in it, in the order of the edge IDs. For undirected graphs this argument is bit trickier, since for these the flow direction is not predetermined by the edge direction. For these graphs the elements of the <i>flow</i> vector can be negative, this means that the flow goes from the bigger vertex ID to the smaller one. Positive values mean that the flow goes from the smaller vertex ID to the bigger one.
<i>cut</i> :	A null pointer or a pointer to an initialized vector. If not a null pointer, then the minimum cut corresponding to the maximum flow is stored here, i.e. all edge IDs that are part of the minimum cut are stored in the vector.
<i>partition</i> :	A null pointer or a pointer to an initialized vector. If not a null pointer, then the first partition of the minimum cut that corresponds to the maximum flow will be placed here. The first partition is always the one that contains the source vertex.
<i>partition2</i> :	A null pointer or a pointer to an initialized vector. If not a null pointer, then the second partition of the minimum cut that corresponds to the maximum flow will be placed here. The second partition is always the one that contains the target vertex.

source: The id of the source vertex.

target: The id of the target vertex.

capacity: Vector containing the capacity of the edges. If NULL, then every edge is considered to have capacity 1.0.

stats: Counts of the number of different operations preformed by the algorithm are stored here.

Returns:

Error code.

Time complexity: $O(|V|^3)$. In practice it is much faster, but i cannot prove a better lower bound for the data structure i've used. In fact, this implementation runs much faster than the `hi_pr` implementation discussed in B. V. Cherkassky and A. V. Goldberg: On implementing the push-relabel method for the maximum flow problem, (Algorithmica, 19:390--410, 1997) on all the graph classes i've tried.

See also:

`igraph_mincut_value()`, `igraph_edge_connectivity()`, `igraph_vertex_connectivity()` for properties based on the maximum flow.

Example 22.1. File `examples/simple/flow.c`

Example 22.2. File `examples/simple/flow2.c`

`igraph_maxflow_value` — Maximum flow in a network with the push/relabel algorithm

```
igraph_error_t igraph_maxflow_value(const igraph_t *graph, igraph_real_t *value,
                                   igraph_integer_t source, igraph_integer_t target,
                                   const igraph_vector_t *capacity,
                                   igraph_maxflow_stats_t *stats);
```

This function implements the Goldberg-Tarjan algorithm for calculating value of the maximum flow in a directed or undirected graph. The algorithm was given in Andrew V. Goldberg, Robert E. Tarjan: A New Approach to the Maximum-Flow Problem, Journal of the ACM, 35(4), 921-940, 1988.

The input of the function is a graph, a vector of real numbers giving the capacity of the edges and two vertices of the graph, the source and the target. A flow is a function assigning positive real numbers to the edges and satisfying two requirements: (1) the flow value is less than the capacity of the edge and (2) at each vertex except the source and the target, the incoming flow (i.e. the sum of the flow on the incoming edges) is the same as the outgoing flow (i.e. the sum of the flow on the outgoing edges). The value of the flow is the incoming flow at the target vertex. The maximum flow is the flow with the maximum value.

According to a theorem by Ford and Fulkerson (L. R. Ford Jr. and D. R. Fulkerson. Maximal flow through a network. Canadian J. Math., 8:399-404, 1956.) the maximum flow between two vertices is the same as the minimum cut between them (also called the minimum s-t cut). So `igraph_st_mincut_value()` gives the same result in all cases as `igraph_maxflow_value()`.

Note that the value of the maximum flow is the same as the minimum cut in the graph.

Arguments:

- graph*: The input graph, either directed or undirected.
- value*: Pointer to a real number, the result will be placed here.
- source*: The id of the source vertex.
- target*: The id of the target vertex.
- capacity*: Vector containing the capacity of the edges. If NULL, then every edge is considered to have capacity 1.0.
- stats*: Counts of the number of different operations preformed by the algorithm are stored here.

Returns:

Error code.

Time complexity: $O(|V|^3)$.

See also:

`igraph_maxflow()` to calculate the actual flow. `igraph_mincut_value()`, `igraph_edge_connectivity()`, `igraph_vertex_connectivity()` for properties based on the maximum flow.

igraph_dominator_tree — Calculates the dominator tree of a flowgraph

```
igraph_error_t igraph_dominator_tree(const igraph_t *graph,
                                     igraph_integer_t root,
                                     igraph_vector_int_t *dom,
                                     igraph_t *domtree,
                                     igraph_vector_int_t *leftout,
                                     igraph_neimode_t mode);
```

A flowgraph is a directed graph with a distinguished start (or root) vertex r , such that for any vertex v , there is a path from r to v . A vertex v dominates another vertex w (not equal to v), if every path from r to w contains v . Vertex v is the immediate dominator of w , $v = \text{idom}(w)$, if v dominates w and every other dominator of w dominates v . The edges $\{(\text{idom}(w), w) \mid w \text{ is not } r\}$ form a directed tree, rooted at r , called the dominator tree of the graph. Vertex v dominates vertex w if and only if v is an ancestor of w in the dominator tree.

This function implements the Lengauer-Tarjan algorithm to construct the dominator tree of a directed graph. For details please see Thomas Lengauer, Robert Endre Tarjan: A fast algorithm for finding dominators in a flowgraph, ACM Transactions on Programming Languages and Systems (TOPLAS) I/1, 121--141, 1979.

Arguments:

- graph*: A directed graph. If it is not a flowgraph, and it contains some vertices not reachable from the root vertex, then these vertices will be collected in the `leftout` vector.
- root*: The id of the root (or source) vertex, this will be the root of the tree.

<i>dom</i> :	Pointer to an initialized vector or a null pointer. If not a null pointer, then the immediate dominator of each vertex will be stored here. For vertices that are not reachable from the root, -2 is stored here. For the root vertex itself, -1 is added.
<i>domtree</i> :	Pointer to an uninitialized <code>igraph_t</code> , or <code>NULL</code> . If not a null pointer, then the dominator tree is returned here. The graph contains the vertices that are unreachable from the root (if any), these will be isolates.
<i>leftout</i> :	Pointer to an initialized vector object, or <code>NULL</code> . If not <code>NULL</code> , then the IDs of the vertices that are unreachable from the root vertex (and thus not part of the dominator tree) are stored here.
<i>mode</i> :	Constant, must be <code>IGRAPH_IN</code> or <code>IGRAPH_OUT</code> . If it is <code>IGRAPH_IN</code> , then all directions are considered as opposite to the original one in the input graph.

Returns:

Error code.

Time complexity: very close to $O(|E|+|V|)$, linear in the number of edges and vertices. More precisely, it is $O(|V|+|E|\alpha(|E|,|V|))$, where $\alpha(|E|,|V|)$ is a functional inverse of Ackermann's function.

Example 22.3. File `examples/simple/dominator_tree.c`

`igraph_maxflow_stats_t` — A simple data type to return some statistics from the

```
typedef struct {
    igraph_integer_t nopush, norelabel, nogap, nogapnodes, nobfs;
```

push-relabel maximum flow solver.

Arguments:

<i>nopush</i> :	The number of push operations performed.
<i>norelabel</i> :	The number of relabel operations performed.
<i>nogap</i> :	The number of times the gap heuristics was used.
<i>nogapnodes</i> :	The total number of vertices that were omitted from further calculations because of the gap heuristics.
<i>nobfs</i> :	The number of times the reverse BFS was run to assign good values to the height function. This includes an initial run before the whole algorithm, so it is always at least one.

Cuts and minimum cuts

`igraph_st_mincut` — Minimum cut between a source and a target vertex

```
igraph_error_t igraph_st_mincut(const igraph_t *graph, igraph_real_t *value,  
                                igraph_vector_int_t *cut, igraph_vector_int_t *partition,  
                                igraph_vector_int_t *partition2,  
                                igraph_integer_t source, igraph_integer_t target,  
                                const igraph_vector_t *capacity);
```

Finds the edge set that has the smallest total capacity among all edge sets that disconnect the source and target vertices.

The calculation is performed using maximum flow techniques, by calling `igraph_maxflow()`.

Arguments:

<i>graph</i> :	The input graph.
<i>value</i> :	Pointer to a real variable, the value of the cut is stored here.
<i>cut</i> :	Pointer to an initialized vector, the edge IDs that are included in the cut are stored here. This argument is ignored if it is a null pointer.
<i>partition</i> :	Pointer to an initialized vector, the vertex IDs of the vertices in the first partition of the cut are stored here. The first partition is always the one that contains the source vertex. This argument is ignored if it is a null pointer.
<i>partition2</i> :	Pointer to an initialized vector, the vertex IDs of the vertices in the second partition of the cut are stored here. The second partition is always the one that contains the target vertex. This argument is ignored if it is a null pointer.
<i>source</i> :	Integer, the id of the source vertex.
<i>target</i> :	Integer, the id of the target vertex.
<i>capacity</i> :	Vector containing the capacity of the edges. If a null pointer, then every edge is considered to have capacity 1.0.

Returns:

Error code.

See also:

`igraph_maxflow()`.

Time complexity: see `igraph_maxflow()`.

igraph_st_mincut_value — The minimum s-t cut in a graph

```
igraph_error_t igraph_st_mincut_value(const igraph_t *graph, igraph_real_t *value,  
                                       igraph_integer_t source, igraph_integer_t target,  
                                       const igraph_vector_t *capacity);
```

The minimum s-t cut in a weighted (=valued) graph is the total minimum edge weight needed to remove from the graph to eliminate all paths from a given vertex (*source*) to another vertex (*target*). Directed paths are considered in directed graphs, and undirected paths in undirected graphs.

The minimum s-t cut between two vertices is known to be same as the maximum flow between these two vertices. So this function calls `igraph_maxflow_value()` to do the calculation.

Arguments:

- graph*: The input graph.
- value*: Pointer to a real variable, the result will be stored here.
- source*: The id of the source vertex.
- target*: The id of the target vertex.
- capacity*: Pointer to the capacity vector, it should contain non-negative numbers and its length should be the same the the number of edges in the graph. It can be a null pointer, then every edge has unit capacity.

Returns:

Error code.

Time complexity: $O(|V|^3)$, see also the discussion for `igraph_maxflow_value()`, $|V|$ is the number of vertices.

igraph_all_st_cuts — List all edge-cuts between two vertices in a directed graph

```
igraph_error_t igraph_all_st_cuts(const igraph_t *graph,
                                igraph_vector_int_list_t *cuts,
                                igraph_vector_int_list_t *partitionls,
                                igraph_integer_t source,
                                igraph_integer_t target);
```

This function lists all edge-cuts between a source and a target vertex. Every cut is listed exactly once. The implemented algorithm is described in JS Provan and DR Shier: A Paradigm for listing (s,t)-cuts in graphs, *Algorithmica* 15, 351--372, 1996.

Arguments:

- graph*: The input graph, is must be directed.
- cuts*: An initialized list of integer vectors, the cuts are stored here. Each vector will contain the IDs of the edges in the cut. This argument is ignored if it is a null pointer.
- partitionls*: An initialized list of integer vectors, the list of vertex sets generating the actual edge cuts are stored here. Each vector contains a set of vertex IDs. If X is such a set, then all edges going from X to the complement of X form an (s, t) edge-cut in the graph. This argument is ignored if it is a null pointer.
- source*: The id of the source vertex.
- target*: The id of the target vertex.

Returns:

Error code.

Time complexity: $O(n(|V|+|E|))$, where $|V|$ is the number of vertices, $|E|$ is the number of edges, and n is the number of cuts.

igraph_all_st_mincuts — All minimum s-t cuts of a directed graph

```
igraph_error_t igraph_all_st_mincuts(const igraph_t *graph, igraph_real_t *value,
                                     igraph_vector_int_list_t *cuts,
                                     igraph_vector_int_list_t *partitionls,
                                     igraph_integer_t source,
                                     igraph_integer_t target,
                                     const igraph_vector_t *capacity);
```

This function lists all edge cuts between two vertices, in a directed graph, with minimum total capacity. Possibly, multiple cuts may have the same total capacity, although there is often only one minimum cut in weighted graphs. It is recommended to supply integer-values capacities. Otherwise, not all minimum cuts may be detected because of numerical roundoff errors. The implemented algorithm is described in JS Provan and DR Shier: A Paradigm for listing (s,t)-cuts in graphs, *Algorithmica* 15, 351--372, 1996.

Arguments:

- graph*: The input graph, it must be directed.
- value*: Pointer to a real number, the value of the minimum cut is stored here, unless it is a null pointer.
- cuts*: An initialized pointer vector, the cuts are stored here. It is a list of pointers to `igraph_vector_int_t` objects. Each vector will contain the IDs of the edges in the cut. This argument is ignored if it is a null pointer. To free all memory allocated for *cuts*, you need call `igraph_vector_int_destroy()` and then `igraph_free()` on each element, before destroying the pointer vector itself.
- partitionls*: An initialized pointer vector, the list of vertex sets, generating the actual edge cuts, are stored here. It is a list of pointers to `igraph_vector_int_t` objects. Each vector contains a set of vertex IDs. If X is such a set, then all edges going from X to the complement of X form an (s,t) edge-cut in the graph. This argument is ignored if it is a null pointer.
- source*: The id of the source vertex.
- target*: The id of the target vertex.
- capacity*: Vector of edge capacities. All capacities must be strictly positive. If this is a null pointer, then all edges are assumed to have capacity one.

Returns:

Error code.

Time complexity: $O(n(|V|+|E|))+O(F)$, where $|V|$ is the number of vertices, $|E|$ is the number of edges, and n is the number of cuts; $O(F)$ is the time complexity of the maximum flow algorithm, see `igraph_maxflow()`.

Example 22.4. File `examples/simple/igraph_all_st_mincuts.c`

igraph_mincut — Calculates the minimum cut in a graph.

```
igraph_error_t igraph_mincut(const igraph_t *graph,
                             igraph_real_t *value,
                             igraph_vector_int_t *partition,
                             igraph_vector_int_t *partition2,
                             igraph_vector_int_t *cut,
                             const igraph_vector_t *capacity);
```

This function calculates the minimum cut in a graph. The minimum cut is the minimum set of edges which needs to be removed to disconnect the graph. The minimum is calculated using the weights (*capacity*) of the edges, so the cut with the minimum total capacity is calculated.

For directed graphs an implementation based on calculating $2|V|-2$ maximum flows is used. For undirected graphs we use the Stoer-Wagner algorithm, as described in M. Stoer and F. Wagner: A simple min-cut algorithm, Journal of the ACM, 44 585-591, 1997.

The first implementation of the actual cut calculation for undirected graphs was made by Gregory Benison, thanks Greg.

Arguments:

- graph*: The input graph.
- value*: Pointer to a float, the value of the cut will be stored here.
- partition*: Pointer to an initialized vector, the ids of the vertices in the first partition after separating the graph will be stored here. The vector will be resized as needed. This argument is ignored if it is a NULL pointer.
- partition2*: Pointer to an initialized vector the ids of the vertices in the second partition will be stored here. The vector will be resized as needed. This argument is ignored if it is a NULL pointer.
- cut*: Pointer to an initialized vector, the IDs of the edges in the cut will be stored here. This argument is ignored if it is a NULL pointer.
- capacity*: A numeric vector giving the capacities of the edges. If a null pointer then all edges have unit capacity.

Returns:

Error code.

See also:

`igraph_mincut_value()`, a simpler interface for calculating the value of the cut only.

Time complexity: for directed graphs it is $O(|V|^4)$, but see the remarks at `igraph_maxflow()`. For undirected graphs it is $O(|V||E|+|V|^2 \log|V|)$. $|V|$ and $|E|$ are the number of vertices and edges respectively.

Example 22.5. File `examples/simple/igraph_mincut.c`

igraph_mincut_value — The minimum edge cut in a graph

```
igraph_error_t igraph_mincut_value(const igraph_t *graph, igraph_real_t *res,  
                                   const igraph_vector_t *capacity);
```

The minimum edge cut in a graph is the total minimum weight of the edges needed to remove from the graph to make the graph *not* strongly connected. (If the original graph is not strongly connected then this is zero.) Note that in undirected graphs strong connectedness is the same as weak connectedness.

The minimum cut can be calculated with maximum flow techniques, although the current implementation does this only for directed graphs and a separate non-flow based implementation is used for undirected graphs. See Mechthild Stoer and Frank Wagner: A simple min-cut algorithm, Journal of the ACM 44 585--591, 1997. For directed graphs the maximum flow is calculated between a fixed vertex and all the other vertices in the graph and this is done in both directions. Then the minimum is taken to get the minimum cut.

Arguments:

graph: The input graph.

res: Pointer to a real variable, the result will be stored here.

capacity: Pointer to the capacity vector, it should contain the same number of non-negative numbers as the number of edges in the graph. If a null pointer then all edges will have unit capacity.

Returns:

Error code.

See also:

`igraph_mincut()`, `igraph_maxflow_value()`, `igraph_st_mincut_value()`.

Time complexity: $O(\log(|V|)*|V|^2)$ for undirected graphs and $O(|V|^4)$ for directed graphs, but see also the discussion at the documentation of `igraph_maxflow_value()`.

igraph_gomory_hu_tree — Gomory-Hu tree of a graph.

```
igraph_error_t igraph_gomory_hu_tree(const igraph_t *graph, igraph_t *tree,  
                                     igraph_vector_t *flows, const igraph_vector_t *capaci
```

The Gomory-Hu tree is a concise representation of the value of all the maximum flows (or minimum cuts) in a graph. The vertices of the tree correspond exactly to the vertices of the original graph in the same order. Edges of the Gomory-Hu tree are annotated by flow values. The value of the maximum flow (or minimum cut) between an arbitrary (u,v) vertex pair in the original graph is then given by the minimum flow value (i.e. edge annotation) along the shortest path between u and v in the Gomory-Hu tree.

This implementation uses Gusfield's algorithm to construct the Gomory-Hu tree. See the following paper for more details:

Gusfield D: Very simple methods for all pairs network flow analysis. SIAM J Comput 19(1):143-155, 1990.

Arguments:

graph: The input graph.

tree: Pointer to an uninitialized graph; the result will be stored here.

flows: Pointer to an uninitialized vector; the flow values corresponding to each edge in the Gomory-Hu tree will be returned here. You may pass a NULL pointer here if you are not interested in the flow values.

capacity: Vector containing the capacity of the edges. If NULL, then every edge is considered to have capacity 1.0.

Returns:

Error code.

Time complexity: $O(|V|^4)$ since it performs a max-flow calculation between vertex zero and every other vertex and max-flow is $O(|V|^3)$.

See also:

`igraph_maxflow()`

Connectivity

`igraph_st_edge_connectivity` — Edge connectivity of a pair of vertices

```
igraph_error_t igraph_st_edge_connectivity(const igraph_t *graph, igraph_integer_t source,
                                           igraph_integer_t target);
```

The edge connectivity of two vertices (*source* and *target*) in a graph is the minimum number of edges that have to be deleted from the graph to eliminate all paths from *source* to *target*.

This function uses the maximum flow algorithm to calculate the edge connectivity.

Arguments:

graph: The input graph, it has to be directed.

res: Pointer to an integer, the result will be stored here.

source: The id of the source vertex.

target: The id of the target vertex.

Returns:

Error code.

Time complexity: $O(|V|^3)$.

See also:

`igraph_maxflow_value()`, `igraph_edge_connectivity()`, `igraph_st_vertex_connectivity()`, `igraph_vertex_connectivity()`.

`igraph_edge_connectivity` — The minimum edge connectivity in a graph.

```
igraph_error_t igraph_edge_connectivity(const igraph_t *graph, igraph_integer_t  
                                         igraph_bool_t checks);
```

This is the minimum of the edge connectivity over all pairs of vertices in the graph.

The edge connectivity of a graph is the same as group adhesion as defined in Douglas R. White and Frank Harary: The cohesiveness of blocks in social networks: node connectivity and conditional density, Sociological Methodology 31:305--359, 2001.

Arguments:

graph: The input graph.

res: Pointer to an integer, the result will be stored here.

checks: Logical constant. Whether to check that the graph is connected and also the degree of the vertices. If the graph is not (strongly) connected then the connectivity is obviously zero. Otherwise if the minimum degree is one then the edge connectivity is also one. It is a good idea to perform these checks, as they can be done quickly compared to the connectivity calculation itself. They were suggested by Peter McMahan, thanks Peter.

Returns:

Error code.

Time complexity: $O(\log(|V|)*|V|^2)$ for undirected graphs and $O(|V|^4)$ for directed graphs, but see also the discussion at the documentation of `igraph_maxflow_value()`.

See also:

`igraph_st_edge_connectivity()`, `igraph_maxflow_value()`, `igraph_vertex_connectivity()`.

`igraph_st_vertex_connectivity` — The vertex connectivity of a pair of vertices

```
igraph_error_t igraph_st_vertex_connectivity(const igraph_t *graph,
```

```
igraph_integer_t *res,  
igraph_integer_t source,  
igraph_integer_t target,  
igraph_vconn_nei_t neighbors);
```

The vertex connectivity of two vertices (*source* and *target*) is the minimum number of vertices that have to be deleted to eliminate all paths from *source* to *target*. Directed paths are considered in directed graphs.

The vertex connectivity of a pair is the same as the number of different (i.e. node-independent) paths from *source* to *target*.

The current implementation uses maximum flow calculations to obtain the result.

Arguments:

graph: The input graph.

res: Pointer to an integer, the result will be stored here.

source: The id of the source vertex.

target: The id of the target vertex.

neighbors: A constant giving what to do if the two vertices are connected. Possible values: `IGRAPH_VCONN_NEI_ERROR`, stop with an error message, `IGRAPH_VCONN_NEGATIVE`, return -1. `IGRAPH_VCONN_NUMBER_OF_NODES`, return the number of nodes. `IGRAPH_VCONN_IGNORE`, ignore the fact that the two vertices are connected and calculate the number of vertices needed to eliminate all paths except for the trivial (direct) paths between *source* and *vertex*. TODO: what about neighbors?

Returns:

Error code.

Time complexity: $O(|V|^3)$, but see the discussion at `igraph_maxflow_value()`.

See also:

```
igraph_vertex_connectivity(),  
igraph_maxflow_value(),  
igraph_edge_connectivity(),
```

igraph_vertex_connectivity — The vertex connectivity of a graph

```
igraph_error_t igraph_vertex_connectivity(const igraph_t *graph, igraph_integer_t  
igraph_bool_t checks);
```

The vertex connectivity of a graph is the minimum vertex connectivity along each pairs of vertices in the graph.

The vertex connectivity of a graph is the same as group cohesion as defined in Douglas R. White and Frank Harary: The cohesiveness of blocks in social networks: node connectivity and conditional density, Sociological Methodology 31:305--359, 2001.

Arguments:

- graph*: The input graph.
- res*: Pointer to an integer, the result will be stored here.
- checks*: Logical constant. Whether to check that the graph is connected and also the degree of the vertices. If the graph is not (strongly) connected then the connectivity is obviously zero. Otherwise if the minimum degree is one then the vertex connectivity is also one. It is a good idea to perform these checks, as they can be done quickly compared to the connectivity calculation itself. They were suggested by Peter McMahan, thanks Peter.

Returns:

Error code.

Time complexity: $O(|V|^5)$.

See also:

`igraph_st_vertex_connectivity()`, `igraph_maxflow_value()`, and
`igraph_edge_connectivity()`.

Edge- and vertex-disjoint paths

`igraph_edge_disjoint_paths` — The maximum number of edge-disjoint paths between two vertices.

```
igraph_error_t igraph_edge_disjoint_paths(const igraph_t *graph, igraph_integer_t  
                                         igraph_integer_t source,  
                                         igraph_integer_t target);
```

A set of paths between two vertices is called edge-disjoint if they do not share any edges. The maximum number of edge-disjoint paths are calculated by this function using maximum flow techniques. Directed paths are considered in directed graphs.

Note that the number of disjoint paths is the same as the edge connectivity of the two vertices using uniform edge weights.

Arguments:

- graph*: The input graph, can be directed or undirected.
- res*: Pointer to an integer variable, the result will be stored here.
- source*: The id of the source vertex.
- target*: The id of the target vertex.

Returns:

Error code.

Time complexity: $O(|V|^3)$, but see the discussion at `igraph_maxflow_value()`.

See also:

```
igraph_vertex_disjoint_paths(),      igraph_st_edge_connectivity(),  
igraph_maxflow_value().
```

igraph_vertex_disjoint_paths — Maximum number of vertex-disjoint paths between two vertices.

```
igraph_error_t igraph_vertex_disjoint_paths(const igraph_t *graph, igraph_integer_t  
                                             igraph_integer_t source,  
                                             igraph_integer_t target);
```

A set of paths between two vertices is called vertex-disjoint if they share no vertices. The calculation is performed by using maximum flow techniques.

Note that the number of vertex-disjoint paths is the same as the vertex connectivity of the two vertices in most cases (if the two vertices are not connected by an edge).

Arguments:

graph: The input graph.

res: Pointer to an integer variable, the result will be stored here.

source: The id of the source vertex.

target: The id of the target vertex.

Returns:

Error code.

Time complexity: $O(|V|^3)$.

See also:

```
igraph_edge_disjoint_paths(),      igraph_vertex_connectivity(),  
igraph_maxflow_value().
```

Graph adhesion and cohesion

igraph_adhesion — Graph adhesion, this is (almost) the same as edge connectivity.

```
igraph_error_t igraph_adhesion(const igraph_t *graph, igraph_integer_t *res,  
                                igraph_bool_t checks);
```

This quantity is defined by White and Harary in The cohesiveness of blocks in social networks: node connectivity and conditional density, (Sociological Methodology 31:305--359, 2001) and basically it is the edge connectivity of the graph with uniform edge weights.

Arguments:

- graph*: The input graph, either directed or undirected.
- res*: Pointer to an integer, the result will be stored here.
- checks*: Logical constant. Whether to check that the graph is connected and also the degree of the vertices. If the graph is not (strongly) connected then the cohesion is obviously zero. Otherwise if the minimum degree is one then the cohesion is also one. It is a good idea to perform these checks, as they can be done quickly compared to the edge connectivity calculation itself. They were suggested by Peter McMahan, thanks Peter. *

Returns:

Error code.

Time complexity: $O(\log(|V|)*|V|^2)$ for undirected graphs and $O(|V|^4)$ for directed graphs, but see also the discussion at the documentation of `igraph_maxflow_value()`.

See also:

`igraph_cohesion()`, `igraph_maxflow_value()`, `igraph_edge_connectivity()`, `igraph_mincut_value()`.

igraph_cohesion — Graph cohesion, this is the same as vertex connectivity.

```
igraph_error_t igraph_cohesion(const igraph_t *graph, igraph_integer_t *res,
                               igraph_bool_t checks);
```

This quantity was defined by White and Harary in “The cohesiveness of blocks in social networks: node connectivity and conditional density”, (Sociological Methodology 31:305--359, 2001) and it is the same as the vertex connectivity of a graph.

Arguments:

- graph*: The input graph.
- res*: Pointer to an integer variable, the result will be stored here.
- checks*: Logical constant. Whether to check that the graph is connected and also the degree of the vertices. If the graph is not (strongly) connected then the cohesion is obviously zero. Otherwise if the minimum degree is one then the cohesion is also one. It is a good idea to perform these checks, as they can be done quickly compared to the vertex connectivity calculation itself. They were suggested by Peter McMahan, thanks Peter.

Returns:

Error code.

Time complexity: $O(|V|^4)$, $|V|$ is the number of vertices. In practice it is more like $O(|V|^2)$, see `igraph_maxflow_value()`.

See also:

```
igraph_vertex_connectivity(),igraph_adhesion(),igraph_maxflow_val-  
ue().
```

Cohesive blocks

igraph_cohesive_blocks — Identifies the hierarchical cohesive block structure of a graph

```
igraph_error_t igraph_cohesive_blocks(const igraph_t *graph,  
                                       igraph_vector_int_list_t *blocks,  
                                       igraph_vector_int_t *cohesion,  
                                       igraph_vector_int_t *parent,  
                                       igraph_t *block_tree);
```

Cohesive blocking is a method of determining hierarchical subsets of graph vertices based on their structural cohesion (or vertex connectivity). For a given graph G , a subset of its vertices S is said to be maximally k -cohesive if there is no superset of S with vertex connectivity greater than or equal to k . Cohesive blocking is a process through which, given a k -cohesive set of vertices, maximally l -cohesive subsets are recursively identified with $l > k$. Thus a hierarchy of vertex subsets is found, with the entire graph G at its root. See the following reference for details: J. Moody and D. R. White. Structural cohesion and embeddedness: A hierarchical concept of social groups. *American Sociological Review*, 68(1):103--127, Feb 2003.

This function implements cohesive blocking and calculates the complete cohesive block hierarchy of a graph.

Arguments:

- graph*: The input graph. It must be undirected and simple. See `igraph_is_simple()`.
- blocks*: If not a null pointer, then it must be an initialized list of integers vectors; the cohesive blocks will be stored here. Each block is encoded with a vector of type `igraph_vector_int_t` that contains the vertex IDs of the block.
- cohesion*: If not a null pointer, then it must be an initialized vector and the cohesion of the blocks is stored here, in the same order as the blocks in the *blocks* pointer vector.
- parent*: If not a null pointer, then it must be an initialized vector and the block hierarchy is stored here. For each block, the id (i.e. the position in the *blocks* pointer vector) of its parent block is stored. For the top block in the hierarchy, -1 is stored.
- block_tree*: If not a null pointer, then it must be a pointer to an uninitialized graph, and the block hierarchy is stored here as an igraph graph. The vertex IDs correspond to the order of the blocks in the *blocks* vector.

Returns:

Error code.

Time complexity: TODO.

Example 22.6. File `examples/simple/cohesive_blocks.c`

Chapter 23. Vertex separators

igraph_is_separator — Would removing this set of vertices disconnect the graph?

```
igraph_error_t igraph_is_separator(const igraph_t *graph,
                                   const igraph_vs_t candidate,
                                   igraph_bool_t *res);
```

Arguments:

graph: The input graph. It may be directed, but edge directions are ignored.

candidate: The candidate separator. It must not contain all vertices.

res: Pointer to a Boolean variable, the result is stored here.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number vertices and edges.

Example 23.1. File `examples/simple/igraph_is_separator.c`

igraph_is_minimal_separator — Decides whether a set of vertices is a minimal separator.

```
igraph_error_t igraph_is_minimal_separator(const igraph_t *graph,
                                           const igraph_vs_t candidate,
                                           igraph_bool_t *res);
```

A set of vertices is a minimal separator, if the removal of the vertices disconnects the graph, and this is not true for any subset of the set.

This implementation first checks that the given candidate is a separator, by calling `igraph_is_separator()`. If it is a separator, then it checks that each subset of size $n-1$, where n is the size of the candidate, is not a separator.

Arguments:

graph: The input graph. It may be directed, but edge directions are ignored.

candidate: The candidate minimal separators.

res: Pointer to a boolean variable, the result is stored here.

Returns:

Error code.

Time complexity: $O(n(|V|+|E|))$, $|V|$ is the number of vertices, $|E|$ is the number of edges, n is the number vertices in the candidate separator.

Example	23.2.	File	examples/simple/
igraph_is_minimal_separator.c			

igraph_all_minimal_st_separators — List all vertex sets that are minimal (s,t) separators for some s and t.

```
igraph_error_t igraph_all_minimal_st_separators(  
    const igraph_t *graph, igraph_vector_int_list_t *separators  
);
```

This function lists all vertex sets that are minimal (s,t) separators for some (s,t) vertex pair.

Note that some vertex sets returned by this function may not be minimal with respect to disconnecting the graph (or increasing the number of connected components). Take for example the 5-vertex graph with edges 0-1-2-3-4-1. This function returns the vertex sets $\{1\}$, $\{2, 4\}$ and $\{1, 3\}$. Notice that $\{1, 3\}$ is not minimal with respect to disconnecting the graph, as $\{1\}$ would be sufficient for that. However, it is minimal with respect to separating vertices 2 and 4.

See more about the implemented algorithm in Anne Berry, Jean-Paul Bordat and Olivier Cogis: Generating All the Minimal Separators of a Graph, In: Peter Widmayer, Gabriele Neyer and Stephan Eidenbenz (editors): Graph-theoretic concepts in computer science, 1665, 167--172, 1999. Springer. https://doi.org/10.1007/3-540-46784-X_17

Arguments:

<i>graph</i> :	The input graph. It may be directed, but edge directions are ignored.
<i>separators</i> :	An initialized pointer vector, the separators are stored here. It is a list of pointers to <code>igraph_vector_int_t</code> objects. Each vector will contain the ids of the vertices in the separator. To free all memory allocated for <i>separators</i> , you need call <code>igraph_vector_destroy()</code> and then <code>igraph_free()</code> on each element, before destroying the pointer vector itself.

Returns:

Error code.

See also:

```
igraph_minimum_size_separators()
```

Time complexity: $O(n|V|^3)$, $|V|$ is the number of vertices, n is the number of separators.

Example	23.3.	File	examples/simple/
igraph_minimal_separators.c			

igraph_minimum_size_separators — Find all minimum size separating vertex sets.

```
igraph_error_t igraph_minimum_size_separators(  
    const igraph_t *graph, igraph_vector_int_list_t *separators  
);
```

This function lists all separator vertex sets of minimum size. A vertex set is a separator if its removal disconnects the graph.

The implementation is based on the following paper: Arkady Kanevsky: Finding all minimum-size separating vertex sets in a graph, Networks 23, 533--541, 1993.

Arguments:

graph: The input graph, which must be undirected.

separators: An initialized list of integer vectors, the separators are stored here. It is a list of pointers to `igraph_vector_int_t` objects. Each vector will contain the IDs of the vertices in the separator. The separators are returned in an arbitrary order.

Returns:

Error code.

Time complexity: TODO.

Example	23.4.	File	examples/simple/
igraph_minimum_size_separators.c			

igraph_even_tarjan_reduction — Even-Tarjan reduction of a graph.

```
igraph_error_t igraph_even_tarjan_reduction(const igraph_t *graph, igraph_t *gr  
    igraph_vector_t *capacity);
```

A digraph is created with twice as many vertices and edges. For each original vertex i , two vertices $i' = i$ and $i'' = i' + n$ are created, with a directed edge from i' to i'' . For each original directed edge from i to j , two new edges are created, from i' to j'' and from i'' to j' .

This reduction is used in the paper (observation 2): Arkady Kanevsky: Finding all minimum-size separating vertex sets in a graph, Networks 23, 533--541, 1993.

The original paper where this reduction was conceived is Shimon Even and R. Endre Tarjan: Network Flow and Testing Graph Connectivity, SIAM J. Comput., 4(4), 507–518.

Arguments:

graph: A graph. Although directness is not checked, this function is commonly used only on directed graphs.

graphbar: Pointer to a new directed graph that will contain the reduction, with twice as many vertices and edges.

capacity: Pointer to an initialized vector or a null pointer. If not a null pointer, then it will be filled the capacity from the reduction: the first $|E|$ elements are 1, the remaining $|E|$ are equal to $|V|$ (which is used to indicate infinity).

Returns:

Error code.

Time complexity: $O(|E|+|V|)$.

Example 23.5. File `examples/simple/even_tarjan.c`

Chapter 24. Detecting community structure

Common functions related to community structure

igraph_modularity — Calculates the modularity of a graph with respect to some clusters or vertex types.

```
igraph_error_t igraph_modularity(const igraph_t *graph,
                                const igraph_vector_int_t *membership,
                                const igraph_vector_t *weights,
                                const igraph_real_t resolution,
                                const igraph_bool_t directed,
                                igraph_real_t *modularity);
```

The modularity of a graph with respect to some clustering of the vertices (or assignment of vertex types) measures how strongly separated the different clusters are from each other compared to a random null model. It is defined as

$$Q = 1/(2m) \sum_{i,j} (A_{ij} - \# k_i k_j / (2m)) \#(c_i, c_j),$$

where m is the number of edges, A_{ij} is the adjacency matrix, k_i is the degree of vertex i , c_i is the cluster that vertex i belongs to (or its vertex type), $\#(i, j) = 1$ if $i = j$ and 0 otherwise, and the sum goes over all i, j pairs of vertices. Note that in this formula, the diagonal of the adjacency matrix contains twice the number of self-loops.

The resolution parameter $\#$ allows weighting the random null model, which might be useful when finding partitions with a high modularity. Maximizing modularity with higher values of the resolution parameter typically results in more, smaller clusters when finding partitions with a high modularity. Lower values typically results in fewer, larger clusters. The original definition of modularity is retrieved when setting $\# = 1$.

Modularity can also be calculated on directed graphs. This only requires a relatively modest change,

$$Q = 1/m \sum_{i,j} (A_{ij} - \# k^{\text{out}}_i k^{\text{in}}_j / m) \#(c_i, c_j),$$

where k^{out}_i is the out-degree of node i and k^{in}_j is the in-degree of node j .

Modularity on weighted graphs is also meaningful. When taking edge weights into account, A_{ij} equals the weight of the corresponding edge (or 0 if there is no edge), k_i is the strength (i.e. the weighted degree) of vertex i , with similar counterparts for a directed graph, and m is the total weight of all edges.

Note that the modularity is not well-defined for graphs with no edges. `igraph` returns NaN for graphs with no edges; see <https://github.com/igraph/igraph/issues/1539> for a detailed discussion.

For the original definition of modularity, see Newman, M. E. J., and Girvan, M. (2004). Finding and evaluating community structure in networks. *Physical Review E* 69, 026113. <https://doi.org/10.1103/PhysRevE.69.026113>

For the directed definition of modularity, see Leicht, E. A., and Newman, M. E. J. (2008). Community Structure in Directed Networks. Physical Review Letters 100, 118703. <https://doi.org/10.1103/PhysRevLett.100.118703>

For the introduction of the resolution parameter q , see Reichardt, J., and Bornholdt, S. (2006). Statistical mechanics of community detection. Physical Review E 74, 016110. <https://doi.org/10.1103/PhysRevE.74.016110>

Arguments:

<i>graph</i> :	The input graph.
<i>membership</i> :	Numeric vector of integer values which gives the type of each vertex, i.e. the cluster to which it belongs. It does not have to be consecutive, i.e. empty communities are allowed.
<i>weights</i> :	Weight vector or NULL if no weights are specified.
<i>resolution</i> :	The resolution parameter q . Must not be negative. Set it to 1 to use the classical definition of modularity.
<i>directed</i> :	Whether to use the directed or undirected version of modularity. Ignored for undirected graphs.
<i>modularity</i> :	Pointer to a real number, the result will be stored here.

Returns:

Error code.

See also:

`igraph_modularity_matrix()`

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges.

igraph_modularity_matrix — Calculates the modularity matrix.

```
igraph_error_t igraph_modularity_matrix(const igraph_t *graph,
                                         const igraph_vector_t *weights,
                                         const igraph_real_t resolution,
                                         igraph_matrix_t *modmat,
                                         igraph_bool_t directed);
```

This function returns the modularity matrix, which is defined as

$$B_{ij} = A_{ij} - \frac{k_i k_j}{2m}$$

for undirected graphs, where A_{ij} is the adjacency matrix, q is the resolution parameter, k_i is the degree of vertex i , and m is the number of edges in the graph. When there are no edges, or the weights add up to zero, the result is undefined.

For directed graphs the modularity matrix is changed to

$$B_{ij} = A_{ij} - \frac{k^{\text{out}}_i k^{\text{in}}_j}{m}$$

where k^{out}_i is the out-degree of node i and k^{in}_j is the in-degree of node j .

Note that self-loops in undirected graphs are multiplied by 2 in this implementation. If weights are specified, the weighted counterparts of the adjacency matrix and degrees are used.

Arguments:

<i>graph</i> :	The input graph.
<i>weights</i> :	Edge weights, pointer to a vector. If this is a null pointer then every edge is assumed to have a weight of 1.
<i>resolution</i> :	The resolution parameter #. Must not be negative. Default is 1. Lower values favor fewer, larger communities; higher values favor more, smaller communities.
<i>modmat</i> :	Pointer to an initialized matrix in which the modularity matrix is stored.
<i>directed</i> :	For directed graphs: if the edges should be treated as undirected. For undirected graphs this is ignored.

See also:

`igraph_modularity()`

`igraph_community_optimal_modularity` — Calculate the community structure with the highest modularity value

```
igraph_error_t igraph_community_optimal_modularity(const igraph_t *graph,
                                                    igraph_real_t *modularity,
                                                    igraph_vector_int_t *membership,
                                                    const igraph_vector_t *weights);
```

This function calculates the optimal community structure for a graph, in terms of maximal modularity score.

The calculation is done by transforming the modularity maximization into an integer programming problem, and then calling the GLPK library to solve that. Please see Ulrik Brandes et al.: On Modularity Clustering, IEEE Transactions on Knowledge and Data Engineering 20(2):172-188, 2008.

Note that modularity optimization is an NP-complete problem, and all known algorithms for it have exponential time complexity. This means that you probably don't want to run this function on larger graphs. Graphs with up to fifty vertices should be fine, graphs with a couple of hundred vertices might be possible.

Arguments:

<i>graph</i> :	The input graph. It is always treated as undirected.
<i>modularity</i> :	Pointer to a real number, or a null pointer. If it is not a null pointer, then a optimal modularity value is returned here.
<i>membership</i> :	Pointer to a vector, or a null pointer. If not a null pointer, then the membership vector of the optimal community structure is stored here.
<i>weights</i> :	Vector giving the weights of the edges. If it is NULL then each edge is supposed to have the same weight.

Returns:

Error code. When GLPK is not available, `IGRAPH_UNIMPLEMENTED` is returned.

See also:

`igraph_modularity()`, `igraph_community_fastgreedy()` for an algorithm that finds a local optimum in a greedy way.

Time complexity: exponential in the number of vertices.

Example **24.1.** **File** **examples/simple/igraph_community_optimal_modularity.c**

igraph_community_to_membership — Create membership vector from community structure dendrogram

```
igraph_error_t igraph_community_to_membership(const igraph_matrix_int_t *merges,
                                              igraph_integer_t nodes,
                                              igraph_integer_t steps,
                                              igraph_vector_int_t *membership,
                                              igraph_vector_int_t *csize);
```

This function creates a membership vector from a community structure dendrogram. A membership vector contains for each vertex the id of its graph component, the graph components are numbered from zero, see the same argument of `igraph_connected_components()` for an example of a membership vector.

Many community detection algorithms return with a *merges* matrix, `igraph_community_walktrap()` and `igraph_community_edge_betweenness()` are two examples. The matrix contains the merge operations performed while mapping the hierarchical structure of a network. If the matrix has $n-1$ rows, where n is the number of vertices in the graph, then it contains the hierarchical structure of the whole network and it is called a dendrogram.

This function performs *steps* merge operations as prescribed by the *merges* matrix and returns the current state of the network.

If *merges* is not a complete dendrogram, it is possible to take *steps* steps if *steps* is not bigger than the number lines in *merges*.

Arguments:

<i>merges</i> :	The two-column matrix containing the merge operations. See <code>igraph_community_walktrap()</code> for the detailed syntax.
<i>nodes</i> :	The number of leaf nodes in the dendrogram.
<i>steps</i> :	Integer constant, the number of steps to take.
<i>membership</i> :	Pointer to an initialized vector, the membership results will be stored here, if not NULL. The vector will be resized as needed.
<i>csize</i> :	Pointer to an initialized vector, or NULL. If not NULL then the sizes of the components will be stored here, the vector will be resized as needed.

See also:

`igraph_community_walktrap()`, `igraph_community_edge_betweenness()`, `igraph_community_fastgreedy()` for community structure detection algorithms.

Time complexity: $O(|V|)$, the number of vertices in the graph.

igraph_reindex_membership — Makes the IDs in a membership vector continuous

```
igraph_error_t igraph_reindex_membership(igraph_vector_int_t *membership,
                                         igraph_vector_int_t *new_to_old,
                                         igraph_integer_t *nb_clusters);
```

This function reindexes component IDs in a membership vector in a way that the new IDs start from zero and go up to $C-1$, where C is the number of unique component IDs in the original vector. The supplied membership is expected to fall in the range $0, \dots, n-1$.

Arguments:

- membership*: Numeric vector which gives the type of each vertex, i.e. the component to which it belongs. The vector will be altered in-place.
- new_to_old*: Pointer to a vector which will contain the old component ID for each new one, or NULL, in which case it is not returned. The vector will be resized as needed.
- nb_clusters*: Pointer to an integer for the number of distinct clusters. If not NULL, this will be updated to reflect the number of distinct clusters found in membership.

Time complexity: should be $O(n)$ for n elements.

igraph_compare_communities — Compares community structures using various metrics.

```
igraph_error_t igraph_compare_communities(const igraph_vector_int_t *comm1,
                                         const igraph_vector_int_t *comm2, igraph_real_t *
                                         igraph_community_comparison_t method);
```

This function assesses the distance between two community structures using the variation of information (VI) metric of Meila (2003), the normalized mutual information (NMI) of Danon et al (2005), the split-join distance of van Dongen (2000), the Rand index of Rand (1971) or the adjusted Rand index of Hubert and Arabie (1985).

Some of these measures are defined based on the entropy of a discrete random variable associated with a given clustering C of vertices. Let p_i be the probability that a randomly picked vertex would be part of cluster i . Then the entropy of the clustering is

$$H(C) = - \sum_i p_i \log p_i$$

Similarly, we can define the joint entropy of two clusterings C_1 and C_2 based on the probability p_{ij} that a random vertex is part of cluster i in the first clustering and cluster j in the second one:

$$H(C_1, C_2) = - \sum_{ij} p_{ij} \log p_{ij}$$

The mutual information of C_1 and C_2 is then $MI(C_1, C_2) = H(C_1) + H(C_2) - H(C_1, C_2) \geq 0$. A large mutual information indicates a high overlap between the two clusterings. The normalized mutual information, as computed by igraph, is

$$\text{NMI}(C_1, C_2) = 2 \text{MI}(C_1, C_2) / (H(C_1) + H(C_2)).$$

It takes its value from the interval (0, 1], with 1 achieved when the two clusterings coincide.

The variation of information is defined as $\text{VI}(C_1, C_2) = [H(C_1) - \text{MI}(C_1, C_2)] + [H(C_2) - \text{MI}(C_1, C_2)]$. Lower values of the variation of information indicate a smaller difference between the two clusterings, with $\text{VI} = 0$ achieved precisely when they coincide.

For an explanation of the split-join distance, see `igraph_split_join_distance()`.

References:

Meil# M: Comparing clusterings by the variation of information. In: Schölkopf B, Warmuth MK (eds.). Learning Theory and Kernel Machines: 16th Annual Conference on Computational Learning Theory and 7th Kernel Workshop, COLT/Kernel 2003, Washington, DC, USA. Lecture Notes in Computer Science, vol. 2777, Springer, 2003. ISBN: 978-3-540-40720-1. https://doi.org/10.1007/978-3-540-45167-9_14

Danon L, Diaz-Guilera A, Duch J, Arenas A: Comparing community structure identification. J Stat Mech P09008, 2005. <https://doi.org/10.1088/1742-5468/2005/09/P09008>

van Dongen S: Performance criteria for graph clustering and Markov cluster experiments. Technical Report INS-R0012, National Research Institute for Mathematics and Computer Science in the Netherlands, Amsterdam, May 2000. <https://ir.cwi.nl/pub/4461>

Rand WM: Objective criteria for the evaluation of clustering methods. J Am Stat Assoc 66(336):846-850, 1971. <https://doi.org/10.2307/2284239>

Hubert L and Arabie P: Comparing partitions. Journal of Classification 2:193-218, 1985. <https://doi.org/10.1007/BF01908075>

Arguments:

comm1: the membership vector of the first community structure

comm2: the membership vector of the second community structure

result: the result is stored here.

method: the comparison method to use. `IGRAPH_COMMCMP_VI` selects the variation of information (VI) metric of Meila (2003), `IGRAPH_COMMCMP_NMI` selects the normalized mutual information measure proposed by Danon et al (2005), `IGRAPH_COMMCMP_SPLIT_JOIN` selects the split-join distance of van Dongen (2000), `IGRAPH_COMMCMP_P_RAND` selects the unadjusted Rand index (1971) and `IGRAPH_COMMCMP_ADJUSTED_RAND` selects the adjusted Rand index.

Returns:

Error code.

See also:

`igraph_split_join_distance()`.

Time complexity: $O(n \log(n))$.

igraph_split_join_distance — Calculates the split-join distance of two community structures

```
igraph_error_t igraph_split_join_distance(const igraph_vector_int_t *comm1,
                                          const igraph_vector_int_t *comm2, igraph_integer_t *distance12,
                                          igraph_integer_t *distance21);
```

The split-join distance between partitions A and B is the sum of the projection distance of A from B and the projection distance of B from A. The projection distance is an asymmetric measure and it is defined as follows:

First, each set in partition A is evaluated against all sets in partition B. For each set in partition A, the best matching set in partition B is found and the overlap size is calculated. (Matching is quantified by the size of the overlap between the two sets). Then, the maximal overlap sizes for each set in A are summed together and subtracted from the number of elements in A.

The split-join distance will be returned in two arguments, `distance12` will contain the projection distance of the first partition from the second, while `distance21` will be the projection distance of the second partition from the first. This makes it easier to detect whether a partition is a subpartition of the other, since in this case, the corresponding distance will be zero.

Reference:

van Dongen S: Performance criteria for graph clustering and Markov cluster experiments. Technical Report INS-R0012, National Research Institute for Mathematics and Computer Science in the Netherlands, Amsterdam, May 2000.

Arguments:

comm1: the membership vector of the first community structure

comm2: the membership vector of the second community structure

distance12: pointer to an `igraph_integer_t`, the projection distance of the first community structure from the second one will be returned here.

distance21: pointer to an `igraph_integer_t`, the projection distance of the second community structure from the first one will be returned here.

Returns:

Error code.

See also:

`igraph_compare_communities()` with the `IGRAPH_COMMCMP_SPLIT_JOIN` method if you are not interested in the individual distances but only the sum of them.

Time complexity: $O(n \log(n))$.

Community structure based on statistical mechanics

`igraph_community_spinglass` — Community detection based on statistical mechanics

```
igraph_error_t igraph_community_spinglass(const igraph_t *graph,
```

```

const igraph_vector_t *weights,
igraph_real_t *modularity,
igraph_real_t *temperature,
igraph_vector_int_t *membership,
igraph_vector_int_t *csize,
igraph_integer_t spins,
igraph_bool_t parupdate,
igraph_real_t starttemp,
igraph_real_t stoptemp,
igraph_real_t coolfact,
igraph_spincomm_update_t update_rule,
igraph_real_t gamma,
igraph_spinglass_implementation_t implementation,
igraph_real_t gamma_minus);

```

This function implements the community structure detection algorithm proposed by Joerg Reichardt and Stefan Bornholdt. The algorithm is described in their paper: Statistical Mechanics of Community Detection, <http://arxiv.org/abs/cond-mat/0603718> .

From version 0.6, igraph also supports an extension to the algorithm that allows negative edge weights. This is described in V. A. Traag and Jeroen Bruggeman: Community detection in networks with positive and negative links, <http://arxiv.org/abs/0811.2329> .

Arguments:

<i>graph</i> :	The input graph, it may be directed but the direction of the edges is not used in the algorithm.
<i>weights</i> :	The vector giving the edge weights, it may be NULL, in which case all edges are weighted equally. The edge weights must be positive unless using the IGRAPH_SPINCOMM_IMP_NEG implementation. This condition is not verified by the function.
<i>modularity</i> :	Pointer to a real number, if not NULL then the modularity score of the solution will be stored here. This is the generalized modularity that simplifies to the one defined in M. E. J. Newman and M. Girvan, Phys. Rev. E 69, 026113 (2004), if the gamma parameter is one.
<i>temperature</i> :	Pointer to a real number, if not NULL then the temperature at the end of the algorithm will be stored here.
<i>membership</i> :	Pointer to an initialized vector or NULL. If not NULL then the result of the clustering will be stored here. For each vertex, the number of its cluster is given, with the first cluster numbered zero. The vector will be resized as needed.
<i>csize</i> :	Pointer to an initialized vector or NULL. If not NULL then the sizes of the clusters will be stored here in cluster number order. The vector will be resized as needed.
<i>spins</i> :	Integer giving the number of spins, i.e. the maximum number of clusters. Usually it is not a program to give a high number here, the default was 25 in the original code. Even if the number of spins is high the number of clusters in the result might be small.
<i>parupdate</i> :	A logical constant, whether to update all spins in parallel. The default for this argument was <i>false</i> in the original code. It is not implemented in the IGRAPH_SPINCOMM_INP_NEG implementation.
<i>starttemp</i> :	Real number, the temperature at the start. The value of this argument was 1.0 in the original code.

<i>stoptemp:</i>	Real number, the algorithm stops at this temperature. The default was 0.01 in the original code.
<i>coolfact:</i>	Real number, the cooling factor for the simulated annealing. The default was 0.99 in the original code.
<i>update_rule:</i>	The type of the update rule. Possible values: IGRAPH_SPINCOMM_UPDATE_SIMPLE and IGRAPH_SPINCOMM_UPDATE_CONFIG. Basically this parameter defines the null model based on which the actual clustering is done. If this is IGRAPH_SPINCOMM_UPDATE_SIMPLE then the random graph (i.e. $G(n,p)$), if it is IGRAPH_SPINCOMM_UPDATE then the configuration model is used. The configuration means that the baseline for the clustering is a random graph with the same degree distribution as the input graph.
<i>gamma:</i>	Real number. The gamma parameter of the algorithm. This defines the weight of the missing and existing links in the quality function for the clustering. The default value in the original code was 1.0, which is equal weight to missing and existing edges. Smaller values make the existing links contribute more to the energy function which is minimized in the algorithm. Bigger values make the missing links more important. (If my understanding is correct.)
<i>implementation:</i>	Constant, chooses between the two implementations of the spin-glass algorithm that are included in igraph. IGRAPH_SPINCOMM_IMP_ORIG selects the original implementation, this is faster, IGRAPH_SPINCOMM_INP_NEG selects a new implementation by Vincent Traag that allows negative edge weights.
<i>gamma_minus:</i>	Real number. Parameter for the IGRAPH_SPINCOMM_IMP_NEG implementation. This specifies the balance between the importance of present and non-present negative weighted edges in a community. Smaller values of <i>gamma_minus</i> lead to communities with lesser negative intra-connectivity. If this argument is set to zero, the algorithm reduces to a graph coloring algorithm, using the number of spins as the number of colors.

Returns:

Error code.

See also:

`igraph_community_spinglass_single()` for calculating the community of a single vertex.

Time complexity: TODO.

igraph_community_spinglass_single — Community of a single node based on statistical mechanics

```
igraph_error_t igraph_community_spinglass_single(const igraph_t *graph,
                                                const igraph_vector_t *weights,
                                                igraph_integer_t vertex,
                                                igraph_vector_int_t *community,
                                                igraph_real_t *cohesion,
                                                igraph_real_t *adhesion,
                                                igraph_integer_t *inner_links,
                                                igraph_integer_t *outer_links,
```

```
igraph_integer_t spins,
igraph_spincomm_update_t update_rule,
igraph_real_t gamma);
```

This function implements the community structure detection algorithm proposed by Joerg Reichardt and Stefan Bornholdt. It is described in their paper: Statistical Mechanics of Community Detection, <http://arxiv.org/abs/cond-mat/0603718>.

This function calculates the community of a single vertex without calculating all the communities in the graph.

Arguments:

<i>graph</i> :	The input graph, it may be directed but the direction of the edges is not used in the algorithm.
<i>weights</i> :	Pointer to a vector with the weights of the edges. Alternatively NULL can be supplied to have the same weight for every edge.
<i>vertex</i> :	The vertex ID of the vertex of which this community is calculated.
<i>community</i> :	Pointer to an initialized vector, the result, the IDs of the vertices in the community of the input vertex will be stored here. The vector will be resized as needed.
<i>cohesion</i> :	Pointer to a real variable, if not NULL the cohesion index of the community will be stored here.
<i>adhesion</i> :	Pointer to a real variable, if not NULL the adhesion index of the community will be stored here.
<i>inner_links</i> :	Pointer to an integer, if not NULL the number of edges within the community is stored here.
<i>outer_links</i> :	Pointer to an integer, if not NULL the number of edges between the community and the rest of the graph will be stored here.
<i>spins</i> :	The number of spins to use, this can be higher than the actual number of clusters in the network, in which case some clusters will contain zero vertices.
<i>update_rule</i> :	The type of the update rule. Possible values: IGRAPH_SPINCOMM_UPDATE_SIMPLE and IGRAPH_SPINCOMM_UPDATE_CONFIG. Basically this parameter defined the null model based on which the actual clustering is done. If this is IGRAPH_SPINCOMM_UPDATE_SIMPLE then the random graph (ie. $G(n,p)$), if it is IGRAPH_SPINCOMM_UPDATE then the configuration model is used. The configuration means that the baseline for the clustering is a random graph with the same degree distribution as the input graph.
<i>gamma</i> :	Real number. The gamma parameter of the algorithm. This defined the weight of the missing and existing links in the quality function for the clustering. The default value in the original code was 1.0, which is equal weight to missing and existing edges. Smaller values make the existing links contribute more to the energy function which is minimized in the algorithm. Bigger values make the missing links more important. (If my understanding is correct.)

Returns:

Error code.

See also:

`igraph_community_spinglass()` for the traditional version of the algorithm.

Time complexity: TODO.

Community structure based on eigenvectors of matrices

The function documented in these section implements the “leading eigenvector” method developed by Mark Newman and published in MEJ Newman: Finding community structure using the eigenvectors of matrices, Phys Rev E 74:036104 (2006).

The heart of the method is the definition of the modularity matrix, B , which is $B=A-P$, A being the adjacency matrix of the (undirected) network, and P contains the probability that certain edges are present according to the “configuration model” In other words, a P_{ij} element of P is the probability that there is an edge between vertices i and j in a random network in which the degrees of all vertices are the same as in the input graph.

The leading eigenvector method works by calculating the eigenvector of the modularity matrix for the largest positive eigenvalue and then separating vertices into two community based on the sign of the corresponding element in the eigenvector. If all elements in the eigenvector are of the same sign that means that the network has no underlying community structure. Check Newman's paper to understand why this is a good method for detecting community structure.

The leading eigenvector community structure detection method is implemented in `igraph_community_leading_eigenvector()`. After the initial split, the following splits are done in a way to optimize modularity regarding to the original network. Note that any further refinement, for example using Kernighan-Lin, as proposed in Section V.A of Newman (2006), is not implemented here.

Example	24.2.	File	examples/simple/
<code>igraph_community_leading_eigenvector.c</code>			

`igraph_community_leading_eigenvector` — Leading eigenvector community finding (proper version).

```
igraph_error_t igraph_community_leading_eigenvector(
    const igraph_t *graph,
    const igraph_vector_t *weights,
    igraph_matrix_int_t *merges,
    igraph_vector_int_t *membership,
    igraph_integer_t steps,
    igraph_arnpack_options_t *options,
    igraph_real_t *modularity,
    igraph_bool_t start,
    igraph_vector_t *eigenvalues,
    igraph_vector_list_t *eigenvectors,
    igraph_vector_t *history,
    igraph_community_leading_eigenvector_callback_t *callback,
    void *callback_extra);
```

Newman's leading eigenvector method for detecting community structure. This is the proper implementation of the recursive, divisive algorithm: each split is done by maximizing the modularity regarding the original network, see MEJ Newman: Finding community structure in networks using the eigenvectors of matrices, Phys Rev E 74:036104 (2006).

Arguments:

<i>graph</i> :	The undirected input graph.	
<i>weights</i> :	The weights of the edges, or a null pointer for unweighted graphs.	
<i>merges</i> :	The result of the algorithm, a matrix containing the information about the splits performed. The matrix is built in the opposite way however, it is like the result of an agglomerative algorithm. If at the end of the algorithm (after <i>steps</i> steps was done) there are “p” communities, then these are numbered from zero to “p-1”. The first line of the matrix contains the first “merge” (which is in reality the last split) of two communities into community “p”, the merge in the second line forms community “p+1”, etc. The matrix should be initialized before calling and will be resized as needed. This argument is ignored if it is NULL.	
<i>membership</i> :	The membership of the vertices after all the splits were performed will be stored here. The vector must be initialized before calling and will be resized as needed. This argument is ignored if it is NULL. This argument can also be used to supply a starting configuration for the community finding, in the format of a membership vector. In this case the <i>start</i> argument must be set to 1.	
<i>steps</i> :	The maximum number of steps to perform. It might happen that some component (or the whole network) has no underlying community structure and no further steps can be done. If you want as many steps as possible then supply the number of vertices in the network here.	
<i>options</i> :	The options for ARPACK. Supply NULL here to use the defaults. <i>n</i> is always overwritten. <i>ncv</i> is set to at least 4.	
<i>modularity</i> :	If not a null pointer, then it must be a pointer to a real number and the modularity score of the final division is stored here.	
<i>start</i> :	Boolean, whether to use the community structure given in the <i>membership</i> argument as a starting point.	
<i>eigenvalues</i> :	Pointer to an initialized vector or a null pointer. If not a null pointer, then the eigenvalues calculated along the community structure detection are stored here. The non-positive eigenvalues, that do not result a split, are stored as well.	
<i>eigenvectors</i> :	If not a null pointer, then the eigenvectors that are calculated in each step of the algorithm are stored here, in a list of vectors. Each eigenvector is stored in an <code>igraph_vector_t</code> object.	
<i>history</i> :	Pointer to an initialized vector or a null pointer. If not a null pointer, then a trace of the algorithm is stored here, encoded numerically. The various operations:	
	IGRAPH_LEVC_HIST_START_FULL	Start the algorithm from an initial state where each connected component is a separate community.
	IGRAPH_LEVC_HIST_START_GIVEN	Start the algorithm from a given community structure. The next value in the vector contains the initial number of communities.
	IGRAPH_LEVC_HIST_SPLIT	Split a community into two communities. The id of the splitted community

nity is given in the next element of the history vector. The id of the first new community is the same as the id of the splitted community. The id of the second community equals to the number of communities before the split.

`IGRAPH_LEVC_HIST_FAILED` Tried to split a community, but it was not worth it, as it does not result in a bigger modularity value. The id of the community is given in the next element of the vector.

callback: A null pointer or a function of type `igraph_community_leading_eigenvector_callback_t`. If given, this callback function is called after each eigenvector/eigenvalue calculation. If the callback returns `IGRAPH_STOP`, then the community finding algorithm stops. If it returns `IGRAPH_SUCCESS`, the algorithm continues normally. Any other return value is considered an igraph error code and will terminate the algorithm with the same error code. See the arguments passed to the callback at the documentation of `igraph_community_leading_eigenvector_callback_t`.

callback_extra: Extra argument to pass to the callback function.

Returns:

Error code.

See also:

`igraph_community_walktrap()` and `igraph_community_spinglass()` for other community structure detection methods.

Time complexity: $O(|E|+|V|^2 \cdot \text{steps})$, $|V|$ is the number of vertices, $|E|$ the number of edges, “steps” the number of splits performed.

`igraph_community_leading_eigenvector_callback_t` — Callback for the leading eigenvector community finding method.

```
typedef igraph_error_t igraph_community_leading_eigenvector_callback_t(
    const igraph_vector_int_t *membership,
    igraph_integer_t comm,
    igraph_real_t eigenvalue,
    const igraph_vector_t *eigenvector,
    igraph_arnpack_function_t *arnpack_multiplier,
    void *arnpack_extra,
    void *extra);
```

The leading eigenvector community finding implementation in igraph is able to call a callback function, after each eigenvalue calculation. This callback function must be of `igraph_community_leading_eigenvector_callback_t` type. The following arguments are passed to the callback:

Arguments:

<i>membership:</i>	The actual membership vector, before recording the potential change implied by the newly found eigenvalue.
<i>comm:</i>	The id of the community that the algorithm tried to split in the last iteration. The community IDs are indexed from zero here!
<i>eigenvalue:</i>	The eigenvalue the algorithm has just found.
<i>eigenvector:</i>	The eigenvector corresponding to the eigenvalue the algorithm just found.
<i>arpack_multiplier:</i>	A function that was passed to <code>igraph_arpack_rssolve()</code> to solve the last eigenproblem.
<i>arpack_extra:</i>	The extra argument that was passed to the ARPACK solver.
<i>extra:</i>	Extra argument that as passed to <code>igraph_community_leading_eigenvector()</code> .

See also:

`igraph_community_leading_eigenvector()`, `igraph_arpack_function_t`, `igraph_arpack_rssolve()`.

igraph_le_community_to_membership — Vertex membership from the leading eigenvector community structure

```
igraph_error_t igraph_le_community_to_membership(const igraph_matrix_int_t *merges,
                                                igraph_integer_t steps,
                                                igraph_vector_int_t *membership,
                                                igraph_vector_int_t *csize);
```

This function creates a membership vector from the result of `igraph_community_leading_eigenvector()`. It takes membership and performs steps merges, according to the supplied merges matrix.

Arguments:

<i>merges:</i>	The two-column matrix containing the merge operations. See <code>igraph_community_walktrap()</code> for the detailed syntax. This is usually from the output of the leading eigenvector community structure detection routines.
<i>steps:</i>	The number of steps to make according to merges.
<i>membership:</i>	Initially the starting membership vector, on output the resulting membership vector, after performing steps merges.
<i>csize:</i>	Optionally the sizes of the communities is stored here, if this is not a null pointer, but an initialized vector.

Returns:

Error code.

Time complexity: $O(|V|)$, the number of vertices.

Walktrap: Community structure based on random walks

`igraph_community_walktrap` — This function is the implementation of the Walktrap community

```
igraph_error_t igraph_community_walktrap(const igraph_t *graph,
                                         const igraph_vector_t *weights,
                                         igraph_integer_t steps,
                                         igraph_matrix_int_t *merges,
                                         igraph_vector_t *modularity,
                                         igraph_vector_int_t *membership);
```

finding algorithm, see Pascal Pons, Matthieu Latapy: Computing communities in large networks using random walks, <https://arxiv.org/abs/physics/0512106>

Currently the original C++ implementation is used in igraph, see <https://www-complexnetworks.lip6.fr/~latapy/PP/walktrap.html> We are grateful to Matthieu Latapy and Pascal Pons for providing this source code.

In contrast to the original implementation, isolated vertices are allowed in the graph and they are assumed to have a single incident loop edge with weight 1.

Arguments:

- graph*: The input graph, edge directions are ignored.
- weights*: Numeric vector giving the weights of the edges. If it is a NULL pointer then all edges will have equal weights. The weights are expected to be positive.
- steps*: Integer constant, the length of the random walks. Typically, good results are obtained with values between 3-8 with 4-5 being a reasonable default.
- merges*: Pointer to a matrix, the merges performed by the algorithm will be stored here (if not NULL). Each merge is a row in a two-column matrix and contains the IDs of the merged clusters. Clusters are numbered from zero and cluster numbers smaller than the number of nodes in the network belong to the individual vertices as singleton clusters. In each step a new cluster is created from two other clusters and its id will be one larger than the largest cluster id so far. This means that before the first merge we have n clusters (the number of vertices in the graph) numbered from zero to $n-1$. The first merge creates cluster n , the second cluster $n+1$, etc.
- modularity*: Pointer to a vector. If not NULL then the modularity score of the current clustering is stored here after each merge operation.
- membership*: Pointer to a vector. If not a NULL pointer, then the membership vector corresponding to the maximal modularity score is stored here. If it is not a NULL pointer, then neither *modularity* nor *merges* may be NULL.

Returns:

Error code.

See also:

```
igraph_community_spinglass(), igraph_community_edge_betweenness().
```

Time complexity: $O(|E||V|^2)$ in the worst case, $O(|V|^2 \log |V|)$ typically, $|V|$ is the number of vertices, $|E|$ is the number of edges.

Example 24.3. File `examples/simple/walktrap.c`

Edge betweenness based community detection

`igraph_community_edge_betweenness` — Community finding based on edge betweenness.

```
igraph_error_t igraph_community_edge_betweenness(const igraph_t *graph,
                                                igraph_vector_int_t *result,
                                                igraph_vector_t *edge_betweenness,
                                                igraph_matrix_int_t *merges,
                                                igraph_vector_int_t *bridges,
                                                igraph_vector_t *modularity,
                                                igraph_vector_int_t *membership,
                                                igraph_bool_t directed,
                                                const igraph_vector_t *weights);
```

Community structure detection based on the betweenness of the edges in the network. The algorithm was invented by M. Girvan and M. Newman, see: M. Girvan and M. E. J. Newman: Community structure in social and biological networks, Proc. Nat. Acad. Sci. USA 99, 7821-7826 (2002).

The idea is that the betweenness of the edges connecting two communities is typically high, as many of the shortest paths between nodes in separate communities go through them. So we gradually remove the edge with highest betweenness from the network, and recalculate edge betweenness after every removal. This way sooner or later the network falls off to two components, then after a while one of these components falls off to two smaller components, etc. until all edges are removed. This is a divisive hierarchical approach, the result is a dendrogram.

Arguments:

<i>graph</i> :	The input graph.
<i>result</i> :	Pointer to an initialized vector, the result will be stored here, the IDs of the removed edges in the order of their removal. It will be resized as needed. It may be NULL if the edge IDs are not needed by the caller.
<i>edge_betweenness</i> :	Pointer to an initialized vector or NULL. In the former case the edge betweenness of the removed edge is stored here. The vector will be resized as needed.
<i>merges</i> :	Pointer to an initialized matrix or NULL. If not NULL then merges performed by the algorithm are stored here. Even if this is a divisive algorithm, we can replay it backwards and note which two clusters were merged. Clusters are numbered from zero, see the <i>merges</i> argument of <code>igraph_community_walktrap()</code> for details. The matrix will be resized as needed.

<i>bridges</i> :	Pointer to an initialized vector of NULL. If not NULL then the indices into <i>result</i> of all edges which caused one of the <i>merges</i> will be put here. This is equal to all edge removals which separated the network into more components, in reverse order.
<i>modularity</i> :	If not a null pointer, then the modularity values of the different divisions are stored here, in the order corresponding to the merge matrix. The modularity values will take weights into account if <i>weights</i> is not null.
<i>membership</i> :	If not a null pointer, then the membership vector, corresponding to the highest modularity value, is stored here.
<i>directed</i> :	Logical constant, whether to calculate directed betweenness (i.e. directed paths) for directed graphs. It is ignored for undirected graphs.
<i>weights</i> :	An optional vector containing edge weights. If null, the unweighted edge betweenness scores will be calculated and used. If not null, the weighted edge betweenness scores will be calculated and used.

Returns:

Error code.

See also:

`igraph_community_eb_get_merges()`, `igraph_community_spinglass()`,
`igraph_community_walktrap()`.

Time complexity: $O(|V||E|^2)$, as the betweenness calculation requires $O(|V||E|)$ and we do it $|E|-1$ times.

Example **24.4.** **File** **examples/simple/**
igraph_community_edge_betweenness.c

igraph_community_eb_get_merges — Calculating the merges, i.e. the dendrogram for an edge betweenness community structure.

```
igraph_error_t igraph_community_eb_get_merges(const igraph_t *graph,
                                              const igraph_bool_t directed,
                                              const igraph_vector_int_t *edges,
                                              const igraph_vector_t *weights,
                                              igraph_matrix_int_t *res,
                                              igraph_vector_int_t *bridges,
                                              igraph_vector_t *modularity,
                                              igraph_vector_int_t *membership);
```

This function is handy if you have a sequence of edges which are gradually removed from the network and you would like to know how the network falls apart into separate components. The edge sequence may come from the `igraph_community_edge_betweenness()` function, but this is not necessary. Note that `igraph_community_edge_betweenness()` can also calculate the dendrogram, via its *merges* argument. Merges happen when the edge removal process is run backwards and two components become connected.

Arguments:

<i>graph</i> :	The input graph.
<i>edges</i> :	Vector containing the edges to be removed from the network, all edges are expected to appear exactly once in the vector.
<i>directed</i> :	Whether to use the directed or undirected version of modularity. Will be ignored for undirected graphs.
<i>weights</i> :	An optional vector containing edge weights. If null, the unweighted modularity scores will be calculated. If not null, the weighted modularity scores will be calculated. Ignored if both <i>modularity</i> and <i>membership</i> are NULL pointers.
<i>res</i> :	Pointer to an initialized matrix, if not NULL then the dendrogram will be stored here, in the same form as for the <code>igraph_community_walktrap()</code> function: the matrix has two columns and each line is a merge given by the IDs of the merged components. The component IDs are numbered from zero and component IDs smaller than the number of vertices in the graph belong to individual vertices. The non-trivial components containing at least two vertices are numbered from n , where n is the number of vertices in the graph. So if the first line contains a and b that means that components a and b are merged into component n , the second line creates component $n+1$, etc. The matrix will be resized as needed.
<i>bridges</i> :	Pointer to an initialized vector of NULL. If not NULL then the indices into <i>edges</i> of all edges which caused one of the merges will be put here. This is equal to all edge removals which separated the network into more components, in reverse order.
<i>modularity</i> :	If not a null pointer, then the modularity values for the different divisions, corresponding to the merges matrix, will be stored here.
<i>membership</i> :	If not a null pointer, then the membership vector for the best division (in terms of modularity) will be stored here.

Returns:

Error code.

See also:

`igraph_community_edge_betweenness()`.

Time complexity: $O(|E|+|V|\log|V|)$, $|V|$ is the number of vertices, $|E|$ is the number of edges.

Community structure based on the optimization of modularity

`igraph_community_fastgreedy` — Finding community structure by greedy optimization of modularity.

```
igraph_error_t igraph_community_fastgreedy(const igraph_t *graph,
                                           const igraph_vector_t *weights,
                                           igraph_matrix_int_t *merges,
```

```
igraph_vector_t *modularity,
igraph_vector_int_t *membership);
```

This function implements the fast greedy modularity optimization algorithm for finding community structure, see A Clauset, MEJ Newman, C Moore: Finding community structure in very large networks, <http://www.arxiv.org/abs/cond-mat/0408187> for the details.

Some improvements proposed in K Wakita, T Tsurumi: Finding community structure in mega-scale social networks, <http://www.arxiv.org/abs/cs.CY/0702048v1> have also been implemented.

Arguments:

- graph*: The input graph. It must be a graph without multiple edges. This is checked and an error message is given for graphs with multiple edges.
- weights*: Potentially a numeric vector containing edge weights. Supply a null pointer here for unweighted graphs. The weights are expected to be non-negative.
- merges*: Pointer to an initialized matrix or NULL, the result of the computation is stored here. The matrix has two columns and each merge corresponds to one merge, the IDs of the two merged components are stored. The component IDs are numbered from zero and the first n components are the individual vertices, n is the number of vertices in the graph. Component n is created in the first merge, component $n + 1$ in the second merge, etc. The matrix will be resized as needed. If this argument is NULL then it is ignored completely.
- modularity*: Pointer to an initialized vector or NULL pointer, in the former case the modularity scores along the stages of the computation are recorded here. The vector will be resized as needed.
- membership*: Pointer to a vector. If not a null pointer, then the membership vector corresponding to the best split (in terms of modularity) is stored here.

Returns:

Error code.

See also:

`igraph_community_walktrap()`, `igraph_community_edge_betweenness()` for other community detection algorithms, `igraph_community_to_membership()` to convert the dendrogram to a membership vector.

Time complexity: $O(|E||V|\log|V|)$ in the worst case, $O(|E|+|V|\log^2|V|)$ typically, $|V|$ is the number of vertices, $|E|$ is the number of edges.

Example	24.5.	File	examples/simple/
igraph_community_fastgreedy.c			

igraph_community_multilevel — Finding community structure by multi-level optimization of modularity.

```
igraph_error_t igraph_community_multilevel(const igraph_t *graph,
const igraph_vector_t *weights,
```

```
const igraph_real_t resolution,
igraph_vector_int_t *membership,
igraph_matrix_int_t *memberships, igraph_vector_t
```

This function implements the multi-level modularity optimization algorithm for finding community structure, see Blondel, V. D., Guillaume, J.-L., Lambiotte, R., & Lefebvre, E. (2008). Fast unfolding of communities in large networks. *Journal of Statistical Mechanics: Theory and Experiment*, 10008(10), 6. <https://doi.org/10.1088/1742-5468/2008/10/P10008> for the details (preprint: <http://arxiv.org/abs/0803.0476>). The algorithm is sometimes known as the "Louvain" algorithm.

The algorithm is based on the modularity measure and a hierarchical approach. Initially, each vertex is assigned to a community on its own. In every step, vertices are re-assigned to communities in a local, greedy way: in a random order, each vertex is moved to the community with which it achieves the highest contribution to modularity. When no vertices can be reassigned, each community is considered a vertex on its own, and the process starts again with the merged communities. The process stops when there is only a single vertex left or when the modularity cannot be increased any more in a step.

The resolution parameter `gamma` allows finding communities at different resolutions. Higher values of the resolution parameter typically result in more, smaller communities. Lower values typically result in fewer, larger communities. The original definition of modularity is retrieved when setting `gamma=1`. Note that the returned modularity value is calculated using the indicated resolution parameter. See `igraph_modularity()` for more details. This function was contributed by Tom Gregorovic.

Arguments:

<i>graph</i> :	The input graph. It must be an undirected graph.
<i>weights</i> :	Numeric vector containing edge weights. If <code>NULL</code> , every edge has equal weight. The weights are expected to be non-negative.
<i>resolution</i> :	Resolution parameter. Must be greater than or equal to 0. Lower values favor fewer, larger communities; higher values favor more, smaller communities. Set it to 1 to use the classical definition of modularity.
<i>membership</i> :	The membership vector, the result is returned here. For each vertex it gives the ID of its community. The vector must be initialized and it will be resized accordingly.
<i>memberships</i> :	Numeric matrix that will contain the membership vector after each level, if not <code>NULL</code> . It must be initialized and it will be resized accordingly.
<i>modularity</i> :	Numeric vector that will contain the modularity score after each level, if not <code>NULL</code> . It must be initialized and it will be resized accordingly.

Returns:

Error code.

Time complexity: in average near linear on sparse graphs.

Example	24.6.	File	examples/simple/
<code>igraph_community_multilevel.c</code>			

`igraph_community_leiden` — Finding community structure using the Leiden algorithm.

```
igraph_error_t igraph_community_leiden(const igraph_t *graph,
                                       const igraph_vector_t *edge_weights, const igraph_vector_t *node_weights,
                                       const igraph_real_t resolution_parameter, const igraph_vector_int_t *membership, igraph_integer_t *membership_out)
```

This function implements the Leiden algorithm for finding community structure, see Traag, V. A., Waltman, L., & van Eck, N. J. (2019). From Louvain to Leiden: guaranteeing well-connected communities. *Scientific reports*, 9(1), 5233. <http://dx.doi.org/10.1038/s41598-019-41695-z>

It is similar to the multilevel algorithm, often called the Louvain algorithm, but it is faster and yields higher quality solutions. It can optimize both modularity and the Constant Potts Model, which does not suffer from the resolution-limit (see preprint <http://arxiv.org/abs/1104.3083>).

The Leiden algorithm consists of three phases: (1) local moving of nodes, (2) refinement of the partition and (3) aggregation of the network based on the refined partition, using the non-refined partition to create an initial partition for the aggregate network. In the local move procedure in the Leiden algorithm, only nodes whose neighborhood has changed are visited. The refinement is done by restarting from a singleton partition within each cluster and gradually merging the subclusters. When aggregating, a single cluster may then be represented by several nodes (which are the subclusters identified in the refinement).

The Leiden algorithm provides several guarantees. The Leiden algorithm is typically iterated: the output of one iteration is used as the input for the next iteration. At each iteration all clusters are guaranteed to be connected and well-separated. After an iteration in which nothing has changed, all nodes and some parts are guaranteed to be locally optimally assigned. Finally, asymptotically, all subsets of all clusters are guaranteed to be locally optimally assigned. For more details, please see Traag, Waltman & van Eck (2019).

The objective function being optimized is

$$1 / 2m \sum_{ij} (A_{ij} - \gamma n_i n_j) d(s_i, s_j)$$

where m is the total edge weight, A_{ij} is the weight of edge (i, j) , γ is the so-called resolution parameter, n_i is the node weight of node i , s_i is the cluster of node i and $d(x, y) = 1$ if and only if $x = y$ and 0 otherwise. By setting $n_i = k_i$, the degree of node i , and dividing γ by $2m$, you effectively obtain an expression for modularity. Hence, the standard modularity will be optimized when you supply the degrees as `node_weights` and by supplying as a resolution parameter $1.0 / (2 * m)$, with m the number of edges.

Arguments:

<i>graph</i> :	The input graph. It must be an undirected graph.
<i>edge_weights</i> :	Numeric vector containing edge weights. If NULL, every edge has equal weight of 1. The weights need not be non-negative.
<i>node_weights</i> :	Numeric vector containing node weights. If NULL, every node has equal weight of 1.
<i>resolution_parameter</i> :	The resolution parameter used, which is represented by γ in the objective function mentioned in the documentation.
<i>beta</i> :	The randomness used in the refinement step when merging. A small amount of randomness ($\beta = 0.01$) typically works well.
<i>start</i> :	Start from membership vector. If this is true, the optimization will start from the provided membership vector. If this is false, the optimization will start from a singleton partition.
<i>membership</i> :	The membership vector. This is both used as the initial membership from which optimisation starts and is updated in place. It must hence

be properly initialized. When finding clusters from scratch it is typically started using a singleton clustering. This can be achieved using `igraph_vector_int_init_range`.

nb_clusters: The number of clusters contained in membership. If NULL, the number of clusters will not be returned.

quality: The quality of the partition, in terms of the objective function as included in the documentation. If NULL the quality will not be calculated.

Returns:

Error code.

Time complexity: near linear on sparse graphs.

Example 24.7. File `examples/simple/igraph_community_leiden.c`

Fluid communities

`igraph_community_fluid_communities` — Community detection based on fluids interacting on the graph.

```
igraph_error_t igraph_community_fluid_communities(const igraph_t *graph,
                                                  igraph_integer_t no_of_communities,
                                                  igraph_vector_int_t *membership);
```

The algorithm is based on the simple idea of several fluids interacting in a non-homogeneous environment (the graph topology), expanding and contracting based on their interaction and density. This function implements the community detection method described in: Parés F, Gasulla DG, et. al. (2018) Fluid Communities: A Competitive, Scalable and Diverse Community Detection Algorithm. In: Complex Networks & Their Applications VI: Proceedings of Complex Networks 2017 (The Sixth International Conference on Complex Networks and Their Applications), Springer, vol 689, p 229.

Arguments:

graph: The input graph. The graph must be simple and connected. Empty graphs are not supported as well as single vertex graphs. Edge directions are ignored. Weights are not considered.

no_of_communities: The number of communities to be found. Must be greater than 0 and fewer than number of vertices in the graph.

membership: The result vector mapping vertices to the communities they are assigned to.

modularity: If not a null pointer, then it must be a pointer to a real number. The modularity score of the detected community structure is stored here.

Returns:

Error code.

Time complexity: $O(|E|)$

Label propagation

`igraph_community_label_propagation` — Community detection based on label propagation.

```
igraph_error_t igraph_community_label_propagation(const igraph_t *graph,
                                                  igraph_vector_int_t *membership,
                                                  igraph_neimode_t mode,
                                                  const igraph_vector_t *weights,
                                                  const igraph_vector_int_t *initial,
                                                  const igraph_vector_bool_t *fixed);
```

This function implements the label propagation-based community detection algorithm described by Raghavan, Albert and Kumara. This version extends the original method by the ability to take edge weights into consideration and also by allowing some labels to be fixed.

Weights are taken into account as follows: when the new label of node i is determined, the algorithm iterates over all edges incident on node i and calculate the total weight of edges leading to other nodes with label $0, 1, 2, \dots, k - 1$ (where k is the number of possible labels). The new label of node i will then be the label whose edges (among the ones incident on node i) have the highest total weight.

For directed graphs, it is important to know that labels can circulate freely only within the strongly connected components of the graph and may propagate in only one direction (or not at all) *between* strongly connected components. You should treat directed edges as directed only if you are aware of the consequences.

References:

Raghavan, U.N. and Albert, R. and Kumara, S.: Near linear time algorithm to detect community structures in large-scale networks. Phys Rev E 76, 036106 (2007). <https://doi.org/10.1103/PhysRevE.76.036106>

Šubelj, L.: Label propagation for clustering. Chapter in "Advances in Network Clustering and Block-modeling" edited by P. Doreian, V. Batagelj & A. Ferligoj (Wiley, New York, 2018). <https://doi.org/10.1002/9781119483298.ch5> <https://arxiv.org/abs/1709.05634>

Arguments:

- | | |
|---------------------|--|
| <i>graph</i> : | The input graph. Note that the algorithm was originally defined for undirected graphs. You are advised to set <i>mode</i> to <code>IGRAPH_ALL</code> if you pass a directed graph here to treat it as undirected. |
| <i>membership</i> : | The membership vector, the result is returned here. For each vertex it gives the ID of its community (label). |
| <i>mode</i> : | Whether to consider edge directions for the label propagation, and if so, which direction the labels should propagate. Ignored for undirected graphs. <code>IGRAPH_ALL</code> means to ignore edge directions (even in directed graphs). <code>IGRAPH_OUT</code> means to propagate labels along the natural direction of the edges. <code>IGRAPH_IN</code> means to propagate labels <i>backwards</i> (i.e. from head to tail). It is advised to set this to <code>IGRAPH_ALL</code> unless you are specifically interested in the effect of edge directions. |
| <i>weights</i> : | The weight vector, it should contain a positive weight for all the edges. |

initial: The initial state. If NULL, every vertex will have a different label at the beginning. Otherwise it must be a vector with an entry for each vertex. Non-negative values denote different labels, negative entries denote vertices without labels. Unlabeled vertices which are not reachable from any labeled ones will remain unlabeled at the end of the label propagation process, and will be labeled in an additional step to avoid returning negative values in *membership*. In undirected graphs, this happens when entire connected components are unlabeled. Then, each unlabeled component will receive its own separate label. In directed graphs, the outcome of the additional labeling should be considered undefined and may change in the future; please do not rely on it.

fixed: Boolean vector denoting which labels are fixed. Of course this makes sense only if you provided an initial state, otherwise this element will be ignored. Note that vertices without labels cannot be fixed. The fixed status will be ignored for these with a warning. Also note that label numbers by themselves have no meaning, and igraph may renumber labels. However, co-membership constraints will be respected: two vertices can be fixed to be in the same or in different communities.

modularity: If not a null pointer, then it must be a pointer to a real number. The modularity score of the detected community structure is stored here. Note that igraph will calculate the *directed* modularity if the input graph is directed, even if you set *mode* to IGRAPH_ALL

Returns:

Error code.

Time complexity: $O(m+n)$

Example	24.8.	File	examples/simple/
igraph_community_label_propagation.c			

The InfoMAP algorithm

igraph_community_infomap — Find community structure that minimizes the expected description length of a random walker trajectory.

```
igraph_error_t igraph_community_infomap(const igraph_t * graph,
                                       const igraph_vector_t *e_weights,
                                       const igraph_vector_t *v_weights,
                                       igraph_integer_t nb_trials,
                                       igraph_vector_int_t *membership,
                                       igraph_real_t *codelength);
```

Implementation of the InfoMap community detection algorithm of Martin Rosvall and Carl T. Bergstrom.

For more details, see the visualization of the math and the map generator at <https://www.mapequation.org>. The original paper describing the algorithm is: M. Rosvall and C. T. Bergstrom, Maps of information flow reveal community structure in complex networks, PNAS 105, 1118 (2008) (<http://dx.doi.org/10.1073/pnas.0706851105>, <http://arxiv.org/abs/0707.0609>). A more detailed paper

about the algorithm is: M. Rosvall, D. Axelsson, and C. T. Bergstrom, The map equation, Eur. Phys. J. Special Topics 178, 13 (2009). (<http://dx.doi.org/10.1140/epjst/e2010-01179-1>, <http://arxiv.org/abs/0906.1405>)

The original C++ implementation of Martin Rosvall is used, see http://www.tp.umu.se/~rosvall/downloads/infomap_undir.tgz . Intergation in igraph was done by Emmanuel Navarro (who is grateful to Martin Rosvall and Carl T. Bergstrom for providing this source code.)

Note that the graph must not contain isolated vertices.

If you want to specify a random seed (as in the original implementation) you can use `igraph_rng_seed()`.

Arguments:

- graph*: The input graph.
- e_weights*: Numeric vector giving the weights of the edges. If it is a NULL pointer then all edges will have equal weights. The weights are expected to be positive.
- v_weights*: Numeric vector giving the weights of the vertices. If it is a NULL pointer then all vertices will have equal weights. The weights are expected to be positive.
- nb_trials*: The number of attempts to partition the network (can be any integer value equal or larger than 1).
- membership*: Pointer to a vector. The membership vector is stored here.
- code_length*: Pointer to a real. If not NULL the code length of the partition is stored here.

Returns:

Error code.

See also:

`igraph_community_spinglass()`, `igraph_community_edge_betweenness()`,
`igraph_community_walktrap()`.

Time complexity: TODO.

Chapter 25. Graphlets

Introduction

Graphlet decomposition models a weighted undirected graph via the union of potentially overlapping dense social groups. This is done by a two-step algorithm. In the first step, a candidate set of groups (a candidate basis) is created by finding cliques in the thresholded input graph. In the second step, the graph is projected onto the candidate basis, resulting in a weight coefficient for each clique in the candidate basis.

For more information on graphlet decomposition, see Hossein Azari Soufiani and Edoardo M Airolidi: "Graphlet decomposition of a weighted network", <https://arxiv.org/abs/1203.2821> and <http://proceedings.mlr.press/v22/azari12/azari12.pdf>

`igraph` contains three functions for performing the graphlet decomposition of a graph. The first is `igraph_graphlets()`, which performs both steps of the method and returns a list of subgraphs with their corresponding weights. The other two functions correspond to the first and second steps of the algorithm, and they are useful if the user wishes to perform them individually: `igraph_graphlets_candidate_basis()` and `igraph_graphlets_project()`.

Note: The term "graphlet" is used for several unrelated concepts in the literature. If you are looking to count induced subgraphs, see `igraph_motifs_randesu()` and `igraph_subisomorphic_lad()`.

Performing graphlet decomposition

`igraph_graphlets` — Calculate graphlets basis and project the graph on it

```
igraph_error_t igraph_graphlets(const igraph_t *graph,
                                const igraph_vector_t *weights,
                                igraph_vector_int_list_t *cliques,
                                igraph_vector_t *Mu, igraph_integer_t niter);
```

This function simply calls `igraph_graphlets_candidate_basis()` and `igraph_graphlets_project()`, and then orders the graphlets according to decreasing weights.

Arguments:

- graph*: The input graph, it must be a simple graph, edge directions are ignored.
- weights*: Weights of the edges, a vector.
- cliques*: An initialized list of integer vectors. The graphlet basis is stored here. Each element of the list is an integer vector of vertex IDs, encoding a single basis subgraph.
- Mu*: An initialized vector, the weights of the graphlets will be stored here.
- niter*: Integer scalar, the number of iterations to perform for the projection step.

Returns:

Error code.

See also: `igraph_graphlets_candidate_basis()` and `igraph_graphlets_project()`.

`igraph_graphlets_candidate_basis` — Calculate a candidate graphlets basis

```
igraph_error_t igraph_graphlets_candidate_basis(const igraph_t *graph,
                                                const igraph_vector_t *weights,
                                                igraph_vector_int_list_t *cliques,
                                                igraph_vector_t *thresholds);
```

Arguments:

graph: The input graph, it must be a simple graph, edge directions are ignored.

weights: Weights of the edges, a vector.

cliques: An initialized list of integer vectors. The graphlet basis is stored here. Each element of the list is an integer vector of vertex IDs, encoding a single basis subgraph.

thresholds: An initialized vector, the (highest possible) weight thresholds for finding the basis subgraphs are stored here.

Returns:

Error code.

See also: `igraph_graphlets()` and `igraph_graphlets_project()`.

`igraph_graphlets_project` — Project a graph on a graphlets basis

```
igraph_error_t igraph_graphlets_project(const igraph_t *graph,
                                        const igraph_vector_t *weights,
                                        const igraph_vector_int_list_t *cliques,
                                        igraph_vector_t *Mu, igraph_bool_t startMu,
                                        igraph_integer_t niter);
```

Note that the graph projected does not have to be the same that was used to calculate the graphlet basis, but it is assumed that it has the same number of vertices, and the vertex IDs of the two graphs match.

Arguments:

graph: The input graph, it must be a simple graph, edge directions are ignored.

weights: Weights of the edges in the input graph, a vector.

cliques: An initialized list of integer vectors. The graphlet basis is stored here. Each element of the list is an integer vector of vertex IDs, encoding a single basis subgraph.

Mu: An initialized vector, the weights of the graphlets will be stored here. This vector is also used to initialize the the weight vector for the iterative algorithm, if the `startMu` argument is true (non-zero).

startMu: If true (non-zero), then the supplied Mu vector is used as the starting point of the iteration. Otherwise a constant 1 vector is used.

niter: Integer scalar, the number of iterations to perform.

Returns:

Error code.

See also: `igraph_graphlets()` and `igraph_graphlets_candidate_basis()`.

Chapter 26. Hierarchical random graphs

Introduction

A hierarchical random graph is an ensemble of undirected graphs with n vertices. It is defined via a binary tree with n leaf and $n-1$ internal vertices, where the internal vertices are labeled with probabilities. The probability that two vertices are connected in the random graph is given by the probability label at their closest common ancestor.

Please read the following two articles for more about hierarchical random graphs: A. Clauset, C. Moore, and M.E.J. Newman. Hierarchical structure and the prediction of missing links in networks. *Nature* 453, 98 - 101 (2008); and A. Clauset, C. Moore, and M.E.J. Newman. Structural Inference of Hierarchies in Networks. In E. M. Airolti et al. (Eds.): *ICML 2006 Ws, Lecture Notes in Computer Science* 4503, 1-13. Springer-Verlag, Berlin Heidelberg (2007).

igraph contains functions for fitting HRG models to a given network (`igraph_hrg_fit`), for generating networks from a given HRG ensemble (`igraph_hrg_game`, `igraph_hrg_sample`), converting an igraph graph to a HRG and back (`igraph_hrg_create`, `igraph_hrg_dendrogram`), for calculating a consensus tree from a set of sampled HRGs (`igraph_hrg_consensus`) and for predicting missing edges in a network based on its HRG models (`igraph_hrg_predict`).

The igraph HRG implementation is heavily based on the code published by Aaron Clauset, at his website, <http://tuvalu.santafe.edu/~aaronc/hierarchy/>

Representing HRGs

`igraph_hrg_t` — Data structure to store a hierarchical random graph

```
typedef struct igraph_hrg_t {
    igraph_vector_int_t left;
    igraph_vector_int_t right;
    igraph_vector_t prob;
    igraph_vector_int_t vertices;
    igraph_vector_int_t edges;
} igraph_hrg_t;
```

A hierarchical random graph (HRG) can be given as a binary tree, where the internal vertices are labeled with real numbers.

Note that you don't necessarily have to know this internal representation for using the HRG functions, just pass the HRG objects created by one igraph function, to another igraph function.

It has the following members:

Values:

`left`: Vector that contains the left children of the internal tree vertices. The first vertex is always the root vertex, so the first element of the vector is the left child of the root vertex. Internal vertices are denoted with negative numbers, starting from -1 and going

down, i.e. the root vertex is -1. Leaf vertices are denoted by non-negative number, starting from zero and up.

right: Vector that contains the right children of the vertices, with the same encoding as the left vector.

prob: The connection probabilities attached to the internal vertices, the first number belongs to the root vertex (i.e. internal vertex -1), the second to internal vertex -2, etc.

edges: The number of edges in the subtree below the given internal vertex.

vertices: The number of vertices in the subtree below the given internal vertex, including itself.

igraph_hrg_init — Allocate memory for a HRG.

```
igraph_error_t igraph_hrg_init(igraph_hrg_t *hrg, igraph_integer_t n);
```

This function must be called before passing an `igraph_hrg_t` to an `igraph` function.

Arguments:

hrg: Pointer to the HRG data structure to initialize.

n: The number of vertices in the graph that is modeled by this HRG. It can be zero, if this is not yet known.

Returns:

Error code.

Time complexity: $O(n)$, the number of vertices in the graph.

igraph_hrg_destroy — Deallocate memory for an HRG.

```
void igraph_hrg_destroy(igraph_hrg_t *hrg);
```

The HRG data structure can be reinitialized again with an `igraph_hrg_destroy` call.

Arguments:

hrg: Pointer to the HRG data structure to deallocate.

Time complexity: operating system dependent.

igraph_hrg_size — Returns the size of the HRG, the number of leaf nodes.

```
igraph_integer_t igraph_hrg_size(const igraph_hrg_t *hrg);
```

Arguments:

hrg: Pointer to the HRG.

Returns:

The number of leaf nodes in the HRG.

Time complexity: $O(1)$.

igraph_hrg_resize — Resize a HRG.

```
igraph_error_t igraph_hrg_resize(igraph_hrg_t *hrg, igraph_integer_t newsize);
```

Arguments:

hrg: Pointer to an initialized (see `igraph_hrg_init`) HRG.

newsize: The new size, i.e. the number of leaf nodes.

Returns:

Error code.

Time complexity: $O(n)$, n is the new size.

Fitting HRGs

igraph_hrg_fit — Fit a hierarchical random graph model to a network.

```
igraph_error_t igraph_hrg_fit(const igraph_t *graph,
                              igraph_hrg_t *hrg,
                              igraph_bool_t start,
                              igraph_integer_t steps);
```

Arguments:

graph: The igraph graph to fit the model to. Edge directions are ignored in directed graphs.

hrg: Pointer to an initialized HRG, the result of the fitting is stored here. It can also be used to pass a HRG to the function, that can be used as the starting point of the Markov Chain Monte Carlo fitting, if the *start* argument is true.

start: Logical, whether to start the fitting from the given HRG model.

steps: Integer, the number of MCMC steps to take in the fitting procedure. If this is zero, then the fitting stop is a convergence criteria is fulfilled.

Returns:

Error code.

Time complexity: TODO.

igraph_hrg_consensus — Calculate a consensus tree for a HRG.

```
igraph_error_t igraph_hrg_consensus(const igraph_t *graph,
                                     igraph_vector_int_t *parents,
                                     igraph_vector_t *weights,
                                     igraph_hrg_t *hrg,
                                     igraph_bool_t start,
                                     igraph_integer_t num_samples);
```

The calculation can be started from the given HRG (*hrg*), or (if *start* is false), a HRG is first fitted to the given graph.

Arguments:

- graph*: The input graph.
- parents*: An initialized vector, the results are stored here. For each vertex, the id of its parent vertex is stored, or -1, if the vertex is the root vertex in the tree. The first *n* vertex IDs (from 0) refer to the original vertices of the graph, the other IDs refer to vertex groups.
- weights*: Numeric vector, counts the number of times a given tree split occurred in the generated network samples, for each internal vertices. The order is the same as in *parents*.
- hrg*: A hierarchical random graph. It is used as a starting point for the sampling, if the *start* argument is true. It is modified along the MCMC.
- start*: Logical, whether to use the supplied HRG (in *hrg*) as a starting point for the MCMC.
- num_samples*: The number of samples to generate for creating the consensus tree.

Returns:

Error code.

Time complexity: TODO.

HRG sampling

igraph_hrg_sample — Sample from a hierarchical random graph model.

```
igraph_error_t igraph_hrg_sample(const igraph_hrg_t *hrg, igraph_t *sample);
```

This function draws a single sample from a hierarchical random graph model.

Arguments:

hrg: A HRG model to sample from
sample: Pointer to an uninitialized graph; the sample is stored here.

Returns:

Error code.
Time complexity: TODO.

igraph_hrg_game — Generate a hierarchical random graph.

```
igraph_error_t igraph_hrg_game(igraph_t *graph,  
                               const igraph_hrg_t *hrg);
```

This function is a simple shortcut to `igraph_hrg_sample`. It creates a single graph from the given HRG.

Arguments:

graph: Pointer to an uninitialized graph, the new graph is created here.
hrg: The hierarchical random graph model to sample from.

Returns:

Error code.
Time complexity: TODO.

Conversion to and from igraph graphs

igraph_hrg_dendrogram — Create a dendrogram from a hierarchical random graph.

```
igraph_error_t igraph_hrg_dendrogram(  
    igraph_t *graph, const igraph_hrg_t *hrg  
);
```

Creates the igraph graph equivalent of an `igraph_hrg_t` data structure.

Arguments:

graph: Pointer to an uninitialized graph, the result is stored here.
hrg: The hierarchical random graph to convert.

Returns:

Error code.

Time complexity: $O(n)$, the number of vertices in the graph.

igraph_hrg_create — Create a HRG from an igraph graph.

```
igraph_error_t igraph_hrg_create(igraph_hrg_t *hrg,  
                                const igraph_t *graph,  
                                const igraph_vector_t *prob);
```

Arguments:

- hrg*: Pointer to an initialized `igraph_hrg_t`. The result is stored here.
- graph*: The igraph graph to convert. It must be a directed binary tree, with $n-1$ internal and n leaf vertices. The root vertex must have in-degree zero.
- prob*: The vector of probabilities, this is used to label the internal nodes of the hierarchical random graph. The values corresponding to the leaves are ignored.

Returns:

Error code.

Time complexity: $O(n)$, the number of vertices in the tree.

Predicting missing edges

igraph_hrg_predict — Predict missing edges in a graph, based on HRG models.

```
igraph_error_t igraph_hrg_predict(const igraph_t *graph,  
                                igraph_vector_int_t *edges,  
                                igraph_vector_t *prob,  
                                igraph_hrg_t *hrg,  
                                igraph_bool_t start,  
                                igraph_integer_t num_samples,  
                                igraph_integer_t num_bins);
```

Samples HRG models for a network, and estimated the probability that an edge was falsely observed as non-existent in the network.

Arguments:

- graph*: The input graph.
- edges*: The list of missing edges is stored here, the first two elements are the first edge, the next two the second edge, etc.
- prob*: Vector of probabilities for the existence of missing edges, in the order corresponding to edges.

hrg: A HRG, it is used as a starting point if `start` is true. It is also modified during the MCMC sampling.

start: Logical, whether to start the MCMC from the given HRG.

num_samples: The number of samples to generate.

num_bins: Controls the resolution of the edge probabilities. Higher numbers result higher resolution.

Returns:

Error code.

Time complexity: TODO.

Chapter 27. Embedding of graphs

Spectral embedding

`igraph_adjacency_spectral_embedding` — Adjacency spectral embedding

```
igraph_error_t igraph_adjacency_spectral_embedding(const igraph_t *graph,
                                                    igraph_integer_t n,
                                                    const igraph_vector_t *weights,
                                                    igraph_eigen_which_position_t which,
                                                    igraph_bool_t scaled,
                                                    igraph_matrix_t *X,
                                                    igraph_matrix_t *Y,
                                                    igraph_vector_t *D,
                                                    const igraph_vector_t *cvec,
                                                    igraph_arnpack_options_t *options);
```

Spectral decomposition of the adjacency matrices of graphs. This function computes an n -dimensional Euclidean representation of the graph based on its adjacency matrix, A . This representation is computed via the singular value decomposition of the adjacency matrix, $A=U D V^T$. In the case, where the graph is a random dot product graph generated using latent position vectors in R^n for each vertex, the embedding will provide an estimate of these latent vectors.

For undirected graphs, the latent positions are calculated as $X = U^n D^{(1/2)}$ where U^n equals to the first n columns of U , and $D^{(1/2)}$ is a diagonal matrix containing the square root of the selected singular values on the diagonal.

For directed graphs, the embedding is defined as the pair $X = U^n D^{(1/2)}$, $Y = V^n D^{(1/2)}$. (For undirected graphs $U=V$, so it is sufficient to keep one of them.)

Arguments:

- graph*: The input graph, can be directed or undirected.
- n*: An integer scalar. This value is the embedding dimension of the spectral embedding. Should be smaller than the number of vertices. The largest n -dimensional non-zero singular values are used for the spectral embedding.
- weights*: Optional edge weights. Supply a null pointer for unweighted graphs.
- which*: Which eigenvalues (or singular values, for directed graphs) to use, possible values:
- `IGRAPH_EIGEN_LM` the ones with the largest magnitude
 - `IGRAPH_EIGEN_LA` the (algebraic) largest ones
 - `IGRAPH_EIGEN_SA` the (algebraic) smallest ones.
- For directed graphs, `IGRAPH_EIGEN_LM` and `IGRAPH_EIGEN_LA` are the same because singular values are used for the ordering instead of eigenvalues.
- scaled*: Whether to return X and Y (if *scaled* is true), or U and V .
- X*: Initialized matrix, the estimated latent positions are stored here.

- Y*: Initialized matrix or a null pointer. If not a null pointer, then the second half of the latent positions are stored here. (For undirected graphs, this always equals *X*.)
- D*: Initialized vector or a null pointer. If not a null pointer, then the eigenvalues (for undirected graphs) or the singular values (for directed graphs) are stored here.
- cvec*: A numeric vector, its length is the number vertices in the graph. This vector is added to the diagonal of the adjacency matrix, before performing the SVD.
- options*: Options to ARPACK. See `igraph_arnpack_options_t` for details. Supply `NULL` to use the defaults. Note that the function overwrites the `n` (number of vertices), `nev` and `which` parameters and it always starts the calculation from a random start vector.

Returns:

Error code.

igraph_laplacian_spectral_embedding — Spectral embedding of the Laplacian of a graph

```
igraph_error_t igraph_laplacian_spectral_embedding(const igraph_t *graph,
                                                  igraph_integer_t n,
                                                  const igraph_vector_t *weights,
                                                  igraph_eigen_which_position_t which,
                                                  igraph_laplacian_spectral_embedding_type_t type,
                                                  igraph_bool_t scaled,
                                                  igraph_matrix_t *X,
                                                  igraph_matrix_t *Y,
                                                  igraph_vector_t *D,
                                                  igraph_arnpack_options_t *options);
```

This function essentially does the same as `igraph_adjacency_spectral_embedding`, but works on the Laplacian of the graph, instead of the adjacency matrix.

Arguments:

- graph*: The input graph.
- n*: The number of eigenvectors (or singular vectors if the graph is directed) to use for the embedding.
- weights*: Optional edge weights. Supply a null pointer for unweighted graphs.
- which*: Which eigenvalues (or singular values, for directed graphs) to use, possible values:
- `IGRAPH_EIGEN_LM` the ones with the largest magnitude
 - `IGRAPH_EIGEN_LA` the (algebraic) largest ones
 - `IGRAPH_EIGEN_SA` the (algebraic) smallest ones.
- For directed graphs, `IGRAPH_EIGEN_LM` and `IGRAPH_EIGEN_LA` are the same because singular values are used for the ordering instead of eigenvalues.
- type*: The type of the Laplacian to use. Various definitions exist for the Laplacian of a graph, and one can choose between them with this argument. Possible values:

`IGRAPH_EMBEDDING_D_A` means $D - A$ where D is the degree matrix and A is the adjacency matrix

`IGRAPH_EMBEDDING_DAD` means D_i times A times D_i , where D_i is the inverse of the square root of the degree matrix;

`IGRAPH_EMBEDDING_I_DAD` means $I - D_i A D_i$, where I is the identity matrix.

scaled: Whether to return X and Y (if *scaled* is true), or U and V .

X: Initialized matrix, the estimated latent positions are stored here.

Y: Initialized matrix or a null pointer. If not a null pointer, then the second half of the latent positions are stored here. (For undirected graphs, this always equals X .)

D: Initialized vector or a null pointer. If not a null pointer, then the eigenvalues (for undirected graphs) or the singular values (for directed graphs) are stored here.

options: Options to ARPACK. See `igraph_arnpack_options_t` for details. Supply `NULL` to use the defaults. Note that the function overwrites the `n` (number of vertices), `nev` and `which` parameters and it always starts the calculation from a random start vector.

Returns:

Error code.

See also:

`igraph_adjacency_spectral_embedding` to embed the adjacency matrix.

igraph_dim_select — Dimensionality selection

```
igraph_error_t igraph_dim_select(const igraph_vector_t *sv, igraph_integer_t *d,
```

Dimensionality selection for singular values using profile likelihood.

The input of the function is a numeric vector which contains the measure of "importance" for each dimension.

For spectral embedding, these are the singular values of the adjacency matrix. The singular values are assumed to be generated from a Gaussian mixture distribution with two components that have different means and same variance. The dimensionality d is chosen to maximize the likelihood when the d largest singular values are assigned to one component of the mixture and the rest of the singular values assigned to the other component.

This function can also be used for the general separation problem, where we assume that the left and the right of the vector are coming from two normal distributions, with different means, and we want to know their border.

Arguments:

sv: A numeric vector, the ordered singular values.

dim: The result is stored here.

Returns:

Error code.

Time complexity: $O(n)$, n is the number of values in `sv`.

See also:

`igraph_adjacency_spectral_embedding()`.

Chapter 28. Graph operators

Union and intersection

igraph_disjoint_union — Creates the union of two disjoint graphs

```
igraph_error_t igraph_disjoint_union(igraph_t *res, const igraph_t *left,
                                     const igraph_t *right);
```

First the vertices of the second graph will be relabeled with new vertex IDs to have two disjoint sets of vertex IDs, then the union of the two graphs will be formed. If the two graphs have $|V1|$ and $|V2|$ vertices and $|E1|$ and $|E2|$ edges respectively then the new graph will have $|V1|+|V2|$ vertices and $|E1|+|E2|$ edges.

Both graphs need to have the same directedness, i.e. either both directed or both undirected.

The current version of this function cannot handle graph, vertex and edge attributes, they will be lost.

Arguments:

res: Pointer to an uninitialized graph object, the result will stored here.

left: The first graph.

right: The second graph.

Returns:

Error code.

See also:

`igraph_disjoint_union_many()` for creating the disjoint union of more than two graphs,
`igraph_union()` for non-disjoint union.

Time complexity: $O(|V1|+|V2|+|E1|+|E2|)$.

Example 28.1. File `examples/simple/igraph_disjoint_union.c`

igraph_disjoint_union_many — The disjoint union of many graphs.

```
igraph_error_t igraph_disjoint_union_many(igraph_t *res,
                                           const igraph_vector_ptr_t *graphs);
```

First the vertices in the graphs will be relabeled with new vertex IDs to have pairwise disjoint vertex ID sets and then the union of the graphs is formed. The number of vertices and edges in the result is the total number of vertices and edges in the graphs.

All graphs need to have the same directedness, i.e. either all directed or all undirected. If the graph list has length zero, the result will be a *directed* graph with no vertices.

The current version of this function cannot handle graph, vertex and edge attributes, they will be lost.

Arguments:

res: Pointer to an uninitialized graph object, the result of the operation will be stored here.

graphs: Pointer vector, contains pointers to initialized graph objects.

Returns:

Error code.

See also:

`igraph_disjoint_union()` for an easier syntax if you have only two graphs, `igraph_union_many()` for non-disjoint union.

Time complexity: $O(|V|+|E|)$, the number of vertices plus the number of edges in the result.

igraph_union — Calculates the union of two graphs.

```
igraph_error_t igraph_union(igraph_t *res,
                             const igraph_t *left, const igraph_t *right,
                             igraph_vector_int_t *edge_map1, igraph_vector_int_t *edge_map2)
```

The number of vertices in the result is that of the larger graph from the two arguments. The result graph contains edges which are present in at least one of the operand graphs.

Arguments:

res: Pointer to an uninitialized graph object, the result will be stored here.

left: The first graph.

right: The second graph.

edge_map1: Pointer to an initialized vector or a null pointer. If not a null pointer, it will contain a mapping from the edges of the first argument graph (*left*) to the edges of the result graph.

edge_map2: The same as *edge_map1*, but for the second graph, *right*.

Returns:

Error code.

See also:

`igraph_union_many()` for the union of many graphs, `igraph_intersection()` and `igraph_difference()` for other operators.

Time complexity: $O(|V|+|E|)$, $|V|$ is the number of vertices, $|E|$ the number of edges in the result graph.

Example 28.2. File `examples/simple/igraph_union.c`

igraph_union_many — Creates the union of many graphs.

```
igraph_error_t igraph_union_many(  
    igraph_t *res, const igraph_vector_ptr_t *graphs,  
    igraph_vector_int_list_t *edgemaps  
);
```

The result graph will contain as many vertices as the largest graph among the arguments does, and an edge will be included in it if it is part of at least one operand graph.

The directedness of the operand graphs must be the same. If the graph list has length zero, the result will be a *directed* graph with no vertices.

Arguments:

- res*: Pointer to an uninitialized graph object, this will contain the result.
- graphs*: Pointer vector, contains pointers to the operands of the union operator, graph objects of course.
- edgemaps*: If not a null pointer, then it must be an initialized list of integer vectors, and the mappings of edges from the graphs to the result graph will be stored here, in the same order as *graphs*. Each mapping is stored in a separate `igraph_vector_int_t` object.

Returns:

Error code.

See also:

`igraph_union()` for the union of two graphs, `igraph_intersection_many()`, `igraph_intersection()` and `igraph_difference` for other operators.

Time complexity: $O(|V|+|E|)$, $|V|$ is the number of vertices in largest graph and $|E|$ is the number of edges in the result graph.

Example 28.3. File `examples/simple/igraph_union.c`

igraph_intersection — Collect the common edges from two graphs.

```
igraph_error_t igraph_intersection(igraph_t *res,  
    const igraph_t *left, const igraph_t *right,  
    igraph_vector_int_t *edge_map1,  
    igraph_vector_int_t *edge_map2);
```

The result graph contains only edges present both in the first and the second graph. The number of vertices in the result graph is the same as the larger from the two arguments.

Arguments:

- res*: Pointer to an uninitialized graph object. This will contain the result of the operation.
- left*: The first operand, a graph object.
- right*: The second operand, a graph object.
- edge_map1*: Null pointer, or an initialized vector. If the latter, then a mapping from the edges of the result graph, to the edges of the *left* input graph is stored here.
- edge_map2*: Null pointer, or an initialized vector. The same as *edge_map1*, but for the *right* input graph.

Returns:

Error code.

See also:

`igraph_intersection_many()` to calculate the intersection of many graphs at once, `igraph_union()`, `igraph_difference()` for other operators.

Time complexity: $O(|V|+|E|)$, $|V|$ is the number of nodes, $|E|$ is the number of edges in the smaller graph of the two. (The one containing less vertices is considered smaller.)

Example 28.4. File `examples/simple/igraph_intersection.c`

`igraph_intersection_many` — The intersection of more than two graphs.

```
igraph_error_t igraph_intersection_many(  
    igraph_t *res, const igraph_vector_ptr_t *graphs,  
    igraph_vector_int_list_t *edgemaps  
);
```

This function calculates the intersection of the graphs stored in the *graphs* argument. Only those edges will be included in the result graph which are part of every graph in *graphs*.

The number of vertices in the result graph will be the maximum number of vertices in the argument graphs.

Arguments:

- res*: Pointer to an uninitialized graph object, the result of the operation will be stored here.
- graphs*: Pointer vector, contains pointers to graphs objects, the operands of the intersection operator.
- edgemaps*: If not a null pointer, then it must be an initialized list of integer vectors, and the mappings of edges from the graphs to the result graph will be stored here, in the same

order as *graphs*. Each mapping is stored in a separate `igraph_vector_int_t` object. For the edges that are not in the intersection, -1 is stored.

Returns:

Error code.

See also:

`igraph_intersection()` for the intersection of two graphs, `igraph_union_many()`, `igraph_union()` and `igraph_difference()` for other operators.

Time complexity: $O(|V|+|E|)$, $|V|$ is the number of vertices, $|E|$ is the number of edges in the smallest graph (i.e. the graph having the less vertices).

Other set-like operators

`igraph_difference` — Calculate the difference of two graphs

```
igraph_error_t igraph_difference(igraph_t *res,  
                                const igraph_t *orig, const igraph_t *sub);
```

The number of vertices in the result is the number of vertices in the original graph, i.e. the left, first operand. In the results graph only edges will be included from *orig* which are not present in *sub*.

Arguments:

res: Pointer to an uninitialized graph object, the result will be stored here.

orig: The left operand of the operator, a graph object.

sub: The right operand of the operator, a graph object.

Returns:

Error code.

See also:

`igraph_intersection()` and `igraph_union()` for other operators.

Time complexity: $O(|V|+|E|)$, $|V|$ is the number vertices in the smaller graph, $|E|$ is the number of edges in the result graph.

Example 28.5. File `examples/simple/igraph_difference.c`

`igraph_complementer` — Create the complementer of a graph

```
igraph_error_t igraph_complementer(igraph_t *res, const igraph_t *graph,
                                   igraph_bool_t loops);
```

The complementer graph means that all edges which are not part of the original graph will be included in the result.

Arguments:

res: Pointer to an uninitialized graph object.

graph: The original graph.

loops: Whether to add loop edges to the complementer graph.

Returns:

Error code.

See also:

`igraph_union()`, `igraph_intersection()` and `igraph_difference()`.

Time complexity: $O(|V|+|E1|+|E2|)$, $|V|$ is the number of vertices in the graph, $|E1|$ is the number of edges in the original and $|E2|$ in the complementer graph.

Example 28.6. File `examples/simple/igraph_complementer.c`

igraph_compose — Calculates the composition of two graphs.

```
igraph_error_t igraph_compose(igraph_t *res, const igraph_t *g1, const igraph_t *g2,
                              igraph_vector_int_t *edge_map1, igraph_vector_int_t *edge_map2);
```

The composition of graphs contains the same number of vertices as the bigger graph of the two operands. It contains an (i,j) edge if and only if there is a k vertex, such that the first graph contains an (i,k) edge and the second graph a (k,j) edge.

This is of course exactly the composition of two binary relations.

The two graphs must have the same directedness, otherwise the function returns with an error. Note that for undirected graphs the two relations are by definition symmetric.

Arguments:

res: Pointer to an uninitialized graph object, the result will be stored here.

g1: The first operand, a graph object.

g2: The second operand, another graph object.

edge_map1: If not a null pointer, then it must be a pointer to an initialized vector, and a mapping from the edges of the result graph to the edges of the first graph is stored here.

edge_map1: If not a null pointer, then it must be a pointer to an initialized vector, and a mapping from the edges of the result graph to the edges of the second graph is stored here.

Returns:

Error code.

Time complexity: $O(|V|*d1*d2)$, $|V|$ is the number of vertices in the first graph, $d1$ and $d2$ the average degree in the first and second graphs.

Example 28.7. File `examples/simple/igraph_compose.c`

Miscellaneous operators

igraph_connect_neighborhood — Graph power: connect each vertex to its neighborhood.

```
igraph_error_t igraph_connect_neighborhood(igraph_t *graph, igraph_integer_t order,
                                           igraph_neimode_t mode);
```

This function adds new edges to the input graph. Each vertex is connected to all vertices reachable by at most *order* steps from it (unless a connection already existed). In other words, the *order* power of the graph is computed.

Note that the input graph is modified in place, no new graph is created. Call `igraph_copy()` if you want to keep the original graph as well.

For undirected graphs reachability is always symmetric: if vertex A can be reached from vertex B in at most *order* steps, then the opposite is also true. Only one undirected (A,B) edge will be added in this case.

Arguments:

graph: The input graph, this is the output graph as well.

order: Integer constant, it gives the distance within which the vertices will be connected to the source vertex.

mode: Constant, it specifies how the neighborhood search is performed for directed graphs. If `IGRAPH_OUT` then vertices reachable from the source vertex will be connected, `IGRAPH_IN` is the opposite. If `IGRAPH_ALL` then the directed graph is considered as an undirected one.

Returns:

Error code.

See also:

`igraph_square_lattice()` uses this function to connect the neighborhood of the vertices.

Time complexity: $O(|V|*d^k)$, $|V|$ is the number of vertices in the graph, d is the average degree and k is the *order* argument.

igraph_contract_vertices — Replace multiple vertices with a single one.

```
igraph_error_t igraph_contract_vertices(igraph_t *graph,
                                       const igraph_vector_int_t *mapping,
                                       const igraph_attribute_combination_t *vertex_comb)
```

This function modifies the graph by merging several vertices into one. The vertices in the modified graph correspond to groups of vertices in the input graph. No edges are removed, thus the modified graph will typically have self-loops (corresponding to in-group edges) and multi-edges (corresponding to multiple connections between two groups). Use `igraph_simplify()` to eliminate self-loops and merge multi-edges.

Arguments:

- graph*: The input graph. It will be modified in-place.
- mapping*: A vector giving the mapping. For each vertex in the original graph, it should contain its desired ID in the result graph. In order to create "orphan vertices" that have no corresponding vertices in the original graph, ensure that the IDs are consecutive integers starting from zero.
- vertex_comb*: What to do with the vertex attributes. NULL means that vertex attributes are not kept after the contraction (not even for unaffected vertices). See the igraph manual section about attributes for details.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices plus edges.

igraph_induced_subgraph — Creates a subgraph induced by the specified vertices.

```
igraph_error_t igraph_induced_subgraph(const igraph_t *graph, igraph_t *res,
                                       const igraph_vs_t vids, igraph_subgraph_implementation_t impl)
```

This function collects the specified vertices and all edges between them to a new graph. As the vertex IDs in a graph always start with zero, this function very likely needs to reassign IDs to the vertices.

Arguments:

- graph*: The graph object.
- res*: The subgraph, another graph object will be stored here, do *not* initialize this object before calling this function, and call `igraph_destroy()` on it if you don't need it any more.
- vids*: A vertex selector describing which vertices to keep.
- impl*: This parameter selects which implementation should we use when constructing the new graph. Basically there are two possibilities: `IGRAPH_SUBGRAPH_COPY_AND_DELETE` copies the existing graph and deletes the vertices that are not needed in the new graph,

while `IGRAPH_SUBGRAPH_CREATE_FROM_SCRATCH` constructs the new graph from scratch without copying the old one. The latter is more efficient if you are extracting a relatively small subpart of a very large graph, while the former is better if you want to extract a subgraph whose size is comparable to the size of the whole graph. There is a third possibility: `IGRAPH_SUBGRAPH_AUTO` will select one of the two methods automatically based on the ratio of the number of vertices in the new and the old graph.

Returns:

Error code: `IGRAPH_ENOMEM`, not enough memory for temporary data. `IGRAPH_EINVVID`, invalid vertex ID in *vids*.

Time complexity: $O(|V|+|E|)$, $|V|$ and $|E|$ are the number of vertices and edges in the original graph.

See also:

`igraph_delete_vertices()` to delete the specified set of vertices from a graph, the opposite of this function.

igraph_linegraph — Create the line graph of a graph.

```
igraph_error_t igraph_linegraph(const igraph_t *graph, igraph_t *linegraph);
```

The line graph $L(G)$ of a G undirected graph is defined as follows. $L(G)$ has one vertex for each edge in G and two different vertices in $L(G)$ are connected by an edge if their corresponding edges share an end point. In a multigraph, if two end points are shared, two edges are created. The vertex of a loop is counted as two end points.

The line graph $L(G)$ of a G directed graph is slightly different, $L(G)$ has one vertex for each edge in G and two vertices in $L(G)$ are connected by a directed edge if the target of the first vertex's corresponding edge is the same as the source of the second vertex's corresponding edge.

Edge i in the original graph will correspond to vertex i in the line graph.

The first version of this function was contributed by Vincent Matossian, thanks.

Arguments:

graph: The input graph, may be directed or undirected.

linegraph: Pointer to an uninitialized graph object, the result is stored here.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, the number of edges plus the number of vertices.

igraph_simplify — Removes loop and/or multiple edges from the graph.

```
igraph_error_t igraph_simplify(igraph_t *graph, igraph_bool_t multiple,
                              igraph_bool_t loops,
                              const igraph_attribute_combination_t *edge_comb);
```

Arguments:

graph: The graph object.

multiple: Logical, if true, multiple edges will be removed.

loops: Logical, if true, loops (self edges) will be removed.

edge_comb: What to do with the edge attributes. NULL means to discard the edge attributes after the operation, even for edges that were unaffected. See the igraph manual section about attributes for details.

Returns:

Error code: IGRAPH_ENOMEM if we are out of memory.

Time complexity: $O(|V|+|E|)$.

Example 28.8. File `examples/simple/igraph_simplify.c`

igraph_subgraph_edges — Creates a subgraph with the specified edges and their endpoints.

```
igraph_error_t igraph_subgraph_edges(const igraph_t *graph, igraph_t *res,
                                     const igraph_es_t eids, igraph_bool_t delete_vertices)
```

This function collects the specified edges and their endpoints to a new graph. As the vertex IDs in a graph always start with zero, this function very likely needs to reassign IDs to the vertices.

Arguments:

graph: The graph object.

res: The subgraph, another graph object will be stored here, do *not* initialize this object before calling this function, and call `igraph_destroy()` on it if you don't need it any more.

eids: An edge selector describing which edges to keep.

delete_vertices: Whether to delete the vertices not incident on any of the specified edges as well. If `false`, the number of vertices in the result graph will always be equal to the number of vertices in the input graph.

Returns:

Error code: IGRAPH_ENOMEM, not enough memory for temporary data. IGRAPH_EINVAL, invalid edge ID in *eids*.

Time complexity: $O(|V|+|E|)$, $|V|$ and $|E|$ are the number of vertices and edges in the original graph.

See also:

`igraph_delete_edges()` to delete the specified set of edges from a graph, the opposite of this function.

`igraph_reverse_edges` — Reverses some edges of a directed graph.

```
igraph_error_t igraph_reverse_edges(igraph_t *graph, const igraph_es_t eids);
```

This function reverses some edges of a directed graph. The modification is done in place. All attributes, as well as the ordering of edges and vertices are preserved.

Note that it is rarely necessary to reverse *all* edges, as almost all functions that handle directed graphs take a `mode` argument that can be set to `IGRAPH_IN` to effectively treat edges as reversed.

Arguments:

graph: The graph whose edges will be reversed.

es: The edges to be reversed. Pass `igraph_ess_all(IGRAPH_EDGEORDER_ID)` to reverse all edges.

Returns:

Error code.

Time complexity: $O(1)$ if all edges are reversed, otherwise $O(|E|)$ where $|E|$ is the number of edges in the graph.

Chapter 29. Using BLAS, LAPACK and ARPACK for igraph matrices and graphs

BLAS interface in igraph

BLAS is a highly optimized library for basic linear algebra operations such as vector-vector, matrix-vector and matrix-matrix product. Please see <http://www.netlib.org/blas/> for details and a reference implementation in Fortran. igraph contains some wrapper functions that can be used to call BLAS routines in a somewhat more user-friendly way. Not all BLAS routines are included in igraph, and even those which are included might not have wrappers; the extension of the set of wrapped functions will probably be driven by igraph's internal requirements. The wrapper functions usually substitute double-precision floating point arrays used by BLAS with `igraph_vector_t` and `igraph_matrix_t` instances and also remove those parameters (such as the number of rows/columns) that can be inferred from the passed arguments directly.

igraph_blas_ddot — Dot product of two vectors.

```
igraph_error_t igraph_blas_ddot(const igraph_vector_t *v1, const igraph_vector_t *v2, igraph_real_t *res);
```

Arguments:

`v1`: The first vector.

`v2`: The second vector.

`res`: Pointer to a real, the result will be stored here.

Time complexity: $O(n)$ where n is the length of the vectors.

Example 29.1. File `examples/simple/blas.c`

igraph_blas_dnrm2 — Euclidean norm of a vector.

```
igraph_real_t igraph_blas_dnrm2(const igraph_vector_t *v);
```

Arguments:

`v`: The vector.

Returns:

Real value, the norm of `v`.

Time complexity: $O(n)$ where n is the length of the vector.

igraph_blas_dgemv — Matrix-vector multiplication using BLAS, vector version.

```
igraph_error_t igraph_blas_dgemv(igraph_bool_t transpose, igraph_real_t alpha,  
                                const igraph_matrix_t* a, const igraph_vector_t* x,  
                                igraph_real_t beta, igraph_vector_t* y);
```

This function is a somewhat more user-friendly interface to the `dgemv` function in BLAS. `dgemv` performs the operation $y = \alpha * A * x + \beta * y$, where x and y are vectors and A is an appropriately sized matrix (symmetric or non-symmetric).

Arguments:

transpose: whether to transpose the matrix A

alpha: the constant α

a: the matrix A

x: the vector x

beta: the constant β

y: the vector y (which will be modified in-place)

Time complexity: $O(nk)$ if the matrix is of size $n \times k$

Returns:

IGRAPH_EOVERFLOW if the matrix is too large for BLAS, IGRAPH_SUCCESS otherwise.

See also:

`igraph_blas_dgemv_array` if you have arrays instead of vectors.

Example 29.2. File `examples/simple/blas.c`

igraph_blas_dgemm — Matrix-matrix multiplication using BLAS.

```
igraph_error_t igraph_blas_dgemm(igraph_bool_t transpose_a, igraph_bool_t transp  
                                igraph_real_t alpha, const igraph_matrix_t *a, const igraph_matrix_t *b  
                                igraph_real_t beta, igraph_matrix_t *c);
```

This function is a somewhat more user-friendly interface to the `dgemm` function in BLAS. `dgemm` calculates $\alpha * a * b + \beta * c$, where a , b and c are matrices, of which a and b can be transposed.

Arguments:

transpose_a: whether to transpose the matrix a

transpose_b: whether to transpose the matrix b

<i>alpha</i> :	the constant <i>alpha</i>
<i>a</i> :	the matrix <i>a</i>
<i>b</i> :	the matrix <i>b</i>
<i>beta</i> :	the constant <i>beta</i>
<i>c</i> :	the matrix <i>c</i> . The result will also be stored here. If <i>beta</i> is zero, <i>c</i> will be resized to fit the result.

Time complexity: $O(n m k)$ where matrix *a* is of size $n \times k$, and matrix *b* is of size $k \times m$.

Returns:

IGRAPH_EOVERFLOW if the matrix is too large for BLAS, IGRAPH_EINVAL if the matrices have incompatible sizes, IGRAPH_SUCCESS otherwise.

Example 29.3. File `examples/simple/blas_dgemm.c`

igraph_blas_dgemv_array — Matrix-vector multiplication using BLAS, array version.

```
igraph_error_t igraph_blas_dgemv_array(igraph_bool_t transpose, igraph_real_t a,
                                       const igraph_matrix_t* a, const igraph_real_t* x,
                                       igraph_real_t beta, igraph_real_t* y);
```

This function is a somewhat more user-friendly interface to the `dgemv` function in BLAS. `dgemv` performs the operation $y = \alpha * A * x + \beta * y$, where *x* and *y* are vectors and *A* is an appropriately sized matrix (symmetric or non-symmetric).

Arguments:

<i>transpose</i> :	whether to transpose the matrix <i>A</i>
<i>alpha</i> :	the constant <i>alpha</i>
<i>a</i> :	the matrix <i>A</i>
<i>x</i> :	the vector <i>x</i> as a regular C array
<i>beta</i> :	the constant <i>beta</i>
<i>y</i> :	the vector <i>y</i> as a regular C array (which will be modified in-place)

Time complexity: $O(nk)$ if the matrix is of size $n \times k$

Returns:

IGRAPH_EOVERFLOW if the matrix is too large for BLAS, IGRAPH_SUCCESS otherwise.

See also:

`igraph_blas_dgemv` if you have vectors instead of arrays.

LAPACK interface in igraph

LAPACK is written in Fortran90 and provides routines for solving systems of simultaneous linear equations, least-squares solutions of linear systems of equations, eigenvalue problems, and singular value problems. The associated matrix factorizations (LU, Cholesky, QR, SVD, Schur, generalized Schur) are also provided, as are related computations such as reordering of the Schur factorizations and estimating condition numbers. Dense and banded matrices are handled, but not general sparse matrices. In all areas, similar functionality is provided for real and complex matrices, in both single and double precision.

igraph provides an interface to a very limited set of LAPACK functions, using the regular igraph data structures.

See more about LAPACK at <http://www.netlib.org/lapack/>

Matrix factorization, solving linear systems

igraph_lapack_dgetrf — LU factorization of a general M-by-N matrix.

```
igraph_error_t igraph_lapack_dgetrf(igraph_matrix_t *a, igraph_vector_int_t *ipiv,
                                     int *info);
```

The factorization has the form $A = P * L * U$ where P is a permutation matrix, L is lower triangular with unit diagonal elements (lower trapezoidal if $m > n$), and U is upper triangular (upper trapezoidal if $m < n$).

Arguments:

- a*: The input/output matrix. On entry, the M-by-N matrix to be factored. On exit, the factors L and U from the factorization $A = P * L * U$; the unit diagonal elements of L are not stored.
- ipiv*: An integer vector, the pivot indices are stored here, unless it is a null pointer. Row i of the matrix was interchanged with row $ipiv[i]$.
- info*: LAPACK error code. Zero on successful exit. If its value is a positive number i , it indicates that $U(i,i)$ is exactly zero. The factorization has been completed, but the factor U is exactly singular, and division by zero will occur if it is used to solve a system of equations. If LAPACK returns an error, i.e. a negative *info* value, then an igraph error is generated as well.

Returns:

Error code.

Time complexity: TODO.

igraph_lapack_dgetrs — Solve general system of linear equations using LU factorization.

```
igraph_error_t igraph_lapack_dgetrs(igraph_bool_t transpose, const igraph_matrix_t *a,
                                     const igraph_vector_int_t *ipiv, igraph_matrix_t *b);
```

This function calls LAPACK to solve a system of linear equations $A * X = B$ or $A' * X = B$ with a general N-by-N matrix A using the LU factorization computed by `igraph_lapack_dgetrf`.

Arguments:

- transpose*: Logical scalar, whether to transpose the input matrix.
- a*: A matrix containing the L and U factors from the factorization $A = P * L * U$. L is expected to be unittriangular, diagonal entries are those of U. If A is singular, no warning or error will be given and random output will be returned.
- ipiv*: An integer vector, the pivot indices from `igraph_lapack_dgetrf()` must be given here. Row *i* of A was interchanged with row `ipiv[i]`.
- b*: The right hand side matrix must be given here. The solution will also be placed here.

Returns:

Error code.

Time complexity: TODO.

igraph_lapack_dgesv — Solve system of linear equations with LU factorization

```
igraph_error_t igraph_lapack_dgesv(igraph_matrix_t *a, igraph_vector_int_t *ipiv,  
                                   igraph_matrix_t *b, int *info);
```

This function computes the solution to a real system of linear equations $A * X = B$, where A is an N-by-N matrix and X and B are N-by-NRHS matrices.

The LU decomposition with partial pivoting and row interchanges is used to factor A as $A = P * L * U$, where P is a permutation matrix, L is unit lower triangular, and U is upper triangular. The factored form of A is then used to solve the system of equations $A * X = B$.

Arguments:

- a*: Matrix. On entry the N-by-N coefficient matrix, on exit, the factors L and U from the factorization $A = P * L * U$; the unit diagonal elements of L are not stored.
- ipiv*: An integer vector or a null pointer. If not a null pointer, then the pivot indices that define the permutation matrix P, are stored here. Row *i* of the matrix was interchanged with row `IPIV(i)`.
- b*: Matrix, on entry the right hand side matrix should be stored here. On exit, if there was no error, and the info argument is zero, then it contains the solution matrix X.
- info*: The LAPACK info code. If it is positive, then `U(info,info)` is exactly zero. In this case the factorization has been completed, but the factor U is exactly singular, so the solution could not be computed.

Returns:

Error code.

Time complexity: TODO.

Example 29.4. File `examples/simple/igraph_lapack_dgesv.c`

Eigenvalues and eigenvectors of matrices

`igraph_lapack_dsyevr` — Selected eigenvalues and optionally eigenvectors of a symmetric matrix

```
igraph_error_t igraph_lapack_dsyevr(const igraph_matrix_t *A,
                                     igraph_lapack_dsyev_which_t which,
                                     igraph_real_t vl, igraph_real_t vu, int vestimate,
                                     int il, int iu, igraph_real_t abstol,
                                     igraph_vector_t *values, igraph_matrix_t *vectors,
                                     igraph_vector_int_t *support);
```

Calls the DSYEVR LAPACK function to compute selected eigenvalues and, optionally, eigenvectors of a real symmetric matrix *A*. Eigenvalues and eigenvectors can be selected by specifying either a range of values or a range of indices for the desired eigenvalues.

See more in the LAPACK documentation.

Arguments:

- A:** Matrix, on entry it contains the symmetric input matrix. Only the leading N-by-N upper triangular part is used for the computation.
- which:** Constant that gives which eigenvalues (and possibly the corresponding eigenvectors) to calculate. Possible values are `IGRAPH_LAPACK_DSYEV_ALL`, all eigenvalues; `IGRAPH_LAPACK_DSYEV_INTERVAL`, all eigenvalues in the half-open interval $(vl, vu]$; `IGRAPH_LAPACK_DSYEV_SELECT`, the *il*-th through *iu*-th eigenvalues.
- vl:** If *which* is `IGRAPH_LAPACK_DSYEV_INTERVAL`, then this is the lower bound of the interval to be searched for eigenvalues. See also the *vestimate* argument.
- vu:** If *which* is `IGRAPH_LAPACK_DSYEV_INTERVAL`, then this is the upper bound of the interval to be searched for eigenvalues. See also the *vestimate* argument.
- vestimate:** An upper bound for the number of eigenvalues in the $(vl, vu]$ interval, if *which* is `IGRAPH_LAPACK_DSYEV_INTERVAL`. Memory is allocated only for the given number of eigenvalues (and eigenvectors), so this upper bound must be correct.
- il:** The index of the smallest eigenvalue to return, if *which* is `IGRAPH_LAPACK_DSYEV_SELECT`.
- iu:** The index of the targets eigenvalue to return, if *which* is `IGRAPH_LAPACK_DSYEV_SELECT`.
- abstol:** The absolute error tolerance for the eigenvalues. An approximate eigenvalue is accepted as converged when it is determined to lie in an interval $[a, b]$ of width less than or equal to $abstol + EPS * \max(|a|, |b|)$, where *EPS* is the machine precision.
- values:** An initialized vector, the eigenvalues are stored here, unless it is a null pointer. It will be resized as needed.
- vectors:** An initialized matrix, the eigenvectors are stored in its columns, unless it is a null pointer. It will be resized as needed.
- support:** An integer vector. If not a null pointer, then it will be resized to $(2 * \max(1, M))$ (*M* is the total number of eigenvalues found). Then the support of the eigenvectors in *vectors* is stored here, i.e., the indices indicating the nonzero elements in *vec*-

tors. The *i*-th eigenvector is nonzero only in elements `support(2*i-1)` through `support(2*i)`.

Returns:

Error code.

Time complexity: TODO.

Example 29.5. File `examples/simple/igraph_lapack_dsyevr.c`

igraph_lapack_dgeev — Eigenvalues and optionally eigenvectors of a non-symmetric matrix

```
igraph_error_t igraph_lapack_dgeev(const igraph_matrix_t *A,
                                   igraph_vector_t *valuesreal,
                                   igraph_vector_t *valuesimag,
                                   igraph_matrix_t *vectorsleft,
                                   igraph_matrix_t *vectorsright,
                                   int *info);
```

This function calls LAPACK to compute, for an *N*-by-*N* real nonsymmetric matrix *A*, the eigenvalues and, optionally, the left and/or right eigenvectors.

The right eigenvector *v*(*j*) of *A* satisfies $A * v(j) = \lambda(j) * v(j)$ where $\lambda(j)$ is its eigenvalue. The left eigenvector *u*(*j*) of *A* satisfies $u(j)**H * A = \lambda(j) * u(j)**H$ where $u(j)**H$ denotes the conjugate transpose of *u*(*j*).

The computed eigenvectors are normalized to have Euclidean norm equal to 1 and largest component real.

Arguments:

- | | |
|-----------------------|--|
| <i>A</i> : | matrix. On entry it contains the <i>N</i> -by- <i>N</i> input matrix. |
| <i>valuesreal</i> : | Pointer to an initialized vector, or a null pointer. If not a null pointer, then the real parts of the eigenvalues are stored here. The vector will be resized as needed. |
| <i>valuesimag</i> : | Pointer to an initialized vector, or a null pointer. If not a null pointer, then the imaginary parts of the eigenvalues are stored here. The vector will be resized as needed. |
| <i>vectorsleft</i> : | Pointer to an initialized matrix, or a null pointer. If not a null pointer, then the left eigenvectors are stored in the columns of the matrix. The matrix will be resized as needed. |
| <i>vectorsright</i> : | Pointer to an initialized matrix, or a null pointer. If not a null pointer, then the right eigenvectors are stored in the columns of the matrix. The matrix will be resized as needed. |
| <i>info</i> : | This argument is used for two purposes. As an input argument it gives whether an igraph error should be generated if the QR algorithm fails to compute all eigenvalues. If <i>info</i> is non-zero, then an error is generated, otherwise only a warning is given. On exit it contains the LAPACK error code. Zero means successful exit. A negative values means that some of the arguments had an illegal value, this always triggers an igraph error. An <i>i</i> positive value means that the |

QR algorithm failed to compute all the eigenvalues, and no eigenvectors have been computed; element $i+1:N$ of *valuesreal* and *valuesimag* contain eigenvalues which have converged. This case only generates an igraph error, if *info* was non-zero on entry.

Returns:

Error code.

Time complexity: TODO.

Example 29.6. File `examples/simple/igraph_lapack_dgeev.c`

igraph_lapack_dgeevx — Eigenvalues/vectors of nonsymmetric matrices, expert mode

```
igraph_error_t igraph_lapack_dgeevx(igraph_lapack_dgeevx_balance_t balance,
                                     const igraph_matrix_t *A,
                                     igraph_vector_t *valuesreal,
                                     igraph_vector_t *valuesimag,
                                     igraph_matrix_t *vectorsleft,
                                     igraph_matrix_t *vectorsright,
                                     int *ilo, int *ihi, igraph_vector_t *scale,
                                     igraph_real_t *abnrm,
                                     igraph_vector_t *rconde,
                                     igraph_vector_t *rcondv,
                                     int *info);
```

This function calculates the eigenvalues and optionally the left and/or right eigenvectors of a nonsymmetric N -by- N real matrix.

Optionally also, it computes a balancing transformation to improve the conditioning of the eigenvalues and eigenvectors (*ilo*, *ihi*, *scale*, and *abnrm*), reciprocal condition numbers for the eigenvalues (*rconde*), and reciprocal condition numbers for the right eigenvectors (*rcondv*).

The right eigenvector $v(j)$ of A satisfies $A * v(j) = \text{lambda}(j) * v(j)$ where $\text{lambda}(j)$ is its eigenvalue. The left eigenvector $u(j)$ of A satisfies $u(j)^H * A = \text{lambda}(j) * u(j)^H$ where $u(j)^H$ denotes the conjugate transpose of $u(j)$.

The computed eigenvectors are normalized to have Euclidean norm equal to 1 and largest component real.

Balancing a matrix means permuting the rows and columns to make it more nearly upper triangular, and applying a diagonal similarity transformation $D * A * D^{-1}$, where D is a diagonal matrix, to make its rows and columns closer in norm and the condition numbers of its eigenvalues and eigenvectors smaller. The computed reciprocal condition numbers correspond to the balanced matrix. Permuting rows and columns will not change the condition numbers (in exact arithmetic) but diagonal scaling will. For further explanation of balancing, see section 4.10.2 of the LAPACK Users' Guide.

Arguments:

balance: Scalar that indicated, whether the input matrix should be balanced. Possible values:

IGRAPH_LAPACK_DGEEVX_BALANCE_NONE	no not diagonally scale or permute.
-----------------------------------	-------------------------------------

Using BLAS, LAPACK
and ARPACK for igraph
matrices and graphs

	IGRAPH_LA- PACK_DGEEVX_BALANCE_PERM	perform permutations to make the matrix more nearly upper triangular. Do not diagonally scale.
	IGRAPH_LA- PACK_DGEEVX_BALANCE_SCALE	diagonally scale the matrix, i.e. replace A by $D*A*D^{(-1)}$, where D is a diagonal matrix, chosen to make the rows and columns of A more equal in norm. Do not permute.
	IGRAPH_LA- PACK_DGEEVX_BALANCE_BOTH	both diagonally scale and permute A .
<i>A</i> :	The input matrix, must be square.	
<i>valuesreal</i> :	An initialized vector, or a NULL pointer. If not a NULL pointer, then the real parts of the eigenvalues are stored here. The vector will be resized, as needed.	
<i>valuesimag</i> :	An initialized vector, or a NULL pointer. If not a NULL pointer, then the imaginary parts of the eigenvalues are stored here. The vector will be resized, as needed.	
<i>vectorsleft</i> :	An initialized matrix or a NULL pointer. If not a null pointer, then the left eigenvectors are stored here. The order corresponds to the eigenvalues and the eigenvectors are stored in a compressed form. If the j -th eigenvalue is real then column j contains the corresponding eigenvector. If the j -th and $(j+1)$ -th eigenvalues form a complex conjugate pair, then the j -th and $(j+1)$ -th columns contain their corresponding eigenvectors.	
<i>vectorsright</i> :	An initialized matrix or a NULL pointer. If not a null pointer, then the right eigenvectors are stored here. The format is the same, as for the <i>vectorsleft</i> argument.	
<i>ilo</i> :		
<i>ihi</i> :	<i>ilo</i> and <i>ihi</i> are integer values determined when A was balanced. The balanced $A(i,j) = 0$ if $I > J$ and $J = 1, \dots, ilo-1$ or $I = ihi+1, \dots, N$.	
<i>scale</i> :	<p>Pointer to an initialized vector or a NULL pointer. If not a NULL pointer, then details of the permutations and scaling factors applied when balancing A, are stored here. If $P(j)$ is the index of the row and column interchanged with row and column j, and $D(j)$ is the scaling factor applied to row and column j, then</p> <p>$scale(J) = P(J)$, for $J = 1, \dots, ilo-1$</p> <p>$scale(J) = D(J)$, for $J = ilo, \dots, ihi$</p> <p>$scale(J) = P(J)$ for $J = ihi+1, \dots, N$.</p> <p>The order in which the interchanges are made is N to $ih i+1$, then 1 to $ilo-1$.</p>	
<i>abnrm</i> :	Pointer to a real variable, the one-norm of the balanced matrix is stored here. (The one-norm is the maximum of the sum of absolute values of elements in any column.)	
<i>rconde</i> :	An initialized vector or a NULL pointer. If not a null pointer, then the reciprocal condition numbers of the eigenvalues are stored here.	

<i>rcondv</i> :	An initialized vector or a NULL pointer. If not a null pointer, then the reciprocal condition numbers of the right eigenvectors are stored here.
<i>info</i> :	This argument is used for two purposes. As an input argument it gives whether an igraph error should be generated if the QR algorithm fails to compute all eigenvalues. If <i>info</i> is non-zero, then an error is generated, otherwise only a warning is given. On exit it contains the LAPACK error code. Zero means successful exit. A negative values means that some of the arguments had an illegal value, this always triggers an igraph error. An i positive value means that the QR algorithm failed to compute all the eigenvalues, and no eigenvectors have been computed; element i+1:N of <i>valuesreal</i> and <i>valuesimag</i> contain eigenvalues which have converged. This case only generated an igraph error, if <i>info</i> was non-zero on entry.

Returns:

Error code.

Time complexity: TODO

Example 29.7. File `examples/simple/igraph_lapack_dgeevx.c`

ARPACK interface in igraph

ARPACK is a library for solving large scale eigenvalue problems. The package is designed to compute a few eigenvalues and corresponding eigenvectors of a general n by n matrix A . It is most appropriate for large sparse or structured matrices A where structured means that a matrix-vector product $w \leftarrow Av$ requires order n rather than the usual order n^2 floating point operations. Please see <http://www.caam.rice.edu/software/ARPACK/> for details.

The eigenvalue calculation in ARPACK (in the simplest case) involves the calculation of the Av product where A is the matrix we work with and v is an arbitrary vector. A user-defined function of type `igraph_arpack_function_t` is expected to perform this product. If the product can be done efficiently, e.g. if the matrix is sparse, then ARPACK is usually able to calculate the eigenvalues very quickly.

In igraph, eigenvalue/eigenvector calculations usually involve the following steps:

1. Initialization of an `igraph_arpack_options_t` data structure using `igraph_arpack_options_init`.
2. Setting some options in the initialized `igraph_arpack_options_t` object.
3. Defining a function of type `igraph_arpack_function_t`. The input of this function is a vector, and the output should be the output matrix multiplied by the input vector.
4. Calling `igraph_arpack_rssolve()` (is the matrix is symmetric), or `igraph_arpack_rnsolve()`.

The `igraph_arpack_options_t` object can be used multiple times.

If we have many eigenvalue problems to solve, then it might worth to create an `igraph_arpack_storage_t` object, and initialize it via `igraph_arpack_storage_init()`. This structure contains all memory needed for ARPACK (with the given upper limit regarding to the size of the eigenvalue problem). Then many problems can be solved using the same `igraph_arpack_storage_t` object, without always reallocating the required memory. The `igraph_arpack_storage_t` object needs to be destroyed by calling `igraph_arpack_storage_destroy()` on it, when it is not needed any more.

igraph does not contain all ARPACK routines, only the ones dealing with symmetric and non-symmetric eigenvalue problems using double precision real numbers.

Data structures

igraph_arpack_options_t — Options for ARPACK

```
typedef struct igraph_arpack_options_t {
    /* INPUT */
    char bmat[1];          /* I-standard problem, G-generalized */
    int n;                 /* Dimension of the eigenproblem */
    char which[2];         /* LA, SA, LM, SM, BE */
    int nev;               /* Number of eigenvalues to be computed */
    igraph_real_t tol;     /* Stopping criterion */
    int ncv;               /* Number of columns in V */
    int ldv;               /* Leading dimension of V */
    int ishift;            /* 0-reverse comm., 1-exact with tridiagonal */
    int mxiter;            /* Maximum number of update iterations to take */
    int nb;                /* Block size on the recurrence, only 1 works */
    int mode;              /* The kind of problem to be solved (1-5)
                           1: A*x=l*x, A symmetric
                           2: A*x=l*M*x, A symm. M pos. def.
                           3: K*x = l*M*x, K symm., M pos. semidef.
                           4: K*x = l*KG*x, K s. pos. semidef. KG s. indef.
                           5: A*x = l*M*x, A symm., M symm. pos. semidef. */
    int start;             /* 0: random, 1: use the supplied vector */
    int lworkl;            /* Size of temporary storage, default is fine */
    igraph_real_t sigma;   /* The shift for modes 3,4,5 */
    igraph_real_t sigmai;  /* The imaginary part of shift for rnsolve */
    /* OUTPUT */
    int info;              /* What happened, see docs */
    int ierr;              /* What happened in the dseupd call */
    int noiter;            /* The number of iterations taken */
    int nconv;
    int numop;             /* Number of OP*x operations */
    int numopb;            /* Number of B*x operations if BMAT='G' */
    int numreo;            /* Number of steps of re-orthogonalizations */
    /* INTERNAL */
    int iparam[11];
    int ipntr[14];
} igraph_arpack_options_t;
```

This data structure contains the options of the ARPACK eigenvalue solver routines. It must be initialized by calling `igraph_arpack_options_init()` on it. Then it can be used for multiple ARPACK calls, as the ARPACK solvers do not modify it. Input options:

Values:

bmat: Character. Whether to solve a standard ('I') or a generalized problem ('B').

n: Dimension of the eigenproblem.

which: Specifies which eigenvalues/vectors to compute. Possible values for symmetric matrices:

LA Compute nev largest (algebraic) eigenvalues.

SA	Compute nev smallest (algebraic) eigenvalues.
LM	Compute nev largest (in magnitude) eigenvalues.
SM	Compute nev smallest (in magnitude) eigenvalues.
BE	Compute nev eigenvalues, half from each end of the spectrum. When nev is odd, compute one more from the high end than from the low end.
Possible values for non-symmetric matrices:	
LM	Compute nev largest (in magnitude) eigenvalues.
SM	Compute nev smallest (in magnitude) eigenvalues.
LR	Compute nev eigenvalues of largest real part.
SR	Compute nev eigenvalues of smallest real part.
LI	Compute nev eigenvalues of largest imaginary part.
SI	Compute nev eigenvalues of smallest imaginary part.
nev:	The number of eigenvalues to be computed.
tol:	Stopping criterion: the relative accuracy of the Ritz value is considered acceptable if its error is less than tol times its estimated value. If this is set to zero then machine precision is used.
ncv:	Number of Lanczos vectors to be generated. Setting this to zero means that <code>igraph_arnoldi_solve</code> and <code>igraph_arnoldi_rnsolve</code> will determine a suitable value for ncv automatically.
ldv:	Numeric scalar. It should be set to zero in the current igraph implementation.
ishift:	Either zero or one. If zero then the shifts are provided by the user via reverse communication. If one then exact shifts with respect to the reduced tridiagonal matrix T. Please always set this to one.
mxiter:	Maximum number of Arnoldi update iterations allowed.
nb:	Blocksize to be used in the recurrence. Please always leave this on the default value, one.
mode:	The type of the eigenproblem to be solved. Possible values if the input matrix is symmetric: <ol style="list-style-type: none"> 1. $A*x = \lambda*x$, A is symmetric. 2. $A*x = \lambda*M*x$, A is symmetric, M is symmetric positive definite. 3. $K*x = \lambda*M*x$, K is symmetric, M is symmetric positive semi-definite. 4. $K*x = \lambda*KG*x$, K is symmetric positive semi-definite, KG is symmetric indefinite. 5. $A*x = \lambda*M*x$, A is symmetric, M is symmetric positive semi-definite. (Cayley transformed mode.) Please note that only mode ==1 was tested and other values might not work properly. Possible values if the input matrix is not symmetric: <ol style="list-style-type: none"> 1. $A*x = \lambda*x$. 2. $A*x = \lambda*M*x$, M is symmetric positive definite.

3. $A*x=\lambda M*x$, M is symmetric semi-definite.

4. $A*x=\lambda M*x$, M is symmetric semi-definite.

Please note that only mode == 1 was tested and other values might not work properly.

start: Whether to use the supplied starting vector (1), or use a random starting vector (0). The starting vector must be supplied in the first column of the `vectors` argument of the `igraph_arnpack_rssolve()` or `igraph_arnpack_rnsolve()` call.

Output options:

Values:

info: Error flag of ARPACK. Possible values:

0 Normal exit.

1 Maximum number of iterations taken.

3 No shifts could be applied during a cycle of the Implicitly restarted Arnoldi iteration. One possibility is to increase the size of `ncv` relative to `nev`.

ARPACK can return other error flags as well, but these are converted to igraph errors, see `igraph_error_type_t`.

ierr: Error flag of the second ARPACK call (one eigenvalue computation usually involves two calls to ARPACK). This is always zero, as other error codes are converted to igraph errors.

noiter: Number of Arnoldi iterations taken.

nconv: Number of converged Ritz values. This represents the number of Ritz values that satisfy the convergence criterion.

numop: Total number of matrix-vector multiplications.

numopb: Not used currently.

numreo: Total number of steps of re-orthogonalization.

Internal options:

Values:

lworkl: Do not modify this option.

sigma: The shift for the shift-invert mode.

sigmai: The imaginary part of the shift, for the non-symmetric or complex shift-invert mode.

iparam: Do not modify this option.

ipntr: Do not modify this option.

igraph_arnpack_storage_t — Storage for ARPACK

```
typedef struct igraph_arnpack_storage_t {
    int maxn, maxncv, maxldv;
```

```
igraph_real_t *v;
igraph_real_t *workl;
igraph_real_t *workd;
igraph_real_t *d;
igraph_real_t *resid;
igraph_real_t *ax;
int *select;
igraph_real_t *di;          /* These two only for non-symmetric problems */
igraph_real_t *workev;
} igraph_arpack_storage_t;
```

Public members, do not modify them directly, these are considered to be read-only.

Values:

maxn: Maximum rank of matrix.
maxncv: Maximum NCV.
maxldv: Maximum LDV.

These members are considered to be private:

Values:

workl: Working memory.
workd: Working memory.
d: Memory for eigenvalues.
resid: Memory for residuals.
ax: Working memory.
select: Working memory.
di: Memory for eigenvalues, non-symmetric case only.
workev: Working memory, non-symmetric case only.

igraph_arpack_function_t — Type of the ARPACK callback function

```
typedef igraph_error_t igraph_arpack_function_t(igraph_real_t *to, const igraph_
int n, void *extra);
```

Arguments:

to: Pointer to an `igraph_real_t`, the result of the matrix-vector product is expected to be stored here.
from: Pointer to an `igraph_real_t`, the input matrix should be multiplied by the vector stored here.
n: The length of the vector (which is the same as the order of the input matrix).

extra: Extra argument to the matrix-vector calculation function. This is coming from the `igraph_arnpack_rssolve()` or `igraph_arnpack_rnsolve()` function.

Returns:

Error code, if not zero, then the ARPACK solver considers this as an error, stops and calls the igraph error handler.

igraph_arnpack_options_init — Initialize ARPACK options

```
void igraph_arnpack_options_init(igraph_arnpack_options_t *o);
```

Initializes ARPACK options, set them to default values. You can always pass the initialized `igraph_arnpack_options_t` object to built-in igraph functions without any modification. The built-in igraph functions modify the options to perform their calculation, e.g. `igraph_pagerank()` always searches for the eigenvalue with the largest magnitude, regardless of the supplied value.

If you want to implement your own function involving eigenvalue calculation using ARPACK, however, you will likely need to set up the fields for yourself.

Arguments:

o: The `igraph_arnpack_options_t` object to initialize.

Time complexity: $O(1)$.

igraph_arnpack_storage_init — Initialize ARPACK storage

```
igraph_error_t igraph_arnpack_storage_init(igraph_arnpack_storage_t *s, igraph_int_t  
                                           igraph_integer_t maxncv, igraph_integer_t maxldv,  
                                           igraph_bool_t symm);
```

You only need this function if you want to run multiple eigenvalue calculations using ARPACK, and want to spare the memory allocation/deallocation between each two runs. Otherwise it is safe to supply a null pointer as the storage argument of both `igraph_arnpack_rssolve()` and `igraph_arnpack_rnsolve()` to make memory allocated and deallocated automatically.

Don't forget to call the `igraph_arnpack_storage_destroy()` function on the storage object if you don't need it any more.

Arguments:

s: The `igraph_arnpack_storage_t` object to initialize.

maxn: The maximum order of the matrices.

maxncv: The maximum NCV parameter intended to use.

maxldv: The maximum LDV parameter intended to use.

symm: Whether symmetric or non-symmetric problems will be solved using this `igraph_arnpack_storage_t`. (You cannot use the same storage both with symmetric and non-symmetric solvers.)

Returns:

Error code.

Time complexity: $O(\max_{ncv} * (\max_{ldv} + \max_n))$.

igraph_arpack_storage_destroy — Deallocate ARPACK storage

```
void igraph_arpack_storage_destroy(igraph_arpack_storage_t *s);
```

Arguments:

s: The `igraph_arpack_storage_t` object for which the memory will be deallocated.

Time complexity: operating system dependent.

ARPACK solvers

igraph_arpack_rssolve — ARPACK solver for symmetric matrices

```
igraph_error_t igraph_arpack_rssolve(igraph_arpack_function_t *fun, void *extra,  
                                     igraph_arpack_options_t *options,  
                                     igraph_arpack_storage_t *storage,  
                                     igraph_vector_t *values, igraph_matrix_t *vectors);
```

This is the ARPACK solver for symmetric matrices. Please use `igraph_arpack_rnsolve()` for non-symmetric matrices.

Arguments:

fun: Pointer to an `igraph_arpack_function_t` object, the function that performs the matrix-vector multiplication.

extra: An extra argument to be passed to *fun*.

options: An `igraph_arpack_options_t` object.

storage: An `igraph_arpack_storage_t` object, or a null pointer. In the latter case memory allocation and deallocation is performed automatically. Either this or the *vectors* argument must be non-null if the ARPACK iteration is started from a given starting vector. If both are given *vectors* take precedence.

values: If not a null pointer, then it should be a pointer to an initialized vector. The eigenvalues will be stored here. The vector will be resized as needed.

vectors: If not a null pointer, then it must be a pointer to an initialized matrix. The eigenvectors will be stored in the columns of the matrix. The matrix will be resized as needed. Either this or the *vectors* argument must be non-null if the ARPACK iteration is started from a given starting vector. If both are given *vectors* take precedence.

Returns:

Error code.

Time complexity: depends on the matrix-vector multiplication. Usually a small number of iterations is enough, so if the matrix is sparse and the matrix-vector multiplication can be done in $O(n)$ time (the number of vertices), then the eigenvalues are found in $O(n)$ time as well.

igraph_arpack_rnsolve — ARPACK solver for non-symmetric matrices

```
igraph_error_t igraph_arpack_rnsolve(igraph_arpack_function_t *fun, void *extra,
                                     igraph_arpack_options_t *options,
                                     igraph_arpack_storage_t *storage,
                                     igraph_matrix_t *values, igraph_matrix_t *vectors);
```

Please always consider calling `igraph_arpack_rssolve()` if your matrix is symmetric, it is much faster. `igraph_arpack_rnsolve()` for non-symmetric matrices.

Note that ARPACK is not called for 2x2 matrices as an exact algebraic solution exists in these cases.

Arguments:

- fun*: Pointer to an `igraph_arpack_function_t` object, the function that performs the matrix-vector multiplication.
- extra*: An extra argument to be passed to *fun*.
- options*: An `igraph_arpack_options_t` object.
- storage*: An `igraph_arpack_storage_t` object, or a null pointer. In the latter case memory allocation and deallocation is performed automatically.
- values*: If not a null pointer, then it should be a pointer to an initialized matrix. The (possibly complex) eigenvalues will be stored here. The matrix will have two columns, the first column contains the real, the second the imaginary parts of the eigenvalues. The matrix will be resized as needed.
- vectors*: If not a null pointer, then it must be a pointer to an initialized matrix. The eigenvectors will be stored in the columns of the matrix. The matrix will be resized as needed. Note that real eigenvalues will have real eigenvectors in a single column in this matrix; however, complex eigenvalues come in conjugate pairs and the result matrix will store the eigenvector corresponding to the eigenvalue with *positive* imaginary part only. Since in this case the eigenvector is also complex, it will occupy *two* columns in the eigenvector matrix (the real and the imaginary parts, in this order). Caveat: if the eigenvalue vector returns only the eigenvalue with the *negative* imaginary part for a complex conjugate eigenvalue pair, the result vector will *still* store the eigenvector corresponding to the eigenvalue with the positive imaginary part (since this is how ARPACK works).

Returns:

Error code.

Time complexity: depends on the matrix-vector multiplication. Usually a small number of iterations is enough, so if the matrix is sparse and the matrix-vector multiplication can be done in $O(n)$ time (the number of vertices), then the eigenvalues are found in $O(n)$ time as well.

igraph_arpack_unpack_complex — Make the result of the non-symmetric ARPACK solver more readable

```
igraph_error_t igraph_arpack_unpack_complex(igraph_matrix_t *vectors, igraph_ma  
igraph_integer_t nev);
```

This function works on the output of `igraph_arpack_rnsolve` and brushes it up a bit: it only keeps *nev* eigenvalues/vectors and every eigenvector is stored in two columns of the *vectors* matrix.

The output of the non-symmetric ARPACK solver is somewhat hard to parse, as real eigenvectors occupy only one column in the matrix, and the complex conjugate eigenvectors are not stored at all (usually). The other problem is that the solver might return more eigenvalues than requested. The common use of this function is to call it directly after `igraph_arpack_rnsolve` with its *vectors* and *values* argument and `options->nev` as *nev*. This will add the vectors for eigenvalues with a negative imaginary part and return all vectors as 2 columns, a real and imaginary part.

Arguments:

- vectors*: The eigenvector matrix, as returned by `igraph_arpack_rnsolve`. It will be resized, typically it will be larger.
- values*: The eigenvalue matrix, as returned by `igraph_arpack_rnsolve`. It will be resized, typically extra, unneeded rows (=eigenvalues) will be removed.
- nev*: The number of eigenvalues/vectors to keep. Can be less or equal than the number originally requested from ARPACK.

Returns:

Error code.

Time complexity: linear in the number of elements in the *vectors* matrix.

Chapter 30. Bipartite, i.e. two-mode graphs

Bipartite networks in igraph

A bipartite network contains two kinds of vertices and connections are only possible between two vertices of different kinds. There are many natural examples, e.g. movies and actors as vertices and a movie is connected to all participating actors, etc.

igraph does not have direct support for bipartite networks, at least not at the C language level. In other words the `igraph_t` structure does not contain information about the vertex types. The C functions for bipartite networks usually have an additional input argument to graph, called `types`, a boolean vector giving the vertex types.

Most functions creating bipartite networks are able to create this extra vector, you just need to supply an initialized boolean vector to them.

Create two-mode networks

`igraph_create_bipartite` — Create a bipartite graph.

```
igraph_error_t igraph_create_bipartite(igraph_t *graph, const igraph_vector_bool_t *types,
                                       const igraph_vector_int_t *edges,
                                       igraph_bool_t directed);
```

This is a simple wrapper function to create a bipartite graph. It does a little more than `igraph_create()`, e.g. it checks that the graph is indeed bipartite with respect to the given `types` vector. If there is an edge connecting two vertices of the same kind, then an error is reported.

Arguments:

- graph*: Pointer to an uninitialized graph object, the result is created here.
- types*: Boolean vector giving the vertex types. The length of the vector defines the number of vertices in the graph.
- edges*: Vector giving the edges of the graph. The highest vertex ID in this vector must be smaller than the length of the *types* vector.
- directed*: Boolean scalar, whether to create a directed graph.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

Example 30.1. File `examples/simple/igraph_bipartite_create.c`

igraph_full_bipartite — Create a full bipartite network.

```
igraph_error_t igraph_full_bipartite(igraph_t *graph,
                                     igraph_vector_bool_t *types,
                                     igraph_integer_t n1, igraph_integer_t n2,
                                     igraph_bool_t directed,
                                     igraph_neimode_t mode);
```

A bipartite network contains two kinds of vertices and connections are only possible between two vertices of different kind. There are many natural examples, e.g. movies and actors as vertices and a movie is connected to all participating actors, etc.

igraph does not have direct support for bipartite networks, at least not at the C language level. In other words the `igraph_t` structure does not contain information about the vertex types. The C functions for bipartite networks usually have an additional input argument to `graph`, called `types`, a boolean vector giving the vertex types.

Most functions creating bipartite networks are able to create this extra vector, you just need to supply an initialized boolean vector to them.

Arguments:

graph: Pointer to an `igraph_t` object, the graph will be created here.

types: Pointer to a boolean vector. If not a null pointer, then the vertex types will be stored here.

n1: Integer, the number of vertices of the first kind.

n2: Integer, the number of vertices of the second kind.

directed: Boolean, whether to create a directed graph.

mode: A constant that gives the type of connections for directed graphs. If `IGRAPH_OUT`, then edges point from vertices of the first kind to vertices of the second kind; if `IGRAPH_IN`, then the opposite direction is realized; if `IGRAPH_ALL`, then mutual edges will be created.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

See also:

`igraph_full()` for non-bipartite full graphs.

igraph_bipartite_game — Generate a bipartite random graph (similar to Erdős-Rényi).

```
igraph_error_t igraph_bipartite_game(igraph_t *graph, igraph_vector_bool_t *types,
```

```
igraph_erdos_renyi_t type,  
igraph_integer_t n1, igraph_integer_t n2,  
igraph_real_t p, igraph_integer_t m,  
igraph_bool_t directed, igraph_neimode_t mode);
```

Similarly to unipartite (one-mode) networks, we can define the $G(n,p)$, and $G(n,m)$ graph classes for bipartite graphs, via their generating process. In $G(n,p)$ every possible edge between top and bottom vertices is realized with probability p , independently of the rest of the edges. In $G(n,m)$, we uniformly choose m edges to realize.

Arguments:

- graph*: Pointer to an uninitialized igraph graph, the result is stored here.
- types*: Pointer to an initialized boolean vector, or a null pointer. If not a null pointer, then the vertex types are stored here. Bottom vertices come first, $n1$ of them, then $n2$ top vertices.
- type*: The type of the random graph, possible values:
- | | |
|------------------------|---|
| IGRAPH_ERDOS_RENYI_GNM | $G(n,m)$ graph, m edges are selected uniformly randomly in a graph with n vertices. |
| IGRAPH_ERDOS_RENYI_GNP | $G(n,p)$ graph, every possible edge is included in the graph with probability p . |
- n1*: The number of bottom vertices.
- n2*: The number of top vertices.
- p*: The connection probability for $G(n,p)$ graphs. It is ignored for $G(n,m)$ graphs.
- m*: The number of edges for $G(n,m)$ graphs. It is ignored for $G(n,p)$ graphs.
- directed*: Boolean, whether to generate a directed graph. See also the *mode* argument.
- mode*: Specifies how to direct the edges in directed graphs. If it is IGRAPH_OUT, then directed edges point from bottom vertices to top vertices. If it is IGRAPH_IN, edges point from top vertices to bottom vertices. IGRAPH_OUT and IGRAPH_IN do not generate mutual edges. If this argument is IGRAPH_ALL, then each edge direction is considered independently and mutual edges might be generated. This argument is ignored for undirected graphs.

Returns:

Error code.

See also:

`igraph_erdos_renyi_game`.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

Incidence matrices

`igraph_incidence` — Creates a bipartite graph from an incidence matrix.

```
igraph_error_t igraph_incidence(igraph_t *graph, igraph_vector_bool_t *types,
                                const igraph_matrix_t *incidence,
                                igraph_bool_t directed,
                                igraph_neimode_t mode, igraph_bool_t multiple);
```

A bipartite (or two-mode) graph contains two types of vertices and edges always connect vertices of different types. An incidence matrix is an $n \times m$ matrix, n and m are the number of vertices of the two types, respectively. Nonzero elements in the matrix denote edges between the two corresponding vertices.

Note that this function can operate in two modes, depending on the *multiple* argument. If it is *false*, then a single edge is created for every non-zero element in the incidence matrix. If *multiple* is *true*, then the matrix elements are rounded up to the closest non-negative integer to get the number of edges to create between a pair of vertices.

This function does not create multiple edges if *multiple* is *false*, but might create some if it is *true*.

Arguments:

- graph*: Pointer to an uninitialized graph object.
- types*: Pointer to an initialized boolean vector, or a null pointer. If not a null pointer, then the vertex types are stored here. It is resized as needed.
- incidence*: The incidence matrix.
- directed*: Gives whether to create an undirected or a directed graph.
- mode*: Specifies the direction of the edges in a directed graph. If `IGRAPH_OUT`, then edges point from vertices of the first kind (corresponding to rows) to vertices of the second kind (corresponding to columns); if `IGRAPH_IN`, then the opposite direction is realized; if `IGRAPH_ALL`, then mutual edges will be created.
- multiple*: How to interpret the incidence matrix elements. See details below.

Returns:

Error code.

Time complexity: $O(n \cdot m)$, the size of the incidence matrix.

igraph_get_incidence — Convert a bipartite graph into an incidence matrix.

```
igraph_error_t igraph_get_incidence(const igraph_t *graph,
                                     const igraph_vector_bool_t *types,
                                     igraph_matrix_t *res,
                                     igraph_vector_int_t *row_ids,
                                     igraph_vector_int_t *col_ids);
```

Arguments:

- graph*: The input graph, edge directions are ignored.

types: Boolean vector containing the vertex types. All vertices in one part of the graph should have type 0, the others type 1.

res: Pointer to an initialized matrix, the result is stored here. An element of the matrix gives the number of edges (irrespectively of their direction) between the two corresponding vertices. The rows will correspond to vertices with type 0, the columns correspond to vertices with type 1.

row_ids: Pointer to an initialized vector or a null pointer. If not a null pointer, then the vertex IDs (in the graph) corresponding to the rows of the result matrix are stored here.

col_ids: Pointer to an initialized vector or a null pointer. If not a null pointer, then the vertex IDs corresponding to the columns of the result matrix are stored here.

Returns:

Error code.

Time complexity: $O(n*m)$, n and m are number of vertices of the two different kind.

See also:

`igraph_incidence()` for the opposite operation.

Project two-mode graphs

`igraph_bipartite_projection_size` — Calculate the number of vertices and edges in the bipartite projections.

```
igraph_error_t igraph_bipartite_projection_size(const igraph_t *graph,
                                                const igraph_vector_bool_t *types,
                                                igraph_integer_t *vcount1,
                                                igraph_integer_t *ecount1,
                                                igraph_integer_t *vcount2,
                                                igraph_integer_t *ecount2);
```

This function calculates the number of vertices and edges in the two projections of a bipartite network. This is useful if you have a big bipartite network and you want to estimate the amount of memory you would need to calculate the projections themselves.

Arguments:

graph: The input graph.

types: Boolean vector giving the vertex types of the graph.

vcount1: Pointer to an `igraph_integer_t`, the number of vertices in the first projection is stored here. May be NULL if not needed.

ecount1: Pointer to an `igraph_integer_t`, the number of edges in the first projection is stored here. May be NULL if not needed.

vcount2: Pointer to an `igraph_integer_t`, the number of vertices in the second projection is stored here. May be NULL if not needed.

ecount2: Pointer to an `igraph_integer_t`, the number of edges in the second projection is stored here. May be NULL if not needed.

Returns:

Error code.

See also:

`igraph_bipartite_projection()` to calculate the actual projection.

Time complexity: $O(|V|*d^2+|E|)$, $|V|$ is the number of vertices, $|E|$ is the number of edges, d is the average (total) degree of the graphs.

Example **30.2.** **File** **examples/simple/
igraph_bipartite_projection.c**

igraph_bipartite_projection — Create one or both projections of a bipartite (two-mode) network.

```
igraph_error_t igraph_bipartite_projection(const igraph_t *graph,
                                           const igraph_vector_bool_t *types,
                                           igraph_t *proj1,
                                           igraph_t *proj2,
                                           igraph_vector_int_t *multiplicity1,
                                           igraph_vector_int_t *multiplicity2,
                                           igraph_integer_t probe1);
```

Creates one or both projections of a bipartite graph.

Arguments:

<i>graph</i> :	The bipartite input graph. Directedness of the edges is ignored.
<i>types</i> :	Boolean vector giving the vertex types of the graph.
<i>proj1</i> :	Pointer to an uninitialized graph object, the first projection will be created here. If a null pointer, then it is ignored, see also the <i>probe1</i> argument.
<i>proj2</i> :	Pointer to an uninitialized graph object, the second projection is created here, if it is not a null pointer. See also the <i>probe1</i> argument.
<i>multiplicity1</i> :	Pointer to a vector, or a null pointer. If not the latter, then the multiplicity of the edges is stored here. E.g. if there is an A-C-B and also an A-D-B triple in the bipartite graph (but no more X, such that A-X-B is also in the graph), then the multiplicity of the A-B edge in the projection will be 2.
<i>multiplicity2</i> :	The same as <i>multiplicity1</i> , but for the other projection.
<i>probe1</i> :	This argument can be used to specify the order of the projections in the resulting list. When it is non-negative, then it is considered as a vertex ID and the projection containing this vertex will be the first one in the result. Setting this argument to a non-negative value implies that <i>proj1</i> must be a non-null pointer. If you don't care about the ordering of the projections, pass -1 here.

Returns:

Error code.

See also:

`igraph_bipartite_projection_size()` to calculate the number of vertices and edges in the projections, without creating the projection graphs themselves.

Time complexity: $O(|V|*d^2+|E|)$, $|V|$ is the number of vertices, $|E|$ is the number of edges, d is the average (total) degree of the graphs.

Example	30.3.	File	examples/simple/
igraph_bipartite_projection.c			

Other operations on bipartite graphs

igraph_is_bipartite — Check whether a graph is bipartite.

```
igraph_error_t igraph_is_bipartite(const igraph_t *graph,
                                   igraph_bool_t *res,
                                   igraph_vector_bool_t *types);
```

This function checks whether a graph is bipartite. It tries to find a mapping that gives a possible division of the vertices into two classes, such that no two vertices of the same class are connected by an edge.

The existence of such a mapping is equivalent of having no circuits of odd length in the graph. A graph with loop edges cannot be bipartite.

Note that the mapping is not necessarily unique, e.g. if the graph has at least two components, then the vertices in the separate components can be mapped independently.

Arguments:

graph: The input graph.

res: Pointer to a boolean, the result is stored here.

types: Pointer to an initialized boolean vector, or a null pointer. If not a null pointer and a mapping was found, then it is stored here. If not a null pointer, but no mapping was found, the contents of this vector is invalid.

Returns:

Error code.

Time complexity: $O(|V|+|E|)$, linear in the number of vertices and edges.

Chapter 31. Advanced igraph programming

Using igraph in multi-threaded programs

The igraph library is considered thread-safe if it has been compiled with thread-local storage enabled, i.e. the `IGRAPH_ENABLE_TLS` setting was toggled to ON and the current platform supports this feature. To check whether an igraph build is thread-safe, use the `IGRAPH_THREAD_SAFE` macro. When linking to external versions of igraph's dependencies, it is the responsibility of the user to check that these dependencies were also compiled to be thread-safe.

IGRAPH_THREAD_SAFE — Specifies whether igraph was built in thread-safe mode.

```
#define IGRAPH_THREAD_SAFE
```

This macro is defined to 1 if the current build of the igraph library is built in thread-safe mode, and 0 if it is not. A thread-safe igraph library attempts to use thread-local data structures instead of global ones, but note that this is not (and can not) be guaranteed for third-party libraries that igraph links to.

Thread-safe ARPACK library

Note that igraph is only thread-safe if it was built with the internal ARPACK library, i.e. the one that comes with igraph. The standard ARPACK library is not thread-safe.

Thread-safety of random number generators

The default random number generator that igraph uses is *not* guaranteed to be thread-safe. You need to set a different random number generator instance for every thread that you want to use igraph from. This is especially important if you set the seed of the random number generator to ensure reproducibility; sharing a random number generator between threads would break reproducibility as the order in which the various threads are scheduled is random, and therefore they would still receive random numbers in an unpredictable order from the shared random number generator.

Progress handlers

About progress handlers

It is often useful to report the progress of some long calculation, to allow the user to follow the computation and guess the total running time. A couple of igraph functions support this at the time of writing, hopefully more will support it in the future.

To see the progress of a computation, the user has to install a progress handler, as there is none installed by default. If an igraph function supports progress reporting, then it calls the installed progress handler periodically, and passes a percentage value to it, the percentage of computation already performed. To install a progress handler, you need to call `igraph_set_progress_handler()`. Currently there is a single pre-defined progress handler, called `igraph_progress_handler_stderr()`.

Setting up progress handlers

`igraph_progress_handler_t` — Type of progress handler functions

```
typedef igraph_error_t igraph_progress_handler_t(const char *message, igraph_res_t res, void *data);
```

This is the type of the igraph progress handler functions. There is currently one such predefined function, `igraph_progress_handler_stderr()`, but the user can write and set up more sophisticated ones.

Arguments:

- message*: A string describing the function or algorithm that is reporting the progress. Current igraph functions always use the name *message* argument if reporting from the same function.
- percent*: Numeric, the percentage that was completed by the algorithm or function.
- data*: User-defined data. Current igraph functions that report progress pass a null pointer here. Users can write their own progress handlers and functions with progress reporting, and then pass some meaningful context here.

Returns:

If the return value of the progress handler is not `IGRAPH_SUCCESS`, then `igraph_progress()` returns the error code `IGRAPH_INTERRUPTED`. The `IGRAPH_PROGRESS()` macro frees all memory and finishes the igraph function with error code `IGRAPH_INTERRUPTED` in this case.

`igraph_set_progress_handler` — Install a progress handler, or remove the current handler.

```
igraph_progress_handler_t *  
igraph_set_progress_handler(igraph_progress_handler_t new_handler);
```

There is a single simple predefined progress handler: `igraph_progress_handler_stderr()`.

Arguments:

- new_handler*: Pointer to a function of type `igraph_progress_handler_t`, the progress handler function to install. To uninstall the current progress handler, this argument can be a null pointer.

Returns:

Pointer to the previously installed progress handler function.

Time complexity: $O(1)$.

igraph_progress_handler_stderr — A simple predefined progress handler.

```
igraph_error_t igraph_progress_handler_stderr(const char *message, igraph_real_t percent, void* data);
```

This simple progress handler first prints *message*, and then the percentage complete value in a short message to standard error.

Arguments:

message: A string describing the function or algorithm that is reporting the progress. Current igraph functions always use the same *message* argument if reporting from the same function.

percent: Numeric, the percentage that was completed by the algorithm or function.

data: User-defined data. Current igraph functions that report progress pass a null pointer here. Users can write their own progress handlers and functions with progress reporting, and then pass some meaningful context here.

Returns:

This function always returns with IGRAPH_SUCCESS.

Time complexity: O(1).

Invoking the progress handler

IGRAPH_PROGRESS — Report progress.

```
#define IGRAPH_PROGRESS(message, percent, data)
```

The standard way to report progress from an igraph function

Arguments:

message: A string, a textual message that references the calculation under progress.

percent: Numeric scalar, the percentage that is complete.

data: User-defined data, this can be used in user-defined progress handler functions, from user-written igraph functions.

Returns:

If the progress handler returns with IGRAPH_INTERRUPTED, then this macro frees up the igraph allocated memory for temporary data and returns to the caller with IGRAPH_INTERRUPTED.

igraph_progress — Report progress

```
igraph_error_t igraph_progress(const char *message, igraph_real_t percent, void* data);
```

Note that the usual way to report progress is the `IGRAPH_PROGRESS` macro, as that takes care of the return value of the progress handler.

Arguments:

- message*: A string describing the function or algorithm that is reporting the progress. Current igraph functions always use the name *message* argument if reporting from the same function.
- percent*: Numeric, the percentage that was completed by the algorithm or function.
- data*: User-defined data. Current igraph functions that report progress pass a null pointer here. Users can write their own progress handlers and functions with progress reporting, and then pass some meaningful context here.

Returns:

If there is a progress handler installed and it does not return `IGRAPH_SUCCESS`, then `IGRAPH_INTERRUPTED` is returned.

Time complexity: $O(1)$.

igraph_progressf — Report progress, printf-like version

```
igraph_error_t igraph_progressf(const char *message, igraph_real_t percent, void *data, ...);
```

This is a more flexible version of `igraph_progress()`, with a printf-like template string. First the template string is filled with the additional arguments and then `igraph_progress()` is called.

Note that there is an upper limit for the length of the *message* string, currently 1000 characters.

Arguments:

- message*: A string describing the function or algorithm that is reporting the progress. For this function this is a template string, using the same syntax as the standard `libc printf` function.
- percent*: Numeric, the percentage that was completed by the algorithm or function.
- data*: User-defined data. Current igraph functions that report progress pass a null pointer here. Users can write their own progress handlers and functions with progress reporting, and then pass some meaningful context here.
- ...*: Additional argument that were specified in the *message* argument.

Returns:

If there is a progress handler installed and it does not return `IGRAPH_SUCCESS`, then `IGRAPH_INTERRUPTED` is returned. \return

Writing progress handlers

To write a new progress handler, one needs to create a function of type `igraph_progress_handler_t`. The new progress handler can then be installed with the `igraph_set_progress_handler()` function.

One can assume that the first progress handler call from a calculation will be call with zero as the *percentage* argument, and the last call from a function will have 100 as the *percentage* argument. Note, however, that if an error happens in the middle of a computation, then the 100 percent call might be omitted.

Writing igraph functions with progress reporting

If you want to write a function that uses igraph and supports progress reporting, you need to include `igraph_progress()` calls in your function, usually via the `IGRAPH_PROGRESS()` macro.

It is good practice to always include a call to `igraph_progress()` with a zero *percentage* argument, before the computation; and another call with 100 *percentage* value after the computation is completed.

It is also good practice *not* to call `igraph_progress()` too often, as this would slow down the computation. It might not be worth to support progress reporting in functions with linear or log-linear time complexity, as these are fast, even with a large amount of data. For functions with quadratic or higher time complexity make sure that the time complexity of the progress reporting is constant or at least linear. In practice this means having at most $O(n)$ progress checks and at most 100 `igraph_progress()` calls.

Multi-threaded programs

In multi-threaded programs, each thread has its own progress handler, if thread-local storage is supported and igraph is thread-safe. See the `IGRAPH_THREAD_SAFE` macro for checking whether an igraph build is thread-safe.

Status handlers

Status reporting

In addition to the possibility of reporting the progress of an igraph computation via `igraph_progress()`, it is also possible to report simple status messages from within igraph functions, without having to judge how much of the computation was performed already. For this one needs to install a status handler function.

Status handler functions must be of type `igraph_status_handler_t` and they can be install by a call to `igraph_set_status_handler()`. Currently there is a simple predefined status handler function, called `igraph_status_handler_stderr()`, but the user can define new ones.

igraph functions report their status via a call to the `IGRAPH_STATUS()` or the `IGRAPH_STATUSEF()` macro.

Setting up status handlers

`igraph_status_handler_t` — The type of the igraph status handler functions

```
typedef igraph_error_t igraph_status_handler_t(const char *message, void *data)
```

Arguments:

message: The status message.

data: Additional context, with user-defined semantics. Existing igraph functions pass a null pointer here.

Returns:

Error code. The current calculation will abort if you return anything else than IGRAPH_SUCCESS here.

igraph_set_status_handler — Install or uninstall a status handler function.

```
igraph_status_handler_t *  
igraph_set_status_handler(igraph_status_handler_t new_handler);
```

To uninstall the currently installed status handler, call this function with a null pointer.

Arguments:

new_handler: The status handler function to install.

Returns:

The previously installed status handler function.

Time complexity: O(1).

igraph_status_handler_stderr — A simple predefined status handler function.

```
igraph_error_t igraph_status_handler_stderr(const char *message, void *data);
```

A simple status handler function that writes the status message to the standard error.

Arguments:

message: The status message.

data: Additional context, with user-defined semantics. Existing igraph functions pass a null pointer here.

Returns:

Error code.

Time complexity: O(1).

Invoking the status handler

IGRAPH_STATUS — Report the status of an igraph function.

```
#define IGRAPH_STATUS(message, data)
```

Typically this function is called only a handful of times from an igraph function. E.g. if an algorithm has three major steps, then it is logical to call it three times, to signal the three major steps.

Arguments:

message: The status message.

data: Additional context, with user-defined semantics. Existing igraph functions pass a null pointer here.

Returns:

If the status handler returns with a value other than `IGRAPH_SUCCESS`, then the function that called this macro returns as well, with error code `IGRAPH_INTERRUPTED`.

IGRAPH_STATUSF — Report the status from an igraph function

```
#define IGRAPH_STATUSF(args)
```

This is the more flexible version of `IGRAPH_STATUS()`, having a printf-like syntax. As this macro takes variable number of arguments, they must be all supplied as a single argument, enclosed in parentheses. Then `igraph_statusf()` is called with the given arguments.

Arguments:

args: The arguments to pass to `igraph_statusf()`.

Returns:

If the status handler returns with a value other than `IGRAPH_SUCCESS`, then the function that called this macro returns as well, with error code `IGRAPH_INTERRUPTED`.

igraph_status — Report status from an igraph function.

```
igraph_error_t igraph_status(const char *message, void *data);
```

It calls the installed status handler function, if there is one. Otherwise it does nothing. Note that the standard way to report the status from an igraph function is the `IGRAPH_STATUS` or `IGRAPH_STATUSF` macro, as these take care of the termination of the calling function if the status handler returns with `IGRAPH_INTERRUPTED`.

Arguments:

message: The status message.

data: Additional context, with user-defined semantics. Existing igraph functions pass a null pointer here.

Returns:

Error code. If a status handler function was called and it did not return with `IGRAPH_SUCCESS`, then `IGRAPH_INTERRUPTED` is returned by `igraph_status()`.

Time complexity: $O(1)$.

igraph_statusf — Report status, more flexible printf-like version.

```
igraph_error_t igraph_statusf(const char *message, void *data, ...);
```

This is the more flexible version of `igraph_status()`, that has a syntax similar to the `printf` standard C library function. It substitutes the values of the additional arguments into the *message* template string and calls `igraph_status()`.

Arguments:

- message*: Status message template string, the syntax is the same as for the `printf` function.
- data*: Additional context, with user-defined semantics. Existing igraph functions pass a null pointer here.
- ...: The additional arguments to fill the template given in the *message* argument.

Returns:

Error code. If a status handler function was called and it did not return with `IGRAPH_SUCCESS`, then `IGRAPH_INTERRUPTED` is returned by `igraph_status()`.

Chapter 32. Non-graph related functions

igraph version number

igraph_version — Return the version of the igraph C library

```
void igraph_version(const char **version_string,
                   int *major,
                   int *minor,
                   int *subminor);
```

Arguments:

version_string: Pointer to a string pointer. If not null, it is set to the igraph version string, e.g. "0.6" or "0.5.3". This string should not be modified or deallocated.

major: If not a null pointer, then it is set to the major igraph version. E.g. for version "0.5.3" this is 0.

minor: If not a null pointer, then it is set to the minor igraph version. E.g. for version "0.5.3" this is 5.

subminor: If not a null pointer, then it is set to the subminor igraph version. E.g. for version "0.5.3" this is 3.

Returns:

Error code.

Time complexity: $O(1)$.

Example 32.1. File `examples/simple/igraph_version.c`

Running mean of a time series

igraph_running_mean — Calculates the running mean of a vector.

```
igraph_error_t igraph_running_mean(const igraph_vector_t *data, igraph_vector_t
                                   igraph_integer_t binwidth);
```

The running mean is defined by the mean of the previous *binwidth* values.

Arguments:

data: The vector containing the data.

res: The vector containing the result. This should be initialized before calling this function and will be resized.

binwidth: Integer giving the width of the bin for the running mean calculation.

Returns:

Error code.

Time complexity: $O(n)$, n is the length of the data vector.

Random sampling from very long sequences

`igraph_random_sample` — Generates an increasing random sequence of integers.

```
igraph_error_t igraph_random_sample(igraph_vector_int_t *res, igraph_integer_t l, igraph_integer_t h, igraph_integer_t length);
```

This function generates an increasing sequence of random integer numbers from a given interval. The algorithm is taken literally from (Vitter 1987). This method can be used for generating numbers from a *very* large interval. It is primarily created for randomly selecting some edges from the sometimes huge set of possible edges in a large graph.

Reference:

J. S. Vitter. An efficient algorithm for sequential random sampling. ACM Transactions on Mathematical Software, 13(1):58--67, 1987. <https://doi.org/10.1145/23002.23003>

Arguments:

res: Pointer to an initialized vector. This will hold the result. It will be resized to the proper size.

l: The lower limit of the generation interval (inclusive). This must be less than or equal to the upper limit, and it must be integral.

h: The upper limit of the generation interval (inclusive). This must be greater than or equal to the lower limit, and it must be integral.

length: The number of random integers to generate.

Returns:

The error code `IGRAPH_EINVAL` is returned in each of the following cases: (1) The given lower limit is greater than the given upper limit, i.e. $l > h$. (2) Assuming that $l < h$ and N is the sample size, the above error code is returned if $N > |h - l|$, i.e. the sample size exceeds the size of the candidate pool.

Time complexity: according to (Vitter 1987), the expected running time is $O(\text{length})$.

Example 32.2. File `examples/simple/igraph_random_sample.c`

Random sampling of spatial points

igraph_sample_sphere_surface — Sample points uniformly from the surface of a sphere.

```
igraph_error_t igraph_sample_sphere_surface(igraph_integer_t dim, igraph_integer_t n,  
                                             igraph_real_t radius,  
                                             igraph_bool_t positive,  
                                             igraph_matrix_t *res);
```

The center of the sphere is at the origin.

Arguments:

dim: The dimension of the random vectors.

n: The number of vectors to sample.

radius: Radius of the sphere, it must be positive.

positive: Whether to restrict sampling to the positive orthant.

res: Pointer to an initialized matrix, the result is stored here, each column will be a sampled vector. The matrix is resized, as needed.

Returns:

Error code.

Time complexity: $O(n \cdot \text{dim} \cdot g)$, where g is the time complexity of generating a standard normal random number.

See also:

`igraph_sample_sphere_volume()`, `igraph_sample_dirichlet()` for other similar samplers.

igraph_sample_sphere_volume — Sample points uniformly from the volume of a sphere.

```
igraph_error_t igraph_sample_sphere_volume(igraph_integer_t dim, igraph_integer_t n,  
                                             igraph_real_t radius,  
                                             igraph_bool_t positive,  
                                             igraph_matrix_t *res);
```

The center of the sphere is at the origin.

Arguments:

dim: The dimension of the random vectors.

n: The number of vectors to sample.

radius: Radius of the sphere, it must be positive.

positive: Whether to restrict sampling to the positive orthant.

res: Pointer to an initialized matrix, the result is stored here, each column will be a sampled vector. The matrix is resized, as needed.

Returns:

Error code.

Time complexity: $O(n \cdot \text{dim} \cdot g)$, where g is the time complexity of generating a standard normal random number.

See also:

`igraph_sample_sphere_surface()`, `igraph_sample_dirichlet()` for other similar samplers.

`igraph_sample_dirichlet` — Sample points from a Dirichlet distribution.

```
igraph_error_t igraph_sample_dirichlet(igraph_integer_t n, const igraph_vector_t *alpha,
                                       igraph_matrix_t *res);
```

Arguments:

n: The number of vectors to sample.

alpha: The parameters of the Dirichlet distribution. They must be positive. The length of this vector gives the dimension of the generated samples.

res: Pointer to an initialized matrix, the result is stored here, one sample in each column. It will be resized, as needed.

Returns:

Error code.

Time complexity: $O(n \cdot \text{dim} \cdot g)$, where dim is the dimension of the sample vectors, set by the length of α , and g is the time complexity of sampling from a Gamma distribution.

See also:

`igraph_sample_sphere_surface()` and `igraph_sample_sphere_volume()` for other methods to sample latent vectors.

Convex hull of a set of points on a plane

`igraph_convex_hull` — Determines the convex hull of a given set of points in the 2D plane

```
igraph_error_t igraph_convex_hull(  
    const igraph_matrix_t *data, igraph_vector_int_t *resverts,  
    igraph_matrix_t *rescoords  
);
```

The convex hull is determined by the Graham scan algorithm. See the following reference for details:

Thomas H. Cormen, Charles E. Leiserson, Ronald L. Rivest, and Clifford Stein. Introduction to Algorithms, Second Edition. MIT Press and McGraw-Hill, 2001. ISBN 0262032937. Pages 949-955 of section 33.3: Finding the convex hull.

Arguments:

data: vector containing the coordinates. The length of the vector must be even, since it contains X-Y coordinate pairs.

resverts: the vector containing the result, e.g. the vector of vertex indices used as the corners of the convex hull. Supply NULL here if you are only interested in the coordinates of the convex hull corners.

rescoords: the matrix containing the coordinates of the selected corner vertices. Supply NULL here if you are only interested in the vertex indices.

Returns:

Error code: IGRAPH_ENOMEM: not enough memory

Time complexity: $O(n \log(n))$ where n is the number of vertices

Example 32.3. File `examples/simple/igraph_convex_hull.c`

Fitting power-law distributions to empirical data

`igraph_plfit_result_t` — Result of fitting a power-law distribution to a vector

```
typedef struct igraph_plfit_result_t {  
    igraph_bool_t continuous;  
    igraph_real_t alpha;  
    igraph_real_t xmin;  
    igraph_real_t L;  
    igraph_real_t D;  
    const igraph_vector_t* data;  
} igraph_plfit_result_t;
```

This data structure contains the result of `igraph_power_law_fit()`, which tries to fit a power-law distribution to a vector of numbers. The structure contains the following members:

Values:

<code>continuous:</code>	Whether the fitted power-law distribution was continuous or discrete.
<code>alpha:</code>	The exponent of the fitted power-law distribution.
<code>xmin:</code>	The minimum value from which the power-law distribution was fitted. In other words, only the values larger than <code>xmin</code> were used from the input vector.
<code>L:</code>	The log-likelihood of the fitted parameters; in other words, the probability of observing the input vector given the parameters.
<code>D:</code>	The test statistic of a Kolmogorov-Smirnov test that compares the fitted distribution with the input vector. Smaller scores denote better fit.
<code>p:</code>	The p-value of the Kolmogorov-Smirnov test; NaN if it has not been calculated yet. Small p-values (less than 0.05) indicate that the test rejected the hypothesis that the original data could have been drawn from the fitted power-law distribution.
<code>data:</code>	The vector containing the original input data. May not be valid any more if the caller already destroyed the vector.

`igraph_power_law_fit` — Fits a power-law distribution to a vector of numbers

```
igraph_error_t igraph_power_law_fit(  
    const igraph_vector_t* data, igraph_plfit_result_t* result,  
    igraph_real_t xmin, igraph_bool_t force_continuous  
);
```

This function fits a power-law distribution to a vector containing samples from a distribution (that is assumed to follow a power-law of course). In a power-law distribution, it is generally assumed that $P(X=x)$ is proportional to $x^{-\alpha}$, where x is a positive number and α is greater than 1. In many real-world cases, the power-law behaviour kicks in only above a threshold value *xmin*. The goal of this functions is to determine *alpha* if *xmin* is given, or to determine *xmin* and the corresponding value of *alpha*.

The function uses the maximum likelihood principle to determine *alpha* for a given *xmin*; in other words, the function will return the *alpha* value for which the probability of drawing the given sample is the highest. When *xmin* is not given in advance, the algorithm will attempt to find the optimal *xmin* value for which the p-value of a Kolmogorov-Smirnov test between the fitted distribution and the original sample is the largest. The function uses the method of Clauset, Shalizi and Newman to calculate the parameters of the fitted distribution. See the following reference for details:

Aaron Clauset, Cosma R. Shalizi and Mark E.J. Newman: Power-law distributions in empirical data. SIAM Review 51(4):661-703, 2009.

Arguments:

<code>data:</code>	vector containing the samples for which a power-law distribution is to be fitted. Note that you have to provide the <i>samples</i> , not the probability density function or the cumulative distribution function. For example, if you wish to fit a power-law to the degrees of a graph, you can use the output of <code>igraph_degree</code> directly as an input argument to <code>igraph_power_law_fit</code>
<code>result:</code>	the result of the fitting algorithm. See <code>igraph_plfit_result_t</code> for more details. Note that the p-value of the fit is <i>not</i> calculated by de-

fault as it is time-consuming; you need to call `igraph_plfit_result_calculate_p_value()` to calculate the p-value itself

xmin: the minimum value in the sample vector where the power-law behaviour is expected to kick in. Samples smaller than *xmin* will be ignored by the algorithm. Pass zero here if you want to include all the samples. If *xmin* is negative, the algorithm will attempt to determine its best value automatically.

force_continuous: assume that the samples in the *data* argument come from a continuous distribution even if the sample vector contains integer values only (by chance). If this argument is false, *igraph* will assume a continuous distribution if at least one sample is non-integer and assume a discrete distribution otherwise.

Returns:

Error code: `IGRAPH_ENOMEM`: not enough memory `IGRAPH_EINVAL`: one of the arguments is invalid `IGRAPH_EOVERFLOW`: overflow during the fitting process `IGRAPH_EUNDERFLOW`: underflow during the fitting process `IGRAPH_FAILURE`: the underlying algorithm signaled a failure without returning a more specific error code

Time complexity: in the continuous case, $O(n \log(n))$ if *xmin* is given. In the discrete case, the time complexity is dominated by the complexity of the underlying L-BFGS algorithm that is used to optimize α . If *xmin* is not given, the time complexity is multiplied by the number of unique samples in the input vector (although it should be faster in practice).

Example 32.4. File `examples/simple/igraph_power_law_fit.c`

`igraph_plfit_result_calculate_p_value` — Calculates the p-value of a fitted power-law model

```
igraph_error_t igraph_plfit_result_calculate_p_value(
    const igraph_plfit_result_t* model, igraph_real_t* result, igraph_real_t precision
);
```

The p-value is calculated by resampling the input data many times in a way that the part below the fitted *x_min* threshold is resampled from the input data itself, while the part above the fitted *x_min* threshold is drawn from the fitted power-law function. A Kolmogorov-Smirnov test is then performed for each resampled dataset and its test statistic is compared with the observed test statistic from the original dataset. The fraction of resampled datasets that have a *higher* test statistic is the returned p-value.

Note that the precision of the returned p-value depends on the number of resampling attempts. The number of resampling trials is determined by 0.25 divided by the square of the required precision. For instance, a required precision of 0.01 means that 2500 samples will be drawn.

Arguments:

model: The fitted power-law model from the `igraph_power_law_fit()` function

result: The calculated p-value is returned here

precision: The desired precision of the p-value. Higher values correspond to longer calculation time. @return `igraph_error_t`

Comparing floats with a tolerance

igraph_cmp_epsilon — Compare two double-precision floats with a tolerance.

```
int igraph_cmp_epsilon(double a, double b, double eps);
```

Determines whether two double-precision floats are "almost equal" to each other with a given level of tolerance on the relative error.

Arguments:

a: The first float.

b: The second float.

eps: The level of tolerance on the relative error. The relative error is defined as $\frac{\text{abs}(a-b)}{(\text{abs}(a) + \text{abs}(b))}$. The two numbers are considered equal if this is less than *eps*.

Returns:

Zero if the two floats are nearly equal to each other within the given level of tolerance, positive number if the first float is larger, negative number if the second float is larger.

igraph_almost_equals — Compare two double-precision floats with a tolerance.

```
igraph_bool_t igraph_almost_equals(double a, double b, double eps);
```

Determines whether two double-precision floats are "almost equal" to each other with a given level of tolerance on the relative error.

Arguments:

a: The first float.

b: The second float.

eps: The level of tolerance on the relative error. The relative error is defined as $\frac{\text{abs}(a-b)}{(\text{abs}(a) + \text{abs}(b))}$. The two numbers are considered equal if this is less than *eps*.

Returns:

True if the two floats are nearly equal to each other within the given level of tolerance, false otherwise.

igraph_complex_almost_equals — Compare two complex numbers with a tolerance.

```
igraph_bool_t igraph_complex_almost_equals(igraph_complex_t a,  
                                           igraph_complex_t b,  
                                           igraph_real_t eps);
```

Determines whether two complex numbers are "almost equal" to each other with a given level of tolerance on the relative error.

Arguments:

a: The first complex number.

b: The second complex number.

eps: The level of tolerance on the relative error. The relative error is defined as $\text{abs}(a-b) / (\text{abs}(a) + \text{abs}(b))$. The two numbers are considered equal if this is less than *eps*.

Returns:

True if the two complex numbers are nearly equal to each other within the given level of tolerance, false otherwise.

Chapter 33. Licenses for igraph and this manual

THE GNU GENERAL PUBLIC LICENSE

Copyright © 1989, 1991 Free Software Foundation, Inc. 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public License is intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users. This General Public License applies to most of the Free Software Foundation's software and to any other program whose authors commit to using it. (Some other Free Software Foundation software is covered by the GNU Library General Public License instead.) You can apply it to your programs, too.

When we speak of free software, we are referring to freedom, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish), that you receive source code or can get it if you want it, that you can change the software or use pieces of it in new free programs; and that you know you can do these things.

To protect your rights, we need to make restrictions that forbid anyone to deny you these rights or to ask you to surrender the rights. These restrictions translate to certain responsibilities for you if you distribute copies of the software, or if you modify it.

For example, if you distribute copies of such a program, whether gratis or for a fee, you must give the recipients all the rights that you have. You must make sure that they, too, receive or can get the source code. And you must show them these terms so they know their rights.

We protect your rights with two steps: (1) copyright the software, and (2) offer you this license which gives you legal permission to copy, distribute and/or modify the software.

Also, for each author's protection and ours, we want to make certain that everyone understands that there is no warranty for this free software. If the software is modified by someone else and passed on, we want its recipients to know that what they have is not the original, so that any problems introduced by others will not reflect on the original authors' reputations.

Finally, any free program is threatened constantly by software patents. We wish to avoid the danger that redistributors of a free program will individually obtain patent licenses, in effect making the program proprietary. To prevent this, we have made it clear that any patent must be licensed for everyone's free use or not licensed at all.

The precise terms and conditions for copying, distribution and modification follow.

GNU GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License applies to any program or other work which contains a notice placed by the copyright holder saying it may be distributed under the terms of this General Public License. The "Program", below, refers to any such program or work, and a "work based on the Program" means either the Program or any derivative work under copyright law: that is to say, a work containing the Program or a portion of it, either verbatim or with modifications and/or translated into another language. (Hereinafter, translation is included without limitation in the term "modification".) Each licensee is addressed as "you".

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running the Program is not restricted, and the output from the Program is covered only if its contents constitute a work based on the Program (independent of having been made by running the Program). Whether that is true depends on what the Program does.

1. You may copy and distribute verbatim copies of the Program's source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and give any other recipients of the Program a copy of this License along with the Program.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Program or any portion of it, thus forming a work based on the Program, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a. You must cause the modified files to carry prominent notices stating that you changed the files and the date of any change.
- b. You must cause any work that you distribute or publish, that in whole or in part contains or is derived from the Program or any part thereof, to be licensed as a whole at no charge to all third parties under the terms of this License.
- c. If the modified program normally reads commands interactively when run, you must cause it, when started running for such interactive use in the most ordinary way, to print or display an announcement including an appropriate copyright notice and a notice that there is no warranty (or else, saying that you provide a warranty) and that users may redistribute the program under these conditions, and telling the user how to view a copy of this License. (Exception: if the Program itself is interactive but does not normally print such an announcement, your work based on the Program is not required to print an announcement.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Program, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Program, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Program.

In addition, mere aggregation of another work not based on the Program with the Program (or with a work based on the Program) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may copy and distribute the Program (or a work based on it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you also do one of the following:

- a. Accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,
- b. Accompany it with a written offer, valid for at least three years, to give any third party, for a charge no more than your cost of physically performing source distribution, a complete machine-readable copy of the corresponding source code, to be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange; or,

- c. Accompany it with the information you received as to the offer to distribute corresponding source code. (This alternative is allowed only for noncommercial distribution and only if you received the program in object code or executable form with such an offer, in accord with Subsection b above.)

The source code for a work means the preferred form of the work for making modifications to it. For an executable work, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable. However, as a special exception, the source code distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

If distribution of executable or object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place counts as distribution of the source code, even though third parties are not compelled to copy the source along with the object code.

4. You may not copy, modify, sublicense, or distribute the Program except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense or distribute the Program is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

5. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Program or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Program (or any work based on the Program), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Program or works based on it.

6. Each time you redistribute the Program (or any work based on the Program), the recipient automatically receives a license from the original licensor to copy, distribute or modify the Program subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties to this License.

7. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Program at all. For example, if a patent license would not permit royalty-free redistribution of the Program by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Program.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system, which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

8. If the distribution and/or use of the Program is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Program under this License may

add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

9. The Free Software Foundation may publish revised and/or new versions of the General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Program specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Program does not specify a version number of this License, you may choose any version ever published by the Free Software Foundation.

10. If you wish to incorporate parts of the Program into other free programs whose distribution conditions are different, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

11. BECAUSE THE PROGRAM IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE PROGRAM, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE PROGRAM "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE PROGRAM IS WITH YOU. SHOULD THE PROGRAM PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

12. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE PROGRAM AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE PROGRAM (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE PROGRAM TO OPERATE WITH ANY OTHER PROGRAMS), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Programs

If you develop a new program, and you want it to be of the greatest possible use to the public, the best way to achieve this is to make it free software which everyone can redistribute and change under these terms.

To do so, attach the following notices to the program. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the program's name and a brief idea of what it does.>
Copyright (C) <year> <name of author>

This program is free software; you can redistribute it and/or modify
it under the terms of the GNU General Public License as published by

the Free Software Foundation; either version 2 of the License, or
(at your option) any later version.

This program is distributed in the hope that it will be useful,
but WITHOUT ANY WARRANTY; without even the implied warranty of
MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
GNU General Public License for more details.

You should have received a copy of the GNU General Public License
along with this program; if not, write to the Free Software
Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

If the program is interactive, make it output a short notice like this when it starts in an interactive mode:

```
Gnomovision version 69, Copyright (C) year name of author
Gnomovision comes with ABSOLUTELY NO WARRANTY; for details type `show w'.
This is free software, and you are welcome to redistribute it
under certain conditions; type `show c' for details.
```

The hypothetical commands ``show w'` and ``show c'` should show the appropriate parts of the General Public License. Of course, the commands you use may be called something other than ``show w'` and ``show c'`; they could even be mouse-clicks or menu items--whatever suits your program.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the program, if necessary. Here is a sample; alter the names:

```
Yoyodyne, Inc., hereby disclaims all copyright interest in the program
`Gnomovision' (which makes passes at compilers) written by James Hacker.
```

```
<signature of Ty Coon>, 1 April 1989
Ty Coon, President of Vice
```

This General Public License does not permit incorporating your program into proprietary programs. If your program is a subroutine library, you may consider it more useful to permit linking proprietary applications with the library. If this is what you want to do, use the GNU Library General Public License instead of this License.

The GNU Free Documentation License

Copyright © 2000, 2001, 2002 Free Software Foundation, Inc. 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The "Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ

stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section

of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties--for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by)

any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements".

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in

addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

G.1.1 ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

Copyright (c) YEAR YOUR NAME.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.2
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts.
A copy of the license is included in the section entitled "GNU
Free Documentation License".

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the "with...Texts." line with this:

with the Invariant Sections being LIST THEIR TITLES, with the
Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

Index

A

add_edge, 25
add_edges, 26
add_vertices, 26
adhesion, 555
adjacency, 208
adjacency_spectral_embedding, 597
adjacent_triangles, 495
adjlist, 211
adjlist_clear, 186
adjlist_destroy, 185
adjlist_get, 185
adjlist_init, 184
adjlist_init_complementer, 185
adjlist_init_empty, 184
adjlist_simplify, 186
adjlist_size, 186
adjlist_sort, 186
all_minimal_st_separators, 559
all_st_cuts, 547
all_st_mincuts, 548
almost_equals, 652
are_connected, 328
arpack_function_t, 625
arpack_options_init, 626
arpack_options_t, 622
arpack_rnsolve, 628
arpack_rssolve, 627
arpack_storage_destroy, 627
arpack_storage_init, 626
arpack_storage_t, 624
arpack_unpack_complex, 628
articulation_points, 370
ASSERT, 45
assortativity, 424
assortativity_degree, 425
assortativity_nominal, 422
asymmetric_preference_game, 244
atlas, 226
attribute_combination_add, 296
attribute_combination_destroy, 297
attribute_combination_init, 296
attribute_combination_remove, 297
attribute_combination_type_t, 297
attribute_table_t, 292
attribute_type_t, 295
authority_score, 386
automorphisms, 472
automorphism_group, 473
average_local_efficiency, 358
average_path_length, 343
average_path_length_dijkstra, 344
avg_nearest_neighbor_degree, 436

B

barabasi_aging_game, 246
barabasi_game, 230
betweenness, 376
betweenness_cutoff, 390
betweenness_subset, 391
bfs, 447
bfshandler_t, 449
bfs_simple, 448
bibcoupling, 400
biconnected_components, 369
bipartite_game, 631
bipartite_projection, 635
bipartite_projection_size, 634
blas_ddot, 612
blas_dgemm, 613
blas_dgemv, 613
blas_dgemv_array, 614
blas_dnrm2, 612
bliss_info_t, 470
bliss_sh_t, 470
bridges, 371

C

callaway_traits_game, 241
calloc, 47
canonical_permutation, 471
cattributte_EAB, 309
cattributte_EABV, 310
cattributte_EAB_set, 318
cattributte_EAB_setv, 323
cattributte_EAN, 307
cattributte_EANV, 308
cattributte_EAN_set, 317
cattributte_EAN_setv, 322
cattributte_EAS, 310
cattributte_EASV, 311
cattributte_EAS_set, 318
cattributte_EAS_setv, 323
cattributte_GAB, 301
cattributte_GAB_set, 313
cattributte_GAN, 300
cattributte_GAN_set, 312
cattributte_GAS, 301
cattributte_GAS_set, 313
cattributte_has_attr, 300
cattributte_list, 299
cattributte_remove_all, 326
cattributte_remove_e, 325
cattributte_remove_g, 324
cattributte_remove_v, 325
cattributte_VAB, 304
cattributte_VABV, 305
cattributte_VAB_set, 315
cattributte_VAB_setv, 320
cattributte_VAN, 302
cattributte_VANV, 303

cattribute_VAN_set, 314
cattribute_VAN_setv, 319
cattribute_VAS, 305
cattribute_VASV, 306
cattribute_VAS_set, 316
cattribute_VAS_setv, 321
centralization, 393
centralization_betweenness, 395
centralization_betweenness_tmax, 398
centralization_closeness, 395
centralization_closeness_tmax, 399
centralization_degree, 394
centralization_degree_tmax, 397
centralization_eigenvector centrality, 396
centralization_eigenvector centrality_tmax, 400
CHECK, 41
CHECK_CALLBACK, 42
circulant, 227
cited_type_game, 249
citing_cited_type_game, 250
cliques, 454
cliques_callback, 455
clique_handler_t, 456
clique_number, 462
clique_size_hist, 454
closeness, 373
closeness_cutoff, 387
clusters, 367
cmp_epsilon, 652
cocitation, 401
cohesion, 556
cohesive_blocks, 557
coloring_greedy_t, 491
community_eb_get_merges, 578
community_edge_betweenness, 577
community_fastgreedy, 579
community_fluid_communities, 583
community_infomap, 585
community_label_propagation, 584
community_leading_eigenvector, 572
community_leading_eigenvector_callback_t, 574
community_leiden, 581
community_multilevel, 580
community_optimal_modularity, 564
community_spinglass, 568
community_spinglass_single, 570
community_to_membership, 565
community_walktrap, 576
compare_communities, 566
complementer, 605
complex_almost_equals, 652
compose, 606
connected_components, 366
connect_neighborhood, 607
constraint, 382
contract_vertices, 608
convergence_degree, 387
convex_hull, 648

copy, 17
coreness, 426
correlated_game, 254
correlated_pair_game, 255
count_isomorphisms_vf2, 475
count_multiple, 422
count_subisomorphisms_vf2, 480
create, 207
create_bipartite, 630

D

decompose, 368
decompose_destroy, 369
degree, 24
degree_sequence_game, 235
DELALL, 327
DELEA, 326
DELEAS, 327
delete_edges, 27
delete_vertices, 27
delete_vertices_idx, 28
DELGA, 325
DELGAS, 326
DELVA, 325
DELVAS, 326
density, 434
destroy, 18
deterministic_optimal_imitation, 258
de_bruijn, 226
dfs, 450
dfshandler_t, 451
diameter, 346
diameter_dijkstra, 347
difference, 605
dim_select, 599
disjoint_union, 601
disjoint_union_many, 601
distances, 329
distances_bellman_ford, 331
distances_dijkstra, 330
distances_johnson, 332
diversity, 435
dominator_tree, 544
dot_product_game, 253
dqueue_back, 157
dqueue_clear, 156
dqueue_destroy, 155
dqueue_empty, 155
dqueue_full, 155
dqueue_head, 156
dqueue_init, 154
dqueue_pop, 157
dqueue_pop_back, 157
dqueue_push, 157
dqueue_size, 156
dyad_census, 493

E

EAB, 309
EABV, 310
EAN, 308
EANV, 308
EAS, 311
EASV, 312
eccentricity, 348
eccentricity_dijkstra, 349
ecount, 18
ECOUNT_MAX, 29
edge, 19
edges, 19
edge_betweenness, 377
edge_betweenness_cutoff, 390
edge_betweenness_subset, 392
edge_connectivity, 552
edge_disjoint_paths, 554
eigenvector_centrality, 384
eit_create, 286
eit_destroy, 287
EIT_END, 288
EIT_GET, 288
EIT_NEXT, 287
EIT_RESET, 288
EIT_SIZE, 288
empty, 16
empty_attrs, 16
enter_safelocale, 539
erdos_renyi_game, 232
ERROR, 40
error, 40
ERRORF, 40
errorf, 41
error_handler_abort, 32
error_handler_ignore, 32
error_handler_printignore, 32
error_handler_t, 31
error_t, 32
error_type_t, 32
ess_1, 283
ess_all, 282
ess_none, 283
ess_range, 284
ess_seq, 289
ess_vector, 284
establishment_game, 242
es_1, 279
es_all, 277
es_as_vector, 284
es_copy, 285
es_destroy, 285
es_incident, 278
es_is_all, 285
es_none, 278
es_pairs, 280
es_pairs_small, 281

es_path, 281
es_range, 280
es_seq, 289
es_size, 286
es_type, 286
es_vector, 279
es_vector_copy, 282
eulerian_cycle, 445
eulerian_path, 446
even_tarjan_reduction, 560
exit_safelocale, 540
expand_path_to_pairs, 29
extended_chordal_ring, 229

F

famous, 222
FATAL, 44
fatal, 45
FATALF, 44
fatalf, 45
fatal_handler_abort, 44
fatal_handler_t, 44
feedback_arc_set, 428
FINALLY, 42
FINALLY_CLEAN, 43
FINALLY_FREE, 43
forest_fire_game, 239
free, 48
FROM, 20
from_prufer, 225
full, 217
full_bipartite, 631
full_citation, 218
full_multipartite, 218

G

GAB, 301
GAN, 300
GAS, 302
generalized_petersen, 228
get_adjacency, 437
get_adjacency_sparse, 439
get_all_eids_between, 23
get_all_shortest_paths, 339
get_all_shortest_paths_dijkstra, 340
get_all_simple_paths, 343
get_edgelist, 440
get_eid, 21
get_eids, 22
get_incidence, 633
get_isomorphisms_vf2, 476
get_isomorphisms_vf2_callback, 477
get_k_shortest_paths, 342
get_laplacian, 417
get_laplacian_sparse, 418
get_shortest_path, 334
get_shortest_paths, 333

get_shortest_paths_bellman_ford, 337
get_shortest_paths_dijkstra, 335
get_shortest_path_bellman_ford, 338
get_shortest_path_dijkstra, 336
get_sparsemat, 443
get_stochastic, 439
get_stochastic_sparse, 440
get_stochastic_sparsemat, 443
get_subisomorphisms_vf2, 481
get_subisomorphisms_vf2_callback, 482
get_widest_path, 352
get_widest_paths, 353
girth, 348
global_efficiency, 356
gomory_hu_tree, 550
graphlets, 587
graphlets_candidate_basis, 588
graphlets_project, 588
graph_center, 350
graph_count, 488
grg_game, 230
growing_random_game, 241

H

harmonic_centrality, 375
harmonic_centrality_cutoff, 389
has_multiple, 421
heap_clear, 159
heap_delete_top, 160
heap_destroy, 159
heap_empty, 159
heap_init, 158
heap_init_array, 158
heap_push, 160
heap_reserve, 161
heap_size, 161
heap_top, 160
hrg_consensus, 593
hrg_create, 595
hrg_dendrogram, 594
hrg_destroy, 591
hrg_fit, 592
hrg_game, 594
hrg_init, 591
hrg_predict, 595
hrg_resize, 592
hrg_sample, 593
hrg_size, 591
hrg_t, 590
hsbm_game, 251
hsbm_list_game, 252
hub_score, 385

I

igraph_bool_t, 15
IGRAPH_INTEGER_MAX, 15
IGRAPH_INTEGER_MIN, 15

igraph_integer_t, 15
igraph_real_t, 15
IGRAPH_UINT_MAX, 15
IGRAPH_UINT_MIN, 15
igraph_uint_t, 15
incidence, 632
incident, 24
inclist_clear, 188
inclist_destroy, 187
inclist_get, 188
inclist_init, 187
inclist_size, 188
independence_number, 466
independent_vertex_sets, 464
induced_subgraph, 608
intersection, 603
intersection_many, 604
invalidate_cache, 29
isoclass, 486
isoclass_create, 487
isoclass_subgraph, 486
isocompat_t, 479
isohandler_t, 478
isomorphic, 468
isomorphic_34, 489
isomorphic_bliss, 472
isomorphic_function_vf2, 484
isomorphic_vf2, 474
is_acyclic, 441
is_bigraphical, 373
is_bipartite, 636
is_chordal, 430
is_connected, 367
is_dag, 427
is_directed, 18
is_eulerian, 445
is_forest, 411
is_graphical, 371
is_loop, 420
is_matching, 431
is_maximal_matching, 431
is_minimal_separator, 558
is_multiple, 421
is_mutual, 436
is_perfect, 492
is_same_graph, 30
is_separator, 558
is_simple, 420
is_tree, 411

K

kary_tree, 215
kautz, 227
k_regular_game, 236

L

lapack_dgeev, 618

lapack_dgeevx, 619
lapack_dgesv, 616
lapack_dgetrf, 615
lapack_dgetrs, 615
lapack_dsyevr, 617
laplacian, 444
laplacian_normalization_t, 419
laplacian_spectral_embedding, 598
largest_cliques, 456
largest_independent_vertex_sets, 465
largest_weighted_cliques, 463
lastcit_game, 248
lattice, 256
layout_bipartite, 504
layout_circle, 501
layout_davidson_harel, 512
layout_drl, 507
layout_drl_3d, 508
layout_drl_default_t, 506
layout_drl_options_init, 507
layout_drl_options_t, 505
layout_fruchterman_reingold, 508
layout_fruchterman_reingold_3d, 521
layout_gem, 511
layout_graphopt, 503
layout_grid, 502
layout_grid_3d, 521
layout_kamada_kawai, 510
layout_kamada_kawai_3d, 522
layout_lgl, 513
layout_mds, 513
layout_merge_dla, 524
layout_random, 501
layout_random_3d, 520
layout_reingold_tilford, 514
layout_reingold_tilford_circular, 515
layout_sphere, 520
layout_star, 502
layout_sugiyama, 517
layout_umap, 518
layout_umap_3d, 523
lazy_adjlist_clear, 190
lazy_adjlist_destroy, 189
lazy_adjlist_get, 189
lazy_adjlist_init, 189
lazy_adjlist_size, 190
lazy_inclist_clear, 192
lazy_inclist_destroy, 191
lazy_inclist_get, 191
lazy_inclist_init, 190
lazy_inclist_size, 192
lcf, 224
lcf_vector, 225
le_community_to_membership, 575
linegraph, 609
list_triangles, 495
local_efficiency, 357
local_scan_0, 361

local_scan_0_them, 363
local_scan_1_ecount, 362
local_scan_1_ecount_them, 363
local_scan_k_ecount, 362
local_scan_k_ecount_them, 364
local_scan_neighborhood_ecount, 365
local_scan_subset_ecount, 365

M

malloc, 47
MATRIX, 94
matrix_add, 102
matrix_add_cols, 116
matrix_add_constant, 102
matrix_add_rows, 116
matrix_all_almost_e, 106
matrix_all_e, 106
matrix_all_g, 107
matrix_all_ge, 107
matrix_all_l, 106
matrix_all_le, 107
matrix_as_sparsemat, 149
matrix_capacity, 112
matrix_cbind, 109
matrix_colsum, 105
matrix_complex_all_almost_e, 119
matrix_complex_create, 118
matrix_complex_create_polar, 119
matrix_complex_imag, 117
matrix_complex_real, 117
matrix_complex_realimag, 118
matrix_complex_zapsmall, 119
matrix_contains, 114
matrix_copy, 120
matrix_copy_to, 97
matrix_destroy, 93
matrix_div_elements, 104
matrix_e, 120
matrix_empty, 111
matrix_e_ptr, 120
matrix_fill, 94
matrix_get, 94
matrix_get_col, 98
matrix_get_ptr, 95
matrix_get_row, 98
matrix_init, 93
matrix_init_copy, 93
matrix_isnull, 112
matrix_is_symmetric, 113
matrix_max, 109
matrix_maxdifference, 114
matrix_min, 109
matrix_minmax, 110
matrix_mul_elements, 103
matrix_ncol, 113
matrix_nrow, 113
matrix_null, 94
matrix_prod, 104

matrix_rbind, 108
matrix_remove_col, 117
matrix_remove_row, 116
matrix_resize, 115
matrix_resize_min, 115
matrix_rowsum, 105
matrix_scale, 102
matrix_search, 114
matrix_select_cols, 101
matrix_select_rows, 100
matrix_select_rows_cols, 101
matrix_set, 95
matrix_set_col, 99
matrix_set_row, 99
matrix_size, 112
matrix_sub, 103
matrix_sum, 104
matrix_swap, 98
matrix_swap_cols, 100
matrix_swap_rows, 100
matrix_transpose, 105
matrix_update, 97
matrix_view, 96
matrix_view_from_vector, 96
matrix_which_max, 110
matrix_which_min, 110
matrix_which_minmax, 111
matrix_zapsmall, 108
maxdegree, 382
maxflow, 542
maxflow_stats_t, 545
maxflow_value, 543
maximal_cliques, 457
maximal_cliques_callback, 461
maximal_cliques_count, 458
maximal_cliques_file, 459
maximal_cliques_hist, 460
maximal_cliques_subset, 459
maximal_independent_vertex_sets, 466
maximum_bipartite_matching, 432
maximum_cardinality_search, 429
mincut, 549
mincut_value, 550
minimum_size_separators, 560
minimum_spanning_tree, 408
minimum_spanning_tree_prim, 409
minimum_spanning_tree_unweighted, 409
modularity, 562
modularity_matrix, 563
morán_process, 259
motifs_handler_t, 499
motifs_randesu, 496
motifs_randesu_callback, 498
motifs_randesu_estimate, 497
motifs_randesu_no, 497

N

neighborhood, 360

neighborhood_graphs, 360
neighborhood_size, 359
neighbors, 23

O

OTHER, 21

P

pagerank, 378
pagerank_algo_t, 377
path_length_hist, 345
permute_vertices, 488
personalized_pagerank, 379
personalized_pagerank_vs, 380
plfit_result_calculate_p_value, 651
plfit_result_t, 649
power_law_fit, 650
preference_game, 243
PROGRESS, 639
progress, 639
progressf, 640
progress_handler_stderr, 639
progress_handler_t, 638
pseudo_diameter, 351
psumtree_destroy, 193
psumtree_get, 194
psumtree_init, 193
psumtree_search, 194
psumtree_size, 193
psumtree_sum, 194
psumtree_update, 195

R

radius, 350
random_edge_walk, 453
random_sample, 646
random_spanning_tree, 410
random_walk, 452
read_graph_dimacs, 541
read_graph_dimacs_flow, 530
read_graph_dl, 538
read_graph_edgelist, 526
read_graph_gml, 534
read_graph_graphdb, 532
read_graph_graphml, 533
read_graph_lgl, 528
read_graph_ncol, 527
read_graph_pajek, 536
realize_degree_sequence, 219
realloc, 48
recent_degree_aging_game, 247
recent_degree_game, 245
reciprocity, 434
regular_tree, 216
reindex_membership, 566
reverse_edges, 611
rewire, 240

rewire_directed_edges, 234
rewire_edges, 233
ring, 214
rngtype_glibc2, 203
rngtype_mt19937, 203
rngtype_pcg32, 204
rngtype_pcg64, 204
rng_bits, 198
rng_default, 196
rng_destroy, 197
rng_get_binom, 201
rng_get_exp, 200
rng_get_gamma, 201
rng_get_geom, 202
rng_get_integer, 199
rng_get_normal, 200
rng_get_pois, 202
rng_get_unif, 199
rng_get_unif01, 199
rng_init, 197
rng_max, 198
rng_name, 198
rng_seed, 197
rng_set_default, 196
roots_for_tree_layout, 516
roulette_wheel_imitation, 261
running_mean, 645

S

sample_dirichlet, 648
sample_sphere_surface, 647
sample_sphere_volume, 647
sbm_game, 251
SETEAB, 318
SETEABV, 323
SETEAN, 317
SETEANV, 322
SETEAS, 319
SETEASV, 324
SETGAB, 313
SETGAN, 312
SETGAS, 314
SETVAB, 315
SETVABV, 321
SETVAN, 315
SETVANV, 320
SETVAS, 316
SETVASV, 322
set_attribute_table, 294
set_error_handler, 39
set_progress_handler, 638
set_status_handler, 642
set_warning_handler, 36
shortest_paths, 441
shortest_paths_bellman_ford, 442
shortest_paths_dijkstra, 442
shortest_paths_johnson, 442
similarity_dice, 404
similarity_dice_es, 406
similarity_dice_pairs, 405
similarity_inverse_log_weighted, 407
similarity_jaccard, 402
similarity_jaccard_es, 403
similarity_jaccard_pairs, 402
simple_interconnected_islands_game, 255
simplify, 609
simplify_and_colorize, 489
sir, 264
sir_destroy, 265
sir_t, 264
small, 207
spanner, 328
sparsemat, 149
sparsemat_add, 135
sparsemat_add_cols, 136
sparsemat_add_rows, 136
sparsemat_arpark_rnsolve, 148
sparsemat_arpark_rssolve, 147
sparsemat_as_matrix, 150
sparsemat_cholsol, 144
sparsemat_colsums, 131
sparsemat_compress, 140
sparsemat_copy, 150
sparsemat_count_nonzero, 130
sparsemat_count_nonzerotol, 130
sparsemat_destroy, 124
sparsemat_diag, 151
sparsemat_droptol, 133
sparsemat_dropzeros, 133
sparsemat_dupl, 141
sparsemat_entry, 132
sparsemat_eye, 151
sparsemat_fkeep, 132
sparsemat_gaxpy, 136
sparsemat_get, 127
sparsemat_getelements, 128
sparsemat_getelements_sorted, 128
sparsemat_index, 125
sparsemat_init, 121
sparsemat_init_copy, 122
sparsemat_init_diag, 122
sparsemat_init_eye, 123
sparsemat_is_cc, 127
sparsemat_is_symmetric, 127
sparsemat_is_triplet, 126
sparsemat_iterator_col, 139
sparsemat_iterator_end, 138
sparsemat_iterator_get, 139
sparsemat_iterator_idx, 140
sparsemat_iterator_init, 138
sparsemat_iterator_next, 140
sparsemat_iterator_reset, 138
sparsemat_iterator_row, 139
sparsemat_lsolve, 142
sparsemat_ltsolve, 142
sparsemat_lu, 145

sparsemat_luresol, 146
sparsemat_lusol, 144
sparsemat_max, 129
sparsemat_min, 129
sparsemat_minmax, 130
sparsemat_multiply, 135
sparsemat_ncol, 126
sparsemat_nonzero_storage, 131
sparsemat_nrow, 126
sparsemat_numeric_destroy, 147
sparsemat_permute, 134
sparsemat_print, 150
sparsemat_qr, 145
sparsemat_qrresol, 146
sparsemat_realloc, 123
sparsemat_resize, 137
sparsemat_rowsums, 131
sparsemat_scale, 134
sparsemat_sort, 137
sparsemat_syblu, 141
sparsemat_symbolic_destroy, 147
sparsemat_symbqr, 142
sparsemat_transpose, 134
sparsemat_type, 126
sparsemat_utsolve, 143
sparsemat_utsolve, 143
sparsemat_view, 124
sparse_adjacency, 210
sparse_weighted_adjacency, 211
split_join_distance, 567
square_lattice, 213
stack_clear, 153
stack_destroy, 152
stack_empty, 152
stack_init, 151
stack_pop, 154
stack_push, 153
stack_reserve, 152
stack_size, 153
stack_top, 154
star, 211
static_fitness_game, 237
static_power_law_game, 238
STATUS, 642
status, 643
STATUSF, 643
statusf, 644
status_handler_stderr, 642
status_handler_t, 641
stochastic_imitation, 262
STR, 162
strength, 383
strerror, 36
strvector_add, 169
strvector_append, 165
strvector_capacity, 168
strvector_clear, 166
strvector_copy, 169

strvector_destroy, 162
strvector_get, 163
strvector_init, 161
strvector_init_copy, 162
strvector_merge, 166
strvector_push_back, 164
strvector_push_back_len, 164
strvector_remove, 165
strvector_remove_section, 165
strvector_reserve, 167
strvector_resize, 167
strvector_resize_min, 168
strvector_set, 163
strvector_set2, 169
strvector_set_len, 164
strvector_size, 168
st_edge_connectivity, 551
st_mincut, 545
st_mincut_value, 546
st_vertex_connectivity, 552
subcomponent, 366
subgraph_edges, 610
subisomorphic, 469
subisomorphic_function_vf2, 484
subisomorphic_lad, 485
subisomorphic_vf2, 479
symmetric_tree, 215

T

THREAD_SAFE, 637
TO, 20
topological_sorting, 427
to_directed, 416
to_prufer, 412
to_undirected, 417
transitivity_avglocal_undirected, 414
transitivity_barrat, 415
transitivity_local_undirected, 414
transitivity_undirected, 413
tree, 256
tree_game, 253
triad_census, 493
trussness, 426
turan, 219

U

unfold_tree, 433
union, 602
union_many, 603

V

VAB, 304
VABV, 305
VAN, 303
VANV, 303
VAS, 306
VASV, 307

vcount, 18
VCOUNT_MAX, 28
VECTOR, 54
vector_add, 60
vector_add_constant, 59
vector_all_almost_e, 62
vector_all_e, 62
vector_all_g, 63
vector_all_ge, 64
vector_all_l, 63
vector_all_le, 63
vector_append, 57
vector_binsearch, 73
vector_binsearch2, 74
vector_binsearch_slice, 74
vector_capacity, 70
vector_clear, 75
vector_colex_cmp, 66
vector_colex_cmp_untyped, 67
vector_complex_all_almost_e, 80
vector_complex_create, 79
vector_complex_create_polar, 80
vector_complex_imag, 79
vector_complex_real, 78
vector_complex_realimag, 79
vector_complex_zapsmall, 81
vector_contains, 72
vector_copy, 90
vector_copy_to, 56
vector_destroy, 52
vector_difference_sorted, 83
vector_div, 61
vector_e, 91
vector_empty, 69
vector_e_ptr, 91
vector_fill, 53
vector_floor, 62
vector_get, 54
vector_get_ptr, 55
vector_init, 51
vector_init_array, 51
vector_init_copy, 52
vector_init_range, 52
vector_init_seq, 91
vector_insert, 77
vector_intersect_sorted, 82
vector_isininterval, 71
vector_is_any_nan, 72
vector_is_nan, 72
vector_lex_cmp, 65
vector_lex_cmp_untyped, 65
vector_list_capacity, 174
vector_list_clear, 174
vector_list_destroy, 171
vector_list_discard, 180
vector_list_discard_back, 180
vector_list_discard_fast, 181
vector_list_empty, 173
vector_list_get_ptr, 172
vector_list_init, 171
vector_list_insert, 177
vector_list_insert_copy, 178
vector_list_insert_new, 178
vector_list_permute, 181
vector_list_pop_back, 177
vector_list_push_back, 176
vector_list_push_back_copy, 176
vector_list_push_back_new, 177
vector_list_remove, 179
vector_list_remove_fast, 179
vector_list_replace, 173
vector_list_reserve, 175
vector_list_resize, 175
vector_list_set, 172
vector_list_size, 174
vector_list_sort, 182
vector_list_sort_ind, 182
vector_list_swap, 182
vector_list_swap_elements, 183
vector_list_tail_ptr, 172
vector_max, 67
vector_maxdifference, 71
vector_min, 67
vector_minmax, 68
vector_mul, 61
vector_null, 53
vector_permute, 59
vector_pop_back, 77
vector_prod, 71
vector_ptr_clear, 86
vector_ptr_copy, 92
vector_ptr_destroy, 84
vector_ptr_destroy_all, 85
vector_ptr_e, 92
vector_ptr_free_all, 85
vector_ptr_get, 87
vector_ptr_get_item_destructor, 90
vector_ptr_init, 83
vector_ptr_init_copy, 84
vector_ptr_insert, 87
vector_ptr_permute, 89
vector_ptr_pop_back, 86
vector_ptr_push_back, 86
vector_ptr_resize, 88
vector_ptr_set, 87
vector_ptr_set_item_destructor, 90
VECTOR_PTR_SET_ITEM_DESTRUCTOR, 90
vector_ptr_size, 85
vector_ptr_sort, 88
vector_ptr_sort_ind, 88
vector_push_back, 76
vector_qsort_ind, 82
vector_range, 53
vector_remove, 78
vector_remove_section, 78
vector_reserve, 75

vector_resize, 76
vector_resize_min, 76
vector_reverse, 58
vector_reverse_sort, 81
vector_scale, 60
vector_search, 73
vector_set, 55
vector_shuffle, 58
vector_size, 70
vector_sort, 81
vector_sub, 60
vector_sum, 70
vector_swap, 57
vector_swap_elements, 58
vector_tail, 55
vector_update, 56
vector_view, 56
vector_which_max, 68
vector_which_min, 68
vector_which_minmax, 69
vector_zapsmall, 64
version, 645
vertex_coloring_greedy, 491
vertex_connectivity, 553
vertex_disjoint_paths, 555
vertex_path_from_edge_path, 352
vit_create, 274
vit_destroy, 275
VIT_END, 276
VIT_GET, 277
VIT_NEXT, 276
VIT_RESET, 277
VIT_SIZE, 276
vss_1, 273
vss_all, 272
vss_none, 273
vss_range, 274
vss_seq, 290
vss_vector, 274
vs_1, 268
vs_adj, 267
vs_all, 266
vs_copy, 271
vs_destroy, 271
vs_is_all, 272
vs_nonadj, 267
vs_none, 268
vs_range, 270
vs_seq, 290
vs_size, 272
vs_type, 272
vs_vector, 269
vs_vector_copy, 270
vs_vector_small, 269

W

WARNING, 37
warning, 37

WARNINGF, 37
warningf, 38
warning_handler_ignore, 38
warning_handler_print, 38
warning_handler_t, 36
watts_strogatz_game, 232
weighted_adjacency, 209
weighted_cliques, 462
weighted_clique_number, 464
wheel, 212
widest_path_widths_dijkstra, 354
widest_path_widths_floyd_warshall, 355
write_graph_dimacs, 541
write_graph_dimacs_flow, 531
write_graph_dot, 539
write_graph_edgelist, 526
write_graph_gml, 535
write_graph_graphml, 533
write_graph_lgl, 530
write_graph_ncol, 528
write_graph_pajek, 537