




Project Mental - 2024 : Bert





BERT

- Bidirectional Encoder Representation from Tranformer



BERT?

BERT'S KEY FEATURES

- ✓ Bidirectional Encoding
- ✓ Transformer Architecture

BERT

COMPARE WITH PREVIOUS MODEL

PREVIOUS

- Sequential Processing
- Unidirectionality
- Word Embeddings limits




BERT

- Bidirectionality
- Pretraining + Fine-Tuning
- Contextualized Word Embeddings
- Use of Transformers



NLP

NLP




- Machine Translation (Google Search Engine,DeepL)
- Speech Recognition
- Predictive Text
- Spam filtering
- Voice assistants




Transformer

Transformer



- Transformer: A model that replaces RNN/LSTM
- Self-Attention: Dynamically calculates relationships between words in a sentence
- Multi-Head Attention: Learns various relationships through parallel processing
- Positional Encoding: Incorporates word order information
- Encoder-Decoder Structure: Handles input-output sequence processing



Encoder



- Input Embedding
- Positional Encoding
- Self-Attention
- Multi-Head Attention
- Feedforward Neural Network
- Layer Normalization
- Residual Connection




Bert Structure



BERT Model





BERT Input Representation

- Token Embedding: Token Embeddings use the WordPiece method to break words into smaller sub-words and employ [CLS] and [SEP] tokens to capture sentence-level meaning and distinguish between sentences.
- Segment Embedding: Adds unique vectors for different segments (e.g., Sentence A, Sentence B) to distinguish between them.
- Position Embedding: Represents the position of each word in a sentence to help the model understand the word order by adding position information.

Pre-Training

MLM

Masked Language Model

1. MASKING
2. MASKED TOKEN PROCESSING
3. USING TRANSFORMER ARCHITECTURE
4. PRE-TRAINING
5. IMPROVING CONTEXT UNDERSTANDING



NSP

Next Sentence Prediction

1. SENTENCE PAIRING
2. PREDICTION TASK
3. SENTENCE PAIR LABELS
4. TRANSFORMER STRUCTURE

TL & Fine-Tuning

TL

Transfer Learning



1. Models trained on large datasets can be used for learning even in areas with limited data.
2. Features learned from one model can be applied to a new model.
3. Use the existing model as a feature extractor.
4. Leverage the feature extraction capability of the existing model to easily build a new model.

Fine-Tuning

Fine-Tuning

1. Fine-tuning is the process of further training a pre-trained model to adapt it for a specific task.
2. Based on the existing model used as a feature extractor, fine-tuning involves training on a smaller domain-specific dataset to create a model optimized for that task.
3. The weights of the trained model are adjusted to adapt to the new task.

TL & Fine-Tuning



System	MNLI-(m/mm) 392k	QQP 363k	QNLI 108k	SST-2 67k	CoLA 8.5k	STS-B 5.7k	MRPC 3.5k	RTE 2.5k	Average -
Pre-OpenAI SOTA	80.6/80.1	66.1	82.3	93.2	35.0	81.0	86.0	61.7	74.0
BiLSTM+ELMo+Attn	76.4/76.1	64.8	79.8	90.4	36.0	73.3	84.9	56.8	71.0
OpenAI GPT	82.1/81.4	70.3	87.4	91.3	45.4	80.0	82.3	56.0	75.1
BERT _{BASE}	84.6/83.4	71.2	90.5	93.5	52.1	85.8	88.9	66.4	79.6
BERT _{LARGE}	86.7/85.9	72.1	92.7	94.9	60.5	86.5	89.3	70.1	82.1

Table 1: GLUE Test results, scored by the evaluation server (<https://gluebenchmark.com/leaderboard>). The number below each task denotes the number of training examples. The “Average” column is slightly different than the official GLUE score, since we exclude the problematic WNLI set.⁸ BERT and OpenAI GPT are single-model, single task. F1 scores are reported for QQP and MRPC, Spearman correlations are reported for STS-B, and accuracy scores are reported for the other tasks. We exclude entries that use BERT as one of their components.

System	Dev		Test	
	EM	F1	EM	F1
Top Leaderboard Systems (Dec 10th, 2018)				
Human	-	-	82.3	91.2
#1 Ensemble - nlnet	-	-	86.0	91.7
#2 Ensemble - QANet	-	-	84.5	90.5
Published				
BiDAF+ELMo (Single)	-	85.6	-	85.8
R.M. Reader (Ensemble)	81.2	87.9	82.3	88.5
Ours				
BERT _{BASE} (Single)	80.8	88.5	-	-
BERT _{LARGE} (Single)	84.1	90.9	-	-
BERT _{LARGE} (Ensemble)	85.8	91.8	-	-
BERT _{LARGE} (Sgl.+TriviaQA)	84.2	91.1	85.1	91.8
BERT _{LARGE} (Ens.+TriviaQA)	86.2	92.2	87.4	93.2

Table 2: SQuAD 1.1 results. The BERT ensemble is 7x systems which use different pre-training checkpoints and fine-tuning seeds.

System	Dev		Test	
	EM	F1	EM	F1
Top Leaderboard Systems (Dec 10th, 2018)				
Human	86.3	89.0	86.9	89.5
#1 Single - MIR-MRC (F-Net)	-	-	74.8	78.0
#2 Single - nlnet	-	-	74.2	77.1
Published				
unet (Ensemble)	-	-	71.4	74.9
SLQA+ (Single)	-	-	71.4	74.4
Ours				
BERT _{LARGE} (Single)	78.7	81.9	80.0	83.1

Table 3: SQuAD 2.0 results. We exclude entries that use BERT as one of their components.

Bert Evalutaion


- GLUE
- SQuAD




Reserch Overview



BackGround





DistilBERT

- DistilBERT is 60% smaller than BERT
- Faster Processing
- Retains High Performance
- Uses Knowledge Distillation
- Lower Resource Requirements



Code Structure



Structure(Debug)

Main_Complaints_input_ids (InputLayer)	[(None, 128)]	0	[]
Memory_input_ids (InputLayer)	[(None, 128)]	0	[]
Language_input_ids (InputLayer)	[(None, 128)]	0	[]
Orientation_input_ids (InputLayer)	[(None, 128)]	0	[]
Judgment_and_Problem_Solving_input_ids (InputLayer)	[(None, 128)]	0	[]
Home_and_Hobbies_input_ids (InputLayer)	[(None, 128)]	0	[]
Personality_and_Behavior_input_ids (InputLayer)	[(None, 128)]	0	[]
Age (InputLayer)	[(None, 1)]	0	[]

[DistilBERTEEmbeddingLayer] input_ids shape: [4 128]
[DistilBERTEEmbeddingLayer] attention_mask shape: [4 128]
[DistilBERTEEmbeddingLayer] hidden_state shape: [4 128 768]
[DistilBERTEEmbeddingLayer] CLS embedding shape: [4 768]

[DistilBERTEEmbeddingLayer] input_ids shape: [4 128]
[DistilBERTEEmbeddingLayer] attention_mask shape: [4 128]
[DistilBERTEEmbeddingLayer] hidden_state shape: [4 128 768]
[DistilBERTEEmbeddingLayer] CLS embedding shape: [4 768]

[DistilBERTEEmbeddingLayer] input_ids shape: [4 128]
[DistilBERTEEmbeddingLayer] attention_mask shape: [4 128]
[DistilBERTEEmbeddingLayer] hidden_state shape: [4 128 768]
[DistilBERTEEmbeddingLayer] CLS embedding shape: [4 768]

Debug [Personality_and_Behavior_bert_out] shape: [4 768]
Debug [Home_and_Hobbies_bert_out] shape: [4 768]
Debug [Judgment_and_Problem_Solving_bert_out] shape: [4 768]
Debug [Orientation_bert_out] shape: [4 768]
Debug [Language_bert_out] shape: [4 768]
Debug [Memory_bert_out] shape: [4 768]
Debug [Main_Complaints_bert_out] shape: [4 768]
Debug [Age_num_in] shape: [4 1]

Code-Conclusion

Epoch 1/10

1/4 [=====>.....] - ETA: 1:14 - loss: 0.9355 - categorical_accuracy: 0.5000 - 2/4
[=====>.....] - ETA: 1s - loss: 0.9936 - categorical_accuracy: 0.4375 - pr3/4
[=====>.....] - ETA: 0s - loss: 0.8326 - categorical_accuracy: 0.4583 -
pr4/4 [=====>.....] - ETA: 0s - loss: 0.7897 - categorical_accuracy:
0.4688 - precision_2: 0.5000 - precision_3: 0.3125 - recall_2: 0.4958 - recall_3: 0.4375
model save [True, False]: [loss: 0.643076] [f1: 0.000000 --> 0.000000] [f1_0: 0.000000 -->
0.000000] [f1_1: 0.000000 --> 0.000000] [pr0: 0.000000 --> 0.000000] [pr1: 0.000000 -->
0.000000]
4/4 [=====>.....] - 34s 3s/step - loss: 0.7897 -
categorical_accuracy: 0.4688 - precision_2: 0.5000 - precision_3: 0.3125 - recall_2: 0.4958 -
recall_3: 0.4375 - val_loss: 0.6431 - val_categorical_accuracy: 0.5500 - val_precision_2: 0.5714
- val_precision_3: 0.5385 - val_recall_2: 0.4000 - val_recall_3: 0.7000

Epoch 10/10


1/4 [=====>.....] - ETA: 1s - loss: 6.1612e-04 - categorical_accuracy: 0.8967 2/4
[=====>.....] - ETA: 1s - loss: 5.0488e-04 - categorical_accuracy: 0.8978 3/4
[=====>.....] - ETA: 0s - loss: 6.1528e-04 - categorical_accuracy: 0.8989
4/4 [=====>.....] - ETA: 0s - loss: 5.0549e-04 -
categorical_accuracy: 0.8999 4/4 [=====>.....] - 3s 719ms/step -
loss: 5.0549e-04 - categorical_accuracy: 0.8999 - precision_2: 0.8963 - precision_3: 0.9037 -
recall_2: 0.9057 - recall_3: 0.8941 - val_loss: 0.2554 - val_categorical_accuracy: 0.9000 -
val_precision_2: 0.9000 - val_precision_3: 0.9000 - val_recall_2: 0.9000 - val_recall_3: 0.9000

accuracy			1.00		4
macro avg	1.00	1.00	1.00		4
weighted avg	1.00	1.00	1.00		4


Confusion matrix, without normalization

[[2 0]
[0 2]]

CodeStructure



CodeStructure



Layer Nomerization

fedtherapist: mental health monitoring with user-generated linguistic expressions on smartphones via federated learning

