```
Copyright (c) 1986-2008 by Cisco Systems, Inc.
Compiled Tue 08-Apr-08 21:57 by prod_rel_team
*Mar  1 00:00:23.711: %SNMP-5-COLDSTART: SNMP agent on host R2 is undergoing a c
old start
[*Mar  1 00:00:23.891: %CRYPTO-6-ISAKMP_ON_OFF: ISAKMP is OFF
R2#show ip route
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

     10.0.0.0/8 is variably subnetted, 6 subnets, 2 masks
S       10.0.10.0/24 [1/0] via 10.10.10.1
C       10.10.10.8/30 is directly connected, FastEthernet0/1
C       10.10.10.0/30 is directly connected, FastEthernet0/0
S       10.0.30.0/24 [1/0] via 10.10.10.9
S       10.0.20.0/24 [1/0] via 10.10.10.1
S       10.0.40.0/24 [1/0] via 10.10.10.9
R2#
```