

Forward chaining algorithms for deductive reasoning in natural language

Rules

R1: If X is a parent of Y, then X is an ancestor of Y.

R2: If X is a parent of Y and Y is an ancestor of Z, then X is an ancestor of Z.

Axioms

A1: Terah is a parent of Abraham.

A2: Abraham is a parent of Isaac.

A3: Isaac is a parent of Jacob.

A4: Abraham is a parent of Ishmael.

Goal: Prove that Terah is an ancestor of Jacob · evaluation: $f = w + h$ (w = inside weight, h = heuristic)

A* search trace (true cost-to-go)

3 proof steps · all on goal path

Step 1 R1 · $f = 1 + 2 = 3$

• Isaac is a parent of Jacob
→ Isaac is an ancestor of Jacob

Step 2 R2 · $f = 2 + 1 = 3$

• Abraham is a parent of Isaac
• Isaac is an ancestor of Jacob
→ Abraham is an ancestor of Jacob

Step 3 R2 · goal · $f = 3 + 0 = 3$

• Terah is a parent of Abraham
• Abraham is an ancestor of Jacob
→ Terah is an ancestor of Jacob

search terminates

h guides search: all steps at $f = w^* = 3$

Dijkstra's algorithm — search trace ($h = 0$)

8 proof steps · 3 on path, 5 off path

Step 1 R1 · $f = 1$

→ Terah is an ancestor of Abraham

Step 2 R1 · $f = 1$

→ Abraham is an ancestor of Isaac

Step 3 R1 · $f = 1$

• Isaac is a parent of Jacob
→ Isaac is an ancestor of Jacob

Step 4 R1 · $f = 1$

→ Abraham is an ancestor of Ishmael

Step 5 R2 · $f = 2$

→ Terah is an ancestor of Isaac

Step 6 R2 · $f = 2$

• Abraham is a parent of Isaac
• Isaac is an ancestor of Jacob
→ Abraham is an ancestor of Jacob

Step 7 R2 · $f = 2$

→ Terah is an ancestor of Ishmael

Step 8 R2 · goal · $f = 3$

• Terah is a parent of Abraham
• Abraham is an ancestor of Jacob
→ Terah is an ancestor of Jacob

search terminates

no heuristic: must exhaust $f = 1, 2$ before reaching $f = 3$

on goal path

off goal path

goal reached