

DeepQ Decoding for Fault Tolerant Quantum Computation

Ryan Sweke,¹ Markus S. Kesselring,¹ Evert P.L. van Nieuwenburg,² and Jens Eisert¹

¹*Dahlem Center for Complex Quantum Systems, Freie Universität Berlin, 14195 Berlin, Germany*

²*Institute for Quantum Information and Matter, Caltech, Pasadena, CA 91125, USA*

(Dated: September 27, 2018)

Topological error correcting codes, and particularly the surface code, currently provide the most feasible roadmap towards large-scale fault tolerant quantum computation. As such, obtaining fast and flexible decoding algorithms for these codes, within the experimentally relevant context of faulty syndrome measurements, is of critical importance. In this work we show that the problem of decoding such codes, in the full fault tolerant setting, can be naturally reformulated as a process of repeated interactions between a decoding agent and a code environment, to which the machinery of reinforcement learning can be applied to obtain decoding agents. As a demonstration, by using deepQ learning, we obtain fast decoding agents for the surface code, for a variety of noise-models, within the fully fault tolerant setting.

I. INTRODUCTION

In order to implement large scale quantum algorithms it is necessary to be able to store and manipulate quantum information in a manner that is robust with respect to the unavoidable errors introduced through the interaction of physical qubits with a noisy environment. A typical strategy for achieving such robustness is to encode a single logical qubit into the state of many physical qubits, via a quantum error correcting code, from which it may be possible to actively diagnose and correct errors that might occur [1, 2]. While many quantum error correcting codes exist, topological quantum codes [1–8] in which only local operations are required to diagnose and correct errors, are of particular interest as a result of their experimental feasibility [9–15]. Recently the surface code has emerged as an especially promising code for large scale fault tolerant quantum computation, due to the combination of its comparatively low overhead and locality requirements, coupled with the availability of convenient strategies for the implementation of all required logical gates.

Within any such code based strategy for fault tolerant quantum computation, decoding algorithms play a critical role. At a high level, throughout the course of a computation these algorithms take as input the outcome of diagnostic syndrome measurements and should provide as output suggested corrections for any errors which might have occurred, which can then be tracked through the computation and later used to apply corrections to any obtained results. It is particularly important to note that in any physically realistic setting the required syndrome measurements are themselves obtained via small quantum circuits, and are therefore also generically faulty. As such, while the setting of perfect syndrome measurements provides a good test-bed for the development of decoding algorithms, any decoding algorithm which aims to be experimentally feasible should also be capable of dealing with such faulty syndrome measurements. Additionally, such algorithms should also be capable of dealing with experimentally relevant noise models, as well as be fast enough to not present a bottleneck to the execution of computations, even as the size of the code scales to larger code distances.

Due to the importance of decoding algorithms for fault tolerant quantum computation, many different approaches have been developed, each of which tries to satisfy as many of the experimentally required criterion as possible. Perhaps most prominent are algorithms based on minimum-weight perfect matching subroutines [16], however alternative approaches based on techniques such as the renormalization group [17] and locally operating cellular automata [18] have also been put forward. Furthermore, recently techniques from classical machine learning have begun to find application in diverse areas of quantum physics - such as in the efficient representation of many-body quantum states, the identification of phase transitions, and the autonomous design of novel experimental setups [MK: TODO: add citations](#) - and various neural-network based decoders have also been proposed [19–25]. However, despite the diversity of decoding algorithms now available, there is not as of yet an algorithm which clearly satisfies all the required criteria, or a clear consensus as to which technique would be the most experimentally feasible in any given experimental context. In particular, while the so-far proposed neural network decoders promise extremely fast decoding times, flexibility with respect to the underlying noise model and the potential to scale to large code distances, all such decoders are so far restricted either to the setting of perfect syndrome measurements, or to the setting in which one is trying to store a logical qubit as long as possible, without the requirement of performing a subsequent logical gate. As such, while this approach seems promising, there remains room for improvement and generalization.

Simultaneously, the last few years have also seen extremely impressive advances in the development of deep reinforcement learning algorithms, which have allowed for the training of neural network based agents capable of obtaining super-human performance in domains such as Atari [26], Chess [27] and Go [28]. These techniques are

particularly powerful in situations where it is necessary to learn strategies for complex sequential decision making, involving consideration of the future effects of ones actions. At a surface level, the problem of decoding within the context of fault-tolerant quantum computation seems like exactly such a setting and as such it natural to ask to what extent reinforcement learning techniques could be used to obtain decoding agents, and what advantages such agents might have over existing approaches. In this work we set out to provide answers to these questions.

In particular, we reformulate the problem of decoding within the setting of fault-tolerant quantum computation as a process of sequential competitive interaction between a decoding agent and a code environment. This reframing provides a conceptual framework which allows for the application of various deep reinforcement learning algorithms to obtain neural network based decoding agents. As a proof-of-principle, we then utilize to deepQ learning to obtain fast surface code decoders, for a variety of noise models, within the fully fault-tolerant setting. These results then provide a foundation for extension via both more sophisticated reinforcement learning techniques and more sophisticated neural network models.

In this work we begin by providing an introductory overview of the surface code in Section II, before presenting a description of the decoding problem for fault-tolerant quantum computation in Section III. After a brief introduction to the formalism of reinforcement learning and Q -functions in Section IV we are then able to provide the conceptual reframing of decoding as a reinforcement learning problem in Section V, which is one of the primary results of this work. In Section VI we then present deepQ surface code decoders for a variety of noise models, before finally in Section VII discussing both the advantages and disadvantages of the approach presented here, along with various potential strategies for building upon the results presented in this work.

II. THE SURFACE CODE

The framework and methods presented in this work are not restricted to the surface code, and could be applied to any stabilizer code, but we choose to restrict ourselves to this code here for both simplicity of presentation and experimental relevance. We will focus here on presenting the elements of the surface code necessary for understanding the decoding problem that we aim to address, in the process omitting many details. We refer the reader to the references [5, 29] for indepth discussion of quantum error correction and stabilizer codes.

For the surface code, we will consider a $d \times d$ lattices with a *physical data qubit* on each vertex, as illustrated in Fig. 1. Plaquettes of this lattice are associated with stabilizers of one of two types. Given single-qubit Pauli operators X and Z , bulk (boundary) plaquette stabilizers X_p and Z_p are local four (two) body operators,

$$X_p \equiv \bigotimes_{q \in p} X_q, \quad Z_p \equiv \bigotimes_{q \in p} Z_q, \quad (1)$$

which act only on the vertex qubits of plaquette p . With reference to Fig 1, if we denote the set of all blue (orange) plaquettes as B_p (O_p), then the set S of stabilizers defining the surface code is given by,

$$S = \{X_p | p \in B_p\} \cup \{Z_p | p \in O_p\}, \quad (2)$$

from which we can define the Hamiltonian of the surface code as $H_{sc} \equiv -\sum_{\hat{O} \in S} \hat{O}$.

The *code space* \mathcal{H}_{sc} is the ground state space of the surface code Hamiltonian H_{sc} . This code space contains all surface code states $|\psi\rangle \in \mathcal{H}_{sc}$ which are simultaneous $+1$ eigenstates of all stabilizers $\hat{O} \in S$. A simple counting argument allows one to verify that this code space is two-dimensional - i.e. $\mathcal{H}_{sc} \simeq \mathbb{C}^2$. We can thus effectively identify the code space with the state space of a single *logical qubit*. Operators acting on logical qubits are called *logical operators*, examples of the logical X and Z operators Z_L (X_L) are illustrated in Fig. 1.

Errors on physical qubits anticommute with surrounding stabilizers, see Fig. 1 (b). The stabilizer operators are measured in regular intervals to obtain the *syndrome*, a list of violated stabilizers. This enables an indirect detection of errors, as the outcome of the syndrome measurements depend on the occurred errors. However, there exist multiple inequivalent error configurations with the same syndrome. A *decoder* is an algorithm which takes in a syndrome and returns a proposed correction, hopefully undoing the error and returning the logical qubit to its original state.

III. THE DECODING PROBLEM

Given the foundations from the previous section, we are able to succinctly state a simple preliminary version of the decoding problem:




FIG. 1. An overview of the surface code. (a) We consider square $d \times d$ lattices (shown $d = 5$), with a data qubit on each vertex of the lattice. Additionally, there exist two types of local stabilizer operators: X (Z) stabilizers, which act on the vertex qubits of blue (orange) plaquettes. (b) Assuming an initial simultaneous $+1$ eigenstate of all stabilizers, a qubit Pauli flip on a single physical qubit will anti-commute with certain stabilizers supported on this qubit. We call these stabilizers *violated* and marked them with a red dot. (c) Logical X_L (Z_L) operators for the surface code are provided by continuous strings of single qubit X (Z) operators connecting the top and bottom (left and right) boundaries of the code respectively. MK: I am not a big fan of these colours =)




FIG. 2. In the left hand panel, the syndromes associated with various error configurations are illustrated. Note that the error configurations in (a) and (b) lead to the same syndrome. Also, as can be seen in (c), note that continuous strings of errors result in violated stabilizers only at the endpoint of the string. In the right hand panel a typical decoding cycle is illustrated, for the simplified faulty measurements scenario in which one imagines each time step consisting of an initial physical error process generating errors on the data qubits, followed by a second measurement error process which corrupts the true syndrome. The decoding algorithm then has access to a sequence of potentially faulty syndromes.

Assume that at $t = 0$ one is given a global lattice state $|\psi\rangle = \alpha|0_L\rangle + \beta|1_L\rangle$, which is an element of the code space. At some time $t_1 > 0$ a syndrome measurement is performed which indicates that one or more stabilizers are violated - i.e. some errors have occurred on data qubits. From the given syndrome, determine a set of corrections which should be applied to the code lattice such that the subsequent global state of the lattice is equal to the state $|\psi\rangle$ at $t = 0$.

Before proceeding to discuss more subtle and technical versions of the decoding problem, let's examine why even the above problem is indeed potentially difficult. The most important observation is that the map from error configurations

to syndromes is many-to-one, i.e. many different sets of errors can lead to the same syndrome. As an example, consider the error configurations illustrated in lattices (a) and (b) of Fig. 2, both of which lead to the same syndrome. If the probability of an error on a single data qubit is low, given such a syndrome one might reasonably assume that the error in lattice (b) occurred, as one single qubit error is a much more likely event than four single qubit errors. Given this reasoning, one might then suggest to correct by applying an X flip on the data qubit in the first row and fourth column. If indeed the error in lattice (b) occurred then this would be the correct operation. However, if an unlikely event occurred and the error in lattice (a) occurred, then the combination of the original errors with the correction would effectively implement a logical X_L operation. As a result, even though the post-correction state is back in the code space, it will be in a different state to the original state and the information we were trying to preserve would have been corrupted. From this simple example one can see that most often solving the decoding problem as stated above involves deciding, given an inherently ambiguous syndrome and (possibly imperfect) knowledge of the underlying error model, which error configuration was most likely to have occurred.

As previously mentioned, in addition to the inherent difficulty resulting from syndrome ambiguity, in experimental settings the process of extracting the syndrome is also subject to noise, and as such the syndrome one receives may also contain errors. In practice, each stabilizer is associated with an ancilla qubit, and the syndrome value for that particular stabilizer is obtained by first executing a small quantum circuit which entangles the ancilla with each of the data qubits on which the corresponding stabilizer is supported, before extracting the syndrome value via a measurement of the ancilla qubit. In order to fully account for errors during the process of syndrome extraction one should therefore model this entire circuit, in which errors can occur on both the data qubits and ancilla qubits at each time step, and importantly, errors on the ancilla qubits can propagate onto the data qubits via the required entangling gates. However, the essential aspect of the additional difficulty from faulty syndrome measurements can be more simply modelled by imagining each time step as consisting of two distinct error processes, as illustrated in Fig. 2. In the first error process, an error occurs on each data qubit with some probability. One then imagines extracting the perfect syndrome before a second error process occurs, in which with a given probability an error occurs on each stabilizer measurement outcome.

RS: TO DO: syndrome volume instead of single syndrome in faulty measurements case, and then, differentiate single-shot decoding from multi-cycle decoding! in the context of fault tolerant quantum computation we always imagine that there is a decoded gate or measurement process still to come, and the idea is not necessarily to always put the qubit back into the ground state, but rather to avoid the accumulation of errors for as long as possible, such that the decoding process involved in the next circuit element may be successful. As a proxy for whether or not this would work we can imagine a decoder which has access to the true syndrome, and is trying to solve the single shot decoding problem - we say that the logical qubit is "alive" if at any moment in time such a static referee decoder could decode it, and we say that the qubit is dead if at any moment errors have accumulated to the point where a referee decoder would not be successful in single shot decoding with perfect syndrome measurements. voila.

IV. REINFORCEMENT LEARNING AND Q-FUNCTIONS

V. DECODING AS A REINFORCEMENT LEARNING PROBLEM

VI. RESULTS

VII. CONCLUSION

ACKNOWLEDGMENTS

The authors gratefully acknowledge helpful and insightful discussions with Daniel Litinski, Nicolas Delfosse, Paul Baireuther, and Hendrik Poulsen Nautrup. Additionally, the authors would like to thank Jörg Behrmann for incredible technical support, without which this work would not have been possible. RS acknowledges the financial support of the Alexander von Humboldt foundation. MSK is supported by the DFG (CRC183, project B02). EvN is supported by ... JE is supported by DFG (CRC 183, EI 519/14-1, and EI 519/7-1), the ERC (TAQ), the Templeton Foundation, and the BMBF (Q.com).

[1] B. M. Terhal, "Quantum error correction for quantum memories," *Rev. Mod. Phys.* **87**, 307 (2015).

- [2] Earl T Campbell, Barbara M Terhal, and Christophe Vuillot, “Roads towards fault-tolerant universal quantum computation,” *Nature* **549**, 172 (2017).
- [3] Alexei Yu. Kitaev, “Fault-tolerant quantum computation by anyons,” *Ann. Phys.* **303**, 2 (2003).
- [4] Eric Dennis, Alexei Kitaev, Andrew Landahl, and John Preskill, “Topological quantum memory,” *J. Math. Phys.* **43**, 4452 (2002).
- [5] J. Preskill, “Topological quantum computation,” (2017), (Chapter 9 of Lecture Notes on Quantum Computation).
- [6] Chetan Nayak, Steven H. Simon, Ady Stern, Michael Freedman, and Sankar Das Sarma, “Non-Abelian anyons and topological quantum computation,” *Rev. Mod. Phys.* **80**, 1083 (2008).
- [7] Jiannis K Pachos, *Introduction to topological quantum computation* (Cambridge University Press, 2012).
- [8] B. J. Brown, D. Loss, J. K. Pachos, C. N. Self, and J. R. Wootton, “Quantum memories at finite temperature,” *Rev. Mod. Phys.* **88**, 045005 (2016).
- [9] M. D. Reed, L. DiCarlo, S. E. Nigg, L. Sun, L. Frunzio, S. M. Girvin, and R. J. Schoelkopf, “Realization of three-qubit quantum error correction with superconducting circuits,” *Nature* **482**, 382 (2012).
- [10] R. Barends, J. Kelly, A. Megrant, A. Veitia, D. Sank, E. Jeffry, T. C. White, J. Mutus, A. G. Fowler, B. Campbell, Y. Chen, Z. Chen, B. Chiaro, A. Dunsworth, C. Neill, P. O’Malley, P. Roushan, A. Vainsencher, J. Wenner, A. N. Korotkov, A. N. Cleland, and J. M. Martinis, “Superconducting quantum circuits at the surface code threshold for fault tolerance,” *Nature* **508**, 500 (2014).
- [11] D. Nigg, M. Müller, E. A. Martinez, P. Schindler, M. Hennrich, T. Monz, M. A. Martin-Delgado, and R. Blatt, “Quantum computations on a topologically encoded qubit,” *Science* **345**, 302–305 (2014).
- [12] A. D. Córcoles, Easwar Magesan, Srikanth J. Srinivasan, Andrew W. Cross, M. Steffen, Jay M. Gambetta, and Jerry M. Chow, “Demonstration of a quantum error detection code using a square lattice of four superconducting qubits,” *Nat. Comms.* **6**, 6979 (2015).
- [13] S. M. Albrecht, A. P. Higginbotham, M. Madsen, F. Kuemmeth, T. S. Jespersen, J. Nygård, P. Krogstrup, and C. M. Marcus, “Exponential protection of zero modes in Majorana islands,” *Nature* **531**, 206 (2016).
- [14] Maika Takita, A. D. Córcoles, Easwar Magesan, Baleeg Abdo, Markus Brink, Andrew W. Cross, Jerry M. Chow, and Jay M. Gambetta, “Demonstration of weight-four parity measurements in the surface code architecture,” *Phys. Rev. Lett.* **117**, 210505 (2016).
- [15] Norbert M. Linke, Mauricio Gutierrez, Kevin A. Landsman, Caroline Figgatt, Shantanu Debnath, Kenneth R. Brown, and Christopher Monroe, “Fault-tolerant quantum error detection,” *Sci. Adv.* **3**, e1701074 (2017).
- [16] Austin G Fowler, “Minimum weight perfect matching of fault-tolerant topological quantum error correction in average $o(1)$ parallel time,” *arXiv preprint arXiv:1307.1740* (2013).
- [17] Guillaume Duclos-Cianci and David Poulin, “Fast decoders for topological quantum codes,” *Physical review letters* **104**, 050504 (2010).
- [18] Michael Herold, Earl T Campbell, Jens Eisert, and Michael J Kastoryano, “Cellular-automaton decoders for topological quantum memories,” *npj Quantum Information* **1**, 15010 (2015).
- [19] Giacomo Torlai and Roger G Melko, “Neural decoder for topological codes,” *Physical review letters* **119**, 030501 (2017).
- [20] Savvas Varsamopoulos, Ben Criger, and Koen Bertels, “Decoding small surface codes with feedforward neural networks,” *Quantum Science and Technology* **3**, 015004 (2017).
- [21] Stefan Krastanov and Liang Jiang, “Deep neural network probabilistic decoder for stabilizer codes,” *Scientific reports* **7**, 11003 (2017).
- [22] Nikolas P Breuckmann and Xiaotong Ni, “Scalable neural network decoders for higher dimensional quantum codes,” *Quantum* **2**, 68 (2018).
- [23] Paul Baireuther, Thomas E O’Brien, Brian Tarasinski, and Carlo WJ Beenakker, “Machine-learning-assisted correction of correlated qubit errors in a topological code,” *Quantum* **2**, 48 (2018).
- [24] P Baireuther, MD Caio, B Criger, CWJ Beenakker, and TE O’Brien, “Neural network decoder for topological color codes with circuit level noise,” *arXiv preprint arXiv:1804.02926* (2018).
- [25] Xiaotong Ni, “Neural network decoders for large-distance 2d toric codes,” *arXiv preprint arXiv:1809.06640* (2018).
- [26] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller, “Playing atari with deep reinforcement learning,” *arXiv preprint arXiv:1312.5602* (2013).
- [27] David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharmashan Kumaran, Thore Graepel, *et al.*, “Mastering chess and shogi by self-play with a general reinforcement learning algorithm,” *arXiv preprint arXiv:1712.01815* (2017).
- [28] David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, *et al.*, “Mastering the game of go without human knowledge,” *Nature* **550**, 354 (2017).
- [29] Daniel Gottesman, *Stabilizer Codes and Quantum Error Correction*, *Ph.D. thesis*, California Institute of Technology (1997).