```python
# server.py  X

1    # Group B api server @jalex-yestera
2    import os, sys
3    from flask import Flask, render_template, redirect, request, jsonify
4    import json
5
6    # ----------------------
7    # $$$$$$$ FLASK $$$$$$$$
8    # ----------------------
9    app = Flask(__name__)  # init
10   @app.route("/")  # Default path
11 ∨ def default():
12       # Redirect
13       return '''<h1> Api del grupo B</h1> <p> Añadir get_token?id= para conseguir el token, get_json?id= para el json</p>'''
14
15   @app.route("/get_token", methods = ['GET'])
16 ∨ def get_token():
17       clave = None
18       yeison = {"token": "B23866390994081818446940"}
19 ∨     if 'id' in request.args:
20           clave = str(request.args['id'])
21 ∨     if clave == 'B145':
22           return yeison['token']
23 ∨     else:
24           return "Error al introducir la clave. Prueba con B145"
25
26   @app.route("/get_json", methods = ['GET'])
27 ∨ def get_json():
28       token = None
29       # Get the settings fullpath
30       settings_file = os.path.dirname(__file__) + "\\d_averages.json"
31       # Load json from file
32 ∨     with open(settings_file, "r") as json_file_readed:
33           jason = json.load(json_file_readed)
34 ∨     if 'id' in request.args:
35           token = str(request.args['id'])
36 ∨     if token == 'B23866390994081818446940':
37           return jason
38
39

41   # ----------------------
42   # $$$$$$$ MAIN $$$$$$$$
43   # ----------------------
44
45 ∨ def main():
46
47       print("STARTING PROCESS")
48       print(os.path.dirname(__file__))
49
50       # Get the settings fullpath
51       settings_file = os.path.dirname(__file__) + "\\settings.json"
52       # Load json from file
53 ∨     with open(settings_file, "r") as json_file_readed:
54           json_readed = json.load(json_file_readed)
55
56       # Load variables from jsons
57       SERVER_RUNNING = json_readed["server_running"]
58
59 ∨     if SERVER_RUNNING:
60           DEBUG = json_readed["debug"]
61           HOST = json_readed["host"]
62           PORT_NUM = json_readed["port"]
63           app.run(debug=DEBUG, host=HOST, port=PORT_NUM)
64 ∨     else:
65 ∨         print("Server settings.json doesn't allow to start server. " +
66               "Please, allow it to run it.")
67
68 ∨ if __name__ == "__main__":
69       main()
70
```