MAC 3052 HW3

MP3 Music Library

A page named `music.html` that contains a display of all the MP3s in the songs folder and `viewer.css`, the styles for the page, are provided.

However, the page is not very flexible, because it must be manually edited it every time songs are added to the collection. You are to turn this page into a dynamic PHP page in a file named `music.php` that will list the MP3s and will always display the songs currently on the computer.

1. The first task is to convert `music.html` into a PHP page that displays MP3s. Examine the files in the `songs/` folder and display each `.mp3` file in the format currently shown in the `music.html` page. Each one becomes a list item (`li`) with a `class` of `mp3item`. Each song's title should be a link to download that song file from the computer.

2. The music collection also includes *playlists*, which are text files containing lists of his favorite songs. For this exercise, modify your PHP code to display any playlist files, which are `.txt` files in the `songs/` directory. They should display very similarly to the `.mp3` files, except they use a `class` of `playlistitem` so that they have a different icon. For now, a playlist's link is the same as an MP3's link: It downloads the file.

3. Next you should modify the behavior of your page so that it can optionally display just the songs that are listed in a certain playlist.

A playlist is just a text file, where each line of the file contains the file name of an MP3 that is part of the playlist. For this exercise, change your PHP code so that if your page is given a *query parameter* of `playlist`, it will read the playlist text file with the given name and display its songs only. For example, if your page is displayed with the following URL: **music.php?playlist=mypicks.txt** You may assume that any songs contained in a playlist actually do exist on the computer. If no query parameter is given, your page should use its previous behavior, displaying all `.mp3` and `.txt` files. You can test whether a particular parameter has been passed by calling PHP's **`isset`** function.

4. Add some information to the end of each song shown on the page. Display the song's size in the appropriate unit. If the song is 0 to 1023 bytes in size, display it as bytes. If it is 1024 to 1048575 bytes in size, display it as kilobytes (multiples of 1024 bytes). If it is 1048576 or more bytes, display it as megabytes (multiples of 1048576 bytes). If displaying kb or mb, you should round your value to the nearest hundredth. You may want to review the documentation for the **`round`** function.

- **Shuffle:** Add another optional query parameter to your page named `shuffle`. When `shuffle` is set to `on`, you should display the songs in a random ordering rather than in their default sorted order. For example, if the page were requested in the following way: **music.php?shuffle=on**. Then the songs would display in a random order. You may want to review the array functions from the book or slides to see how to rearrange an array's elements.