

Pseudocode Notation

Some stimulus material contains code segments written in pseudocode. The notation used in the pseudocode is described below

Explanation	Notation
Assignment operator	<code>←</code>
Arithmetic operators	<code>+</code> <code>-</code> <code>/</code> <code>*</code> <code>^</code> <code>%</code> Note that <code>/</code> indicates floating point division unless stated otherwise.
Relational operators	<code>==</code> <code><</code> <code>></code> <code>≤</code> <code>≥</code> <code>≠</code>
Logical operators	and or not
String concatenation operator	<code>+</code>
Boolean values	true false
Null	null
Comments	<code>// this is a single-line comment</code>
Placeholder for missing code	For example, <code>/* missing code */</code> <code>/* missing condition */</code>
Print A comment is used where necessary to indicate if a line feed or blank is appended to the argument.	print arg
Data types	boolean char double float int int[] int[][] short String

Explanation	Notation
Array initialization and reference	<pre> int[] a ← {1, 2, 3} int b[0..2] ← {1, 2, 3} int[][] c a[0]</pre>
Conditional statements: Indentation and end if statements are significant. Example: <pre> if (x > 10) print "big number" else print "small number" end if</pre>	<pre> if (condition) block of statements end if if (condition) block of statements else another block of statements end if</pre>
Iterative statements: Indentation and end statements are significant	<pre> for (initialization; condition; increment) block of statements end for while (condition) block of statements end while do block of statements while (condition) repeat block of statements until (condition)</pre>

Explanation	Notation
Procedures: Indentation and end statements are significant. The return type is indicated in the procedure header and is based on the value returned by the procedure or is void if the procedure does not return a value.	<pre> int procedureName (arg1, arg2, ...) block of statements return value end procedureName void procedureName (arg1, arg2, ...) block of statements end procedureName </pre>
Classes	<pre> class className variable declarations procedures end class className </pre>
Object-oriented keywords	<pre> extends new public private </pre>