

SRM INSTITUTE OF SCIENCE AND TECHNOLOGY
FACULTY OF SCIENCE AND HUMANITIES
DEPARTMENT OF COMPUTER APPLICATIONS



PRACTICAL RECORD NOTE

STUDENT NAME :

REGISTER NUMBER :

CLASS : III BCA SECTION:

YEAR & : III YEAR & V SEMESTER
SEMESTER

SUBJECT CODE : UCA23G03J

SUBJECT TITLE : BASICS OF ANDROID

OCTOBER 2025



SRM INSTITUTE OF SCIENCE AND TECHNOLOGY
FACULTY OF SCIENCE AND HUMANITIES
DEPARTMENT OF COMPUTER APPLICATIONS

SRM Nagar, Kattankulathur – 603 203

CERTIFICATE

Certified to be the bonafide record of practical work done
by _____
Register No. _____ of _____ Degree
course for UCA23G03J - BASICS OF ANDROID in the computer lab
in SRM Institute of Science and Technology during the academic year
2025 – 2026

Staff In-charge

Head of the Department

Submitted for Semester Practical Examination held on _____

Internal Examiner

External Examiner

INDEX

S.NO	TITLE OF THE EXPERIMENT	Page.No	Staff sign
1.	Program to display your name		
2.	Program to change the screen orientation		
3.	Program to display a toggle button		
4.	Program to create radio group and radio button		
5.	Program to display progress bar		
6.	Program to create auto complete text view		
7.	Program to create picker view (calendar view)		
8.	Program to create list view		
9.	Program to display spinner view		
10.	Program to display web page using web view		
11.	Program to display image using image view		
12.	Program to display digital clock		
13.	Program to create android services (play music)		
14.	Program to handle run time error using exception handling		
15.	Program to connect SQLite to android		

Source Code:

Activity_main.XML

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout
    xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:gravity="center"
    android:background="#FFFFFF">

    <TextView
        android:id="@+id/textView"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Your Name"
        android:textSize="40sp"
        android:textColor="#000000"
        android:layout_gravity="center" />
</LinearLayout>
```

Mainactivity.java

```
package com.example.name1;

import android.os.Bundle;
import androidx.appcompat.app.AppCompatActivity;

public class MainActivity extends AppCompatActivity {
    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
    }
}
```

Output:



RESULT:

Thus, the Android Application to display a name using TextView is developed and executed successfully.

Source Code:

Activitymain.XML

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout
    xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:gravity="center"
    android:background="#FFFFFF">

<TextView
    android:id="@+id/textView"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:text="Your Name"
    android:textSize="40sp"
    android:textColor="#000000"
    android:layout_gravity="center" />
</LinearLayout>
```


Mainactivity.java

```
package com.example.name1;
import android.content.pm.ActivityInfo;

import android.os.Bundle;
import androidx.appcompat.app.AppCompatActivity;

public class MainActivity extends AppCompatActivity {
    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setRequestedOrientation(ActivityInfo.SCREEN_ORIENTATION_LANDSCAPE);
        setContentView(R.layout.activity_main);    }
}
```

Output:



RESULT:

Thus, the Android Application to change the screen orientation is developed and executed successfully.

Source Code:

Activitimain.XML

```
<?xml version="1.0" encoding="utf-8"?>
<androidx.coordinatorlayout.widget.CoordinatorLayout
xmlns:android="http://schemas.android.com/apk/res/android"
    xmlns:app="http://schemas.android.com/apk/res-auto"
    xmlns:tools="http://schemas.android.com/tools"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:fitsSystemWindows="true"
    tools:context=".MainActivity">

    <androidx.constraintlayout.widget.ConstraintLayout
        android:id="@+id/constraintLayout"
        android:layout_width="match_parent"
        android:layout_height="match_parent">

        <ToggleButton
            android:id="@+id/toggleButton"
            android:layout_width="wrap_content"
            android:layout_height="wrap_content"
            android:layout_marginTop="420dp"
            android:onClick="onToggleClick"
            android:text="ToggleButton"
            app:layout_constraintEnd_toEndOf="parent"
            app:layout_constraintHorizontal_bias="0.458"
            app:layout_constraintLeft_toLeftOf="@id/textView"
            app:layout_constraintStart_toStartOf="parent"
            app:layout_constraintTop_toTopOf="parent" />

        <TextView
            android:id="@+id/textView"
            android:layout_width="232dp"
```



```

        android:layout_height="49dp"
        android:layout_marginEnd="88dp"
        android:gravity="center"
        android:text="TextView"
        app:layout_anchor="@+id/constraintLayout"
        app:layout_anchorGravity="center"
        app:layout_constraintBottom_toTopOf="@id/toggleButton"
        app:layout_constraintEnd_toEndOf="parent"
        app:layout_constraintTop_toTopOf="parent"
        app:layout_constraintVertical_bias="0.574" />
    </androidx.constraintlayout.widget.ConstraintLayout>
</androidx.coordinatorlayout.widget.CoordinatorLayout>

```

Mainactivity.java

```

package com.example.toggle1;

import android.os.Bundle;
import android.view.View;
import android.widget.*;
import androidx.appcompat.app.AppCompatActivity;

public class MainActivity extends AppCompatActivity {

    @Override
    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);

        // Initialize

        ToggleButton togglebutton = findViewById(R.id.toggleButton);
        TextView textview = findViewById(R.id.textView);
        togglebutton.setOnClickListener(new View.OnClickListener() {
            public void onClick(View view) {

```

```
if (togglebutton.isChecked()) {  
    textview.setText("Toggle is ON");  
} else {  
    textview.setText("Toggle is OFF");  
}  
};}}
```

Output:



RESULT:

Thus, the Android Application to display a toggle button and change text based on ON/OFF state is developed and executed successfully.

Source Code:

activitymai.XML

```
<?xml version="1.0" encoding="utf-8"?>

<LinearLayout

xmlns:android="http://schemas.android.com/apk/res/android"

xmlns:tools="http://schemas.android.com/tools"

android:id="@+id/idRLContainer"

android:layout_width="match_parent"

android:layout_height="match_parent"

android:orientation="vertical"

android:gravity="center"

tools:context=".MainActivity">

<!--headline text-->

<TextView

android:id="@+id/idTVHeading"

android:layout_width="wrap_content"

android:layout_height="wrap_content"

android:text="Radio Button in Android"

android:textColor="@color/black"

android:textSize="20sp"

android:textStyle="bold" />

<!--status text-->

<TextView
```

```
android:id="@+id/idTVStatus"
android:layout_width="wrap_content"
android:layout_height="wrap_content"
android:layout_margin="32dp"
android:text="Status"
android:textColor="@color/black"
android:textSize="20sp"
android:textStyle="bold" />
<!--radio group-->
<RadioGroup
android:id="@+id/idRadioGroup"
android:layout_width="wrap_content"
android:layout_height="wrap_content"
android:gravity="center">
<!--radio buttons-->
<RadioButton
android:id="@+id/idBtnJavaRadio"
android:layout_width="wrap_content"
android:layout_height="wrap_content"
android:text="Java"
android:textSize="20sp" />
<RadioButton
android:id="@+id/idBtnKotlinRadio"
android:layout_width="wrap_content"
android:layout_height="wrap_content"
android:text="Kotlin"
```

```
android:textSize="20sp" />
```

```
</RadioGroup>
```

```
</LinearLayout>
```

Mainactivity.java

```
package com.example.radio1;
```

```
import android.os.Bundle;
```

```
import android.widget.*;
```

```
import androidx.appcompat.app.AppCompatActivity;
```

```
public class MainActivity extends AppCompatActivity {
```

```
    @Override
```

```
    protected void onCreate(Bundle savedInstanceState) {
```

```
        super.onCreate(savedInstanceState);
```

```
        setContentView(R.layout.activity_main);
```

```
        RadioGroup radioGroup = findViewById(R.id.rg);
```

```
        TextView textView = findViewById(R.id.tv1);
```

```
        // Set listener on RadioGroup
```

```
        radioGroup.setOnCheckedChangeListener(new
```

```
        RadioGroup.OnCheckedChangeListener() {
```

```
            @Override
```

```
            public void onCheckedChanged(RadioGroup group, int checkedId) {
```


```
                RadioButton radioButton = group.findViewById(checkedId);
```

```
                if (radioButton != null) {
```

```
                    textView.setText(radioButton.getText());
```

```
                } } }); }
```

Output:



RESULT:

Thus, the Android Application to create a radio group and display the selected option is developed and executed successfully.

Source Code:

Activitymain.XML

```
<androidx.constraintlayout.widget.ConstraintLayout
xmlns:android="http://schemas.android.com/apk/res/android"
xmlns:app="http://schemas.android.com/apk/res-auto"
xmlns:tools="http://schemas.android.com/tools"
android:layout_width="match_parent"
android:layout_height="match_parent"
android:background="@color/white"
tools:context=".MainActivity">
<TextView
android:id="@+id/textView"
android:layout_width="match_parent"
android:layout_height="wrap_content"
android:layout_marginBottom="32dp"
android:padding="10dp"
android:text="Progress Bar in Android"
android:textAlignment="center"
android:textColor="@color/black"
android:textSize="20sp"
android:textStyle="bold"
app:layout_constraintBottom_toTopOf="@+id/progressBar"
app:layout_constraintEnd_toEndOf="parent"
```

```
app:layout_constraintStart_toStartOf="parent"
app:layout_constraintTop_toTopOf="parent"
app:layout_constraintVertical_chainStyle="packed" />
<!--on below line we are creating a progress bar-->
<ProgressBar
    android:id="@+id/progressBar"
    android:layout_width="wrap_content"
    android:layout_height="wrap_content"
    android:visibility="gone"
    app:layout_constraintBottom_toTopOf="@+id/button"
    app:layout_constraintEnd_toEndOf="parent"
    app:layout_constraintStart_toStartOf="parent"
    app:layout_constraintTop_toBottomOf="@+id/textView" />
<!--on below line we are creating a button-->
<Button
    android:id="@+id/button"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:layout_marginTop="32dp"
    android:text="Show Progress Bar"
    app:layout_constraintBottom_toBottomOf="parent"
    app:layout_constraintEnd_toEndOf="parent"
    app:layout_constraintStart_toStartOf="parent"
    app:layout_constraintTop_toBottomOf="@+id/progressBar" />
</androidx.constraintlayout.widget.ConstraintLayout>
```

Mainactivity.java


```
package com.example.progress;

import android.os.Bundle;
import android.view.View;
import android.widget.*;

import androidx.appcompat.app.AppCompatActivity;

public class MainActivity extends AppCompatActivity {

    private boolean isProgressVisible = false;

    @Override

    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);

        // Initializing the variables
        Button Btn = findViewById(R.id.button);
        ProgressBar PB = findViewById(R.id.progressBar);

        // Click listener for the button
        Btn.setOnClickListener(new View.OnClickListener() {

            @Override

            public void onClick(View v) {

                if (isProgressVisible) {

                    // Hide progress bar and update button text
                    Btn.setText("Show Progress Bar");
                    PB.setVisibility(View.GONE);

                    isProgressVisible = false;
                }

                else {

                    // Show progress bar and update button text
```

```
Btn.setText("Hide Progress Bar");  
PB.setVisibility(View.VISIBLE);  
isProgressVisible = true;} } };
```

Output:



RESULT:

Thus, the Android Application to display and control a progress bar using a button is developed and executed successfully.

Source Code:

Activitymain.XML

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:orientation="vertical"
    android:padding="20dp">
    <AutoCompleteTextView
        android:id="@+id/txtcountries"
        android:layout_width="match_parent"
        android:layout_height="wrap_content"
        android:hint="Enter Country" />
</LinearLayout>
```

Mainactivity.java


```
package com.example.myapplication;

import android.app.Activity;
import android.os.Bundle;
import android.widget.ArrayAdapter;
import android.widget.AutoCompleteTextView;

public class MainActivity extends Activity {
```

```
String[] countries = {  
    "India", "Australia", "West Indies", "Indonesia", "Indiana",  
    "South Africa", "England", "Bangladesh", "Sri Lanka", "Singapore"  
};  
  
@Override  
protected void onCreate(Bundle savedInstanceState) {  
    super.onCreate(savedInstanceState);  
    setContentView(R.layout.activity_main);  
    AutoCompleteTextView autoTextView = findViewById(R.id.txtcountries);  
    ArrayAdapter<String> adapter = new ArrayAdapter<>(this,  
        android.R.layout.simple_dropdown_item_1line, countries);  
    autoTextView.setThreshold(1); // Start suggesting after 1 character  
    autoTextView.setAdapter(adapter);  
}  
}
```

Output:



RESULT:

Thus, the Android Application to create an autoComplete TextView with country suggestions is developed and executed successfully.

Source Code:

activitymain.XML

```
<androidx.constraintlayout.widget.ConstraintLayout
xmlns:android="http://schemas.android.com/apk/res/android"
xmlns:app="http://schemas.android.com/apk/res-auto"
xmlns:tools="http://schemas.android.com/tools"
android:id="@+id/main"
android:layout_width="match_parent"
android:layout_height="match_parent"
android:background="@color/white"
tools:context=".MainActivity">
<DatePicker
android:id="@+id/datePicker"
android:layout_width="wrap_content"
android:layout_height="wrap_content"
android:datePickerMode="calendar"
app:layout_constraintBottom_toBottomOf="parent"
app:layout_constraintEnd_toEndOf="parent"
app:layout_constraintStart_toStartOf="parent"
app:layout_constraintTop_toTopOf="parent" />
</androidx.constraintlayout.widget.ConstraintLayout>
```

Mainactivity.java

```
package org.example.demo;
```

```
import android.os.Bundle;

import android.widget.DatePicker;

import android.widget.Toast;

import androidx.appcompat.app.AppCompatActivity;

import java.util.Calendar;

public class MainActivity extends AppCompatActivity {

    @Override

    protected void onCreate(Bundle savedInstanceState) {

        super.onCreate(savedInstanceState);

        setContentView(R.layout.activity_main);

        // Initialize DatePicker from layout

        DatePicker datePicker = findViewById(R.id.datePicker);

        // Get today's date using Calendar instance

        Calendar today = Calendar.getInstance();

        // Initialize DatePicker with the current date

        datePicker.init(today.get(Calendar.YEAR), today.get(Calendar.MONTH),

            today.get(Calendar.DAY_OF_MONTH), new DatePicker.OnDateChangedListener()

        {

            @Override

            public void onDateChanged(DatePicker view, int year, int month, int day) {

                // Display selected date in Toast message

                String msg = "You Selected: " + day + "/" + (month + 1) + "/" + year;

                Toast.makeText(MainActivity.this, msg, Toast.LENGTH_SHORT).show();

            }

        });

    }

}
```

Output:



RESULT:

Thus, the Android Application to create a date picker and show the selected date in a toast is developed and executed successfully.

Source Code:

activitymain.XML

```
<?xml version="1.0" encoding="utf-8"?>

<LinearLayout

xmlns:android="http://schemas.android.com/apk/res/android"
xmlns:app="http://schemas.android.com/apk/res-auto"
xmlns:tools="http://schemas.android.com/tools"
android:layout_width="match_parent"
android:layout_height="match_parent"
tools:context=".MainActivity">

<ListView
android:id="@+id/list"
android:layout_width="match_parent"
android:layout_height="match_parent"/>

</LinearLayout>
```

Mainactivity.java


```
import android.os.Bundle;
import android.widget.ArrayAdapter;
import android.widget.ListView;
import androidx.appcompat.app.AppCompatActivity;

public class MainActivity extends AppCompatActivity {

String tutorials[] = { "Algorithms",
"Data Structures",
"Languages",
"Interview Corner",
```

```
"GATE",  
"ISRO CS",  
"CS Subjects",  
"Web Technologies" };  
  
@Override  
protected void onCreate(Bundle savedInstanceState){  
    super.onCreate(savedInstanceState);  
    setContentView(R.layout.activity_main);  
    ListView l = findViewById(R.id.list);  
    ArrayAdapter<String> arr = new ArrayAdapter<String>(this,  
        android.R.layout.simple_spinner_dropdown_item, tutorials);  
    l.setAdapter(arr);}}
```

Output:



RESULT:

Thus, the Android Application to display a list view of items is developed and executed successfully.

Source Code:

activitymain.XML

```
<?xml version="1.0" encoding="utf-8"?>

<LinearLayout

xmlns:android="http://schemas.android.com/apk/res/android"

android:orientation="vertical"

android:padding="16dp"

android:layout_width="match_parent"

android:layout_height="match_parent">

<Spinner

android:id="@+id/spinner"

android:layout_width="match_parent"

android:layout_height="wrap_content"/>

</LinearLayout>
```

Mainactivity.java

```
package com.example.spinner1;

import android.app.Activity;

import android.os.Bundle;

import android.widget.ArrayAdapter;

import android.widget.Spinner;


public class MainActivity extends Activity {

    @Override

    protected void onCreate(Bundle savedInstanceState) {
```

```
super.onCreate(savedInstanceState);  
setContentView(R.layout.activity_main);  
Spinner spinner = findViewById(R.id.spinner);  
String[] items = {"India", "USA", "Japan"};  
ArrayAdapter<String> adapter = new ArrayAdapter<>(this,  
    android.R.layout.simple_spinner_dropdown_item, items);  
spinner.setAdapter(adapter);  
}}
```

Output:



RESULT:

Thus, the Android Application to display a spinner with a dropdown list is developed and executed successfully.

Source Code:

activitymain.XML

```
<?xml version="1.0" encoding="utf-8"?>

<LinearLayout

xmlns:android="http://schemas.android.com/apk/res/android"

android:orientation="vertical"

android:layout_width="match_parent"

android:layout_height="match_parent">

<WebView

android:id="@+id/webview"

android:layout_width="match_parent"

android:layout_height="match_parent"/>

</LinearLayout>
```

Mainactivity.java

```
package com.example.webview1;

import android.os.Bundle;

import android.webkit.WebView;

import android.webkit.WebViewClient;

import androidx.appcompat.app.AppCompatActivity;

public class MainActivity extends AppCompatActivity {

    @Override

    protected void onCreate(Bundle savedInstanceState) {

        super.onCreate(savedInstanceState);

        setContentView(R.layout.activity_main);
```

```

WebView webView = findViewById(R.id.webview);

webView.setWebViewClient(new WebViewClient()); //page is loaded inside app's WebView

webView.getSettings().setJavaScriptEnabled(true); //Enables JavaScript for interactive websites.


webView.getSettings().setDomStorageEnabled(true); //sites can store data locally.

webView.loadUrl("https://wikipedia.org");

}}

```

Output:



RESULT:

Thus, the Android Application to display a webpage using WebView is developed and executed successfully.

Source Code:

activitymain.xml:

```
<?xml version="1.0" encoding="utf-8"?>

<androidx.coordinatorlayout.widget.CoordinatorLayout
xmlns:android="http://schemas.android.com/apk/res/android"
xmlns:app="http://schemas.android.com/apk/res-auto"
xmlns:tools="http://schemas.android.com/tools"
android:layout_width="match_parent"
android:layout_height="match_parent"
android:fitsSystemWindows="true"
tools:context=".MainActivity">

<androidx.constraintlayout.widget.ConstraintLayout
android:layout_width="match_parent"
android:layout_height="match_parent">

<ImageView
android:id="@+id/imageView"
android:layout_width="wrap_content"
android:layout_height="wrap_content"
android:foregroundGravity="center"
app:srcCompat="@drawable/book_publication"
tools:layout_editor_absoluteX="100dp"
tools:layout_editor_absoluteY="321dp" />


</androidx.constraintlayout.widget.ConstraintLayout>

</androidx.coordinatorlayout.widget.CoordinatorLayout>
```

Mainactivity.java

```
package com.example.image1;  
  
import androidx.appcompat.app.AppCompatActivity;  
  
import android.os.Bundle;  
  
public class MainActivity extends AppCompatActivity {  
  
    @Override  
  
    protected void onCreate(Bundle savedInstanceState) {  
  
        super.onCreate(savedInstanceState);  
  
        setContentView(R.layout.activity_main);}}
```

Output:



RESULT:

Thus, the Android Application to display an image using ImageView is developed and executed successfully.

Source Code:

activitymain.XML

```
<?xml version="1.0" encoding="utf-8"?>

<androidx.coordinatorlayout.widget.CoordinatorLayout
xmlns:android="http://schemas.android.com/apk/res/android"
xmlns:app="http://schemas.android.com/apk/res-auto"
xmlns:tools="http://schemas.android.com/tools"
android:layout_width="match_parent"
android:layout_height="match_parent"
android:fitsSystemWindows="true"
tools:context=".MainActivity">

<androidx.constraintlayout.widget.ConstraintLayout
android:layout_width="match_parent"
android:layout_height="match_parent">

<TextClock
android:id="@+id/textClock"
android:layout_width="182dp"
android:layout_height="58dp"
android:foregroundGravity="center"
android:gravity="center"
android:textSize="24sp"
app:layout_constraintBottom_toBottomOf="parent"
app:layout_constraintEnd_toEndOf="parent"
app:layout_constraintHorizontal_bias="0.497"
app:layout_constraintStart_toStartOf="parent"
```

```
app:layout_constraintTop_toTopOf="parent"
app:layout_constraintVertical_bias="0.644" />
</androidx.constraintlayout.widget.ConstraintLayout>
</androidx.coordinatorlayout.widget.CoordinatorLayout>
```

Mainactivity.java


```
package com.example.clock1;

import androidx.appcompat.app.AppCompatActivity;
import android.os.Bundle; public class MainActivity extends AppCompatActivity {

    @Override

    protected void onCreate(Bundle savedInstanceState){
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);}}
```

Output:



RESULT:

Thus, the Android Application to display the current time using Digital Clock is developed and executed successfully.

Source Code:

activitymain.XML

```
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:gravity="center"
    android:orientation="vertical">
    <Button
        android:id="@+id/startBtn"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Start Music" />
    <Button
        android:id="@+id/stopBtn"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Stop Music" />
</LinearLayout>
```

Mainactivity.java

```
package com.example.service1;

import android.app.Service;
import android.content.Intent;
import android.media.MediaPlayer;
```

```
import android.os.IBinder;

public class MusicService extends Service {

    private MediaPlayer player;

    @Override

    public void onCreate() {

        super.onCreate();

        // put your music file inside res/raw/music.mp3

        player = MediaPlayer.create(this, R.raw.audio);

        player.setLooping(true); // play in loop

    }

    @Override

    public int onStartCommand(Intent intent, int flags, int startId) {

        player.start();

        return START_STICKY;

    }

    @Override

    public void onDestroy() {

        super.onDestroy();

        if (player != null) {

            player.stop();

            player.release();

        }

    }

    @Override

    public IBinder onBind(Intent intent) {

        return null; }}


```

MusicService.java

```
package com.example.service1;

import android.app.Service;
import android.content.Intent;
import android.media.MediaPlayer;
import android.os.IBinder;

public class MusicService extends Service {

    private MediaPlayer player;

    @Override

    public void onCreate() {

        super.onCreate();

        player = MediaPlayer.create(this, R.raw.audio);

        player.setLooping(true); // play in loop

    }

    @Override

    public int onStartCommand(Intent intent, int flags, int startId) // intent to start the service,
    additional data of start request, unique number for request

    { player.start();

        return START_STICKY; }

    @Override

    public void onDestroy() {

        super.onDestroy();

        if (player != null) {

            player.stop();

            player.release();

        } }

    @Override
```


```
public IBinder onBind(Intent intent) {  
    return null;  
}
```

Register Service in AndroidManifest.xml

Inside <application>...</application> add:

```
<service android:name=".MusicService" />
```

Output:



RESULT:

Thus, the Android Application to create a service for playing music is developed and executed successfully.

Source Code:

Mainactivity.java

```
package com.example.exception1;

import androidx.appcompat.app.AppCompatActivity;
import android.os.Bundle;
import android.widget.Button;
import android.widget.EditText;
import android.widget.TextView;

public class MainActivity extends AppCompatActivity {

    EditText inputNumber;

    Button btnDivide;


    TextView resultView;

    @Override

    protected void onCreate(Bundle savedInstanceState) {
        super.onCreate(savedInstanceState);
        setContentView(R.layout.activity_main);
        inputNumber = findViewById(R.id.inputNumber);
        btnDivide = findViewById(R.id.btnDivide);
        resultView = findViewById(R.id.resultView);
        btnDivide.setOnClickListener(v ->
        {
            try
            { // Get user input
```

```
String input = inputNumber.getText().toString();  
  
// May cause NumberFormatException if input is not a number  
  
int number = Integer.parseInt(input);  
  
// May cause ArithmeticException if number = 0  
  
int result = 100 / number;  
  
resultView.setText("Result: " + result);  
  
} catch (NumberFormatException e) {  
    resultView.setText("Error: Please enter a valid number.");  
  
    } catch (ArithmeticException e) {  
        resultView.setText("Error: Division by zero is not allowed.");  
  
    } catch (Exception e) {  
        resultView.setText("Unexpected error: " + e.getMessage());  
  
    } }); }
```


Output:



RESULT:

Thus, the Android Application to handle runtime errors using exception handling is developed and executed successfully.

Source Code:

activitymain.XML

```
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:orientation="vertical" android:padding="20dp"
    android:layout_width="match_parent" android:layout_height="match_parent">
    <EditText android:id="@+id/editId"
        android:hint="Enter ID (for update/delete)"
        android:layout_width="match_parent" android:layout_height="wrap_content"/>
    <EditText android:id="@+id/editName"
        android:hint="Enter Name"
        android:layout_width="match_parent" android:layout_height="wrap_content"/>
    <Button android:id="@+id/btnAdd"
        android:text="Add" android:layout_width="wrap_content"
        android:layout_height="wrap_content"/>
    <Button android:id="@+id/btnUpdate"
        android:text="Update" android:layout_width="wrap_content"
        android:layout_height="wrap_content"/>
    <Button android:id="@+id/btnDelete"
        android:text="Delete" android:layout_width="wrap_content"
        android:layout_height="wrap_content"/>
    <TextView android:id="@+id/txtStudents"
        android:layout_width="match_parent" android:layout_height="wrap_content"
        android:paddingTop="10dp"/>
</LinearLayout>
```

Mainactivity.java

```
package com.example.database1;

import android.content.Context;

import android.database.sqlite.SQLiteDatabase;

import android.database.sqlite.SQLiteOpenHelper;

public class database1 extends SQLiteOpenHelper {

    public database1(Context context) {

        super(context, "StudentDB", null, 1);

    }

    @Override

    public void onCreate(SQLiteDatabase db) {

        db.execSQL("CREATE TABLE students(id INTEGER PRIMARY KEY AUTOINCREMENT, name TEXT)");

    }

    @Override

    public void onUpgrade(SQLiteDatabase db, int oldV, int newV) {

        db.execSQL("DROP TABLE IF EXISTS students");

        onCreate(db);

    }

}
```

Database1.java

```
package com.example.database1;

import android.content.Context;

import android.database.sqlite.SQLiteDatabase;

import android.database.sqlite.SQLiteOpenHelper;

public class database1 extends SQLiteOpenHelper

{

    public database1(Context context) {    super(context, "StudentDB", null, 1);    }

}
```

```

@Override
public void onCreate(SQLiteDatabase db) {
    db.execSQL("CREATE TABLE students(id INTEGER PRIMARY KEY AUTOINCREMENT, name
TEXT)");
}
@Override
public void onUpgrade(SQLiteDatabase db, int oldV, int newV) {
    db.execSQL("DROP TABLE IF EXISTS students");
    onCreate(db);
}

```

Student1.java

```

package com.example.database1;

import android.content.ContentValues;
import android.content.Context;
import android.database.Cursor;
import android.database.sqlite.SQLiteDatabase;

public class student{
    database1 helper;

    public student(Context c)
    { helper = new database1 (c); }

    // CREATE

    public void addStudent(String name) {
        SQLiteDatabase db = helper.getWritableDatabase();

        ContentValues v = new ContentValues();

        v.put("name", name);

        db.insert("students", null, v);

        db.close();
    }
}

```

```
// READ
```

```
public Cursor getStudents() {  
    return helper.getReadableDatabase().rawQuery("SELECT * FROM students", null);  
}
```


```
// UPDATE
```

```
public void updateStudent(int id, String newName) {  
    SQLiteDatabase db = helper.getWritableDatabase();  
    ContentValues v = new ContentValues();  
    v.put("name", newName);  
    db.update("students", v, "id=?", new String[]{String.valueOf(id)});  
    db.close();  
}
```

```
// DELETE
```

```
public void deleteStudent(int id) {  
    SQLiteDatabase db = helper.getWritableDatabase();  
    db.delete("students", "id=?", new String[]{String.valueOf(id)});  
    db.close();  
}}
```

Output:



RESULT:

Thus, the Android Application to connect and manage data using SQLite database is developed and executed successfully.