



Care, Maintenance and Warranty

For **your** Windows and Doors

© Ali-Frame Windows & Doors™



CARE AND MAINTENANCE OF YOUR WINDOWS AND DOORS

Congratulations for purchasing one of New Zealand's most respected brands of windows and doors from a member of the Window Association of New Zealand.

Remember that a very simple regular maintenance programme is required in order to comply with warranty requirements and will aid in retaining the appeal of your windows and doors for many years to come.

After any construction, pay particular attention to ensuring that builder's debris and dirt are cleaned from the inside of all window and door sills so that drainage holes are unobstructed. This is especially applicable to doorways that have been in regular use during the construction phase. Regularly cleaning of door sills, tracks and all drain holes as part of your ongoing maintenance programme.



CLEANING YOUR WINDOWS AND DOORS

Window and door frames should be cleaned each time your windows and doors are washed in order to remove atmospheric dirt and grime. A soft brush with warm water and a mild household detergent are recommended. Rinse with fresh water.

- DO remove obvious deposits as they occur
- DO mask windows if painting. Use only methylated spirits, isopropyl or water to remove fresh paint splashes
- DO NOT use abrasive steel wool, scrapers, scouring liquids or aggressive solvents, thinners, petrol, etc. These will all damage the windows and doors and the surface finish
- DO NOT expose your joinery to excessive heat, heaters or hot air guns as these may damage the surface finish of the joinery.

Cleaning once every three months should be sufficient, however, in coastal or industrial environments more frequent washing will be required. The frequency of washing in these harsh environments should be determined by the degree of salt and/or other contaminant build up on the windows and doors, but ideally should be at least once a month. Washing should include the rinsing of all window and door cavities to avoid salt build up and corrosion.

We strongly recommend that you protect your powder coated joinery from the possibility of damage by some sunscreens. The damage occurs when skin which has sunscreen on it has touched the powder coated metal surface.





USE, CARE AND MAINTENANCE OF YOUR HARDWARE

Your windows and doors feature a hardware solution with unique features.

Powdercoated hardware should be cleaned regularly with a wet sponge or soft brush, warm water and a mild detergent and rinsed with fresh water. Plated products should be cleaned with a wet sponge or dry duster. NEVER use detergent on plating.

Plated hardware (eg. chrome or bronze) is not recommended for coastal applications and is excluded from any warranty as deterioration is possible under some environmental conditions.

Stainless steel hardware also needs regular cleaning. It is resistant to rust, however rust spots can sometimes occur. These can be removed with a mildly abrasive cleaner and rinsed with fresh water. In cases of heavy corrosion a Scotch-Brite hand pad can be used.

Stainless steel hardware should not be exposed to bleach products, hydrochloric acid solutions, soap concentrates and water with high iron content, such as bore water. We recommend regular treatment with 3M Stainless Steel Cleaner and polish to further protect and enhance stainless steel hardware.

YOUR SURFACE FINISHING

Powdercoatings and anodising are surface finishes that are well proven for corrosion resistance and durability.

Regular cleaning as detailed in the "Care and maintenance of your windows and doors" section is required in order to comply with warranty requirements. Powdercoating warranties, as offered by Dulux, are:

- Duralloy, 10 years on film and 10 years colour integrity
- Duralloy +Plus, 15 years on film and 15 years colour integrity
- Duratec, 20 years on film and 15 years colour integrity



Anodising warranties offered, are: 12 micron which is available with a 10 year warranty whereas, 25 micron is available with a 20 year warranty, these are on a job-specific basis.

Projects within the coastal sea spray zone i.e. within 500 metres of the sea or 100m from tidal estuaries and sheltered inlets, should use 25 micron anodising or Duralloy +Plus as a minimum.

When judging colour consistency and integrity of finish, the accepted industry standard is inspection from a distance of two metres. Slight surface finish blemishes and/or colour variations that are not visible from two metres are deemed to be acceptable.

For products treated with anodising, variability of colour and visible grain are common features and are not defects. Powdercoated tracks in sliding and bi-fold applications will wear over time and show a silver use line. This is unavoidable and does not contravene either the warranty or the durability requirements of the building code.



Vantage



Rylock

GLASS

Glass is a very delicate product that can be easily damaged during the construction process. Extreme care is required when cleaning glass as scratching can occur, so never use abrasive cleaning solutions or razor blades in the maintenance process.

Please ensure that any concrete, plaster, mortar or paint is removed as soon as possible from the surface of the windows and doors or glass before the splashes harden. Wipe with a damp cloth and wash down with clean water or mild detergent immediately. DO NOT use solvents.

Only detergents and cleaning solutions which are recommended for cleaning glass should be used. Commence cleaning by soaking the glass surfaces to loosen dirt and debris. Then using a mild, non-abrasive window washing solution, uniformly apply to the glass surfaces with a non-abrasive applicator and follow with a squeegee to remove all the cleaning solution from the glass surface. All water and cleaning residue should be dried from the window glass, gaskets, seals and frames as dried residue can permanently mark the surface of the glass.

When washing double glazing and laminated glass use the same procedures as above but ensure no solvents come into contact with the edge laminate interlayer or unit sealant. Avoid cleaning tinted and reflective glass surfaces in direct sunlight. A separate warranty of 10-12 years applies to your double glazed units, and is held by the window manufacturer in conjunction with their glass supplier.



JOINERY

All joinery supplied by Ali-Frame meet or exceed the requirements of the New Zealand Building Code and New Zealand Standards.

This means our windows and doors have been designed and successfully tested to perform in New Zealand's most diverse conditions.

Our window and door joinery is covered by warranty for 10 years against defects in manufacturing, functionality and surface finish, provided care and maintenance guidelines have been followed.

SUSTAINABILITY

Wide-ranging environmental measures are being implemented by the window supplier for Ali-Frame.

Aluminium balances two features – on the one hand, the disadvantage of a high embodied energy (the energy used in metal manufacture); on the other hand, they have a long product life and excellent recyclability.

Aluminium is an attractive recycle prospect – it has a high value, and the facilities used for remelt and repurification are readily available. Remelt uses only 5% of the energy consumed in the manufacture of the original metal product.

Vantage believes that energy-rich materials, like aluminium, are best used for appropriate end uses where their unique properties are indispensable. Window construction is one such application.

Aluminium alloys have unique properties of strength, light weight, ductility and corrosion-resistance. The metal's use in windows allows span, scale, strength, functionality and aesthetic capability.

uPVC reduces energy consumption through its high thermal efficiency rating. Also, instead of using heavy metal lead, the PVC stabilisers are made of calcium and zinc which is a much more eco-friendly option.

JOB #

ALI-FRAMETM
ALUMINIUM WINDOWS AND DOORS

WARRANTY

CUSTOMER NAME

CUSTOMER ADDRESS

ADDRESS OF PROJECT (IF DIFFERENT)

DATE OF WARRANTY

1. We warrant this product for the terms shown below.
 - (a) The aluminium joinery in the Product will perform in accordance with: AAMA 2603-05 Performance Standard for Exterior Architectural Aluminium Joinery; and SFA 3503 03:2005 Window & Glass Association Voluntary Specification for Anodic Oxide Coatings. The doors and windows of the Product will comply with: NZS 4211:2008 Performance of Windows; NZS 4223 Code of Practice for Glazing in Buildings; Specification 140307:2013, Window & Glass Association Industry Standard for Glazing Blocks; The Product will remain watertight, as required under NZS 4211.
 2. Subject to paragraph 3 below, if at any time in the 2 years after delivery or installation if installed by us, the Product becomes faulty, we will, at our election if the fault is not serious but at your election if the fault is serious, replace, repair or fully refund the affected Product, at no cost to you.
 3. This warranty only applies subject to the following:
 - (a) You must advise us of a fault in the Product as soon as possible and give us an opportunity to inspect any fault shortly thereafter;
 - (b) You must lodge a warranty claim with us in writing within 7 days of the fault becoming apparent;
 - (c) This warranty only applies:
 - (i) To you, the original purchaser; it is not transferable unless we agree otherwise in writing;
 - (ii) Where the Product has been maintained as specified below;
 - (iii) Where the fault is attributable to the workmanship or the material of the Product; and
 - (iv) Where you have paid in full for the supply (and installation if applicable) of the Product.
 - (d) This warranty does not apply to:
 - (i) Normal wear and tear;
 - (ii) Product purchased outside of New Zealand or second hand;
 - (iii) Defects due to any cause beyond our control including, without limitation:
 - a. defects in the structure in which the Product has been installed;
 - b. defects caused by poor maintenance of the Products as specified in this Care and Maintenance Guide.
 4. Materials, hardware or componentry not manufactured by us but covered by any other supplier warranty including fair wear and tear components included in the manufactured Product such as vinyl glazing gasket materials, mohair, moving parts amongst others that are not replaced as required to maintain the integrity of the manufactured Product; Any fault caused by incorrect installation by anyone other than us, including weather tightness issues attributable to a defect in the junction between the Product and the cladding system where we only supply you and do not install the Product (that junction being the responsibility of the builder); We will not be liable for any consequential, indirect or special damage or loss including, without limitation, any loss of profits.



aliframe.co.nz