
Review your last 10 questions

3 days, 1 hour remaining until quiz ends.



8/8/2019 Datamin | Review

3/10

James was studying the properties of different distributions, he obtained a dataset that follows power law, so he thought of using Box-Cox transformation with parameter lambda to get a better understanding of the transformed dataset. Answer the questions based on the given information.

Box-Cox transformation is used to transforms power law distributions into

- Normal distribution
- Geometric distribution
- Hyper geometric distribution
- None of the above



4/10

Topic: Confidence Interval

A sample of 400 students from a university were randomly selected. They were asked if the current duration of the university needed to be reduced. 46% of the students, answered yes. If the sample consisted of 300 students instead of 400 students, but the sample proportion of students who answered yes to the question was still 46%, the margin of error would be

- smaller
- larger
- same
- Can't determine



5/10

Bran chose a random number from 10 consecutive positive integers. Find probability that the randomly chosen number is greater than average?

- 3/10
- 2/5
- 1/2
- 7/10
- 4/5



6/10

Akhil wants to classify emails as spam or not spam. He starts by creating a

perceptron for the problem.

Complete Akhil's code:

from keras.models import Sequential from keras.layers import Dense

model = Sequential()
model.add(Dense(5, input_dim=2, activation='relu'))

model.add(Dense(1, activation=___?___))

- sigmoid
- relu
- linear
- None of the above

Correct

#7/10

John, a student, is given the task of binary classification of a given dataset, consisting of 1 million datapoints. Further, after feature engineering, the dimensionality of this dataset has been decreased from 750 to 200. He has been told to use KNN approach only. Further, his priority is that the algorithm should be as fast as possible.

If he tries to use LSH, with 'm' hyperplanes, how many regions will the 'd' dimensional space be divided into?

- d*m
- m
- 2ⁿ
- None of the above

Incorrect

8/10

Given two numpy arrays, *names* and *salary*(containing the names and salaries of employees of a company).

Which of the following options will sort the *names* array in decreasing order of their salary?

- name[np.argsort(salary)[::-1]]
- name.sort(np.argsort(salary)[::-1])
- name[np.argsort(salary, ascending=False)]
- name.sort(np.argsort(salary, ascending=False))

Incorrect

3/5

```
# 9/10
Complete the code to print the following output:
Output:
xyz@analytics.com True
- False
Congrats False
sharma@gomail.com True
on False
winning False
the False
latest False
hackathon False
Code:
import spacy
nlp = spacy.load('en_core_web_sm')
text = 'xyz@analytics.com - Congrats sharma@gomail.com on winning the
latest hackathon'
doc = nlp(text)
for ___1__ in ___2__:
print(each, ___3___)
  • 1 - doc
     2 - each
     3 - doc.is_email
      1 - each
      2 - doc
      3 - each.like_email
  • 1 - each
     2 - doc
     3 - each.is_email
  • 1 - doc
     2 - each
     3 - each.like_email
     Correct
# 10/10
Which of the following is true for a soft margin SVM?
  • It is known as the primal form of SVM
  • It is equivalent to the optimization of dual form of SVM
      Both a and b
  • None of the above
```

Incorrect

i Suggested reading

8/8/2019 Datamin | Review

Pytorch Introduction - How to Build Quick and Accurate Neural Networks

Pause Quiz

Show Leaderboard

Continue with Quiz

Analytics Vidhya Data Scientists Companies

 About Us
 Blog
 Post Jobs

 Our Team
 Hackathon
 Trainings

<u>Careers</u> <u>Discussions</u> <u>Hiring Hackathons</u>

<u>Contact us</u> <u>Apply Jobs</u> <u>Advertising</u>

Visit us Download App

f in D y

Get IT ON Google Play

Sign up to our newsletter

your email address

© Copyright 2013-2019 Analytics Vidhya.

Privacy Policy Terms of Use Refund Policy