

Phase 5B Migration Instructions

IMPORTANT: Manual Migration Required

Supabase's REST API doesn't support DDL operations programmatically. You need to run the migration manually in the Supabase SQL Editor.

Quick Steps (2 minutes)

Step 1: Open Supabase SQL Editor

Direct Link: <https://supabase.com/dashboard/project/yxikmojxbiihkpayndw/sql/new> (<https://supabase.com/dashboard/project/yxikmojxbiihkpayndw/sql/new>)

(Or navigate manually: Supabase Dashboard → SQL Editor → New Query)

Step 2: Copy the Migration SQL

File Location: `/home/ubuntu/jnx-os/MIGRATION_PHASE5B_SIMPLE.sql`

```
cat /home/ubuntu/jnx-os/MIGRATION_PHASE5B_SIMPLE.sql
```

Step 3: Paste & Run

1. Copy the **ENTIRE content** of `MIGRATION_PHASE5B_SIMPLE.sql`
2. Paste it into the Supabase SQL Editor
3. Click **"Run"** (or press Cmd/Ctrl + Enter)

Step 4: Verify Success

After running, you should see:

SUCCESS: No errors

Results:

table_name	count
user_conversation_usage	0
qryx_shops	0
qryx_conversations	0
qryx_messages	0

column_name	data_type
conversations_limit	integer

✓ What This Migration Does

1. Extends `billing_subscriptions` Table

- Adds `conversations_limit` column (INTEGER, default 500)
- Updates existing records:
 - **Starter Plan:** 500 conversations/month
 - **Professional Plan:** 2,000 conversations/month
 - **Business Plan:** 5,000 conversations/month

2. Creates `user_conversation_usage` Table

- Tracks monthly conversation usage per user
- Links to `billing_subscriptions` via `clerk_user_id`
- Automatically resets per billing period
- Includes warning flags for 80%/100% usage notifications

3. Creates Qryx Tables

- `qryx_shops` : Links users to Shopify stores
- `qryx_conversations` : Tracks chat sessions
- `qryx_messages` : Stores individual messages

4. Creates Performance Indexes

- 11 indexes for optimized queries
- Foreign keys for data integrity



Troubleshooting

Error: “column already exists”

✓ **This is SAFE** - The migration is idempotent. Just ignore this error.

Error: “relation already exists”

✓ **This is SAFE** - Tables already exist. Migration complete.

Error: “foreign key constraint violation”

✗ **Issue:** Make sure `users` table exists with `clerk_user_id` column.

Fix: Run the base schema first:

```
-- Ensure users table exists
CREATE TABLE IF NOT EXISTS users (
  user_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  clerk_user_id TEXT UNIQUE NOT NULL,
  email TEXT NOT NULL,
  first_name TEXT,
  last_name TEXT,
  role TEXT DEFAULT 'member',
  created_at TIMESTAMPTZ DEFAULT NOW()
);
```

Verification Commands

After migration, verify in Supabase SQL Editor:

```
-- Check if all tables exist
SELECT table_name
FROM information_schema.tables
WHERE table_schema = 'public'
AND table_name IN (
  'user_conversation_usage',
  'qryx_shops',
  'qryx_conversations',
  'qryx_messages'
)
ORDER BY table_name;

-- Check if conversations_limit column exists
SELECT column_name, data_type, column_default
FROM information_schema.columns
WHERE table_name = 'billing_subscriptions'
AND column_name = 'conversations_limit';

-- Check indexes
SELECT tablename, indexname
FROM pg_indexes
WHERE schemaname = 'public'
AND tablename LIKE '%user_conversation%' OR tablename LIKE 'qryx%'
ORDER BY tablename, indexname;
```

Need Help?

If you encounter any issues:

1. **Check Supabase Logs:** Dashboard → Database → Logs
2. **Verify Base Schema:** Ensure `users` and `orgs` tables exist
3. **Contact Support:** Share the error message from SQL Editor

After Migration Complete

Tell the Agent:

“Migration done! Let’s continue with Phase 5B.2.”

The agent will then proceed to:

1. Extend `lib/db/billing-helpers.ts` with usage tracking functions
 2. Implement usage increment logic in chat API
 3. Add limit enforcement guards
 4. Update Stripe webhooks for plan changes
-

Last Updated: December 31, 2025

Phase: 5B.1 - Core Infrastructure

Status: Ready to Execute