Cheat Sheet

Logical Operators

The logical operators are used to perform logical operations on Boolean values.
Gives `True` or `False` as the result.

Following are the logical operators

- `and`
- `or`
- `not`

Logical AND Operator

Gives `True` if both the booleans are true else, it gives `False`

Code

PYTHON

```
print(True and True)
```

Output

```
True
```

Examples of Logical AND

Code

PYTHON

```
print((2 < 3) and (1 < 2))
```

Step by Step Explanation

```
(2 < 3) and (1 < 2)
True and (1 < 2)
True and True
```

Output

```
True
```

Logical OR Operator

Gives `True` if any one of the booleans is true else, it gives `False`

Code

PYTHON

```python
print(False or False)
```

Output

```
False
```

Examples of Logical OR

Code

PYTHON

```python
print((2 < 3) or (2 < 1))
```

Step by Step Explanation

```
(2 < 3) or (2 < 1)
True or (2 < 1)
True or False
```

Output

```
True
```

Logical NOT Operator

Gives the opposite value of the given boolean.

Code

```python
print(not(False))
```

Output

```
True
```

Examples of Logical NOT

Code

```python
print(not(2 < 3))
```

Step by Step Explanation

```
not(2 < 3)
not(True)
False
```

Output

```
False
```

Summary

1. Logical *AND* Operator gives `True` if all the booleans are true.
2. Logical *OR* Operator gives `True` if any of the booleans are true.

3. Logical *NOT* Operator gives the opposite value

Submit Feedback

MARK AS COMPLETED

PROCEED TO NEXT ›