

1. Reusability of CSS Rulesets

If we want the same style for multiple HTML elements, we can write the CSS Ruleset once and use it for different HTML elements.

CSS

```
1 .button {  
2   width: 138px;  
3   height: 36px;  
4   border-width: 0px;  
5   border-radius: 10px;  
6 }
```

HTML

```
1 <button class="button">Get Started</button>  
2 <button class="button">Visit Now</button>
```

[<](#) Question 1 of 1

Can we write the **CSS Ruleset** once and use it for multiple HTML elements?

☐ Yes☐ No[Show Answer](#)[Submit](#)

2. Multiple class names as an HTML attribute value

We can provide multiple class names separated by space as a value to the HTML class attribute.

Syntax: `<tag class = "name1 name2 name3 name4 ..." >Content</tag>`

HTML attribute value: `name1 name2 name3 name4 ...`

class names: `name1` , `name2` , `name3` , and `name4`

CSS

```
1 .button {  
2   width: 138px;  
3   height: 36px;  
4   border-width: 0px;  
5   border-radius: 10px;  
6 }  
7 .button-green {  
8   background-color: #8cc63f;  
9 }
```

HTML

```
1 <button class="button button-green">Get Started</button>
```

Code

Output



HTML CSS JS JAVASCRIPT

```
1 <!DOCTYPE html>  
2 <html>  
3   <head></head>  
4   <body>  
5     <button class="button button-green">Get Started</button>  
6     <button class="button button-orange">Visit Now</button>  
7   </body>  
8 </html>
```

Question 1 of 2

What is the **correct syntax** to provide multiple class names as a value to the HTML class attribute?

- ☐ <tag class = name1 name2 name3 name4>Welcome</tag>
- ☐ <tag class = "name1,name2,name3,name4">Welcome</tag>
- ☐ <tag class = "name1 name2 name3 name4">Welcome</tag>
- ☐ <tag "name1 name2 name3 name4">Welcome</tag>

Show Answer

Submit

3. Bootstrap

Bootstrap is a large collection of predefined reusable Code Snippets written in HTML, CSS, and Javascript. The Code Snippets include Buttons, Cards, Carousels, etc.

3.1 How to use Bootstrap?

To use the Code Snippets provided by Bootstrap, we need to add the below piece of code within the HTML `head` element. We call it **BootstrapCDN**.

```
1 <link rel="stylesheet" href="https://stackpath.bootstrapcdn.com/bootstrap/4.5.2/
2 <script src="https://code.jquery.com/jquery-3.5.1.slim.min.js" integrity="sha384
3 <script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.1/dist/umd/popper.min.js
4 <script src="https://stackpath.bootstrapcdn.com/bootstrap/4.5.2/js/bootstrap.min.js">
```

HTML

Submit Feedback

✓ Completed

✓ Completed

Ask doubt

Notes

Discussions

Notes

+ NEW NOTE

B *I* U ↺ ☰ ☷ 🔗 🖼️ 📎

Title
Take a Note

🕒 Not Saved

