

1. Bootstrap Grid System

Bootstrap Grid System is a collection of reusable code snippets to create responsive layouts. It is made up of **containers**, **rows**, and **columns**.

It uses a **12 column system** for layouting. We can create up to 12 columns across the page.

1.1 Container

The purpose of a container is to hold rows and columns.

```
i 1 <div class="container"></div>
```

[HTML](#)

Here, the container is a `div` element with the Bootstrap class name `container`.

Here, the container is a `div` element with the Bootstrap class name `container`.

1.2 Row

The purpose of a row is to wrap all the columns.

```
i 1 <div class="container">
  2   <div class="row"></div>
  3 </div>
```

[HTML](#)

Here, the row is a `div` element with the Bootstrap class name `row`.

1.3 Column

We should place the columns inside a row and the content inside a column.

We can specify the number of columns our content should occupy in any device. The number of columns we specify should be a number in the range of `1` to `12`.

```
i 1 <div class="container">
```

[HTML](#)

```

2 <div class="row">
3   <div class="col-12">
4     I'm your content inside the grid!
5   </div>
6 </div>
7 </div>

```

Here, the column is a `div` element with the Bootstrap class name `col-12`.

Note

If Bootstrap class name is `col-12`, it occupies the entire width available inside the row.

The Bootstrap class names `col-*` indicates the number of columns you would like to use out of the possible 12 columns per row. For example, `col-1`, `col-5`, etc.

Try out changing the number of columns in the below Code Playground and check the output.

Code

Output

HTML

CSS

JAVASCRIPT

```

1 <!DOCTYPE html>
2 <html>
3   <head>
4     <link rel="stylesheet" href="https://stackpath.bootstrapcdn.com/bootstrap/4.5.2/c
5     <script src="https://code.jquery.com/jquery-3.5.1.slim.min.js" integrity="sha384-
6     <script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.1/dist/umd/popper.min.js
7     <script src="https://stackpath.bootstrapcdn.com/bootstrap/4.5.2/js/bootstrap.min.
8   </head>
9   <body>
10    <div class="container">
11      <div class="row">
12        <div class="col-12">

```

Run Code

2. Creating Multiple Column Layouts

The Layout in the below Code Playground is a **Two Column Layout**. Similarly try out multiple column layouts like One Column Layout, Three Column Layout, etc. in the below Code Playground.

Code

Output

HTML

CSS

JAVASCRIPT

```
1 <!DOCTYPE html>
2 <html>
3   <head>
4     <link rel="stylesheet" href="https://stackpath.bootstrapcdn.com/bootstrap/4.5.2/c
5     <script src="https://code.jquery.com/jquery-3.5.1.slim.min.js" integrity="sha384-
6     <script src="https://cdn.jsdelivr.net/npm/popper.js@1.16.1/dist/umd/popper.min.js
7     <script src="https://stackpath.bootstrapcdn.com/bootstrap/4.5.2/js/bootstrap.min.
8   </head>
9   <body>
10    <div class="container">
11      <div class="row">
12        <div class="col-8">
```

▶ Run Code

Submit Feedback

✓ Completed

Ask doubt

Notes Discussions

Notes

+ NEW NOTE

B *I* U ↺ ☰ ☷ 🔗 🖼️ 📎

Title
Take a Note

🕒 Not Saved

🏠
Home

🗺️
My Journey

📖
Course Library

🎧
Live Classes

📅
Events

⌄
More