

Theme 1

Compilers, Languages and Grammars

Introduction

Compilers, 2nd semester 2024-2025

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Miguel Oliveira e Silva
DETI, University of Aveiro, Portugal

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine


Linearly bounded
automata

Pushdown automata

Finite automata

Framework

- In this course we will talk about **languages** – what they are and how we can define them – and about **compilers** – tools that recognize them and allow you to perform actions as a result of that process.



Frame

Programming languages

Compilers:
Introduction

Structure of a Compiler

Lexical Analysis
Syntax Analysis
Semantic Analysis
Synthesis

Implementation of a
Compiler

Lexical analysis
Syntax parsing
Semantic analysis
Synthesis: code
interpretation

Languages: Definition
as a Set

Basic concepts and
terminology
Operations on words
Operations on languages

Introduction to
grammars

Chomsky hierarchy
Automatons
Turing Machine
Linearly bounded
automata
Pushdown automata
Finite automata

- ◀ ▶ ↺ 🔍 ↻ ⌂

- Different languages may use different symbols (letters or characters), or share many of them.
- Comprehension of a word is done letter by letter, but this does not happen with a text.
- Thus, we can see a natural language like Portuguese as being composed of more than one language:
 - One that spells out the rules for building words from the alphabet of letters:

$a + d + e + u + s \rightarrow \text{goodbye}$

- And another one that contains the grammar rules for building sentences from the resulting words from the previous language:

$\text{goodbye} + \text{and} + \text{see you} + \text{tomorrow} \rightarrow \text{goodbye and see you tomorrow}$

In this case, the alphabet ceases to be the set of letters and becomes the set of existing words.

Frame

Programming languages

Compilers:
Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a
Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition
as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to
grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- Inherent in languages is the need to decide whether a sequence of alphabet symbols is valid.
 - **correct:**
a + d + e + u + s → goodbye
goodbye + and + until + tomorrow →
goodbye and see you tomorrow
 - **incorrect:**
e + d + u + a + s → edes
until + goodbye + tomorrow + and → see you tomorrow and
- Only valid strings allow correct communication.
- On the other hand, this communication often has an effect.
- Whether that effect is a response to the initial message, or the triggering of any action.

Frame

Programming languages

Compilers:
Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a
Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition
as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to
grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- The languages for communicating with computers – called programming languages – share all these characteristics.
- They differ in that they cannot have any **ambiguity**, and that the triggered actions often be a change in the state of the computational system, which may be linked to entities such as other computers, people, robotic systems, washing machines, etc.
- Let's see that we can define programming languages by well-behaved formal structures.
- Furthermore, we will also see that these definitions help us to implement interesting actions.

Development of programming languages umbilically linked with compilation technologies!

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis
Syntax Analysis
Semantic Analysis
Synthesis

Implementation of a Compiler

Lexical analysis
Syntax parsing
Semantic analysis
Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology
Operations on words
Operations on languages

Introduction to grammars

Chomsky hierarchy
Automatons
Turing Machine
Linearly bounded
automata
Pushdown automata
Finite automata

Frame

Programming languages

Compilers:
Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a
Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition
as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to
grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Compilers: Introduction

Frame

Programming languages

Compilers:
Introduction

Structure of a Compiler

Lexical Analysis
Syntax Analysis
Semantic Analysis
Synthesis

Implementation of a
Compiler

Lexical analysis
Syntax parsing
Semantic analysis
Synthesis: code
interpretation

Languages: Definition
as a Set

Basic concepts and
terminology
Operations on words
Operations on languages

Introduction to
grammars

Chomsky hierarchy
Automatons
Turing Machine
Linearly bounded
automata
Pushdown automata
Finite automata

Compilers

Comprehension, interpretation and/or automatic translation of languages.

Compilers (Language Processors)

- **compilers** are programs that allow:
 - 1 decide on the correction of sequences of symbols of the respective alphabet;
 - 2 trigger actions resulting from those decisions.
- Compilers are often “limited” to translating between languages.



- This is the case for compilers of high-level programming languages (Java, C++, Eiffel, etc.), which translate the source code of these languages in code of languages closer to the *hardware* of the system computational (e.g. *assembly* or *Java bytecode*).
- In these cases, in the absence of errors, a program composed of executable code is generated directly or indirectly by the computer system:



Example: Java *bytecode*

```
public class hello
{
    public static void main(String [] args)
    {
        System.out.println ("Hello!");
    }
}
```

```
javac Hello.java
```

```
javap -c Hello.class
```

Compiled from "Hello.java"

```
public class Hello {
    public Hello();
        Code:
        0: aload_0
        1: invokespecial #1 // Method java/lang/Object."<init>":()V
        4: return

    public static void main(java.lang.String []);
        Code:
        0: getstatic     #2 // Field java/lang/System.out:Ljava/io/PrintStream;
        3: ldc           #3 // String Hello!
        5: invokevirtual #4 // Method java/io/PrintStream.println:(Ljava/lang/String;)V
        8: return
}
```

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis
Syntax Analysis
Semantic Analysis
Synthesis

Implementation of a Compiler

Lexical analysis
Syntax parsing
Semantic analysis
Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology
Operations on words
Operations on languages

Introduction to grammars

Chomsky hierarchy
Automatons
Turing Machine
Linearly bounded
automata
Pushdown automata
Finite automata

Example 2: Calculator

- Source code:


```
1+2*3:4
```

- A possible compilation for Java:

```
public class CodeGen {  
    public static void main( String [] args ) {  
        double v2 = 1;  
        double v5 = 2;  
        double v6 = 3;  
        double v4 = v5 * v6;  
        double v7 = 4;  
        double v3 = v4 / v7;  
        double v1 = v2 + v3;  
        System.out.println( v1 );  
    }  
}
```

Compilers: Language Processors (2)

- A possible variant consists of an **interpreter**:



- In this case, execution is carried out instruction by instruction.
- `Python` and `bash` are examples of interpreted languages.
- There are also hybrid approaches where there is compilation of code for a language intermediate, which is then interpreted at runtime.
- The language `Java` uses a strategy like this where the source code is compiled to *Java bytecode*, which is then interpreted by the `Java` virtual machine.
- In general, compilers process source code in *text* format, with a wide variety in the format of the generated code (text, binary, interpreted, ...).

Example: Calculator

- Source code:

1+2*3:4

- One possible interpretation:

2.5

Frame

Programming languages

Compilers:
Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a
Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition
as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to
grammars

Chomsky hierarchy

Automatons

Turing Machine


Linearly bounded
automata

Pushdown automata

Finite automata

Structure of a Compiler

Structure of a Compiler



Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis
Syntax Analysis
Semantic Analysis
Synthesis

Implementation of a Compiler

Lexical analysis
Syntax parsing
Semantic analysis
Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology
Operations on words
Operations on languages

Introduction to grammars

Chomsky hierarchy
Automatons
Turing Machine
Linearly bounded
automata
Pushdown automata
Finite automata

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- An interesting feature of high-level language compilation is the fact that that, as in the case of natural languages, this compilation involves more than one language:
 - **lexical analysis**: composition of letters and other characters into words (*tokens*);
 - **parsing**: composition of *tokens* into a suitable syntactic structure.
 - **semantic analysis**: checking – as much as possible – that the syntactic structure has meaning.
- Actions consist of generating the program in the target language and may involve also different stages of code generation and optimization.

- Conversion of the input string into a string of lexical elements.
- This strategy greatly simplifies the grammar of parsing, and allows for an implementation very efficient lexical analyzer (later we will see in detail why).
- Each lexical element can be defined by a tuple with an element id and its value (value can be omitted when not applicable):

```
<token_name , attribute_value >
```

- Example 1:

```
pos = pos + vel * 5;
```

can be converted by the lexical analyzer (*scanner*) into:

```
<id , pos> <=> <id , pos> <+> <id , vel> <*> <int , 5> <;>
```

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automata

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- In general whitespace, newlines and comments are not relevant in languages programming, so they can be eliminated by the lexical analyzer.


- Example 2: Geometric Processing Language Sketch:

```
distance ( 0 , 0 ) ( 4 , 3 )
```

can be converted by the lexical analyzer (*scanner*) into:

```
<distance> <( > <num,0> <,> <num,0> <)>  
<( > <num,4> <,> <num,3> <)>
```

- After the lexical analysis, the so-called syntactic analysis (*parsing*) is carried out, where conformity is verified of the sequence of lexical elements with the syntactic structure of the language.
- In languages that are intended to be syntactically processed, we can always make an approximation to the its formal structure through a representation like *tree*.
- For this purpose, a *grammar* is needed that specifies the desired structure (we will return to this problem later).
- In the example 1 (`pos = pos + vel * 5;`):



Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons


Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- In the example 2 (`distance (0 , 0) (4 , 3)`):



- Attention is drawn to two characteristics of syntax trees:
 - does not include some lexical elements (which are only relevant to the formal structure);
 - unambiguously define the order of operations (we'll come back to this problem).

- The final part of the compiler's *front end* is *semantic analysis*.
- In this phase, as much as possible, restrictions are checked that are not possible (or even desirable) to be made in the two previous phases.
- For example: check if an identifier was declared, check conformance in the type system of language, etc.
- Note that only constraints with static checking (i.e. at compile time), can be object of semantic analysis by the compiler.
- If in the example 2 there was an instruction for a circle of which the definition of its radius was part, it would not in general be possible, during semantic analysis, to guarantee a non-negative value for this radius (this semantics could only be verified dynamically, i.e., at runtime).

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- Uses the parsing syntax tree as well as a data structure called symbol table (based on associative arrays).
- This last phase of analysis should guarantee the success of subsequent phases (generation and eventual code optimization, or interpretation).

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- Having guaranteed that the source language code is valid, then we can move on to the intended effects with that code.
- Effects can be:
 - ① simply the indication of source code validity;
 - ② the translation of the source code into a target language;
 - ③ or interpretation and immediate execution.
- In all cases, it may be of interest to accurately identify and locate any errors.
- As most source code is text based, it is usual to indicate not only the instruction but also the line where each error occurs.

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Code generation: example

- In the compilation process, it may be interesting to generate an intermediate representation of the code that facilitates the final generation of code.
- One possible form for this intermediate representation is the so-called *triple address code*.
- For example 1 (`pos = pos + vel * 5;`) we could have:

```
t1 = inttofloat(5)
t2 = id(vel) * t1
t3 = id(pos) + t2
id(pos) = t3
```

- This code could then be optimized in the next phase of compilation:

```
t1 = id(vel) * 5.0
id(pos) = id(pos) + t1
```

- And finally, one could generate *assembly* (pseudo-code):

```
LOAD R2, id(vel) // load value from memory to register R2
MULT R2, R2, #5.0 // mult. 5 with R2 and store result in R2
LOAD R1, id(pos) // load value from memory to register R1
ADD R1, R1, R2 // add R1 with R2 and store result in R1
STORE id(pos), R1 // store value to memory from register R1
```

Frame

Programming languages

Compilers:
Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a
Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition
as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to
grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Languages: Definition as Set

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- Languages are for **communicating**.
- A message can be seen as a sequence of **symbols**.
- However, a language does not accept all types of symbols and sequences.
- A language is characterized by a set of symbols and a way of describe valid sequences of these symbols (i.e. the set of valid sequences).
- If natural languages allow for some subjectivity and ambiguity, programming languages require complete objectivity.

- How to define languages in a synthetic and objective way?
- Setting by **extension** is a possibility.
- However, for minimally interesting not only would we have a gigantic description, but also probably an incomplete one.
- Programming languages tend to accept infinite variants of input.
- Alternatively we can describe it as **understanding**.
- One possibility is to use the formalisms linked to the definition of **sets**.

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Basic Concepts

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- A set can be defined by **extension** (or enumeration) or by **comprehension**.
- An example of a set defined by extension is the set of binary digits $\{0, 1\}$.
- In the definition by comprehension, the following notation is used:

$$\{x \mid p(x)\}$$

or

$$\{x : p(x)\}$$

- x is the variable that represents any element of the set, and $p(x)$ is a predicate on that variable.
- Thus, this set is defined as containing all values of x where the predicate $p(x)$ is true.
- For example:
$$\{n \mid n \in \mathbb{N} \wedge n \leq 9\} = \{1, 2, 3, 4, 5, 6, 7, 8, 9\}$$

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- A **symbol** (or **letter**) is the atomic (indivisible) unit of languages.
- In text-based languages, a symbol will be a character.
- An **alphabet** is a non-empty finite set of symbols.
- For example:
 - $A = \{0, 1\}$ is the alphabet of binary digits.
 - $A = \{0, 1, \dots, 9\}$ is the alphabet of decimal digits.
- A **word** (*string* or string) is a sequence of symbols about a given alphabet A .

$$U = a_1 a_2 \cdots a_n, \quad \text{com} \quad a_i \in A \wedge n \geq 0$$

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- For example:
 - $A = \{0, 1\}$ is the alphabet of binary digits.
01101, 11, 0
 - $A = \{0, 1, \dots, 9\}$ is the alphabet of decimal digits.
2016, 234523, 999999999999999, 0
 - $A = \{0, 1, \dots, 0, a, b, \dots, z, @, \dots\}$
mos@ua.pt, Good morning!

- The **empty word** is a sequence of zero symbols and is denoted by ε (epsilon).
- Note that ε does not belong to the alphabet.
- An **subword** of a word u is a contiguous string of 0 or more u symbols.
- A **prefix** of a word u is a contiguous string of 0 or more leading symbols of u .
- An **suffix** of a word u is a contiguous sequence of 0 or more terminal symbols of u .
- For example:
 - as is a subword of home, but not a prefix or suffix
 - 001 is prefix and subword of 00100111 but not suffix
 - ε is prefix, suffix and subword of any word u
 - any word u is prefix, suffix and subword of itself

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- The **closing** (or set of strings) of the alphabet A named by A^* , represents the set of all the definable words over the A alphabet, including the empty word.
- For example:
 - $\{0, 1\}^* = \{\varepsilon, 0, 1, 00, 01, 10, 11, 000, 001, \dots\}$
 - $\{\clubsuit, \diamond, \heartsuit, \spadesuit\}^* = \{\varepsilon, \clubsuit, \diamond, \heartsuit, \spadesuit, \clubsuit\diamond, \dots\}$
- Given an alphabet A , a **language** L over A is a finite or infinite set of valid words defined with A symbols.
That is: $L \subseteq A^*$

- Example languages about the alphabet $A = \{0, 1\}$
 - $L_1 = \{u \mid u \in A^* \wedge |u| \leq 2\} = \{\varepsilon, 0, 1, 00, 01, 10, 11\}$
 - $L_2 = \{u \mid u \in A^* \wedge \forall_i u_i = 0\} = \{\varepsilon, 0, 00, 000, 0000, \dots\}$
 - $L_3 = \{u \mid u \in A^* \wedge u.\text{count}(1) \bmod 2 = 0\} = \{000, 11, 000110101, \dots\}$
 - $L_4 = \{\} = \emptyset$ (emptyset)
 - $L_5 = \{\varepsilon\}$
 - $L_6 = A$
 - $L_7 = A^*$
- Note that $\{\}, \{\varepsilon\}, A$ and A^* are languages over the alphabet A whatever A is
- Since languages are sets, all mathematical operations on sets apply: meeting, interception, complement, difference, etc.



Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis
Syntax Analysis
Semantic Analysis
Synthesis

Implementation of a Compiler

Lexical analysis
Syntax parsing
Semantic analysis
Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and terminology

Operations on words
Operations on languages

Introduction to grammars

Chomsky hierarchy
Automatons
Turing Machine
Linearly bounded
automata
Pushdown automata
Finite automata

Operations on words

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- The **length** of a word u is denoted by $|u|$ and represents its number of symbols.
- The length of the empty word is zero

$$|\varepsilon| = 0$$

- It is customary to interpret the word u as a function to access its symbols (like *array*):

$$u : \{1, 2, \dots, n\} \rightarrow A, \quad \text{com } n = |u|$$

where u_i represents the i th symbol of u

- The **reverse** of a word u is the word, denoted by u^R , and is obtained reversing the order of u symbols

$$u = \{u_1, u_2, \dots, u_n\} \implies u^R = \{u_n, \dots, u_2, u_1\}$$

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- The **concatenation** (or **product**) of the words u and v is denoted by $u.v$, or simply uv , and represents the juxtaposition of u and v , i.e., the word consisting of the u symbols followed by the v symbols.
- Concatenation properties:
 - $|u.v| = |u| + |v|$
 - $u.(v.w) = (u.v).w = u.v.w$ (associative)
 - $u.\varepsilon = \varepsilon.u = u$ (neutral element)
 - $u \neq \varepsilon \wedge v \neq \varepsilon \wedge u \neq v \implies u.v \neq v.u$ (non-commutative)
- The **power** of order n , with $n \geq 0$, of a word u is denoted by u^n and represents the concatenation of n replicas of u , that is, $\underbrace{uu \cdots u}_{n \times}$.
- $u^0 = \varepsilon$

Operations on languages

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Language operations: meeting

- The **meeting** of two languages L_1 and L_2 is denoted by $L_1 \cup L_2$ and is given by:

$$L_1 \cup L_2 = \{u \mid u \in L_1 \vee u \in L_2\}$$

- For example, if we define the languages L_1 and L_2 over the alphabet $A = \{a, b\}$:

$$L_1 = \{u \mid u \text{ starts with } The\} = \{aW \mid w \in A^*\}$$

$$L_2 = \{u \mid u \text{ ends with } The\} = \{wa \mid w \in A^*\}$$

- what will be the result of merging these languages?

$$L = L_1 \cup L_2 = ?$$

- Answer:

$$L = \{w_1 a w_2 \mid w_1, w_2 \in A^* \wedge (w_1 = \varepsilon \vee w_2 = \varepsilon)\}$$

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Language operations: interception

- The **interception** of two languages L_1 and L_2 is denoted by $L_1 \cap L_2$ and is given by:

$$L_1 \cap L_2 = \{u \mid u \in L_1 \wedge u \in L_2\}$$

- For example, if we define the languages L_1 and L_2 over the alphabet $A = \{a, b\}$:

$$L_1 = \{u \mid u \text{ starts with } The\} = \{aW \mid w \in A^*\}$$

$$L_2 = \{u \mid u \text{ ends with } The\} = \{wa \mid w \in A^*\}$$

- what will be the result of the interception of these languages?

$$L = L_1 \cap L_2 = ?$$

- Answer:

$$L = \{awa \mid w \in A^*\} \cup \{The\}$$

Operations on languages: difference

- The **difference** of two languages L_1 and L_2 is denoted by $L_1 - L_2$ and is given by:

$$L_1 - L_2 = \{u \mid u \in L_1 \wedge u \notin L_2\}$$

- For example, if we define the languages L_1 and L_2 over the alphabet $A = \{a, b\}$:

$$L_1 = \{u \mid u \text{ starts with } The\} = \{aW \mid w \in A^*\}$$

$$L_2 = \{u \mid u \text{ ends with } The\} = \{wa \mid w \in A^*\}$$

- what will be the result of the difference of these languages?

$$L = L_1 - L_2 = ?$$

- Answer:

$$L = \{awx \mid w \in A^* \wedge x \in A \wedge x \neq a\}$$

- or:

$$L = \{awb \mid w \in A^*\}$$

Operations on languages: completion

- The **complement** of the L language is denoted by \bar{L} and is given by:

$$\bar{L} = A^* - L = \{u \mid u \notin L\}$$

- For example, if we define the language L_1 over the alphabet $A = \{a, b\}$:

$$L_1 = \{u \mid u \text{ starts with } The\} = \{aW \mid w \in A^*\}$$

- what will be the result of complementing this language?

$$L = \bar{L_1} = ?$$

- Answer:

$$L = \{xw \mid w \in A^* \wedge x \in A \wedge x \neq a\} \cup \{\varepsilon\}$$

- or:

$$L = \{bw \mid w \in A^*\} \cup \{\varepsilon\}$$

Language operations: concatenation

- The **concatenation** of two languages L_1 and L_2 is denoted by $L_1.L_2$ and is given by:

$$L_1.L_2 = \{uv \mid u \in L_1 \wedge v \in L_2\}$$

- For example, if we define the languages L_1 and L_2 over the alphabet $A = \{a, b\}$:

$$L_1 = \{u \mid u \text{ starts with } The\} = \{aW \mid w \in A^*\}$$

$$L_2 = \{u \mid u \text{ ends with } The\} = \{wa \mid w \in A^*\}$$

- what will be the result of the concatenation of these languages?

$$L = L_1.L_2 = ?$$

- Answer:

$$L = \{awa \mid w \in A^*\}$$

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Operations on languages: potentiation

- The **power** of order n of the language L is denoted by L^n and is defined inductively by:

$$\begin{aligned}L^0 &= \{\varepsilon\} \\ L^{n+1} &= L^n.L\end{aligned}$$

- For example, if we define the language L_1 over the alphabet $A = \{a, b\}$:

$$L_1 = \{u \mid u \text{ starts with } The\} = \{aW \mid w \in A^*\}$$

- what will be the result of the power of order 2 of this language?

$$L = L_1^2 = ?$$

- Answer:

$$L = \{a w_1 a w_2 \mid w_1, w_2 \in A^*\}$$

Operations on languages: Kleene closure

- The **Kleene closure** of the language L is denoted by L^* and is given by:

$$L^* = L^0 \cup L^1 \cup L^2 \cup \dots = \bigcup_{i=0}^{\infty} L^i$$

- For example, if we define the language L_1 over the alphabet $A = \{a, b\}$:

$$L_1 = \{u \mid u \text{ starts with } The\} = \{aW \mid w \in A^*\}$$

- what will be the Kleene closure of this language?

$$L = L_1^* = ?$$

- Answer:

$$L = L_1 \cup \{\varepsilon\}$$

- Note that for $n > 1$ $L_1^n \subset L_1$

- Note that in binary operations on sets it is not required that the two languages are defined on the same alphabet.
- So if we have two languages L_1 and L_2 respectively defined on the alphabets A_1 and A_2 , then the alphabet resulting from the application of any binary operation on the languages is: $A_1 \cup A_2$

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Introduction to grammars

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- The use of sets to define languages is often not the most appropriate way and versatile to describe them.
- It is often preferable to identify intermediate structures, which abstract parts or important subsets of the language.
- As in programming, many times recursive descriptions are much simpler, without losing the necessary objectivity and rigor.
- This is where we find the **grammars**.
- **grammars** describe languages by comprehension using **formal** and (often) **recursive** representations.
- Seeing languages as sequences of symbols (or words), grammars formally define the **valid** sequences.

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- For example, in Portuguese the sentence “The dog barks” can be grammatically described by:

phrase	→	subject predicate
subject	→	article noun
predicate	→	verb
article	→	O Um
noun	→	dog wolf
verb	→	thief howl

- This grammar describes 8 possible sentences and contains more information than the original sentence.
- Contains 6 **terminal symbols** and 6 **non-terminal symbols**.
- A non-terminal symbol is defined by an **production** describing possible representations of that symbol, depending on terminal and/or non-terminal symbols.

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis
Syntax Analysis
Semantic Analysis
Synthesis

Implementation of a Compiler

Lexical analysis
Syntax parsing
Semantic analysis
Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology
Operations on words
Operations on languages

Introduction to grammars

Chomsky hierarchy
Automatons
Turing Machine
Linearly bounded
automata
Pushdown automata
Finite automata

- Formally, a grammar is a quadruple $G = (T, N, S, P)$, where:
 - T is a non-empty finite set called the terminal alphabet, where each element is called the **terminal** symbol;
 - N is a non-empty finite set, disjoint from T ($N \cap T = \emptyset$), whose elements are designated by **non-terminal** symbols;
 - $S \in N$ is a specific non-terminal symbol called **start symbol**;
 - P is a finite set of **rules** (or productions) of the form $\alpha \rightarrow \beta$ where $\alpha \in (T \cup N)^* N (T \cup N)^*$ and $\beta \in (T \cup N)^*$, that is, α is a string of terminal and non-terminal symbols containing at least one non-terminal symbol; and β is a string of symbols, eventually empty, terminal and non-terminal.

- Formally, the previous grammar will be:

$$G = (\{\mathbf{O}, \mathbf{Um}, \mathbf{dog}, \mathbf{wolf}, \mathbf{thief}, \mathbf{howl}\}, \\ \{\text{sentence, subject, predicate, article, noun, verb}\}, \\ \text{phrase}, P)$$

- P is made up of the rules already presented:

phrase \rightarrow subject predicate
subject \rightarrow article noun
predicate \rightarrow verb
article \rightarrow **O** | **A**
noun \rightarrow **dog** | **wolf**
verb \rightarrow **thief** | **howl**

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons


Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- We can describe the sentence “The dog barks” with the following tree (called syntactic).



- Consider the following grammar

$G = (\{0, 1\}, \{S, A\}, S, P)$, where P consists of the rules:

$$S \rightarrow 0S$$

$$S \rightarrow 0A$$

$$A \rightarrow 0A1$$

$$A \rightarrow \varepsilon$$

- What will be the language defined by this grammar?

$$L = \{0^n 1^m : n \in \mathbb{N} \wedge m \in \mathbb{N}_0 \wedge n > m\}$$

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Grammars: examples (4)

- Being $A = \{a, b\}$, define a grammar for the following language:

$$L_1 = \{aW \mid w \in A^*\}$$

- The grammar $G = (\{a, b\}, \{S, X\}, S, P)$, where P is made up of the rules:

$$S \rightarrow aX$$

$$X \rightarrow aX$$

$$X \rightarrow bX$$

$$X \rightarrow \varepsilon$$

or:

$$S \rightarrow aX$$

$$X \rightarrow aX \mid bX \mid \varepsilon$$

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- Being $A = \{0, 1\}$, define a grammar for the following language:

$$L_3 = \{u \mid u \in A^* \wedge u.\text{count}(1) \bmod 2 = 0\}$$

- The grammar $G = (\{0, 1\}, \{S, A\}, S, P)$, where P is made up of the rules:

$$S \rightarrow S1S1S \mid A$$

$$A \rightarrow 0A \mid \varepsilon$$

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Frame

Programming languages

Compilers:
Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a
Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition
as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to
grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Chomsky Hierarchy

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis
Syntax Analysis
Semantic Analysis
Synthesis

Implementation of a Compiler

Lexical analysis
Syntax parsing
Semantic analysis
Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology
Operations on words
Operations on languages


Introduction to grammars

Chomsky hierarchy

Automatons
Turing Machine
Linearly bounded
automata
Pushdown automata
Finite automata

- Constraints on α and β allow to define a taxonomy of languages – Chomsky hierarchy:
 - 1 If there is no restriction, G is designated by **type-0** grammar.
 - 2 G will be of **1-type**, or **context-dependent** grammar, if each rule $\alpha \rightarrow \beta$ of P obeys $|\alpha| \leq |\beta|$ (with the exception that there may also be the empty output: $S \rightarrow \varepsilon$).
 - 3 G will be of **2-type**, or grammar **context-independent, or free**, if each rule $\alpha \rightarrow \beta$ of P obeys $|\alpha| = 1$, that is: α consists of a single non-terminal.
 - 4 G will be of **3-type**, or **regular** grammar, if each rule has one of the forms: $A \rightarrow cB$, $A \rightarrow c$ or $A \rightarrow \varepsilon$, where A and B are non-terminal symbols (A can be equal to B) and c a terminal symbol. That is, in all productions, β can only have at most one non-terminal symbol always on the right (or, alternatively, always on the left).

Chomsky hierarchy (2)



- For each of these types different types of machines can be defined (algorithms, automata) that can recognize them.
- The simpler the grammar, the simpler and more efficient the machine that recognizes these languages.

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- Each language class of **type- i** contains the language class **type- $(i+1)$** ($i = 0, 1, 2$)
- This hierarchy not only translates the formal characteristics of languages, but also expresses The required computing requirements:
 - 1 **Turing machines** process grammars without restrictions (type-0);
 - 2 **linearly bounded automata** process context-dependent (1-type) grammars;
 - 3 **Pushdown automata** process context-independent grammars (2-type);
 - 4 **finite automata** process regular grammars (3-type).

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Automata

- (Alan Turing, 1936)
- Abstract computing model.
- Allows (in theory) to implement any computable program.
- Relies on a finite state machine, symbol read/write head and on an infinite tape (where these symbols are written or read).
- The read/write "head" can move one position left or right.
- Very important model in the theory of computation.
- Little relevant in the practical implementation of language processors.

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons


Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

Turing Machine (2)



Possible operations:

- 1 Write symbol to tape;
- 2 Move head one position to the right;
- 3 Move head one position to the left;
- 4 Halt (accept input).

- The finite state machine (FSM) has access to the current symbol and decides the next action to be performed.
- The action consists of the state transition and what is the operation on the tape.
- If no action is possible, the input is rejected.

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata

- Given the alphabet $A = \{0, 1\}$, and considering that a non-negative integer n is represented by sequence of $n + 1$ 1 symbols, let's implement a TM that adds the next ones (i.e. to the right of the current position) two existing integers on the tape (separated only by a 0).
- The algorithm could be simply swapping the 0 symbol between the two numbers for 1, and swapping the last two symbols 1 for 0.
- For example: $3 + 2$ which corresponds to the following state on the tape (bold symbol is the position of the "head"): $\dots \mathbf{0}111101110\dots$ (the intended result will be: $\dots \mathbf{0}111111000\dots$).
- Whereas the states are designated by $E_i, i \geq 1$ (E_1 being the initial state); and the operations:
 - d move one position to the right;
 - e move one position to the left;
 - 0 write the 0 symbol on the tape;
 - 1 write the 1 symbol on the tape;
 - h accept and terminate automaton.

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code interpretation

Languages: Definition as a Set

Basic concepts and terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded automata

Pushdown automata

Finite automata

Turing machine: example (2)

- A possible solution is given by the following state transition diagram:

State	Input	
	0	1
E_1	E_1/d	E_2/d
E_2	$E_3/1$	E_2/d
E_3	E_4/e	E_3/d
E_4	—	$E_5/0$
E_5	E_5/e	$E_6/0$
E_6	E_7/e	—
E_7	E_1/h	E_7/e

- $E_1 \dots 0111101110 \dots \rightarrow E_1 \dots 0111101110 \dots \xrightarrow{*} E_2 \dots 0111101110 \dots \rightarrow$
 $E_3 \dots 0111111110 \dots \rightarrow E_3 \dots 0111111110 \dots \xrightarrow{*} E_3 \dots 0111111110 \dots \rightarrow$
 $E_4 \dots 0111111110 \dots \rightarrow E_5 \dots 0111111100 \dots \rightarrow E_5 \dots 0111111100 \dots \rightarrow$
 $E_6 \dots 0111111000 \dots \rightarrow E_7 \dots 0111111000 \dots \xrightarrow{*} E_7 \dots 0111111000 \dots$

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis
Syntax Analysis
Semantic Analysis
Synthesis

Implementation of a Compiler

Lexical analysis
Syntax parsing
Semantic analysis
Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology
Operations on words
Operations on languages


Introduction to grammars

Chomsky hierarchy
Automatons

Turing Machine

Linearly bounded
automata
Pushdown automata
Finite automata

Linearly bounded automata



- They differ from MT by the finitude of the tape.

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons


Turing Machine

Linearly bounded automata

Pushdown automata

Finite automata

Pushdown automata



- "Head" is read-only and supports an unbounded stack.
- Movement of the "head" in one direction only.
- Automata suitable for parsing.

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy


Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata



- No state machine write support.
- Automata suitable for lexical analysis.

Frame

Programming languages

Compilers: Introduction

Structure of a Compiler

Lexical Analysis

Syntax Analysis

Semantic Analysis

Synthesis

Implementation of a Compiler

Lexical analysis

Syntax parsing

Semantic analysis

Synthesis: code
interpretation

Languages: Definition as a Set

Basic concepts and
terminology

Operations on words

Operations on languages

Introduction to grammars

Chomsky hierarchy

Automatons

Turing Machine

Linearly bounded
automata

Pushdown automata

Finite automata