



universidade de aveiro
theoria poiesis praxis

ARQUITETURA DE REDES


NAT/SNAT & STATIC/DYNAMIC DEFAULT ROUTES

Objectives

- NAT, PAT, SNAT
- Dynamic default routes propagation
- Weighted static routes

NAT/PAT and Stateful NAT (SNAT) mechanisms

1. Configure the following network according to the following figure and the following constraints:
- Router2 and Router3 have the following pool of IP public addresses: 193.136.0.1-128
 - Routers1, 2 and 3 have OSPF routing protocol active in the interfaces connected to the private networks, Router1 should have a **dynamic** preferential default route via Router3.
 - Router4 should have a **static** route to network 192.136.0.0/24 via Router2.



Specific configurations. Basic configurations are not included.

#In Router2

```
Router2(config)# router ospf 1
Router2(config-router)# network 192.168.1.0 0.0.0.255 area 0
#To announce default route with metric 10 (not preferred/backup)
Router2(config-router)# default-information originate always metric 10
```

#Default route via 192.1.1.2

```
Router2(config)# ip route 0.0.0.0 0.0.0.0 192.1.1.2
```

#In Router3

```
Router3(config)# router ospf 1
Router3(config-router)# network 192.168.2.0 0.0.0.255 area 0
#To announce default route with metric 5 (preferred)
Router3(config-router)# default-information originate always metric 5
```

#Default route via 192.2.2.2

```
Router3(config)# ip route 0.0.0.0 0.0.0.0 192.2.2.2
```

#In Router4

#Creation/activation of a loopback interface

```
Router4(config)# interface Loopback0
Router4(config-if)# ip address 192.3.3.4 255.255.255.0
Router4(config-if)# no shutdown
```

#Weighted static routes to network 193.136.0.0/24

#using Router 2 metric 1 (preferred)

```
Router4(config)# ip route 193.136.0.0 255.255.255.0 192.1.1.1
```

#using Router 3 metric 10 (not preferred/backup)

```
Router4(config)# ip route 193.136.0.0 255.255.255.0 192.2.2.1 10
```

2. Verify the full connectivity within the private networks. Test the connectivity between Router1 and Router4's Loopback0 interface. Explain the obtained results.

3. Activate the NAT/PAT mechanism in Router2 and Router3. Test the connectivity between Router1 and Router4's Loopback0 interface. Explain the obtained results.

#In Router2

#Private networks

```
Router2(config)# access-list 1 permit 192.168.1.0 0.0.0.255
Router2(config)# access-list 1 permit 192.168.2.0 0.0.0.255
```

#Public addresses pool

```
Router2(config)# ip nat pool POOLR 193.136.0.1 193.136.0.128 netmask 255.255.255.0
```

#Association between public pool address and private networks (NAT+PAT)

```
Router2(config)# ip nat inside source list 1 pool POOLR overload
```

#In Router3

#Private networks

```
Router3(config)# access-list 1 permit 192.168.1.0 0.0.0.255
Router3(config)# access-list 1 permit 192.168.2.0 0.0.0.255
```

#Public addresses pool

```
Router3(config)# ip nat pool POOLR 193.136.0.1 193.136.0.128 netmask 255.255.255.0
```

#Association between public pool address and private networks (NAT+PAT)

```
Router3(config)# ip nat inside source list 1 pool POOLR overload
```

Activate the NAT mechanisms at the respective interfaces using the commands `ip nat inside` and `ip nat outside`. Verify the NAT mechanism status (in Router2 and Router3) with the commands:

```
show ip nat translations
show ip nat translations verbose
```

4. Activate the SNAT mechanism between Router2 and Router3 (Router3 as primary and Router2 as backup). Test the connectivity between Router1 and Router4's Loopback0 interface. Explain the obtained results.

#In Router2

#SNAT configuration

```
Router2(config)# ip nat Stateful id 2
Router2(config-ipnat-snat)# backup 192.168.1.2
Router2(config-ipnat-snat-bkp)# peer 192.168.2.3
Router2(config-ipnat-snat-bkp)# mapping-id 10
```

#Association between public pool address and private networks (NAT+PAT+SNAT)

```
Router2(config)# no ip nat inside source list 1 pool POOLR overload
Router2(config)# ip nat inside source list 1 pool POOLR mapping-id 10 overload
```

#In Router3

#SNAT configuration

```
Router3(config)# ip nat Stateful id 3
Router3(config-ipnat-snat)# primary 192.168.2.3
Router3(config-ipnat-snat-bkp)# peer 192.168.1.2
Router3(config-ipnat-snat-bkp)# mapping-id 10
```

#Association between public pool address and private networks (NAT+PAT+SNAT)

```
Router3(config)# no ip nat inside source list 1 pool POOLR overload
Router3(config)# ip nat inside source list 1 pool POOLR mapping-id 10 overload
```

Verify the SNAT mechanism status (in Router2 and Router3) with the commands:

```
show ip snat distributed verbose
```