Vehicular Networks

Mestrado em Engenharia de Computadores e Telemática

2021/2022

Vehicular Ad Hoc Networks

The VANET can provide

- Safety
- Efficiency
- Traffic and road conditions
- Road signal alarm
- Local information



Vehicular networks

- Vehicle-to-vehicle *(V2V)* and vehicle-to-infrastructure (*V2I)* communication will be possible
- On-board units in vehicles to perform communication, routing and application
- Road-side infrastructure units (RSUs), named network nodes, are equipped with on-board processing and wireless communication modules



Vehicular networks



Warnings







Traffic and road conditions

Safety


6
6
6
4
3
2
1
5




a)


STS ACTIVE
b)


Oncoming Vehicles
Warns drivers of lane closings and reduced speeds when approaching incident zones.
Merge Left
ADVISORY
ALERT
WARNING
STOP
REDUCED SPEED SAFETY ZONE
Responder Vehicles
Warns on-scene responders of vehicles approaching the incident zone at speeds or in lanes that pose a high risk to their safety.


N

Efficiency


Ride
Share
Ride
Share


LIACC


1 MINUTE DELAY
AWAITING BUS TRANSFER RIDERS

SelfDriving

Other types of vehicular networks



Other types of vehicular networks





How do they work?



Awareness and warning information

- Cooperative Awareness Messages (CAM)
  - Periodic
  - Contain information about the station such as the position and speed
- Decentralized Environmental Notification Messages (DENM)
  - Asynchronous
  - Contain information about the event and the station that generated the message



Cooperative awareness messages



- Create and maintain awareness of vehicles using the road network or RSUs.
- The content varies depending on the type of ITS-S:
  - Vehicles: time, position, motion state, activated systems (*e.g.*, cruise control, pedals, and others), and the attribute information includes data about the dimensions, vehicle type, and role in the road traffic;
  - RSUs: station type and location.
- HF (High-Frequency) container with the fast-changing vehicle data (such as location, heading, or speed)
- LF (Low-Frequency) container with static or slow-changing data (such as the status of the exterior lights or pedals).

Cooperative awareness messages

- CAMs have generation requirements, with the generation frequency between 1 Hz and 10 Hz.
- The HF container must be in every CAM message, while the low-frequency container can be updated at a maximum of 5 Hz frequency.
- The generation process must be effective, since the difference between CAM generation time and the time at which the CAM is delivered to networking transport layer shall be less than 50 ms.

CAM Information	Basis Container	ITS-Station Type
		Last Geographic Position
	High Frequency Container	Speed
		Driving Direction
		Longitudinal Acceleration
		Curvature
		Vehicle Length
		Vehicle Width
		Steering Angle
		Lane Number
		…
	Low Frequency Container	Vehicle Role
		Lights
		Trajectory
	Special Container	Emergency
		Police
		Fire Service
		Road Works
		Dangerous Goods
		Safety Car
		…

Decentralized environmental notification messages



- Asynchronous messages to create and maintain awareness about a road event - *e.g.* road hazard or an abnormal traffic condition - such as its type, position, validity, timestamp and the history of the event.
- While the content varies depending on the type of event, it is expected that at least the detection time, the position of the event, the type of the related station and a set of cause codes identifying the type of event are present.
- Containers for certain types of events - such as the Road Works
- Stationary Vehicle Containers.

Decentralized environmental notification messages

- Unlike CAMs, DENMs are generated as events occur, and thus, they are not generated periodically.
- They have a validity period, which after ending, means the DENM can no longer be considered up-to-date.
- When an event is no longer occurring, a particular type of DENM, a termination DENM, can be used to signal the end of the event - *e.g.* the end of the road hazard or of adverse weather conditions.

DENM Information	Management Container	Last Vehicle Position (GPS)
		Event Identifier
		Time of Detection
		Time of Message Transmission
		Event Position (GPS)
		Validity Period
		Station Type (Motor Cycle, Vehicle, Truck)
		Message Update / Removal
		Relevant Local Message Area (geographic)
		Traffic Direction (forward, backwards, both)
		Transmission Interval
		….
	Situation Container	Information Quality (low -high, tbd)
		Event Type (Number)
		Linked Events
		Event Route (geographical)
	Location Container	Event Path
		Event Speed
		Event Direction
		Road Type
	A la carte Container	Road Works (Speed Limit, Lane Blockage….)
		….





Vulnerable Road User Awareness Message



- Periodic messages exchanged in the ITS network between stations to create and maintain awareness on VRUs, and support the risk assessment
- Basic status: time, position, speed, heading, yaw rate and acceleration, orientation, lane position, dimensions and VRU type.
- Advantages of a VAM standard message over the usage of a CAM
  - flexibility in terms of fully specifying the VRU type and situation, which is not possible without changing the CAM standard (therefore defeating the purpose of using a standard).



Vulnerable Road User Awareness Message

- VAMs can distinguish between several types of VRU - pedestrian, cyclist, motorcyclist, animal
- Within each category, they can distinguish several possible roles (*e.g.* for a cyclist VRU, between bicyclist, a wheelchair user, a horse rider, a roller skater, an e-scooter, and others).
- This distinction is crucial: several different VRUs - for example, a child pedestrian or a disabled pedestrian - have different dynamics from a typical pedestrian. That information can be used, for example, by safety services to fine-tune an accident prediction algorithm.

Cooperative Perception Message



- Periodic messages between stations to broadcast information about the current environment a perceived by 1 or more sensors.
- Sensors from a vehicle, a VRU and infrastructure can use CPMs to exchange the information obtained from their surroundings, improving the awareness of the situation.
- Sensor Information Container: sensor type - *e.g.* Radar, Lidar, video cameras or fusion algorithms, and the area the sensor covers.
- Perceived Object Container: objected perceived by the sensor, the classification, the confidence of the classification, and several data about its dynamics, such as distance, speed, acceleration and angle.

Examples of objects in CPMs



: Describing the setup of trailers attached to a towing vehicle in the CPM



Coordinate System for detected object for vehicle

SPAT: Signal Phase And Timing

- Defines an open interface for two-way communication between traffic signal controller and mobile devices
- Current movement state of each active phase
  - Safety applications, such as warnings and alerts for crash avoidance, red light violations
  - Mobility applications to enable dynamic and efficient traffic management
  - Environment applications that allow savings in fuel consumption and reduction in CO2 emissions
- Current state of all lanes at the intersection are provided, as well as any active preemption or priority

SPAT: Signal Phase And Timing



SPAT: Signal Phase And Timing

- Intersection state
- Movement state
  - Lane set (lanes 9-10 are for movement state 1)
  - Current state (green, yellow, red)
  - Time until current signal state changes

- Used in cooperation with a **map**



SPAT: State diagram



They can be used virtually





MAP: MAP

- Geometric layout of intersection
- Message data
  - Reference point (intersection center)
  - Number of approaches
  - Lane number
  - Lane width
  - Lane attributes
    - Straight, left, right, turn on red, speed limit, bus, etc...
  - Offsets
    - Points along each lane – used to detect vehicle position



Example of a MAP information

refPoint [Position3D]	The Position3D data frame provides a precise location in the WGS-84 coordinate system, from which short offsets may be used to create additional data using a flat earth projection centred on this location.	
laneWidth [LaneWidth]	The LaneWidth data element conveys the width of a lane in units of 1 cm.	
speedLimits [SpeedLimitList] (1..9)	The SpeedLimitList data frame consists of a list of SpeedLimit entries.	RegulatorySpeedLimit The RegulatorySpeedLimit data frame is used to convey a regulatory speed about a lane, lanes, or roadway segment.
[laneSet] LaneList (1..255)	The LaneList data frame consists of a list of GenericLane entries.	GenericLane The GenericLane data frame is used for all types of lanes, e.g. motorized vehicle lanes, crosswalks, medians. The GenericLane describes the basic attribute information of the lane.
preemptPriorityData [PreemptPriorityList] (1..32)	The PreemptPriorityList data frame consists of a list of RegionalSignalControl-Zone entries.	SignalControlZone



Communication Technologies

Critical Requirements for the Communication Technologies

- Range (>200-400m)
- Delays (<10msec)
- Time for communication when in range (<10-20msec)
- Bandwidth (>10Mbsec.... → as much as possible)

ITS-G5 (DSRC, IEEE 802.11p)

- Based on IEEE 802.11a with PHY and MAC extensions
- Frequency: 5.9GHz
- Range: LoS it can go up to 1Km
  - Prone to obstructions: buildings, trees, cars
- Delay: < 10msec
- Time for communication when in range (10-20msec)
- Rate up to 27Mb/sec in the largest mode (usual is 12Mb/sec)

C-V2X (LTE-based 3GPP Rel 14)

- Based on 3GPP Rel 14
- Frequency: 5.9GHz
- Range: LoS it can go up to 1Km
  - Prone to obstructions: buildings, trees, cars
- Delay: < 20msec
- Time for communication when in range (~100msec?)
- Rate up to 150Mb/sec in the largest mode

ITS-G5


Layers
* CEN/ISO Blue: ETSI
Core Standards – Release 1
Applications
Facilities
Networking & Transport
Access Technologies
Management
Other Applications
Safety and Traffic Efficiency App
V2X Messages
TCP/UDP (IETF RFC 793/768)
IPv6 (RFC 2460)
GN6
BTP GeoNetworking
MAC Extensions
MAC
PHY
Security
TS 102 539 † RHS, ICRW, LCRW
EN 302 637 † CAM, DENM
TS 19 091 * SPAT, MAP
TS 19 321 * IVI
EN 302 636 † GN, BTP, GN6
TS 103 097 † Security
TS 102 941 † Privacy
EN 302 663 † ITS-G5
TS 102 724 † Multi-channel
TS 102 687 † DCC framework
TS 103 175 † DCC management

ITS-G5 vs C-V2X



ITS-G5, C-V2X, 5G (Standalone)

Parameters	ITS-G5	C-V2X (LTE Rel. 14)	Future 5G SA
Currently available technology	Yes	Yes	No
Field trials (+10 years)	Yes	No	No
Applications	V2V, V21	V2V, V2I, V2N	V2V, V2I, V2N
Latency	5 ms	20 ms	<5 ms
Data rate	3-27 Mbps	150 Mbps	10 Gbps
Multimedia and cloud services support	No	Yes	Yes

ITS-G5 vs C-V2X (Simulation)



(a) *Empirical-size model*. 120 veh/km (CBR~0.33)



(b) *Empirical-time model*. 200 veh/km (CBR~0.23)

ITS-G5 vs C-V2X (Qualcomm)





ITS-G5 vs C-V2X (NXP)



https://www.etsi.org/deliver/etsi_ts/102600_102699/10263702/01.02.01_60/ts_10263702v010201p.pdf

https://www.etsi.org/deliver/etsi_ts/102600_102699/10263703/01.01.01_60/ts_10263703v010101p.pdf

https://www.etsi.org/deliver/etsi_tr/103500_103599/103562/02.01.01_60/tr_103562v020101p.pdf

https://www.etsi.org/deliver/etsi_ts/103300_103399/10330003/02.01.01_60/ts_10330003v020101p.pdf

https://www.etsi.org/deliver/etsi_ts/103100_103199/10319103/01.01.01_60/ts_10319103v010101p.pdf

https://www.crow.nl/downloads/pdf/verkeer-en-vervoer/verkeersmanagement/landelijke-ivri-standaarden/d3046-2_spat-profile.aspx

https://www.crow.nl/downloads/pdf/verkeer-en-vervoer/verkeersmanagement/landelijke-ivri-standaarden/d3046-1_map-profile.aspx