

Homework 4

1 Sorting in Place in Linear Time

(2pts) Suppose that we have an array of n data records to sort and that the key of each record has the value 0 or 1. An algorithm for sorting such a set of records might possess some subset of the following three desirable characteristics:

1. The algorithm runs in $O(n)$ time.
 2. The algorithm is stable.
 3. The algorithm sorts in place, using no more than a constant amount of storage space in addition to the original array.
- (a) Give an algorithm that satisfies criteria 1 and 2 above.
 - (b) Give an algorithm that satisfies criteria 1 and 3 above.
 - (c) Give an algorithm that satisfies criteria 2 and 3 above.
 - (d) Can any of your sorting algorithms from parts(a)–(c) be used to sort n records with b -bit keys using radix sort in $O(bn)$ time? Explain how or why not.
 - (e) Suppose that the n records have keys in the range from 1 to k . Show how to modify counting sort so that the records can be sorted in place in $O(n + k)$ time. You may use $O(k)$ storage outside the input array. Is your algorithm stable? (Hint: How would you do it for $k = 3$?)

2 Alternative Quicksort Analysis

(2pts) An alternative analysis of the running time of randomized quicksort focuses on the expected running time of each individual recursive call to QUICKSORT, rather than on the number of comparisons performed.

- (a) Argue that, given an array of size n , the probability that any particular element is chosen as the pivot is $1/n$. Use this to define indicator random variables $X_i = I\{i\text{th smallest element is chosen as the pivot}\}$. What is $E[X_i]$?
- (b) Let $T(n)$ be a random variable denoting the running time of quicksort on an array of size n . Argue that

$$E[T(n)] = E \left[\sum_{q=1}^n X_q (T(q-1) + T(n-q) + \Theta(n)) \right] \quad (1)$$

(c) Show that equation 1 simplifies to

$$E[T(n)] = \frac{2}{n} \sum_{q=0}^{n-1} E[T(q)] + \Theta(n) \quad (2)$$

(d) Show that

$$\sum_{k=1}^{n-1} k \lg k \leq \frac{1}{2} n^2 \lg n - \frac{1}{8} n^2 \quad (3)$$

(Hint: Split the summation into two parts, one for $k = 1, 2, \dots, \lceil n/2 \rceil - 1$ and one for $k = \lceil n/2 \rceil, \dots, n - 1$.)

(e) Using the bound from equation 3, show that the recurrence in equation 2 has the solution $E[T(n)] = \Theta(n \lg n)$. (Hint: Show, by substitution, that $E[T(n)] \leq an \log n - bn$ for some positive constants a and b .)

3 Red-Black Trees

I am attaching a binary tree source code (`bst-0.0.cpp`) with the methods `insert`, `delete`, and `print`. Your job would be to implement a Red-Black Tree, adapting the functions `insert`, `remove`, and `print` as convenient. To test your code, you can follow the examples described in the document `anexo1.pdf`. Also, you might be interested in the document `anexo2.pdf` for a more detailed description of this tree, there is also some Java code that might be useful. However, your code must be in C++ and modifying the attached code. The grading will be as follow:

(a) **(2pts)** `insert`

(b) **(2pts)** `remove`

An example of the main function is:

```
1 int main() {
2     // this constructor must call the function insert multiple times
3     // respecting the order
4     RBTree tree(41, 38, 31, 12, 19, 8);
5     tree.print();
6
7     // testing the remove function
8     tree.remove(8);
9     tree.print();
10 }
```

4 Radix Sort

(2pts) Your job is to implement the radix sort algorithm described in class. You must use python for this task. The following code is going to be used to test your implementation. You have to submit a notebook with your code.

```
1 def radix_sort(A, d, k):
2     # A consists of n d-digit ints, with digits ranging 0 -> k-1
3     #
4     # implement your code here
5     # return A_sorted
6
7
```

```
8 # Testing your function
9 A = [201, 10, 3, 100]
10 A_sorted = radix_sort(A, 3, 10)
11 print(A_sorted)
12 # output: [3, 10, 100, 201]
```
