










## Interior Lighting.

No.	Specification Description	Symbol	Manufacturer	Quantity	Remarks
1	<b>Ceiling Recessed Down Light.</b>	ADN1	<b>ABBY Lighting</b>	14.00 Nos	
	<b>Housing :</b> Die Cast Aluminium		Go Pro 70 PF - 30W		
	<b>Accessory :</b>				
	<b>Lamp:</b> 30W LED, 30°optics. 3000K. <b>CRI</b> =80				
	<b>Lumen Output :</b> 2300lm				
	<b>Control Gear:</b> Remote Dimmable Driver (0-10V Analogue).				
	<b>Power Consumption:</b> 30W				
	<b>IP44</b>				
2	<b>Strip Light With Rigid Aluminium Channel &amp; frosted Cover/lens</b>	COV1	<b>YYZ Lighting</b>	290.0 Mtrs	
	<b>Housing :</b> Anodized Aluminium Extrusion, Polycarbonate Lens		LFX-O-14.4W-CT30		
	<b>Accessory :</b> Alu. channel & Frosted cover.				
	<b>Lamp:</b> 14.4W/m LED . 3000K. <b>CRI</b> = >90				
	<b>Lumen Output :</b> 1300 lm/m				
	<b>Control Gear:</b> . Remote Dimmable driver. (0 – 10V Analogue)				
	<b>Power Consumption:</b> 14.4W/m				
	<b>IP20</b>				
3	<b>Ceiling Recessed Downlight.</b>	DNL1	<b>ABBY LIGHTING</b>	10.0 Nos	
	<b>Housing :</b> Die Cast Aluminium.		Go Pro 35 PF-12W		
	<b>Accessory :</b> -				
	<b>Lamp:</b> 12W LED, 28°optics. 3000K. <b>CRI</b> = 80				
	<b>Lumen Output :</b> 1100lm				
	<b>Control Gear:</b> Remote analogue dimmable Driver				
	<b>Power Consumption:</b> 12W				
	<b>IP44</b>				

4	<b>Surface Mounted Downlight</b>	SDN1	<b>UNILAMP LIGHTING</b>	18.0 Nos	
	<b>Housing</b> :High-pressure Die Cast Aluminium alloy body and components.		4002-6-3-902-XX		
	<b>Accessory</b> : -				
	<b>Lamp</b> : 19W LED, 23°optics, 3000K. <b>CRI</b> =80				
	<b>Lumen Output</b> : 2180lm				
	<b>Control Gear</b> : Integral constant current driver.				
	<b>Power Consumption</b> : 19W				
	<b>IP65</b>				
5	<b>Suspended LED Downlight</b>	SDN2	<b>ABBY LIGHTING</b>	14.0 Nos	
	<b>Housing</b> : Aluminium extrusion		iBarrel P		
	<b>Accessory</b> : suspension cable				
	<b>Lamp</b> : 15W LED, 22° optics, 3000K. <b>CRI</b> =80				
	<b>Lumen Output</b> : 1500lm				
	<b>Control Gear</b> : Integral analogue dimmable Driver.				
	<b>Power Consumption</b> : 15W				
	<b>IP20</b>				
6	<b>Suspended Ring Fixture.(Dia = 1500mm)</b>	SRF1	<b>ABBY LIGHTING</b>	4.0 Nos	
	<b>Housing</b> : Extruded Aluminium, Frosted acrylic diffuser		Hoopla Soft 150		
	<b>Accessory</b> : Suspension kit				
	<b>Lamp</b> : (75W LED, Customised) 15W/m LED, 3000K. <b>CRI</b> =80				
	<b>Lumen Output</b> : 1000lm/m				
	<b>Control Gear</b> : Integral analogue dimmable Driver.				
	<b>Power Consumption</b> : 15W/m				
	<b>IP20</b>				

7	<b>Suspended Ring Fixture.(Dia = 1200mm)</b>	SRF2	<b>ABBY LIGHTING</b>	6.0 Nos	
	<b>Housing :</b> Extruded Aluminium, Frosted acrylic diffuser		Hoopla Soft 120		
	<b>Accessory :</b> Suspension kit				
	<b>Lamp:</b> (60W LED, Customised) 15W/m LED, 3000K, CRI=80				
	<b>Lumen Output :</b> 1000lm/m				
	<b>Control Gear:</b> Integral analogue dimmable Driver.				
	<b>Power Consumption:</b> 15W/m				
	IP20				
8	<b>LED Marker Light Integrated in Step Nosing.</b>	STP1	<b>SHRIKRISHNASHRAY</b>	90.0 Mtrs	
	<b>Housing :</b> Extruded aluminium, End-lit fibre optic rod		SKS102		
	<b>Accessory :</b>				
	<b>Lamp:</b> 0.25W LED, 3000K, CRI = --				
	<b>Lumen Output :</b> -- lm/mt				
	<b>Control Gear:</b> Remote Power supply				
	<b>Power Consumption:</b> 0.25W				
	IP20				
9	<b>Wall Recessed Light.</b>	WRL1	<b>K-LITE</b>	15.0 Nos	
	<b>Housing :</b> Die cast aluminium		2743		
	<b>Accessory :</b> mounting sleeve				
	<b>Lamp:</b> 12W LED Forward Asymmetrical, 3000K, CRI =80+				
	<b>Lumen Output :</b> 300lm				
	<b>Control Gear:</b> Integral Constant Current Driver.				
	<b>Power Consumption:</b> 12W				
	IP65				