



Facade Lighting

No.	Specification Description	Symbol	Manufacturer	Quantity	Remarks
1	InGround Uplighter, adjustable	IGU1	UNILAMP Lighting	12	
	Housing: High-pressure Die Cast Aluminium alloy body and components.			Nos.	
	Accessories: anti-glare louvre				
	Dimension: Trim Diameter = 129mm, Height=173mm,				
	Lamp: 8W LED, 12° optics, 3000K, CRI= 80+				
	Lumen Output : 700lm (customised)				
	Control Gear: . Remote LED Driver.				
	Power Consumption: 8W				
	IP67				
2	Floor Recessed Up-lighter (L=1000mm).	LLP1	YYZ LIGHTING	39	
	Housing: Extruded Aluminium		LRO- 36/48	Nos.	
	Accessories: Housing box				
	Dimension: length=1000mm, Width=90mm, Height=80mm				
	Lamp: 24W/m LED, 15° optics, 3000K, CRI=80+				
	Lumen Output : 2700lm				
	Control Gear: Remote power supply 24 V DC.				
	Power Consumption: 36W/m				
	IP67				
3	Floor Recessed Up-lighter (L=500mm).	LLP1a	YYZ LIGHTING	14	
	Housing: Extruded Aluminium		LRO- 36/48	Nos.	
	Accessories: Housing Box				
	Dimension: length=500mm, Width=90mm, Height=80mm				
	Lamp: 24W/m LED (12W / Fixture), 15° optics, 3000K, CRI=80+				
	Lumen Output : 1350lm				
	Control Gear: Remote power supply 24 V DC.				
	Power Consumption: 18W/m				
	IP67				

4	Rigid LED strip-light.	LST1	YYZ LIGHTING	35	
	Housing: UV Resistant PVC Encapsulation		LFX-O-14.4W-CT30	Mtrs.	
	Accessories: Rigid Aluminium Channel, Frosted Diffuser,				
	Dimension: Width=17mm, Height=10 mm				
	Lamp: 14.4W/m LED, 3000K, CRI=80+				
	Lumen Output : 1300lm/m				
	Control Gear: Remote driver.				
	Power Consumption: 14.4W/m				
	IP67				
5	Wall Mounted Luminaire.	WML1	UNILAMP LIGHTING	10	
	Housing: High-pressure Die Cast Aluminium alloy body and components.		7029-0-3-902-XX	Nos.	
	Accessories:				
	Dimension: Height=219mm, TrimØ=324mm				
	Lamp: 18W LED, 3000K, CRI=80+				
	Lumen Output : 1320lm				
	Control Gear: Integral constant current driver.				
	Power Consumption: 18W				
	IP65				