## PB1L

## Pushbutton/Raised pushbutton/Illuminated pushbutton/Raised illuminated pushbutton

Name	Туре	Status	Model	Color	Rated voltage of illumination module	Dimensions
Pushbutton	4	Momentary	PB1L-■/▲	red-r green-g yellow-y		
		Maintained	PB1L-■T/▲	blue-b white-w black-k		
Raised pushbutton		Momentary	P81L-■/▲-H	red-r green-g yellow-y		
		Maintained	PB1L-■T/▲-H	blue-b white-w black-k		
lluminated pushbutton		Momentary	PB1L-■D/▲★	red-ir green-g yellow-y	21-AC/DC 6V 22-AC/DC 12V 23-AC/DC 24V 25-AC/DC48V 26-AC/DC110V	
		Maintained	PB1L-■TD/▲★	blue-b white-w	28-DC220V 31-AC220V 32-AC380V	
Raised		Momentary	P81L-■D/▲★-H	red-r green-g yellow-y	21-AC/DC 6V 22-AC/DC 12V 23-AC/DC 24V 25-AC/DC46V 26-AC/DC110V	
pushbutton		Maintained	PB1L-■TD/▲★-H	blue-b white-w	28-DC220V 31-AC220V 32-AC380V	

## Notes:

- 1. 

  The type of contact module.
- 2 ▲ :The color of handle.
- 3. \* : Rated voltage of illumination module.