

SiScLab Project 8

Katta, Partmann, Wasmer

January 24, 2019

Problem Statement

- Solid state physics: electronic structure computation
 - → Fleur: electronic structure of crystals using DFT
 - huge amount of data
 - physics not accessible unless structured / analysed / visualized

The goal of the project was to implement a complete data analysis pipeline for this application:

- preprocessing → data exploration → visualization

Motivation

- Physicists problem with the simulation data
- fast computation time
- code modularization
- intuitive usage
- high-quality export features

Requirements

- process Fleur output files
- fast computation
- code: modularization, easy maintainability
- frontend: no installation required, intuitive usage
- plots: publication-quality export

Steps



- Understanding physics and problem
- preprocessing the data
- exploring the data(implementation)
- visualization(GUI)
- Results

How is the data generated?

- Fluer computes electron density in crystals
- Density functional theory (DFT) approach:
 - Hohenberg Kohn theorem: use electron density
 - Kohn Sham system: Solve one particle Schrödinger equations in effective potential (self consistent)
 - State of the art method for electronic structure computations in solids


What data is generated?

- Bandstructure $E_\nu(k)$:
 - Eigenenergies of (Bloch-) Eigenfunctions of the Hamiltonian for each (crystal-) momentum k
 - Dispersion relation: Relation between crystal momentum and Energies of the Bloch electrons
 - Sampled along a 1d Path between high symmetry points in 3d reciprocal space




- Bandstructure $D(E)$:
 - Density of electron states per energy interval
- Interesting for Physicist: Where do the contributions to $E(k)$ and $D(E)$ come from?
 - Contributions from Basis functions of the DFT calculation corresponding to different Atomgroups and atomic orbitals (s, p, d, f)
 - User might be interested in any superposition of them (e.g. to locate states in real space)
 - Information stored in form of weights for all Atom Groups and the atomic orbitals s, p, d, f


Module Design Goals




Multifunctionality:

- automated workflows like in  AiiDA
- manual data analysis with Python


Module Design Goals




Multifunctionality:

- automated workflows like in  AiiDA
 - manual data analysis with Python
-
- no boilerplate code!

Module Design Goals



Multifunctionality:

- automated workflows like in  AiiDA
 - manual data analysis with Python
-

- no boilerplate code!
-

- Desktop 
- Web    like in  AiiDA lab

Preprocessor Module

Input: Fleur calculation results
stored in Hierarchical Data
Format (HDF).

- modular output types for application domain (e.g. viz)
- dependency resolution

Preprocessor Module

Input: Fleur calculation results stored in Hierarchical Data Format (HDF).

Module uses *type introspection* to enable features:

- modular output types for application domain (e.g. viz)
- dependency resolution


Preprocessor Module

Input: Fleur calculation results stored in Hierarchical Data Format (HDF).

Module uses *type introspection* to enable features:

- modular output types for application domain (e.g. viz)
- dependency resolution

Preprocessor Module




Input: Fleur calculation results stored in Hierarchical Data Format (HDF).

Module uses *type introspection* to enable features:

- modular output types for application domain (e.g. viz)
- dependency resolution

Preprocessor Module



Input: Fleur calculation results stored in Hierarchical Data Format (HDF).

Module uses *type introspection* to enable features:

- modular output types for application domain (e.g. viz)
- dependency resolution

Data Selection for Viz

The main compute-intensive routine:

$$W_{s,k,\nu}^{\text{eff}} = \left(\frac{\sum_{\substack{g \in \text{groups} \\ c \in \text{characters}}} n_{s,k,\nu,g,l} N_g}{\sum_{\substack{g \in \text{all groups} \\ c \in \text{all characters}}} n_{s,k,\nu,g,l} N_g} \right) \left(W_{s,k,\nu}^{\text{unf}} \right)^\alpha$$

- $W_{s,k,\nu}^{\text{eff}}$: effective weight
- $n_{s,k,\nu,g,l}$: State-specific l -like charge
- N_g : no. of atoms in group
- $W_{s,k,\nu}^{\text{unf}}$: unfolding weight; $\alpha = 0 \implies$ no unfolding

Data Selection for Viz

The main compute-intensive routine:

$$W_{s,k,\nu}^{\text{eff}} = \left(\frac{\sum_{\substack{g \in \text{groups} \\ c \in \text{characters}}} n_{s,k,\nu,g,l} N_g}{\sum_{\substack{g \in \text{all groups} \\ c \in \text{all characters}}} n_{s,k,\nu,g,l} N_g} \right) \left(W_{s,k,\nu}^{\text{unf}} \right)^\alpha$$

- $W_{s,k,\nu}^{\text{eff}}$: effective weight
- $n_{s,k,\nu,g,l}$: State-specific l -like charge
- N_g : no. of atoms in group
- $W_{s,k,\nu}^{\text{unf}}$: unfolding weight; $\alpha = 0 \implies$ no unfolding

Data Selection for Viz

The main compute-intensive routine:

$$W_{s,k,\nu}^{\text{eff}} = \left(\frac{\sum_{\substack{g \in \text{groups} \\ c \in \text{characters}}} n_{s,k,\nu,g,l} N_g}{\sum_{\substack{g \in \text{all groups} \\ c \in \text{all characters}}} n_{s,k,\nu,g,l} N_g} \right) \left(W_{s,k,\nu}^{\text{unf}} \right)^\alpha$$

- $W_{s,k,\nu}^{\text{eff}}$: effective weight
- $n_{s,k,\nu,g,l}$: State-specific l -like charge
- N_g : no. of atoms in group
- $W_{s,k,\nu}^{\text{unf}}$: unfolding weight; $\alpha = 0 \implies$ no unfolding

Data Selection for Viz

The main compute-intensive routine:

$$W_{s,k,\nu}^{\text{eff}} = \left(\frac{\sum_{\substack{g \in \text{groups} \\ c \in \text{characters}}} n_{s,k,\nu,g,l} N_g}{\sum_{\substack{g \in \text{all groups} \\ c \in \text{all characters}}} n_{s,k,\nu,g,l} N_g} \right) \left(W_{s,k,\nu}^{\text{unf}} \right)^\alpha$$

- $W_{s,k,\nu}^{\text{eff}}$: effective weight
- $n_{s,k,\nu,g,l}$: State-specific l -like charge
- N_g : no. of atoms in group
- $W_{s,k,\nu}^{\text{unf}}$: unfolding weight; $\alpha = 0 \implies$ no unfolding

Data Selection for Viz

The main compute-intensive routine:

$$W_{s,k,\nu}^{\text{eff}} = \left(\frac{\sum_{\substack{g \in \text{groups} \\ c \in \text{characters}}} n_{s,k,\nu,g,l} N_g}{\sum_{\substack{g \in \text{all groups} \\ c \in \text{all characters}}} n_{s,k,\nu,g,l} N_g} \right) \left(W_{s,k,\nu}^{\text{unf}} \right)^\alpha$$

- $W_{s,k,\nu}^{\text{eff}}$: effective weight
- $n_{s,k,\nu,g,l}$: State-specific l -like charge
- N_g : no. of atoms in group
- $W_{s,k,\nu}^{\text{unf}}$: unfolding weight; $\alpha = 0 \implies$ no unfolding

Data Selection for Viz

Typically, $\sim 10^7$ data points are accessed.

Optimizations:

- reshaping $(\mathbf{k}, \nu) \rightarrow (\mathbf{k} \cdot \nu)$
 - weight filter t : $W_{s,\mathbf{k},\nu}^{\text{eff}} > t$
 - using optimized numpy functions for tensor product
 - buffering on selection change
- ➔ Speedup $\sim 10^2$

Data Selection for Viz

Typically, $\sim 10^7$ data points are accessed.

Optimizations:

- reshaping $(\mathbf{k}, \nu) \rightarrow (\mathbf{k} \cdot \nu)$
- weight filter t : $W_{s,\mathbf{k},\nu}^{\text{eff}} > t$
- using optimized numpy functions for tensor product
- buffering on selection change

➔ Speedup $\sim 10^2$

Data Selection for Viz

Typically, $\sim 10^7$ data points are accessed.

Optimizations:

- reshaping $(\mathbf{k}, \nu) \rightarrow (\mathbf{k} \cdot \nu)$
 - weight filter t : $W_{s,\mathbf{k},\nu}^{\text{eff}} > t$
 - using optimized numpy functions for tensor product
 - buffering on selection change
- ➔ Speedup $\sim 10^2$

Data Selection for Viz

Typically, $\sim 10^7$ data points are accessed.

Optimizations:

- reshaping $(\mathbf{k}, \nu) \rightarrow (\mathbf{k} \cdot \nu)$
 - weight filter t : $W_{s,\mathbf{k},\nu}^{\text{eff}} > t$
 - using optimized `numpy` functions for tensor product
 - buffering on selection change
- ➔ Speedup $\sim 10^2$

Data Selection for Viz

Typically, $\sim 10^7$ data points are accessed.

Optimizations:

- reshaping $(\mathbf{k}, \nu) \rightarrow (\mathbf{k} \cdot \nu)$
- weight filter t : $W_{s,\mathbf{k},\nu}^{\text{eff}} > t$
- using optimized `numpy` functions for tensor product
- buffering on selection change

→ Speedup $\sim 10^2$

Data Selection for Viz

Typically, $\sim 10^7$ data points are accessed.

Optimizations:

- reshaping $(\mathbf{k}, \nu) \rightarrow (\mathbf{k} \cdot \nu)$
- weight filter t : $W_{s,\mathbf{k},\nu}^{\text{eff}} > t$
- using optimized numpy functions for tensor product
- buffering on selection change

→ Speedup $\sim 10^2$

Data Selection for Viz

Typically, $\sim 10^7$ data points are accessed.

Optimizations:

- reshaping $(\mathbf{k}, \nu) \rightarrow (\mathbf{k} \cdot \nu)$
- weight filter t : $W_{s, \mathbf{k}, \nu}^{\text{eff}} > t$
- using optimized numpy functions for tensor product
- buffering on selection change

➔ Speedup $\sim 10^2$

Visualization Module


- Abstract interfaces for different viz. libs and applications
- `InteractiveControlDisplay` as frontend contracts

Visualization Module

- Abstract interfaces for different viz. libs and applications
- InteractiveControlDisplay as frontend contracts

Visualization Module

- Abstract interfaces for different viz. libs and applications
- InteractiveControlDisplay as frontend contracts



Powered by yFiles

Desktop Frontend


Choice of GUI Toolkit: **TKinter**, Kivy, PySide/PyQt, ...

Choice of Plotting tool: **matplotlib**

Web Frontend


The Python Visualization Landscape as of 2017...

The Python Visualization Landscape as of 2017...



Python Visualization Landscape by rougier / BSD-2


Web Frontend

- Needed: an OSS **Tool Selection Process** for building a Web Dashboard using **only** .
- Decision Priority Order: *support...*
 - I. ... *interactive graphical control elements ('widgets')*
 - II. ... *easy deployment*
 - III. ... *some actual plotting libraries*


Web Frontend

- Needed: an OSS **Tool Selection Process** for building a Web Dashboard using **only** .
- Decision Priority Order: *support...*
 - I. ... *interactive graphical control elements ('widgets')*
 - II. ... *easy deployment*
 - III. ... *some actual plotting libraries*


Web Frontend

- Needed: an OSS **Tool Selection Process** for building a Web Dashboard using **only** .
- Decision Priority Order: *support...*
 - I. ... *interactive graphical control elements ('widgets')*
 - II. ... *easy deployment*
 - III. ... *some actual plotting libraries*









Web Frontend

- Needed: an OSS **Tool Selection Process** for building a Web Dashboard using **only** .
- Decision Priority Order: *support...*
 - I. ... *interactive graphical control elements ('widgets')*
 - II. ... *easy deployment*
 - III. ... *some actual plotting libraries*

Web Frontend

- Needed: an OSS **Tool Selection Process** for building a Web Dashboard using **only** .
- Decision Priority Order: *support...*
 - I. ... *interactive graphical control elements ('widgets')*
 - II. ... *easy deployment*
 - III. ... *some actual plotting libraries*

Web Frontend
















I. Widgets	 jupyter	pyviz  panel	 bokeh	 dash
Languages			 / JS	 / JS

¹Excluded: writing from scratch using Flask

²workaround. See also: [appmode](#), [voila](#), [thebelab](#)

³interactive only

Web Frontend























I. Widgets	 jupyter	pyviz  panel	 bokeh	 dash
Languages			 / 	 / 
II. Deployment				
- Jupyter	✓	✓	✗	✗
- Standalone ¹	( binder, ) ²			 plotly

¹Excluded: writing from scratch using Flask

²workaround. See also: [appmode](#), [voila](#), [thebelab](#)

³interactive only

Web Frontend

I. Widgets	 jupyter	pyviz  panel	 bokeh	 dash
Languages			 / 	 / 
II. Deployment				
- Jupyter	✓	✓	✗	✗
- Standalone ¹	( binder, ) ²			 plotly
III. Plots ³				
- 2D	 mpl, bqplot, ...	 hvplot, 		
- 3D	ipyvolume	✗		

¹Excluded: writing from scratch using Flask

²workaround. See also: [appmode](#), [voila](#), [thebelab](#)

³interactive only

Effective mass and Fermi velocity:

- Derived Quantities:
- mass, that an electron in a crystal appears to have compared to a free electron (due to interactions in the solid)
- $m^* = \hbar^2 \frac{d^2 E(k)}{dk^2}$
- Group velocity at the Fermi energy
- $v_{Fermi} = \frac{dE(k)}{dk}$ at $E = E_F$
- Bandstructure periodic: Using FFT to compute accurate Derivates:
- \Leftrightarrow Differentiate finite Fourier Series
 $f^{(n)}(x) = \mathcal{F}^{-1}((ik)^n \mathcal{F}(f(x)))$