

The plugin otagrum: learning nonparametric Copula Bayesian Networks

Marvin LASSERRE

supervised by Pierre-Henri WUILLEMIN (LIP6) and Régis LEBRUN (Airbus CRT)

June 10, 2022



- **Why distributions ?** Because we are faced with uncertainties (lack of information, inherently uncertain problems),

- **Why distributions ?** Because we are faced with uncertainties (lack of information, inherently uncertain problems),
- **Why continuous ?** Because in applications such as physics, engineering or finance variables are often continuous,

- **Why distributions ?** Because we are faced with uncertainties (lack of information, inherently uncertain problems),
- **Why continuous ?** Because in applications such as physics, engineering or finance variables are often continuous,
- **Why non-parametric ?** Because parametric models such as Gaussian are too restrictive for certain applications such as anomaly detection, risk analysis or reliability analysis.

- **Why distributions ?** Because we are faced with uncertainties (lack of information, inherently uncertain problems),
- **Why continuous ?** Because in applications such as physics, engineering or finance variables are often continuous,
- **Why non-parametric ?** Because parametric models such as Gaussian are too restrictive for certain applications such as anomaly detection, risk analysis or reliability analysis.
- **Why high-dimensional ?** Because complex systems involve a large number of variables,

Context: learning high dimensional non-parametric continuous distributions

- **Why distributions ?** Because we are faced with uncertainties (lack of information, inherently uncertain problems),
- **Why continuous ?** Because in applications such as physics, engineering or finance variables are often continuous,
- **Why non-parametric ?** Because parametric models such as Gaussian are too restrictive for certain applications such as anomaly detection, risk analysis or reliability analysis.
- **Why high-dimensional ?** Because complex systems involve a large number of variables,
- **Challenge:** Various non-parametric models exists to estimate a density but they are limited to a **few dimensions** (~ 5 variables),

Context: learning high dimensional non-parametric continuous distributions

- **Why distributions ?** Because we are faced with uncertainties (lack of information, inherently uncertain problems),
- **Why continuous ?** Because in applications such as physics, engineering or finance variables are often continuous,
- **Why non-parametric ?** Because parametric models such as Gaussian are too restrictive for certain applications such as anomaly detection, risk analysis or reliability analysis.
- **Why high-dimensional ?** Because complex systems involve a large number of variables,
- **Challenge:** Various non-parametric models exists to estimate a density but they are limited to a **few dimensions** (~ 5 variables),
- **Solution:** Use of Probabilistic Graphical Models (PGM) to break the joint distribution into a product of conditional distributions of **lesser dimensions**.

Modeling with copulas

Definition

- $\mathbf{U} = (U_1, \dots, U_n)$, **continuous** random variable over $[0, 1]^n$,

Definition

- $\mathbf{U} = (U_1, \dots, U_n)$, **continuous** random variable over $[0, 1]^n$,

Definition (Copula Nelsen 2007)

A copula function is a cumulative distribution function on $[0, 1]^n$:

$$C(u_1, \dots, u_n) = \mathbb{P}(U_1 \leq u_1, \dots, U_n \leq u_n)$$

with **uniform** one-dimensional marginals :

$$C(1, \dots, u_i, \dots, 1) = u_i.$$

Definition

- $\mathbf{U} = (U_1, \dots, U_n)$, **continuous** random variable over $[0, 1]^n$,

Definition (Copula Nelsen 2007)

A copula function is a cumulative distribution function on $[0, 1]^n$:

$$C(u_1, \dots, u_n) = \mathbb{P}(U_1 \leq u_1, \dots, U_n \leq u_n)$$

with **uniform** one-dimensional marginals :

$$C(1, \dots, u_i, \dots, 1) = u_i.$$

- If C is **absolutely continuous**, a copula density function c exists :

$$c(\mathbf{x}) = \frac{\partial^n C}{\partial x_1 \dots \partial x_n}(x_1, \dots, x_n)$$

Sklar's theorem

Theorem (Sklar, 1959)

Sklar's theorem

Theorem (Sklar, 1959)

*For any **continuous** distribution F over X_1, \dots, X_n , there exists a **unique** copula function C , such that:*

Sklar's theorem

Theorem (Sklar, 1959)

For any *continuous* distribution F over X_1, \dots, X_n , there exists a *unique* copula function C , such that:

$$F(x_1, \dots, x_n) = C(F_1(x_1), \dots, F_n(x_n))$$

Sklar's theorem

Theorem (Sklar, 1959)

For any **continuous** distribution F over X_1, \dots, X_n , there exists a **unique** copula function C , such that:

$$F(x_1, \dots, x_n) = C(F_1(x_1), \dots, F_n(x_n))$$

Moreover, if F is **absolutely** continuous,

$$f(x_1, \dots, x_n) = c(F_1(x_1), \dots, F_n(x_n)) \prod_{i=1}^n f_i(x_i)$$

Sklar's theorem

Theorem (Sklar, 1959)

For any *continuous* distribution F over X_1, \dots, X_n , there exists a *unique* copula function C , such that:

$$F(x_1, \dots, x_n) = C(F_1(x_1), \dots, F_n(x_n))$$

Moreover, if F is *absolutely* continuous,

$$f(x_1, \dots, x_n) = c(F_1(x_1), \dots, F_n(x_n)) \prod_{i=1}^n f_i(x_i)$$

- Decomposition of the joint distribution into a copula function and a set of marginals : **more freedom for modeling.**

Sklar's theorem

Theorem (Sklar, 1959)

For any *continuous* distribution F over X_1, \dots, X_n , there exists a *unique* copula function C , such that:

$$F(x_1, \dots, x_n) = C(F_1(x_1), \dots, F_n(x_n))$$

Moreover, if F is *absolutely* continuous,

$$f(x_1, \dots, x_n) = c(F_1(x_1), \dots, F_n(x_n)) \prod_{i=1}^n f_i(x_i)$$

- Decomposition of the joint distribution into a copula function and a set of marginals : **more freedom for modeling**.
- C encodes all the information about the dependencies between the variables: **interesting for independence tests**.

Sklar's theorem

Theorem (Sklar, 1959)

For any *continuous* distribution F over X_1, \dots, X_n , there exists a *unique* copula function C , such that:

$$F(x_1, \dots, x_n) = C(F_1(x_1), \dots, F_n(x_n))$$

Moreover, if F is *absolutely continuous*,

$$f(x_1, \dots, x_n) = c(F_1(x_1), \dots, F_n(x_n)) \prod_{i=1}^n f_i(x_i)$$

- Decomposition of the joint distribution into a copula function and a set of marginals : **more freedom for modeling**.
- C encodes all the information about the dependencies between the variables: **interesting for independence tests**.
- Non-parametric estimation of the copula with the Empirical Bernstein Copula (EBC),

Sklar's theorem

Theorem (Sklar, 1959)

For any *continuous* distribution F over X_1, \dots, X_n , there exists a *unique* copula function C , such that:

$$F(x_1, \dots, x_n) = C(F_1(x_1), \dots, F_n(x_n))$$

Moreover, if F is *absolutely continuous*,

$$f(x_1, \dots, x_n) = c(F_1(x_1), \dots, F_n(x_n)) \prod_{i=1}^n f_i(x_i)$$

- Decomposition of the joint distribution into a copula function and a set of marginals : **more freedom for modeling**.
- C encodes all the information about the dependencies between the variables: **interesting for independence tests**.
- Non-parametric estimation of the copula with the Empirical Bernstein Copula (EBC),

 C becomes hard to model for high dimensions !


Modeling with Bayesian Networks

Bayesian Networks

- **Compact** representation of a joint probability distribution over a set of variables \mathbf{X} using :

Bayesian Networks


- **Compact** representation of a joint probability distribution over a set of variables \mathbf{X} using :
 - A Directed Acyclic Graph (*DAG*),



$$\mathcal{I}_I(\mathcal{G}) = \{(X_i \perp \text{ND}_i | \text{Pa}_i)\}.$$

Bayesian Networks


- **Compact** representation of a joint probability distribution over a set of variables \mathbf{X} using :
 - A Directed Acyclic Graph (*DAG*),
 - A set of Conditional Probability Distributions (*CPD*).



$$f(\mathbf{x}) = \prod_{i=1}^n f(x_i | \mathbf{pa}_i)$$

Bayesian Networks


- **Compact** representation of a joint probability distribution over a set of variables \mathbf{X} using :
 - A Directed Acyclic Graph (DAG),
 - A set of Conditional Probability Distributions (CPD).



Discrete case : Conditional Probability Tables.

Bayesian Networks

- **Compact** representation of a joint probability distribution over a set of variables \mathbf{X} using :
 - A Directed Acyclic Graph (DAG),
 - A set of Conditional Probability Distributions (CPD).



Discrete case : Conditional Probability Tables.

Continuous case : ???

- **Discretization :**

1. Limited to only a few bins for fast inference and learning algorithms.
2. Which one do we chose to minimize the loss of information ?
3. How to a continuous model from there ?

Bayesian Networks and continuous data

- **Discretization :**

1. Limited to only a few bins for fast inference and learning algorithms.
2. Which one do we chose to minimize the loss of information ?
3. How to a continuous model from there ?

- **Linear Gaussian Bayesian Networks (LGBN)** Lauritzen et al.

1989:
$$f(y|\mathbf{x}) = \mathcal{N}(y; \beta_0 + \sum_{i=1}^k \beta_i x_i, \sigma_y^2)$$

1. **Good:** Fast inference and learning algorithms,
2. **Bad:** Strong model assumptions (Gaussian),

Bayesian Networks and continuous data

- **Discretization :**

1. Limited to only a few bins for fast inference and learning algorithms.
2. Which one do we chose to minimize the loss of information ?
3. How to a continuous model from there ?

- **Linear Gaussian Bayesian Networks (LGBN)** Lauritzen et al.

1989:
$$f(y|\mathbf{x}) = \mathcal{N}(y; \beta_0 + \sum_{i=1}^k \beta_i x_i, \sigma_y^2)$$

1. **Good:** Fast inference and learning algorithms,
2. **Bad:** Strong model assumptions (Gaussian),

- **Mixture models:** Langseth et al. 2012; Cortijo et al. 2016

1. **Good:** Expressive models,
2. **Bad:** Hard to learn

Copula Bayesian Networks (CBNs)

Copula Bayesian Networks : definition

Definition (Copula Bayesian Network, Elidan 2010)

Copula Bayesian Networks : definition

Definition (Copula Bayesian Network, Elidan 2010)

- \mathcal{G} : DAG over \mathbf{X} ,

Copula Bayesian Networks : definition

Definition (Copula Bayesian Network, Elidan 2010)

- \mathcal{G} : DAG over \mathbf{X} ,
- Θ_C : set of (local) copula densities c_i ,

Copula Bayesian Networks : definition

Definition (Copula Bayesian Network, Elidan 2010)

- \mathcal{G} : DAG over \mathbf{X} ,
- Θ_C : set of (local) copula densities c_i ,
- Θ_f set of marginal densities f_i

Copula Bayesian Networks : definition

Definition (Copula Bayesian Network, Elidan 2010)

- \mathcal{G} : DAG over \mathbf{X} ,
- Θ_C : set of (local) copula densities c_i ,
- Θ_f set of marginal densities f_i

A Copula Bayesian Network (CBN) is a triplet $(\mathcal{G}, \Theta_C, \Theta_f)$

Copula Bayesian Networks : definition

Definition (Copula Bayesian Network, Elidan 2010)

- \mathcal{G} : DAG over \mathbf{X} ,
- Θ_C : set of (local) copula densities c_i ,
- Θ_f set of marginal densities f_i

A Copula Bayesian Network (CBN) is a triplet $(\mathcal{G}, \Theta_C, \Theta_f)$ which encodes a joint density $f(\mathbf{X})$ that factorizes over \mathcal{G} :

$$\begin{aligned} f(x_1, \dots, x_n) &= c(F_1(x_1), \dots, F_n(x_n)) \prod_{i=1}^n f_i(x_i) \quad (\text{Sklar}) \\ &= \prod_{i=1}^n R_i(F_i(x_i) | \mathbf{F}(\text{pa}_{X_i})) \cdot f_i(x_i) \end{aligned}$$

where $R_i(u_i | \pi_i) = \frac{c_i(u_i, \pi_i)}{c_i(\pi_i)}$.

Copula Bayesian Networks : definition

Definition (Copula Bayesian Network, Elidan 2010)

- \mathcal{G} : DAG over \mathbf{X} ,
- Θ_C : set of (local) copula densities c_i ,
- Θ_f set of marginal densities f_i

A Copula Bayesian Network (CBN) is a triplet $(\mathcal{G}, \Theta_C, \Theta_f)$ which encodes a joint density $f(\mathbf{X})$ that factorizes over \mathcal{G} :

$$\begin{aligned} f(x_1, \dots, x_n) &= c(F_1(x_1), \dots, F_n(x_n)) \prod_{i=1}^n f_i(x_i) \quad (\text{Sklar}) \\ &= \prod_{i=1}^n R_i(F_i(x_i) | \mathbf{F}(\text{pa}_{X_i})) \cdot f_i(x_i) \end{aligned}$$

where $R_i(u_i | \pi_i) = \frac{c_i(u_i, \pi_i)}{c_i(\pi_i)}$.

- Same graphical language than classical BNs (same independences)

Copula Bayesian Networks : definition

Definition (Copula Bayesian Network, Elidan 2010)

- \mathcal{G} : DAG over \mathbf{X} ,
- Θ_C : set of (local) copula densities c_i ,
- Θ_f set of marginal densities f_i


A Copula Bayesian Network (CBN) is a triplet $(\mathcal{G}, \Theta_C, \Theta_f)$ which encodes a joint density $f(\mathbf{X})$ that factorizes over \mathcal{G} :

$$\begin{aligned} f(x_1, \dots, x_n) &= c(F_1(x_1), \dots, F_n(x_n)) \prod_{i=1}^n f_i(x_i) \quad (\text{Sklar}) \\ &= \prod_{i=1}^n R_i(F_i(x_i) | \mathbf{F}(\text{pa}_{X_i})) \cdot f_i(x_i) \end{aligned}$$


where $R_i(u_i | \pi_i) = \frac{c_i(u_i, \pi_i)}{c_i(\pi_i)}$.

- Same graphical language than classical BNs (same independences)
- Classic algorithms can be adapted for structural learning.


Copula Bayesian Networks : example



Copula Bayesian Networks : example




Copula Bayesian Networks : example




- $\Theta_C = \{c_1(u_1) \equiv 1, c_2(u_2) \equiv 1, c_3(u_3, u_1, u_2), c_4(u_4, u_3)\}$

Copula Bayesian Networks : example




- $\Theta_C = \{c_1(u_1) \equiv 1, c_2(u_2) \equiv 1, c_3(u_3, u_1, u_2), c_4(u_4, u_3)\}$
- $\Theta_f = \{f_1(x_1), f_2(x_2), f_3(x_3), f_4(x_4)\}$

Copula Bayesian Networks : example




- $\Theta_C = \{c_1(u_1) \equiv 1, c_2(u_2) \equiv 1, c_3(u_3, u_1, u_2), c_4(u_4, u_3)\}$
- $\Theta_f = \{f_1(x_1), f_2(x_2), f_3(x_3), f_4(x_4)\}$
- $f(x_1, x_2, x_3, x_4) = [R_1(F_1(x_1))f_1(x_1)][R_2(F_2(x_2))f_2(x_2)]$
 $\times [R_3(F_3(x_3)|F_1(x_1), F_2(x_2))f_3(x_3)]$
 $\times [R_4(F_4(x_4)|F_3(x_3))f_4(x_4)]$

Copula Bayesian Networks : example



- $\Theta_C = \{c_1(u_1) \equiv 1, c_2(u_2) \equiv 1, c_3(u_3, u_1, u_2), c_4(u_4, u_3)\}$
- $\Theta_f = \{f_1(x_1), f_2(x_2), f_3(x_3), f_4(x_4)\}$
- $f(x_1, x_2, x_3, x_4) = [R_1(F_1(x_1))f_1(x_1)][R_2(F_2(x_2))f_2(x_2)]$
 $\times [R_3(F_3(x_3)|F_1(x_1), F_2(x_2))f_3(x_3)]$
 $\times [R_4(F_4(x_4)|F_3(x_3))f_4(x_4)]$
- Parametric copulas: Gaussian, Student, Dirichlet, ...

Copula Bayesian Networks : example



- $\Theta_C = \{c_1(u_1) \equiv 1, c_2(u_2) \equiv 1, c_3(u_3, u_1, u_2), c_4(u_4, u_3)\}$
- $\Theta_f = \{f_1(x_1), f_2(x_2), f_3(x_3), f_4(x_4)\}$
- $f(x_1, x_2, x_3, x_4) = [R_1(F_1(x_1))f_1(x_1)][R_2(F_2(x_2))f_2(x_2)]$
 $\times [R_3(F_3(x_3)|F_1(x_1), F_2(x_2))f_3(x_3)]$
 $\times [R_4(F_4(x_4)|F_3(x_3))f_4(x_4)]$
- Parametric copulas: Gaussian, Student, Dirichlet, ...
- Non-parametric copulas: Empirical Bernstein Copula (EBC)

Structure learning for CBNs

- CPC a continuous PC algorithm based on an independence test using Hellinger distance:
 - M. Lasserre et al. (May 2020). “Constraint-Based Learning for Non-Parametric Continuous Bayesian Networks”. In: *FLAIRS 33 - 33rd Florida Artificial Intelligence Research Society Conference*. Miami, United States: AAAI, pp. 581–586
 - M. Lasserre et al. (2021a). “Constraint-based learning for non-parametric continuous bayesian networks”. In: *Annals of Mathematics and Artificial Intelligence*, pp. 1–18

Learning algorithms


- CPC a continuous PC algorithm based on an independence test using Hellinger distance:
 - M. Lasserre et al. (May 2020). “Constraint-Based Learning for Non-Parametric Continuous Bayesian Networks”. In: *FLAIRS 33 - 33rd Florida Artificial Intelligence Research Society Conference*. Miami, United States: AAAI, pp. 581–586
 - M. Lasserre et al. (2021a). “Constraint-based learning for non-parametric continuous bayesian networks”. In: *Annals of Mathematics and Artificial Intelligence*, pp. 1–18
- CMIIC, an algorithm based on information theory:
 - M. Lasserre et al. (2021b). “Learning Continuous High-Dimensional Models using Mutual Information and Copula Bayesian Networks”. In: *Proceedings of the AAAI Conference on Artificial Intelligence*. Vol. 35. 13, pp. 12139–12146

Learning algorithms

- CPC a continuous PC algorithm based on an independence test using Hellinger distance:
 - M. Lasserre et al. (May 2020). “Constraint-Based Learning for Non-Parametric Continuous Bayesian Networks”. In: *FLAIRS 33 - 33rd Florida Artificial Intelligence Research Society Conference*. Miami, United States: AAAI, pp. 581–586
 - M. Lasserre et al. (2021a). “Constraint-based learning for non-parametric continuous bayesian networks”. In: *Annals of Mathematics and Artificial Intelligence*, pp. 1–18
- CMIIC, an algorithm based on information theory:
 - M. Lasserre et al. (2021b). “Learning Continuous High-Dimensional Models using Mutual Information and Copula Bayesian Networks”. In: *Proceedings of the AAAI Conference on Artificial Intelligence*. Vol. 35. 13, pp. 12139–12146
- Improvement of the state of the art algorithm (CBIC) by using mutual information to speed up the calculations.


Comparison method

1. We generate random reference structures,
2. Copulas are parametrized : Gaussian, Student or Dirichlet,
3. Samples are generated from the CBN : forward-sampling,
4. A structure is learned from the generated data,
5. Structural scores are computed : F-score et SHD.




Comparison method

-
1. We generate random reference structures,
 2. Copulas are parametrized : Gaussian, Student or Dirichlet,
 3. Samples are generated from the CBN : forward-sampling,
 4. A structure is learned from the generated data,
 5. Structural scores are computed : F-score et SHD.



Comparison method

- 1. We generate **random** reference structures,
- 2. Copulas are parametrized : Gaussian, Student or Dirichlet,
- 3. Samples are generated from the CBN : forward-sampling,
- 4. A structure is learned from the generated data,
- 5. Structural scores are computed : F-score et SHD.




Number of nodes : n



Number of arcs : $\lfloor 1.2 \times n \rfloor$


Comparison method

1. We generate random reference structures,
- 2. Copulas are parametrized : Gaussian, Student or Dirichlet,
3. Samples are generated from the CBN : forward-sampling,
4. A structure is learned from the generated data,
5. Structural scores are computed : F-score et SHD.




Comparison method

1. We generate random reference structures,
- 2. Copulas are parametrized : **Gaussian**, Student or Dirichlet,
3. Samples are generated from the CBN : forward-sampling,
4. A structure is learned from the generated data,
5. Structural scores are computed : F-score et SHD.




Comparison method

1. We generate random reference structures,
- 2. Copulas are parametrized : Gaussian, **Student** or Dirichlet,
3. Samples are generated from the CBN : forward-sampling,
4. A structure is learned from the generated data,
5. Structural scores are computed : F-score et SHD.




Comparison method

1. We generate random reference structures,
- 2. Copulas are parametrized : Gaussian, Student or **Dirichlet**,
3. Samples are generated from the CBN : forward-sampling,
4. A structure is learned from the generated data,
5. Structural scores are computed : F-score et SHD.




Comparison method

1. We generate random reference structures,
2. Copulas are parametrized : Gaussian, Student or Dirichlet,
- 3. Samples are generated from the CBN : forward-sampling,
4. A structure is learned from the generated data,
5. Structural scores are computed : F-score et SHD.




Comparison method

1. We generate random reference structures,
2. Copulas are parametrized : Gaussian, Student or Dirichlet,
3. Samples are generated from the CBN : forward-sampling,
- 4. A structure is learned from the generated data,
5. Structural scores are computed : F-score et SHD.




Comparison method

1. We generate random reference structures,
2. Copulas are parametrized : Gaussian, Student or Dirichlet,
3. Samples are generated from the CBN : forward-sampling,
4. A structure is learned from the generated data,
- 5. Structural scores are computed : F-score et SHD.



Comparison method

1. We generate random reference structures,
 2. Copulas are parametrized : Gaussian, Student or Dirichlet,
 3. Samples are generated from the CBN : forward-sampling,
 4. A structure is learned from the generated data,
- 5. Structural scores are computed : **F-score** et SHD.



Comparison method

1. We generate random reference structures,
 2. Copulas are parametrized : Gaussian, Student or Dirichlet,
 3. Samples are generated from the CBN : forward-sampling,
 4. A structure is learned from the generated data,
- 5. Structural scores are computed : **F-score** et SHD.

- **F-score** : skeleton (undirected structure)

Comparison method

1. We generate random reference structures,
 2. Copulas are parametrized : Gaussian, Student or Dirichlet,
 3. Samples are generated from the CBN : forward-sampling,
 4. A structure is learned from the generated data,
- 5. Structural scores are computed : F-score et **SHD**.

- **F-score** : skeleton (undirected structure)

- Skeleton perfectly retrieved : **F-score** = 1

Comparison method

1. We generate random reference structures,
 2. Copulas are parametrized : Gaussian, Student or Dirichlet,
 3. Samples are generated from the CBN : forward-sampling,
 4. A structure is learned from the generated data,
- 5. Structural scores are computed : F-score et **SHD**.


- **F-score** : skeleton (undirected structure)
 - Skeleton perfectly retrieved : **F-score** = 1
- **Structural Hamming Distance (SHD)** : CPDAG (skeleton + v-structures)

Comparison method


1. We generate random reference structures,
 2. Copulas are parametrized : Gaussian, Student or Dirichlet,
 3. Samples are generated from the CBN : forward-sampling,
 4. A structure is learned from the generated data,
- 5. Structural scores are computed : F-score et SHD.

- **F-score** : skeleton (undirected structure)
 - Skeleton perfectly retrieved : **F-score** = 1
- **Structural Hamming Distance (SHD)** : CPDAG (skeleton + v-structures)
 - CPDAG perfectly retrieved : **SHD** = 0


F-score evolution : random structures



(a) Gaussian case




(b) Student case




(c) Dirichlet case

F-score evolution for CBIC, CPC, G-CMIIC and B-CMIIC methods with respect to the dimension of the random structures. The results are averaged over 2 random structures of same dimension and over 5 different samples of size $m = 10^4$.


SHD evolution : random structures



(a) Gaussian case




(b) Student case




(c) Dirichlet case

SHD evolution for **CBIC**, **CPC**, **G-CMIIC** and **B-CMIIC** methods with respect to the **dimension** of the random structure. The results are averaged over 2 different structures of same dimension and over 5 different samples of size $m = 10^4$.


Temporal complexity



(a) Gaussian case



(b) Student case



(c) Dirichlet case

Learning time in seconds for **CBIC**, **CPC**, **G-CMIIC** et **B-CMIIC** with respect to the **dimension** of the random structures. The results are averaged over 2 different **random structures** of same dimension and over 5 different samples of size $m = 10^4$.

The otagrum module

otagrum: an open source library to learn CBNs

Two similar libraries (C++, python wrappers, open source):

otagrum: an open source library to learn CBNs

Two similar libraries (C++, python wrappers, open source):

- **OpenTURNS** deals with copulas and continuous distributions (available on GitHub, pip and conda).

otagrum: an open source library to learn CBNs

Two similar libraries (C++, python wrappers, open source):

- **OpenTURNS** deals with copulas and continuous distributions (available on GitHub, pip and conda).
- **aGrUM** deals with (discrete) graphical models (available on GitLab, pip and conda).

otagrum: an open source library to learn CBNs

Two similar libraries (C++, python wrappers, open source):

- **OpenTURNS** deals with copulas and continuous distributions (available on GitHub, pip and conda).
- **aGrUM** deals with (discrete) graphical models (available on GitLab, pip and conda).

*A module to rule them all: **otagrum**.*

otagrum: an open source library to learn CBNs

Two similar libraries (C++, python wrappers, open source):

- **OpenTURNS** deals with copulas and continuous distributions (available on GitHub, pip and conda).
- **aGrUM** deals with (discrete) graphical models (available on GitLab, pip and conda).

*A module to rule them all: **otagrum**.*

What does it contain ?

otagrum: an open source library to learn CBNs

Two similar libraries (C++, python wrappers, open source):

- **OpenTURNS** deals with copulas and continuous distributions (available on GitHub, pip and conda).
- **aGrUM** deals with (discrete) graphical models (available on GitLab, pip and conda).

A module to rule them all: otagrum.

What does it contain ?

- A CBN class,

otagrum: an open source library to learn CBNs

Two similar libraries (C++, python wrappers, open source):

- **OpenTURNS** deals with copulas and continuous distributions (available on GitHub, pip and conda).
- **aGrUM** deals with (discrete) graphical models (available on GitLab, pip and conda).

*A module to rule them all: **otagrum**.*

What does it contain ?

- A CBN class,
- Several learning algorithms,

otagrum: an open source library to learn CBNs

Two similar libraries (C++, python wrappers, open source):

- **OpenTURNS** deals with copulas and continuous distributions (available on GitHub, pip and conda).
- **aGrUM** deals with (discrete) graphical models (available on GitLab, pip and conda).

*A module to rule them all: **otagrum**.*

What does it contain ?

- A CBN class,
- Several learning algorithms,
- A detailed documentation.

otagrum: an open source library to learn CBNs

Two similar libraries (C++, python wrappers, open source):

- **OpenTURNS** deals with copulas and continuous distributions (available on GitHub, pip and conda).
- **aGrUM** deals with (discrete) graphical models (available on GitLab, pip and conda).

*A module to rule them all: **otagrum**.*

What does it contain ?

- A CBN class,
- Several learning algorithms,
- A detailed documentation.

Where to find it ?

otagrump: an open source library to learn CBNs

Two similar libraries (C++, python wrappers, open source):

- **OpenTURNS** deals with copulas and continuous distributions (available on GitHub, pip and conda).
- **aGrUM** deals with (discrete) graphical models (available on GitLab, pip and conda).

*A module to rule them all: **otagrump**.*

What does it contain ?

- A CBN class,
- Several learning algorithms,
- A detailed documentation.

Where to find it ?

- Module : openturns/otagrump (GitHub)

otagrum: an open source library to learn CBNs

Two similar libraries (C++, python wrappers, open source):

- **OpenTURNS** deals with copulas and continuous distributions (available on GitHub, pip and conda).
- **aGrUM** deals with (discrete) graphical models (available on GitLab, pip and conda).

*A module to rule them all: **otagrum**.*

What does it contain ?


- A CBN class,
- Several learning algorithms,
- A detailed documentation.

Where to find it ?

- Module : openturns/otagrum (GitHub)
- Experiments : MLasserre/otagrum-experiments (GitHub)

otagram: installation

- Online website : <https://openturns.github.io/otagram/master/index.html>



The screenshot shows the OTagram documentation website. The left sidebar contains a 'Table of Contents' with links to 'Introduction', 'What is otagram?', 'How to install it?', 'Conda', 'Manually (Linux)', 'User documentation', and 'Indices and tables'. Below this are links for 'Next topic', 'API', 'This Page', 'Show Source', and 'Quick search'. The main content area is titled 'OTagram documentation' and includes an 'Introduction' section. The introduction explains that the aGrUM library provides efficient algorithms for creating and manipulating graphical models, specifically Bayesian Networks (BN). It defines a Bayesian network as a probabilistic graphical model represented by a directed acyclic graph (DAG), where edges represent conditional dependencies and nodes represent variables. It also mentions that the manipulation of a Bayesian network is called inference and that efficient algorithms exist for this purpose. Below the introduction is a section titled 'What is otagram?' which states that the otagram module links Bayesian networks built with aGrUM to distributions defined with OpenTURNS. It lists three capabilities: defining discretized aGrUM distributions from OpenTURNS distributions, extracting marginal distributions of aGrUM Bayesian networks as OpenTURNS distributions, and defining and estimating Bayesian networks parameterized by local conditional copula functions for each node (CBN).

- Can be easily installed using conda:

```
$ conda install -c conda-forge otagram
```

- Or manually to have the development version.

otagram: an example of use

Using OTaGrUM: The wine data set

Importing modules

```
Entrée [1]: import openturns as ot
import openturns.viewer as otv

import pyAgrum as gum
import pyAgrum.lib.notebook as gnb

import otagrum as otagr
```


Loading data

```
Entrée [2]: data_ref = ot.Sample.ImportFromTextFile('winequality-red.csv', ";")
```

otagram: an example of use

Structure learning with CBIC algorithm


```
Entrée [3]: learner = otagr.TabuList(data_ref, 2, 10, 2) # Creating a TabuList learner  
cbic_dag = learner.learnDAG() # Learning DAG  
gnb.showDot(cbic_dag.toDot())
```



otagram: an example of use

Structure learning with CPC algorithm


```
Entrée [4]: learner = otagr.ContinuousPC(data_ref, 4, 0.05) # Using a CPC learner  
cpc_dag = learner.learnDAG() # Learning DAG  
gnb.showDot(cpc_dag.toDot())
```



otagram: an example of use

Structure learning with CMiIC algorithm

```
Entrée [5]: learner = otagr.ContinuousMIIC(data_ref) # Using a CMiIC learner  
learner.setAlpha(0.04) # Setting the value of alpha  
cmiic_dag = learner.learnDAG() # Learning DAG  
gmb.showDot(cmiic_dag.toDot())
```



otagrum: an example of use

Parameter learning


```
Entrée [7]: cpc_cbn = otagr.ContinuousBayesianNetworkFactory(ot.KernelSmoothing(ot.Histogram()),  
                                                         ot.BernsteinCopulaFactory(),  
                                                         cpc_dag,  
                                                         0.05,  
                                                         4,  
                                                         False).build(data_ref)
```

otagram: an example of use

Sampling the CBN

```
Entrée [9]: sample = cpc_cbn.getSample(1000)  
ot.VisualTest.DrawPairs(sample.getMarginal([0,1]))
```

Out[9]:



Conclusion & Future Works

Conclusion

Summary:

- CBNs allow to take advantage of conditional independences to reduce the global complexity,
- Using the Empirical Bernstein Copula we obtained non-parametric independence tests and non-parametric CBNs,
- We implemented learning algorithms for CBNs in the plugin otagram,

Future works : Inference in CBNs

- It consists in finding:






$$f(\mathbf{T}|\mathbf{E} = \mathbf{e})$$




where $\mathbf{T}, \mathbf{E} \subset \mathbf{X}$ such that $\mathbf{T} \cap \mathbf{E}$.

- Use of sampling to make approximate inferences,
- Use of junction trees to make numerical integrations.

Thank you for your attention !

Bibliography

-  Cortijo, S. and C. Gonzales (2016). “Bayesian networks with conditional truncated densities”. In: *The Twenty-Ninth International Flairs Conference* (cit. on pp. 27–29).
-  Elidan, G. (2010). “Copula bayesian networks”. In: *Advances in neural information processing systems*, pp. 559–567 (cit. on pp. 31–38).
-  Langseth, H., T. D. Nielsen, R. Rumi, and A. Salmerón (2012). “Mixtures of truncated basis functions”. In: *International Journal of Approximate Reasoning* 53.2, pp. 212–227 (cit. on pp. 27–29).
-  Lasserre, M., R. Lebrun, and P.-H. Wuillemin (May 2020). “Constraint-Based Learning for Non-Parametric Continuous Bayesian Networks”. In: *FLAIRS 33 - 33rd Florida Artificial Intelligence Research Society Conference*. Miami, United States: AAAI, pp. 581–586 (cit. on pp. 47–49).
-  Lasserre, M., R. Lebrun, and P.-H. Wuillemin (2021a). “Constraint-based learning for non-parametric continuous bayesian networks”. In: *Annals of Mathematics and Artificial Intelligence*, pp. 1–18 (cit. on pp. 47–49).

-  Lasserre, M., R. Lebrun, and P.-H. Wuillemin (2021b). “Learning Continuous High-Dimensional Models using Mutual Information and Copula Bayesian Networks”. In: *Proceedings of the AAAI Conference on Artificial Intelligence*. Vol. 35. 13, pp. 12139–12146 (cit. on pp. 47–49).
-  Lauritzen, S. L. and N. Wermuth (1989). “Graphical models for associations between variables, some of which are qualitative and some quantitative”. In: *The annals of Statistics*, pp. 31–57 (cit. on pp. 27–29).
-  Nelsen, R. B. (2007). *An introduction to copulas*. Springer Science & Business Media (cit. on pp. 9–12).