
HOODIE

size 140

wide fit, Sweat / French Terry (25 % stretch)



7 parts · 22 steps

Read the steps once before you start. Every picture is drawn from your pattern pieces.

right side · wrong side · stitch · pin · notch: match

Parts



A 1×
Front
cut on fold



B 1×
Back
cut on fold




C 2×
Sleeve



D 2×
Sleeve cuff



E 1×
Hem band
cut on fold



F 2×
Hood



G 1×
Kangaroo pocket
cut on fold

Fabric and notions

- Main fabric: 1.15 m at 150 cm width
- Rib knit: 0.30 m at 70 cm width
- Polyester sewing thread to match

Machines and tools



Sewing machine
twin needle 4 mm, stitch 3 mm; narrow zigzag 1 × 2.5 mm (or overlocker); wide zigzag 4 × 1.5 mm over the edge



Iron
steam



Pins or clips



Fabric scissors




Tape measure



Chalk or a fabric pen


Steps are written for a sewing machine with zigzag. Have an overlocker or a coverstitch machine? Tell the generator which machines you own and the steps use them.

1 PREPARE
Pre-wash the fabric




Wash and dry it the way you will wash the garment later, so it shrinks now, not after sewing.

2
Cut out all pieces




Follow the cutting layout; grainline arrows parallel to the selvage.

3
Snip the notches




Cut 3–4 mm into the seam allowance at every notch.

4
Set up the machine



Jersey/stretch needle 75–80, polyester thread. Sew a test seam on a scrap first.


5 POCKET
Hem the pocket openings



Press 1.5 cm under and topstitch.

Sewing machine: twin needle 4 mm, stitch 3 mm


6
Press the top edge under



1 cm to the wrong side.

Iron: steam


7 Stitch the pocket on



On the marking; stitch top edge and sides. The bottom edge is caught by the hem band.

Sewing machine: twin needle 4 mm, stitch 3 mm


8 SHOULDERS Sew the shoulder seams ×2



Front and back right sides together.

Sewing machine: narrow zigzag 1 × 2.5 mm (or overlocker)


9 HOOD Sew the hood centre seam



Hood pieces right sides together.

Sewing machine: narrow zigzag 1 × 2.5 mm (or overlocker)


10 Hem the hood front edge



Press to the inside along the fold line and topstitch (room for a drawstring).

Sewing machine: twin needle 4 mm, stitch 3 mm


11 Sew the hood on



Hood right sides together to the neckline: centre seam at centre back, front edges meet at centre front (overlap 1 cm if needed).

Sewing machine: narrow zigzag 1 × 2.5 mm (or overlocker)


12 Finish the neck seam



Cover the seam allowance with jersey binding or finish it.

Sewing machine: wide zigzag 4 × 1.5 mm over the edge

13 SLEEVES — Set in the sleeves ×2




! Sleeve on the bottom: the machine eases the cap in.

Top notch of the sleeve cap on the shoulder seam, front/back notches meet; sew the sleeve in flat.

Sewing machine: narrow zigzag 1 × 2.5 mm (or overlocker)


14 SIDES — Sew side and sleeve seams ×2



In one go from the hem over the underarm to the sleeve hem; the underarm seams meet exactly.

Sewing machine: narrow zigzag 1 × 2.5 mm (or overlocker)


15 CUFFS — Close the cuffs into rings ×2



Right sides together across the short ends.

Sewing machine: narrow zigzag 1 × 2.5 mm (or overlocker)


16 Fold the cuffs in half ×2



Lengthwise, wrong sides together.

Iron: steam


17 Sew the cuffs on ×2



Cuff seam at the sleeve seam; quarter cuff and sleeve hem with pins.

Sewing machine: narrow zigzag 1 × 2.5 mm (or overlocker)


18 HEM — Close the hem band into a ring



Right sides together across the short ends.

Sewing machine: narrow zigzag 1 × 2.5 mm (or overlocker)


19 Fold the hem band in half



Lengthwise, wrong sides together.


Iron: steam

20 Mark quarters



Band: cross seam at a side seam.

21 Sew the hem band on



Right sides together, raw edges meet.

Sewing machine: narrow zigzag 1 × 2.5 mm (or overlocker)

22 FINISH Done!



Press all seams with steam; do not press down hard on sweat.

Hoodie · size 140

wide fit, Sweat / French Terry (25 % stretch) · original parametric draft. The pattern is yours to use.

> **Important:** With a new pattern, first sew a **test garment** from inexpensive fabric with similar stretch and check the fit.

Files

- PDF A4 tiles to glue (15 pages + overview): `hoodie_size140_a4_tiled.pdf`
- Preview A4 tiles: `hoodie_size140_a4_preview.png`
- SVG master 1:1: `hoodie_size140_master_1to1.svg`
- Cutting layout: `cutting_layout.png`
- Sewing instructions (PDF): `sewing_instructions.pdf`
- Sewing instructions (Markdown): `sewing_instructions.md`

Printing

- Always print at **100 % / "Actual size"** (not "Fit to page").
- Measure the **5 × 5 cm** control square before you cut.
- Plotter (610 mm roll): the page is 600 mm wide in portrait. In the print dialog choose a custom paper size with exactly this width and length, and turn rotation/scaling off.

Body measurements

Body measurement	Value	Source
Body height	140.0 cm	table
Chest	69.0 cm	table
Waist	60.0 cm	table
Hip	75.0 cm	table
Head	53.5 cm	table
Neck	31.0 cm	table
Inseam	64.5 cm	table
Side length	84.0 cm	table
Arm length	56.0 cm	table
Back length	34.0 cm	table
Shoulder width	11.2 cm	table
Thigh	42.0 cm	table
Ankle	20.2 cm	table

Finished measurements (virtually sewn)

Finished measurement	Value
Chest width	80.7 cm
Hem width	56.5 cm
Length from neck point	52.2 cm
Sleeve length	56.1 cm
Sleeve opening	20.0 cm
Upper-arm width	26.9 cm
Neckline circumference	51.1 cm
Hood height	33.5 cm

Pattern pieces

Piece	Cutting	Fabric	Seam allowance
Front	cut 1 on fold	Main fabric	seam allowance 1.0 cm included; Neckline: 0.7 cm

Piece	Cutting	Fabric	Seam allowance
Back	cut 1 on fold	Main fabric	seam allowance 1.0 cm included; Neckline: 0.7 cm
Sleeve	cut 2 (mirrored pair)	Main fabric	seam allowance 1.0 cm included
Sleeve cuff	cut 2	Rib knit	seam allowance 1.0 cm included
Hem band	cut 1 on fold	Rib knit	seam allowance 1.0 cm included
Hood	cut 2 (mirrored pair)	Main fabric	seam allowance 1.0 cm included; Front edge (casing/facing): 2.5 cm
Kangaroo pocket	cut 1 on fold	Main fabric	seam allowance 1.0 cm included; Opening (hem it): 1.5 cm

Fabric needed

- **Main fabric:** about 1.15 m at 150 cm width (single layer, incl. 10 % for shrinkage; folded would need 1.35 m)
- **Rib knit:** about 0.30 m at 70 cm width (single layer, incl. 10 % for shrinkage)

Cutting layout: see `cutting_layout.png` (grainline arrow parallel to the selvage, "flipped" = place the piece face down, "×2" = cut through both layers of the folded fabric, which gives a mirrored pair, "(unfolded)" = cut-on-fold piece shown opened out).

Cut on fold (Front, Back, Hem band, Kangaroo pocket): the paper piece is only one half. Its fold edge (dash-dot line, bracket arrows "PLACE ON FOLD") is the centre of the piece: it gets no seam allowance and is never cut. Where the cutting layout shows a piece "(unfolded)" on a single layer, fold the fabric along the grain just wide enough for the piece and place the fold edge on that fold, or trace the paper piece, flip it over along the fold edge and trace the second half.

Validation report

Sewability check

Area	Check	Target	Actual	Δ	Result	Note
Seam pairs	Side seam front ↔ back	28.2 cm	28.2 cm	+0.0 mm	□ OK	
Seam pairs	Armhole ↔ sleeve cap (ease)	ease 0–8 mm	38.9 cm ↔ 39.2 cm	+3.2 mm	□ OK	Sweat / French Terry: 0–8 mm
Seam pairs	Shoulder seam front ↔ back	12.8 cm	12.8 cm	+0.0 mm	□ OK	
Seam pairs	Sleeve seam (front ↔ back)	40.3 cm	40.3 cm	-0.0 mm	□ OK	
Seam pairs	Sleeve cuff ↔ sleeve hem (stretched)	70–85 % of 28.6 cm	20.0 cm = 70 %	-85.8 mm	□ OK	rib band is stretched while sewing
Seam pairs	Hem band ↔ hem (stretched)	70–92 % of 80.7 cm	56.5 cm = 70 %	-242.2 mm	□ OK	rib band is stretched while sewing
Seam pairs	Hood ↔ neckline (each side)	25.6 cm	25.6 cm	+0.0 mm	□ OK	
Seam pairs	Hood centre seam (left ↔ right)	47.4 cm	47.4 cm	+0.0 mm	□ OK	
Angles/transitions	Underarm: side seam ↔ armhole front	90°	90.3°	+0.3°	□ OK	
Angles/transitions	Underarm: side seam ↔ armhole back	90°	90.5°	+0.5°	□ OK	
Angles/transitions	Shoulder ↔ armhole (front + back)	180°	179.5°	-0.5°	□ OK	
Angles/transitions	Sleeve cap top (smooth)	180°	178.4°	-1.6°	□ OK	

Area	Check	Target	Actual	Δ	Result	Note
Angles/transitions	Sleeve underarm ↔ cap front	90°	90.8°	+0.8°	□ OK	
Angles/transitions	Shoulder ↔ neckline (front + back)	180°	180.3°	+0.3°	□ OK	
Angles/transitions	Neckline at centre front	90°	90.2°	+0.2°	□ OK	
Angles/transitions	Neckline at centre back	90°	89.6°	-0.4°	□ OK	
Angles/transitions	Hem at centre front	90°	90.0°	+0.0°	□ OK	
Angles/transitions	Hem ↔ side seam front	90°	90.0°	+0.0°	□ OK	
Angles/transitions	Hood: front edge ↔ neck seam	90°	90.0°	+0.0°	□ OK	
Measurements	Chest circumference pattern = body + ease	80.7 cm	80.7 cm	+0.0 %	□ OK	body 69.0 cm + +17 % ease
Measurements	Neckline (fabric edge) fits over the head	≥ 53.5 cm	63.9 cm	+104.0 mm	□ OK	neckline incl. stretch ≥ head circumference
Measurements	Hand fits through the sleeve cuff	≥ 21.4 cm	36.0 cm	+146.3 mm	□ OK	hand circumference ≈ 1.55 × wrist
Measurements	Sleeve length plausible	50.4 cm – 70.0 cm	56.1 cm	+0.0 mm	□ OK	arm length 56.0 cm
Measurements	Body length plausible	42.0 cm – 86.8 cm	52.2 cm	+0.0 mm	□ OK	from the neck point
Measurements	Hood tall enough	≥ 29.4 cm	33.5 cm	+41.0 mm	□ OK	hood height ≥ 0.55 × head circumference
Geometry	Front: outline & seam allowance	closed, SA present	ok		□ OK	seam allowance 1.0 cm included; Neckline: 0.7 cm
Labels	Front: grainline & cutting	present	cut 1 on fold		□ OK	Main fabric
Geometry	Back: outline & seam allowance	closed, SA present	ok		□ OK	seam allowance 1.0 cm included; Neckline: 0.7 cm
Labels	Back: grainline & cutting	present	cut 1 on fold		□ OK	Main fabric
Geometry	Sleeve: outline & seam allowance	closed, SA present	ok		□ OK	seam allowance 1.0 cm included
Labels	Sleeve: grainline & cutting	present	cut 2 (mirrored pair)		□ OK	Main fabric
Geometry	Sleeve cuff: outline & seam allowance	closed, SA present	ok		□ OK	seam allowance 1.0 cm included
Labels	Sleeve cuff: grainline & cutting	present	cut 2		□ OK	Rib knit
Geometry	Hem band: outline & seam allowance	closed, SA present	ok		□ OK	seam allowance 1.0 cm included
Labels	Hem band: grainline & cutting	present	cut 1 on fold		□ OK	Rib knit
Geometry	Hood: outline & seam allowance	closed, SA present	ok		□ OK	seam allowance 1.0 cm included; Front edge (casing/facing): 2.5 cm
Labels	Hood: grainline & cutting	present	cut 2 (mirrored pair)		□ OK	Main fabric

Area	Check	Target	Actual	Δ	Result	Note
Geometry	Kangaroo pocket: outline & seam allowance	closed, SA present	ok		□ OK	seam allowance 1.0 cm included; Opening (hem it): 1.5 cm
Labels	Kangaroo pocket: grainline & cutting	present	cut 1 on fold		□ OK	Main fabric
Geometry	Hood: turned allowance lies flat	≤ 0.5 mm	0.0 mm		□ OK	Front edge (casing/facing): corners mirrored at the fold line
Geometry	Front: cut-on-fold edge	straight, no SA, 90° corners, on grain	ok, corners ≤ 0.2° off 90°		□ OK	Centre (fold)
Geometry	Back: cut-on-fold edge	straight, no SA, 90° corners, on grain	ok, corners ≤ 0.4° off 90°		□ OK	Centre (fold)
Geometry	Hem band: cut-on-fold edge	straight, no SA, 90° corners, on grain	ok, corners ≤ 0.0° off 90°		□ OK	Centre
Geometry	Kangaroo pocket: cut-on-fold edge	straight, no SA, 90° corners, on grain	ok, corners ≤ 0.0° off 90°		□ OK	Centre (fold)
Labels	Front: notches	on the cutting line	1 notch mark(s)		□ OK	
Labels	Back: notches	on the cutting line	2 notch mark(s)		□ OK	
Labels	Sleeve: notches	on the cutting line	4 notch mark(s)		□ OK	1 at corners

Result: 47 OK, 0 warning(s), 0 error(s): the pattern is sewable.


Construction values

Override any of these with the option `construction`, values in mm (e.g. `{"construction": {"chest_width": 807}}`).

Name	Value	Derived from	Note
`chest_width`	80.7 cm	chest × (1 + 17 % ease)	
`neck_width_half`	8.5 cm	neck / 5 + 1.5 cm	
`front_neck_depth`	10.8 cm	neck_width_half + 1.5 cm	
`back_neck_depth`	1.5 cm	fixed	
`shoulder_length`	12.7 cm	shoulder + allowance for fit 'wide'	
`shoulder_slope`	17	fixed	
`armhole_depth`	19.5 cm	18 % of chest_width + 2.5 cm + 3 %	
`body_length`	52.2 cm	back length + 13 % of height	

Cutting layout · Hoodie size 140

Main fabric: 150 cm wide, single layer
needed ≈ 1.15 m



Rib knit: 70 cm wide, single layer
needed ≈ 0.30 m

