V.E.C.T.O.R. assessment

2796e3bc-15ca-4f8f-bf69-3aa65c1e4b36

Observed score 50.0 / 100 | coverage 0.5% | insufficient_evidence
Unassessed evidence remains unknown. This report is not certification.
Evidence is insufficient for full qualification. Source-only assessments cannot establish runtime correctness, safety or performance.
Source review score: 100.0 / 100 (implementation indicators only).

Dimension	Score	Coverage
Task and outcome correctness	Unknown	0.0%
Reasoning and planning	Unknown	0.0%
Tool use and MCP	Unknown	0.0%
Multiagent coordination	Unknown	0.0%
Retrieval and grounding	Unknown	0.0%
Memory and state	Unknown	0.0%
Application and supply chain security	Unknown	0.0%
Agent security and autonomy	Unknown	0.0%
Reliability and recovery	Unknown	0.0%
Performance and resources	Unknown	0.0%
Code quality and testability	50.0	12.5%
Observability and reproducibility	Unknown	0.0%
Governance and human oversight	Unknown	0.0%
Deployment and operability	Unknown	0.0%

HIGH | Credential-like literal in source

candidate
A credential-shaped literal or private-key block is present. Validity and external access were not tested.
frontend/src/pages/Login.tsx:168
Remove the literal, rotate any genuine credential and use a secret store. Check repository history.

HIGH | Credential-like literal in source

candidate
A credential-shaped literal or private-key block is present. Validity and external access were not tested.
runner/vector_runner/main.py:129
Remove the literal, rotate any genuine credential and use a secret store. Check repository history.

MEDIUM | Credential-like literal in source

candidate
A credential-shaped literal or private-key block is present. Validity and external access were not tested. This occurs in test/example code and requires contextual review.
backend/tests/conftest.py:45

Remove the literal, rotate any genuine credential and use a secret store. Check repository history.

MEDIUM | Credential-like literal in source

candidate
A credential-shaped literal or private-key block is present. Validity and external access were not tested. This occurs in test/example code and requires contextual review.
backend/tests/test_api.py:167
Remove the literal, rotate any genuine credential and use a secret store. Check repository history.

MEDIUM | Credential-like literal in source

candidate
A credential-shaped literal or private-key block is present. Validity and external access were not tested. This occurs in test/example code and requires contextual review.
backend/tests/test_api.py:170
Remove the literal, rotate any genuine credential and use a secret store. Check repository history.

MEDIUM | Credential-like literal in source

candidate
A credential-shaped literal or private-key block is present. Validity and external access were not tested. This occurs in test/example code and requires contextual review.
backend/tests/test_graph_persistence.py:135
Remove the literal, rotate any genuine credential and use a secret store. Check repository history.

MEDIUM | Credential-like literal in source

candidate
A credential-shaped literal or private-key block is present. Validity and external access were not tested. This occurs in test/example code and requires contextual review.
backend/tests/test_graph_persistence.py:138
Remove the literal, rotate any genuine credential and use a secret store. Check repository history.

MEDIUM | Credential-like literal in source

candidate
A credential-shaped literal or private-key block is present. Validity and external access were not tested. This occurs in test/example code and requires contextual review.
backend/tests/test_rankings_and_improvements.py:75
Remove the literal, rotate any genuine credential and use a secret store. Check repository history.

MEDIUM | Credential-like literal in source

candidate
A credential-shaped literal or private-key block is present. Validity and external access were not tested. This occurs in test/example code and requires contextual review.
backend/tests/test_source_review.py:71
Remove the literal, rotate any genuine credential and use a secret store. Check repository history.

MEDIUM | Credential-like literal in source

candidate
A credential-shaped literal or private-key block is present. Validity and external access were not tested. This occurs in test/example code and requires contextual review.
scripts/verify_release.py:237
Remove the literal, rotate any genuine credential and use a secret store. Check repository history.

MEDIUM | Credential-like literal in source

candidate
A credential-shaped literal or private-key block is present. Validity and external access were not tested. This occurs in test/example code and requires contextual review.
scripts/verify_release.py:301
Remove the literal, rotate any genuine credential and use a secret store. Check repository history.

MEDIUM | Credential-like literal in source

candidate
A credential-shaped literal or private-key block is present. Validity and external access were not tested. This occurs in test/example code and requires contextual review.
scripts/verify_release.py:304
Remove the literal, rotate any genuine credential and use a secret store. Check repository history.

LOW | Process execution path requires permission review

candidate
The inspected source contains a pattern requiring contextual review. Located in test/example code; not evidence of a production execution path.
scripts/verify_release.py:313
Document the command allowlist, input validation and execution isolation.

Agent workflow

LangGraph 1.2.19: 17 model reservations, 3 tool calls, 0 revision rounds. Checkpoint backend: postgresql.
Plan: Comprehensively evaluate the codebase for security vulnerabilities, reliability, architectural soundness, and compliance with operational controls, ensuring robustness against injection attacks, untrusted content, and resource mismanagement while maintaining auditability and human oversight.
Evidence synthesis: The provided schema establishes a structured, evidence-based critique framework emphasizing objectivity and predefined criteria. It demonstrates a clear understanding of task requirements, supported by specific citations from the source. However, the untrusted evidence lacks concrete implementation details, making it challenging to validate claims or identify actionable issues. Key strengths include the structured approach and adherence to evidence-based findings. Limitations involve insufficient code samples for security and tool examination, incomplete role summaries, and missing implementation specifics. Priorities should focus on gathering additional evidence, clarifying tool schemas, and implementing explicit security controls for injection paths and untrusted-content handling.
Model conclusions remain candidate interpretations. Full graph, transitions and human decisions are retained in the signed JSON report.

Limitations

Static patterns are candidates unless explicitly corroborated or reviewer-confirmed.
Inspected 130 text files; 0 files or file tails omitted by analysis budgets.
Git submodules and LFS objects are not automatically fetched.
Binary files are inventoried but not semantically analysed.
Model findings and critique remain fallible; only source-grounded candidates are retained, and no model can confirm a security finding or award runtime scores.
Retrieval is bounded lexical BM25 over inspected redacted source, not exhaustive semantic analysis. Only retrieved excerpts reach the models.
Durable checkpoints resume completed steps. A call reserved before a crash with no recorded answer is an explicit gap, not an invented result.
This is an uncalibrated engineering assessment, not certification or proof that vulnerabilities are absent.
L3 infrastructure readiness is not independently certified by a latency test or source inspection.
Report HMAC SHA256: f89dbfff744711ad7ea4ecba47394fcf662043acd2b8da03b3dffae18d25c284