

SEMESTER HS2020

---

# C++ Zusammenfassung

---

Joel Schaltegger  
24. Dezember 2020

## **Lizenz**

"THE BEER-WARE LICENSE"(Revision 42): Joel Schaltegger wrote this file. As long as you retain this notice you can do whatever you want with this stuff. If we meet some day, and you think this stuff is worth it, you can buy me a beer in return.

## Inhaltsverzeichnis

<b>1</b>	<b>Introduction to C++</b>	<b>3</b>
1.1	C++ Compilation Process . . . . .	3
1.2	Declarations and Definitions . . . . .	3
<b>2</b>	<b>Values and Streams</b>	<b>4</b>
2.1	Variable Definitions . . . . .	4
2.2	Values and Expressions . . . . .	4
2.3	Strings and Sequences . . . . .	5
2.4	Input and Output Streams . . . . .	5
<b>3</b>	<b>Woche03</b>	<b>6</b>
<b>4</b>	<b>Woche04</b>	<b>7</b>
<b>5</b>	<b>Woche05</b>	<b>8</b>
<b>6</b>	<b>Woche06</b>	<b>9</b>
<b>7</b>	<b>Woche07</b>	<b>10</b>
<b>8</b>	<b>Woche08</b>	<b>11</b>
<b>9</b>	<b>Woche09</b>	<b>12</b>
<b>10</b>	<b>Woche10</b>	<b>13</b>
<b>11</b>	<b>Woche11</b>	<b>14</b>
<b>12</b>	<b>Woche12</b>	<b>15</b>
<b>13</b>	<b>Woche13</b>	<b>16</b>
<b>14</b>	<b>Anhang</b>	<b>17</b>
14.1	Übungen Woche XX . . . . .	17

# 1 Introduction to C++

In C++ gibt es keinen Garbage Collector, wie man es aus anderen Sprachen, wie Java oder C# kennt. Warnung: Wenn Code "falsch" geschrieben wurde, kann **Undefined Behavior** auftreten.

## 1.1 C++ Compilation Process

### \*.cpp Files

- Also called Implementation File
- For function implementations (can be in .h as well)
- Source of compilation

### \*.h File

- Also called Header File
- Declarations and definitions to be used in other implementation files

### 3 Phases of compilation

- Preprocessor Textual replacement of preprocessor directives (include)
- Compiler Translation of C++ code into machine code (source file to object file)
- Linker Combination of object files and libraries into libraries and executables

## 1.2 Declarations and Definitions

All things with a name that you use in a C++ program must be declared before you can do so.

### One Definition Rule

While a program element can be declared several times without problem there can be only one definition of it. This is called the **One Definition Rule** (ODR)!

### Include Guard

Include guards ensure that a header file is only included once. Multiple inclusions could violate the One Definition Rule when the header contains definitions.

---

```
1  #ifndef SAYHELLO_H_
2  #define SAYHELLO_H_
3
4  #include <iosfwd>
5  struct Greeter { /* Some Code */ };
6
7  #endif /* SAYHELLO_H_ */
```

---

## 2 Values and Streams

### 2.1 Variable Definitions

- Defining a variable consists of specifying its type, its variable name and its initial value. E.g. `int x{42};`
- Empty braces mean default initialization. E.g. `double x{};`
- Using `=` for initialization we can have the compiler determine its type. E.g. `auto const i = 5;`

#### Constants

- Adding the `const` keyword in front of the name makes the variable a single assignment variable, aka a constant. E.g. `int const x{42};`
  - Must be initialized and immutable
- Use the keyword `constexpr` if the variable is required to be fixed at compile time. E.g. `double constexpr pi{3.14159};`

#### Why should I use `const`?

- A lot of code needs names for values, but often does not intend to change it
- It helps to avoid reusing the same variable for different purposes (code smell)
- It creates safer code, because a `const` variable cannot be inadvertently changed
- It makes reasoning about code easier
- Constness is checked by the compiler
- It improves optimization and parallelization (shared mutable state is dangerous)

#### Important types for Variable

- `short`, `int`, `long`, `long long` - each also available as unsigned version
- `bool`, `char`, unsigned `char`, signed `char`
- `float`, `double`, `long double`
- `void` is special, it is the type with no values
- class defined: E.g. `std::string`, `std::vector`

### 2.2 Values and Expressions

**Integer to boolean:** `0 = False`, every other value = `True`

if (`a < b < c`) → zuerst wird `a < b` ausgewertet (true oder false). Dann wird der Boolean mit einem `int` (`c`) verglichen. Der Bool wird dafür implizit in 0 oder 1 gecastet.

Literal Example	Type	Value
'a'	char	Letter a, value: 97
'\n'	char	<NL> character, value: 10
'\x0a'	char	<NL> character, value: 10
1	int	1
42L	long	42
5LL	long long	5
int{} (not really a literal)	int	0 (default value)
1u	unsigned int	1
42ul	unsigned long	42
5ull	unsigned long long	5
020	int	16 (octal 20)
0x1f	int	31 (hex 1F)
0XFULL	unsigned long long	15 (hex F)
0.f	float	0
.33	double	0.33
1e9	double	1000000000 (10 <sup>9</sup> )
42.E-12L	long double	0.00000000042 (42*10 <sup>-12</sup> )
.3l	long double	0.3
"hello"	char const [6]	Array of 6 chars: h e l l o <NUL>
"\012\n\\"	char const [4]	Array of 4 chars: <NL> <NL> \ <NUL>

## 2.3 Strings and Sequences

`std::string` is C++'s type for representing sequences of `char` (which is often only 8 bit) and are mutable. That means, we can modify the content. (Vergleich zu Java: Dort würde ein neues String Objekt erstellt werden)

Grundsätzlich werden Strings also als `char const[ ]` abgespeichert. Mit dem namespace `std::literals` hat man die Option hinter dem String eine 's' anzufügen, um das Objekt effektiv als String zu speichern. z.B. `"ab"s`

### toUpper Iterator

---

```
1 void toUpper(std::string & value) {
2     transform(cbegin(value), cend(value), begin(value), ::toupper);
3 }
```

---

## 2.4 Input and Output Streams

Functions taking a stream object must take it as a reference, because they provide a side effect to the stream (i.e., output characters).

### Reading from Input

- Reading into a `std::string` always works. Unless the stream is already `!good()` → Spaces werden übersprungen (neues String-Objekt)!
- Reading into other types (e.g. `int`) has no error recovery. A wrong input puts the stream into status fail and the characters remain in the input.
- Post-read check: `if (in » age) { ... }`
- Multiple subsequent reads are possible: `if (in » symbol » count) { ... }`
- Remove fail flag: `in.clear()`
- Ignore one char: `in.ignore();`
- Helpfull for reading: `while (in.good())` um die Leseoperationen setzen.

### Robust reading of an int value

---

```
1 // Use an std::istringstream as intermediate stream
2 int inputAge(std::istream & in)
3 {
4     std::string line{}
5     while (getline(in, line)) {
6         std::istringstream is{line};
7         int age{-1};
8         if (is >> age) {
9             return age;
10        }
11    }
12    return -1;
13 }
```

---

### Stream States

State Bit Set	Query	Entered
<none>	<code>is.good()</code>	initial <code>is.clear()</code>
failbit	<code>is.fail()</code>	formatted input failed
eofbit	<code>is.eof()</code>	trying to read at end of input
badbit	<code>is.bad()</code>	unrecoverable I/O error

## 3 Woche03

## **4 Woche04**

## 5 Woche05



## **6 Woche06**

## **7 Woche07**

## **8 Woche08**

## **9 Woche09**

## 10 Woche10

## **11 Woche11**

## 12 Woche12

## 13 Woche13



## 14 Anhang

### 14.1 Übungen Woche XX

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

#### Includes

---

```
1 // Only the declaration for input and output streams
2 #include <iosfwd>
3
4 // Implementation of input stream
5 #include <istream>
6
7 // Implementation of output stream
8 #include <ostream>
9
10 // Declaration of both streams and additionally std::cout, std::cin, std::cerr
11 #include <iostream>
12
13 // Functions: std::tolower(c), std::isupper(c)
14 #include <cctype>
15
16 // Strings
17 #include <string>
```

---