

# Pandas Cheat Sheet

Note: df - A pandas DataFrame object, s - A pandas Series object

import pandas as pd

import numpy as np

## Importing data

**pd.read\_csv(filename)** # From a CSV file

**pd.DataFrame(dict)** # From a dict, keys for column names, and values for data as lists

## Viewing/inspecting data

**df.head(n)**

**df.tail(n)**

**df.shape**

**df.info()**

**df.describe()** # Summary statistics for numerical columns

**df.isna().sum()** # Sum of null values per col

**df.notna()**

**s.value\_counts(dropna=False)** # View unique values and counts

**df.value\_counts(dropna=False, normalize=True, ascending=True)**

## Selection and reference

*# Slicing with [], work on rows*

**s[:5]**

**df[:5]** # Return first 5 rows

**df[::2]** # Return dataframe with a step of 2 on row selection

**df[::-1]** # Return a reversed dataframe

*# Select columns and rows*

**df["col"]** # Return the column as 'Series'

**df[["col"]]** # Return the col as 'DataFrame'

**df[["col1", "col2"]]**

**df[df["col1"]>0]** # Return the rows where the values of 'col1'>0

**df[df["col1"]>0][["col2"]]** # Return 'col2' on selected rows based on values of 'col1' as a Series

**df[df["col1"]>0][["col2"]]** # Return 'col2' on selected rows based on values of 'col1' as a DataFrame

*# Select by label via .loc[]*

**df.loc[0]** # Return a Series for row 0

**df.loc[0]** # Return a DataFrame for row 0

**df.loc[0,3]** # Return a DataFrame -- the rows with integer index 0 and 3

**df.loc[:5]** # Return a DataFrame with rows index from 0 to 5 (*note include index 5*)

**df.loc["row1":"row2"]** # Return a DataFrame with rows index from "row1" to "row2"

**df.loc[5,"col1":"col2"]** # Return a DataFrame with rows index from 0 to 5, columns index between "col1" and "col2"

**df.loc[["a", "c"], "col2"]** # Return a DataFrame with rows index "a" and "c", columns index from "col2" to the end

**df.loc["a", "A"]** # Return a cell value at row "a", col "A"

**df.loc[:, "col1"]>0** # Return a boolean type Series along rows

**df.loc[df.loc[:, "col1"]>0, :]** # Return rows selected by a boolean array

**df.loc[df.col1>0, :]** # Return rows selected by a boolean array, a simplified way

**df.loc[lambda df: df.col1>0, :]** # Selection by Callable lambda function  
#lambda with .loc be more useful in complex operations or when chaining multiple methods together, as it allows you to pass functions dynamically.

**df.loc[lambda df: (df.col1>0) & (df.col2=="2009-01-02"), :].assign(col3=lambda df: df.col1 - 2, col4=lambda df: df.col3\*2)**

*# Select by position via .iloc[], integer based indexing*

**df.iloc[0]** # Return a Series -- the first row

**df.iloc[0]** # Return a DataFrame

**df.iloc[0,3]** # Return 1<sup>st</sup> and 4th rows

**df.iloc[:4, :4]** # Return the top\_left\_corner (first four rows, and first four columns)

**df.iloc[-4:, -4:]** # Return the bottom right corner

**df.iloc[[1, 3, 5], [1, 3]]**

**df.iloc[0,0]** # Return the cell value at first row, first column

## Data cleaning

*# Change column or index names*

**df.columns= ['new1', 'new2', 'new3']**

# Rename columns

**df.rename(columns={"old1":"new1", "old2":"new2"})** # Selective renaming using a mapping

**df.rename(index={0: "x", 1: "y", 2: "z"})**

# Rename index using a mapping

**df.rename(index=lambda x: x+1)**

# Mass renaming index

**df.set\_index("col\_A")** # Set the DataFrame index using existing column "col\_A"

*# Dealing with null values*

**df.isna()** # Return a boolean same-sized object

**df["col1"].isna()** # Return a boolean Series

**df.notna()** # opposite of .isna()

**df.dropna()** # Drop all rows that contain null values, default inplace=False

**df.dropna(inplace=True)** # Change inplace

**df.dropna().reset\_index()** # Drops rows with null values and reset index

**df.dropna(axis=1)** # Drop columns that contain null values

**df.dropna(how='all')** # Drop rows when all elements are missing ; Default= "any" (at least one element is missing)

**df.dropna(thresh=n)** # Drop rows that have less than thresh n non-null values

**df.fillna(x)** # Replace all null values with x

**df.fillna(value={"A": 0, "B": 1})** # Replace NaN in column 'A', 'B', with 0, 1 respectively.

**s.fillna(s.mean())** # Replace NaN with mean

**df.fillna(df.mean(axis=0))** # Fill NaN values with the mean of each column

**df["col1"].fillna(df["col1"].mode()[0])** # Fill NaN values with the mode of the column; Note that .mode() here returns a Series object so use [0] to select the (first) element/value

*# Dealing with duplicates*

**df.drop\_duplicates(subset=["col1,col2"], keep='last')**

*# Drop rows or columns*

**df.drop([0,1])** # Drop rows by index

**df.drop(['A', 'B'], axis=1)** # Drop columns

**df[df["col1"] <= 2]** # Drop rows where the values of "col1" >2

*# Change data type*

**s.astype(float)** # Convert to float

*# Replace values*

**s.replace(1, "one")** # Replace 1 with "one"

**df.replace([1,3], ["one", "three"])**

**df.replace({1:"one", 3: "three"})**

## Filter, sort, groupby and transform

*# Filtering*

**df[df["col"]>0.5]** # Select rows that meet the condition

**df[(df["col"]>0.5) & (df["col"]<1)]**

**df.loc[df["col"]>0.5, :]**

**df.where(df>0.5)** # Keeps the original values where the condition is True and replaces with np.nan where the condition is false

**df.where(df>0.5, other=0)** # replace with 0 where the condition is false

*# Sorting*

**df.sort\_index()** # Sort by index along rows in ascending order

**df.sort\_index(ascending=False,**

**inplace=True)** # Sort by index along rows in descending order, inplace change

**df.sort\_values(by="col", ascending=False)** # Sort values by col in descending order;

**df.sort\_values(by=["col1", "col2"], ascending=[False, True])**

**df.reset\_index()** # Reset index

**df["col\_rank"]=df["col"].rank()** # Creates a new column where each entry corresponds to the rank (1 through n) of that row's value in column 'col'

**df["col\_rank"]=df["col"].rank(method='min', ascending=False)** # the records that have the same values are ranked using the lowest rank; by default the average rank is used; other methods are 'max', 'first', 'dense'.

*# Grouping*

**df.groupby('col')** # Returns a groupby object for values from col; this did a mapping to df

**df.groupby(['col1', 'col2'])**

**df.groupby('col').size()** # Return the number of rows in each group

**df.groupby('col').count()** # Return the number of NON\_NULL values for each column

```

df.groupby('col')[col2].count() # Return
the number of NON_NULL values for 'col2'
df.groupby('col').mean() # Produces a
DataFrame with the group names as its new
index and the mean values for each numeric
column by group; other methods include
median(), mode(), sum(), size(), count(),
min(), max(), std(), var(), describe() ,
nunique()
df.groupby('col1')[col2].mean() #Return
the mean of the values in col2, grouped by
the values in col1
df.groupby('col1')[[col2, col3]].mean()
#Return the mean of the values in col2 and
col3, grouped by the values in col1
df.groupby('col1')[col2,
'col3'].agg(['sum', 'mean', 'std']) # Apply
functions at once, using pandas' optimized
groupby sum(), mean(), std() methods
df.groupby('col1').agg({"col2": "mean",
"col3": "std"}) # Apply "mean" to "col2",
"std" to "col3"
df.groupby('col1')[col2].transform(lamb
da x: (x - x.mean()) / x.std()) # Return a
new DataFrame with the same row numbers
and indexing as the original one but with
transformed individual values
df.groupby('col1')[col2].transform(lamb
da x: x.fillna(x.mode()[0]))
df.groupby('col1').head(n) # Returns the
first n rows (5, by default) of each group
correspondingly
# Other transformation
df[['B', 'A']] = df[['A', 'B']] # Swap column
contents
df.assign(name = ["Emil", "Tobias",
"Linus"]) # Assign a new column "name" to a
df, returning a new object with the new
columns added to the original ones
df.assign(temp_f=lambda x: x.temp_c *
9 / 5 + 32) # Assign a new column "temp_f"
from values of column "temp_c" via lambda
function
# use of .apply() on Series and
DataFrames
df.apply(my_function) # Apply
my_function to each column
df.apply(my_function, axis=1) # Apply
my_function to each row
df['FirstName'] =
df['EmployeeName'].apply(lambda x :
x.split()[0]) # Apply lambda function on
'EmployeeName' col to create a new column
df['Value3']=df['Value1'].apply(lambda
x: x**2)
mask=df.apply(lambda x: True if x
['Gender'] == 'F' and x['Kids'] > 0 else
False, axis=1) # return a boolean Series
df['BMI'] = df.apply(lambda x:
calc_bmi(x['Weight'], x['Height']),
axis=1) # Apply the custom function
calc_bmi to the data frame, across each row
# PIVOT_TABLE
table=pd.pivot_table(df,index=['col','col
2'],values=['col3','col4'],columns='col5',

```

```

aggfunc='sum') # Create a pivot table that
groups by 'col1' and 'col2'; by default,
aggfunc='mean'
Join/Combine
pd.concat([df1,df2]) # Concatenate along
rows, retain original index
pd.concat([df1,df2],join="inner",ignore_
index=True) # Concatenate along rows and
return only overlapping columns, reset index
pd.concat([df1,df2],axis=1) # Concatenate
along columns (only work if the tables have
the same height)
# Note df.append() had been deprecated
pd.merge(left, right, on="key") # Inner
join on "key" in both dataframes
pd.merge(left, right, how="left",
on=["key1", "key2"]) # Left join on ["key1",
"key2"] in left
pd.merge(left, right, left_on="key",
right_index=True, how="left",
sort=False) # Join DataFrame left's column
"key" with DataFrame right's index
df1.merge(df2, left_on='lkey',
right_on='rkey') # how="inner" by default
df1.join(df2, how="inner") # .join() joins
on indexes by default, how="left" by default

```

### Statistics and Some Common Operations

```

df.sum() # Defual axis=0, sum of columns
df.min()
df.max()
df.median()
df.mode() # Retrurns the mode of each
column, a Series or a DataFrame
df.std()
df.count() # Return the number of non-null
values in each column
df.nunique() # number of unique values
df.corr() # Returns the correlation
coefficients between columns
df.copy()
df.T # Transpose rows and cols
df.size # nrows* ncols; different to
the .size() for groupby object
df.values # Get a numpy array for df

```

### Datetime in Pandas

```

# Create Pandas Timestamp object
date = pd.Timestamp('2013-01-01')
date2 = pd.Timestamp('2013-01-01
21:15:06')
date3 = pd.Timestamp('Sep 04, 1982
1:35.18')
# Create a Period object
month = pd.Period('2013-01', freq='M')
# Create a sequence of dates
dates=pd.date_range('2022-2-7',
periods=7) # Return a fixed frequency
DatetimeIndex. Each date in the
DatetimeIndex instance is an instance of the
Timestamp.
pd.date_range(start='1/1/2018',
periods=5, freq='3ME') # 3 month end
frequency, by default, freq='D'
# Separate element of a Timestamp
object from built-in attributes

```

```

year=date.year
month=date.month
day=date.day
hour=date.hour
month_name=date.month_name()
week_day=date.weekday() # Return the
day of the week as a number, counting from 0
(for monday)
day_name=date.day_name()
# Convert to a pandas datetime object
df['datetime'] =
pd.to_datetime(df['datetime'],yearfirst=
True) # Convert column 'datetime' (string
object) to a datetime object
df['datetime'] =
pd.to_datetime(df['datetime'],
format="%y-%m-%d") # # Convert column
'datetime' (string object) to a datetime object
by providing an exact format
mask = (df['datetime'] >=
pd.Timestamp('2019-03-06')) &
(df.datetime < pd.Timestamp('2019-03-
07')) # Create a Boolean mask to select the
DataFrame rows between two specific dates
df[mask]
df.set_index('datetime', inplace=True) #
Set the datetime column as the index of the
DataFrame for Timestamp slicing
df.loc['03-04-2019':'04-04-2019'] # Return
rows within a date range.

```