



PasswordStore Audit Report

Version 1.0

Lamassu

November 22, 2024

Table of Contents

- Table of Contents
- Protocol Summary
- Disclaimer
- Risk Classification
- Audit Details
 - Scope
- Protocol Summary
 - Roles
- Executive Summary
 - Issues found
- Findings
 - High
 - * [H-1] Passwords stored on-chain are visible to anyone, not matter solidity variable visibility
 - * [H-2] `PasswordStore::setPassword` is callable by anyone
 - * [I-1] The `PasswordStore::getPassword` natspec indicates a parameter that doesn't exist, causing the natspec to be incorrect

Protocol Summary

PasswordStore is a protocol dedicated to storage and retrieval of a user's passwords. The protocol is designed to be used by a single user, and is not designed to be used by multiple users. Only the owner should be able to set and access this password.

Disclaimer

I make all effort to find as many vulnerabilities in the code in the given time period, but hold no responsibilities for the findings provided in this document. A security audit is not an endorsement of the underlying business or product. The audit was time-boxed and the review of the code was solely on the security aspects of the Solidity implementation of the contracts.

Risk Classification

		Impact		
		High	Medium	Low
Likelihood	High	C	H	M
	Medium	H	M	L
	Low	M	L / M	L

I use this severity matrix to determine the severity.

Audit Details

The findings described in this document correspond the following commit hash:

```
1 2e8f81e263b3a9d18fab4fb5c46805ffc10a9990
```

Scope

```
1 src/  
2 --- PasswordStore.sol
```

Protocol Summary

PasswordStore is a protocol dedicated to storage and retrieval of a user’s passwords. The protocol is designed to be used by a single user, and is not designed to be used by multiple users. Only the owner should be able to set and access this password.

Roles

- Owner: Is the only one who should be able to set and access the password.
- For this contract, only the owner should be able to interact with the contract.

Executive Summary

A mock report from the Cyfrin Updraft course. The whole idea was to get familiar with creating audit reports.

Issues found

Severity	Number of issues found
Critical	2
High	0
Medium	0
Low	0
Info	1
Total	3

Findings

High

[H-1] Passwords stored on-chain are visible to anyone, not matter solidity variable visibility

Description: All data stored on-chain is visible to anyone, and can be read directly from the blockchain. The `PasswordStore : s_password` variable is intended to be a private variable, and only accessed through the `PasswordStore : getPassword` function, which is intended to be only called by the owner of the contract.

However, anyone can directly read this using any number of off chain methodologies

Impact: The password is not private.

Impact: High

Likelihood: High

Proof of Concept: The below test case shows how anyone could read the password directly from the blockchain. We use foundry's cast tool to read directly from the storage of the contract, without being the owner.

- ## 1. Create a locally running chain

```
1 make anvil
```

- ## 2. Deploy the contract to the chain

```
1 make deploy
```

- ### 3. Run the storage tool

We use 1 because that's the storage slot of `s_password` in the contract.

```
1 cast storage <ADDRESS_HERE> 1 --rpc-url http://127.0.0.1:8545
```

You'll get an output that looks like this:

[illegible]

You can then parse that hex to a string with:

[illegible]

And get an output of:

```
1 myPassword
```

Recommended Mitigation: Due to this, the overall architecture of the contract should be rethought. One could encrypt the password off-chain, and then store the encrypted password on-chain. This would require the user to remember another password off-chain to decrypt the password. However, you'd also likely want to remove the view function as you wouldn't want the user to accidentally send a transaction with the password that decrypts your password.

[H-2] PasswordStore::setPassword is callable by anyone

Description: The `PasswordStore : : setPassword` function is set to be an `external` function, however the natspec of the function and overall purpose of the smart contract is that `This function allows only the owner to set a new password.`

```
1     function setPassword(string memory newPassword) external {
2 @>     // @audit - There are no access controls here
3         s_password = newPassword;
4         emit SetNetPassword();
5     }
```

Impact: Anyone can set/change the password of the contract.

Impact: High

Likelihood: High

Proof of Concept:

Add the following to the `PasswordStore.t.sol` test suite.

```
1 function test_anyone_can_set_password(address randomAddress) public {
2     vm.prank(randomAddress);
3     string memory expectedPassword = "myNewPassword";
4     passwordStore.setPassword(expectedPassword);
5     vm.prank(owner);
6     string memory actualPassword = passwordStore.getPassword();
7     assertEq(actualPassword, expectedPassword);
8 }
```

Recommended Mitigation: Add an access control modifier to the `setPassword` function.

```
1 if (msg.sender != s_owner) {
2     revert PasswordStore__NotOwner();
3 }
```

[I-1] The PasswordStore::getPassword natspec indicates a parameter that doesn't exist, causing the natspec to be incorrect

Description:

```
1 /*
2  * @notice This allows only the owner to retrieve the password.
3  * @param newPassword The new password to set.
4  */
5 function getPassword() external view returns (string memory) {
```

The natspec for the function `PasswordStore::getPassword` indicates it should have a parameter with the signature `getPassword(string)`. However, the actual function signature is `getPassword()`.

Impact: The natspec is incorrect.

Impact: None

Likelihood: N/A

Recommended Mitigation: Remove the incorrect natspec line.

```
1 - * @param newPassword The new password to set.
```