

Fuzzy Systems and Neural Networks

Jéssica Consciência e Tiago Leite

October 5, 2024

Part I

Fuzzy System

Firstly we started by deciding between which type of fuzzy system we should implement: Mamdani, Takagi-Sugeno or Tsukamoto. From the project statement we observe that the output *CLP-Variation* is not any clear function of the input, rulling out Takagi-Sugeno, also meaning that our output is a **Fuzzy Set**. If we wish for our output to be monotonic then the choice would be Tsukamoto, since we did not want this restriction and decided for starting with a simple approach then later on adding difficulty when needed. (Early on we decided to try to make data-driven decisions with an iterative improving process)

0.1 First Iterations

In the initial iteration, we selected the variables *ProcessorLoad*, and *MemoryUsage* based on which variables we though were more important. These variables were chosen as inputs, while *CLP* was designated as the output. We opted for triangular membership functions, defining four levels for each input variable: (low, medium, high, critical).

We then defined the range of the membership functions associated with each term of the two linguistic variables, *MemoryUsage* and *ProcessorLoad*. Considering that a device with more than 85% processor load or memory usage is typically unable to perform its basic tasks, it became clear that this threshold would correspond to a specific term, labeled as “critical”. The ranges for the other membership function terms were distributed between 0 and 1 based on what we deemed appropriate. We also decided to keep the terms associated with *CLP* straightforward, using only three terms: “decrease”, “increase”, and “maintain”. The values for the membership functions of these terms were distributed between -1 and 1.

The figures below illustrate the membership function graphs for these variables.




Figure 1: Memory Usage




Figure 2: Processor Load




Figure 3: CLP Variation

To design the system’s rules, we created a truth table, which can be found below in Table 1. The logic behind the table was as follows: when both *MemoryUsage* and *ProcessorLoad* were either “low” or “medium,” the *CLP* would increase. When one of them reached “high,” the *CLP* remained unchanged (this decision was made to ensure that the node’s processing capacity stayed above average). Finally, if any of these variables entered a “critical” state, the *CLP* had to decrease.

CPL		ProcessorLoad			
		low	medium	high	critical
[htbp]	low	increase	increase	mantain	decrease
	medium	increase	increase	maintain	decrease
	high	maintain	maintain	maintain	Decrease
	critical	Decrease	Decrease	Decrease	Decrease

Table 1: Truth table

To visualize the system's output, we generated 50 data points for *MemoryUsage* and *ProcessorLoad* ranging between 0 and 1. We then created an interactive 3D plot that showed the evolution of *CLP* based on these two values, this can be seen in Figure4. Upon reviewing the graph, we noticed that the variables *ProcessorLoad* and *MemoryUsage* exhibited very similar behavior because intuitively, when designing the system, we had structured the membership functions for each term in the same way for both variables, and the truth table was also symmetric. This indicates that the system should react in the same way to both variables and they could, in fact, be merged into a single variable without losing the system's effectiveness. By combining these two variables, we simplify the model while still accurately representing the system's behavior, as both variables seem to influence the *CLP* in a nearly identical manner.




Figure 4: Fuzzy CLP Inference

From the graph we also noticed that the *CLP* only varies between -0.5 and 0.5, which is not the

desired range; we aim for it to vary between -1 and 1. This limitation is due to the configurations of the membership functions for the terms "increase" and "decrease" of the *CLP*. Additionally, two constant plateau regions are visible where the *CLP* remains unchanged: when *MemoryUsage* and *ProcessorLoad* are between 0 and 0.6, and when they are between 0.7 and 0.85, which does not make sense in our context. Finally, in the area of the graph where *CLP* is less than -0.2 and *MemoryUsage/ProcessorLoad* is greater than 0.6, there is a "hump" with no *CLP* values, which is undesirable.

Subsequently, we explored the effect of switching the membership functions to a Gaussian distribution because they provide a smoother transition between membership grades. To make a direct comparison with the system we previously developed using triangular membership functions, we retained the same linguistic variables, the same terms for these variables, and the same rules as presented in Table 1.




Figure 5: Memory Usage MF




Figure 6: CLP Variation MF

The resulting 3D graph showing the variation of the *CLP* with *MemoryUsage* and *ProcessorLoad* can be seen in Figure 7




Figure 7: Fuzzy CLP Inference using Gaussians as MF

This time, the system achieved higher positive *CLP* values, but it worsened on the negative *CLP* values, only going down to -0.2.

To achieve better results, we decided to add more terms to the linguistic variables, merge *MemoryUsage* with *ProcessorLoad* into a single variable, and experiment with different membership functions. By increasing the number of terms, we aim to capture more detailed nuances in the system’s behavior, improving its responsiveness to variations in input. Additionally, merging the two load-related variables simplifies the model without losing critical information. The next sections will address these adjustments in detail, explaining the rationale behind these changes and the impact they have on the system’s performance.

During the experimentation phase with different membership functions, the need for visualization became apparent. To facilitate this, we developed a helper script [fuzzy/visualization/fuzzy_system_to_dataframe] that converts the FuzzySystem Python object into a dynamic dataframe, enabling easy plotting and analysis of the membership functions.

But this time, we combined the variables *ProcessorLoad* and *MemoryUsage* into a single variable: *SystemLoad*, which is defined as the maximum value between these two variables. We chose the maximum value because it allows us to capture the most critical resource constraint affecting system performance. By focusing on the higher load, we ensure that the system reacts to the most demanding condition.

0.2 Generalized Bell

We decided to experiment with a more generic Membership function, so we extended `simpful`'s Base Membership Function class and created `Bell_MF` [in `fuzzy/models/bell_mf.py`]. The first results are shown in the figure bellow.




Figure 8: Memory Usage




Figure 9: Processor Load




Figure 10: CLP Variation

0.3 Architecture

This should contain choice of architecture and why.

0.4 Membership Functions

all the membership functions and linguistic terms

0.5 Rules

rules

CLP Variation		Latency			
		low	moderate	high	very high
System Load	low	IS	IS	I	I
	moderate	I	I	I	I
	high	M	M	D	D
	critical	DS	DS	DS	DS

0.6 Results

Part II

Neural Networks