



```
In [1]: %matplotlib inline
import torch
from d2l import torch as d2l
```


```
In [2]: x = torch.arange(-8.0, 8.0, 0.1, requires_grad=True)
y = torch.relu(x)
d2l.plot(x.detach(), y.detach(), 'x', 'relu(x)', figsize=(5, 2.5))
```




```
In [3]: y.backward(torch.ones_like(x), retain_graph=True)
d2l.plot(x.detach(), x.grad, 'x', 'grad of relu', figsize=(5, 2.5))
```




```
In [4]: y = torch.sigmoid(x)
d2l.plot(x.detach(), y.detach(), 'x', 'sigmoid(x)', figsize=(5, 2.5))
```




```
In [6]: x.grad.data.zero_()
y.backward(torch.ones_like(x), retain_graph=True)
d2l.plot(x.detach(), x.grad, 'x', 'grad of sigmoid', figsize=(5, 2.5))
```



```
In [8]: y = torch.tanh(x)
d2l.plot(x.detach(), y.detach(), 'x', 'tanh(x)', figsize=(5, 2.5))
```



```
In [9]: x.grad.data.zero_()
y.backward(torch.ones_like(x), retain_graph=True)
d2l.plot(x.detach(), x.grad, 'x', 'grad of tanh', figsize=(5, 2.5))
```



Discussion: I learned about multilayer networks in this chapter, and at first, I wondered why we needed to use such complex functions. However, I came to understand that no matter how many linear functions are combined, they cannot break free from linearity, so it's important to use activation functions to introduce non-linearity. Among the various activation functions, I personally like the sigmoid function the most.:

Loading [MathJax]/jax/output/CommonHTML/fonts/TeX/fontdata.js