# Shell Gadus S2 V220 0

Version 2.3 | Revision Date. 31.10.2025 | Print Date. 02.11.2026

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

| | | |
|---|---|---|
| Product name | : | Shell Gadus S2 V220 0 |
| Product code | : | 001D8448 |

### 1.2 Identified relevant uses of the substance or mixture and restrictions on use

**Recommended use of the chemical and restrictions on use**

| | | |
|---|---|---|
| Recommended use | : | Automotive and industrial grease. |
| Restrictions on use | : | This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier. |

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer or supplier's details**

| | | |
|---|---|---|
| Manufacturer/Supplier | : | **Shell India Markets Private Limited**<br>Commerzone, Block-2, No.2<br>200 Feet Radial Road<br>Pallikaranai<br>CHENNAI<br>600100<br>India |
| Telephone | : | (+91) 04446945100 |
| Telefax | : | (+91) 04443451516 |

### 1.4 Emergency telephone number

| | | |
|---|---|---|
| Emergency telephone number | : | +91 22 6516 1058 |

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

| | | |
|---|---|---|
| Substance / Mixture | : | Mixture |
| Chemical nature | : | A lubricating grease containing highly-refined mineral oils and additives.<br>The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.<br>Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L). |

**Hazardous components**

| Chemical name | CAS-No.<br>EC-No.<br>Registration number | Classification (REGULATION (EC) No 1272/2008) | Concentration (% w/w) |
|---|---|---|---|
| Bismuth Naphthenate | 85736-59-0 | Skin Sens. 1; H317<br>Eye Irrit. 2; H319<br>Aquatic Chronic 3; H412 | 0.1 - 0.99 |
| Naphthenic acid | 1338-24-5 | Skin Irrit. 2; H315<br>Skin Sens. 1; H317<br>Eye Irrit. 2; H319 | 0.1 - 0.99 |
| Zinc naphthenate | 12001-85-3 | Skin Sens. 1B; H317<br>Eye Irrit. 2; H319<br>Aquatic Chronic 2; H411 | 0.1 - 0.49 |

For explanation of abbreviations see section 16.

## 3. HAZARDS IDENTIFICATION

### 3.1 Classification of the substance or mixture

Based on available data this substance / mixture does not meet the classification criteria.

### 3.2 Label elements

Safety data sheet available on request.

Hazard pictograms : No Hazard Symbol required
Signal word : No signal word

Hazard statements : PHYSICAL HAZARDS:
Not classified as a physical hazard according to CLP criteria.
HEALTH HAZARDS:
Not classified as a health hazard under CLP criteria.
ENVIRONMENTAL HAZARDS:
Not classified as environmental hazard according to CLP criteria.

Precautionary statements : **Prevention:**
No precautionary phrases.
**Response:**
No precautionary phrases.

**Storage:**
No precautionary phrases.
**Disposal:**
No precautionary phrases.

### 3.3 Other hazards

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used grease may contain harmful impurities. High-pressure injection under the skin may cause serious damage including local necrosis. Not classified as flammable but will burn.

## 4. FIRST-AID MEASURES

### 4.1 Description of first aid measures

| | | |
|---|---|---|
| If inhaled | : | No treatment necessary under normal conditions of use.<br>If symptoms persist, obtain medical advice. |
| In case of skin contact | : | Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.<br>If persistent irritation occurs, obtain medical attention.<br>When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.<br>Obtain medical attention even in the absence of apparent wounds. |
| In case of eye contact | : | Flush eye with copious quantities of water.<br>Remove contact lenses, if present and easy to do. Continue rinsing.<br>If persistent irritation occurs, obtain medical attention. |
| If swallowed | : | In general no treatment is necessary unless large quantities are swallowed, however, get medical advice. |

### 4.2 Protection of first-aiders

| | | |
|---|---|---|
| Protection of first-aiders | : | When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings. |

### 4.3 Most important symptoms and effects, both acute and delayed

| | | |
|---|---|---|
| Most important symptoms and effects, both acute and delayed | : | Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.<br>Ingestion may result in nausea, vomiting and/or diarrhea.<br>Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection. |
| Notes to physician | : | Treat symptomatically.<br>High pressure injection injuries require prompt surgical |

intervention and possibly steroid therapy, to minimise tissue damage and loss of function.
Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

## 5. FIRE-FIGHTING MEASURES

### 5.1 Extinguishing media

| | | |
|---|---|---|
| Suitable extinguishing media | : | Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. |
| Unsuitable extinguishing media | : | Do not use water in a jet. |

### 5.2 Special hazards arising from the substance or mixture

| | | |
|---|---|---|
| Specific hazards during firefighting | : | Hazardous combustion products may include:<br>A complex mixture of airborne solid and liquid particulates and gases (smoke).<br>Carbon monoxide may be evolved if incomplete combustion occurs.<br>Unidentified organic and inorganic compounds. |

### 5.3 Recomendations for fire-fighters

| | | |
|---|---|---|
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Special protective equipment for firefighters | : | Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469). |

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

| | | |
|---|---|---|
| Personal precautions | : | Avoid contact with skin and eyes. |

### 6.2 Environmental precautions

| | | |
|---|---|---|
| Environmental precautions | : | Use appropriate containment to prevent uncontrolled release.<br>Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. |

### 6.3 Methods and material for containment and cleaning up

| | | |
|---|---|---|
| Methods and materials for containment and cleaning up | : | Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. |

### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

| | | |
|---|---|---|
| General Precautions | : | Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.<br>Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. |
| Advice on safe handling | : | Avoid prolonged or repeated contact with skin.<br>Avoid inhaling vapour and/or mists.<br>When handling product in drums, safety footwear should be worn and proper handling equipment should be used.<br>Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. |
| Avoidance of contact | : | Strong oxidising agents. |

### 7.2 Conditions for safe storage, including any incompatibilities

| | | |
|---|---|---|
| Other data | : | Keep container tightly closed and in a cool, well-ventilated place.<br>Use properly labeled and closable containers.<br><br>Store at ambient temperature. |
| Packaging material | : | Suitable material: For containers or container linings, use mild steel or high density polyethylene.<br>Unsuitable material: PVC. |
| Container Advice | : | Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion. |

### 7.3 Specific end use(s)

Specific use(s) : Automotive and industrial grease.

Uses advised against : This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---|---|---|---|---|
| Oil mist, mineral | Not Assigned | TWA (Mist) | 5 mg/m3 | IN OEL |
| Oil mist, mineral | Not Assigned | STEL (Mist) | 10 mg/m3 | IN OEL |
| Oil mist, mineral | Not Assigned | TWA (inhalable fraction) | 5 mg/m3 | US. ACGIH Threshold Limit Values |
| Oil mist, mineral | Not Assigned | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| Oil mist, mineral | Not Assigned | TWA (Inhalable particulate matter) | 5 mg/m3 | ACGIH |

**Biological occupational exposure limits**

Biological Limit Values (BLV) have not been established for this material.

### 8.2 Exposure controls

**Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.
Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.
Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.
National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/
Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/
Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/
Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp
L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

**Engineering measures** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:
Adequate ventilation to control airborne concentrations.
Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
General Information
Define procedures for safe handling and maintenance of controls.
Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.
Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.
Drain down system prior to equipment break-in or maintenance.
Retain drain downs in sealed storage pending disposal or subsequent recycle.
Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.
Practice good housekeeping.
Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.

**Personal protective equipment**

**Protective measures**

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection : No respiratory protection is ordinarily required under normal conditions of use.
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.
Check with respiratory protective equipment suppliers.
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.
Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Hand protection

| | | |
|---|---|---|
| Remarks | : | Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.<br><br>For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. |
| Eye protection | : | If material is handled such that it could be splashed into eyes, protective eyewear is recommended. |
| Skin and body protection | : | Skin protection is not ordinarily required beyond standard work clothes.<br>It is good practice to wear chemical resistant gloves. |
| Thermal hazards | : | Not applicable |

**Environmental exposure controls**

| | | |
|---|---|---|
| General advice | : | Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.<br>Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. |

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**9.1 Information on basic physical and chemical properties**

| | | |
|---|---|---|
| Appearance | : | Semi-solid at ambient temperature. |
| Colour | : | brown |
| Odour | : | Slight hydrocarbon |
| Odour Threshold | : | Data not available |
| pH | : | Not applicable |
| Dropping point | : | >= 180 °C / >= 356 °F<br>Method: Unspecified |
| Melting point/freezing point | | Data not available |
| Initial boiling point and boiling range | : | Data not available |
| Flash point | : | Not applicable |
| Evaporation rate | : | Data not available |
| Flammability (solid, gas) | : | Not applicable |
| Flammability (liquids) | : | Not classified as flammable but will burn. |
| Upper explosion limit | : | Typical 10 %(V) |
| Lower explosion limit | : | Typical 1 %(V) |
| Vapour pressure | : | < 0.5 Pa (20 °C / 68 °F)<br>estimated value(s) |
| Relative vapour density | : | > 1estimated value(s) |
| Density | : | 1,000 kg/m3 (15.0 °C / 59.0 °F)<br>Method: Unspecified |
| Solubility(ies) | | |
| Water solubility | : | negligible |
| Solubility in other solvents | : | Data not available |
| Partition coefficient: n-octanol/water | : | log Pow: > 6<br>(based on information on similar products) |
| Auto-ignition temperature | : | > 320 °C / 608 °F |
| Decomposition temperature | : | Data not available |
| Viscosity | | |

| | | |
|---|---|---|
| Viscosity, dynamic | : | Data not available |
| Viscosity, kinematic | : | Not applicable |
| Particle size | : | Data not available |

**9.2 Other information**

| | | |
|---|---|---|
| Explosive properties | : | Classification Code: Not classified |
| Oxidizing properties | : | Data not available |
| Conductivity | : | This material is not expected to be a static accumulator. |

## 10. STABILITY AND REACTIVITY

**10.1 Reactivity**

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

**10.2 Chemical stability**

Stable.

**10.3 Possibility of hazardous reactions**

| | | |
|---|---|---|
| Hazardous reactions | : | Reacts with strong oxidising agents. |

**10.4 Conditions to avoid**

| | | |
|---|---|---|
| Conditions to avoid | : | Extremes of temperature and direct sunlight. |

**10.5 Incompatible materials**

| | | |
|---|---|---|
| Materials to avoid | : | Strong oxidising agents. |

**10.6 Hazardous decomposition products**

: No decomposition if stored and applied as directed.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

| | | |
|---|---|---|
| Basis for assessment | : | Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). |
| Information on likely routes of exposure | : | Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion. |

**Acute toxicity**

**Product:**

| | | |
|---|---|---|
| Acute oral toxicity | : | LD50 rat: > 5,000 mg/kg<br>Remarks: Low toxicity<br>Based on available data, the classification criteria are not met. |
| Acute inhalation toxicity | : | Remarks: Based on available data, the classification criteria are not met. |
| Acute dermal toxicity | : | LD50 Rabbit: > 5,000 mg/kg<br>Remarks: Low toxicity<br>Based on available data, the classification criteria are not met. |

**Skin corrosion/irritation**

**Product:**

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

**Serious eye damage/eye irritation**

**Product:**

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation**

**Product:**

Remarks: Not a skin sensitiser.
Based on available data, the classification criteria are not met.

**Components:**

**Naphthenic acid:**
Remarks: May cause an allergic skin reaction in sensitive individuals.

**Germ cell mutagenicity**

**Product:**

Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

**Carcinogenicity**

**Product:**

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

| Material | GHS/CLP Carcinogenicity Classification |
|---|---|
| Highly refined mineral oil | No carcinogenicity classification. |

**Reproductive toxicity**

**Product:**

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

**STOT - single exposure**

**Product:**

Remarks: Based on available data, the classification criteria are not met.

**STOT - repeated exposure**

**Product:**

Remarks: Based on available data, the classification criteria are not met.

**Aspiration toxicity**

**Product:**

Not an aspiration hazard.

### 11.2 Information on other hazards

**Further information**

**Product:**

Remarks: Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal., ALL used grease should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

## 12. ECOLOGICAL INFORMATION

| | | |
|---|---|---|
| Basis for assessment | : | Ecotoxicological data have not been determined specifically for this product.<br>Information given is based on a knowledge of the components and the ecotoxicology of similar products.<br>Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). |

### 12.1 Toxicity

**Product:**

| | | |
|---|---|---|
| Toxicity to fish (Acute toxicity) | : | Remarks: Based on available data, the classification criteria are not met.<br>Practically non toxic:<br>LL/EL/IL50 > 100 mg/l |
| Toxicity to crustacean (Acute toxicity) | : | Remarks: Based on available data, the classification criteria are not met.<br>Practically non toxic:<br>LL/EL/IL50 > 100 mg/l |
| Toxicity to algae/aquatic plants (Acute toxicity) | : | Remarks: Based on available data, the classification criteria are not met.<br>Practically non toxic:<br>LL/EL/IL50 > 100 mg/l |

| | | |
|---|---|---|
| Toxicity to fish (Chronic toxicity) | : | Remarks: Based on available data, the classification criteria are not met. |
| Toxicity to crustacean (Chronic toxicity) | : | Remarks: Based on available data, the classification criteria are not met. |
| Toxicity to microorganisms (Acute toxicity) | : | Remarks: Based on available data, the classification criteria are not met. |

### 12.2 Persistence and degradability

**Product:**

| | | |
|---|---|---|
| Biodegradability | : | Remarks: Not readily biodegradable., Major constituents are inherently biodegradable, but contains components that may persist in the environment., Persistent per IMO criteria., International Oil Pollution Compensation (IOPC) Fund definition: “A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340ºC (645ºF) and (b) at least 95% of which, by volume, distils at a temperature of 370ºC (700ºF) when tested by the ASTM Method D-86/78 or any subsequent revision thereof." |

### 12.3 Bioaccumulative potential

**Product:**

| | | |
|---|---|---|
| Bioaccumulation | : | Remarks: Contains components with the potential to bioaccumulate. |
| Partition coefficient: n-octanol/water | : | log Pow: > 6Remarks: (based on information on similar products) |

### 12.4 Mobility in soil

**Product:**

| | | |
|---|---|---|
| Mobility | : | Remarks: Semi-solid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile.<br>Remarks: Floats on water. |

### 12.5 Other adverse effects

No data available

**Product:**

| | | |
|---|---|---|
| Additional ecological information | : | Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential., Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.<br>Poorly soluble mixture., Causes physical fouling of aquatic organisms.<br>Mineral oil does not cause chronic toxicity to aquatic organisms at concentrations less than 1 mg/l. |

## 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

| | | |
|---|---|---|
| Waste from residues | : | Recover or recycle if possible.<br>It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.<br>Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.<br>Do not dispose into the environment, in drains or in water courses.<br>Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.<br>Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.<br>MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships. |
| Contaminated packaging | : | Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.<br>Disposal should be in accordance with applicable regional, national, and local laws and regulations. |

Local legislation
Remarks : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

## 14. TRANSPORT INFORMATION

### 14.1 UN number or ID number

**ADR** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good
**IATA** : Not regulated as a dangerous good

### 14.2 UN proper shipping name

**ADR** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good
**IATA** : Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

**ADR** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good
**IATA** : Not regulated as a dangerous good

### 14.4 Packing group

**ADR** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good
**IATA** : Not regulated as a dangerous good

### 14.5 Environmental hazards

**ADR** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

### 14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

### 14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

## 15. REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The Manufacture, Storage and Import of Hazardous Chemicals Rules 1989 (amended version issued 2000). The Factories Act, 1948, The Second Schedule: Permissible levels of certain chemical substances in work environment, as amended through 1987. India Central motor Vehicles (Amendment) Rules 1993.

**Other international regulations**

**The components of this product are reported in the following inventories:**

TSCA : All components listed.

## 16. OTHER INFORMATION

**Full text of H-Statements**

| | |
|---|---|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H412 | Harmful to aquatic life with long lasting effects. |

**Full text of other abbreviations**

| | |
|---|---|
| Aquatic Chronic | Long-term (chronic) aquatic hazard |
| Eye Irrit. | Eye irritation |
| Skin Irrit. | Skin irritation |
| Skin Sens. | Skin sensitisation |

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

**Further information**

Other information : A vertical bar (|) in the left margin indicates an amendment from the previous version.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.