

Exp No: 4**Create UDF in PIG****Step-by-step installation of Apache Pig on Hadoop cluster on Ubuntu****Pre-requisite:**

- Ubuntu 16.04 or higher version running (I have installed Ubuntu on Oracle VM (Virtual Machine) VirtualBox),
- Run Hadoop on ubuntu (I have installed Hadoop 3.2.1 on Ubuntu 16.04). You may refer to my blog “How to install Hadoop installation” click here for Hadoop installation).

Pig installation steps

Step 1: Login into Ubuntu

Step 2: Go to <https://pig.apache.org/releases.html> and copy the path of the latest version of pig that you want to install. Run the following command to download Apache Pig in Ubuntu:

```
$ wget https://dlcdn.apache.org/pig/pig-0.16.0/pig-0.16.0.tar.gz
```

Step 3: To untar pig-0.16.0.tar.gz file run the following command:

```
$ tar xvfz pig-0.16.0.tar.gz
```

Step 4: To create a pig folder and move pig-0.16.0 to the pig folder, execute the following command:

```
$ sudo mv /home/hadoop/pig-0.16.0 /home/hadoop/pig
```

Step 5: Now open the .bashrc file to edit the path and variables/settings for pig. Run the following command:

```
$ sudo nano .bashrc
```

Add the below given to .bashrc file at the end and save the file.

```
#PIG settingsexport PIG_HOME=/home/hadoop/pigexport
```

```
PATH=$PATH:$PIG_HOME/binexport
```

```
PIG_CLASSPATH=$PIG_HOME/conf:$HADOOP_INSTALL/etc/hadoop/export
```

```
PIG_CONF_DIR=$PIG_HOME/confexport JAVA_HOME=/usr/lib/jvm/java-8-openjdkamd64export
```

```
PIG_CLASSPATH=$PIG_CONF_DIR:$PATH#PIG setting ends
```

```
export PIG_HOME=/home/haresh/pig
export PATH=$PATH:$PIG_HOME/bin
export PIG_CLASSPATH=$PIG_HOME/conf:$HADOOP_INSTALL/etc/hadoop/
export PIG_CONF_DIR=$PIG_HOME/conf
export PIG_CLASSPATH=$PIG_CONF_DIR:$PATH
```

Step 6: Run the following command to make the changes effective in the .bashrc file:

```
$ source .bashrc
```

Step 7: To start all Hadoop daemons, navigate to the hadoop-3.2.1/sbin folder and run the following commands:

```
$ ./start-dfs.sh$ ./start-yarn$ jps
```

```
kvnk@kv8604:~$ start-all.sh
WARNING: Attempting to start all Apache Hadoop daemons as kvnk in 10 seconds.
WARNING: This is not a recommended production deployment configuration.
WARNING: Use CTRL-C to abort.
Starting namenodes on [localhost]
Starting datanodes
Starting secondary namenodes [kv8604]
2024-11-21 23:18:01,984 WARN util.NativeCodeLoader: Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
Starting resourcemanager
Starting nodemanagers
kvnk@kv8604:~$
```

Now you can launch pig by executing the following command:

```
$ pig
```

```
kvnk@kv8604:~$ pig
2024-11-22 00:03:54,605 INFO pig.ExecTypeProvider: Trying ExecType : LOCAL
2024-11-22 00:03:54,626 INFO pig.ExecTypeProvider: Trying ExecType : MAPREDUCE
2024-11-22 00:03:54,626 INFO pig.ExecTypeProvider: Picked MAPREDUCE as the ExecType
2024-11-22 00:03:54,845 [main] INFO org.apache.pig.Main - Apache Pig version 0.16.0 (r1746530) compiled Jun 01 2016, 23:10:49
2024-11-22 00:03:54,872 [main] INFO org.apache.pig.Main - Logging error messages to: /home/kvnk/pig_1732214034815.log
2024-11-22 00:03:55,076 [main] INFO org.apache.pig.impl.util.Utils - Default bootup file /home/kvnk/.pigbootup not found
2024-11-22 00:03:55,904 [main] WARN org.apache.hadoop.util.NativeCodeLoader - Unable to load native-hadoop library for your platform... using builtin-java classes where applicable
2024-11-22 00:03:56,014 [main] INFO org.apache.hadoop.conf.Configuration.deprecation - mapred.job.tracker is deprecated. Instead, use mapreduce.jobtracker.address
2024-11-22 00:03:56,014 [main] INFO org.apache.hadoop.conf.Configuration.deprecation - fs.default.name is deprecated. Instead, use fs.defaultFS
2024-11-22 00:03:56,014 [main] INFO org.apache.pig.backend.hadoop.executionengine.HExecutionEngine - Connecting to hadoop file system at: hdfs://localhost:9000
2024-11-22 00:03:57,648 [main] INFO org.apache.hadoop.conf.Configuration.deprecation - fs.default.name is deprecated. Instead, use fs.defaultFS
2024-11-22 00:03:57,764 [main] INFO org.apache.pig.PigServer - Pig Script ID for the session: PIG-default-b7180c67-9194-4fb6-b144-d3044fe888ac
2024-11-22 00:03:57,787 [main] WARN org.apache.pig.PigServer - ATS is disabled since yarn.timeline-service.enabled set to false
grunt> █
```

Step 9: Now you are in pig and can perform your desired tasks on pig. You can come out of the pig by the quit command:

```
> quit
```

CREATE USER DEFINED FUNCTION(UDF)

Aim :

To create User Define Function in Apache Pig and execute it on map reduce.

Procedure:

Create a sample text file

```
hadoop@Ubuntu:~/Documents$ nano sample.txt
```

Paste the below content to sample.txt

1,John

2,Jane

3,Joe

4,Emma

```
hadoop@Ubuntu:~/Documents$ hadoop fs -put sample.txt /home/hadoop/piginput/
```

Create PIG File

```
hadoop@Ubuntu:~/Documents$ nano demo_pig.pig
```

paste the below the content to demo_pig.pig

```
-- Load the data from HDFS
```

```
data = LOAD '/home/hadoop/piginput/sample.txt' USING PigStorage(',') AS (id:int>
```

```
-- Dump the data to check if it was loaded correctly
```

```
DUMP data;
```

Run the above file

```
hadoop@Ubuntu:~/Documents$ pig demo_pig.pig
```

```
2024-08-07 12:13:08,791 [main] INFO
```

```
org.apache.pig.backend.hadoop.executionengine.util.MapRedUtil
```

```
- Total input paths to process : 1
```

```
(1,John)
```

```
(2,Jane)
```

```
(3,Joe)
```

```
(4,Emma)
```

Create udf file an save as uppercase_udf.py

```
uppercase_udf.py
```

```
-----
def uppercase(text):
    return text.upper()
if __name__ == "__main__":
    import sys
    for line in sys.stdin:
        line = line.strip()
        result = uppercase(line)
        print(result)
-----
```

Create the udfs folder on hadoop

```
hadoop@Ubuntu:~/Documents$ hadoop fs -mkdir /home/hadoop/udfs
```

put the upppercase_udf.py in to the abv folder

```
hadoop@Ubuntu:~/Documents$ hdfs dfs -put uppercase_udf.py /home/hadoop/udfs/
```

```
-----
hadoop@Ubuntu:~/Documents$ nano udf_example.pig
```

copy and paste the below content on udf_example.pig

-- Register the Python UDF script

```
REGISTER 'hdfs:///home/hadoop/udfs/uppercase_udf.py' USING jython AS udf;
```

-- Load some data

```
data = LOAD 'hdfs:///home/hadoop/sample.txt' AS (text:chararray);
```

-- Use the Python UDF

```
uppercased_data = FOREACH data GENERATE udf.uppercase(text) AS uppercase_text;
```

-- Store the result

```
STORE uppercased_data INTO 'hdfs:///home/hadoop/pig_output_data';
```

place sample.txt file on hadoop

```
-----
hadoop@Ubuntu:~/Documents$ hadoop fs -put sample.txt /home/hadoop/
```

To Run the pig file

hadoop@Ubuntu:~/Documents\$ pig -f udf_example.pig

finally u get

Success!

Job Stats (time in seconds):

JobId Maps Reduces MaxMapTimeMinMapTime AvgMapTime MedianMapTime

MaxReduceTime MinReduceTime AvgReduceTime MedianReducetime

Alias Feature Outputs

job_local1786848041_0001 1 0 n/a n/a n/a n/a 00 0 0

data,uppercased_data MAP_ONLY hdfs:///home/hadoop/pig_output_data,

Input(s):

Successfully read 4 records (42778068 bytes) from: "hdfs:///home/hadoop/sample.txt"

Output(s):

```
2024-09-13 10:19:39,234 [main] INFO org.apache.hadoop.ipc.Client - Retrying connect to server: 0.0.0.0/0.0.0.0:10020. Already tried 4 time(s); retry policy is RetryUpToMaximumCountWithFixedSleep(maxRetries=10, sleepTime=1000 MILLISECONDS)
2024-09-13 10:19:40,251 [main] INFO org.apache.hadoop.ipc.Client - Retrying connect to server: 0.0.0.0/0.0.0.0:10020. Already tried 5 time(s); retry policy is RetryUpToMaximumCountWithFixedSleep(maxRetries=10, sleepTime=1000 MILLISECONDS)
2024-09-13 10:19:41,252 [main] INFO org.apache.hadoop.ipc.Client - Retrying connect to server: 0.0.0.0/0.0.0.0:10020. Already tried 6 time(s); retry policy is RetryUpToMaximumCountWithFixedSleep(maxRetries=10, sleepTime=1000 MILLISECONDS)
2024-09-13 10:19:42,255 [main] INFO org.apache.hadoop.ipc.Client - Retrying connect to server: 0.0.0.0/0.0.0.0:10020. Already tried 7 time(s); retry policy is RetryUpToMaximumCountWithFixedSleep(maxRetries=10, sleepTime=1000 MILLISECONDS)
2024-09-13 10:19:43,259 [main] INFO org.apache.hadoop.ipc.Client - Retrying connect to server: 0.0.0.0/0.0.0.0:10020. Already tried 8 time(s); retry policy is RetryUpToMaximumCountWithFixedSleep(maxRetries=10, sleepTime=1000 MILLISECONDS)
2024-09-13 10:19:44,277 [main] INFO org.apache.hadoop.ipc.Client - Retrying connect to server: 0.0.0.0/0.0.0.0:10020. Already tried 9 time(s); retry policy is RetryUpToMaximumCountWithFixedSleep(maxRetries=10, sleepTime=1000 MILLISECONDS)
2024-09-13 10:19:44,396 [main] WARN org.apache.pig.backend.hadoop.executionengine.mapReduceLayer.MapReduceLauncher - Unable to retrieve job to compute warning aggregation.
2024-09-13 10:19:44,397 [main] INFO org.apache.pig.backend.hadoop.executionengine.mapReduceLayer.MapReduceLauncher - Success!
2024-09-13 10:19:44,490 [main] INFO org.apache.pig.Main - Pig script completed in 2 minutes, 57 seconds and 220 milliseconds (177220 ms)
```

Successfully stored 4 records (42777870 bytes) in: "hdfs:///home/hadoop/pig_output_data"

Counters:

Total records written : 4

Total bytes written : 42777870

Spillable Memory Manager spill count : 0

Total bags proactively spilled: 0

Total records proactively spilled: 0

Job DAG:

job_local1786848041_0001

2024-08-07 13:33:04,631 [main] WARN

org.apache.hadoop.metrics2.impl.MetricsSystemImpl -

JobTracker metrics system already initialized!

2024-08-07 13:33:04,639 [main] WARN

org.apache.hadoop.metrics2.impl.MetricsSystemImpl -

JobTracker metrics system already initialized!

2024-08-07 13:33:04,644 [main] WARN

org.apache.hadoop.metrics2.impl.MetricsSystemImpl -

JobTracker metrics system already initialized!

2024-08-07 13:33:04,667 [main] INFO

org.apache.pig.backend.hadoop.executionengine.mapReduceLayer.MapReduceLauncher -

Success!

Note :

If any error check jython package is installed and check the path specified on the above steps are give correctly

To check the output file is created

hadoop@Ubuntu:~/Documents\$ hdfs dfs -ls /home/hadoop/pig_output_data

Found 2 items

If you need to examine the files in the output folder, use:

To view the output

hadoop@Ubuntu:~/Documents\$ hdfs dfs -cat /home/hadoop/pig_output_data/part-m00000

1,JOHN

2,JANE

3,JOE

4,EMMA

```
kvnk@kv8604:~$ hdfs dfs -cat /pig_output_data/part-m-00000
2024-11-22 00:40:12,343 WARN util.NativeCodeLoader: Unable to load native code
sses where applicable
1,JOHN
2,JANE
3,JOE
4,EMMA
```

Result:

Thus, the program is executed successfully