

Package ‘GLFC’

June 19, 2015

Title Great Lakes Fishery Commission

Version 0.0.0.9003

Description Functions developed for the Great Lakes Fishery Commission's sea lamprey control program, including estimation of the index of adult sea lamprey abundance.

Depends R (>= 3.1.3)

Imports plyr, maps, rtf

License GPL

LazyData TRUE

URL <https://github.com/JVAdams/GLFC>

Author Jean V. Adams [aut, cre]

Maintainer Jean V. Adams <jvadams@usgs.gov>

R topics documented:

Alcheck	2
Alestimate	2
Alprep	3
Alreport	4
Altarget	5
endrtf	6
estAIndex	6
figbig	8
figu	9
GLFCenv	10
heading	10
index2pe	11
jackIndex	11
lsIndex	12
lsKeep	12
para	13
predAntilog	13
prettytable	14
startrtf	15
tabl	16
trappedStreams	17
Index	18

AIcheck

*Error Check the Adult Index Data***Description**

Check the adult sea lamprey trapping data (collected for estimation of the Adult Index) for errors.

Usage

```
AIcheck(streamDat, csvDir, outFile = NULL, otherTabs = NULL)
```

Arguments

streamDat	A data frame of old and new stream mark-recapture estimates used to estimate the lake-wide Adult Indices, typically the output from AIprep . The data frame must include: year, lake, lake-stream ID lscore (see details), population estimate PEmr, coefficient of variation CVmr (100 identifying the index streams; maintain a logical identifying the streams that will continue to have ongoing trapping even if not part of the Adult Index; indexContrib a numeric, the stream population estimate that will be used in the Adult Index (NA for new); and complete a logical identifying streams and years for which the Adult Index has already been estimated (FALSE for new).
csvDir	A character scalar identifying the path where the rtf file will be stored, e.g., csvDir = "C:\temp\mydir".
outFile	Name of the output rtf file, default NULL, in which case the file will be named "YYYY Adult Index - error checking.doc" where YYYY is the latest year represented in streamDat.
otherTabs	A list of other tables to be printed in error check report, default NULL. The list names will be used as captions.

Details

Lake-stream IDs are combination of lake ID and stream ID e.g., 1.064 = lake ID + (stream ID)/1000.

Value

An error checking document as an rtf file (with the file type *.doc, so that MS Word will open it automatically).

AIestimate

*Estimate Index of Sea Lamprey Adults***Description**

Estimate the Adult Index of sea lampreys in a single Great Lake.

Usage

```
AIestimate(streamDat, minNMR = 2)
```

Arguments

streamDat	A data frame of old and new stream mark-recapture estimates used to estimate the lake-wide Adult Indices, typically the output from AIprep . The data frame must include: year, lake, lake-stream ID lscore (see details), population estimate PEmr, coefficient of variation CVmr (100 identifying the index streams; maintain a logical identifying the streams that will continue to have ongoing trapping even if not part of the Adult Index; indexContrib a numeric, the stream population estimate that will be used in the Adult Index (NA for new); and complete a logical identifying streams and years for which the Adult Index has already been estimated (FALSE for new).
minNMR	An integer scalar greater than or equal to 2, the minimum number of mark-recapture estimates needed in a year to generate an index, default 2.

Details

The annual Adult Index is simply the sum of stream population estimates for each year. Missing stream estimates are estimated by a lake-specific ANOVA model relating the log of the stream estimates to the main effects of each stream and each year, weighted by the inverse of the CV squared. The jackknifed range is produced by recalculating the index, leaving out one stream at a time, then scaling up the result to the same scale as the Adult Index based on all streams.

Value

A list with 2 components: streamDat, a data frame of stream mark-recapture and Adult Index contributions for the incomplete rows in streamDat, with the same variables as streamDat; and lakeIndex, a data frame of annual lake-wide Adult Indices for the incomplete rows in (streamDat), with 5 columns: lake, year, the Adult Index index, and the lower and upper jackknifed range jlo and jhi.

AIprep	<i>Prepare the Adult Index Data</i>
--------	-------------------------------------

Description

Read in the adult sea lamprey trapping data (collected for estimation of the Adult Index) and prepare it for estimation.

Usage

```
AIprep(csvDir, csvNew, csvOld = NULL, streamInfo = trappedStreams,
       indexStreams = lsIndex, keepStreams = lsKeep)
```

Arguments

csvDir	A character scalar identifying the path where the csv files are stored, e.g., csvDir = "C:\temp\mydir"
csvNew	A character scalar identifying the name of the csv file with stream mark-recapture estimates for which Adult Indices will be estimated (typically from the current year). The first row of the csv file should be column headers and must include: year, lake, lake-stream ID lscore (see details), population estimate PEmr, coefficient of variation CVmr ($100\% * \sqrt{\text{variance}(\text{PEmr})} / \text{PEmr}$). See details.

csvOld	A character scalar identifying the name of the csv file with stream mark-recapture estimates for which Adult Indices have already been estimated (typically from previous years), with the same variables as in csvNew plus the previously estimated contribution indexContrib, default NULL. See details.
streamInfo	A data frame with stream information to be combined with the estimates data (csvNew and csvOld), default <code>trappedStreams</code> . Set to NULL if you don't want any stream information to be brought in.
indexStreams	Lake-stream IDs identifying index streams, default <code>lsIndex</code> .
keepStreams	Lake-stream IDs identifying streams which will continue to have ongoing trapping even if not part of the Adult Index, default <code>lsKeep</code> .

Details

Lake-stream IDs are combination of lake ID and stream ID e.g., 1.064 = lake ID + (stream ID)/1000. For both estimate files (csvNew and csvOld), there should be no missing values in year, lake, or lscore. Both files may contain variables other than those required. Those with the same name as variables in streamInfo will be replaced. Others will be kept.

Value

A single data frame that contains the information from all of the inputs, including new variables: index, a logical identifying the index streams; maintain a logical identifying the streams that will continue to have ongoing trapping even if not part of the Adult Index; indexContrib a numeric, the stream population estimate that will be used in the Adult Index (NA for csvNew); and complete a logical identifying streams and years for which the Adult Index has already been estimated (FALSE for csvNew).

AIreport

Adult Index Report

Description

Create a draft template-style report of the Adult Index estimates of sea lamprey in the Great Lakes.

Usage

```
AIreport(streamPEs, lakeIPes, targets, csvDir, outFile = NULL)
```

Arguments

streamPEs	A data frame of "complete" stream mark-recapture estimates (meaning all contributions to the Adult Indices have already been calculated). The data frame must include: year, lake, lake-stream ID lscore (see details), population estimate PEmr, coefficient of variation CVmr (100 identifying the index streams; maintain a logical identifying the streams that will continue to have ongoing trapping even if not part of the Adult Index; indexContrib a numeric, the stream population estimate that will be used in the Adult Index (NA for new); and complete a logical identifying streams and years for which the Adult Index has already been estimated (should be all TRUE).
-----------	---

lakeIPes	A data frame of annual lake-wide Adult Indices with 8 columns: lake, year, the Adult Index index, its associated lower and upper jackknifed range jlo and jhi, and the corresponding expansion to a supposed population estimate, pe, pelo and pehi. The data frame may contain variables other than those required.
targets	A data frame with the calculated targets for the Adult Index and expanded PE of each Great Lake, with 3 columns: lake, targInd, and targPE, typically the output from AItarget .
csvDir	A character scalar identifying the path where the rtf file will be stored, e.g., csvDir = "C:\temp\mydir".
outFile	Name of the output rtf file, default NULL, in which case the file will be named "YYYY Adult Index - draft report.doc" where YYYY is the latest year represented in streamDat.

Details

Lake-stream IDs are combination of lake ID and stream ID e.g., 1.064 = lake ID + (stream ID)/1000.

Value

A draft report document as an rtf file (with the file type *.doc, so that MS Word will open it automatically).

AItarget	<i>Calculate Targets for the Adult Index</i>
----------	--

Description

Calculate lake-wide targets for the Adult Index of sea lamprey populations in the Great Lakes from the mean of specified years.

Usage

```
AItarget(lakeIndex, years = list(1994:1998, 1988:1992, 1989:1993, 1991:1995,
                                1993:1997), adjust = c(1, 1, 0.25, 1, 1))
```

Arguments

lakeIndex	A data frame of annual lake-wide Adult Indices with 4 columns: lake, year, the Adult Index index, and the corresponding estimates expanded out to a supposed population estimate, pe. The data frame may contain variables other than those required.
years	A list of length 5 (for each Great Lake respectively: Superior, Michigan, Huron, Erie, and Ontario), each element an integer vector of length 5 specifying the 5 years during which there were acceptable sea lamprey wounding rates on lake trout, default list(1994:1998, 1988:1992, 1989:1993, 1991:1995, 1993:1997). These will be used to generate Adult Index targets.
adjust	A numeric vector of length 5 (for each Great Lake), specifying adjustments to be made to the calculated means to generate Adult Index targets, default c(1, 1, 0.25, 1, 1). Since Lake Huron did not have a time period with acceptable sea lamprey wounding rates, the target is set to 25% of the mean for 1989-1993.

Value

A data frame with the calculated targets for the Adult Index and expanded PE of each Great Lake, with 3 columns: lake, targInd, and targPE.

endrtf	<i>Write and Close an RTF Document</i>
--------	--

Description

Write and close an rtf (rich text format) document.

Usage

```
endrtf(rtf = doc, details = FALSE, ...)
```

Arguments

rtf	An rtf object, default doc.
details	Logical scalar indicating if session details should be added to the end of the document, default FALSE.
...	Additional parameters to addPageBreak .

See Also

[startrtf](#) for an example, [heading](#), [para](#), [tabl](#), [figu](#), [figbig](#), [RTF](#), [addPageBreak](#).

estAIndex	<i>Estimate Index of Sea Lamprey Adults</i>
-----------	---

Description

Estimate the Adult Index of sea lampreys in a single Great Lake.

Usage

```
estAIndex(indexStreams, streamPECurr, streamPEPrev = NULL, varKeep = NULL,
  minNMR = 2)
```

Arguments

indexStreams	A numeric vector of lake-stream IDs identifying streams to be included in the index, e.g., 1.064 = lake ID + (stream ID)/1000.
streamPECurr	A data frame of stream mark-recapture estimates without any previously estimated Adult Indices (typically from the current year), with variables: year, lake, lake-stream ID lscore (see description under indexStreams), population estimate PEmr, coefficient of variation CVmr (100 in year, lake, or lscore). There should be only one value for lake in the data frame. The data frame may include additional variables, but they will be ignored unless listed in varKeep.

streamPEPrev	A data frame of stream mark-recapture estimates with estimated Adult Index contributions (typically from previous years), with the same variables as in streamPECurr plus the previously estimated contribution indexContrib, default NULL. There should be no missing values in year, lake, or lscore. The data frame may include additional variables, but they will be ignored unless listed in varKeep.
varKeep	A character vector naming additional variables (present in both streamPECurr and streamPEPrev) to keep in the output data frame (streamPE), default NULL.
minNMR	An integer scalar greater than or equal to 2, the minimum number of mark-recapture estimates needed in a year to generate an index, default 2.

Details

The annual Adult Index is simply the sum of stream population estimates for each year. Missing stream estimates are estimated by a lake-specific ANOVA model relating the log of the stream estimates to the main effects of each stream and each year, weighted by the inverse of the CV squared. The jackknifed range is produced by recalculating the index, leaving out one stream at a time, then scaling up the result to the same scale as the Adult Index based on all streams.

Value

A list with 2 components: streamPE, a data frame of stream mark-recapture and Adult Index contributions for the current data (streamPECurr), with the same variables as streamPEPrev; and lakeIndex, a data frame of annual lake-wide Adult Indices for the current data (streamPECurr), with 5 columns: lake, year, the Adult Index index, and the lower and upper jackknifed range jlo and jhi.

Examples

```
# estimate the index initially for 1998-1999 data
str9899 <- data.frame(
  year=rep(1998:1999, c(3, 3)), lake=1,
  lscore=rep(c(1.1, 1.2, 1.3), 2),
  PEmr=c(15, 20, NA, 12, 22, 30),
  CVmr=c(50, 50, NA, 50, 40, 30))
istr <- c(1.1, 1.2, 1.3)
est9899 <- estAIndex(indexStreams=istr, streamPECurr=str9899)
est9899

# then estimate the index for 2000 data
str00 <- data.frame(
  year=2000, lake=1,
  lscore=c(1.1, 1.2, 1.3),
  PEmr=c(10, NA, 28),
  CVmr=c(50, NA, 32))
estAIndex(indexStreams=istr, streamPECurr=str00,
  streamPEPrev=est9899$streamPE)

# notice how this is different than
# estimating the index for 1998-2000 altogether
estAIndex(indexStreams=istr, streamPECurr=rbind(str9899, str00))
```

figbig

*Add a Big Figure to an RTF Document***Description**

Add a big figure to an rtf (rich text format) document.

Usage

```
figbig(..., FIG = fig, rtf = doc, figc = GLFCenv$figcount, boldt = TRUE,
       w = NULL, h = NULL, rf = 300, newpage = "none", omi = c(1, 1, 1, 1))
```

Arguments

...	One or more character scalars (separated by commas) of text to use for the figure caption.
FIG	A function to create a figure which will be added to the document, default fig.
rtf	An rtf object, default doc.
figc	Numeric scalar figure number to use in caption, default GLFCenv\$figcount.
boldt	Logical scalar indicating if figure number should use bold font, default TRUE.
w	Numeric scalar width of figure in inches, default 6.5.
h	Numeric scalar height of figure in inches, default 8.
rf	Numeric scalar resolution of figure, default 300.
newpage	Character scalar indicating if the figure should start on a new page in the document "port" for a new portrait page, "land" for a new landscape page, and "none" for no new page (the default).
omi	Numeric vector, length 4, width of document page margins in inches (bottom, left, top, right), default c(1, 1, 1, 1).

Details

The figure and caption are written to the rtf file. The size of a new page is assumed to be 11 by 17 inches.

Value

A 1 is added to the numeric vector of length 1, GLFCenv\$figcount, stored in the working directory to keep track of the number of figures written to the rtf document, and label the captions accordingly.

See Also

[startrtf](#) for an example, [heading](#), [para](#), [tabl](#), [endrtf](#), [RTF](#).

figu

*Add a Figure to an RTF Document***Description**

Add a figure to an rtf (rich text format) document.

Usage

```
figu(..., FIG = fig, rtf = doc, figid = "Figure ",
     fign = GLFCenv$figcount, boldt = TRUE, capunder = TRUE, w = NULL,
     h = NULL, rf = 300, newpage = "none", omi = c(1, 1, 1, 1))
```

Arguments

...	One or more character scalars (separated by commas) of text to use for the figure caption.
FIG	A function to create a figure which will be added to the document, default fig.
rtf	An rtf object, default doc.
figid	Character scalar of caption identifier, default "Figure ".
fign	Numeric scalar of figure number to use in caption, default GLFCenv\$figcount.
boldt	Logical scalar indicating if figure number should use bold font, default TRUE.
capunder	Logical scalar indicating if caption should appear under the figure (TRUE, the default) or on top of the figure (FALSE).
w	Numeric scalar width of figure in inches, default 6.5.
h	Numeric scalar height of figure in inches, default 8.
rf	Numeric scalar resolution of figure, default 300.
newpage	Character scalar indicating if the figure should start on a new page in the document "port" for a new portrait page, "land" for a new landscape page, and "none" for no new page (the default).
omi	Numeric vector, length 4, width of document page margins in inches (bottom, left, top, right), default c(1, 1, 1, 1).

Details

The figure and caption are written to the rtf file. The size of a new page is assumed to be 8.5 by 11 inches.

Value

A 1 is added to the numeric vector of length 1, GLFCenv\$figcount, stored in the working directory to keep track of the number of figures written to the rtf document, and label the captions accordingly.

See Also

[startrtf](#) for an example, [heading](#), [para](#), [tabl](#), [figbig](#), [endrtf](#), [RTF](#).

GLFCenv

*GLFC Package Local Environment***Description**

An environment local to the GLFC package, used to hold objects outside of the individual package functions

Format

An environment.

Source

Post from Hadley Wickham to r-help on 2 Dec 2014 [\[link\]](#).

heading

*Add a Heading to an RTF Document***Description**

Add a text heading to an rtf (rich text format) document.

Usage

```
heading(words, htype = 1, rtf = doc)
```

Arguments

words	Character scalar text of heading to add to document.
htype	Integer scalar heading type, 1=bold and font size 12, 2=bold and font size 10, 3=italics and font size 10, default 1.
rtf	An rtf object, default doc.

Details

The specified heading is written to the rtf file.

See Also

[startrtf](#) for an example, [para](#), [tabl](#), [figu](#), [figbig](#), [endrtf](#), [RTF](#).

index2pe

*Factors to Scale Up the Adult Index to a Lake-Wide Population***Description**

Lake-specific conversion factors to scale up indices of adult sea lamprey abundance in the Great Lakes to lake-wide population estimates.

Format

A named vector of length 5 (for the 5 Great Lakes) with factors rounded to the nearest hundredth.

Author(s)

GLFC Trapping Task Force.

Source

Great Lakes Fishery Commission ([GLFC](#)) Sea Lamprey Control Board Meeting 14-02, 15-17 Oct 2014, Briefing Item 5 - Attachment 2, Transitioning to the New Adult Index in 2015.

jackIndex

*Index with Jackknifed Range***Description**

Given a collection of estimates contributing to an index, this function provides the estimated index (sum) of observations (across a row) and the jackknifed range of the index, the result of leaving out an entire column (e.g., a location) one at a time.

Usage

```
jackIndex(m)
```

Arguments

m A numeric matrix of estimates contributing to the index. Rows are observations (e.g., years). Columns are individuals (e.g., locations).

Details

The index is simply the sum of the columns in **m** for each row. The jackknifed range is produced by recalculating the index, leaving out one column at a time, then scaling up the result to the same scale as the index based on all columns.

Value

A numeric matrix with 3 columns, the index, and the lower and upper jackknifed range of the index.

Examples

```
# 3 years of population estimates from four streams
streampe <- matrix(1:12, nrow=3, dimnames=list(1996:1998, letters[1:4]))
jackIndex(streampe)
```

lsIndex

*Great Lakes Streams used in the Index of Adult Sea Lampreys***Description**

IDs identifying streams to used to generate the Adult Index.

Format

A list of 5 numeric vectors of lake-stream IDs for the 5 Great Lakes, e.g., 1.064 = (lake ID) + (stream ID)/1000.

Author(s)

GLFC Trapping Task Force.

Source

Great Lakes Fishery Commission (**GLFC**) Sea Lamprey Control Board Meeting 14-02, 15-17 Oct 2014, Briefing Item 5 - Attachment 2, Transitioning to the New Adult Index in 2015.

lsKeep

*Great Lakes Streams with Commitment to Adult Sea Lamprey Trapping***Description**

IDs identifying streams which will continue to have ongoing trapping even if not part of the Adult Index.

Format

A list of 5 numeric vectors of lake-stream IDs for the 5 Great Lakes, e.g., 1.064 = (lake ID) + (stream ID)/1000.

Author(s)

GLFC Trapping Task Force.

Source

Great Lakes Fishery Commission (**GLFC**) Sea Lamprey Control Board Meeting 14-02, 15-17 Oct 2014, Briefing Item 5 - Attachment 2, Transitioning to the New Adult Index in 2015.

para	<i>Add a Paragraph to an RTF Document</i>
------	---

Description

Add a paragraph to an rtf (rich text format) document.

Usage

```
para(..., rtf = doc, bold = FALSE, italic = FALSE)
```

Arguments

...	One or more character scalars (separated by commas) of text to add to document as a single paragraph.
rtf	An rtf object, default doc.
bold	Logical scalar indicating if paragraph should use bold font, default FALSE.
italic	Logical scalar indicating if paragraph should use italic font, default FALSE.

Details

The specified heading is written to the rtf file.

See Also

[startrtf](#) for an example, [heading](#), [tabl](#), [figu](#), [figbig](#), [endrtf](#), [RTF](#).

predAntilog	<i>Unbiased Prediction of Log Transformed Response on Original Scale</i>
-------------	--

Description

Provide unbiased estimates on the original scale from an analysis of variance model with a log transformed response.

Usage

```
predAntilog(aovfit, xdata, logbase = exp(1), k = 0)
```

Arguments

aovfit	An object of class c("aov", "lm").
xdata	A data frame with predictor variables corresponding to those in model for which predictions should be made.
logbase	A numeric scalar, the base of the log transformation used in the transformed response of model, default exp(1).
k	A numeric scalar, the constant added to the response prior to transformation, default 0.

Value

A numeric vector of predicted values on the original scale of the response.

References

This is a copy of the `predAntilog` function from the [\[jvamisc\]](#) package.

Examples

```
fit <- aov(log(yield) ~ block + N * P + K, npk)
predAntilog(fit, npk)
```

prettytable	<i>Prettify the Numeric Columns of a Table</i>
-------------	--

Description

Prettify the numeric columns of a table, by formatting them and converting them to character columns for printing.

Usage

```
prettytable(df, digits = 2, rounds = TRUE, bigseps = ",")
```

Arguments

<code>df</code>	A data frame to be prettified.
<code>digits</code>	Integer vector of either length 1 or the number of columns in <code>df</code> , number of digits to be used, default 2. See <code>round</code> .
<code>rounds</code>	Logical vector of either length 1 or the number of columns in <code>df</code> , indicating whether numbers should be rounded to <code>digits</code> decimal places (TRUE, the default), rounded to <code>digits</code> significant digits (FALSE), or not rounded at all (NULL).
<code>bigseps</code>	Character vector of either length 1 or the number of columns in <code>df</code> , giving the character to be used as a mark between every three digits before the decimal, default ",".

Value

A data frame the same dimensions as `df` with the numeric columns converted to character columns, formatted as specified.

References

This is a copy of the `prettytable` function from the [\[jvamisc\]](#) package.

Examples

```
head(mtcars)
prettytable(head(mtcars))
```

starttrtf	<i>Create an RTF Document</i>
-----------	-------------------------------

Description

Create an rtf (rich text format) document.

Usage

```
starttrtf(file = NULL, dir = getwd(), width = 8.5, height = 11,
  omi = c(1, 1, 1, 1), quiet = FALSE)
```

Arguments

file	Character scalar name of document, default "RGeneratedDocument" with Sys.Date() suffix.
dir	Character scalar name of directory where document should be stored, default getwd() .
width	Numeric scalar width of document page in inches, default 8.5.
height	Numeric scalar height of document page in inches, default 11.
omi	Numeric vector, length 4, width of document page margins in inches (bottom, left, top, right), default c(1, 1, 1, 1).
quiet	Logical scalar indicating if name of new rtf document should be printed to command line, default FALSE.

Details

The rtf file may be written to until the [endrtf\(\)](#) function is run. If you assign your rtf file to an object called doc, you can use the default settings in other **GLFC** rtf functions.

Value

An rtf file is created in the specified directory. An object of class rtf is created. This object is referred to in other function to write to the file. In addition, two numeric vectors of length 1, tabcount and figcount, are written to the working directory to keep track of the number of tables and figures written to the rtf document, and label the captions accordingly.

See Also

[heading](#), [para](#), [tabl](#), [figu](#), [figbig](#), [endrtf](#), [RTF](#).

Examples

```
## Not run:
# open a Word-friendly rtf file
today <- Sys.Date()
doc <- starttrtf(file=paste("Example", today))
# add headings
heading("Title")
heading(paste("Author", today, sep=" - "), 2)
# add a paragraph
```

```

para("This is how write a paragraph.")
# reference a table
para("This is how you reference a table (Table ", GLFCenv$tabcount, ").")
# add the table
tab <- matrix(sample(20), ncol=5,
  dimnames=list(paste("Row", 1:4), paste("Column", 1:5)))
tbl("A silly table.")
# reference a figure
para("And this is how you reference a figure (Figure ",
  GLFCenv$figcount, ").")
# add the figure
fig <- function() {
  par(mar=c(4, 4, 1, 1))
  plot(1:10, 1:10, xlab="X", ylab="Y")
}
figu("A silly plot.", h=4, w=4)
# save the rtf file
endrtf()

## End(Not run)

```

tbl

*Add a Table to an RTF Document***Description**

Add a table to an rtf (rich text format) document.

Usage

```
tbl(..., TAB = tab, rtf = doc, fontt = 8, row.names = TRUE,
  tabc = GLFCenv$tabcount, boldt = TRUE, newpage = "none", omi = c(1, 1,
  1, 1))
```

Arguments

...	One or more character scalars (separated by commas) of text to use for the table caption.
TAB	A matrix, data frame, or table to be added to the document as a table, default tab.
rtf	An rtf object, default doc.
fontt	Numeric scalar font size for table caption, default 8.
row.names	Logical scalar whether to include the row.names of TAB in the table, default TRUE.
tabc	Numeric scalar table number to use in caption, default GLFCenv\$tabcount.
boldt	Logical scalar indicating if table number should use bold font, default TRUE.
newpage	Character scalar indicating if the table should start on a new page in the document "port" for a new portrait page, "land" for a new landscape page, and "none" for no new page (the default).
omi	Numeric vector, length 4, width of document page margins in inches (bottom, left, top, right), default c(1, 1, 1, 1).

Details

The table and caption are written to the rtf file. The size of a new page is assumed to be 8.5 by 11 inches.

Value

A 1 is added to the numeric vector of length 1, GLFCenv\$tabcount, stored in the working directory to keep track of the number of tables written to the rtf document, and label the captions accordingly.

See Also

[startrtf](#) for an example, [heading](#), [para](#), [figu](#), [figbig](#), [endrtf](#), [RTF](#).

trappedStreams	<i>General Information on Great Lakes Streams Trapped for Adult Sea Lampreys</i>
----------------	--

Description

Location information on trapped streams (past and present).

Format

A data frame with 8 elements: lake (lake ID), lscore (lake-stream ID, lake + strcode/1000), country, strcode (stream ID), estr (stream ID for Empiric Stream Treatment Ranking), strname (stream name), lat (latitude), long (longitude).

Author(s)

GLFC Trapping Task Force.

Source

Great Lakes Fishery Commission ([GLFC](#)) spawner model data base, last updated 12 May 2015.

Index

addPageBreak, [6](#)
AIcheck, [2](#)
AIestimate, [2](#)
AIprep, [2](#), [3](#), [3](#)
AIreport, [4](#)
AItarget, [5](#), [5](#)

endrtrf, [6](#), [8–10](#), [13](#), [15](#), [17](#)
estAIndex, [6](#)

figbig, [6](#), [8](#), [9](#), [10](#), [13](#), [15](#), [17](#)
figu, [6](#), [9](#), [10](#), [13](#), [15](#), [17](#)

getwd, [15](#)
GLFCenv, [10](#)

heading, [6](#), [8](#), [9](#), [10](#), [13](#), [15](#), [17](#)

index2pe, [11](#)

jackIndex, [11](#)

lsIndex, [12](#)
lsKeep, [12](#)

para, [6](#), [8–10](#), [13](#), [15](#), [17](#)
predAntilog, [13](#)
prettytable, [14](#)

RTF, [6](#), [8–10](#), [13](#), [15](#), [17](#)

starttrtf, [6](#), [8–10](#), [13](#), [15](#), [17](#)
Sys.Date, [15](#)

tabl, [6](#), [8–10](#), [13](#), [15](#), [16](#)
trappedStreams, [4](#), [17](#)