

Kaushik JV

Design System v1

Zillennial Bridge | Heritage Cream x Cerulean Teal

The foundation version -- the warmest, most saturated cream in the palette. Heritage Cream (#E8E4D9) gives a toasted, organic warmth. Five-layer glass morphism, haptic spring animation, and token-first architecture.

VERSION 1.0

TECH STACK

Framework	Next.js 14 (App Router) + TypeScript
Styling	CSS Custom Properties (--v1-*) + Tailwind CSS
Animation	Framer Motion -- Spring physics
Tokens	W3C Design Tokens format (tokens.json)
Repository	github.com/JVK0804/DesignSystem_Retro

CONTENTS

01	Design Philosophy
02	Colour Tokens
03	Glass Tokens
04	Spacing & Radius
05	Glass Card Component
06	Haptic Spring
07	Button Variants
08	Tags & Badges

09 File Structure & Usage

10 System Status

01 -- Design Philosophy

v1 is the foundation -- the original Figma token set before any brightness adjustments. The Heritage Cream base (#E8E4D9) carries a toasted, organic warmth that v2 lightened for the coded implementation. v1 preserves the source value exactly as designed in Figma.

1

Organic Warmth

Heritage Cream (#E8E4D9) is the warmest point in the cream ramp. It reads like aged paper, sun-bleached plastic, or the inside of a well-used sketchbook. Every surface in v1 carries this undertone -- never substitute with cool or neutral greys.

2

Tactile Skeuomorphism 2.0

Modern glassmorphism mimics the weight and texture of physical hardware -- translucent plastics, grain on every surface. Physical weight is achieved through layered translucency, not literal texture mapping. Specular at 32% (brighter than v2's 28%) compensates for the warmer, more absorptive cream base.

3




Intentional Friction

Interactions have a physical press phase (30ms compress to scale(0.955)) and a spring-return (280ms overshoot to scale(1.018)). Mechanical feel, fluid 120Hz execution. The haptic spring values are identical across v1, v2, and v3 -- physics does not version.

02 -- Colour Tokens



All tokens are prefixed --v1-* to allow coexistence with v2 and v3 in the same codebase. The key distinction: --v1-color-bg is #E8E4D9 (Heritage Cream) vs v2's #F5F2EB (Cream Bright). Both share the same Cerulean Teal accent ramp.

BASE -- HERITAGE CREAM

	--v1-color-bg	#E8E4D9	Canvas background -- original Figma value
	--v1-color-cream-bright	#F5F2EB	Surface / card background
	--v1-color-cream-shadow	#D4CFBF	Pressed state / border / divider

ACCENT -- CERULEAN TEAL

	--v1-color-primary	#0E7490	Primary interactive, CTAs
			

	--v1-color-primary-hover	#22B8CF	Hover states
	--v1-color-primary-phosphor	#A5F3FC	Teal Phosphor -- highlight point
	--v1-color-primary-subtle	rgba(14,116,144,0.10)	Tag fills
	--v1-color-primary-border	rgba(14,116,144,0.28)	Tag borders
INK -- TEXT RAMP			
	--v1-color-ink	#1C1A14	Primary text on cream
	--v1-color-ink-muted	#5A5648	Body copy, descriptions
	--v1-color-ink-disabled	#9A9488	Captions, metadata, placeholders

03 -- Glass Tokens

v1 glass uses 45% opacity -- enough translucency to show grain underneath without making the card invisible. Specular is 32% (vs v2's 28%) because the warmer Heritage Cream base absorbs more light and needs the extra highlight to read clearly.

GLASS TOKEN VALUES

Token	Value
--v1-glass-bg	rgba(232, 228, 217, 0.45)
--v1-glass-specular-from	rgba(255, 255, 255, 0.32)
--v1-glass-specular-to	rgba(255, 255, 255, 0.06)
--v1-glass-glnt	rgba(255, 255, 255, 0.80)
--v1-border-glass	1px solid rgba(255, 255, 255, 0.55)
--v1-blur-glass	blur(12px)

LAYER COMPOSITION

#	Layer	Description
1	Scene Grain	SVG feTurbulence on scene -- opt-in via withGrain prop
2	Heritage Cream	#E8E4D9 base canvas -- warm brown undertone
3	Glass Fill	rgba(232,228,217,0.45) + backdrop-filter: blur(12px)
4	Specular ::before	linear-gradient(135deg, white/32%, white/6%) -- top-left light
5	Glnt ::after	1px top edge: transparent -> white/80% -> transparent
6	Content	z-index: 20, relative positioning

04 -- Spacing & Radius

Base unit: 4px. All spacing is a multiple of 4. Radius follows Apple concentric logic: outer container always larger than inner element.

SPACING SCALE

Token	Value	Semantic Role
--v1-space-1	4px	Icon gaps, micro spacing
--v1-space-2	8px	Inline elements
--v1-space-3	12px	Tight stacks
--v1-space-4	16px	Component padding
--v1-space-6	24px	Card internal spacing
--v1-space-8	32px	Between components
--v1-space-12	48px	Section gap (mobile)
--v1-space-20	80px	Section gap (desktop)

BORDER RADIUS

Token	Value	Usage	Component
--v1-radius-sm	4px	Tags, chips, badges	Tag component
--v1-radius-md	8px	Buttons, inputs	HapticButton
--v1-radius-lg	14px	Project cards	GlassCard
--v1-radius-xl	20px	Modals, scene frames	Scene container
--v1-radius-pill	100px	Label pills, CTA buttons	Pill variant

05 -- Glass Card Component -- GlassCard.v1

GlassCard.v1 is the foundation glass card. Identical layer composition to v2 but reads from --v1-glass-* tokens. The warmer base (#E8E4D9) and brighter specular (32%) give it a more toasted, physical quality compared to v2.

GLASSCARD.V1 -- USAGE

```
import { GlassCardV1 } from '@components/v1/GlassCard.v1'

// Basic
<GlassCardV1>
  <h3>Project Title</h3>
  <p>Description</p>
</GlassCardV1>
```

```
// With grain texture overlay
<GlassCardV1 withGrain>
  <h3>Project Title</h3>
</GlassCardV1>
```

PROPS

Prop	Type	Default	Description
children	ReactNode	--	Card content
withGrain	boolean	false	Renders grain texture overlay
className	string	"	Additional CSS classes
style	CSSProperties	--	Inline styles

06 -- Haptic Spring -- Click-Clack

Spring values are locked across v1, v2, and v3. The mechanical sensation is version-agnostic -- only the visual surface changes. Always bind to `onPointerDown`, not `onClick` -- the 60-80ms difference is the entire tactile illusion.

Phase	Duration	Transform	Easing
Press	30ms	scale(0.955)	cubic-bezier(0.4, 0, 1, 1)
Hold	20ms	static	--
Return	280ms	scale(1.018->1.0)	Spring: stiffness 520, damping 22, mass 0.6
Settle	50ms	scale(1.0)	micro-damp

USEHAPTICPRESS.TS

```
const springConfig = {
  type: 'spring',
  stiffness: 520,
  damping: 22,
  mass: 0.6
}

export function useHapticPress() {
  const controls = useAnimation()
  const onPointerDown = async () => {
    await controls.start({ scale: 0.955, transition: { duration: 0.03 } })
  }
  const onPointerUp = async () => {
    await controls.start({ scale: 1.018, transition: springConfig })
  }
}
```

```
    await controls.start({ scale: 1, transition: { duration: 0.05 } })
  }
  return { controls, onPointerDown, onPointerUp }
}
```

07 -- Button Variants -- HapticButton.v1

All six states share the same HapticButton.v1 component via the variant prop. Reads from --v1-* tokens. Spring is disabled when variant="disabled".

Variant	Background	Text	Border	Notes
primary	#0E7490	#F5F2EB	none	Default CTA -- radius-md (8px)
pill	#0E7490	#F5F2EB	none	Full pill -- radius-pill (100px)
hover	#22B8CF	#F5F2EB	none	Active/hover state
secondary	transparent	#0E7490	#0E7490	Outlined -- 1px solid teal
ghost	transparent	#0E7490	none	No border, subtle hover tint
disabled	#D4CFBF	#9A9488	none	cursor: not-allowed

08 -- Tags & Badges -- Tag.v1

Tag.v1 uses --v1-color-primary-subtle (teal 10%) fill and --v1-color-primary-border (teal 28%) stroke. Size "sm" renders as an uppercase badge with letter-spacing.

Size	Height	Font	Padding	Notes
md	28px	13px	0 12px	Normal case -- standard label
sm	22px	11px	0 10px	Uppercase -- +0.08em letter-spacing (badge style)

USAGE

```
import { TagV1 } from '@components/v1/Tag.v1'

<TagV1 size="md">Design Systems</TagV1>
<TagV1 size="md">Figma</TagV1>
<TagV1 size="sm">v1</TagV1>
<TagV1 size="sm">LOCKED</TagV1>
```

09 -- File Structure & Usage

DIRECTORY TREE

```
DesignSystem_Retro/
|-- styles/
|   |-- tokens.css          <- v2 base tokens (--color-*)
|   `-- tokens.v1.css      <- v1 tokens (--v1-*)
|-- components/
|   |-- v1/
|   |   |-- GlassCard.v1.tsx
|   |   |-- HapticButton.v1.tsx
|   |   `-- Tag.v1.tsx
|   `-- GrainOverlay.tsx
|-- hooks/
|   `-- useHapticPress.ts
`-- tokens/
    `-- tokens.json        <- W3C Design Tokens
```

SETUP

```
// 1. Import tokens in app/layout.tsx
import '@components/styles/tokens.v1.css'

// 2. Set canvas background in globals.css
body {
  background-color: var(--v1-color-bg); /* #E8E4D9 */
  color: var(--v1-color-ink);
}

// 3. Ensure backdrop-filter works
// Cards must sit above a visible background -- not transparent
```

10 -- System Status

Component	Status
tokens.v1.css	Complete
GlassCard.v1.tsx	Complete
HapticButton.v1.tsx	Complete
Tag.v1.tsx	Complete
useHapticPress.ts	Shared -- v1/v2/v3
GrainOverlay.tsx	Shared -- v1/v2
tokens.json	W3C format -- complete

Navigation shell

v5 (adaptive)

Kaushik JV | Design System v1 | 2026 | Generated by Claude AI