



Outscraper API Docs (0.4.3)

Download OpenAPI specification: [Download](#)

SDKs

The supported list of official SDKs: [Python](#), [Ruby](#), [PHP](#), [Node](#), [Go](#), and [Java](#). Check out the [Outscraper GitHub page](#) to learn more about SDKs and find more code examples.

QPS & Limits

The limit of queries per second depends on the nature of the requests, service, and request parameters (amount of results, amount of queries, etc.). The average QPS is about `20`. However, Outscraper can scale according to your needs. Please contact the team in case you need higher QPS.

[F.A.Q](#)

Businesses & POI

Google Places v3 (speed optimized)

Returns places from Google Maps based on a given search query (or many queries).

The results from searches are the same as you would see by visiting a regular [Google Maps](#) site.

However, in most cases, it's important to use locations inside queries (e.g., `bars, NY, USA`) as the IP addresses of Outscraper's servers might be located in different countries.

In case no places were found by your search criteria, your search request will consume the usage of one place.

This endpoint is optimized for fast responses and can be used as a real-time API. Set the `limit` parameter to `10` to achieve the maximum response speed.

AUTHORIZATIONS: > [ApiKeyAuth](#)

QUERY PARAMETERS

[Back to Top](#)

query
required

Array of strings

The parameter defines the query you want to search. You can use anything that you would use on a regular Google Maps site. Additionally, you can use `google_id` (feature_id), `place_id`, or `CID`. The example of valid queries: `Real estate agency, Rome, Italy`, `The NoMad Restaurant, NY, USA`, `restaurants, Brooklyn 11203`, `0x886916e8bc273979:0x5141fcb11460b226`, `ChIJrZhup41ZwokRUr_5sLoFlDw`, etc.

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and save on network latency time.

You might want to check out [the web application](#) to play with locations and categories that we would suggest.

limit

integer

Default: `500`

The parameter specifies the limit of organizations to take from one query search.

There are no more than 500 places per one query search on Google Maps. For densely populated areas you might want to split your query into subqueries in order to get all the places inside. (e.g., `restaurants, Brooklyn 11211`, `restaurants, Brooklyn 11215`).

dropDuplicates

boolean

Default: `"false"`

The parameter specifies whether the bot will drop the same organizations from different queries. It makes sense when you use batching and send multiple queries inside one request.

Using the parameter combines results from each query inside one big array (`{'data': [...]}` instead of `{'data': [[...], [...], [...]]}`).

If the amount of ignored rows are less than 5,000% of what was actually extracted, you won't be billed for ignored records.

coordinates

string

The parameter defines the coordinates of the location where you want your query to be applied.

It has to be constructed in the next sequence: `latitude` + `,` + `longitude` (`41.3954381,2.1628662`). Often, you can find this value while visiting [Google Maps](#).

skipPlaces

integer

Default: `0`

Skip first N places, where N should be multiple to 20 (e.g. 0, 20, 40). It's commonly used in pagination.

language

string (language)

Default: "en"

Enum: "en" "de" "es" "es-419" "fr" "hr" "it" "nl" "pl" "pt-BR" "pt-PT" "vi" "tr" "ru" "ar" "th" "ko" "zh-CN" "zh-TW" "ja" "ach" "af" "ak" "ig" "az" "ban" "ceb" "xx-bork" "bs" "br" "ca" "cs" "sn" "co" "cy" "da" "yo" "et" "xx-elmer" "eo" "eu" "ee" "tl" "fil" "fo" "fy" "gaa" "ga" "gd" "gl" "gn" "xx-hacker" "ht" "ha" "haw" "bem" "rn" "id" "ia" "xh" "zu" "is" "jw" "rw" "sw" "tlh" "kg" "mfe" "kri" "la" "lv" "to" "lt" "ln" "loz" "lua" "lg" "hu" "mg" "mt" "mi" "ms" "pcm" "no" "nso" "ny" "nn" "uz" "oc" "om" "xx-pirate" "ro" "rm" "qu" "nyn" "crs" "sq" "sk" "sl" "so" "st" "sr-ME" "sr-Latn" "su" "fi" "sv" "tn" "tum" "tk" "tw" "wo" "el" "be" "bg" "ky" "kk" "mk" "mn" "sr" "tt" "tg" "uk" "ka" "hy" "yi" "iw" "ug" "ur" "ps" "sd" "fa" "ckb" "ti" "am" "ne" "mr" "hi" "bn" "pa" "gu" "or" "ta" "te" "kn" "ml" "si" "lo" "my" "km" "chr"

The parameter specifies the language to use for website.

region

string (region)

Enum: "AF" "AL" "DZ" "AS" "AD" "AO" "AI" "AG" "AR" "AM" "AU" "AT" "AZ" "BS" "BH" "BD" "BY" "BE" "BZ" "BJ" "BT" "BO" "BA" "BW" "BR" "VG" "BN" "BG" "BF" "BI" "KH" "CM" "CA" "CV" "CF" "TD" "CL" "CN" "CO" "CG" "CD" "CK" "CR" "CI" "HR" "CU" "CY" "CZ" "DK" "DJ" "DM" "DO" "EC" "EG" "SV" "EE" "ET" "FJ" "FI" "FR" "GA" "GM" "GE" "DE" "GH" "GI" "GR" "GL" "GT" "GG" "GY" "HT" "HN" "HK" "HU" "IS" "IN" "ID" "IQ" "IE" "IM" "IL" "IT" "JM" "JP" "JE" "JO" "KZ" "KE" "KI" "KW" "KG" "LA" "LV" "LB" "LS" "LY" "LI" "LT" "LU" "MG" "MW" "MY" "MV" "ML" "MT" "MU" "MX" "FM" "MD" "MN" "ME" "MS" "MA" "MQ" "MZ" "MM" "NA" "NR" "NP" "NL" "NZ" "NI" "NE" "NG" "NU" "MK" "NO" "OM" "PK" "PS" "PA" "PG" "PY" "PE" "PH" "PN" "PL" "PT" "PR" "QA" "RO" "RU" "RW" "WS" "SM" "ST" "SA" "SN" "RS" "SC" "SL" "SG" "SK" "SI" "SB" "SO" "ZA" "KR" "ES" "LK" "SH" "VC" "SR" "SE" "CH" "TW" "TJ" "TZ" "TH" "TL" "TG" "TO" "TT" "TN" "TR" "TM" "VI" "UG" "UA" "AE" "GB" "US" "UY" "UZ" "VU" "VE" "VN" "ZM" "ZW"

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

enrichment

Array of strings

The parameter defines an enrichment or enrichments (e.g.,

`enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3`) you want to apply to the results.

Available values:

`domains_service` — **Emails & Contacts Scraper**: finds emails, social links, phones, and other contacts from websites,

`emails_validator_service` — **Email Address Verifier**: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate,

`disposable_email_checker` — **Disposable Emails Checker**: checks origins of email addresses (disposable, free, or corporate),

`company_insights_service` — **Company Insights**: finds company details such as revenue, size, founding year, public status, etc,

`phones_enricher_service` — **Phone Numbers Enricher**: returns phones carrier data (name/type), validates phones, ensures messages deliverability,

`trustpilot_service` — **Trustpilot Scraper**: returns data from a list of businesses,

`whitepages_phones` - **Phone Identity Finder**: returns insights about phone number owners (name, address, etc.),

`ai_chain_info` - **Chain Info**: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting.

Using enrichments increases the time of the response. You might want to use the `async=true` parameter to avoid getting timeouts.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

	As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **204** The request was finished with failure and has no results.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

GET `/maps/search-v3`

Request samples

cURL	cURL (async)	Python	Ruby	PHP	Node.js	Go	Java
------	--------------	--------	------	-----	---------	----	------

[Copy](#)

```
curl -X GET "https://api.outscraper.cloud/maps/search-v3?query=restaurants"
```

Response samples

200

202

204

401

402

422

Content type

application/json

[Copy](#)[Expand all](#)[Collapse all](#)

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Google Places v3 (bigger payload capabilities)

Returns places from Google Maps based on a given search query (or many queries).

The results from searches are the same as you would see by visiting a regular [Google Maps](#) site.

However, in most cases, it's important to use locations inside queries (e.g., `bars, NY, USA`) as the IP addresses of Outscraper's servers might be located in different countries.

In case no places were found by your search criteria, your search request will consume the usage of one place.

This endpoint is optimized for fast responses and can be used as a real-time API. Set the `limit` parameter to `10` to achieve the maximum response speed.

The POST endpoint is identical to GET and made to support a bigger payload, such as when sending a large number of queries.

AUTHORIZATIONS: [>](#) *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

The parameter defines the query you want to search. You can use anything that you would use on a regular Google Maps site. Additionally, you can use `google_id` (feature_id), `place_id`, or `CID`. The example of valid

queries: `Real estate agency, Rome, Italy`, `The NoMad Restaurant, NY, USA`, `restaurants, Brooklyn 11203`, `0x886916e8bc273979:0x5141fcb11460b226`, `ChIJrZhup4lZwokRUr_5sLoF1Dw`, etc.

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and save on network latency time.

You might want to check out [the web application](#) to play with locations and categories that we would suggest.

limit

integer

Default: `500`

The parameter specifies the limit of organizations to take from one query search.

There are no more than 500 places per one query search on Google Maps. For densely populated areas you might want to split your query into subqueries in order to get all the places inside. (e.g., `restaurants, Brooklyn 11211`, `restaurants, Brooklyn 11215`).

dropDuplicates

boolean

Default: `"false"`

The parameter specifies whether the bot will drop the same organizations from different queries. It makes sense when you use batching and send multiple queries inside one request.

Using the parameter combines results from each query inside one big array (`{'data': [...]}` instead of `{'data': [...], [...], [...]}`).

If the amount of ignored rows are less than 5,000% of what was actually extracted, you won't be billed for ignored records.

coordinates

string

The parameter defines the coordinates of the location where you want your query to be applied.

It has to be constructed in the next sequence: `latitude` + `,` + `longitude` (`41.3954381,2.1628662`). Often, you can find this value while visiting [Google Maps](#).

skipPlaces

integer

Default: `0`

Skip first N places, where N should be multiple to 20 (e.g. 0, 20, 40). It's commonly used in pagination.

language

string (language)

Default: `"en"`

Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"` `"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"`

"ko"	"zh-CN"	"zh-TW"	"ja"	"ach"	"af"	"ak"	"ig"	
"az"	"ban"	"ceb"	"xx-bork"	"bs"	"br"	"ca"	"cs"	
"sn"	"co"	"cy"	"da"	"yo"	"et"	"xx-elmer"	"eo"	
"eu"	"ee"	"tl"	"fil"	"fo"	"fy"	"gaa"	"ga"	"gd"
"gl"	"gn"	"xx-hacker"	"ht"	"ha"	"haw"	"bem"	"rn"	
"id"	"ia"	"xh"	"zu"	"is"	"jw"	"rw"	"sw"	"tlh"
"kg"	"mfe"	"kri"	"la"	"lv"	"to"	"lt"	"ln"	"loz"
"lua"	"lg"	"hu"	"mg"	"mt"	"mi"	"ms"	"pcm"	"no"
"nso"	"ny"	"nn"	"uz"	"oc"	"om"	"xx-pirate"	"ro"	
"rm"	"qu"	"nyn"	"crs"	"sq"	"sk"	"sl"	"so"	"st"
"sr-ME"	"sr-Latn"	"su"	"fi"	"sv"	"tn"	"tum"	"tk"	
"tw"	"wo"	"el"	"be"	"bg"	"ky"	"kk"	"mk"	"mn"
"sr"	"tt"	"tg"	"uk"	"ka"	"hy"	"yi"	"iw"	"ug"
"ur"	"ps"	"sd"	"fa"	"ckb"	"ti"	"am"	"ne"	"mr"
"hi"	"bn"	"pa"	"gu"	"or"	"ta"	"te"	"kn"	"ml"
"si"	"lo"	"my"	"km"	"chr"				

The parameter specifies the language to use for website.

region

string (region)
Enum: "AF" "AL" "DZ" "AS" "AD" "AO" "AI" "AG" "AR"
"AM" "AU" "AT" "AZ" "BS" "BH" "BD" "BY" "BE"
"BZ" "BJ" "BT" "BO" "BA" "BW" "BR" "VG" "BN"
"BG" "BF" "BI" "KH" "CM" "CA" "CV" "CF" "TD"
"CL" "CN" "CO" "CG" "CD" "CK" "CR" "CI" "HR"
"CU" "CY" "CZ" "DK" "DJ" "DM" "DO" "EC" "EG"
"SV" "EE" "ET" "FJ" "FI" "FR" "GA" "GM" "GE"
"DE" "GH" "GI" "GR" "GL" "GT" "GG" "GY" "HT"
"HN" "HK" "HU" "IS" "IN" "ID" "IQ" "IE" "IM"
"IL" "IT" "JM" "JP" "JE" "JO" "KZ" "KE" "KI"
"KW" "KG" "LA" "LV" "LB" "LS" "LY" "LI" "LT"
"LU" "MG" "MW" "MY" "MV" "ML" "MT" "MU" "MX"
"FM" "MD" "MN" "ME" "MS" "MA" "MQ" "MZ" "MM"
"NA" "NR" "NP" "NL" "NZ" "NI" "NE" "NG" "NU"
"MK" "NO" "OM" "PK" "PS" "PA" "PG" "PY" "PE"
"PH" "PN" "PL" "PT" "PR" "QA" "RO" "RU" "RW"
"WS" "SM" "ST" "SA" "SN" "RS" "SC" "SL" "SG"
"SK" "SI" "SB" "SO" "ZA" "KR" "ES" "LK" "SH"
"VC" "SR" "SE" "CH" "TW" "TJ" "TZ" "TH" "TL"
"TG" "TO" "TT" "TN" "TR" "TM" "VI" "UG" "UA"
"AE" "GB" "US" "UY" "UZ" "VU" "VE" "VN" "ZM"
"ZW"

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

enrichment

Array of strings

The parameter defines an enrichment or enrichments (e.g.,

`enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3`) you want to apply to the results.

Available values:

`domains_service` — **Emails & Contacts Scraper**: finds emails, social links, phones, and other contacts from websites,

`emails_validator_service` — **Email Address Verifier**: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate,

`disposable_email_checker` — **Disposable Emails Checker**: checks origins of email addresses (disposable, free, or corporate),

`company_insights_service` — **Company Insights**: finds company details such as revenue, size, founding year, public status, etc,

`phones_enricher_service` — **Phone Numbers Enricher**: returns phones carrier data (name/type), validates phones, ensures messages deliverability,

`trustpilot_service` — **Trustpilot Scraper**: returns data from a list of businesses,

`whitepages_phones` - **Phone Identity Finder**: returns insights about phone number owners (name, address, etc.),

`ai_chain_info` - **Chain Info**: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting.

Using enrichments increases the time of the response. You might want to use the `async=true` parameter to avoid getting timeouts.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **204** The request was finished with failure and has no results.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

POST `/maps/search-v3`

Request samples

cURL

cURL (async)

Copy

```
curl -X POST https://api.outscraper.cloud/maps/search-v3 -d '{"query": ["re
```

Response samples

200

202

204

401

402

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Google Places v1 (deprecated)

Returns places from Google Maps based on a given search query (or many queries).

The results from searches are the same as you would see by visiting a regular [Google Maps](#) site.

However, in most cases, it's recommended to use locations inside queries (e.g., `bars, NY, USA`) as the IP addresses of Outscraper's servers might be located in different countries.

In case no places were found by your search criteria, your search request will consume the usage of one place.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

The parameter defines the query you want to search. You can use anything that you would use on a regular Google Maps site. Additionally, you can use `google_id` (feature_id), `place_id`, `CID` or urls to Google Maps places. The example of valid queries: `Real estate agency, Rome, Italy`, `The NoMad Restaurant, NY, USA`, `restaurants, Brooklyn 11203`, `0x886916e8bc273979:0x5141fcb11460b226`, `ChIJu7bMNFV-54gR-lrHScvPRX4`, `https://www.google.com/maps/search/restaurants+near+New+York,+NY`, etc.

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and save on network latency time.

You might want to check out [the web application](#) to play with locations and categories that we would suggest.

limit

integer

Default: `500`

The parameter specifies the limit of organizations to take from one query search.

There are no more than 500 places per one query search on Google Maps. For densely populated areas you might want to split your query into subqueries in order to get all the places inside. (e.g., `restaurants, Brooklyn 11211`, `restaurants, Brooklyn 11215`).

dropDuplicates

boolean

Default: `"false"`

The parameter specifies whether the bot will drop the same organizations from different queries. It makes sense when you use batching and send multiple queries inside one request.

Using the parameter combines results from each query inside one big array (`{'data': [...]}` instead of `{'data': [[...], [...], [...]]}`).

If the amount of ignored rows are less than 5,000% of what was actually extracted, you won't be billed for ignored records.

coordinates

string

The parameter defines the coordinates of the location where you want your query to be applied.

It has to be constructed in the next sequence: `@` + `latitude` + `,` + `longitude` + `,` + `zoom` (`@41.3954381,2.1628662,15.1z`). Often, you can find this value while visiting [Google Maps](#).

language

string (language)

Default: `"en"`

Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"` `"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"` `"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"` `"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"` `"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"` `"eu"` `"ee"` `"tl"` `"fil"` `"fo"` `"fy"` `"gaa"` `"ga"` `"gd"` `"gl"` `"gn"` `"xx-hacker"` `"ht"` `"ha"` `"haw"` `"bem"` `"rn"` `"id"` `"ia"` `"xh"` `"zu"` `"is"` `"jw"` `"rw"` `"sw"` `"tlh"` `"kg"` `"mfe"` `"kri"` `"la"` `"lv"` `"to"` `"lt"` `"ln"` `"loz"` `"lua"` `"lg"` `"hu"` `"mg"` `"mt"` `"mi"` `"ms"` `"pcm"` `"no"` `"nso"` `"ny"` `"nn"` `"uz"` `"oc"` `"om"` `"xx-pirate"` `"ro"` `"rm"` `"qu"` `"nyn"` `"crs"` `"sq"` `"sk"` `"sl"` `"so"` `"st"` `"sr-ME"` `"sr-Latn"` `"su"` `"fi"` `"sv"` `"tn"` `"tum"` `"tk"` `"tw"` `"wo"` `"el"` `"be"` `"bg"` `"ky"` `"kk"` `"mk"` `"mn"`

"sr"	"tt"	"tg"	"uk"	"ka"	"hy"	"yi"	"iw"	"ug"
"ur"	"ps"	"sd"	"fa"	"ckb"	"ti"	"am"	"ne"	"mr"
"hi"	"bn"	"pa"	"gu"	"or"	"ta"	"te"	"kn"	"ml"
"si"	"lo"	"my"	"km"	"chr"				

The parameter specifies the language to use for website.

region

string (region)

Enum:	"AF"	"AL"	"DZ"	"AS"	"AD"	"AO"	"AI"	"AG"	"AR"
	"AM"	"AU"	"AT"	"AZ"	"BS"	"BH"	"BD"	"BY"	"BE"
	"BZ"	"BJ"	"BT"	"BO"	"BA"	"BW"	"BR"	"VG"	"BN"
	"BG"	"BF"	"BI"	"KH"	"CM"	"CA"	"CV"	"CF"	"TD"
	"CL"	"CN"	"CO"	"CG"	"CD"	"CK"	"CR"	"CI"	"HR"
	"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
	"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
	"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
	"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
	"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
	"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
	"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
	"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
	"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
	"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
	"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
	"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
	"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
	"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
	"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
	"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
	"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

enrichment

Array of strings

The parameter defines an enrichment or enrichments (e.g.,

`enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3`) you want to apply to the results.

Available values:

`domains_service` — **Emails & Contacts Scraper**: finds emails, social links, phones, and other contacts from websites,

`emails_validator_service` — **Email Address Verifier**: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate,

`disposable_email_checker` — **Disposable Emails Checker**: checks origins of email addresses (disposable, free, or corporate),

`company_insights_service` — **Company Insights**: finds company details such as revenue, size, founding year, public status, etc,

	<code>phones_enricher_service</code> — Phone Numbers Enricher: returns phones carrier data (name/type), validates phones, ensures messages deliverability, <code>trustpilot_service</code> — Trustpilot Scraper: returns data from a list of businesses, <code>whitepages_phones</code> - Phone Identity Finder: returns insights about phone number owners (name, address, etc.), <code>ai_chain_info</code> - Chain Info: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting. Using enrichments increases the time of the response. You might want to use the <code>async=true</code> parameter to avoid getting timeouts.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for **2** hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

- **422** Wrong query url parameters.

```
GET /maps/search
```

Request samples

cURL (async)

Python

PHP

Copy

```
curl -X GET "https://api.outscraper.cloud/maps/search?query=restaurants%2C%
```

Response samples

202

401

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Google Maps (Places) by Domain

Allows finding places by domains.
In case no places were found by your criteria, your search request will consume the usage of one place.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required Array of strings
Domains or websites (e.g., `dominopark.com`, `https://www.esbnyc.com/`).
It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

perQuery integer
Default: `100`
The parameter specifies the limit of items to return from one query.

region string (region)
Enum: `"AF"` `"AL"` `"DZ"` `"AS"` `"AD"` `"AO"` `"AI"` `"AG"` `"AR"`
`"AM"` `"AU"` `"AT"` `"AZ"` `"BS"` `"BH"` `"BD"` `"BY"` `"BE"`
`"BZ"` `"BJ"` `"BT"` `"BO"` `"BA"` `"BW"` `"BR"` `"VG"` `"BN"`
`"BG"` `"BF"` `"BI"` `"KH"` `"CM"` `"CA"` `"CV"` `"CF"` `"TD"`
`"CL"` `"CN"` `"CO"` `"CG"` `"CD"` `"CK"` `"CR"` `"CI"` `"HR"`
`"CU"` `"CY"` `"CZ"` `"DK"` `"DJ"` `"DM"` `"DO"` `"EC"` `"EG"`
`"SV"` `"EE"` `"ET"` `"FJ"` `"FI"` `"FR"` `"GA"` `"GM"` `"GE"`
`"DE"` `"GH"` `"GI"` `"GR"` `"GL"` `"GT"` `"GG"` `"GY"` `"HT"`
`"HN"` `"HK"` `"HU"` `"IS"` `"IN"` `"ID"` `"IQ"` `"IE"` `"IM"`
`"IL"` `"IT"` `"JM"` `"JP"` `"JE"` `"JO"` `"KZ"` `"KE"` `"KI"`
`"KW"` `"KG"` `"LA"` `"LV"` `"LB"` `"LS"` `"LY"` `"LI"` `"LT"`
`"LU"` `"MG"` `"MW"` `"MY"` `"MV"` `"ML"` `"MT"` `"MU"` `"MX"`
`"FM"` `"MD"` `"MN"` `"ME"` `"MS"` `"MA"` `"MQ"` `"MZ"` `"MM"`
`"NA"` `"NR"` `"NP"` `"NL"` `"NZ"` `"NI"` `"NE"` `"NG"` `"NU"`
`"MK"` `"NO"` `"OM"` `"PK"` `"PS"` `"PA"` `"PG"` `"PY"` `"PE"`
`"PH"` `"PN"` `"PL"` `"PT"` `"PR"` `"QA"` `"RO"` `"RU"` `"RW"`
`"WS"` `"SM"` `"ST"` `"SA"` `"SN"` `"RS"` `"SC"` `"SL"` `"SG"`
`"SK"` `"SI"` `"SB"` `"SO"` `"ZA"` `"KR"` `"ES"` `"LK"` `"SH"`
`"VC"` `"SR"` `"SE"` `"CH"` `"TW"` `"TJ"` `"TZ"` `"TH"` `"TL"`

"TG"

"TO"

"TT"

"TN"

"TR"

"TM"

"VI"

"UG"

"UA"

"AE"

"GB"

"US"

"UY"

"UZ"

"VU"

"VE"

"VN"

"ZM"

"ZW"

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string
The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean
Default: `"true"`
The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.
A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.
As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean
Default: `"false"`
The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string
The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for

2

 hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /google-places-by-domain

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/google-places-by-domain?query=don
```

Response samples

- 200
- 202
- 204
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    { }
  ]
}
```

Yelp Search

Returns search results from Yelp.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings Search links with search parameters (e.g., <code>https://www.yelp.com/search?find_desc=Restaurants&find_loc=San+Francisco%2C+CA</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of items to get from one query.
enrichment	Array of strings The parameter defines an enrichment or enrichments (e.g., <code>enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3</code>) you want to apply to the results. Available values: <code>domains_service</code> — Emails & Contacts Scraper: finds emails, social links, phones, and other contacts from websites, <code>emails_validator_service</code> — Email Address Verifier: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate, <code>disposable_email_checker</code> — Disposable Emails Checker: checks origins of email addresses (disposable, free, or corporate), <code>company_insights_service</code> — Company Insights: finds company details such as revenue, size, founding year, public status, etc, <code>phones_enricher_service</code> — Phone Numbers Enricher: returns phones carrier data (name/type), validates phones, ensures messages deliverability, <code>trustpilot_service</code> — Trustpilot Scraper: returns data from a list of businesses, <code>whitepages_phones</code> - Phone Identity Finder: returns insights about phone number owners (name, address, etc.), <code>ai_chain_info</code> - Chain Info: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting.

Using enrichments increases the time of the response. You might want to use the `async=true` parameter to avoid getting timeouts.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

- **401** Wrong or missing API Key (token).
- **402** Past due invoices or a payment method not connected.
- **422** Wrong query url parameters.

GET /yelp-search

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/yelp-search?query=https%3A%2F%2Fw
```

Response samples

200

202

401

402

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Yelp Business

Return business information from Yelp.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings You can use direct links, and IDs of any Yelp business (e.g., <code>https://www.yelp.com/biz/cancha-boutique-gastrobar-san-francisco</code>, <code>eggcellent-waffles-san-francisco</code>, <code>iXoLJWjbcXCO43RT-H0uQQ</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/yelp-biz`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/yelp-biz?query=eggcellent-waffles"
```

Response samples

200

202

401

402

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + { ... }
  ]
}
```

Yellow Pages Search

Returns search results from Yellow Pages.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings
Categories to search for (e.g., `bars`, `restaurants`, `dentists`). It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

location

string
Default: `"New York, NY"`
The parameter specifies where to search (e.g., `New York, NY`).

limit

integer
Default: `100`
The parameter specifies the limit of items to get from one query.

region

string (region)
Enum: `"AF"` `"AL"` `"DZ"` `"AS"` `"AD"` `"AO"` `"AI"` `"AG"` `"AR"`
`"AM"` `"AU"` `"AT"` `"AZ"` `"BS"` `"BH"` `"BD"` `"BY"` `"BE"`
`"BZ"` `"BJ"` `"BT"` `"BO"` `"BA"` `"BW"` `"BR"` `"VG"` `"BN"`
`"BG"` `"BF"` `"BI"` `"KH"` `"CM"` `"CA"` `"CV"` `"CF"` `"TD"`
`"CL"` `"CN"` `"CO"` `"CG"` `"CD"` `"CK"` `"CR"` `"CI"` `"HR"`
`"CU"` `"CY"` `"CZ"` `"DK"` `"DJ"` `"DM"` `"DO"` `"EC"` `"EG"`
`"SV"` `"EE"` `"ET"` `"FJ"` `"FI"` `"FR"` `"GA"` `"GM"` `"GE"`
`"DE"` `"GH"` `"GI"` `"GR"` `"GL"` `"GT"` `"GG"` `"GY"` `"HT"`
`"HN"` `"HK"` `"HU"` `"IS"` `"IN"` `"ID"` `"IQ"` `"IE"` `"IM"`
`"IL"` `"IT"` `"JM"` `"JP"` `"JE"` `"JO"` `"KZ"` `"KE"` `"KI"`
`"KW"` `"KG"` `"LA"` `"LV"` `"LB"` `"LS"` `"LY"` `"LI"` `"LT"`
`"LU"` `"MG"` `"MW"` `"MY"` `"MV"` `"ML"` `"MT"` `"MU"` `"MX"`
`"FM"` `"MD"` `"MN"` `"ME"` `"MS"` `"MA"` `"MQ"` `"MZ"` `"MM"`
`"NA"` `"NR"` `"NP"` `"NL"` `"NZ"` `"NI"` `"NE"` `"NG"` `"NU"`
`"MK"` `"NO"` `"OM"` `"PK"` `"PS"` `"PA"` `"PG"` `"PY"` `"PE"`
`"PH"` `"PN"` `"PL"` `"PT"` `"PR"` `"QA"` `"RO"` `"RU"` `"RW"`
`"WS"` `"SM"` `"ST"` `"SA"` `"SN"` `"RS"` `"SC"` `"SL"` `"SG"`
`"SK"` `"SI"` `"SB"` `"SO"` `"ZA"` `"KR"` `"ES"` `"LK"` `"SH"`
`"VC"` `"SR"` `"SE"` `"CH"` `"TW"` `"TJ"` `"TZ"` `"TH"` `"TL"`
`"TG"` `"TO"` `"TT"` `"TN"` `"TR"` `"TM"` `"VI"` `"UG"` `"UA"`

"AE" "GB" "US" "UY" "UZ" "VU" "VE" "VN" "ZM"
"ZW"

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

enrichment

Array of strings

The parameter defines an enrichment or enrichments (e.g.,

`enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3`) you want to apply to the results.

Available values:

`domains_service` — **Emails & Contacts Scraper**: finds emails, social links, phones, and other contacts from websites,

`emails_validator_service` — **Email Address Verifier**: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate,

`disposable_email_checker` — **Disposable Emails Checker**: checks origins of email addresses (disposable, free, or corporate),

`company_insights_service` — **Company Insights**: finds company details such as revenue, size, founding year, public status, etc,

`phones_enricher_service` — **Phone Numbers Enricher**: returns phones carrier data (name/type), validates phones, ensures messages deliverability,

`trustpilot_service` — **Trustpilot Scraper**: returns data from a list of businesses,

`whitepages_phones` - **Phone Identity Finder**: returns insights about phone number owners (name, address, etc.),

`ai_chain_info` - **Chain Info**: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting.

Using enrichments increases the time of the response. You might want to use the `async=true` parameter to avoid getting timeouts.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation

	as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

GET /yellowpages-search

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/yellowpages-search?query=restaure"
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Booking Search

Returns search results from Booking.com

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings Search links with search parameters (e.g., <code>https://www.booking.com/searchresults.html?ss=Rome%2C+Lazio%2C+Italy</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of items to get from one query.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

	<code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /booking/search

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/booking-search?query=https%3A%2F%2F"
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Expedia Search

Returns search results from expedia.com

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query	Array of strings
required	Search links with search parameters (e.g., <code>https://www.expedia.com/Hotel-Search?destination=Ankara...</code>).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

`limit`

integer

Default: `100`

The parameter specifies the limit of items to get from one query.

`fields`

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

`async`

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

`ui`

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

`webhook`

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished.

Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for

2

 hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /expedia/search

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/expedia/search?query=https://www.
```

Response samples

200

202

401

402

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Trustpilot

Returns data from Trustpilot businesses.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Links to Trustpilot pages or domain names (e.g., `outscraper.com`, `https://www.trustpilot.com/review/outscraper.com`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

enrichment

Array of strings

The parameter defines an enrichment or enrichments (e.g.,

`enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3`) you want to apply to the results.

Available values:

`domains_service` — **Emails & Contacts Scraper**: finds emails, social links, phones, and other contacts from websites,

`emails_validator_service` — **Email Address Verifier**: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate,

`disposable_email_checker` — **Disposable Emails Checker**: checks origins of email addresses (disposable, free, or corporate),

`company_insights_service` — **Company Insights**: finds company details such as revenue, size, founding year, public status, etc,

`phones_enricher_service` — **Phone Numbers Enricher**: returns phones carrier data (name/type), validates phones, ensures messages deliverability,

`trustpilot_service` — **Trustpilot Scraper**: returns data from a list of businesses,

`whitepages_phones` - **Phone Identity Finder**: returns insights about phone number owners (name, address, etc.),

`ai_chain_info` - **Chain Info**: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting.

Using enrichments increases the time of the response. You might want to use the `async=true` parameter to avoid getting timeouts.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until

	you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /trustpilot

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/trustpilot?query=outscraper.com&a
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + { ... }
  ]
}
```

Trustpilot Search

Returns search results from Trustpilot.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings Company or category to search on Trustpilot (e.g., real estate). It supports batching by sending arrays with up to 250 queries (e.g., query=text1&query=text2&query=text3). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: 100 The parameter specifies the limit of items to get from one query.

skip	integer Default: <code>0</code> The parameter specifies the number of items to skip. It's commonly used in pagination.
enrichment	Array of strings The parameter defines an enrichment or enrichments (e.g., <code>enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3</code>) you want to apply to the results. Available values: <code>domains_service</code> — Emails & Contacts Scraper: finds emails, social links, phones, and other contacts from websites, <code>emails_validator_service</code> — Email Address Verifier: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate, <code>disposable_email_checker</code> — Disposable Emails Checker: checks origins of email addresses (disposable, free, or corporate), <code>company_insights_service</code> — Company Insights: finds company details such as revenue, size, founding year, public status, etc, <code>phones_enricher_service</code> — Phone Numbers Enricher: returns phones carrier data (name/type), validates phones, ensures messages deliverability, <code>trustpilot_service</code> — Trustpilot Scraper: returns data from a list of businesses, <code>whitepages_phones</code> - Phone Identity Finder: returns insights about phone number owners (name, address, etc.), <code>ai_chain_info</code> - Chain Info: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting. Using enrichments increases the time of the response. You might want to use the <code>async=true</code> parameter to avoid getting timeouts.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation

	as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

GET `/trustpilot/search`

Request samples

cURL

cURL (async)

Copy


```
curl -X GET "https://api.outscraper.cloud/trustpilot/search?query=real+estate"
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + { ... }
  ]
}
```

Reviews & Comments

Google Maps Reviews v3

Returns Google Maps reviews from places when using search queries (e.g., `restaurants, Manhattan, NY, USA`) or from a single place when using `Google IDs` or names (e.g., `NoMad Restaurant, NY, USA` , `0x886916e8bc273979:0x5141fcb11460b226`). In addition to the reviews, it returns places information.

In case no reviews were found by your search criteria, your search request will consume the usage of one review.

This endpoint is optimized for fast responses and can be used as a real-time API. Set the `reviewsLimit` parameter to 10 to achieve the maximum response speed.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

`query`
`required` Array of strings

The parameter defines the query you want to search. You can use anything that you would use on a regular Google Maps site. Additionally, you can use `google_id` (`feature_id`), `place_id`, or `CID`. The example of valid queries: `Real estate agency, Rome, Italy`, `The NoMad Restaurant, NY, USA`, `restaurants, Brooklyn 11203`, `0x886916e8bc273979:0x5141fcb11460b226`, `ChIJrZhup4lZwokRUr_5sLoF1Dw`, etc.

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and save on network latency time.

You might want to check out [the web application](#) to play with locations and categories that we would suggest.

reviewsLimit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one place (0 = unlimited).
reviewsQuery	string The parameter specifies the query to search among the reviews (e.g. <code>wow</code>, <code>amazing</code> <code>great</code>).
limit	integer Default: <code>1</code> The parameter specifies the limit of places to take from one query search.
sort	string Default: <code>"most_relevant"</code> Enum: <code>"most_relevant"</code> <code>"newest"</code> <code>"highest_rating"</code> <code>"lowest_rating"</code> The parameter specifies one of the sorting types.
lastPaginationId	string The parameter specifies the <code>review_pagination_id</code> of the last item. It's commonly used in pagination.
start	integer The parameter specifies the start timestamp value for reviews (newest review). The current timestamp is used when the value is not provided. Using the <code>start</code> parameter overwrites the <code>sort</code> parameter to <code>newest</code>. Therefore, the latest reviews will be at the beginning.
cutoff	integer The parameter specifies the oldest timestamp value for reviews (oldest review).

Using the `cutoff` parameter overwrites `sort` parameter to `newest`. Therefore, the latest reviews will be at the beginning.

`cutoffRating`

integer

The parameter specifies the maximum for `lowest_rating` sorting or the minimum for `highest_rating` sorting rating for reviews.

Using the `cutoffRating` requires sorting to be set to `lowest_rating` or `highest_rating`.

`ignoreEmpty`

boolean

Default: `"false"`

The parameter specifies whether to ignore reviews without text or not.

`source`

string

Default: `null`

Value: `"google"`

The parameter specifies source filter. This commonly used for hotels where you can find reviews from other sources like Booking.com, Expedia, etc.

`language`

string (language)

Default: `"en"`

Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"` `"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"` `"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"` `"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"` `"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"` `"eu"` `"ee"` `"tl"` `"fil"` `"fo"` `"fy"` `"gaa"` `"ga"` `"gd"` `"gl"` `"gn"` `"xx-hacker"` `"ht"` `"ha"` `"haw"` `"bem"` `"rn"` `"id"` `"ia"` `"xh"` `"zu"` `"is"` `"jw"` `"rw"` `"sw"` `"tlh"` `"kg"` `"mfe"` `"kri"` `"la"` `"lv"` `"to"` `"lt"` `"ln"` `"loz"` `"lua"` `"lg"` `"hu"` `"mg"` `"mt"` `"mi"` `"ms"` `"pcm"` `"no"` `"nso"` `"ny"` `"nn"` `"uz"` `"oc"` `"om"` `"xx-pirate"` `"ro"` `"rm"` `"qu"` `"nyn"` `"crs"` `"sq"` `"sk"` `"sl"` `"so"` `"st"` `"sr-ME"` `"sr-Latn"` `"su"` `"fi"` `"sv"` `"tn"` `"tum"` `"tk"` `"tw"` `"wo"` `"el"` `"be"` `"bg"` `"ky"` `"kk"` `"mk"` `"mn"` `"sr"` `"tt"` `"tg"` `"uk"` `"ka"` `"hy"` `"yi"` `"iw"` `"ug"` `"ur"` `"ps"` `"sd"` `"fa"` `"ckb"` `"ti"` `"am"` `"ne"` `"mr"` `"hi"` `"bn"` `"pa"` `"gu"` `"or"` `"ta"` `"te"` `"kn"` `"ml"` `"si"` `"lo"` `"my"` `"km"` `"chr"`

The parameter specifies the language to use for website.

`region`

string (region)

Enum: `"AF"` `"AL"` `"DZ"` `"AS"` `"AD"` `"AO"` `"AI"` `"AG"` `"AR"` `"AM"` `"AU"` `"AT"` `"AZ"` `"BS"` `"BH"` `"BD"` `"BY"` `"BE"` `"BZ"` `"BJ"` `"BT"` `"BO"` `"BA"` `"BW"` `"BR"` `"VG"` `"BN"` `"BG"` `"BF"` `"BI"` `"KH"` `"CM"` `"CA"` `"CV"` `"CF"` `"TD"`

"CL"	"CN"	"CO"	"CG"	"CD"	"CK"	"CR"	"CI"	"HR"
"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a place with its reviews.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/maps/reviews-v3`

Request samples

cURL

cURL (async)

Python

Ruby

PHP

Node.js

Go

Java

Copy

```
curl -X GET "https://api.outscraper.cloud/maps/reviews-v3?query=The%20NoMac"
```

Response samples

200

202

204

401

402

422

Content type

application/json

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + { ... }
  ]
}
```

Google Play Reviews

Returns reviews from any app/book/movie in the Google Play store.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

You can use app IDs or direct links (e.g., `https://play.google.com/store/apps/details?id=com.facebook.katana`, `com.facebook.katana`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

limit

integer

Default: `100`

The parameter specifies the limit of reviews to get from one query.

sort

string

Default: `"most_relevant"`

Enum: `"most_relevant"` `"newest"` `"rating"`

The parameter specifies one of the sorting types.

cutoff

integer

The parameter specifies the oldest timestamp value for items.

Using the `cutoff` parameter overwrites `sort` parameter`. Therefore, the latest records will be at the beginning (newest first).

rating

integer

Filter by a specific rating. Works only with `sort=rating`.

language

string (language)

Default: `"en"`

Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"`
`"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"`
`"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"`
`"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"`
`"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"`
`"eu"` `"ee"` `"tl"` `"fil"` `"fo"` `"fy"` `"gaa"` `"ga"` `"gd"`
`"gl"` `"gn"` `"xx-hacker"` `"ht"` `"ha"` `"haw"` `"bem"` `"rn"`
`"id"` `"ia"` `"xh"` `"zu"` `"is"` `"jw"` `"rw"` `"sw"` `"tlh"`
`"kg"` `"mfe"` `"kri"` `"la"` `"lv"` `"to"` `"lt"` `"ln"` `"loz"`
`"lua"` `"lg"` `"hu"` `"mg"` `"mt"` `"mi"` `"ms"` `"pcm"` `"no"`
`"nso"` `"ny"` `"nn"` `"uz"` `"oc"` `"om"` `"xx-pirate"` `"ro"`
`"rm"` `"qu"` `"nyn"` `"crs"` `"sq"` `"sk"` `"sl"` `"so"` `"st"`
`"sr-ME"` `"sr-Latn"` `"su"` `"fi"` `"sv"` `"tn"` `"tum"` `"tk"`
`"tw"` `"wo"` `"el"` `"be"` `"bg"` `"ky"` `"kk"` `"mk"` `"mn"`
`"sr"` `"tt"` `"tg"` `"uk"` `"ka"` `"hy"` `"yi"` `"iw"` `"ug"`
`"ur"` `"ps"` `"sd"` `"fa"` `"ckb"` `"ti"` `"am"` `"ne"` `"mr"`
`"hi"` `"bn"` `"pa"` `"gu"` `"or"` `"ta"` `"te"` `"kn"` `"ml"`
`"si"` `"lo"` `"my"` `"km"` `"chr"`

The parameter specifies the language to use for website.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/google-play/reviews`

Request samples

cURL

cURL (async)

Python

Copy

```
curl -X GET "https://api.outscraper.cloud/google-play/reviews?query=com.fac
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Google Shopping Reviews

Returns reviews from Google product based on a given search query (or many queries).

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings Product links or product IDs (e.g., <code>https://www.google.com/shopping/product/7016166685587850095</code>, <code>7016166685587850095</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
perQuery	integer Default: <code>100</code> The parameter specifies the limit of items to return from one query.
uule	string Google UULE parameter is used to encode a place or an exact location (with latitude and longitude) into a code. By using it you can see a Google result page like someone located at the specified location.
language	string (language) Default: <code>"en"</code>

Enum:

"en"	"de"	"es"	"es-419"	"fr"	"hr"	"it"	"nl"
"pl"	"pt-BR"	"pt-PT"	"vi"	"tr"	"ru"	"ar"	"th"
"ko"	"zh-CN"	"zh-TW"	"ja"	"ach"	"af"	"ak"	"ig"
"az"	"ban"	"ceb"	"xx-bork"	"bs"	"br"	"ca"	"cs"
"sn"	"co"	"cy"	"da"	"yo"	"et"	"xx-elmer"	"eo"
"eu"	"ee"	"tl"	"fil"	"fo"	"fy"	"gaa"	"ga"
"gd"	"gl"	"gn"	"xx-hacker"	"ht"	"ha"	"haw"	"bem"
"rn"	"id"	"ia"	"xh"	"zu"	"is"	"jw"	"rw"
"sw"	"tlh"	"kg"	"mfe"	"kri"	"la"	"lv"	"to"
"lt"	"ln"	"loz"	"lua"	"lg"	"hu"	"mg"	"mt"
"mi"	"ms"	"pcm"	"no"	"nso"	"ny"	"nn"	"uz"
"oc"	"om"	"xx-pirate"	"ro"	"rm"	"qu"	"nyn"	"crs"
"sq"	"sk"	"sl"	"so"	"st"	"sr-ME"	"sr-Latn"	"su"
"fi"	"sv"	"tn"	"tum"	"tk"	"tw"	"wo"	"el"
"be"	"bg"	"ky"	"kk"	"mk"	"mn"	"sr"	"tt"
"tg"	"uk"	"ka"	"hy"	"yi"	"iw"	"ug"	"ur"
"ps"	"sd"	"fa"	"ckb"	"ti"	"am"	"ne"	"mr"
"hi"	"bn"	"pa"	"gu"	"or"	"ta"	"te"	"kn"
"ml"	"si"	"lo"	"my"	"km"	"chr"		

The parameter specifies the language to use for website.

region

string (region)

Enum:

"AF"	"AL"	"DZ"	"AS"	"AD"	"AO"	"AI"	"AG"	"AR"
"AM"	"AU"	"AT"	"AZ"	"BS"	"BH"	"BD"	"BY"	"BE"
"BZ"	"BJ"	"BT"	"BO"	"BA"	"BW"	"BR"	"VG"	"BN"
"BG"	"BF"	"BI"	"KH"	"CM"	"CA"	"CV"	"CF"	"TD"
"CL"	"CN"	"CO"	"CG"	"CD"	"CK"	"CR"	"CI"	"HR"
"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

- **401** Wrong or missing API Key (token).
- **402** Past due invoices or a payment method not connected.
- **422** Wrong query url parameters.

GET /google-shopping-reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/google-shopping-reviews?query=701"
```

Response samples

200

202

204

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Reddit Comments

Returns comments from Reddit.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings Reddit post URLs (e.g., <code>https://www.reddit.com/r/AskReddit/comments/abcdef/example_post_title/</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
sort	string Default: <code>"best"</code> Enum: <code>"best"</code> <code>"top"</code> <code>"new"</code> <code>"controversial"</code> <code>"old"</code> <code>"qa"</code> The parameter specifies one of the sorting types.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /reddit-comments

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/reddit-comments?query=https://www
```

Response samples

- 200
- 202
- 204
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
```

}

YouTube Comments

Returns comments from YouTube videos.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Video links or video IDs (e.g., <https://www.youtube.com/watch?v=ph5pHgklaZ0>, [ph5pHgklaZ0](#)).

It supports batching by sending arrays with up to **250** queries (e.g., [query=text1&query=text2&query=text3](#)). It allows multiple queries to be sent in one request and to save on network latency time.

perQuery

integer

Default: **100**

The parameter specifies the limit of items to return from one query.

language

string (language)

Default: **"en"**

Enum: **"en"** **"de"** **"es"** **"es-419"** **"fr"** **"hr"** **"it"** **"nl"**

"pl" **"pt-BR"** **"pt-PT"** **"vi"** **"tr"** **"ru"** **"ar"** **"th"**

"ko" **"zh-CN"** **"zh-TW"** **"ja"** **"ach"** **"af"** **"ak"** **"ig"**

"az" **"ban"** **"ceb"** **"xx-bork"** **"bs"** **"br"** **"ca"** **"cs"**

"sn" **"co"** **"cy"** **"da"** **"yo"** **"et"** **"xx-elmer"** **"eo"**

"eu" **"ee"** **"tl"** **"fil"** **"fo"** **"fy"** **"gaa"** **"ga"** **"gd"**

"gl" **"gn"** **"xx-hacker"** **"ht"** **"ha"** **"haw"** **"bem"** **"rn"**

"id" **"ia"** **"xh"** **"zu"** **"is"** **"jw"** **"rw"** **"sw"** **"tlh"**

"kg" **"mfe"** **"kri"** **"la"** **"lv"** **"to"** **"lt"** **"ln"** **"loz"**

"lua" **"lg"** **"hu"** **"mg"** **"mt"** **"mi"** **"ms"** **"pcm"** **"no"**

"nso" **"ny"** **"nn"** **"uz"** **"oc"** **"om"** **"xx-pirate"** **"ro"**

"rm" **"qu"** **"nyn"** **"crs"** **"sq"** **"sk"** **"sl"** **"so"** **"st"**

"sr-ME" **"sr-Latn"** **"su"** **"fi"** **"sv"** **"tn"** **"tum"** **"tk"**

"tw" **"wo"** **"el"** **"be"** **"bg"** **"ky"** **"kk"** **"mk"** **"mn"**

"sr" **"tt"** **"tg"** **"uk"** **"ka"** **"hy"** **"yi"** **"iw"** **"ug"**

"ur" **"ps"** **"sd"** **"fa"** **"ckb"** **"ti"** **"am"** **"ne"** **"mr"**

"hi" **"bn"** **"pa"** **"gu"** **"or"** **"ta"** **"te"** **"kn"** **"ml"**

"si" **"lo"** **"my"** **"km"** **"chr"**

The parameter specifies the language to use for website.

region

string (region)

Enum:

"AF"	"AL"	"DZ"	"AS"	"AD"	"AO"	"AI"	"AG"	"AR"
"AM"	"AU"	"AT"	"AZ"	"BS"	"BH"	"BD"	"BY"	"BE"
"BZ"	"BJ"	"BT"	"BO"	"BA"	"BW"	"BR"	"VG"	"BN"
"BG"	"BF"	"BI"	"KH"	"CM"	"CA"	"CV"	"CF"	"TD"
"CL"	"CN"	"CO"	"CG"	"CD"	"CK"	"CR"	"CI"	"HR"
"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /youtube-comments

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/youtube-comments?query=ph5pHgklaž"
```

Response samples

- 200
- 202
- 204
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Indeed Reviews

Returns reviews from Indeed companies.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required Array of strings

You can use direct links, and IDs of any Indeed company (e.g., `https://www.indeed.com/cmp/TEKsystems`, `TEKsystems`). It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

limit

integer

Default: `100`

The parameter specifies the limit of reviews to get from one query.

sort

string

Default: `" "`Enum: `"helpfulness"` `"rating_desc"`

The parameter specifies one of the sorting types.

cutoff

integer

The parameter specifies the oldest timestamp value for items.

Using the `cutoff` parameter overwrites `sort` parameter. Therefore, the latest records will be at the beginning (newest first).**fields**

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.**async**

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /indeed/reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/indeed/reviews?query=TEKsystems&l
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{  
  "id": "your-request-id",  
  "status": "Success",  
  "data": [ ]  
}
```

AppStore Reviews

Returns reviews from AppStore apps.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

You can use direct links, and IDs of any AppStore app (e.g.,

`https://apps.apple.com/us/app/telegram-messenger/id686449807`, `id686449807`).

It supports batching by sending arrays with up to `250` queries (e.g.,

`query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

limit

integer

Default: `100`

The parameter specifies the limit of reviews to get from one query.

sort

string

Default: `"mosthelpful"`

Enum: `"mosthelpful"` `"mostrecent"`

The parameter specifies one of the sorting types.

cutoff

integer

The parameter specifies the oldest timestamp value for items.

Using the `cutoff` parameter overwrites `sort` parameter`. Therefore, the latest records will be at the beginning (newest first).

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).**— 402 Past due invoices or a payment method not connected.****— 422 Wrong query url parameters.**

GET /appstore/reviews

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/appstore/reviews?query=https://a
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Glassdoor Reviews

Returns reviews from Glassdoor companies.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required

Array of strings
You can use direct links to any Glassdoor company (e.g., `'https://www.glassdoor.com/Reviews/Amazon-Reviews-E6036.htm'`).
It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
sort	string Default: <code>"DATE"</code> Enum: <code>"DATE"</code> <code>"RELEVANCE"</code> The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /glassdoor/reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/glassdoor/reviews?query=https%3A%3F"
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Airbnb Reviews

Returns reviews from Airbnb accommodations.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings You can use direct links, and IDs of any Airbnb accommodation (e.g., <code>https://www.airbnb.com/rooms/927539322986647456</code>, <code>1125445123101274851</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
sort	string Default: <code>"MOST_RECENT"</code> Enum: <code>"MOST_RECENT"</code> <code>"RATING_DESC"</code> <code>"RATING_ASC"</code> The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the

	Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/airbnb/reviews`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/airbnb/reviews?query=https://www.
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

GetApp Reviews

Returns reviews from GetApp apps.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required

Array of strings

You can use direct links to any GetApp app (e.g., `https://www.getapp.com/customer-management-software/a/salesforce/reviews/`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

limit

integer

Default: `100`

The parameter specifies the limit of reviews to get from one query.

sort

string

	Default: <code>"recommended"</code> Enum: <code>"recommended"</code> <code>"most_recent"</code> <code>"least_recent"</code> <code>"highest_rated"</code> <code>"lowest_rated"</code> The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/getapp/reviews`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/getapp/reviews?query=https%3A%2F%2F"
```

Response samples

202

401

402

422

Content type

application/json

Copy

```
{
  "id": "your-request-id",
  "status": "Pending",
  "results_location": "https://api.outscraper.cloud/requests/your-request"
}
```

Booking Reviews

Returns reviews from Booking.com hotels.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings You can use direct links, and IDs of any booking hotel (e.g., <code>https://www.booking.com/hotel/tr/old-town-point-amp-spa-antalya.html</code> , <code>old-town-point-amp-spa-antalya</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
skip	integer Default: <code>0</code> The parameter specifies the number of items to skip. It's commonly used in pagination.
sort	string Default: <code>" "</code> Enum: <code>"f_recent_desc"</code> <code>"f_recent_asc"</code> <code>"f_score_desc"</code> <code>"f_score_asc"</code> The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
language	string (language) Default: <code>"en"</code> Enum: <code>"en"</code> <code>"de"</code> <code>"es"</code> <code>"es-419"</code> <code>"fr"</code> <code>"hr"</code> <code>"it"</code> <code>"nl"</code> <code>"pl"</code> <code>"pt-BR"</code> <code>"pt-PT"</code> <code>"vi"</code> <code>"tr"</code> <code>"ru"</code> <code>"ar"</code> <code>"th"</code> <code>"ko"</code> <code>"zh-CN"</code> <code>"zh-TW"</code> <code>"ja"</code> <code>"ach"</code> <code>"af"</code> <code>"ak"</code> <code>"ig"</code> <code>"az"</code> <code>"ban"</code> <code>"ceb"</code> <code>"xx-bork"</code> <code>"bs"</code> <code>"br"</code> <code>"ca"</code> <code>"cs"</code> <code>"sn"</code> <code>"co"</code> <code>"cy"</code> <code>"da"</code> <code>"yo"</code> <code>"et"</code> <code>"xx-elmer"</code> <code>"eo"</code>

"eu"	"ee"	"tl"	"fil"	"fo"	"fy"	"gaa"	"ga"	"gd"
"gl"	"gn"	"xx-hacker"	"ht"	"ha"	"haw"	"bem"	"rn"	
"id"	"ia"	"xh"	"zu"	"is"	"jw"	"rw"	"sw"	"tlh"
"kg"	"mfe"	"kri"	"la"	"lv"	"to"	"lt"	"ln"	"loz"
"lua"	"lg"	"hu"	"mg"	"mt"	"mi"	"ms"	"pcm"	"no"
"nso"	"ny"	"nn"	"uz"	"oc"	"om"	"xx-pirate"	"ro"	
"rm"	"qu"	"nyn"	"crs"	"sq"	"sk"	"sl"	"so"	"st"
"sr-ME"	"sr-Latn"	"su"	"fi"	"sv"	"tn"	"tum"	"tk"	
"tw"	"wo"	"el"	"be"	"bg"	"ky"	"kk"	"mk"	"mn"
"sr"	"tt"	"tg"	"uk"	"ka"	"hy"	"yi"	"iw"	"ug"
"ur"	"ps"	"sd"	"fa"	"ckb"	"ti"	"am"	"ne"	"mr"
"hi"	"bn"	"pa"	"gu"	"or"	"ta"	"te"	"kn"	"ml"
"si"	"lo"	"my"	"km"	"chr"				

The parameter specifies the language to use for website.

region

string (region)

Enum:	"AF"	"AL"	"DZ"	"AS"	"AD"	"AO"	"AI"	"AG"	"AR"
	"AM"	"AU"	"AT"	"AZ"	"BS"	"BH"	"BD"	"BY"	"BE"
	"BZ"	"BJ"	"BT"	"BO"	"BA"	"BW"	"BR"	"VG"	"BN"
	"BG"	"BF"	"BI"	"KH"	"CM"	"CA"	"CV"	"CF"	"TD"
	"CL"	"CN"	"CO"	"CG"	"CD"	"CK"	"CR"	"CI"	"HR"
	"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
	"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
	"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
	"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
	"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
	"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
	"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
	"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
	"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
	"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
	"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
	"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
	"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
	"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
	"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
	"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
	"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).**— 402 Past due invoices or a payment method not connected.****— 422 Wrong query url parameters.**

GET /booking/reviews

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/booking/reviews?query=https://www
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Capterra Reviews

Returns reviews from Capterra.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings Links to Capterra product pages (e.g., <code>https://www.capterra.com/p/228041/Google-Maps-scraper/</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to
-------------------	--

be sent in one request and to save on network latency time.

limit	integer Default: 100 The parameter specifies the limit of reviews to get from one query.
sort	string Default: "MOST_HELPFUL" Enum: "MOST_HELPFUL" "MOST_RECENT" "HIGHEST_RATING" "LOWEST_RATING" The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
language	string (language) Default: "en" Enum: "en" "de" "es" "es-419" "fr" "hr" "it" "nl" "pl" "pt-BR" "pt-PT" "vi" "tr" "ru" "ar" "th" "ko" "zh-CN" "zh-TW" "ja" "ach" "af" "ak" "ig" "az" "ban" "ceb" "xx-bork" "bs" "br" "ca" "cs" "sn" "co" "cy" "da" "yo" "et" "xx-elmer" "eo" "eu" "ee" "tl" "fil" "fo" "fy" "gaa" "ga" "gd" "gl" "gn" "xx-hacker" "ht" "ha" "haw" "bem" "rn" "id" "ia" "xh" "zu" "is" "jw" "rw" "sw" "tlh" "kg" "mfe" "kri" "la" "lv" "to" "lt" "ln" "loz" "lua" "lg" "hu" "mg" "mt" "mi" "ms" "pcm" "no" "nso" "ny" "nn" "uz" "oc" "om" "xx-pirate" "ro" "rm" "qu" "nyn" "crs" "sq" "sk" "sl" "so" "st" "sr-ME" "sr-Latn" "su" "fi" "sv" "tn" "tum" "tk" "tw" "wo" "el" "be" "bg" "ky" "kk" "mk" "mn" "sr" "tt" "tg" "uk" "ka" "hy" "yi" "iw" "ug" "ur" "ps" "sd" "fa" "ckb" "ti" "am" "ne" "mr" "hi" "bn" "pa" "gu" "or" "ta" "te" "kn" "ml" "si" "lo" "my" "km" "chr" The parameter specifies the language to use for website.
region	string (region) Enum: "AF" "AL" "DZ" "AS" "AD" "AO" "AI" "AG" "AR" "AM" "AU" "AT" "AZ" "BS" "BH" "BD" "BY" "BE" "BZ" "BJ" "BT" "BO" "BA" "BW" "BR" "VG" "BN" "BG" "BF" "BI" "KH" "CM" "CA" "CV" "CF" "TD" "CL" "CN" "CO" "CG" "CD" "CK" "CR" "CI" "HR" "CU" "CY" "CZ" "DK" "DJ" "DM" "DO" "EC" "EG"

"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string
The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean
Default: `"true"`
The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.
A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.
As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean
Default: `"false"`
The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /capterra-reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/capterra-reviews?query=https://w
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Product Hunt Reviews

Returns reviews from Product Hunt.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings Links to Product Hunt product pages, or page IDs (e.g., <code>https://www.producthunt.com/products/outscraper</code>, <code>outscraper</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
cursor	string The parameter specifies the next page cursor (<code>next_page_cursor</code>) from the previous chunk of records (usually <code>10</code>). It's commonly used in pagination.
sort	string Default: <code>"BEST"</code> Enum: <code>"BEST"</code> <code>"LATEST"</code> <code>"FAVORABLE"</code> <code>"CRITICAL"</code> The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items.

Using the `cutoff` parameter overwrites `sort` parameter`. Therefore, the latest records will be at the beginning (newest first).

language

string (language)

Default: `"en"`

Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"` `"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"` `"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"` `"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"` `"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"` `"eu"` `"ee"` `"tl"` `"fil"` `"fo"` `"fy"` `"gaa"` `"ga"` `"gd"` `"gl"` `"gn"` `"xx-hacker"` `"ht"` `"ha"` `"haw"` `"bem"` `"rn"` `"id"` `"ia"` `"xh"` `"zu"` `"is"` `"jw"` `"rw"` `"sw"` `"tlh"` `"kg"` `"mfe"` `"kri"` `"la"` `"lv"` `"to"` `"lt"` `"ln"` `"loz"` `"lua"` `"lg"` `"hu"` `"mg"` `"mt"` `"mi"` `"ms"` `"pcm"` `"no"` `"nso"` `"ny"` `"nn"` `"uz"` `"oc"` `"om"` `"xx-pirate"` `"ro"` `"rm"` `"qu"` `"nyn"` `"crs"` `"sq"` `"sk"` `"sl"` `"so"` `"st"` `"sr-ME"` `"sr-Latn"` `"su"` `"fi"` `"sv"` `"tn"` `"tum"` `"tk"` `"tw"` `"wo"` `"el"` `"be"` `"bg"` `"ky"` `"kk"` `"mk"` `"mn"` `"sr"` `"tt"` `"tg"` `"uk"` `"ka"` `"hy"` `"yi"` `"iw"` `"ug"` `"ur"` `"ps"` `"sd"` `"fa"` `"ckb"` `"ti"` `"am"` `"ne"` `"mr"` `"hi"` `"bn"` `"pa"` `"gu"` `"or"` `"ta"` `"te"` `"kn"` `"ml"` `"si"` `"lo"` `"my"` `"km"` `"chr"`

The parameter specifies the language to use for website.

region

string (region)

Enum: `"AF"` `"AL"` `"DZ"` `"AS"` `"AD"` `"AO"` `"AI"` `"AG"` `"AR"` `"AM"` `"AU"` `"AT"` `"AZ"` `"BS"` `"BH"` `"BD"` `"BY"` `"BE"` `"BZ"` `"BJ"` `"BT"` `"BO"` `"BA"` `"BW"` `"BR"` `"VG"` `"BN"` `"BG"` `"BF"` `"BI"` `"KH"` `"CM"` `"CA"` `"CV"` `"CF"` `"TD"` `"CL"` `"CN"` `"CO"` `"CG"` `"CD"` `"CK"` `"CR"` `"CI"` `"HR"` `"CU"` `"CY"` `"CZ"` `"DK"` `"DJ"` `"DM"` `"DO"` `"EC"` `"EG"` `"SV"` `"EE"` `"ET"` `"FJ"` `"FI"` `"FR"` `"GA"` `"GM"` `"GE"` `"DE"` `"GH"` `"GI"` `"GR"` `"GL"` `"GT"` `"GG"` `"GY"` `"HT"` `"HN"` `"HK"` `"HU"` `"IS"` `"IN"` `"ID"` `"IQ"` `"IE"` `"IM"` `"IL"` `"IT"` `"JM"` `"JP"` `"JE"` `"JO"` `"KZ"` `"KE"` `"KI"` `"KW"` `"KG"` `"LA"` `"LV"` `"LB"` `"LS"` `"LY"` `"LI"` `"LT"` `"LU"` `"MG"` `"MW"` `"MY"` `"MV"` `"ML"` `"MT"` `"MU"` `"MX"` `"FM"` `"MD"` `"MN"` `"ME"` `"MS"` `"MA"` `"MQ"` `"MZ"` `"MM"` `"NA"` `"NR"` `"NP"` `"NL"` `"NZ"` `"NI"` `"NE"` `"NG"` `"NU"` `"MK"` `"NO"` `"OM"` `"PK"` `"PS"` `"PA"` `"PG"` `"PY"` `"PE"` `"PH"` `"PN"` `"PL"` `"PT"` `"PR"` `"QA"` `"RO"` `"RU"` `"RW"` `"WS"` `"SM"` `"ST"` `"SA"` `"SN"` `"RS"` `"SC"` `"SL"` `"SG"` `"SK"` `"SI"` `"SB"` `"SO"` `"ZA"` `"KR"` `"ES"` `"LK"` `"SH"` `"VC"` `"SR"` `"SE"` `"CH"` `"TW"` `"TJ"` `"TZ"` `"TH"` `"TL"` `"TG"` `"TO"` `"TT"` `"TN"` `"TR"` `"TM"` `"VI"` `"UG"` `"UA"`

"AE" "GB" "US" "UY" "UZ" "VU" "VE" "VN" "ZM"
"ZW"

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for **2** hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /producthunt-reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/producthunt-reviews?query=outscrea
```

Response samples

200**202****401****402****422**

Content type

application/json

Copy

{ }

Yelp Reviews

Returns reviews from Yelp businesses.

In case no reviews were found by your search criteria, your search request will consume the usage of one review.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings You can use direct links, and IDs of any Yelp business (e.g., <code>https://www.yelp.com/biz/cancha-boutique-gastrobar-san-francisco</code>, <code>eggcellent-waffles-san-francisco</code>, <code>iXoLJWjbcXCO43RT-H0uQQ</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
cursor	string The parameter specifies the next page cursor (<code>next_page_cursor</code>) from the previous chunk of records (usually <code>10</code>). It's commonly used in pagination.
sort	string Default: <code>"relevance_desc"</code> Enum: <code>"relevance_desc"</code> <code>"date_desc"</code> <code>"date_asc"</code> <code>"rating_desc"</code> <code>"rating_asc"</code> <code>"elites_desc"</code> The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation

	as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

GET /yelp/reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/yelp/reviews?query=eggcellent-waf"
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Expedia Reviews

Returns reviews from expedia.com places.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings You can use direct links of any expedia place, or place IDs (e.g., <code>https://www.expedia.com/Las-Vegas-Hotels-The-Orleans-Hotel-Casino.h41313.Hotel-Information</code> , <code>41313</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
sort	string Default: <code>"NEWEST_TO_OLDEST_BY_LANGUAGE"</code>

Enum: `"NEWEST_TO_OLDEST_BY_LANGUAGE"` `"NEWEST_TO_OLDEST"`
`"HIGHEST_TO_LOWEST_RATED"` `"LOWEST_TO_HIGHEST_RATED"`

The parameter specifies one of the sorting types.

cutoff

integer

The parameter specifies the oldest timestamp value for items.

Using the `cutoff` parameter overwrites `sort` parameter`. Therefore, the latest records will be at the beginning (newest first).

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished.

Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/expedia/reviews`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/expedia/reviews?query=https://www
```

Response samples

200

202

401

402

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Trustpilot Reviews

Returns reviews from Trustpilot businesses.

In case no reviews were found by your search criteria, your search request will consume the usage of one review.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

<code>query</code> <code>required</code>	Array of strings Links to Trustpilot pages or domain names (e.g., <code>outscraper.com</code>, <code>https://www.trustpilot.com/review/outscraper.com</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
<code>limit</code>	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
<code>languages</code>	string Default: <code>"default"</code> Enum: <code>"default"</code> <code>"all"</code> <code>"en"</code> <code>"es"</code> <code>"de"</code> The parameter specifies one of the language filters.
<code>sort</code>	string Default: <code>" "</code> Value: <code>"recency"</code> The parameter specifies one of the sorting types.
<code>cutoff</code>	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
<code>fields</code>	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
<code>async</code>	boolean Default: <code>"true"</code>

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /trustpilot/reviews

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/trustpilot/reviews?query=outscraper"
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Tripadvisor Reviews

Returns reviews from Tripadvisor businesses.
In case no reviews were found by your search criteria, your search request will consume the usage of one review.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query	Array of strings
required	Links to Tripadvisor pages (e.g., https://www.tripadvisor.com/Restaurant_Review-g187147-

`dl2947099-Reviews-Mayfair_Garden-Paris_Ile_de_France.html`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

limit

integer

Default: `100`

The parameter specifies the limit of reviews to get from one query.

cutoff

integer

The parameter specifies the oldest timestamp value for items.

Using the `cutoff` parameter overwrites `sort` parameter`. Therefore, the latest records will be at the beginning (newest first).

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished.

Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /tripadvisor-reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/tripadvisor-reviews?query=https://"
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

G2 Reviews

Returns reviews from a list of products.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings Links to G2 products (e.g., <code>https://www.g2.com/products/outscraper</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
sort	string Default: <code>"g2_default"</code> Enum: <code>"g2_default"</code> <code>"most_recent"</code> <code>"most_helpful"</code> <code>"highest_rated"</code> <code>"lowest_rated"</code> The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /g2/reviews

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/g2/reviews?query=https://www.g2.c
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Amazon Reviews

Returns product's reviews from Amazon.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings You can use URLs or ASINs from Amazon products (e.g., <code>https://www.amazon.com/dp/1612680194</code> , <code>1612680194</code> , etc.).
-------------------	---

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

<code>limit</code>	integer Default: <code>10</code> The parameter specifies the limit of reviews to get from one query.
<code>cutoff</code>	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
<code>filterByReviewer</code>	string Default: <code>"all_reviews"</code> Enum: <code>"all_reviews"</code> <code>"avp_only_reviews"</code> The parameter specifies one of the reviewer filter types (All reviewers / Verified purchase only).
<code>filterByReviewer</code>	string Default: <code>"all_reviews"</code> Enum: <code>"all_reviews"</code> <code>"avp_only_reviews"</code> The parameter specifies one of the reviewer filter types (All reviewers / Verified purchase only). Works only for <code>amazon.com</code>, <code>amazon.ca</code>, <code>amazon.com.br</code>, <code>amazon.com.mx</code> .
<code>filterByStar</code>	string Default: <code>"all_stars"</code> Enum: <code>"all_stars"</code> <code>"five_star"</code> <code>"four_star"</code> <code>"three_star"</code> <code>"two_star"</code> <code>"one_star"</code> <code>"positive"</code> <code>"critical"</code> The parameter specifies one of the filter types by stars.
<code>domain</code>	string Default: <code>"amazon.com"</code> Enum: <code>"amazon.com"</code> <code>"amazon.co.uk"</code> <code>"amazon.ca"</code> <code>"amazon.de"</code> <code>"amazon.es"</code> <code>"amazon.fr"</code> <code>"amazon.it"</code> <code>"amazon.in"</code> <code>"amazon.nl"</code> <code>"amazon.se"</code> <code>"amazon.sa"</code> <code>"amazon.com.mx"</code> <code>"amazon.com.br"</code> <code>"amazon.com.au"</code> <code>"amazon.co.jp"</code> <code>"amazon.pl"</code> <code>"amazon.ae"</code> The parameter specifies Amazon domain to use.

fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

- **402** Past due invoices or a payment method not connected.
- **422** Wrong query url parameters.

GET /amazon/reviews

Request samples

cURL

cURL (async)

Python

Copy

```
curl -X GET "https://api.outscraper.cloud/amazon/reviews?query=https://www.
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Walmart Reviews

Returns reviews from a list of products.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required

Array of strings

Links to Walmart products (e.g.,

`https://www.walmart.com/ip/Blackstone-Original-4-Burner-36-
Propane-Omnivore-Griddle-with-Hard-Cover/1347629739`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

limit

integer

Default: `100`

The parameter specifies the limit of reviews to get from one query.

sort

string

Default: `"relevancy"`

Enum: `"relevancy"` `"helpful"` `"submission-desc"`
`"submission-asc"` `"rating-desc"` `"rating-asc"`

The parameter specifies one of the sorting types.

cutoff

integer

The parameter specifies the oldest timestamp value for items.

Using the `cutoff` parameter overwrites `sort` parameter`. Therefore, the latest records will be at the beginning (newest first).

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string
The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

- 401 Wrong or missing API Key (token).
- 402 Past due invoices or a payment method not connected.
- 422 Wrong query url parameters.

GET /walmart/reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/walmart/reviews?query=https://www
```

Response samples

200

202

401

402

422

Content type
application/json

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Target Reviews

Returns reviews from a list of products.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings Links to Target products (e.g., <code>https://www.target.com/p/apple-iphone-15-pro-max/-/A-89957794</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
sort	string Default: <code>"most_recent"</code> Enum: <code>"most_recent"</code> <code>"highest_rating"</code> <code>"lowest_rating"</code> <code>"helpfulness_desc"</code> The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).

fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

- **402** Past due invoices or a payment method not connected.
- **422** Wrong query url parameters.

GET /target/reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/target/reviews?query=https://www.
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Products & Listings

Amazon Products

Returns information about products on Amazon.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings You can use Amazon products, searches, or summary page URLs. It supports batching by sending arrays with up to 250 queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: 24 The parameter specifies the limit of products to get from one query (in case of using summary pages).
domain	string Default: "amazon.com" Enum: "amazon.com" "amazon.co.uk" "amazon.ca" "amazon.de" "amazon.es" "amazon.fr" "amazon.it" "amazon.in" "amazon.nl" "amazon.se" "amazon.sa" "amazon.com.mx" "amazon.com.br" "amazon.com.au" "amazon.co.jp" "amazon.pl" "amazon.ae" The parameter specifies Amazon domain to use.
postal_code	string Default: "11201" The parameter specifies the postal code for delivery.
language	string (language) Default: "en" Enum: "en" "de" "es" "es-419" "fr" "hr" "it" "nl" "pl" "pt-BR" "pt-PT" "vi" "tr" "ru" "ar" "th" "ko" "zh-CN" "zh-TW" "ja" "ach" "af" "ak" "ig" "az" "ban" "ceb" "xx-bork" "bs" "br" "ca" "cs" "sn" "co" "cy" "da" "yo" "et" "xx-elmer" "eo" "eu" "ee" "tl" "fil" "fo" "fy" "gaa" "ga" "gd" "gl" "gn" "xx-hacker" "ht" "ha" "haw" "bem" "rn" "id" "ia" "xh" "zu" "is" "jw" "rw" "sw" "tlh" "kg" "mfe" "kri" "la" "lv" "to" "lt" "ln" "loz" "lua" "lg" "hu" "mg" "mt" "mi" "ms" "pcm" "no" "nso" "ny" "nn" "uz" "oc" "om" "xx-pirate" "ro" "rm" "qu" "nyn" "crs" "sq" "sk" "sl" "so" "st" "sr-ME" "sr-Latn" "su" "fi" "sv" "tn" "tum" "tk" "tw" "wo" "el" "be" "bg" "ky" "kk" "mk" "mn" "sr" "tt" "tg" "uk" "ka" "hy" "yi" "iw" "ug" "ur" "ps" "sd" "fa" "ckb" "ti" "am" "ne" "mr"

"hi" "bn" "pa" "gu" "or" "ta" "te" "kn" "ml"
 "si" "lo" "my" "km" "chr"

The parameter specifies the language to use for website.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished.

Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

- **401** Wrong or missing API Key (token).
- **402** Past due invoices or a payment method not connected.
- **422** Wrong query url parameters.

GET /amazon/products

Request samples

cURL

cURL (async)

Python

Copy

```
curl -X GET "https://api.outscraper.cloud/amazon/products?query=https://www
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Email Related

Emails & Contacts

Allows finding email addresses, social links, and phones from domains.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Domain or link (e.g., `outscraper.com`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

preferredContacts

Array of strings

Items Enum: `"decision makers"` `"influencers"`

`"procurement/purchasing"` `"technical"` `"finance"`
`"operations"` `"marketing"` `"sales"` `"maintenance"` `"human resources"` `"legal and compliance"` `"supply chain/logistics"` `"education/training"`

Preferred contacts. It supports multiple categories (e.g.,

`preferredContacts=technical&preferredContacts=influencers`).

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished.

Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

- **401** Wrong or missing API Key (token).
- **402** Past due invoices or a payment method not connected.
- **422** Wrong query url parameters.

GET /emails-and-contacts

Request samples

[cURL](#) [cURL \(async\)](#) [Python](#) [Ruby](#) [PHP](#) [Node.js](#) [Go](#) [Java](#)

Copy

```
curl -X GET "https://api.outscraper.cloud/emails-and-contacts?query=outscraper"
```

Response samples

[200](#) [202](#) [401](#) [402](#) [422](#)

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + { ... }
  ]
}
```

Email Address Verifier

Allows to validate email addresses. Checks if emails are deliverable.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Email address (e.g., `support@outscraper.com`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

GET /email-validator

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/validators/email?query=support@ou
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + { ... }
  ]
}
```

Disposable Email Checker

Checks origins of email addresses (disposable, free, or corporate)

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query	Array of strings
required	Email address (e.g., support@outscraper.com). It supports batching by sending arrays with up to 250 queries (e.g., query=text1&query=text2&query=text3). It allows multiple queries to

be sent in one request and to save on network latency time.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /disposable-email-checker

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/disposable-email-checker?query=sv
```

Response samples

202

401

402

422

Content type
application/json

Copy

```
{
  "id": "your-request-id",
  "status": "Pending",
```

```
"results_location": "https://api.outscraper.cloud/requests/your-request"
}
```

Contacts Finder

Allows finding company contacts from domains.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings Domain or link (e.g., <code>outscraper.com</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limitPerCompany	integer Default: <code>5</code> The parameter specifies the limit of contacts to get.
preferredContacts	Array of strings Items Enum: <code>"decision makers"</code> <code>"influencers"</code> <code>"procurement/purchasing"</code> <code>"technical"</code> <code>"finance"</code> <code>"operations"</code> <code>"marketing"</code> <code>"sales"</code> <code>"maintenance"</code> <code>"human resources"</code> <code>"legal and compliance"</code> <code>"supply chain/logistics"</code> <code>"education/training"</code> Preferred contacts. It supports multiple categories (e.g., <code>preferredContacts=technical&preferredContacts=influencers</code>).
ignoreWithoutTitle	boolean Default: <code>"false"</code> The parameter allows to return contacts only with title.
ignoreWithoutLinkedin	boolean Default: <code>"false"</code> The parameter allows to return contacts only with LinkedIn.
webhook	string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished.
Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/contacts-finder`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/contacts-finder?query=outscraper."
```

Response samples

200

202

401

402

422

Content type
application/json

Copy



Email Addresses Finder

Finds professional emails by names.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Full name + company domain (e.g., `John Doe company.com`, `Dana outscraper.com`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /emails-finder

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/emails-finder?query=Dana%20outscri
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy

```
{ }
```

Phone Related

Phone Numbers Enricher

Returns phone carrier data (name/type), validates phones and ensures messages deliverability.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required

Array of strings
Phone number (e.g., +1 281 236 8208).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

Responses

— 200

The response contains the `status` of the request and `data` . Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /phones-enricher

Request samples

- cURL
- Python
- Ruby
- PHP
- Node.js
- Go
- Java

Copy

```
curl -X GET "https://api.outscraper.cloud/phones-enricher?query=12812368208"
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + { ... }
  ]
}
```

WhatsApp Checker

Checks whether a phone is connected to the service.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Phone number (e.g., `+1 281 236 8208`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /whatsapp-checker

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/whatsapp-checker?query=12812368208"
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + { ... }
  ]
}
```

Phone Identity Finder (Whitepages)

Returns insights about phone number owners (name, address, etc.).

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required Array of strings
Phone number (e.g., +1 281 236 8208).

It supports batching by sending arrays with up to **250** queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

Responses

— 200

The response contains the `status` of the request and `data` . Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for **2** hours after a request has been completed.

- 401 Wrong or missing API Key (token).
- 402 Past due invoices or a payment method not connected.
- 422 Wrong query url parameters.

GET /whitepages-phones

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/whitepages-phones?query=128123682"
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + { ... }
  ]
}
```

Phones Owners

Returns insights about phone number owners (name, address, etc.).

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Phone number (e.g., `+1 281 236 8208`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

GET /phones-owners

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/phones-owners?query=12812368208"
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + { ... }
  ]
}
```

Other Services

Geocoding

Translates human-readable addresses into locations on the map (latitude, longitude).

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Addresses specifying the location for which you want to get the coordinates (e.g., `321 California Ave, Palo Alto, CA 94306`, `Central Park, NY`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

Responses

— 200

The response contains the `status` of the request and `data` . Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /geocoding

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/geocoding?query=321%20California"
```

Response samples

200

202

401

402

422

Content type
application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + { ... }
  ]
}
```

Reverse Geocoding

Translate locations on the map into human-readable addresses.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

<code>query</code> <code>required</code>	Array of strings The latitude and longitude coordinates specifying the location for which you want the closest, human-readable address (e.g., <code>40.7624284 -73.973794</code> , <code>37.427074,-122.1439166</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
---	---

Responses

— 200

The response contains the `status` of the request and `data` . Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for

2

 hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /reverse-geocoding

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/reverse-geocoding?query=40.762428"
```

Response samples

200

202

401

402

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + { ... }
  ]
}
```

Company Insights

Finds company details such as revenue, size, founding year, public status, etc.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Domains or websites (e.g., `dominopark.com`, `https://www.esbnyc.com/`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

enrichment

Array of strings

The parameter defines an enrichment or enrichments (e.g.,

`enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3`) you want to apply to the results.

Available values:

`domains_service` — **Emails & Contacts Scraper**: finds emails, social links, phones, and other contacts from websites,

`emails_validator_service` — **Email Address Verifier**: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate,

`disposable_email_checker` — **Disposable Emails Checker**: checks origins of email addresses (disposable, free, or corporate),

`company_insights_service` — **Company Insights**: finds company details such as revenue, size, founding year, public status, etc,

`phones_enricher_service` — **Phone Numbers Enricher**: returns phones carrier data (name/type), validates phones, ensures messages deliverability,

`trustpilot_service` — **Trustpilot Scraper**: returns data from a list of businesses,

`whitepages_phones` - **Phone Identity Finder**: returns insights about phone number owners (name, address, etc.),

`ai_chain_info` - **Chain Info**: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting.

Using enrichments increases the time of the response. You might want to use the `async=true` parameter to avoid getting timeouts.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /company-insights

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/company-insights?query=apple.com&
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + { ... }
  ]
}
```

Universal AI-Powered Scraper

Extracts the data you need from any web page by using AI.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required

Array of strings
Links to web pages (e.g., `https://www.apple.com/iphone/`).
It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

attributes	Array of strings The parameter defines attributes to parse from a web page (e.g., <code>attributes=name,price,discount price,description</code>).
limit	integer Default: <code>1</code> The parameter specifies the limit of pages to return from one query.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/universal-scraper`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/universal-scraper?query=https://w
```

Response samples

200

202

401

402

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + { ... }
  ]
}
```


WebPage Screenshoter

Captures high-quality screenshots of any webpage simply by providing its URL

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query

required

Array of strings
Links to web pages (e.g., `https://www.apple.com/iphone/`).
It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

region

string (region)
Enum: "AF" "AL" "DZ" "AS" "AD" "AO" "AI" "AG" "AR" "AM" "AU" "AT" "AZ" "BS" "BH" "BD" "BY" "BE" "BZ" "BJ" "BT" "BO" "BA" "BW" "BR" "VG" "BN" "BG" "BF" "BI" "KH" "CM" "CA" "CV" "CF" "TD" "CL" "CN" "CO" "CG" "CD" "CK" "CR" "CI" "HR" "CU" "CY" "CZ" "DK" "DJ" "DM" "DO" "EC" "EG" "SV" "EE" "ET" "FJ" "FI" "FR" "GA" "GM" "GE" "DE" "GH" "GI" "GR" "GL" "GT" "GG" "GY" "HT" "HN" "HK" "HU" "IS" "IN" "ID" "IQ" "IE" "IM" "IL" "IT" "JM" "JP" "JE" "JO" "KZ" "KE" "KI" "KW" "KG" "LA" "LV" "LB" "LS" "LY" "LI" "LT" "LU" "MG" "MW" "MY" "MV" "ML" "MT" "MU" "MX" "FM" "MD" "MN" "ME" "MS" "MA" "MQ" "MZ" "MM" "NA" "NR" "NP" "NL" "NZ" "NI" "NE" "NG" "NU" "MK" "NO" "OM" "PK" "PS" "PA" "PG" "PY" "PE" "PH" "PN" "PL" "PT" "PR" "QA" "RO" "RU" "RW" "WS" "SM" "ST" "SA" "SN" "RS" "SC" "SL" "SG" "SK" "SI" "SB" "SO" "ZA" "KR" "ES" "LK" "SH" "VC" "SR" "SE" "CH" "TW" "TJ" "TZ" "TH" "TL" "TG" "TO" "TT" "TN" "TR" "TM" "VI" "UG" "UA" "AE" "GB" "US" "UY" "UZ" "VU" "VE" "VN" "ZM" "ZW"

The parameter specifies the country to use for the screenshot.

type

string
Default: "webp"
Enum: "webp" "png" "jpeg" "pdf"
The parameter specifies the image extension.

fullPage	boolean Default: <code>"false"</code> The parameter specifies whether to capture the full page. It overrides the viewport height.
width	integer Default: <code>1200</code> The parameter specifies the width of the viewport.
height	integer Default: <code>800</code> The parameter specifies the height of the viewport.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /screenshoter

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/screenshoter?query=https://www.ag
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + { ... }
  ]
}
```

Amazon

Amazon Products

Returns information about products on Amazon.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings You can use Amazon products, searches, or summary page URLs. It supports batching by sending arrays with up to 250 queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: 24 The parameter specifies the limit of products to get from one query (in case of using summary pages).

domain

string

Default: "amazon.com"

Enum: "amazon.com" "amazon.co.uk" "amazon.ca" "amazon.de" "amazon.es" "amazon.fr" "amazon.it" "amazon.in" "amazon.nl" "amazon.se" "amazon.sa" "amazon.com.mx" "amazon.com.br" "amazon.com.au" "amazon.co.jp" "amazon.pl" "amazon.ae"

The parameter specifies Amazon domain to use.

postal_code

string

Default: "11201"

The parameter specifies the postal code for delivery.

language

string (language)

Default: "en"

Enum: "en" "de" "es" "es-419" "fr" "hr" "it" "nl" "pl" "pt-BR" "pt-PT" "vi" "tr" "ru" "ar" "th" "ko" "zh-CN" "zh-TW" "ja" "ach" "af" "ak" "ig" "az" "ban" "ceb" "xx-bork" "bs" "br" "ca" "cs" "sn" "co" "cy" "da" "yo" "et" "xx-elmer" "eo" "eu" "ee" "tl" "fil" "fo" "fy" "gaa" "ga" "gd" "gl" "gn" "xx-hacker" "ht" "ha" "haw" "bem" "rn" "id" "ia" "xh" "zu" "is" "jw" "rw" "sw" "tlh" "kg" "mfe" "kri" "la" "lv" "to" "lt" "ln" "loz" "lua" "lg" "hu" "mg" "mt" "mi" "ms" "pcm" "no" "nso" "ny" "nn" "uz" "oc" "om" "xx-pirate" "ro" "rm" "qu" "nyn" "crs" "sq" "sk" "sl" "so" "st" "sr-ME" "sr-Latn" "su" "fi" "sv" "tn" "tum" "tk" "tw" "wo" "el" "be" "bg" "ky" "kk" "mk" "mn" "sr" "tt" "tg" "uk" "ka" "hy" "yi" "iw" "ug" "ur" "ps" "sd" "fa" "ckb" "ti" "am" "ne" "mr" "hi" "bn" "pa" "gu" "or" "ta" "te" "kn" "ml" "si" "lo" "my" "km" "chr"

The parameter specifies the language to use for website.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: "true"

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to

Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/amazon/products`

Request samples

- cURL
- cURL (async)
- Python

Copy

```
curl -X GET "https://api.outscraper.cloud/amazon/products?query=https://www
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Amazon Reviews

Returns product's reviews from Amazon.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings You can use URLs or ASINs from Amazon products (e.g., <code>https://www.amazon.com/dp/1612680194</code> , <code>1612680194</code> , etc.). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>10</code> The parameter specifies the limit of reviews to get from one query.

cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
filterByReviewer	string Default: <code>"all_reviews"</code> Enum: <code>"all_reviews"</code> <code>"avp_only_reviews"</code> The parameter specifies one of the reviewer filter types (All reviewers / Verified purchase only).
filterByReviewer	string Default: <code>"all_reviews"</code> Enum: <code>"all_reviews"</code> <code>"avp_only_reviews"</code> The parameter specifies one of the reviewer filter types (All reviewers / Verified purchase only). Works only for <code>amazon.com</code> , <code>amazon.ca</code> , <code>amazon.com.br</code> , <code>amazon.com.mx</code> .
filterByStar	string Default: <code>"all_stars"</code> Enum: <code>"all_stars"</code> <code>"five_star"</code> <code>"four_star"</code> <code>"three_star"</code> <code>"two_star"</code> <code>"one_star"</code> <code>"positive"</code> <code>"critical"</code> The parameter specifies one of the filter types by stars.
domain	string Default: <code>"amazon.com"</code> Enum: <code>"amazon.com"</code> <code>"amazon.co.uk"</code> <code>"amazon.ca"</code> <code>"amazon.de"</code> <code>"amazon.es"</code> <code>"amazon.fr"</code> <code>"amazon.it"</code> <code>"amazon.in"</code> <code>"amazon.nl"</code> <code>"amazon.se"</code> <code>"amazon.sa"</code> <code>"amazon.com.mx"</code> <code>"amazon.com.br"</code> <code>"amazon.com.au"</code> <code>"amazon.co.jp"</code> <code>"amazon.pl"</code> <code>"amazon.ae"</code> The parameter specifies Amazon domain to use.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3

	minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/amazon/reviews`

Request samples

- cURL
- cURL (async)
- Python

Copy

```
curl -X GET "https://api.outscraper.cloud/amazon/reviews?query=https://www.
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Booking

Booking Search

Returns search results from Booking.com

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings Search links with search parameters (e.g., <code>https://www.booking.com/searchresults.html?ss=Rome%2C+Lazio%2C+Italy</code>).
-------------------	--

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

`limit`

integer

Default: `100`

The parameter specifies the limit of items to get from one query.

`fields`

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

`async`

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

`ui`

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

`webhook`

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished.

Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for **2** hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /booking/search

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/booking-search?query=https%3A%2F%2F"
```

Response samples

200**202****401****402****422**

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Booking Reviews

Returns reviews from Booking.com hotels.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings You can use direct links, and IDs of any booking hotel (e.g., <code>https://www.booking.com/hotel/tr/old-town-point-amp-spa-antalya.html</code>, <code>old-town-point-amp-spa-antalya</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
skip	integer Default: <code>0</code> The parameter specifies the number of items to skip. It's commonly used in pagination.
sort	string Default: <code>" "</code> Enum: <code>"f_recent_desc"</code> <code>"f_recent_asc"</code> <code>"f_score_desc"</code> <code>"f_score_asc"</code> The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
language	string (language) Default: <code>"en"</code> Enum: <code>"en"</code> <code>"de"</code> <code>"es"</code> <code>"es-419"</code> <code>"fr"</code> <code>"hr"</code> <code>"it"</code> <code>"nl"</code> <code>"pl"</code> <code>"pt-BR"</code> <code>"pt-PT"</code> <code>"vi"</code> <code>"tr"</code> <code>"ru"</code> <code>"ar"</code> <code>"th"</code> <code>"ko"</code> <code>"zh-CN"</code> <code>"zh-TW"</code> <code>"ja"</code> <code>"ach"</code> <code>"af"</code> <code>"ak"</code> <code>"ig"</code> <code>"az"</code> <code>"ban"</code> <code>"ceb"</code> <code>"xx-bork"</code> <code>"bs"</code> <code>"br"</code> <code>"ca"</code> <code>"cs"</code> <code>"sn"</code> <code>"co"</code> <code>"cy"</code> <code>"da"</code> <code>"yo"</code> <code>"et"</code> <code>"xx-elmer"</code> <code>"eo"</code> <code>"eu"</code> <code>"ee"</code> <code>"tl"</code> <code>"fil"</code> <code>"fo"</code> <code>"fy"</code> <code>"gaa"</code> <code>"ga"</code> <code>"gd"</code> <code>"gl"</code> <code>"gn"</code> <code>"xx-hacker"</code> <code>"ht"</code> <code>"ha"</code> <code>"haw"</code> <code>"bem"</code> <code>"rn"</code> <code>"id"</code> <code>"ia"</code> <code>"xh"</code> <code>"zu"</code> <code>"is"</code> <code>"jw"</code> <code>"rw"</code> <code>"sw"</code> <code>"tlh"</code> <code>"kg"</code> <code>"mfe"</code> <code>"kri"</code> <code>"la"</code> <code>"lv"</code> <code>"to"</code> <code>"lt"</code> <code>"ln"</code> <code>"loz"</code> <code>"lua"</code> <code>"lg"</code> <code>"hu"</code> <code>"mg"</code> <code>"mt"</code> <code>"mi"</code> <code>"ms"</code> <code>"pcm"</code> <code>"no"</code> <code>"nso"</code> <code>"ny"</code> <code>"nn"</code> <code>"uz"</code> <code>"oc"</code> <code>"om"</code> <code>"xx-pirate"</code> <code>"ro"</code> <code>"rm"</code> <code>"qu"</code> <code>"nyn"</code> <code>"crs"</code> <code>"sq"</code> <code>"sk"</code> <code>"sl"</code> <code>"so"</code> <code>"st"</code>

"sr-ME"	"sr-Latn"	"su"	"fi"	"sv"	"tn"	"tum"	"tk"	
"tw"	"wo"	"el"	"be"	"bg"	"ky"	"kk"	"mk"	"mn"
"sr"	"tt"	"tg"	"uk"	"ka"	"hy"	"yi"	"iw"	"ug"
"ur"	"ps"	"sd"	"fa"	"ckb"	"ti"	"am"	"ne"	"mr"
"hi"	"bn"	"pa"	"gu"	"or"	"ta"	"te"	"kn"	"ml"
"si"	"lo"	"my"	"km"	"chr"				

The parameter specifies the language to use for website.

region

string (region)

Enum:	"AF"	"AL"	"DZ"	"AS"	"AD"	"AO"	"AI"	"AG"	"AR"
	"AM"	"AU"	"AT"	"AZ"	"BS"	"BH"	"BD"	"BY"	"BE"
	"BZ"	"BJ"	"BT"	"BO"	"BA"	"BW"	"BR"	"VG"	"BN"
	"BG"	"BF"	"BI"	"KH"	"CM"	"CA"	"CV"	"CF"	"TD"
	"CL"	"CN"	"CO"	"CG"	"CD"	"CK"	"CR"	"CI"	"HR"
	"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
	"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
	"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
	"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
	"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
	"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
	"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
	"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
	"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
	"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
	"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
	"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
	"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
	"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
	"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
	"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
	"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the

	Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/booking/reviews`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/booking/reviews?query=https://www
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Booking Prices

Returns prices from a list of hotels.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings You can use direct links, and IDs of any booking hotel (e.g., <code>https://www.booking.com/hotel/tr/old-town-point-amp-spa-antalya.html</code> , <code>old-town-point-amp-spa-antalya</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

	<code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

GET /booking/prices

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/booking/prices?query=https://www.
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy

```
{ }
```

Capterra

Capterra Reviews

Returns reviews from Capterra.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required Array of strings

Links to Capterra product pages (e.g., <https://www.capterra.com/p/228041/Google-Maps-scraper/>).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
sort	string Default: <code>"MOST_HELPFUL"</code> Enum: <code>"MOST_HELPFUL"</code> <code>"MOST_RECENT"</code> <code>"HIGHEST_RATING"</code> <code>"LOWEST_RATING"</code> The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
language	string (language) Default: <code>"en"</code> Enum: <code>"en"</code> <code>"de"</code> <code>"es"</code> <code>"es-419"</code> <code>"fr"</code> <code>"hr"</code> <code>"it"</code> <code>"nl"</code> <code>"pl"</code> <code>"pt-BR"</code> <code>"pt-PT"</code> <code>"vi"</code> <code>"tr"</code> <code>"ru"</code> <code>"ar"</code> <code>"th"</code> <code>"ko"</code> <code>"zh-CN"</code> <code>"zh-TW"</code> <code>"ja"</code> <code>"ach"</code> <code>"af"</code> <code>"ak"</code> <code>"ig"</code> <code>"az"</code> <code>"ban"</code> <code>"ceb"</code> <code>"xx-bork"</code> <code>"bs"</code> <code>"br"</code> <code>"ca"</code> <code>"cs"</code> <code>"sn"</code> <code>"co"</code> <code>"cy"</code> <code>"da"</code> <code>"yo"</code> <code>"et"</code> <code>"xx-elmer"</code> <code>"eo"</code> <code>"eu"</code> <code>"ee"</code> <code>"tl"</code> <code>"fil"</code> <code>"fo"</code> <code>"fy"</code> <code>"gaa"</code> <code>"ga"</code> <code>"gd"</code> <code>"gl"</code> <code>"gn"</code> <code>"xx-hacker"</code> <code>"ht"</code> <code>"ha"</code> <code>"haw"</code> <code>"bem"</code> <code>"rn"</code> <code>"id"</code> <code>"ia"</code> <code>"xh"</code> <code>"zu"</code> <code>"is"</code> <code>"jw"</code> <code>"rw"</code> <code>"sw"</code> <code>"tlh"</code> <code>"kg"</code> <code>"mfe"</code> <code>"kri"</code> <code>"la"</code> <code>"lv"</code> <code>"to"</code> <code>"lt"</code> <code>"ln"</code> <code>"loz"</code> <code>"lua"</code> <code>"lg"</code> <code>"hu"</code> <code>"mg"</code> <code>"mt"</code> <code>"mi"</code> <code>"ms"</code> <code>"pcm"</code> <code>"no"</code> <code>"nso"</code> <code>"ny"</code> <code>"nn"</code> <code>"uz"</code> <code>"oc"</code> <code>"om"</code> <code>"xx-pirate"</code> <code>"ro"</code> <code>"rm"</code> <code>"qu"</code> <code>"nyn"</code> <code>"crs"</code> <code>"sq"</code> <code>"sk"</code> <code>"sl"</code> <code>"so"</code> <code>"st"</code> <code>"sr-ME"</code> <code>"sr-Latn"</code> <code>"su"</code> <code>"fi"</code> <code>"sv"</code> <code>"tn"</code> <code>"tum"</code> <code>"tk"</code> <code>"tw"</code> <code>"wo"</code> <code>"el"</code> <code>"be"</code> <code>"bg"</code> <code>"ky"</code> <code>"kk"</code> <code>"mk"</code> <code>"mn"</code> <code>"sr"</code> <code>"tt"</code> <code>"tg"</code> <code>"uk"</code> <code>"ka"</code> <code>"hy"</code> <code>"yi"</code> <code>"iw"</code> <code>"ug"</code> <code>"ur"</code> <code>"ps"</code> <code>"sd"</code> <code>"fa"</code> <code>"ckb"</code> <code>"ti"</code> <code>"am"</code> <code>"ne"</code> <code>"mr"</code> <code>"hi"</code> <code>"bn"</code> <code>"pa"</code> <code>"gu"</code> <code>"or"</code> <code>"ta"</code> <code>"te"</code> <code>"kn"</code> <code>"ml"</code> <code>"si"</code> <code>"lo"</code> <code>"my"</code> <code>"km"</code> <code>"chr"</code> The parameter specifies the language to use for website.
region	string (region) Enum: <code>"AF"</code> <code>"AL"</code> <code>"DZ"</code> <code>"AS"</code> <code>"AD"</code> <code>"AO"</code> <code>"AI"</code> <code>"AG"</code> <code>"AR"</code> <code>"AM"</code> <code>"AU"</code> <code>"AT"</code> <code>"AZ"</code> <code>"BS"</code> <code>"BH"</code> <code>"BD"</code> <code>"BY"</code> <code>"BE"</code>

"BZ"	"BJ"	"BT"	"BO"	"BA"	"BW"	"BR"	"VG"	"BN"
"BG"	"BF"	"BI"	"KH"	"CM"	"CA"	"CV"	"CF"	"TD"
"CL"	"CN"	"CO"	"CG"	"CD"	"CK"	"CR"	"CI"	"HR"
"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string
The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

- 401 Wrong or missing API Key (token).
- 402 Past due invoices or a payment method not connected.
- 422 Wrong query url parameters.

GET /capterra-reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/capterra-reviews?query=https://w
```

Response samples

200

202

401

402

422

Content type
application/json

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Google

Google Places v3 (speed optimized)

Returns places from Google Maps based on a given search query (or many queries).

The results from searches are the same as you would see by visiting a regular [Google Maps](#) site.

However, in most cases, it's important to use locations inside queries (e.g., `bars, NY, USA`) as the IP addresses of Outscraper's servers might be located in different countries.

In case no places were found by your search criteria, your search request will consume the usage of one place.

This endpoint is optimized for fast responses and can be used as a real-time API. Set the `limit` parameter to `10` to achieve the maximum response speed.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

`query`
required

Array of strings

The parameter defines the query you want to search. You can use anything that you would use on a regular Google Maps site. Additionally, you can use `google_id` (feature_id), `place_id`, or `CID`. The example of valid queries: `Real estate agency, Rome, Italy`, `The NoMad Restaurant, NY, USA`, `restaurants, Brooklyn 11203`, `0x886916e8bc273979:0x5141fcb11460b226`, `ChIJrZhup4lZwokRUr_5sLoFlDw`, etc.

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and save on network latency time.

You might want to check out [the web application](#) to play with locations and categories that we would suggest.

limit

integer

Default: `500`

The parameter specifies the limit of organizations to take from one query search.

There are no more than 500 places per one query search on Google Maps. For densely populated areas you might want to split your query into subqueries in order to get all the places inside. (e.g., `restaurants, Brooklyn 11211`, `restaurants, Brooklyn 11215`).

dropDuplicates

boolean

Default: `"false"`

The parameter specifies whether the bot will drop the same organizations from different queries. It makes sense when you use batching and send multiple queries inside one request.

Using the parameter combines results from each query inside one big array (`{'data': [...]}` instead of `{'data': [[...], [...], [...]]}`).

If the amount of ignored rows are less than 5,000% of what was actually extracted, you won't be billed for ignored records.

coordinates

string

The parameter defines the coordinates of the location where you want your query to be applied.

It has to be constructed in the next sequence: `latitude` + `,` + `longitude` (`41.3954381,2.1628662`). Often, you can find this value while visiting [Google Maps](#).

skipPlaces

integer

Default: `0`

Skip first N places, where N should be multiple to 20 (e.g. 0, 20, 40). It's commonly used in pagination.

language

string (language)

Default: `"en"`

Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"` `"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"` `"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"` `"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"` `"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"` `"eu"` `"ee"` `"tl"` `"fil"` `"fo"` `"fy"` `"gaa"` `"ga"` `"gd"` `"gl"` `"gn"` `"xx-hacker"` `"ht"` `"ha"` `"haw"` `"bem"` `"rn"` `"id"` `"ia"` `"xh"` `"zu"` `"is"` `"jw"` `"rw"` `"sw"` `"tlh"` `"kg"` `"mfe"` `"kri"` `"la"` `"lv"` `"to"` `"lt"` `"ln"` `"loz"`

"lua"	"lg"	"hu"	"mg"	"mt"	"mi"	"ms"	"pcm"	"no"
"nso"	"ny"	"nn"	"uz"	"oc"	"om"	"xx-pirate"	"ro"	
"rm"	"qu"	"nyn"	"crs"	"sq"	"sk"	"sl"	"so"	"st"
"sr-ME"	"sr-Latn"	"su"	"fi"	"sv"	"tn"	"tum"	"tk"	
"tw"	"wo"	"el"	"be"	"bg"	"ky"	"kk"	"mk"	"mn"
"sr"	"tt"	"tg"	"uk"	"ka"	"hy"	"yi"	"iw"	"ug"
"ur"	"ps"	"sd"	"fa"	"ckb"	"ti"	"am"	"ne"	"mr"
"hi"	"bn"	"pa"	"gu"	"or"	"ta"	"te"	"kn"	"ml"
"si"	"lo"	"my"	"km"	"chr"				

The parameter specifies the language to use for website.

region

string (region)

Enum:	"AF"	"AL"	"DZ"	"AS"	"AD"	"AO"	"AI"	"AG"	"AR"
	"AM"	"AU"	"AT"	"AZ"	"BS"	"BH"	"BD"	"BY"	"BE"
	"BZ"	"BJ"	"BT"	"BO"	"BA"	"BW"	"BR"	"VG"	"BN"
	"BG"	"BF"	"BI"	"KH"	"CM"	"CA"	"CV"	"CF"	"TD"
	"CL"	"CN"	"CO"	"CG"	"CD"	"CK"	"CR"	"CI"	"HR"
	"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
	"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
	"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
	"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
	"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
	"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
	"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
	"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
	"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
	"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
	"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
	"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
	"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
	"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
	"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
	"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
	"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

enrichment

Array of strings

The parameter defines an enrichment or enrichments (e.g.,

`enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3`) you want to apply to the results.

Available values:

`domains_service` — **Emails & Contacts Scraper**: finds emails, social links, phones, and other contacts from websites,

`emails_validator_service` — **Email Address Verifier**: validates emails, checks deliverability, filters out blacklists, spam traps, and

complainers, while significantly reducing your bounce rate,

`disposable_email_checker` — **Disposable Emails Checker**: checks origins of email addresses (disposable, free, or corporate),

`company_insights_service` — **Company Insights**: finds company details such as revenue, size, founding year, public status, etc,

`phones_enricher_service` — **Phone Numbers Enricher**: returns phones carrier data (name/type), validates phones, ensures messages deliverability,

`trustpilot_service` — **Trustpilot Scraper**: returns data from a list of businesses,

`whitepages_phones` - **Phone Identity Finder**: returns insights about phone number owners (name, address, etc.),

`ai_chain_info` - **Chain Info**: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting.

Using enrichments increases the time of the response. You might want to use the `async=true` parameter to avoid getting timeouts.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished.

Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /maps/search-v3

Request samples

- cURL
- cURL (async)
- Python
- Ruby
- PHP
- Node.js
- Go
- Java

Copy

```
curl -X GET "https://api.outscraper.cloud/maps/search-v3?query=restaurants"
```

Response samples

- 200
- 202
- 204
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
```

```
- "data": [  
  + [ ... ]  
]  
}
```

Google Places v3 (bigger payload capabilities)

Returns places from Google Maps based on a given search query (or many queries).

The results from searches are the same as you would see by visiting a regular [Google Maps](#) site.

However, in most cases, it's important to use locations inside queries (e.g., `bars, NY, USA`) as the IP addresses of Outscraper's servers might be located in different countries.

In case no places were found by your search criteria, your search request will consume the usage of one place.

This endpoint is optimized for fast responses and can be used as a real-time API. Set the `limit` parameter to `10` to achieve the maximum response speed.

The POST endpoint is identical to GET and made to support a bigger payload, such as when sending a large number of queries.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

`query`
required

Array of strings

The parameter defines the query you want to search. You can use anything that you would use on a regular Google Maps site. Additionally, you can use `google_id` (feature_id), `place_id`, or `CID`. The example of valid queries: `Real estate agency, Rome, Italy`, `The NoMad Restaurant, NY, USA`, `restaurants, Brooklyn 11203`, `0x886916e8bc273979:0x5141fcb11460b226`, `ChIJrZhup41ZwokRur_5sLoF1Dw`, etc.

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and save on network latency time.

You might want to check out [the web application](#) to play with locations and categories that we would suggest.

`limit`

integer

Default: `500`

The parameter specifies the limit of organizations to take from one query search.

There are no more than 500 places per one query search on Google Maps. For densely populated areas you might want to split your query into subqueries in order to get all the places inside. (e.g., `restaurants, Brooklyn 11211`, `restaurants, Brooklyn 11215`).

dropDuplicates

boolean

Default: `"false"`

The parameter specifies whether the bot will drop the same organizations from different queries. It makes sense when you use batching and send multiple queries inside one request.

Using the parameter combines results from each query inside one big array (`{'data': [...]}`) instead of `{'data': [...], [...], [...]}`).

If the amount of ignored rows are less than 5,000% of what was actually extracted, you won't be billed for ignored records.

coordinates

string

The parameter defines the coordinates of the location where you want your query to be applied.

It has to be constructed in the next sequence: `latitude` + `,` + `longitude` (`41.3954381,2.1628662`). Often, you can find this value while visiting [Google Maps](#).

skipPlaces

integer

Default: `0`

Skip first N places, where N should be multiple to 20 (e.g. 0, 20, 40). It's commonly used in pagination.

language

string (language)

Default: `"en"`

Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"` `"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"` `"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"` `"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"` `"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"` `"eu"` `"ee"` `"tl"` `"fil"` `"fo"` `"fy"` `"gaa"` `"ga"` `"gd"` `"gl"` `"gn"` `"xx-hacker"` `"ht"` `"ha"` `"haw"` `"bem"` `"rn"` `"id"` `"ia"` `"xh"` `"zu"` `"is"` `"jw"` `"rw"` `"sw"` `"tlh"` `"kg"` `"mfe"` `"kri"` `"la"` `"lv"` `"to"` `"lt"` `"ln"` `"loz"` `"lua"` `"lg"` `"hu"` `"mg"` `"mt"` `"mi"` `"ms"` `"pcm"` `"no"` `"nso"` `"ny"` `"nn"` `"uz"` `"oc"` `"om"` `"xx-pirate"` `"ro"` `"rm"` `"qu"` `"nyn"` `"crs"` `"sq"` `"sk"` `"sl"` `"so"` `"st"` `"sr-ME"` `"sr-Latn"` `"su"` `"fi"` `"sv"` `"tn"` `"tum"` `"tk"` `"tw"` `"wo"` `"el"` `"be"` `"bg"` `"ky"` `"kk"` `"mk"` `"mn"` `"sr"` `"tt"` `"tg"` `"uk"` `"ka"` `"hy"` `"yi"` `"iw"` `"ug"` `"ur"` `"ps"` `"sd"` `"fa"` `"ckb"` `"ti"` `"am"` `"ne"` `"mr"`

"hi" "bn" "pa" "gu" "or" "ta" "te" "kn" "ml"

"si" "lo" "my" "km" "chr"

The parameter specifies the language to use for website.

region

string (region)

Enum: "AF" "AL" "DZ" "AS" "AD" "AO" "AI" "AG" "AR"

"AM" "AU" "AT" "AZ" "BS" "BH" "BD" "BY" "BE"

"BZ" "BJ" "BT" "BO" "BA" "BW" "BR" "VG" "BN"

"BG" "BF" "BI" "KH" "CM" "CA" "CV" "CF" "TD"

"CL" "CN" "CO" "CG" "CD" "CK" "CR" "CI" "HR"

"CU" "CY" "CZ" "DK" "DJ" "DM" "DO" "EC" "EG"

"SV" "EE" "ET" "FJ" "FI" "FR" "GA" "GM" "GE"

"DE" "GH" "GI" "GR" "GL" "GT" "GG" "GY" "HT"

"HN" "HK" "HU" "IS" "IN" "ID" "IQ" "IE" "IM"

"IL" "IT" "JM" "JP" "JE" "JO" "KZ" "KE" "KI"

"KW" "KG" "LA" "LV" "LB" "LS" "LY" "LI" "LT"

"LU" "MG" "MW" "MY" "MV" "ML" "MT" "MU" "MX"

"FM" "MD" "MN" "ME" "MS" "MA" "MQ" "MZ" "MM"

"NA" "NR" "NP" "NL" "NZ" "NI" "NE" "NG" "NU"

"MK" "NO" "OM" "PK" "PS" "PA" "PG" "PY" "PE"

"PH" "PN" "PL" "PT" "PR" "QA" "RO" "RU" "RW"

"WS" "SM" "ST" "SA" "SN" "RS" "SC" "SL" "SG"

"SK" "SI" "SB" "SO" "ZA" "KR" "ES" "LK" "SH"

"VC" "SR" "SE" "CH" "TW" "TJ" "TZ" "TH" "TL"

"TG" "TO" "TT" "TN" "TR" "TM" "VI" "UG" "UA"

"AE" "GB" "US" "UY" "UZ" "VU" "VE" "VN" "ZM"

"ZW"

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

enrichment

Array of strings

The parameter defines an enrichment or enrichments (e.g., `enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3`) you want to apply to the results.

Available values:

domains_service — **Emails & Contacts Scraper:** finds emails, social links, phones, and other contacts from websites,

emails_validator_service — **Email Address Verifier:** validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate,

disposable_email_checker — **Disposable Emails Checker:** checks origins of email addresses (disposable, free, or corporate),

company_insights_service — **Company Insights:** finds company details such as revenue, size, founding year, public status, etc,

phones_enricher_service — **Phone Numbers Enricher:** returns phones carrier data (name/type), validates phones, ensures messages

	deliverability, <code>trustpilot_service</code> — Trustpilot Scraper: returns data from a list of businesses, <code>whitepages_phones</code> - Phone Identity Finder: returns insights about phone number owners (name, address, etc.), <code>ai_chain_info</code> - Chain Info: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting. Using enrichments increases the time of the response. You might want to use the <code>async=true</code> parameter to avoid getting timeouts.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

POST `/maps/search-v3`

Request samples

[cURL](#)[cURL \(async\)](#)[Copy](#)

```
curl -X POST https://api.outscraper.cloud/maps/search-v3 -d '{"query": ["re
```

Response samples

[200](#)[202](#)[204](#)[401](#)[402](#)[422](#)

Content type

application/json

[Copy](#)[Expand all](#)[Collapse all](#)

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + [ ... ]
  ]
}
```

Google Places v1 (deprecated)

Returns places from Google Maps based on a given search query (or many queries).
The results from searches are the same as you would see by visiting a regular [Google Maps](#) site.
However, in most cases, it's recommended to use locations inside queries (e.g., `bars, NY, USA`) as the IP addresses of Outscraper's servers might be located in different countries.
In case no places were found by your search criteria, your search request will consume the usage of one place.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings The parameter defines the query you want to search. You can use anything that you would use on a regular Google Maps site. Additionally, you can use <code>google_id</code> (feature_id), <code>place_id</code>, <code>CID</code> or urls to Google Maps places. The example of valid queries: <code>Real estate agency, Rome, Italy</code>, <code>The NoMad Restaurant, NY, USA</code>, <code>restaurants, Brooklyn 11203</code>, <code>0x886916e8bc273979:0x5141fcb11460b226</code>, <code>ChIJu7bMNFV-54gR-lrHScvPRX4</code>, <code>https://www.google.com/maps/search/restaurants+near+New+York,+NY</code>, etc. It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and save on network latency time. You might want to check out the web application to play with locations and categories that we would suggest.
limit	integer Default: <code>500</code> The parameter specifies the limit of organizations to take from one query search. There are no more than 500 places per one query search on Google Maps. For densely populated areas you might want to split your query into subqueries in order to get all the places inside. (e.g., <code>restaurants, Brooklyn 11211</code>, <code>restaurants, Brooklyn 11215</code>).
dropDuplicates	boolean Default: <code>"false"</code> The parameter specifies whether the bot will drop the same organizations from different queries. It makes sense when you use batching and send

multiple queries inside one request.

Using the parameter combines results from each query inside one big array (`{'data': [...]}` instead of `{'data': [...], [...], [...]}`).

If the amount of ignored rows are less than 5,000% of what was actually extracted, you won't be billed for ignored records.

coordinates

string

The parameter defines the coordinates of the location where you want your query to be applied.

It has to be constructed in the next sequence: `@` + `latitude` + `,` + `longitude` + `,` + `zoom` (`@41.3954381,2.1628662,15.1z`). Often, you can find this value while visiting [Google Maps](#).

language

string (language)

Default: `"en"`

Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"`
`"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"`
`"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"`
`"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"`
`"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"`
`"eu"` `"ee"` `"tl"` `"fil"` `"fo"` `"fy"` `"gaa"` `"ga"` `"gd"`
`"gl"` `"gn"` `"xx-hacker"` `"ht"` `"ha"` `"haw"` `"bem"` `"rn"`
`"id"` `"ia"` `"xh"` `"zu"` `"is"` `"jw"` `"rw"` `"sw"` `"tlh"`
`"kg"` `"mfe"` `"kri"` `"la"` `"lv"` `"to"` `"lt"` `"ln"` `"loz"`
`"lua"` `"lg"` `"hu"` `"mg"` `"mt"` `"mi"` `"ms"` `"pcm"` `"no"`
`"nso"` `"ny"` `"nn"` `"uz"` `"oc"` `"om"` `"xx-pirate"` `"ro"`
`"rm"` `"qu"` `"nyn"` `"crs"` `"sq"` `"sk"` `"sl"` `"so"` `"st"`
`"sr-ME"` `"sr-Latn"` `"su"` `"fi"` `"sv"` `"tn"` `"tum"` `"tk"`
`"tw"` `"wo"` `"el"` `"be"` `"bg"` `"ky"` `"kk"` `"mk"` `"mn"`
`"sr"` `"tt"` `"tg"` `"uk"` `"ka"` `"hy"` `"yi"` `"iw"` `"ug"`
`"ur"` `"ps"` `"sd"` `"fa"` `"ckb"` `"ti"` `"am"` `"ne"` `"mr"`
`"hi"` `"bn"` `"pa"` `"gu"` `"or"` `"ta"` `"te"` `"kn"` `"ml"`
`"si"` `"lo"` `"my"` `"km"` `"chr"`

The parameter specifies the language to use for website.

region

string (region)

Enum: `"AF"` `"AL"` `"DZ"` `"AS"` `"AD"` `"AO"` `"AI"` `"AG"` `"AR"`
`"AM"` `"AU"` `"AT"` `"AZ"` `"BS"` `"BH"` `"BD"` `"BY"` `"BE"`
`"BZ"` `"BJ"` `"BT"` `"BO"` `"BA"` `"BW"` `"BR"` `"VG"` `"BN"`
`"BG"` `"BF"` `"BI"` `"KH"` `"CM"` `"CA"` `"CV"` `"CF"` `"TD"`
`"CL"` `"CN"` `"CO"` `"CG"` `"CD"` `"CK"` `"CR"` `"CI"` `"HR"`
`"CU"` `"CY"` `"CZ"` `"DK"` `"DJ"` `"DM"` `"DO"` `"EC"` `"EG"`
`"SV"` `"EE"` `"ET"` `"FJ"` `"FI"` `"FR"` `"GA"` `"GM"` `"GE"`
`"DE"` `"GH"` `"GI"` `"GR"` `"GL"` `"GT"` `"GG"` `"GY"` `"HT"`
`"HN"` `"HK"` `"HU"` `"IS"` `"IN"` `"ID"` `"IQ"` `"IE"` `"IM"`

"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

enrichment

Array of strings

The parameter defines an enrichment or enrichments (e.g.,

`enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3`) you want to apply to the results.

Available values:

`domains_service` — **Emails & Contacts Scraper**: finds emails, social links, phones, and other contacts from websites,

`emails_validator_service` — **Email Address Verifier**: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate,

`disposable_email_checker` — **Disposable Emails Checker**: checks origins of email addresses (disposable, free, or corporate),

`company_insights_service` — **Company Insights**: finds company details such as revenue, size, founding year, public status, etc,

`phones_enricher_service` — **Phone Numbers Enricher**: returns phones carrier data (name/type), validates phones, ensures messages deliverability,

`trustpilot_service` — **Trustpilot Scraper**: returns data from a list of businesses,

`whitepages_phones` - **Phone Identity Finder**: returns insights about phone number owners (name, address, etc.),

`ai_chain_info` - **Chain Info**: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting.

Using enrichments increases the time of the response. You might want to use the `async=true` parameter to avoid getting timeouts.

fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

- **401** Wrong or missing API Key (token).
- **402** Past due invoices or a payment method not connected.
- **422** Wrong query url parameters.

GET /maps/search

Request samples

[cURL](#)[cURL \(async\)](#)[Python](#)[PHP](#)[Copy](#)

```
curl -X GET "https://api.outscraper.cloud/maps/search?query=restaurants%2C%26"
```

Response samples

[200](#)[202](#)[204](#)[401](#)[402](#)[422](#)

Content type

application/json

[Copy](#)[Expand all](#)[Collapse all](#)

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Google Maps (Places) by Domain

Allows finding places by domains.

In case no places were found by your criteria, your search request will consume the usage of one place.

QUERY PARAMETERS

query
required

Array of strings
Domains or websites (e.g., `dominopark.com`, `https://www.esbnyc.com/`).
It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

perQuery

integer
Default: `100`
The parameter specifies the limit of items to return from one query.

region

string (region)
Enum: `"AF"` `"AL"` `"DZ"` `"AS"` `"AD"` `"AO"` `"AI"` `"AG"` `"AR"`
`"AM"` `"AU"` `"AT"` `"AZ"` `"BS"` `"BH"` `"BD"` `"BY"` `"BE"`
`"BZ"` `"BJ"` `"BT"` `"BO"` `"BA"` `"BW"` `"BR"` `"VG"` `"BN"`
`"BG"` `"BF"` `"BI"` `"KH"` `"CM"` `"CA"` `"CV"` `"CF"` `"TD"`
`"CL"` `"CN"` `"CO"` `"CG"` `"CD"` `"CK"` `"CR"` `"CI"` `"HR"`
`"CU"` `"CY"` `"CZ"` `"DK"` `"DJ"` `"DM"` `"DO"` `"EC"` `"EG"`
`"SV"` `"EE"` `"ET"` `"FJ"` `"FI"` `"FR"` `"GA"` `"GM"` `"GE"`
`"DE"` `"GH"` `"GI"` `"GR"` `"GL"` `"GT"` `"GG"` `"GY"` `"HT"`
`"HN"` `"HK"` `"HU"` `"IS"` `"IN"` `"ID"` `"IQ"` `"IE"` `"IM"`
`"IL"` `"IT"` `"JM"` `"JP"` `"JE"` `"JO"` `"KZ"` `"KE"` `"KI"`
`"KW"` `"KG"` `"LA"` `"LV"` `"LB"` `"LS"` `"LY"` `"LI"` `"LT"`
`"LU"` `"MG"` `"MW"` `"MY"` `"MV"` `"ML"` `"MT"` `"MU"` `"MX"`
`"FM"` `"MD"` `"MN"` `"ME"` `"MS"` `"MA"` `"MQ"` `"MZ"` `"MM"`
`"NA"` `"NR"` `"NP"` `"NL"` `"NZ"` `"NI"` `"NE"` `"NG"` `"NU"`
`"MK"` `"NO"` `"OM"` `"PK"` `"PS"` `"PA"` `"PG"` `"PY"` `"PE"`
`"PH"` `"PN"` `"PL"` `"PT"` `"PR"` `"QA"` `"RO"` `"RU"` `"RW"`
`"WS"` `"SM"` `"ST"` `"SA"` `"SN"` `"RS"` `"SC"` `"SL"` `"SG"`
`"SK"` `"SI"` `"SB"` `"SO"` `"ZA"` `"KR"` `"ES"` `"LK"` `"SH"`
`"VC"` `"SR"` `"SE"` `"CH"` `"TW"` `"TJ"` `"TZ"` `"TH"` `"TL"`
`"TG"` `"TO"` `"TT"` `"TN"` `"TR"` `"TM"` `"VI"` `"UG"` `"UA"`
`"AE"` `"GB"` `"US"` `"UY"` `"UZ"` `"VU"` `"VE"` `"VN"` `"ZM"`
`"ZW"`
The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string
The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /google-places-by-domain

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/google-places-by-domain?query=don
```

Response samples

- 200
- 202
- 204
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    { }
  ]
}
```

Google Directory Places (beta)

Returns Google Maps places located in a parent place (mall, food court, etc.)

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required

Array of strings

The parameter defines the query you want to search. You can use anything that you would use on a regular Google Maps site. Additionally, you can use `google_id` (feature_id), `place_id`, `CID` or urls to Google Maps places. The example of valid queries: `Real estate agency, Rome, Italy`, `The NoMad Restaurant, NY, USA`, `restaurants, Brooklyn 11203`, `0x886916e8bc273979:0x5141fcb11460b226`, `ChIJu7bMNFV-54gR-lrHScvPRX4`, `https://www.google.com/maps/search/restaurants+near+New+York,+NY`, etc.

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and save on network latency time.

You might want to check out [the web application](#) to play with locations and categories that we would suggest.

perQuery

integer
Default: `100`
The parameter specifies the limit of places to get from one parent place (mall, food court, etc.).

coordinates

string
The parameter defines the coordinates of the location where you want your query to be applied.
It has to be constructed in the next sequence: `@` + `latitude` + `,` + `longitude` + `,` + `zoom` (`@41.3954381,2.1628662,15.1z`). Often, you can find this value while visiting [Google Maps](#).

language

string (language)
Default: `"en"`
Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"` `"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"` `"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"` `"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"` `"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"` `"eu"` `"ee"` `"tl"` `"fil"` `"fo"` `"fy"` `"gaa"` `"ga"` `"gd"` `"gl"` `"gn"` `"xx-hacker"` `"ht"` `"ha"` `"haw"` `"bem"` `"rn"` `"id"` `"ia"` `"xh"` `"zu"` `"is"` `"jw"` `"rw"` `"sw"` `"tlh"` `"kg"` `"mfe"` `"kri"` `"la"` `"lv"` `"to"` `"lt"` `"ln"` `"loz"` `"lua"` `"lg"` `"hu"` `"mg"` `"mt"` `"mi"` `"ms"` `"pcm"` `"no"` `"nso"` `"ny"` `"nn"` `"uz"` `"oc"` `"om"` `"xx-pirate"` `"ro"` `"rm"` `"qu"` `"nyn"` `"crs"` `"sq"` `"sk"` `"sl"` `"so"` `"st"` `"sr-ME"` `"sr-Latn"` `"su"` `"fi"` `"sv"` `"tn"` `"tum"` `"tk"` `"tw"` `"wo"` `"el"` `"be"` `"bg"` `"ky"` `"kk"` `"mk"` `"mn"` `"sr"` `"tt"` `"tg"` `"uk"` `"ka"` `"hy"` `"yi"` `"iw"` `"ug"` `"ur"` `"ps"` `"sd"` `"fa"` `"ckb"` `"ti"` `"am"` `"ne"` `"mr"`

"hi" "bn" "pa" "gu" "or" "ta" "te" "kn" "ml"

"si" "lo" "my" "km" "chr"

The parameter specifies the language to use for website.

region

string (region)

Enum: "AF" "AL" "DZ" "AS" "AD" "AO" "AI" "AG" "AR"

"AM" "AU" "AT" "AZ" "BS" "BH" "BD" "BY" "BE"

"BZ" "BJ" "BT" "BO" "BA" "BW" "BR" "VG" "BN"

"BG" "BF" "BI" "KH" "CM" "CA" "CV" "CF" "TD"

"CL" "CN" "CO" "CG" "CD" "CK" "CR" "CI" "HR"

"CU" "CY" "CZ" "DK" "DJ" "DM" "DO" "EC" "EG"

"SV" "EE" "ET" "FJ" "FI" "FR" "GA" "GM" "GE"

"DE" "GH" "GI" "GR" "GL" "GT" "GG" "GY" "HT"

"HN" "HK" "HU" "IS" "IN" "ID" "IQ" "IE" "IM"

"IL" "IT" "JM" "JP" "JE" "JO" "KZ" "KE" "KI"

"KW" "KG" "LA" "LV" "LB" "LS" "LY" "LI" "LT"

"LU" "MG" "MW" "MY" "MV" "ML" "MT" "MU" "MX"

"FM" "MD" "MN" "ME" "MS" "MA" "MQ" "MZ" "MM"

"NA" "NR" "NP" "NL" "NZ" "NI" "NE" "NG" "NU"

"MK" "NO" "OM" "PK" "PS" "PA" "PG" "PY" "PE"

"PH" "PN" "PL" "PT" "PR" "QA" "RO" "RU" "RW"

"WS" "SM" "ST" "SA" "SN" "RS" "SC" "SL" "SG"

"SK" "SI" "SB" "SO" "ZA" "KR" "ES" "LK" "SH"

"VC" "SR" "SE" "CH" "TW" "TJ" "TZ" "TH" "TL"

"TG" "TO" "TT" "TN" "TR" "TM" "VI" "UG" "UA"

"AE" "GB" "US" "UY" "UZ" "VU" "VE" "VN" "ZM"

"ZW"

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean

Default: "true"

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

	As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— **200** The response contains the `status` of the request and `data`.

— **202**

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **204** The request was finished with failure and has no results.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

GET `/maps/directory`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/maps/directory?query=0x471ecd8244"
```

Response samples

200

202

204

401

402

422

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Google Maps Reviews v3

Returns Google Maps reviews from places when using search queries (e.g., `restaurants, Manhattan, NY, USA`) or from a single place when using `Google IDs` or names (e.g., `NoMad Restaurant, NY, USA`, `0x886916e8bc273979:0x5141fcb11460b226`). In addition to the reviews, it returns places information.

In case no reviews were found by your search criteria, your search request will consume the usage of one review.

This endpoint is optimized for fast responses and can be used as a real-time API. Set the `reviewsLimit` parameter to 10 to achieve the maximum response speed.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

The parameter defines the query you want to search. You can use anything that you would use on a regular Google Maps site. Additionally, you can use `google_id` (`feature_id`), `place_id`, or `CID`. The example of valid queries: `Real estate agency, Rome, Italy`, `The NoMad Restaurant, NY, USA`, `restaurants, Brooklyn 11203`, `0x886916e8bc273979:0x5141fcb11460b226`, `ChIJrZhup4lZwokRUr_5sLoFlDw`, etc.

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and save on network latency time. You might want to check out [the web application](#) to play with locations and categories that we would suggest.

reviewsLimit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one place (0 = unlimited).
reviewsQuery	string The parameter specifies the query to search among the reviews (e.g. <code>wow</code>, <code>amazing</code> <code>great</code>).
limit	integer Default: <code>1</code> The parameter specifies the limit of places to take from one query search.
sort	string Default: <code>"most_relevant"</code> Enum: <code>"most_relevant"</code> <code>"newest"</code> <code>"highest_rating"</code> <code>"lowest_rating"</code> The parameter specifies one of the sorting types.
lastPaginationId	string The parameter specifies the review_pagination_id of the last item. It's commonly used in pagination.
start	integer The parameter specifies the start timestamp value for reviews (newest review). The current timestamp is used when the value is not provided. Using the <code>start</code> parameter overwrites the <code>sort</code> parameter to <code>newest</code>. Therefore, the latest reviews will be at the beginning.
cutoff	integer The parameter specifies the oldest timestamp value for reviews (oldest review). Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter to <code>newest</code>. Therefore, the latest reviews will be at the beginning.
cutoffRating	integer The parameter specifies the maximum for <code>lowest_rating</code> sorting or the minimum for <code>highest_rating</code> sorting rating for reviews. Using the <code>cutoffRating</code> requires sorting to be set to <code>lowest_rating</code> or <code>highest_rating</code>.

ignoreEmpty

boolean

Default: `"false"`

The parameter specifies whether to ignore reviews without text or not.

source

string

Default: `null`Value: `"google"`

The parameter specifies source filter. This commonly used for hotels where you can find reviews from other sources like Booking.com, Expedia, etc.

language

string (language)

Default: `"en"`

Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"` `"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"` `"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"` `"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"` `"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"` `"eu"` `"ee"` `"tl"` `"fil"` `"fo"` `"fy"` `"gaa"` `"ga"` `"gd"` `"gl"` `"gn"` `"xx-hacker"` `"ht"` `"ha"` `"haw"` `"bem"` `"rn"` `"id"` `"ia"` `"xh"` `"zu"` `"is"` `"jw"` `"rw"` `"sw"` `"tlh"` `"kg"` `"mfe"` `"kri"` `"la"` `"lv"` `"to"` `"lt"` `"ln"` `"loz"` `"lua"` `"lg"` `"hu"` `"mg"` `"mt"` `"mi"` `"ms"` `"pcm"` `"no"` `"nso"` `"ny"` `"nn"` `"uz"` `"oc"` `"om"` `"xx-pirate"` `"ro"` `"rm"` `"qu"` `"nyn"` `"crs"` `"sq"` `"sk"` `"sl"` `"so"` `"st"` `"sr-ME"` `"sr-Latn"` `"su"` `"fi"` `"sv"` `"tn"` `"tum"` `"tk"` `"tw"` `"wo"` `"el"` `"be"` `"bg"` `"ky"` `"kk"` `"mk"` `"mn"` `"sr"` `"tt"` `"tg"` `"uk"` `"ka"` `"hy"` `"yi"` `"iw"` `"ug"` `"ur"` `"ps"` `"sd"` `"fa"` `"ckb"` `"ti"` `"am"` `"ne"` `"mr"` `"hi"` `"bn"` `"pa"` `"gu"` `"or"` `"ta"` `"te"` `"kn"` `"ml"` `"si"` `"lo"` `"my"` `"km"` `"chr"`

The parameter specifies the language to use for website.

region

string (region)

Enum: `"AF"` `"AL"` `"DZ"` `"AS"` `"AD"` `"AO"` `"AI"` `"AG"` `"AR"` `"AM"` `"AU"` `"AT"` `"AZ"` `"BS"` `"BH"` `"BD"` `"BY"` `"BE"` `"BZ"` `"BJ"` `"BT"` `"BO"` `"BA"` `"BW"` `"BR"` `"VG"` `"BN"` `"BG"` `"BF"` `"BI"` `"KH"` `"CM"` `"CA"` `"CV"` `"CF"` `"TD"` `"CL"` `"CN"` `"CO"` `"CG"` `"CD"` `"CK"` `"CR"` `"CI"` `"HR"` `"CU"` `"CY"` `"CZ"` `"DK"` `"DJ"` `"DM"` `"DO"` `"EC"` `"EG"` `"SV"` `"EE"` `"ET"` `"FJ"` `"FI"` `"FR"` `"GA"` `"GM"` `"GE"` `"DE"` `"GH"` `"GI"` `"GR"` `"GL"` `"GT"` `"GG"` `"GY"` `"HT"` `"HN"` `"HK"` `"HU"` `"IS"` `"IN"` `"ID"` `"IQ"` `"IE"` `"IM"` `"IL"` `"IT"` `"JM"` `"JP"` `"JE"` `"JO"` `"KZ"` `"KE"` `"KI"` `"KW"` `"KG"` `"LA"` `"LV"` `"LB"` `"LS"` `"LY"` `"LI"` `"LT"` `"LU"` `"MG"` `"MW"` `"MY"` `"MV"` `"ML"` `"MT"` `"MU"` `"MX"`

"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a place with its reviews.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/maps/reviews-v3`

Request samples

cURL

cURL (async)

Python

Ruby

PHP

Node.js

Go

Java

[Copy](#)

```
curl -X GET "https://api.outscraper.cloud/maps/reviews-v3?query=The%20NoMac
```

Response samples

200

202

204

401

402

422

Content type

application/json

[Copy](#)[Expand all](#)[Collapse all](#)

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + { ... }
  ]
}
```

Google Maps Photos

Returns Google Maps photos from places when using search queries (e.g., `restaurants, Manhattan, NY, USA`) or from a single place when using IDs or names (e.g., `NoMad Restaurant, NY, USA`, `0x886916e8bc273979:0x5141fcb11460b226`, `ChIJu7bMNFV-54gR-lrHScvPRX4`).

In case no photos were found by your search criteria, your search request will consume the usage of one photo.

AUTHORIZATIONS: > `ApiKeyAuth`

QUERY PARAMETERS

<code>query</code> <code>required</code>	Array of strings The parameter defines the query you want to search. You can use anything that you would use on a regular Google Maps site. Additionally, you can use <code>google_id</code> (feature_id), <code>place_id</code>, <code>CID</code> or urls to Google Maps places. The example of valid queries: <code>Real estate agency, Rome, Italy</code>, <code>The NoMad Restaurant, NY, USA</code>, <code>restaurants, Brooklyn 11203</code>, <code>0x886916e8bc273979:0x5141fcb11460b226</code>, <code>ChIJu7bMNFV-54gR-lrHScvPRX4</code>, <code>https://www.google.com/maps/search/restaurants+near+New+York,+NY</code>, etc. It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and save on network latency time. You might want to check out the web application to play with locations and categories that we would suggest.
<code>photosLimit</code>	integer Default: <code>100</code> The parameter specifies the limit of photos to get from one place.
<code>limit</code>	integer Default: <code>1</code> The parameter specifies the limit of places to take from one query search.
<code>tag</code>	string Default: <code>"all"</code> Enum: <code>"all"</code> <code>"latest"</code> <code>"menu"</code> <code>"by_owner"</code> The parameter specifies one of the filtering types.

language

string (language)

Default: "en"

Enum: "en" "de" "es" "es-419" "fr" "hr" "it" "nl" "pl" "pt-BR" "pt-PT" "vi" "tr" "ru" "ar" "th" "ko" "zh-CN" "zh-TW" "ja" "ach" "af" "ak" "ig" "az" "ban" "ceb" "xx-bork" "bs" "br" "ca" "cs" "sn" "co" "cy" "da" "yo" "et" "xx-elmer" "eo" "eu" "ee" "tl" "fil" "fo" "fy" "gaa" "ga" "gd" "gl" "gn" "xx-hacker" "ht" "ha" "haw" "bem" "rn" "id" "ia" "xh" "zu" "is" "jw" "rw" "sw" "tlh" "kg" "mfe" "kri" "la" "lv" "to" "lt" "ln" "loz" "lua" "lg" "hu" "mg" "mt" "mi" "ms" "pcm" "no" "nso" "ny" "nn" "uz" "oc" "om" "xx-pirate" "ro" "rm" "qu" "nyn" "crs" "sq" "sk" "sl" "so" "st" "sr-ME" "sr-Latn" "su" "fi" "sv" "tn" "tum" "tk" "tw" "wo" "el" "be" "bg" "ky" "kk" "mk" "mn" "sr" "tt" "tg" "uk" "ka" "hy" "yi" "iw" "ug" "ur" "ps" "sd" "fa" "ckb" "ti" "am" "ne" "mr" "hi" "bn" "pa" "gu" "or" "ta" "te" "kn" "ml" "si" "lo" "my" "km" "chr"

The parameter specifies the language to use for website.

region

string (region)

Enum: "AF" "AL" "DZ" "AS" "AD" "AO" "AI" "AG" "AR" "AM" "AU" "AT" "AZ" "BS" "BH" "BD" "BY" "BE" "BZ" "BJ" "BT" "BO" "BA" "BW" "BR" "VG" "BN" "BG" "BF" "BI" "KH" "CM" "CA" "CV" "CF" "TD" "CL" "CN" "CO" "CG" "CD" "CK" "CR" "CI" "HR" "CU" "CY" "CZ" "DK" "DJ" "DM" "DO" "EC" "EG" "SV" "EE" "ET" "FJ" "FI" "FR" "GA" "GM" "GE" "DE" "GH" "GI" "GR" "GL" "GT" "GG" "GY" "HT" "HN" "HK" "HU" "IS" "IN" "ID" "IQ" "IE" "IM" "IL" "IT" "JM" "JP" "JE" "JO" "KZ" "KE" "KI" "KW" "KG" "LA" "LV" "LB" "LS" "LY" "LI" "LT" "LU" "MG" "MW" "MY" "MV" "ML" "MT" "MU" "MX" "FM" "MD" "MN" "ME" "MS" "MA" "MQ" "MZ" "MM" "NA" "NR" "NP" "NL" "NZ" "NI" "NE" "NG" "NU" "MK" "NO" "OM" "PK" "PS" "PA" "PG" "PY" "PE" "PH" "PN" "PL" "PT" "PR" "QA" "RO" "RU" "RW" "WS" "SM" "ST" "SA" "SN" "RS" "SC" "SL" "SG" "SK" "SI" "SB" "SO" "ZA" "KR" "ES" "LK" "SH" "VC" "SR" "SE" "CH" "TW" "TJ" "TZ" "TH" "TL" "TG" "TO" "TT" "TN" "TR" "TM" "VI" "UG" "UA" "AE" "GB" "US" "UY" "UZ" "VU" "VE" "VN" "ZM" "ZW"

	The parameter specifies the country to use for website. It's recommended to use it for a better search experience.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a place with its photos.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

- **204** The request was finished with failure and has no results.
- **401** Wrong or missing API Key (token).
- **402** Past due invoices or a payment method not connected.
- **422** Wrong query url parameters.

GET /maps/photos-v3

Request samples

cURL

cURL (async)

Python

Copy

```
curl -X GET "https://api.outscraper.cloud/maps/photos-v3?query=Trump%20Tower"
```

Response samples

200

202

204

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Google Directions

Returns directions between two points from Google Maps.

QUERY PARAMETERS

origin required	Array of strings The parameter defines the origin. You can use anything that you would use on Google Maps directions (e.g., <code>Lincoln Way & 19th Ave, San Francisco, USA</code>). It supports batching by sending arrays with up to <code>250</code> origins. It allows multiple directions to be sent in one request and save on network latency time.
destination required	Array of strings The parameter defines the destination. You can use anything that you would use on Google Maps directions (e.g., <code>19th Ave & Taraval St, San Francisco, USA</code>). It supports batching by sending arrays with up to <code>250</code> destinations. It allows multiple directions to be sent in one request and save on network latency time.
departure_time	integer The parameter specifies the departure timestamp. The current timestamp is used when the value is not provided.
finish_time	integer The parameter specifies the end departure timestamp. Using this parameter requires using the <code>interval</code> parameter.
interval	integer The parameter specifies the interval to use between <code>departure_time</code> and <code>finish_time</code>.
travel_mode	string Default: <code>"best"</code> Enum: <code>"best"</code> <code>"car"</code> <code>"transit"</code> <code>"walk"</code> <code>"bike"</code> <code>"flight"</code> The parameter specifies one of the travel modes.
language	string (language) Default: <code>"en"</code> Enum: <code>"en"</code> <code>"de"</code> <code>"es"</code> <code>"es-419"</code> <code>"fr"</code> <code>"hr"</code> <code>"it"</code> <code>"nl"</code> <code>"pl"</code> <code>"pt-BR"</code> <code>"pt-PT"</code> <code>"vi"</code> <code>"tr"</code> <code>"ru"</code> <code>"ar"</code> <code>"th"</code> <code>"ko"</code> <code>"zh-CN"</code> <code>"zh-TW"</code> <code>"ja"</code> <code>"ach"</code> <code>"af"</code> <code>"ak"</code> <code>"ig"</code> <code>"az"</code> <code>"ban"</code> <code>"ceb"</code> <code>"xx-bork"</code> <code>"bs"</code> <code>"br"</code> <code>"ca"</code> <code>"cs"</code> <code>"sn"</code> <code>"co"</code> <code>"cy"</code> <code>"da"</code> <code>"yo"</code> <code>"et"</code> <code>"xx-elmer"</code> <code>"eo"</code> <code>"eu"</code> <code>"ee"</code> <code>"tl"</code> <code>"fil"</code> <code>"fo"</code> <code>"fy"</code> <code>"gaa"</code> <code>"ga"</code> <code>"gd"</code> <code>"gl"</code> <code>"gn"</code> <code>"xx-hacker"</code> <code>"ht"</code> <code>"ha"</code> <code>"haw"</code> <code>"bem"</code> <code>"rn"</code>

"id"	"ia"	"xh"	"zu"	"is"	"jw"	"rw"	"sw"	"tlh"
"kg"	"mfe"	"kri"	"la"	"lv"	"to"	"lt"	"ln"	"loz"
"lua"	"lg"	"hu"	"mg"	"mt"	"mi"	"ms"	"pcm"	"no"
"nso"	"ny"	"nn"	"uz"	"oc"	"om"	"xx-pirate"	"ro"	
"rm"	"qu"	"nyn"	"crs"	"sq"	"sk"	"sl"	"so"	"st"
"sr-ME"	"sr-Latn"	"su"	"fi"	"sv"	"tn"	"tum"	"tk"	
"tw"	"wo"	"el"	"be"	"bg"	"ky"	"kk"	"mk"	"mn"
"sr"	"tt"	"tg"	"uk"	"ka"	"hy"	"yi"	"iw"	"ug"
"ur"	"ps"	"sd"	"fa"	"ckb"	"ti"	"am"	"ne"	"mr"
"hi"	"bn"	"pa"	"gu"	"or"	"ta"	"te"	"kn"	"ml"
"si"	"lo"	"my"	"km"	"chr"				

The parameter specifies the language to use for website.

region

string (region)
Enum: "AF" "AL" "DZ" "AS" "AD" "AO" "AI" "AG" "AR"
"AM" "AU" "AT" "AZ" "BS" "BH" "BD" "BY" "BE"
"BZ" "BJ" "BT" "BO" "BA" "BW" "BR" "VG" "BN"
"BG" "BF" "BI" "KH" "CM" "CA" "CV" "CF" "TD"
"CL" "CN" "CO" "CG" "CD" "CK" "CR" "CI" "HR"
"CU" "CY" "CZ" "DK" "DJ" "DM" "DO" "EC" "EG"
"SV" "EE" "ET" "FJ" "FI" "FR" "GA" "GM" "GE"
"DE" "GH" "GI" "GR" "GL" "GT" "GG" "GY" "HT"
"HN" "HK" "HU" "IS" "IN" "ID" "IQ" "IE" "IM"
"IL" "IT" "JM" "JP" "JE" "JO" "KZ" "KE" "KI"
"KW" "KG" "LA" "LV" "LB" "LS" "LY" "LI" "LT"
"LU" "MG" "MW" "MY" "MV" "ML" "MT" "MU" "MX"
"FM" "MD" "MN" "ME" "MS" "MA" "MQ" "MZ" "MM"
"NA" "NR" "NP" "NL" "NZ" "NI" "NE" "NG" "NU"
"MK" "NO" "OM" "PK" "PS" "PA" "PG" "PY" "PE"
"PH" "PN" "PL" "PT" "PR" "QA" "RO" "RU" "RW"
"WS" "SM" "ST" "SA" "SN" "RS" "SC" "SL" "SG"
"SK" "SI" "SB" "SO" "ZA" "KR" "ES" "LK" "SH"
"VC" "SR" "SE" "CH" "TW" "TJ" "TZ" "TH" "TL"
"TG" "TO" "TT" "TN" "TR" "TM" "VI" "UG" "UA"
"AE" "GB" "US" "UY" "UZ" "VU" "VE" "VN" "ZM"
"ZW"

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string
The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean
Default: "true"

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— **200** The response contains the `status` of the request and `data`.

— **202**

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

GET /maps/directions

Request samples

- cURL
- cURL (async)
- Python

Copy

```
curl -X GET "https://api.outscraper.cloud/maps/directions?origin=Lincoln%20
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Place Autocomplete

Get automatic search suggestions for your queries on Google Maps.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

origin
required

Array of strings
The parameter defines the query to search for suggestions (e.g., `5th Av`, `Central Pa`).
It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

coordinates
required

Array of strings
Default: `"40.7449819,-74.0271321"`

The latitude and longitude coordinates specifying the location for search
(e.g., `37.427074,-122.1439166`, `40.7449819,-74.0271321`).

language

string (language)

Default: `"en"`

Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"` `"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"` `"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"` `"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"` `"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"` `"eu"` `"ee"` `"tl"` `"fil"` `"fo"` `"fy"` `"gaa"` `"ga"` `"gd"` `"gl"` `"gn"` `"xx-hacker"` `"ht"` `"ha"` `"haw"` `"bem"` `"rn"` `"id"` `"ia"` `"xh"` `"zu"` `"is"` `"jw"` `"rw"` `"sw"` `"tlh"` `"kg"` `"mfe"` `"kri"` `"la"` `"lv"` `"to"` `"lt"` `"ln"` `"loz"` `"lua"` `"lg"` `"hu"` `"mg"` `"mt"` `"mi"` `"ms"` `"pcm"` `"no"` `"nso"` `"ny"` `"nn"` `"uz"` `"oc"` `"om"` `"xx-pirate"` `"ro"` `"rm"` `"qu"` `"nyn"` `"crs"` `"sq"` `"sk"` `"sl"` `"so"` `"st"` `"sr-ME"` `"sr-Latn"` `"su"` `"fi"` `"sv"` `"tn"` `"tum"` `"tk"` `"tw"` `"wo"` `"el"` `"be"` `"bg"` `"ky"` `"kk"` `"mk"` `"mn"` `"sr"` `"tt"` `"tg"` `"uk"` `"ka"` `"hy"` `"yi"` `"iw"` `"ug"` `"ur"` `"ps"` `"sd"` `"fa"` `"ckb"` `"ti"` `"am"` `"ne"` `"mr"` `"hi"` `"bn"` `"pa"` `"gu"` `"or"` `"ta"` `"te"` `"kn"` `"ml"` `"si"` `"lo"` `"my"` `"km"` `"chr"`

The parameter specifies the language to use for website.

region

string (region)

Enum: `"AF"` `"AL"` `"DZ"` `"AS"` `"AD"` `"AO"` `"AI"` `"AG"` `"AR"` `"AM"` `"AU"` `"AT"` `"AZ"` `"BS"` `"BH"` `"BD"` `"BY"` `"BE"` `"BZ"` `"BJ"` `"BT"` `"BO"` `"BA"` `"BW"` `"BR"` `"VG"` `"BN"` `"BG"` `"BF"` `"BI"` `"KH"` `"CM"` `"CA"` `"CV"` `"CF"` `"TD"` `"CL"` `"CN"` `"CO"` `"CG"` `"CD"` `"CK"` `"CR"` `"CI"` `"HR"` `"CU"` `"CY"` `"CZ"` `"DK"` `"DJ"` `"DM"` `"DO"` `"EC"` `"EG"` `"SV"` `"EE"` `"ET"` `"FJ"` `"FI"` `"FR"` `"GA"` `"GM"` `"GE"` `"DE"` `"GH"` `"GI"` `"GR"` `"GL"` `"GT"` `"GG"` `"GY"` `"HT"` `"HN"` `"HK"` `"HU"` `"IS"` `"IN"` `"ID"` `"IQ"` `"IE"` `"IM"` `"IL"` `"IT"` `"JM"` `"JP"` `"JE"` `"JO"` `"KZ"` `"KE"` `"KI"` `"KW"` `"KG"` `"LA"` `"LV"` `"LB"` `"LS"` `"LY"` `"LI"` `"LT"` `"LU"` `"MG"` `"MW"` `"MY"` `"MV"` `"ML"` `"MT"` `"MU"` `"MX"` `"FM"` `"MD"` `"MN"` `"ME"` `"MS"` `"MA"` `"MQ"` `"MZ"` `"MM"` `"NA"` `"NR"` `"NP"` `"NL"` `"NZ"` `"NI"` `"NE"` `"NG"` `"NU"` `"MK"` `"NO"` `"OM"` `"PK"` `"PS"` `"PA"` `"PG"` `"PY"` `"PE"` `"PH"` `"PN"` `"PL"` `"PT"` `"PR"` `"QA"` `"RO"` `"RU"` `"RW"` `"WS"` `"SM"` `"ST"` `"SA"` `"SN"` `"RS"` `"SC"` `"SL"` `"SG"` `"SK"` `"SI"` `"SB"` `"SO"` `"ZA"` `"KR"` `"ES"` `"LK"` `"SH"` `"VC"` `"SR"` `"SE"` `"CH"` `"TW"` `"TJ"` `"TZ"` `"TH"` `"TL"` `"TG"` `"TO"` `"TT"` `"TN"` `"TR"` `"TM"` `"VI"` `"UG"` `"UA"`

- "AE"
- "GB"
- "US"
- "UY"
- "UZ"
- "VU"
- "VE"
- "VN"
- "ZM"
- "ZW"

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /maps/suggestions

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/maps/suggestions?query=bars&coord"
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + { ... }
  ]
}
```

Google Play Reviews

Returns reviews from any app/book/movie in the Google Play store.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings
You can use app IDs or direct links (e.g., `https://play.google.com/store/apps/details?id=com.facebook.katana`, `com.facebook.katana`). It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

limit

integer
Default: `100`
The parameter specifies the limit of reviews to get from one query.

sort

string
Default: `"most_relevant"`
Enum: `"most_relevant"` `"newest"` `"rating"`
The parameter specifies one of the sorting types.

cutoff

integer
The parameter specifies the oldest timestamp value for items.
Using the `cutoff` parameter overwrites `sort` parameter`. Therefore, the latest records will be at the beginning (newest first).

rating

integer
Filter by a specific rating. Works only with `sort=rating`.

language

string (language)

Default: `"en"`

Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"`
`"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"`
`"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"`
`"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"`
`"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"`
`"eu"` `"ee"` `"tl"` `"fil"` `"fo"` `"fy"` `"gaa"` `"ga"` `"gd"`
`"gl"` `"gn"` `"xx-hacker"` `"ht"` `"ha"` `"haw"` `"bem"` `"rn"`
`"id"` `"ia"` `"xh"` `"zu"` `"is"` `"jw"` `"rw"` `"sw"` `"tlh"`
`"kg"` `"mfe"` `"kri"` `"la"` `"lv"` `"to"` `"lt"` `"ln"` `"loz"`
`"lua"` `"lg"` `"hu"` `"mg"` `"mt"` `"mi"` `"ms"` `"pcm"` `"no"`
`"nso"` `"ny"` `"nn"` `"uz"` `"oc"` `"om"` `"xx-pirate"` `"ro"`
`"rm"` `"qu"` `"nyn"` `"crs"` `"sq"` `"sk"` `"sl"` `"so"` `"st"`
`"sr-ME"` `"sr-Latn"` `"su"` `"fi"` `"sv"` `"tn"` `"tum"` `"tk"`
`"tw"` `"wo"` `"el"` `"be"` `"bg"` `"ky"` `"kk"` `"mk"` `"mn"`
`"sr"` `"tt"` `"tg"` `"uk"` `"ka"` `"hy"` `"yi"` `"iw"` `"ug"`
`"ur"` `"ps"` `"sd"` `"fa"` `"ckb"` `"ti"` `"am"` `"ne"` `"mr"`
`"hi"` `"bn"` `"pa"` `"gu"` `"or"` `"ta"` `"te"` `"kn"` `"ml"`
`"si"` `"lo"` `"my"` `"km"` `"chr"`

The parameter specifies the language to use for website.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string
The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

- 401 Wrong or missing API Key (token).
- 402 Past due invoices or a payment method not connected.
- 422 Wrong query url parameters.

GET /google-play/reviews

Request samples

cURL

cURL (async)

Python

Copy

```
curl -X GET "https://api.outscraper.cloud/google-play/reviews?query=com.fac
```

Response samples

200

202

401

402

422

Content type
application/json

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Google Search

Returns search results from Google based on a given search query (or many queries). This endpoint is optimized for fast responses and can be used as a real-time API.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings
Queries to search on Google (e.g., `bitcoin`, `37th president of usa`).
It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

pagesPerQuery

integer
Default: `1`
The parameter specifies the limit of pages to return from one query.

uule

string
Google UULE parameter is used to encode a place or an exact location (with latitude and longitude) into a code. By using it you can see a Google result page like someone located at the specified location.

language

string (language)
Default: `"en"`
Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"` `"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"` `"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"` `"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"` `"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"`

"eu"	"ee"	"tl"	"fil"	"fo"	"fy"	"gaa"	"ga"	"gd"
"gl"	"gn"	"xx-hacker"	"ht"	"ha"	"haw"	"bem"	"rn"	
"id"	"ia"	"xh"	"zu"	"is"	"jw"	"rw"	"sw"	"tlh"
"kg"	"mfe"	"kri"	"la"	"lv"	"to"	"lt"	"ln"	"loz"
"lua"	"lg"	"hu"	"mg"	"mt"	"mi"	"ms"	"pcm"	"no"
"nso"	"ny"	"nn"	"uz"	"oc"	"om"	"xx-pirate"	"ro"	
"rm"	"qu"	"nyn"	"crs"	"sq"	"sk"	"sl"	"so"	"st"
"sr-ME"	"sr-Latn"	"su"	"fi"	"sv"	"tn"	"tum"	"tk"	
"tw"	"wo"	"el"	"be"	"bg"	"ky"	"kk"	"mk"	"mn"
"sr"	"tt"	"tg"	"uk"	"ka"	"hy"	"yi"	"iw"	"ug"
"ur"	"ps"	"sd"	"fa"	"ckb"	"ti"	"am"	"ne"	"mr"
"hi"	"bn"	"pa"	"gu"	"or"	"ta"	"te"	"kn"	"ml"
"si"	"lo"	"my"	"km"	"chr"				

The parameter specifies the language to use for website.

region

string (region)

Enum:	"AF"	"AL"	"DZ"	"AS"	"AD"	"AO"	"AI"	"AG"	"AR"
	"AM"	"AU"	"AT"	"AZ"	"BS"	"BH"	"BD"	"BY"	"BE"
	"BZ"	"BJ"	"BT"	"BO"	"BA"	"BW"	"BR"	"VG"	"BN"
	"BG"	"BF"	"BI"	"KH"	"CM"	"CA"	"CV"	"CF"	"TD"
	"CL"	"CN"	"CO"	"CG"	"CD"	"CK"	"CR"	"CI"	"HR"
	"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
	"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
	"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
	"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
	"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
	"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
	"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
	"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
	"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
	"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
	"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
	"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
	"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
	"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
	"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
	"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
	"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

tbs

string

Enum:	"h"	"d"	"w"	"m"	"y"
-------	-----	-----	-----	-----	-----

The parameter specifies the date range of the results (h - past hour, d - past 24 hours, w - past week, m - past month, 'y' - past year).

skip	integer Default: <code>0</code> The parameter specifies the number of items to skip. It's commonly used in pagination.
enrichment	Array of strings The parameter defines an enrichment or enrichments (e.g., <code>enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3</code>) you want to apply to the results. Available values: <code>domains_service</code> — Emails & Contacts Scraper: finds emails, social links, phones, and other contacts from websites, <code>emails_validator_service</code> — Email Address Verifier: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate, <code>disposable_email_checker</code> — Disposable Emails Checker: checks origins of email addresses (disposable, free, or corporate), <code>company_insights_service</code> — Company Insights: finds company details such as revenue, size, founding year, public status, etc, <code>phones_enricher_service</code> — Phone Numbers Enricher: returns phones carrier data (name/type), validates phones, ensures messages deliverability, <code>trustpilot_service</code> — Trustpilot Scraper: returns data from a list of businesses, <code>whitepages_phones</code> - Phone Identity Finder: returns insights about phone number owners (name, address, etc.), <code>ai_chain_info</code> - Chain Info: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting. Using enrichments increases the time of the response. You might want to use the <code>async=true</code> parameter to avoid getting timeouts.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation

as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished.

Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **204** The request was finished with failure and has no results.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

GET `/google-search-v3`

Request samples

cURL

cURL (async)

Python

Ruby

PHP

Node.js

Go

Java

Copy

```
curl -X GET "https://api.outscraper.cloud/google-search-v3?query=buy+iphone"
```

Response samples

- 200
- 202
- 204
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + { ... }
  ]
}
```

Google Search News

Returns search results from Google News based on a given search query (or many queries).

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings Queries to search on Google (e.g., bitcoin , 37th president of usa). It supports batching by sending arrays with up to 250 queries (e.g., query=text1&query=text2&query=text3). It allows multiple queries to be sent in one request and to save on network latency time.
pagesPerQuery	integer Default: 1 The parameter specifies the limit of pages to return from one query.
uule	string

Google UULE parameter is used to encode a place or an exact location (with latitude and longitude) into a code. By using it you can see a Google result page like someone located at the specified location.

language

string (language)

Default: "en"

Enum: "en" "de" "es" "es-419" "fr" "hr" "it" "nl" "pl" "pt-BR" "pt-PT" "vi" "tr" "ru" "ar" "th" "ko" "zh-CN" "zh-TW" "ja" "ach" "af" "ak" "ig" "az" "ban" "ceb" "xx-bork" "bs" "br" "ca" "cs" "sn" "co" "cy" "da" "yo" "et" "xx-elmer" "eo" "eu" "ee" "tl" "fil" "fo" "fy" "gaa" "ga" "gd" "gl" "gn" "xx-hacker" "ht" "ha" "haw" "bem" "rn" "id" "ia" "xh" "zu" "is" "jw" "rw" "sw" "tlh" "kg" "mfe" "kri" "la" "lv" "to" "lt" "ln" "loz" "lua" "lg" "hu" "mg" "mt" "mi" "ms" "pcm" "no" "nso" "ny" "nn" "uz" "oc" "om" "xx-pirate" "ro" "rm" "qu" "nyn" "crs" "sq" "sk" "sl" "so" "st" "sr-ME" "sr-Latn" "su" "fi" "sv" "tn" "tum" "tk" "tw" "wo" "el" "be" "bg" "ky" "kk" "mk" "mn" "sr" "tt" "tg" "uk" "ka" "hy" "yi" "iw" "ug" "ur" "ps" "sd" "fa" "ckb" "ti" "am" "ne" "mr" "hi" "bn" "pa" "gu" "or" "ta" "te" "kn" "ml" "si" "lo" "my" "km" "chr"

The parameter specifies the language to use for website.

region

string (region)

Enum: "AF" "AL" "DZ" "AS" "AD" "AO" "AI" "AG" "AR" "AM" "AU" "AT" "AZ" "BS" "BH" "BD" "BY" "BE" "BZ" "BJ" "BT" "BO" "BA" "BW" "BR" "VG" "BN" "BG" "BF" "BI" "KH" "CM" "CA" "CV" "CF" "TD" "CL" "CN" "CO" "CG" "CD" "CK" "CR" "CI" "HR" "CU" "CY" "CZ" "DK" "DJ" "DM" "DO" "EC" "EG" "SV" "EE" "ET" "FJ" "FI" "FR" "GA" "GM" "GE" "DE" "GH" "GI" "GR" "GL" "GT" "GG" "GY" "HT" "HN" "HK" "HU" "IS" "IN" "ID" "IQ" "IE" "IM" "IL" "IT" "JM" "JP" "JE" "JO" "KZ" "KE" "KI" "KW" "KG" "LA" "LV" "LB" "LS" "LY" "LI" "LT" "LU" "MG" "MW" "MY" "MV" "ML" "MT" "MU" "MX" "FM" "MD" "MN" "ME" "MS" "MA" "MQ" "MZ" "MM" "NA" "NR" "NP" "NL" "NZ" "NI" "NE" "NG" "NU" "MK" "NO" "OM" "PK" "PS" "PA" "PG" "PY" "PE" "PH" "PN" "PL" "PT" "PR" "QA" "RO" "RU" "RW" "WS" "SM" "ST" "SA" "SN" "RS" "SC" "SL" "SG" "SK" "SI" "SB" "SO" "ZA" "KR" "ES" "LK" "SH" "VC" "SR" "SE" "CH" "TW" "TJ" "TZ" "TH" "TL"

"TG" "TO" "TT" "TN" "TR" "TM" "VI" "UG" "UA"
"AE" "GB" "US" "UY" "UZ" "VU" "VE" "VN" "ZM"
"ZW"

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

tbs

string
Enum: "h" "d" "w" "m" "y"

The parameter specifies the date range of the results (**h** - past hour, **d** - past 24 hours, **w** - past week, **m** - past month, 'y' - past year).

fields

string
The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use **&fields=query,name** to return only the specific ones.

async

boolean
Default: "true"
The parameter defines the way you want to submit your task to Outscraper. It can be set to **false** to open an HTTP connection and keep it open until you got your results, or **true** (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for **2** hours after a request has been completed.
A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.
As most of the requests take some time to be executed the **async=true** option is preferred to avoid HTTP requests timeouts.

ui

boolean
Default: "false"
The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the **async** parameter to **true**.

webhook

string
The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/google-search-news`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/google-search-news?query=bitcoins"
```

Response samples

200**202****204****401****402****422**

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + [ ... ]
  ]
}
```

Google Search Events

Returns search results from Google Events based on a given search query (or many queries).

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings Queries to search on Google (e.g., <code>bitcoin</code>, <code>37th president of usa</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
pagesPerQuery	integer Default: <code>1</code> The parameter specifies the limit of pages to return from one query.
uule	string Google UULE parameter is used to encode a place or an exact location (with latitude and longitude) into a code. By using it you can see a Google result page like someone located at the specified location.
language	string (language) Default: <code>"en"</code> Enum: <code>"en"</code> <code>"de"</code> <code>"es"</code> <code>"es-419"</code> <code>"fr"</code> <code>"hr"</code> <code>"it"</code> <code>"nl"</code> <code>"pl"</code> <code>"pt-BR"</code> <code>"pt-PT"</code> <code>"vi"</code> <code>"tr"</code> <code>"ru"</code> <code>"ar"</code> <code>"th"</code> <code>"ko"</code> <code>"zh-CN"</code> <code>"zh-TW"</code> <code>"ja"</code> <code>"ach"</code> <code>"af"</code> <code>"ak"</code> <code>"ig"</code> <code>"az"</code> <code>"ban"</code> <code>"ceb"</code> <code>"xx-bork"</code> <code>"bs"</code> <code>"br"</code> <code>"ca"</code> <code>"cs"</code> <code>"sn"</code> <code>"co"</code> <code>"cy"</code> <code>"da"</code> <code>"yo"</code> <code>"et"</code> <code>"xx-elmer"</code> <code>"eo"</code> <code>"eu"</code> <code>"ee"</code> <code>"tl"</code> <code>"fil"</code> <code>"fo"</code> <code>"fy"</code> <code>"gaa"</code> <code>"ga"</code> <code>"gd"</code> <code>"gl"</code> <code>"gn"</code> <code>"xx-hacker"</code> <code>"ht"</code> <code>"ha"</code> <code>"haw"</code> <code>"bem"</code> <code>"rn"</code> <code>"id"</code> <code>"ia"</code> <code>"xh"</code> <code>"zu"</code> <code>"is"</code> <code>"jw"</code> <code>"rw"</code> <code>"sw"</code> <code>"tlh"</code> <code>"kg"</code> <code>"mfe"</code> <code>"kri"</code> <code>"la"</code> <code>"lv"</code> <code>"to"</code> <code>"lt"</code> <code>"ln"</code> <code>"loz"</code> <code>"lua"</code> <code>"lg"</code> <code>"hu"</code> <code>"mg"</code> <code>"mt"</code> <code>"mi"</code> <code>"ms"</code> <code>"pcm"</code> <code>"no"</code> <code>"nso"</code> <code>"ny"</code> <code>"nn"</code> <code>"uz"</code> <code>"oc"</code> <code>"om"</code> <code>"xx-pirate"</code> <code>"ro"</code> <code>"rm"</code> <code>"qu"</code> <code>"nyn"</code> <code>"crs"</code> <code>"sq"</code> <code>"sk"</code> <code>"sl"</code> <code>"so"</code> <code>"st"</code> <code>"sr-ME"</code> <code>"sr-Latn"</code> <code>"su"</code> <code>"fi"</code> <code>"sv"</code> <code>"tn"</code> <code>"tum"</code> <code>"tk"</code> <code>"tw"</code> <code>"wo"</code> <code>"el"</code> <code>"be"</code> <code>"bg"</code> <code>"ky"</code> <code>"kk"</code> <code>"mk"</code> <code>"mn"</code> <code>"sr"</code> <code>"tt"</code> <code>"tg"</code> <code>"uk"</code> <code>"ka"</code> <code>"hy"</code> <code>"yi"</code> <code>"iw"</code> <code>"ug"</code>

"ur"	"ps"	"sd"	"fa"	"ckb"	"ti"	"am"	"ne"	"mr"
"hi"	"bn"	"pa"	"gu"	"or"	"ta"	"te"	"kn"	"ml"
"si"	"lo"	"my"	"km"	"chr"				

The parameter specifies the language to use for website.

region

string (region)

Enum:	"AF"	"AL"	"DZ"	"AS"	"AD"	"AO"	"AI"	"AG"	"AR"
	"AM"	"AU"	"AT"	"AZ"	"BS"	"BH"	"BD"	"BY"	"BE"
	"BZ"	"BJ"	"BT"	"BO"	"BA"	"BW"	"BR"	"VG"	"BN"
	"BG"	"BF"	"BI"	"KH"	"CM"	"CA"	"CV"	"CF"	"TD"
	"CL"	"CN"	"CO"	"CG"	"CD"	"CK"	"CR"	"CI"	"HR"
	"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
	"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
	"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
	"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
	"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
	"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
	"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
	"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
	"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
	"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
	"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
	"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
	"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
	"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
	"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
	"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
	"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation

	as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code> .
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **204** The request was finished with failure and has no results.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

GET `/google-search-events`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/google-search-events?query=bitcoi
```

Response samples

- 200
- 202
- 204
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Google Search Videos

Returns search results from Google Videos based on a given search query (or many queries).

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings Queries to search on Google (e.g., bitcoin , 37th president of usa). It supports batching by sending arrays with up to 250 queries (e.g., query=text1&query=text2&query=text3). It allows multiple queries to be sent in one request and to save on network latency time.
pagesPerQuery	integer Default: 1 The parameter specifies the limit of pages to return from one query.
uule	string Google UULE parameter is used to encode a place or an exact location (with latitude and longitude) into a code. By using it you can see a Google result page like someone located at the specified location.

language

string (language)

Default: "en"

Enum: "en" "de" "es" "es-419" "fr" "hr" "it" "nl" "pl" "pt-BR" "pt-PT" "vi" "tr" "ru" "ar" "th" "ko" "zh-CN" "zh-TW" "ja" "ach" "af" "ak" "ig" "az" "ban" "ceb" "xx-bork" "bs" "br" "ca" "cs" "sn" "co" "cy" "da" "yo" "et" "xx-elmer" "eo" "eu" "ee" "tl" "fil" "fo" "fy" "gaa" "ga" "gd" "gl" "gn" "xx-hacker" "ht" "ha" "haw" "bem" "rn" "id" "ia" "xh" "zu" "is" "jw" "rw" "sw" "tlh" "kg" "mfe" "kri" "la" "lv" "to" "lt" "ln" "loz" "lua" "lg" "hu" "mg" "mt" "mi" "ms" "pcm" "no" "nso" "ny" "nn" "uz" "oc" "om" "xx-pirate" "ro" "rm" "qu" "nyn" "crs" "sq" "sk" "sl" "so" "st" "sr-ME" "sr-Latn" "su" "fi" "sv" "tn" "tum" "tk" "tw" "wo" "el" "be" "bg" "ky" "kk" "mk" "mn" "sr" "tt" "tg" "uk" "ka" "hy" "yi" "iw" "ug" "ur" "ps" "sd" "fa" "ckb" "ti" "am" "ne" "mr" "hi" "bn" "pa" "gu" "or" "ta" "te" "kn" "ml" "si" "lo" "my" "km" "chr"

The parameter specifies the language to use for website.

region

string (region)

Enum: "AF" "AL" "DZ" "AS" "AD" "AO" "AI" "AG" "AR" "AM" "AU" "AT" "AZ" "BS" "BH" "BD" "BY" "BE" "BZ" "BJ" "BT" "BO" "BA" "BW" "BR" "VG" "BN" "BG" "BF" "BI" "KH" "CM" "CA" "CV" "CF" "TD" "CL" "CN" "CO" "CG" "CD" "CK" "CR" "CI" "HR" "CU" "CY" "CZ" "DK" "DJ" "DM" "DO" "EC" "EG" "SV" "EE" "ET" "FJ" "FI" "FR" "GA" "GM" "GE" "DE" "GH" "GI" "GR" "GL" "GT" "GG" "GY" "HT" "HN" "HK" "HU" "IS" "IN" "ID" "IQ" "IE" "IM" "IL" "IT" "JM" "JP" "JE" "JO" "KZ" "KE" "KI" "KW" "KG" "LA" "LV" "LB" "LS" "LY" "LI" "LT" "LU" "MG" "MW" "MY" "MV" "ML" "MT" "MU" "MX" "FM" "MD" "MN" "ME" "MS" "MA" "MQ" "MZ" "MM" "NA" "NR" "NP" "NL" "NZ" "NI" "NE" "NG" "NU" "MK" "NO" "OM" "PK" "PS" "PA" "PG" "PY" "PE" "PH" "PN" "PL" "PT" "PR" "QA" "RO" "RU" "RW" "WS" "SM" "ST" "SA" "SN" "RS" "SC" "SL" "SG" "SK" "SI" "SB" "SO" "ZA" "KR" "ES" "LK" "SH" "VC" "SR" "SE" "CH" "TW" "TJ" "TZ" "TH" "TL" "TG" "TO" "TT" "TN" "TR" "TM" "VI" "UG" "UA" "AE" "GB" "US" "UY" "UZ" "VU" "VE" "VN" "ZM" "ZW"

	The parameter specifies the country to use for website. It's recommended to use it for a better search experience.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

- **204** The request was finished with failure and has no results.
- **401** Wrong or missing API Key (token).
- **402** Past due invoices or a payment method not connected.
- **422** Wrong query url parameters.

GET /google-search-videos

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/google-search-videos?query=outscr
```

Response samples

200

202

204

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Google Search Images

Returns images search results from Google based on a given search query (or many queries).

QUERY PARAMETERS

query required	Array of strings Queries to search on Google (e.g., <code>bitcoin</code>, <code>37th president of usa</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
perQuery	integer Default: <code>100</code> The parameter specifies the limit of items to return from one query.
uule	string Google UULE parameter is used to encode a place or an exact location (with latitude and longitude) into a code. By using it you can see a Google result page like someone located at the specified location.
language	string (language) Default: <code>"en"</code> Enum: <code>"en"</code> <code>"de"</code> <code>"es"</code> <code>"es-419"</code> <code>"fr"</code> <code>"hr"</code> <code>"it"</code> <code>"nl"</code> <code>"pl"</code> <code>"pt-BR"</code> <code>"pt-PT"</code> <code>"vi"</code> <code>"tr"</code> <code>"ru"</code> <code>"ar"</code> <code>"th"</code> <code>"ko"</code> <code>"zh-CN"</code> <code>"zh-TW"</code> <code>"ja"</code> <code>"ach"</code> <code>"af"</code> <code>"ak"</code> <code>"ig"</code> <code>"az"</code> <code>"ban"</code> <code>"ceb"</code> <code>"xx-bork"</code> <code>"bs"</code> <code>"br"</code> <code>"ca"</code> <code>"cs"</code> <code>"sn"</code> <code>"co"</code> <code>"cy"</code> <code>"da"</code> <code>"yo"</code> <code>"et"</code> <code>"xx-elmer"</code> <code>"eo"</code> <code>"eu"</code> <code>"ee"</code> <code>"tl"</code> <code>"fil"</code> <code>"fo"</code> <code>"fy"</code> <code>"gaa"</code> <code>"ga"</code> <code>"gd"</code> <code>"gl"</code> <code>"gn"</code> <code>"xx-hacker"</code> <code>"ht"</code> <code>"ha"</code> <code>"haw"</code> <code>"bem"</code> <code>"rn"</code> <code>"id"</code> <code>"ia"</code> <code>"xh"</code> <code>"zu"</code> <code>"is"</code> <code>"jw"</code> <code>"rw"</code> <code>"sw"</code> <code>"tlh"</code> <code>"kg"</code> <code>"mfe"</code> <code>"kri"</code> <code>"la"</code> <code>"lv"</code> <code>"to"</code> <code>"lt"</code> <code>"ln"</code> <code>"loz"</code> <code>"lua"</code> <code>"lg"</code> <code>"hu"</code> <code>"mg"</code> <code>"mt"</code> <code>"mi"</code> <code>"ms"</code> <code>"pcm"</code> <code>"no"</code> <code>"nso"</code> <code>"ny"</code> <code>"nn"</code> <code>"uz"</code> <code>"oc"</code> <code>"om"</code> <code>"xx-pirate"</code> <code>"ro"</code> <code>"rm"</code> <code>"qu"</code> <code>"nyn"</code> <code>"crs"</code> <code>"sq"</code> <code>"sk"</code> <code>"sl"</code> <code>"so"</code> <code>"st"</code> <code>"sr-ME"</code> <code>"sr-Latn"</code> <code>"su"</code> <code>"fi"</code> <code>"sv"</code> <code>"tn"</code> <code>"tum"</code> <code>"tk"</code> <code>"tw"</code> <code>"wo"</code> <code>"el"</code> <code>"be"</code> <code>"bg"</code> <code>"ky"</code> <code>"kk"</code> <code>"mk"</code> <code>"mn"</code> <code>"sr"</code> <code>"tt"</code> <code>"tg"</code> <code>"uk"</code> <code>"ka"</code> <code>"hy"</code> <code>"yi"</code> <code>"iw"</code> <code>"ug"</code> <code>"ur"</code> <code>"ps"</code> <code>"sd"</code> <code>"fa"</code> <code>"ckb"</code> <code>"ti"</code> <code>"am"</code> <code>"ne"</code> <code>"mr"</code> <code>"hi"</code> <code>"bn"</code> <code>"pa"</code> <code>"gu"</code> <code>"or"</code> <code>"ta"</code> <code>"te"</code> <code>"kn"</code> <code>"ml"</code> <code>"si"</code> <code>"lo"</code> <code>"my"</code> <code>"km"</code> <code>"chr"</code> The parameter specifies the language to use for website.
region	string (region) Enum: <code>"AF"</code> <code>"AL"</code> <code>"DZ"</code> <code>"AS"</code> <code>"AD"</code> <code>"AO"</code> <code>"AI"</code> <code>"AG"</code> <code>"AR"</code> <code>"AM"</code> <code>"AU"</code> <code>"AT"</code> <code>"AZ"</code> <code>"BS"</code> <code>"BH"</code> <code>"BD"</code> <code>"BY"</code> <code>"BE"</code> <code>"BZ"</code> <code>"BJ"</code> <code>"BT"</code> <code>"BO"</code> <code>"BA"</code> <code>"BW"</code> <code>"BR"</code> <code>"VG"</code> <code>"BN"</code>

"BG"	"BF"	"BI"	"KH"	"CM"	"CA"	"CV"	"CF"	"TD"
"CL"	"CN"	"CO"	"CG"	"CD"	"CK"	"CR"	"CI"	"HR"
"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string
The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean
Default: `"true"`
The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.
A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.
As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/google-search-images-v2`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/google-search-images-v2?query=iph
```

Response samples

200

202

204

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Google Search Shopping

Returns products search results from Google based on a given search query (or many queries).

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings Queries to search on Google (e.g., bitcoin , 37th president of usa). It supports batching by sending arrays with up to 250 queries (e.g., query=text1&query=text2&query=text3). It allows multiple queries to be sent in one request and to save on network latency time.
pagesPerQuery	integer Default: 1 The parameter specifies the limit of pages to return from one query.
uule	string Google UULE parameter is used to encode a place or an exact location (with latitude and longitude) into a code. By using it you can see a Google result page like someone located at the specified location.
language	string (language)

Default: "en"

Enum: "en" "de" "es" "es-419" "fr" "hr" "it" "nl" "pl" "pt-BR" "pt-PT" "vi" "tr" "ru" "ar" "th" "ko" "zh-CN" "zh-TW" "ja" "ach" "af" "ak" "ig" "az" "ban" "ceb" "xx-bork" "bs" "br" "ca" "cs" "sn" "co" "cy" "da" "yo" "et" "xx-elmer" "eo" "eu" "ee" "tl" "fil" "fo" "fy" "gaa" "ga" "gd" "gl" "gn" "xx-hacker" "ht" "ha" "haw" "bem" "rn" "id" "ia" "xh" "zu" "is" "jw" "rw" "sw" "tlh" "kg" "mfe" "kri" "la" "lv" "to" "lt" "ln" "loz" "lua" "lg" "hu" "mg" "mt" "mi" "ms" "pcm" "no" "nso" "ny" "nn" "uz" "oc" "om" "xx-pirate" "ro" "rm" "qu" "nyn" "crs" "sq" "sk" "sl" "so" "st" "sr-ME" "sr-Latn" "su" "fi" "sv" "tn" "tum" "tk" "tw" "wo" "el" "be" "bg" "ky" "kk" "mk" "mn" "sr" "tt" "tg" "uk" "ka" "hy" "yi" "iw" "ug" "ur" "ps" "sd" "fa" "ckb" "ti" "am" "ne" "mr" "hi" "bn" "pa" "gu" "or" "ta" "te" "kn" "ml" "si" "lo" "my" "km" "chr"

The parameter specifies the language to use for website.

region

string (region)

Enum: "AF" "AL" "DZ" "AS" "AD" "AO" "AI" "AG" "AR" "AM" "AU" "AT" "AZ" "BS" "BH" "BD" "BY" "BE" "BZ" "BJ" "BT" "BO" "BA" "BW" "BR" "VG" "BN" "BG" "BF" "BI" "KH" "CM" "CA" "CV" "CF" "TD" "CL" "CN" "CO" "CG" "CD" "CK" "CR" "CI" "HR" "CU" "CY" "CZ" "DK" "DJ" "DM" "DO" "EC" "EG" "SV" "EE" "ET" "FJ" "FI" "FR" "GA" "GM" "GE" "DE" "GH" "GI" "GR" "GL" "GT" "GG" "GY" "HT" "HN" "HK" "HU" "IS" "IN" "ID" "IQ" "IE" "IM" "IL" "IT" "JM" "JP" "JE" "JO" "KZ" "KE" "KI" "KW" "KG" "LA" "LV" "LB" "LS" "LY" "LI" "LT" "LU" "MG" "MW" "MY" "MV" "ML" "MT" "MU" "MX" "FM" "MD" "MN" "ME" "MS" "MA" "MQ" "MZ" "MM" "NA" "NR" "NP" "NL" "NZ" "NI" "NE" "NG" "NU" "MK" "NO" "OM" "PK" "PS" "PA" "PG" "PY" "PE" "PH" "PN" "PL" "PT" "PR" "QA" "RO" "RU" "RW" "WS" "SM" "ST" "SA" "SN" "RS" "SC" "SL" "SG" "SK" "SI" "SB" "SO" "ZA" "KR" "ES" "LK" "SH" "VC" "SR" "SE" "CH" "TW" "TJ" "TZ" "TH" "TL" "TG" "TO" "TT" "TN" "TR" "TM" "VI" "UG" "UA" "AE" "GB" "US" "UY" "UZ" "VU" "VE" "VN" "ZM" "ZW"

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean

Default: "true"

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/google-search-shopping`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/google-search-shopping?query=iphc"
```

Response samples

200

202

204

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Google Search Careers

Allows scraping search results from Google Careers.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings Queries to search on Google (e.g., bitcoin , 37th president of usa). It supports batching by sending arrays with up to 250 queries (e.g., query=text1&query=text2&query=text3). It allows multiple queries to be sent in one request and to save on network latency time.
pagesPerQuery	integer Default: 1 The parameter specifies the limit of pages to return from one query.
language	string (language) Default: "en" Enum: "en" "de" "es" "es-419" "fr" "hr" "it" "nl" "pl" "pt-BR" "pt-PT" "vi" "tr" "ru" "ar" "th" "ko" "zh-CN" "zh-TW" "ja" "ach" "af" "ak" "ig" "az" "ban" "ceb" "xx-bork" "bs" "br" "ca" "cs"

"sn"	"co"	"cy"	"da"	"yo"	"et"	"xx-elmer"	"eo"	
"eu"	"ee"	"tl"	"fil"	"fo"	"fy"	"gaa"	"ga"	"gd"
"gl"	"gn"	"xx-hacker"	"ht"	"ha"	"haw"	"bem"	"rn"	
"id"	"ia"	"xh"	"zu"	"is"	"jw"	"rw"	"sw"	"tlh"
"kg"	"mfe"	"kri"	"la"	"lv"	"to"	"lt"	"ln"	"loz"
"lua"	"lg"	"hu"	"mg"	"mt"	"mi"	"ms"	"pcm"	"no"
"nso"	"ny"	"nn"	"uz"	"oc"	"om"	"xx-pirate"	"ro"	
"rm"	"qu"	"nyn"	"crs"	"sq"	"sk"	"sl"	"so"	"st"
"sr-ME"	"sr-Latn"	"su"	"fi"	"sv"	"tn"	"tum"	"tk"	
"tw"	"wo"	"el"	"be"	"bg"	"ky"	"kk"	"mk"	"mn"
"sr"	"tt"	"tg"	"uk"	"ka"	"hy"	"yi"	"iw"	"ug"
"ur"	"ps"	"sd"	"fa"	"ckb"	"ti"	"am"	"ne"	"mr"
"hi"	"bn"	"pa"	"gu"	"or"	"ta"	"te"	"kn"	"ml"
"si"	"lo"	"my"	"km"	"chr"				

The parameter specifies the language to use for website.

region

string (region)

Enum:	"AF"	"AL"	"DZ"	"AS"	"AD"	"AO"	"AI"	"AG"	"AR"
"AM"	"AU"	"AT"	"AZ"	"BS"	"BH"	"BD"	"BY"	"BE"	
"BZ"	"BJ"	"BT"	"BO"	"BA"	"BW"	"BR"	"VG"	"BN"	
"BG"	"BF"	"BI"	"KH"	"CM"	"CA"	"CV"	"CF"	"TD"	
"CL"	"CN"	"CO"	"CG"	"CD"	"CK"	"CR"	"CI"	"HR"	
"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"	
"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"	
"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"	
"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"	
"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"	
"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"	
"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"	
"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"	
"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"	
"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"	
"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"	
"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"	
"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"	
"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"	
"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"	
"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"	
"ZW"									

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

- **401** Wrong or missing API Key (token).
- **402** Past due invoices or a payment method not connected.
- **422** Wrong query url parameters.

GET /google-search-careers

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/google-search-careers?query=devel
```

Response samples

202

204

401

402

422

Content type

application/json

Copy

```
{
  "id": "your-request-id",
  "status": "Pending",
  "results_location": "https://api.outscraper.cloud/requests/your-request"
}
```

Google Shopping Reviews

Returns reviews from Google product based on a given search query (or many queries).

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Product links or product IDs (e.g., `https://www.google.com/shopping/product/7016166685587850095`, `7016166685587850095`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

perQuery

integer

Default: `100`

The parameter specifies the limit of items to return from one query.

uule

string

Google UULE parameter is used to encode a place or an exact location (with latitude and longitude) into a code. By using it you can see a Google result page like someone located at the specified location.

language

string (language)

Default: `"en"`

Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"` `"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"` `"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"` `"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"` `"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"` `"eu"` `"ee"` `"tl"` `"fil"` `"fo"` `"fy"` `"gaa"` `"ga"` `"gd"` `"gl"` `"gn"` `"xx-hacker"` `"ht"` `"ha"` `"haw"` `"bem"` `"rn"` `"id"` `"ia"` `"xh"` `"zu"` `"is"` `"jw"` `"rw"` `"sw"` `"tlh"` `"kg"` `"mfe"` `"kri"` `"la"` `"lv"` `"to"` `"lt"` `"ln"` `"loz"` `"lua"` `"lg"` `"hu"` `"mg"` `"mt"` `"mi"` `"ms"` `"pcm"` `"no"` `"nso"` `"ny"` `"nn"` `"uz"` `"oc"` `"om"` `"xx-pirate"` `"ro"` `"rm"` `"qu"` `"nyn"` `"crs"` `"sq"` `"sk"` `"sl"` `"so"` `"st"` `"sr-ME"` `"sr-Latn"` `"su"` `"fi"` `"sv"` `"tn"` `"tum"` `"tk"` `"tw"` `"wo"` `"el"` `"be"` `"bg"` `"ky"` `"kk"` `"mk"` `"mn"` `"sr"` `"tt"` `"tg"` `"uk"` `"ka"` `"hy"` `"yi"` `"iw"` `"ug"` `"ur"` `"ps"` `"sd"` `"fa"` `"ckb"` `"ti"` `"am"` `"ne"` `"mr"` `"hi"` `"bn"` `"pa"` `"gu"` `"or"` `"ta"` `"te"` `"kn"` `"ml"` `"si"` `"lo"` `"my"` `"km"` `"chr"`

The parameter specifies the language to use for website.

region

string (region)

Enum: `"AF"` `"AL"` `"DZ"` `"AS"` `"AD"` `"AO"` `"AI"` `"AG"` `"AR"` `"AM"` `"AU"` `"AT"` `"AZ"` `"BS"` `"BH"` `"BD"` `"BY"` `"BE"` `"BZ"` `"BJ"` `"BT"` `"BO"` `"BA"` `"BW"` `"BR"` `"VG"` `"BN"` `"BG"` `"BF"` `"BI"` `"KH"` `"CM"` `"CA"` `"CV"` `"CF"` `"TD"` `"CL"` `"CN"` `"CO"` `"CG"` `"CD"` `"CK"` `"CR"` `"CI"` `"HR"`

"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string
The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean
Default: `"true"`
The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.
A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.
As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean
Default: `"false"`
The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/google-shopping-reviews`

Request samples

[cURL](#)[cURL \(async\)](#)[Copy](#)

```
curl -X GET "https://api.outscraper.cloud/google-shopping-reviews?query=701"
```

Response samples

[200](#)[202](#)[204](#)[401](#)[402](#)[422](#)

Content type

application/json

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Google Trends

Allows scraping results from Google Trends.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings
Queries to search (e.g., `tesla`, `tesla | toyota`).
It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

timeframe

string
Default: `"now 1-d"`
Enum: `"now 1-H"` `"now 4-H"` `"now 1-d"` `"now 7-d"` `"today 1-m"` `"today 3-m"` `"today 12-m"` `"today 5-y"` `"all"`
The parameter specifies one of the timeframes.

resolution

string
Default: `"CITY"`
Enum: `"CITY"` `"COUNTRY"` `"DMA"` `"REGION"`
The parameter specifies one of the resolutions.

region

string (region)
Enum: `"AF"` `"AL"` `"DZ"` `"AS"` `"AD"` `"AO"` `"AI"` `"AG"` `"AR"`
`"AM"` `"AU"` `"AT"` `"AZ"` `"BS"` `"BH"` `"BD"` `"BY"` `"BE"`
`"BZ"` `"BJ"` `"BT"` `"BO"` `"BA"` `"BW"` `"BR"` `"VG"` `"BN"`
`"BG"` `"BF"` `"BI"` `"KH"` `"CM"` `"CA"` `"CV"` `"CF"` `"TD"`
`"CL"` `"CN"` `"CO"` `"CG"` `"CD"` `"CK"` `"CR"` `"CI"` `"HR"`

"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string
The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean
Default: `"true"`
The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.
A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.
As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean
Default: `"false"`
The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/google-trends`

Request samples

[cURL](#)[cURL \(async\)](#)[Copy](#)

```
curl -X GET "https://api.outscraper.cloud/google-trends?query=tesla&async=f
```

Response samples

[202](#)[204](#)[401](#)[402](#)[422](#)

Content type

application/json

```
{
  "id": "your-request-id",
  "status": "Pending",
  "results_location": "https://api.outscraper.cloud/requests/your-request"
}
```

Trustpilot

Trustpilot

Returns data from Trustpilot businesses.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings Links to Trustpilot pages or domain names (e.g., <code>outscraper.com</code> , <code>https://www.trustpilot.com/review/outscraper.com</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
enrichment	Array of strings The parameter defines an enrichment or enrichments (e.g., <code>enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3</code>) you want to apply to the results. Available values: <code>domains_service</code> — Emails & Contacts Scraper: finds emails, social links, phones, and other contacts from websites, <code>emails_validator_service</code> — Email Address Verifier: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate, <code>disposable_email_checker</code> — Disposable Emails Checker: checks origins of email addresses (disposable, free, or corporate),

	<code>company_insights_service</code> — Company Insights: finds company details such as revenue, size, founding year, public status, etc, <code>phones_enricher_service</code> — Phone Numbers Enricher: returns phones carrier data (name/type), validates phones, ensures messages deliverability, <code>trustpilot_service</code> — Trustpilot Scraper: returns data from a list of businesses, <code>whitepages_phones</code> - Phone Identity Finder: returns insights about phone number owners (name, address, etc.), <code>ai_chain_info</code> - Chain Info: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting. Using enrichments increases the time of the response. You might want to use the <code>async=true</code> parameter to avoid getting timeouts.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /trustpilot

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/trustpilot?query=outscraper.com&e
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + { ... }
  ]
}
```

Trustpilot Search

Returns search results from Trustpilot.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings Company or category to search on Trustpilot (e.g., <code>real estate</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of items to get from one query.
skip	integer Default: <code>0</code> The parameter specifies the number of items to skip. It's commonly used in pagination.
enrichment	Array of strings The parameter defines an enrichment or enrichments (e.g., <code>enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3</code>) you want to apply to the results. Available values: <code>domains_service</code> — Emails & Contacts Scraper: finds emails, social links, phones, and other contacts from websites, <code>emails_validator_service</code> — Email Address Verifier: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate,

	<code>disposable_email_checker</code> — Disposable Emails Checker: checks origins of email addresses (disposable, free, or corporate), <code>company_insights_service</code> — Company Insights: finds company details such as revenue, size, founding year, public status, etc, <code>phones_enricher_service</code> — Phone Numbers Enricher: returns phones carrier data (name/type), validates phones, ensures messages deliverability, <code>trustpilot_service</code> — Trustpilot Scraper: returns data from a list of businesses, <code>whitepages_phones</code> - Phone Identity Finder: returns insights about phone number owners (name, address, etc.), <code>ai_chain_info</code> - Chain Info: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting. Using enrichments increases the time of the response. You might want to use the <code>async=true</code> parameter to avoid getting timeouts.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /trustpilot/search

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/trustpilot/search?query=real+estate"
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + { ... }
  ]
}
```

}

Trustpilot Reviews

Returns reviews from Trustpilot businesses.
In case no reviews were found by your search criteria, your search request will consume the usage of one review.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

<code>query</code> <code>required</code>	Array of strings Links to Trustpilot pages or domain names (e.g., <code>outscraper.com</code>, <code>https://www.trustpilot.com/review/outscraper.com</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
<code>limit</code>	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
<code>languages</code>	string Default: <code>"default"</code> Enum: <code>"default"</code> <code>"all"</code> <code>"en"</code> <code>"es"</code> <code>"de"</code> The parameter specifies one of the language filters.
<code>sort</code>	string Default: <code>" "</code> Value: <code>"recency"</code> The parameter specifies one of the sorting types.
<code>cutoff</code>	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
<code>fields</code>	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

	<code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /trustpilot/reviews

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/trustpilot/reviews?query=outscraper"
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + [ ... ]
  ]
}
```

YouTube

YouTube Search

Returns search results from YouTube.

AUTHORIZATIONS: > *ApiKeyAuth*QUERY PARAMETERS

query
required

Array of strings

Queries to search on YouTube (e.g., `funny cats videos`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

limit

integer

Default: `100`

The parameter specifies the limit of items to get from one query.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /youtube-search

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/youtube-search?query=cats&limit=1"
```

Response samples

200

202

204

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
```

```
- "data": [  
  + { ... }  
]  
}
```

YouTube Channel

Returns data from YouTube channels.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

<code>query</code> <code>required</code>	Array of strings Domain or link to YouTube channel (e.g., <code>https://www.youtube.com/@outscraper</code>, <code>outscraper</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
<code>fields</code>	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
<code>async</code>	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
<code>ui</code>	boolean Default: <code>"false"</code>

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /youtube-channel

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/youtube-channel?query=outscraper&
```

Response samples

200

202

204

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + { ... }
  ]
}
```

YouTube Comments

Returns comments from YouTube videos.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required

Array of strings
Video links or video IDs (e.g., `https://www.youtube.com/watch?v=ph5pHgk1aZ0`, `ph5pHgk1aZ0`).
It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

perQuery

integer
Default: `100`
The parameter specifies the limit of items to return from one query.

language

string (language)
Default: `"en"`
Enum: `"en"` `"de"` `"es"` `"es-419"` `"fr"` `"hr"` `"it"` `"nl"` `"pl"` `"pt-BR"` `"pt-PT"` `"vi"` `"tr"` `"ru"` `"ar"` `"th"` `"ko"` `"zh-CN"` `"zh-TW"` `"ja"` `"ach"` `"af"` `"ak"` `"ig"` `"az"` `"ban"` `"ceb"` `"xx-bork"` `"bs"` `"br"` `"ca"` `"cs"` `"sn"` `"co"` `"cy"` `"da"` `"yo"` `"et"` `"xx-elmer"` `"eo"`

"eu"	"ee"	"tl"	"fil"	"fo"	"fy"	"gaa"	"ga"	"gd"
"gl"	"gn"	"xx-hacker"	"ht"	"ha"	"haw"	"bem"	"rn"	
"id"	"ia"	"xh"	"zu"	"is"	"jw"	"rw"	"sw"	"tlh"
"kg"	"mfe"	"kri"	"la"	"lv"	"to"	"lt"	"ln"	"loz"
"lua"	"lg"	"hu"	"mg"	"mt"	"mi"	"ms"	"pcm"	"no"
"nso"	"ny"	"nn"	"uz"	"oc"	"om"	"xx-pirate"	"ro"	
"rm"	"qu"	"nyn"	"crs"	"sq"	"sk"	"sl"	"so"	"st"
"sr-ME"	"sr-Latn"	"su"	"fi"	"sv"	"tn"	"tum"	"tk"	
"tw"	"wo"	"el"	"be"	"bg"	"ky"	"kk"	"mk"	"mn"
"sr"	"tt"	"tg"	"uk"	"ka"	"hy"	"yi"	"iw"	"ug"
"ur"	"ps"	"sd"	"fa"	"ckb"	"ti"	"am"	"ne"	"mr"
"hi"	"bn"	"pa"	"gu"	"or"	"ta"	"te"	"kn"	"ml"
"si"	"lo"	"my"	"km"	"chr"				

The parameter specifies the language to use for website.

region

string (region)

Enum:	"AF"	"AL"	"DZ"	"AS"	"AD"	"AO"	"AI"	"AG"	"AR"
	"AM"	"AU"	"AT"	"AZ"	"BS"	"BH"	"BD"	"BY"	"BE"
	"BZ"	"BJ"	"BT"	"BO"	"BA"	"BW"	"BR"	"VG"	"BN"
	"BG"	"BF"	"BI"	"KH"	"CM"	"CA"	"CV"	"CF"	"TD"
	"CL"	"CN"	"CO"	"CG"	"CD"	"CK"	"CR"	"CI"	"HR"
	"CU"	"CY"	"CZ"	"DK"	"DJ"	"DM"	"DO"	"EC"	"EG"
	"SV"	"EE"	"ET"	"FJ"	"FI"	"FR"	"GA"	"GM"	"GE"
	"DE"	"GH"	"GI"	"GR"	"GL"	"GT"	"GG"	"GY"	"HT"
	"HN"	"HK"	"HU"	"IS"	"IN"	"ID"	"IQ"	"IE"	"IM"
	"IL"	"IT"	"JM"	"JP"	"JE"	"JO"	"KZ"	"KE"	"KI"
	"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
	"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
	"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
	"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
	"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
	"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
	"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
	"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
	"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
	"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
	"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
	"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /youtube-comments

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/youtube-comments?query=ph5pHgklaž"
```

Response samples

- 200
- 202
- 204
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Others

Reddit Comments

Returns comments from Reddit.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Reddit post URLs (e.g.,

`https://www.reddit.com/r/AskReddit/comments/abcdef/example_post_title/`).It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.**sort**

string

Default: `"best"`Enum: `"best"` `"top"` `"new"` `"controversial"` `"old"` `"qa"`

The parameter specifies one of the sorting types.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.**async**

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /reddit-comments

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/reddit-comments?query=https://www
```

Response samples

- 200
- 202
- 204
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
```

```
"status": "Success",
"data": [ ]
}
```

Indeed Job Search

Returns jobs from Indeed.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings Search links with search parameters (e.g., <code>https://www.indeed.com/jobs?q=&l=Fremont+Canyon%2C+CA</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of items to get from one query.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.

ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/indeed-search`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/indeed-search?query=https%3A%2F%2F"
```

Response samples

200

202

204

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Indeed Reviews

Returns reviews from Indeed companies.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings You can use direct links, and IDs of any Indeed company (e.g., <code>https://www.indeed.com/cmp/TEKsystems</code>, <code>TEKsystems</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
sort	string Default: <code>" "</code> Enum: <code>"helpfulness"</code> <code>"rating_desc"</code> The parameter specifies one of the sorting types.
cutoff	integer

	The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter. Therefore, the latest records will be at the beginning (newest first).
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

- **401** Wrong or missing API Key (token).
- **402** Past due invoices or a payment method not connected.
- **422** Wrong query url parameters.

GET /indeed/reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/indeed/reviews?query=TEKsystems&l
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Zillow Search

Returns listings from Zillow.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required

Array of strings

Search links with search parameters (e.g., `Jacksonville, FL`, `https://www.zillow.com/jacksonville-fl/sold/?searchQueryState=...`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

mainFilter

string

Default: `"for_sale"`

Enum: `"for_sale"` `"for_rent"` `"sold"`

The parameter specifies the of the main filters.

limit

integer

Default: `100`

The parameter specifies the limit of items to get from one query.

skip

integer

Default: `0`

The parameter specifies the number of items to skip. It's commonly used in pagination.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /zillow-search

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/zillow-search?query=Jacksonville?"
```

Response samples

200

202

204

401

402

422

Content type
application/json

{ }

Copy

Yelp Search

Returns search results from Yelp.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings Search links with search parameters (e.g., <code>https://www.yelp.com/search?find_desc=Restaurants&find_loc=San+Francisco%2C+CA</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of items to get from one query.
enrichment	Array of strings The parameter defines an enrichment or enrichments (e.g., <code>enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3</code>) you want to apply to the results. Available values: <code>domains_service</code> — Emails & Contacts Scraper: finds emails, social links, phones, and other contacts from websites, <code>emails_validator_service</code> — Email Address Verifier: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate,

	<code>disposable_email_checker</code> — Disposable Emails Checker: checks origins of email addresses (disposable, free, or corporate), <code>company_insights_service</code> — Company Insights: finds company details such as revenue, size, founding year, public status, etc, <code>phones_enricher_service</code> — Phone Numbers Enricher: returns phones carrier data (name/type), validates phones, ensures messages deliverability, <code>trustpilot_service</code> — Trustpilot Scraper: returns data from a list of businesses, <code>whitepages_phones</code> - Phone Identity Finder: returns insights about phone number owners (name, address, etc.), <code>ai_chain_info</code> - Chain Info: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting. Using enrichments increases the time of the response. You might want to use the <code>async=true</code> parameter to avoid getting timeouts.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /yelp-search

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/yelp-search?query=https%3A%2F%2Fv
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Yellow Pages Search

Returns search results from Yellow Pages.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required Array of strings
Categories to search for (e.g., `bars`, `restaurants`, `dentists`). It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

location string
Default: `"New York, NY"`
The parameter specifies where to search (e.g., `New York, NY`).

limit integer
Default: `100`
The parameter specifies the limit of items to get from one query.

region string (region)
Enum: `"AF"` `"AL"` `"DZ"` `"AS"` `"AD"` `"AO"` `"AI"` `"AG"` `"AR"`
`"AM"` `"AU"` `"AT"` `"AZ"` `"BS"` `"BH"` `"BD"` `"BY"` `"BE"`
`"BZ"` `"BJ"` `"BT"` `"BO"` `"BA"` `"BW"` `"BR"` `"VG"` `"BN"`
`"BG"` `"BF"` `"BI"` `"KH"` `"CM"` `"CA"` `"CV"` `"CF"` `"TD"`
`"CL"` `"CN"` `"CO"` `"CG"` `"CD"` `"CK"` `"CR"` `"CI"` `"HR"`
`"CU"` `"CY"` `"CZ"` `"DK"` `"DJ"` `"DM"` `"DO"` `"EC"` `"EG"`
`"SV"` `"EE"` `"ET"` `"FJ"` `"FI"` `"FR"` `"GA"` `"GM"` `"GE"`
`"DE"` `"GH"` `"GI"` `"GR"` `"GL"` `"GT"` `"GG"` `"GY"` `"HT"`
`"HN"` `"HK"` `"HU"` `"IS"` `"IN"` `"ID"` `"IQ"` `"IE"` `"IM"`
`"IL"` `"IT"` `"JM"` `"JP"` `"JE"` `"JO"` `"KZ"` `"KE"` `"KI"`

"KW"	"KG"	"LA"	"LV"	"LB"	"LS"	"LY"	"LI"	"LT"
"LU"	"MG"	"MW"	"MY"	"MV"	"ML"	"MT"	"MU"	"MX"
"FM"	"MD"	"MN"	"ME"	"MS"	"MA"	"MQ"	"MZ"	"MM"
"NA"	"NR"	"NP"	"NL"	"NZ"	"NI"	"NE"	"NG"	"NU"
"MK"	"NO"	"OM"	"PK"	"PS"	"PA"	"PG"	"PY"	"PE"
"PH"	"PN"	"PL"	"PT"	"PR"	"QA"	"RO"	"RU"	"RW"
"WS"	"SM"	"ST"	"SA"	"SN"	"RS"	"SC"	"SL"	"SG"
"SK"	"SI"	"SB"	"SO"	"ZA"	"KR"	"ES"	"LK"	"SH"
"VC"	"SR"	"SE"	"CH"	"TW"	"TJ"	"TZ"	"TH"	"TL"
"TG"	"TO"	"TT"	"TN"	"TR"	"TM"	"VI"	"UG"	"UA"
"AE"	"GB"	"US"	"UY"	"UZ"	"VU"	"VE"	"VN"	"ZM"
"ZW"								

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

enrichment

Array of strings

The parameter defines an enrichment or enrichments (e.g., `enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3`) you want to apply to the results.

Available values:

`domains_service` — **Emails & Contacts Scraper**: finds emails, social links, phones, and other contacts from websites,

`emails_validator_service` — **Email Address Verifier**: validates emails, checks deliverability, filters out blacklists, spam traps, and complainers, while significantly reducing your bounce rate,

`disposable_email_checker` — **Disposable Emails Checker**: checks origins of email addresses (disposable, free, or corporate),

`company_insights_service` — **Company Insights**: finds company details such as revenue, size, founding year, public status, etc,

`phones_enricher_service` — **Phone Numbers Enricher**: returns phones carrier data (name/type), validates phones, ensures messages deliverability,

`trustpilot_service` — **Trustpilot Scraper**: returns data from a list of businesses,

`whitepages_phones` - **Phone Identity Finder**: returns insights about phone number owners (name, address, etc.),

`ai_chain_info` - **Chain Info**: identifies if a business is part of a chain, adding a true/false indication to your data for smarter targeting.

Using enrichments increases the time of the response. You might want to use the `async=true` parameter to avoid getting timeouts.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).**— 402 Past due invoices or a payment method not connected.****— 422 Wrong query url parameters.**

GET /yellowpages-search

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/yellowpages-search?query=restaure"
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

AppStore Reviews

Returns reviews from AppStore apps.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required

Array of strings
You can use direct links, and IDs of any AppStore app (e.g.,
`https://apps.apple.com/us/app/telegram-messenger/id686449807`, `id686449807`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

`limit`

integer

Default: `100`

The parameter specifies the limit of reviews to get from one query.

`sort`

string

Default: `"mosthelpful"`

Enum: `"mosthelpful"` `"mostrecent"`

The parameter specifies one of the sorting types.

`cutoff`

integer

The parameter specifies the oldest timestamp value for items.

Using the `cutoff` parameter overwrites `sort` parameter. Therefore, the latest records will be at the beginning (newest first).

`fields`

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

`async`

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

`ui`

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

`webhook`

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished.

Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /appstore/reviews

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/appstore/reviews?query=https://a
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
```

```
"data": [ ]  
}
```

Glassdoor Reviews

Returns reviews from Glassdoor companies.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query required	Array of strings You can use direct links to any Glassdoor company (e.g., <code>'https://www.glassdoor.com/Reviews/Amazon-Reviews-E6036.htm'</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
sort	string Default: <code>"DATE"</code> Enum: <code>"DATE"</code> <code>"RELEVANCE"</code> The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code>

	The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /glassdoor/reviews

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/glassdoor/reviews?query=https%3A%3F"
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Airbnb Search

Returns search results from Airbnb.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required

Array of strings
Airbnb Search URLs (e.g., `https://www.airbnb.com/s/Italy/homes?tab_id=...`, `https://www.airbnb.com/s/Paris/homes?tab_id=...`).
It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

limit	integer Default: <code>100</code> The parameter specifies the limit of items to get from one query.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for **2** hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /airbnb/search

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/airbnb/search?query=https://www.a
```

Response samples

200**202****401****402****422**

Content type

application/json

Copy

{ }

Airbnb Reviews

Returns reviews from Airbnb accommodations.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

You can use direct links, and IDs of any Airbnb accommodation (e.g.,

`https://www.airbnb.com/rooms/927539322986647456`,
`1125445123101274851`).

It supports batching by sending arrays with up to `250` queries (e.g.,
`query=text1&query=text2&query=text3`). It allows multiple queries to
be sent in one request and to save on network latency time.

limit

integer

Default: `100`

The parameter specifies the limit of reviews to get from one query.

sort

string

Default: `"MOST_RECENT"`

Enum: `"MOST_RECENT"` `"RATING_DESC"` `"RATING_ASC"`

The parameter specifies one of the sorting types.

cutoff

integer

The parameter specifies the oldest timestamp value for items.

Using the `cutoff` parameter overwrites `sort` parameter. Therefore,
the latest records will be at the beginning (newest first).

fields

string

The parameter defines which fields you want to include with each item
returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper.
It can be set to `false` to open an HTTP connection and keep it open until
you got your results, or `true` (default) to just submit your requests to
Outscraper and retrieve them later (usually within 1-3 minutes) with the
[Request Results](#) endpoint. Each response is available for `2` hours after a
request has been completed.

A good practice is to send async requests and start checking the results
after the estimated execution time. Check out [this](#) Python implementation
as an example.

As most of the requests take some time to be executed the `async=true`
option is preferred to avoid HTTP requests timeouts.

ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/airbnb/reviews`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/airbnb/reviews?query=https://www.
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

GetApp Reviews

Returns reviews from GetApp apps.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings You can use direct links to any GetApp app (e.g., <code>https://www.getapp.com/customer-management-software/a/salesforce/reviews/</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
sort	string Default: <code>"recommended"</code> Enum: <code>"recommended"</code> <code>"most_recent"</code> <code>"least_recent"</code> <code>"highest_rated"</code> <code>"lowest_rated"</code> The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items.

Using the `cutoff` parameter overwrites `sort` parameter`. Therefore, the latest records will be at the beginning (newest first).

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished.

Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

- **401** Wrong or missing API Key (token).
- **402** Past due invoices or a payment method not connected.
- **422** Wrong query url parameters.

GET /getapp/reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/getapp/reviews?query=https%3A%2F%2F"
```

Response samples

202

401

402

422

Content type

application/json

Copy

```
{
  "id": "your-request-id",
  "status": "Pending",
  "results_location": "https://api.outscraper.cloud/requests/your-request"
}
```

Product Hunt Reviews

Returns reviews from Product Hunt.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Links to Product Hunt product pages, or page IDs (e.g., `https://www.producthunt.com/products/outscraper`, `outscraper`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
cursor	string The parameter specifies the next page cursor (<code>next_page_cursor</code>) from the previous chunk of records (usually <code>10</code>). It's commonly used in pagination.
sort	string Default: <code>"BEST"</code> Enum: <code>"BEST"</code> <code>"LATEST"</code> <code>"FAVORABLE"</code> <code>"CRITICAL"</code> The parameter specifies one of the sorting types.
cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
language	string (language) Default: <code>"en"</code> Enum: <code>"en"</code> <code>"de"</code> <code>"es"</code> <code>"es-419"</code> <code>"fr"</code> <code>"hr"</code> <code>"it"</code> <code>"nl"</code> <code>"pl"</code> <code>"pt-BR"</code> <code>"pt-PT"</code> <code>"vi"</code> <code>"tr"</code> <code>"ru"</code> <code>"ar"</code> <code>"th"</code> <code>"ko"</code> <code>"zh-CN"</code> <code>"zh-TW"</code> <code>"ja"</code> <code>"ach"</code> <code>"af"</code> <code>"ak"</code> <code>"ig"</code> <code>"az"</code> <code>"ban"</code> <code>"ceb"</code> <code>"xx-bork"</code> <code>"bs"</code> <code>"br"</code> <code>"ca"</code> <code>"cs"</code> <code>"sn"</code> <code>"co"</code> <code>"cy"</code> <code>"da"</code> <code>"yo"</code> <code>"et"</code> <code>"xx-elmer"</code> <code>"eo"</code> <code>"eu"</code> <code>"ee"</code> <code>"tl"</code> <code>"fil"</code> <code>"fo"</code> <code>"fy"</code> <code>"gaa"</code> <code>"ga"</code> <code>"gd"</code> <code>"gl"</code> <code>"gn"</code> <code>"xx-hacker"</code> <code>"ht"</code> <code>"ha"</code> <code>"haw"</code> <code>"bem"</code> <code>"rn"</code> <code>"id"</code> <code>"ia"</code> <code>"xh"</code> <code>"zu"</code> <code>"is"</code> <code>"jw"</code> <code>"rw"</code> <code>"sw"</code> <code>"tlh"</code> <code>"kg"</code> <code>"mfe"</code> <code>"kri"</code> <code>"la"</code> <code>"lv"</code> <code>"to"</code> <code>"lt"</code> <code>"ln"</code> <code>"loz"</code> <code>"lua"</code> <code>"lg"</code> <code>"hu"</code> <code>"mg"</code> <code>"mt"</code> <code>"mi"</code> <code>"ms"</code> <code>"pcm"</code> <code>"no"</code> <code>"nso"</code> <code>"ny"</code> <code>"nn"</code> <code>"uz"</code> <code>"oc"</code> <code>"om"</code> <code>"xx-pirate"</code> <code>"ro"</code> <code>"rm"</code> <code>"qu"</code> <code>"nyn"</code> <code>"crs"</code> <code>"sq"</code> <code>"sk"</code> <code>"sl"</code> <code>"so"</code> <code>"st"</code> <code>"sr-ME"</code> <code>"sr-Latn"</code> <code>"su"</code> <code>"fi"</code> <code>"sv"</code> <code>"tn"</code> <code>"tum"</code> <code>"tk"</code> <code>"tw"</code> <code>"wo"</code> <code>"el"</code> <code>"be"</code> <code>"bg"</code> <code>"ky"</code> <code>"kk"</code> <code>"mk"</code> <code>"mn"</code> <code>"sr"</code> <code>"tt"</code> <code>"tg"</code> <code>"uk"</code> <code>"ka"</code> <code>"hy"</code> <code>"yi"</code> <code>"iw"</code> <code>"ug"</code> <code>"ur"</code> <code>"ps"</code> <code>"sd"</code> <code>"fa"</code> <code>"ckb"</code> <code>"ti"</code> <code>"am"</code> <code>"ne"</code> <code>"mr"</code>

"hi" "bn" "pa" "gu" "or" "ta" "te" "kn" "ml"

"si" "lo" "my" "km" "chr"

The parameter specifies the language to use for website.

region

string (region)

Enum: "AF" "AL" "DZ" "AS" "AD" "AO" "AI" "AG" "AR"

"AM" "AU" "AT" "AZ" "BS" "BH" "BD" "BY" "BE"

"BZ" "BJ" "BT" "BO" "BA" "BW" "BR" "VG" "BN"

"BG" "BF" "BI" "KH" "CM" "CA" "CV" "CF" "TD"

"CL" "CN" "CO" "CG" "CD" "CK" "CR" "CI" "HR"

"CU" "CY" "CZ" "DK" "DJ" "DM" "DO" "EC" "EG"

"SV" "EE" "ET" "FJ" "FI" "FR" "GA" "GM" "GE"

"DE" "GH" "GI" "GR" "GL" "GT" "GG" "GY" "HT"

"HN" "HK" "HU" "IS" "IN" "ID" "IQ" "IE" "IM"

"IL" "IT" "JM" "JP" "JE" "JO" "KZ" "KE" "KI"

"KW" "KG" "LA" "LV" "LB" "LS" "LY" "LI" "LT"

"LU" "MG" "MW" "MY" "MV" "ML" "MT" "MU" "MX"

"FM" "MD" "MN" "ME" "MS" "MA" "MQ" "MZ" "MM"

"NA" "NR" "NP" "NL" "NZ" "NI" "NE" "NG" "NU"

"MK" "NO" "OM" "PK" "PS" "PA" "PG" "PY" "PE"

"PH" "PN" "PL" "PT" "PR" "QA" "RO" "RU" "RW"

"WS" "SM" "ST" "SA" "SN" "RS" "SC" "SL" "SG"

"SK" "SI" "SB" "SO" "ZA" "KR" "ES" "LK" "SH"

"VC" "SR" "SE" "CH" "TW" "TJ" "TZ" "TH" "TL"

"TG" "TO" "TT" "TN" "TR" "TM" "VI" "UG" "UA"

"AE" "GB" "US" "UY" "UZ" "VU" "VE" "VN" "ZM"

"ZW"

The parameter specifies the country to use for website. It's recommended to use it for a better search experience.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean

Default: "true"

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

	As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/producthunt-reviews`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/producthunt-reviews?query=outscraper"
```

Response samples

200

202

401

402

422

Content type
application/json

Copy

{ }

Tripadvisor Reviews

Returns reviews from Tripadvisor businesses.
In case no reviews were found by your search criteria, your search request will consume the usage of one review.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings
Links to Tripadvisor pages (e.g., `https://www.tripadvisor.com/Restaurant_Review-g187147-d12947099-Reviews-Mayfair_Garden-Paris_Ile_de_France.html`). It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

limit

integer
Default: `100`
The parameter specifies the limit of reviews to get from one query.

cutoff

integer
The parameter specifies the oldest timestamp value for items.
Using the `cutoff` parameter overwrites `sort` parameter`. Therefore, the latest records will be at the beginning (newest first).

fields

string

	The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

GET /tripadvisor-reviews

Request samples

- cURL
- cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/tripadvisor-reviews?query=https://"
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Tripadvisor Search

Returns from search results Tripadvisor

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query
required

Array of strings

Search links with search parameters (e.g., `https://www.tripadvisor.com/Search?q=rome`). It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). This allows multiple queries to be sent in one request, helping to save on network latency time.

SearchType

string

Default: `"a"`

Enum: `"a"` `"h"` `"e"` `"A"` `"v"`

The parameter specifies the type of search results you want to retrieve from Tripadvisor. You can choose from the following options:

- 'a' for All Results: Returns all available results for the search query.
- 'h' for Hotels: Filters results to show only hotels.
- 'e' for Restaurants: Filters results to show only restaurants.
- 'A' for Things to Do: Filters results to show activities and attractions.
- 'v' for Vacation Rentals: Filters results to show vacation rental properties.

limit

integer

Default: `100`

The parameter specifies the limit of items to get from one query.

skip

integer

Default: `0`

The parameter specifies the number of items to skip. It's commonly used in pagination.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 204 The request was finished with failure and has no results.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /tripadvisor-search

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/tripadvisor-search?query=https%3F"
```

Response samples

200

202

204

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    { }
  ]
}
```

G2 Reviews

Returns reviews from a list of products.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings Links to G2 products (e.g., <code>https://www.g2.com/products/outscraper</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
sort	string Default: <code>"g2_default"</code> Enum: <code>"g2_default"</code> <code>"most_recent"</code> <code>"most_helpful"</code> <code>"highest_rated"</code> <code>"lowest_rated"</code> The parameter specifies one of the sorting types.

cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for

2

 hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /g2/reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/g2/reviews?query=https://www.g2.c
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Walmart Reviews

Returns reviews from a list of products.

AUTHORIZATIONS: > *ApiKeyAuth*QUERY PARAMETERS

query
required

Array of strings

Links to Walmart products (e.g.,

`https://www.walmart.com/ip/Blackstone-Original-4-Burner-36-Propane-Omnivore-Griddle-with-Hard-Cover/1347629739`).It supports batching by sending arrays with up to `250` queries (e.g.,`query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.**limit**

integer

Default: `100`

The parameter specifies the limit of reviews to get from one query.

sort

string

Default: `"relevancy"`Enum: `"relevancy"` `"helpful"` `"submission-desc"`
`"submission-asc"` `"rating-desc"` `"rating-asc"`

The parameter specifies one of the sorting types.

cutoff

integer

The parameter specifies the oldest timestamp value for items.

Using the `cutoff` parameter overwrites `sort` parameter`. Therefore, the latest records will be at the beginning (newest first).**fields**

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.**async**

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: "false"

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

```
GET /walmart/reviews
```

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/walmart/reviews?query=https://www
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Target Reviews

Returns reviews from a list of products.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings Links to Target products (e.g., <code>https://www.target.com/p/apple-iphone-15-pro-max/-/A-89957794</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of reviews to get from one query.
sort	string Default: <code>"most_recent"</code> Enum: <code>"most_recent"</code> <code>"highest_rating"</code> <code>"lowest_rating"</code> <code>"helpfulness_desc"</code> The parameter specifies one of the sorting types.

cutoff	integer The parameter specifies the oldest timestamp value for items. Using the <code>cutoff</code> parameter overwrites <code>sort</code> parameter`. Therefore, the latest records will be at the beginning (newest first).
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the Request Results endpoint. Each response is available for <code>2</code> hours after a request has been completed. A good practice is to send async requests and start checking the results after the estimated execution time. Check out this Python implementation as an example. As most of the requests take some time to be executed the <code>async=true</code> option is preferred to avoid HTTP requests timeouts.
ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code> .
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for

2

 hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /target/reviews

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/target/reviews?query=https://www.
```

Response samples

200

202

401

402

422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [ ]
}
```

Twitter Profiles

Returns information from the list of Twitter profiles.

AUTHORIZATIONS: > *ApiKeyAuth*QUERY PARAMETERS

query
required

Array of strings

Links to Twitter pages or page usernames (e.g.,

`https://www.twitter.com/outscraper`, `outscraper`).It supports batching by sending arrays with up to `250` queries (e.g.,`query=text1&query=text2&query=text3`). It allows multiple queries tobe sent in one request and to save on network latency time.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper.

It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to

Outscraper and retrieve them later (usually within 1-3 minutes) with the

[Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished.

Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/twitter/profiles`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/twitter/profiles?query=outscraper"
```

Response samples

202

401

402

422

Content type

application/json

Copy

```
{
  "id": "your-request-id",
  "status": "Pending",
  "results_location": "https://api.outscraper.cloud/requests/your-request"
}
```

Tiktok Profiles

Returns information from the list of TikTok profiles.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Links to Tiktok pages or page usernames (e.g.,

`https://www.tiktok.com/@outscraper`, `outscraper`).

It supports batching by sending arrays with up to `250` queries (e.g.,

`query=text1&query=text2&query=text3`). It allows multiple queries to

be sent in one request and to save on network latency time.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished.

Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /tiktok/profiles

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/tiktok/profiles?query=outscraper&
```

Response samples

202

401

402

422

Content type

application/json

Copy

```
{
  "id": "your-request-id",
  "status": "Pending",
```

```
"results_location": "https://api.outscraper.cloud/requests/your-request"
}
```

Linkedin Profiles

Returns information from the list of Linkedin profiles.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings
URLs to profiles or profile IDs (e.g., `https://www.linkedin.com/in/realvlad/`, `realvlad`).
It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

fields

string
The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use `&fields=query,name` to return only the specific ones.

async

boolean
Default: `"true"`
The parameter defines the way you want to submit your task to Outscraper. It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.
A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.
As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean
Default: `"false"`
The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API.

Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET /linkedin/profiles

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/linkedin/profiles?query=realvlads"
```

Response samples

202

401

402

422

Content type

application/json

```
{  
  "id": "your-request-id",  
  "status": "Pending",  
  "results_location": "https://api.outscraper.cloud/requests/your-request"  
}
```

Linkedin Companies

Returns information from the list of Linkedin companies.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

URLs to companies or company IDs (e.g.,

`https://www.linkedin.com/company/outscraper/, outscraper`).

It supports batching by sending arrays with up to `250` queries (e.g.,

`query=text1&query=text2&query=text3`). It allows multiple queries to

be sent in one request and to save on network latency time.

fields

string

The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use

`&fields=query,name` to return only the specific ones.

async

boolean

Default: `"true"`

The parameter defines the way you want to submit your task to Outscraper.

It can be set to `false` to open an HTTP connection and keep it open until you got your results, or `true` (default) to just submit your requests to Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui	boolean Default: <code>"false"</code> The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the <code>async</code> parameter to <code>true</code>.
webhook	string The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/linkedin/companies`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/linkedin/companies?query=outscrap
```

Response samples

202

401

402

422

Content type
application/json

Copy

```
{
  "id": "your-request-id",
  "status": "Pending",
  "results_location": "https://api.outscraper.cloud/requests/your-request"
}
```

Linkedin Posts

Returns posts from Linkedin companies.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings URLs to companies or company IDs (e.g., <code>https://www.linkedin.com/company/outscraper/</code>, <code>outscraper</code>). It supports batching by sending arrays with up to <code>250</code> queries (e.g., <code>query=text1&query=text2&query=text3</code>). It allows multiple queries to be sent in one request and to save on network latency time.
limit	integer Default: <code>100</code> The parameter specifies the limit of items to get from one query.
fields	string The parameter defines which fields you want to include with each item returned in the response. By default, it returns all fields. Use <code>&fields=query,name</code> to return only the specific ones.
async	boolean Default: <code>"true"</code> The parameter defines the way you want to submit your task to Outscraper. It can be set to <code>false</code> to open an HTTP connection and keep it open until you got your results, or <code>true</code> (default) to just submit your requests to

Outscraper and retrieve them later (usually within 1-3 minutes) with the [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

A good practice is to send async requests and start checking the results after the estimated execution time. Check out [this](#) Python implementation as an example.

As most of the requests take some time to be executed the `async=true` option is preferred to avoid HTTP requests timeouts.

ui

boolean

Default: `"false"`

The parameter defines whether a task will be executed as a UI task. This is commonly used when you want to create a regular platform task with API. Using this parameter overwrites the `async` parameter to `true`.

webhook

string

The parameter defines the URL address (callback) to which Outscraper will create a POST request with a JSON body once a task/request is finished. Using this parameter overwrites the webhook from integrations.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/linkedin/posts`

Request samples

cURL

cURL (async)

Copy

```
curl -X GET "https://api.outscraper.cloud/linkedin/posts?query=outscraper&a"
```

Response samples

202

401

402

422

Content type

application/json

Copy

```
{
  "id": "your-request-id",
  "status": "Pending",
  "results_location": "https://api.outscraper.cloud/requests/your-request"
}
```

Phone Identity Finder (Whitepages)

Returns insights about phone number owners (name, address, etc.).

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Phone number (e.g., `+1 281 236 8208`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/whitepages-phones`

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/whitepages-phones?query=128123682"
```

Response samples

200**202****401****402****422**

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + { ... }
  ]
}
```

Phones Owners

Returns insights about phone number owners (name, address, etc.).

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query
required

Array of strings

Phone number (e.g., `+1 281 236 8208`).

It supports batching by sending arrays with up to `250` queries (e.g., `query=text1&query=text2&query=text3`). It allows multiple queries to be sent in one request and to save on network latency time.

Responses

— 200

The response contains the `status` of the request and `data` . Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— **401** Wrong or missing API Key (token).

— **402** Past due invoices or a payment method not connected.

— **422** Wrong query url parameters.

GET `/phones-owners`

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/phones-owners?query=12812368208"
```

Response samples

- 200
- 202
- 401
- 402
- 422

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + { ... }
  ]
}
```

Whitepages Addresses Scraper

Returns insights about addresses and their residents.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

query required	Array of strings Addresses (e.g., 321 California Ave, Palo Alto, CA 94306). It supports batching by sending arrays with up to 250 queries (e.g., query=text1&query=text2&query=text3). It allows multiple queries to be sent in one request and to save on network latency time.
-------------------	--

Responses

— 200

The response contains the `status` of the request and `data`. Data is an array where each element represents a response for a single query from the request.

— 202

The response contains a request ID that can be used to fetch results by using [Request Results](#) endpoint. Each response is available for `2` hours after a request has been completed.

— 401 Wrong or missing API Key (token).

— 402 Past due invoices or a payment method not connected.

— 422 Wrong query url parameters.

GET `/whitepages-addresses`

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/whitepages-addresses?query=321%20"
```

Response samples

200**202****401****402****422**

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  "data": [
    + { ... }
  ]
}
```


Requests

Request Results

Allows you to fetch responses from requests created with async API endpoints. You can fetch responses before the expiration time by request ID, or use webhooks to get the data once it's ready. Request status can be Pending, Success, or Failure. Each response is available for `2` hours after a request has been completed. Once the response is expired the status will be `Pending` again.

PATH PARAMETERS

<code>requestId</code> <code>required</code>	string Request ID provided by API endpoints at <code>["id"]</code> . Example: <code>32692d16-725c-4e66-b013-95e80e873b7e</code>
---	--

QUERY PARAMETERS

<code>flat</code>	boolean Default: <code>"false"</code> The parameter allows you to return flat results. All the results from queries will be combined in one array.
<code>convertFileResult</code>	boolean Default: <code>"true"</code> The parameter allows you to return only the link to the file result (<code>&convertFileResult=false</code>) without converting it to a JSON array. Works only for UI tasks where results are stored in files.

Responses

— 200

The response contains the `status` of the request and `data` in case the request is finished.

— **204** The request was finished with failure and has no results.

GET /requests/{requestId}

Request samples

- cURL
- Python
- PHP
- Node.js
- Go
- Java

Copy

```
curl -X GET "https://api.outscraper.cloud/requests/your-request-id"
```

Response samples

- 200
- 204

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": "your-request-id",
  "status": "Success",
  - "data": [
    + [ ... ]
  ]
}
```

Terminate Request

Allows you to terminate created requests.

PATH PARAMETERS

requestId	string
required	Request ID provided by API endpoints at ["id"]. Example: 32692d16-725c-4e66-b013-95e80e873b7e

Responses

- 200 Request terminated.
- 401 Wrong or missing API Key (token).

DELETE /requests/{requestId}

Request samples

cURL

Copy

```
curl -X DELETE "https://api.outscraper.cloud/requests/your-request-id"
```

Response samples

200 401

Content type
application/json

Copy

```
"Request 17dd74fc-242b-4fdc-b518-009502768cf3 terminated"
```

Requests History

Fetch up to 100 latest requests during the last 24 hours.

AUTHORIZATIONS: > ApiKeyAuth

QUERY PARAMETERS

type string

	Default: <code>"running"</code> The parameter allows you to filter requests by type (running/finished).
skip	integer Default: <code>0</code> The parameter specifies the number of items to skip. It's commonly used in pagination.
pageSize	integer Default: <code>25</code> The parameter specifies the number of requests to return.

Responses

- 200 Your latest request.
- 401 Wrong or missing API Key (token).

GET /requests

Request samples

- cURL
- Python
- Node.js

Copy

```
curl -X GET "https://api.outscraper.cloud/requests?type=finished" -H "X-API-Key: YOUR_API_KEY"
```

Response samples

- 200
- 401

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": "79e6d350-c6c9-449c-a890-7fe14f821ebe",
    "usage": "3"
  },
  - {
    "id": "15188338-029a-4d0c-afdd-318e8808d8fe",
    "usage": "10"
  },
  - {
    "id": "fd96b82c-6b37-49f0-b69f-b5c793d28284",
    "usage": "12"
  }
]
```

Outscraper Platform UI

Get Tasks

Fetch user tasks.

AUTHORIZATIONS: > *ApiKeyAuth*

QUERY PARAMETERS

query	string The parameter specifies the tag to search among the tasks.
lastId	string The parameter specifies the last task ID. It's commonly used in pagination.
pageSize	integer Default: 10 The parameter specifies the number of items to return.

Responses

- 200 User tasks.
- 401 Wrong or missing API Key (token).

GET /tasks

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/tasks" -H "X-API-KEY: YOUR-API-F"
```

Response samples

200 401

Content type
application/json

Copy Expand all Collapse all

```
{
  - "tasks": [
    + { ... }
  ],
  "has_more": true
}
```

Create Task

Allows you to create UI tasks.

REQUEST BODY SCHEMA: application/json

service_name	string ID of the service you want to use (e.g., <code>google_maps_service_v2</code>, <code>google_maps_reviews_service_v3</code>).
queries	Array of strings Queries to search for (e.g., <code>restaurants ny usa</code>, <code>bars ny usa</code>).
enrichments	Array of strings The parameter defines an enrichment or enrichments (e.g., <code>enrichment=enrichment1&enrichment=enrichment2&enrichment=enrichment3</code>) you want to apply to the results. Available values: <code>domains_service</code>, <code>emails_validator_service</code>, <code>disposable_email_checker</code>, <code>whatsapp_checker</code>, <code>imessage_checker</code>, <code>phones_enricher_service</code>, <code>trustpilot_service</code>, <code>company_insights_service</code>, etc. Use <code>&enrichment=domains_service&enrichment=emails_validator_service</code> to enrich data with Emails & Contacts Scraper (<code>domains_service</code>), and Email Address Verifier (<code>emails_validator_service</code>). It increases the time of the response.
tags	Array of strings

Responses

- 200 Task created.
- 401 Wrong or missing API Key (token).

POST

/tasks

Request samples

Payload

Content type

application/json

```
{
  "service_name": "google_maps_service_v2",
  "queries": [ ],
  "enrich": false,
  - "settings": {
    "output_extension": "xlsx",
    "output_columns": [ ]
  },
  - "tags": [
    "restaurant +1"
  ],
  - "enrichments": [
    "domains_service",
    "company_insights_service"
  ],
  - "categories": [
    "restaurant",
    "dentist"
  ],
  - "locations": [
    "SE>Stockholm"
  ],
  "language": "en",
  "region": "SE",
  "limit": 0,
  "organizationsPerQueryLimit": 500,
  "filters": [ ],
  "exactMatch": false,
  "useZipCodes": true,
  "dropDuplicates": true,
  "dropEmailDuplicates": false,
  "ignoreWithoutEmails": false,
  - "UISettings": {
    "isCustomQueries": false,
    "isCustomCategories": false,
    "isCustomLocations": false
  },
  "enrichLocations": true
}
```

Response samples

200**401**

Content type
application/json

Copy

```
{
  "id": "your-task-id"
}
```

Get Task

Fetch user task.

AUTHORIZATIONS: > *ApiKeyAuth*

PATH PARAMETERS

taskId	string
required	Task ID. Example: 20211211132758c8e9

Responses

- 200 User task.
- 401 Wrong or missing API Key (token).

GET /tasks/{taskId}

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/tasks/YOUR_TASK_ID" -H "X-API-KE
```

Response samples

200

401

Content type
application/json

Copy Expand all Collapse all

```
{
  - "metadata": {
    "service_name": "google_maps_service_v2",
    + "queries": [ ... ]
  },
  "updated": "2022-02-08T20:51:17.402668",
  "user_id": "YOUR_USER_ID",
  "status": "SUCCESS",
  "created": "2022-02-08T20:49:06.879078",
  "queue_task_id": "2b9aa187-281a-4d4e-a4c6-fbe941aaac34",
  - "results": [
    + { ... },
    + { ... }
  ],
  "id": "YOUR_TASK_ID"
}
```

Restart Task

Allows you to recreate tasks.

PATH PARAMETERS

taskId	string
required	Task ID. Example: 20211211132758c8e9

Responses

- 200 Task restarted.
- 401 Wrong or missing API Key (token).

PUT /tasks/{taskId}

Request samples

cURL

Copy

```
curl -X PUT "https://api.outscraper.cloud/tasks/your-task-id"
```

Response samples

- 200
- 401

Content type
application/json

Copy

```
"Task restarted"
```

Terminate Task

Allows you to terminate created tasks.

PATH PARAMETERS

taskId
required

string
Task ID. Example: 20211211132758c8e9

Responses

- 200 Task removed.
- 401 Wrong or missing API Key (token).

DELETE /tasks/{taskId}

Request samples

cURL

Copy

```
curl -X DELETE "https://api.outscraper.cloud/tasks/your-task-id"
```

Response samples

- 200
- 401

Content type
application/json

Copy

```
"Task removed"
```

Get Balance

Fetch user balance information.

AUTHORIZATIONS: > ApiKeyAuth

Responses

- 200 Profile Balance.
- 401 Wrong or missing API Key (token).

GET /profile/balance

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/profile/balance" -H "X-API-KEY:"
```

Response samples

200

401

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "balance": 1905.01,
  "account_status": "valid",
  - "upcoming_invoice": {
    "amount_due": 0,
    "applied_balance": 0,
    "total": 0,
    "subtotal": 0,
    "currency": "usd",
    "total_discount": 0,
    "period_start": 1654784241,
    "period_end": 1657376241,
    "collection_method": "charge_automatically",
    + "products_lines": [ ... ],
    "subscription_id": "sub_ID"
  },
  "coupon": { },
  "id": "cus_ID"
}
```

Get Invoices

Fetch user invoices.

AUTHORIZATIONS: > *ApiKeyAuth*

PATH PARAMETERS

lastId	string Last invoice ID. It's commonly used in pagination.
--------	--

Responses

- 200 User invoices.
- 401 Wrong or missing API Key (token).

GET /invoices

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/invoices" -H "X-API-KEY: YOUR-API-KEY"
```

Response samples

200 401

Content type
application/json

Copy Expand all Collapse all

```
{  
  "items": [ ],  
}
```

```
"has_more": false
}
```

Failed Webhook Calls

Fetch the latest 100 failed webhook calls during the last 24 hours

AUTHORIZATIONS: > *ApiKeyAuth*

Responses

- 200 Failed Webhooks.
- 401 Wrong or missing API Key (token).

GET /webhook-calls

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/webhook-calls" -H "X-API-KEY: YC
```

Response samples

200 401

Content type
application/json

Copy Expand all Collapse all

```
[  
  - {  
    "status": "Status code: 404",  
    "date": 1722949581  
  }  
]
```

Get Country Locations

Fetch country locations that you can use to search on Google Maps.

AUTHORIZATIONS: > *ApiKeyAuth*

Responses

— **200** Country Locations.

— **401** Wrong or missing API Key (token).

GET /locations

Request samples

cURL

Copy

```
curl -X GET "https://api.outscraper.cloud/locations?country=IT" -H "X-API-
```

Response samples

200

401

Content type

application/json

Copy

Expand all

Collapse all

```
{  
  - "items": [  
    + { ... }  
  ],  
  "supports_zip_codes": true  
}
```