

# Commands

Copy Page 

Wrangler offers a number of commands to manage your Cloudflare Workers.

- [docs](#) - Open this page in your default browser.
- [init](#) - Create a new project from a variety of web frameworks and templates.
- [d1](#) - Interact with D1.
- [vectorize](#) - Interact with Vectorize indexes.
- [hyperdrive](#) - Manage your Hyperdrives.
- [deploy](#) - Deploy your Worker to Cloudflare.
- [dev](#) - Start a local server for developing your Worker.
- [delete](#) - Delete your Worker from Cloudflare.
- [kv\\_namespace](#) - Manage Workers KV namespaces.
- [kv\\_key](#) - Manage key-value pairs within a Workers KV namespace.
- [kv\\_bulk](#) - Manage multiple key-value pairs within a Workers KV namespace in batches.
- [r2\\_bucket](#) - Manage Workers R2 buckets.
- [r2\\_object](#) - Manage Workers R2 objects.
- [secret](#) - Manage the secret variables for a Worker.
- [secret\\_bulk](#) - Manage multiple secret variables for a Worker.
- [secrets-store secret](#) - Manage account secrets within a secrets store.
- [secrets-store store](#) - Manage your store within secrets store.
- [workflows](#) - Manage and configure Workflows.
- [tail](#) - Start a session to livestream logs from a deployed Worker.
- [pages](#) - Configure Cloudflare Pages.
- [pipelines](#) - Configure Cloudflare Pipelines.

- [queues](#) - Configure Workers Queues.
- [login](#) - Authorize Wrangler with your Cloudflare account using OAuth.
- [logout](#) - Remove Wrangler's authorization for accessing your account.
- [whoami](#) - Retrieve your user information and test your authentication configuration.
- [versions](#) - Retrieve details for recent versions.
- [deployments](#) - Retrieve details for recent deployments.
- [rollback](#) - Rollback to a recent deployment.
- [dispatch-namespace](#) - Interact with a [dispatch namespace](#).
- [mtls-certificate](#) - Manage certificates used for mTLS connections.
- [cert](#) - Manage certificates used for mTLS and Certificate Authority (CA) chain connections.
- [types](#) - Generate types from bindings and module rules in configuration.
- [telemetry](#) - Configure whether Wrangler can collect anonymous usage data.
- [check](#) - Validate your Worker.

### Note

The following global flags work on every command:

- `--help` `boolean`
  - Show help.
- `--config` `string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` `string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## How to run Wrangler commands

This page provides a reference for Wrangler commands.

```
wrangler <COMMAND> <SUBCOMMAND> [PARAMETERS] [OPTIONS]
```

Since Cloudflare recommends [installing Wrangler locally](#) in your project (rather than globally), the way to run Wrangler will depend on your specific setup and package manager.

 **npm** yarn pnpm

```
npx wrangler <COMMAND> <SUBCOMMAND> [PARAMETERS] [OPTIONS]
```

You can add Wrangler commands that you use often as scripts in your project's `package.json` file:

```
{  
  ...  
  "scripts": {  
    "deploy": "wrangler deploy",  
    "dev": "wrangler dev"  
  },  
  ...  
}
```

You can then run them using your package manager of choice:

 **npm** yarn pnpm

```
npm run deploy
```

## docs

Open the Cloudflare developer documentation in your default browser.

```
wrangler docs [<COMMAND>]
```

- **COMMAND** `string` optional

- The Wrangler command you want to learn more about. This opens your default browser to the section of the documentation that describes the command.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## init

Create a new project via the [create-cloudflare-cli \(C3\) tool](#). A variety of web frameworks are available to choose from as well as templates. Dependencies are installed by default, with the option to deploy your project immediately.

```
wrangler init [<NAME>] [OPTIONS]
```

- **NAME** **string** optional (default: name of working directory)
  - The name of the Workers project. This is both the directory name and name property in the generated [Wrangler configuration](#).
- `--yes` **boolean** optional
  - Answer yes to any prompts for new projects.
- `--from-dash` **string** optional
  - Fetch a Worker initialized from the dashboard. This is done by passing the flag and the Worker name. `wrangler init --from-dash <WORKER_NAME>`.
  - The `--from-dash` command will not automatically sync changes made to the dashboard after the command is used. Therefore, it is recommended that you continue using the CLI.

The following global flags work on every command:

- `--help` **boolean**
    - Show help.
  - `--config` **string** (not supported by Pages)
    - Path to your [Wrangler configuration file](#).
  - `--cwd` **string**
    - Run as if Wrangler was started in the specified directory instead of the current working directory.
- 

## d1

Interact with Cloudflare's D1 service.

### create

Creates a new D1 database, and provides the binding and UUID that you will put in your Wrangler file.

```
wrangler d1 create <DATABASE_NAME> [OPTIONS]
```

- `DATABASE_NAME` **string** *required*
  - The name of the new D1 database.
- `--location` **string** *optional*
  - Provide an optional [location hint](#) for your database leader.
  - Available options include weur (Western Europe), eur (Eastern Europe), apac (Asia Pacific), oc (Oceania), wnam (Western North America), and enam (Eastern North America).

### info

Get information about a D1 database, including the current database size and state.

```
wrangler d1 info <DATABASE_NAME> [OPTIONS]
```

- **DATABASE\_NAME** **string** required
  - The name of the D1 database to get information about.
- **--json** **boolean** optional
  - Return output as JSON rather than a table.

## list

List all D1 databases in your account.

```
wrangler d1 list [OPTIONS]
```

- **--json** **boolean** optional
  - Return output as JSON rather than a table.

## delete

Delete a D1 database.

```
wrangler d1 delete <DATABASE_NAME> [OPTIONS]
```

- **DATABASE\_NAME** **string** required
  - The name of the D1 database to delete.
- **-y, --skip-confirmation** **boolean** optional
  - Skip deletion confirmation prompt.

## execute

Execute a query on a D1 database.

```
wrangler d1 execute <DATABASE_NAME> [OPTIONS]
```

### Note

You must provide either **--command** or **--file** for this command to run successfully.

- **DATABASE\_NAME** **string** required
  - The name of the D1 database to execute a query on.
- **--command** **string** optional
  - The SQL query you wish to execute.
- **--file** **string** optional
  - Path to the SQL file you wish to execute.
- **-y, --yes** **boolean** optional
  - Answer yes to any prompts.
- **--local** **boolean** (default: true) optional
  - Execute commands/files against a local database for use with [wrangler dev](#).
- **--remote** **boolean** (default: false) optional
  - Execute commands/files against a remote D1 database for use with [wrangler dev --remote](#).
- **--persist-to** **string** optional
  - Specify directory to use for local persistence (for use in combination with **--local**).
- **--json** **boolean** optional
  - Return output as JSON rather than a table.
- **--preview** **boolean** optional
  - Execute commands/files against a preview D1 database (as defined by `preview_database_id` in the [Wrangler configuration file](#)).

## export

Export a D1 database or table's schema and/or content to a `.sql` file.

```
wrangler d1 export <DATABASE_NAME> [OPTIONS]
```

- **DATABASE\_NAME** **string** required
  - The name of the D1 database to export.
- **--local** **boolean** (default: true) optional
  - Export from a local database for use with [wrangler dev](#).
- **--remote** **boolean** (default: false) optional
  - Export from a remote D1 database for use with [wrangler dev --remote](#).

- **--output** **string** required
  - Path to the SQL file for your export.
- **--table** **string** optional
  - The name of the table within a D1 database to export.
- **--no-data** **boolean** (default: false) optional
  - Controls whether export SQL file contains database data. Note that **--no-data=true** is not recommended due to a known wrangler limitation that interprets the value as false.
- **--no-schema** **boolean** (default: false) optional
  - Controls whether export SQL file contains database schema. Note that **--no-schema=true** is not recommended due to a known wrangler limitation that interprets the value as false.

## time-travel restore

Restore a database to a specific point-in-time using [Time Travel](#).

```
wrangler d1 time-travel restore <DATABASE_NAME> [OPTIONS]
```

- **DATABASE\_NAME** **string** required
  - The name of the D1 database to execute a query on.
- **--bookmark** **string** optional
  - A D1 bookmark representing the state of a database at a specific point in time.
- **--timestamp** **string** optional
  - A UNIX timestamp or JavaScript date-time string within the last 30 days.
- **--json** **boolean** optional
  - Return output as JSON rather than a table.

## time-travel info

Inspect the current state of a database for a specific point-in-time using [Time Travel](#).

```
wrangler d1 time-travel info <DATABASE_NAME> [OPTIONS]
```

- **DATABASE\_NAME** **string** required
  - The name of the D1 database to execute a query on.
- **--timestamp** **string** optional
  - A UNIX timestamp or JavaScript date-time string within the last 30 days.
- **--json** **boolean** optional
  - Return output as JSON rather than a table.

## migrations create

Create a new migration.

This will generate a new versioned file inside the `migrations` folder. Name your migration file as a description of your change. This will make it easier for you to find your migration in the `migrations` folder. An example filename looks like:

`0000_create_user_table.sql`

The filename will include a version number and the migration name you specify below.

```
wrangler d1 migrations create <DATABASE_NAME> <MIGRATION_NAME>
```

- **DATABASE\_NAME** **string** required
  - The name of the D1 database you wish to create a migration for.
- **MIGRATION\_NAME** **string** required
  - A descriptive name for the migration you wish to create.

## migrations list

View a list of unapplied migration files.

```
wrangler d1 migrations list <DATABASE_NAME> [OPTIONS]
```

- **DATABASE\_NAME** **string** required
  - The name of the D1 database you wish to list unapplied migrations for.
- **--local** **boolean** optional
  - Show the list of unapplied migration files on your locally persisted D1 database.

- `--remote` **boolean** (default: false) optional
  - Show the list of unapplied migration files on your remote D1 database.
- `--persist-to` **string** optional
  - Specify directory to use for local persistence (for use in combination with `--local`).
- `--preview` **boolean** optional
  - Show the list of unapplied migration files on your preview D1 database (as defined by `preview_database_id` in the [Wrangler configuration file](#)).

## migrations apply

Apply any unapplied migrations.

This command will prompt you to confirm the migrations you are about to apply. Confirm that you would like to proceed. After, a backup will be captured.

The progress of each migration will be printed in the console.

When running the apply command in a CI/CD environment or another non-interactive command line, the confirmation step will be skipped, but the backup will still be captured.

If applying a migration results in an error, this migration will be rolled back, and the previous successful migration will remain applied.

```
wrangler d1 migrations apply <DATABASE_NAME> [OPTIONS]
```

- `DATABASE_NAME` **string** required
  - The name of the D1 database you wish to apply your migrations on.
- `--env` **string** optional
  - Specify which environment configuration to use for D1 binding
- `--local` **boolean** (default: true) optional
  - Execute any unapplied migrations on your locally persisted D1 database.
- `--remote` **boolean** (default: false) optional
  - Execute any unapplied migrations on your remote D1 database.
- `--persist-to` **string** optional
  - Specify directory to use for local persistence (for use in combination with `--local`).

- `--preview` **boolean** optional
    - Execute any unapplied migrations on your preview D1 database (as defined by `preview_database_id` in the [Wrangler configuration file](#)).
- 

# hyperdrive

Manage [Hyperdrive](#) database configurations.

## create

Create a new Hyperdrive configuration.

```
wrangler hyperdrive create <CONFIG_NAME> [OPTIONS]
```

- `CONFIG_NAME` **string** required
  - The name of the Hyperdrive configuration to create.
- `--connection-string` **string** optional
  - The database connection string in the form `postgres://user:password@hostname:port/database`.
- `--origin-host` **string** optional
  - The hostname or IP address Hyperdrive should connect to.
- `--origin-port` **number** optional
  - The database port to connect to.
- `--origin-scheme` **string** optional
  - The scheme used to connect to the origin database, for example, `postgresql` or `postgres`.
- `--database` **string** optional
  - The database (name) to connect to. For example, `Postgres` or `defaultdb`.
- `--origin-user` **string** optional
  - The username used to authenticate to the database.
- `--origin-password` **string** optional
  - The password used to authenticate to the database.

- `--access-client-id` **string** optional
  - The Client ID of the Access token to use when connecting to the origin database, must be set with a Client Access Secret. Mutually exclusive with `origin-port`.
- `--access-client-secret` **string** optional
  - The Client Secret of the Access token to use when connecting to the origin database, must be set with a Client Access ID. Mutually exclusive with `origin-port`.
- `--caching-disabled` **boolean** optional
  - Disables the caching of SQL responses.
- `--max-age` **number** optional
  - Specifies max duration for which items should persist in the cache, cannot be set when caching is disabled.
- `--swr` **number** optional
  - Stale While Revalidate - Indicates the number of seconds cache may serve the response after it becomes stale, cannot be set when caching is disabled.
- `--ca-certificate-id` **string** optional
  - Sets custom CA certificate when connecting to origin database.
- `--mtls-certificate-id` **string** optional
  - Sets custom mTLS client certificates when connecting to origin database.
- `--sslmode` **string** optional
  - Sets SSL mode for CA verification. Must be `require` | `verify-ca` | `verify-full`.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## update

Update an existing Hyperdrive configuration.

```
wrangler hyperdrive update <ID> [OPTIONS]
```

- **ID** **string** required
  - The ID of the Hyperdrive configuration to update.
- **--name** **string** optional
  - The new name of the Hyperdrive configuration.
- **--connection-string** **string** optional
  - The database connection string in the form  
postgres://user:password@hostname:port/database.
- **--origin-host** **string** optional
  - The new database hostname or IP address Hyperdrive should connect to.
- **--origin-port** **string** optional
  - The new database port to connect to.
- **--origin-scheme** **string** optional
  - The scheme used to connect to the origin database, for example, postgresql or postgres.
- **--database** **string** optional
  - The new database (name) to connect to. For example, Postgres or defaultdb.
- **--origin-user** **string** optional
  - The new username used to authenticate to the database.
- **--origin-password** **string** optional
  - The new password used to authenticate to the database.
- **--access-client-id** **string** optional
  - The Client ID of the Access token to use when connecting to the origin database, must be set with a Client Access Secret. Mutually exclusive with origin-port.
- **--access-client-secret** **string** optional
  - The Client Secret of the Access token to use when connecting to the origin database, must be set with a Client Access ID. Mutually exclusive with origin-port.
- **--caching-disabled** **boolean** optional
  - Disables the caching of SQL responses.
- **--max-age** **number** optional

- Specifies max duration for which items should persist in the cache, cannot be set when caching is disabled.
- `--swr number` optional
  - Stale While Revalidate - Indicates the number of seconds cache may serve the response after it becomes stale, cannot be set when caching is disabled.
- `--ca-certificate-id string` optional
  - Sets custom CA certificate when connecting to origin database.
- `--mtls-certificate-id string` optional
  - Sets custom mTLS client certificates when connecting to origin database.
- `--sslmode string` optional
  - Sets SSL mode for CA verification. Must be require `|verify-ca|verify-full`.

The following global flags work on every command:

- `--help boolean`
  - Show help.
- `--config string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## list

List all Hyperdrive configurations.

```
wrangler hyperdrive list
```

The following global flags work on every command:

- `--help boolean`
  - Show help.
- `--config string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd string`

- Run as if Wrangler was started in the specified directory instead of the current working directory.

## delete

Delete an existing Hyperdrive configuration.

```
wrangler hyperdrive delete <ID>
```

- **ID** **string** required
  - The name of the Hyperdrive configuration to delete.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## get

Get an existing Hyperdrive configuration.

```
wrangler hyperdrive get <ID>
```

- **ID** **string** required
  - The name of the Hyperdrive configuration to get.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)

- Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## vectorize

Interact with a [Vectorize](#) vector database.

### create

Creates a new vector index, and provides the binding and name that you will put in your Wrangler file.

```
npx wrangler vectorize create <INDEX_NAME> [--dimensions=<NUM_DIMENSIONS>]
[--metric=<DISTANCE_METRIC>] [--description=<DESCRIPTION>]
```

- `INDEX_NAME` **string** required
  - The name of the new index to create. Must be unique for an account and cannot be changed after creation.
- `--dimensions` **number** required
  - The vector dimension width to configure the index for. Cannot be changed after creation.
- `--metric` **string** required
  - The distance metric to use for calculating vector distance. Must be one of cosine, euclidean, or dot-product.
- `--description` **string** optional
  - A description for your index.
- `--deprecated-v1` **boolean** optional
  - Create a legacy Vectorize index. Please note that legacy Vectorize indexes are on a [deprecation path](#).

# list

List all Vectorize indexes in your account, including the configured dimensions and distance metric.

```
npx wrangler vectorize list
```

- `--deprecated-v1` **boolean** optional
  - List legacy Vectorize indexes. Please note that legacy Vectorize indexes are on a [deprecation path](#).

# get

Get details about an individual index, including its configuration.

```
npx wrangler vectorize get <INDEX_NAME>
```

- `INDEX_NAME` **string** required
  - The name of the index to fetch details for.
- `--deprecated-v1` **boolean** optional
  - Get a legacy Vectorize index. Please note that legacy Vectorize indexes are on a [deprecation path](#).

# info

Get some additional information about an individual index, including the vector count and details about the last processed mutation.

```
npx wrangler vectorize info <INDEX_NAME>
```

- `INDEX_NAME` **string** required
  - The name of the index to fetch details for.

# delete

Delete a Vectorize index.

```
npx wrangler vectorize delete <INDEX_NAME> [OPTIONS]
```

- **INDEX\_NAME** **string** required
  - The name of the Vectorize index to delete.
- **--force** **boolean** optional
  - Skip confirmation when deleting the index (Note: This is not a recoverable operation).
- **--deprecated-v1** **boolean** optional
  - Delete a legacy Vectorize index. Please note that legacy Vectorize indexes are on a [deprecation path](#).

# insert

Insert vectors into an index.

```
npx wrangler vectorize insert <INDEX_NAME> [OPTIONS]
```

- **INDEX\_NAME** **string** required
  - The name of the Vectorize index to upsert vectors in.
- **--file** **string** required
  - A file containing the vectors to insert in newline-delimited JSON (JSON) format.
- **--batch-size** **number** optional
  - The number of vectors to insert at a time (default: 1000).
- **--deprecated-v1** **boolean** optional
  - Insert into a legacy Vectorize index. Please note that legacy Vectorize indexes are on a [deprecation path](#).

# upsert

Upsert vectors into an index. Existing vectors in the index would be overwritten.

```
npx wrangler vectorize upsert <INDEX_NAME> [OPTIONS]
```

- **INDEX\_NAME** **string** required
  - The name of the Vectorize index to upsert vectors in.
- **--file** **string** required
  - A file containing the vectors to insert in newline-delimited JSON (JSON) format.
- **--batch-size** **number** optional
  - The number of vectors to insert at a time (default: 5000).

## query

Query a Vectorize index for similar vectors.

```
npx wrangler vectorize query <INDEX_NAME> [OPTIONS]
```

- **INDEX\_NAME** **string** required
  - The name of the Vectorize index to query.
- **--vector** **array** optional
  - Vector against which the Vectorize index is queried. Either this or the `vector-id` param must be provided.
- **--vector-id** **string** optional
  - Identifier for a vector that is already present in the index against which the index is queried. Either this or the `vector` param must be provided.
- **--top-k** **number** optional
  - The number of vectors to query (default: 5).
- **--return-values** **boolean** optional
  - Enable to return vector values in the response (default: false).
- **--return-metadata** **string** optional

- Enable to return vector metadata in the response. Must be one of `none`, `indexed`, or `all` (default: `none`).
- `--namespace string` optional
  - Query response to only include vectors from this namespace.
- `--filter string` optional
  - Filter vectors based on this metadata filter. Example: `'{ 'p1': 'abc', 'p2': { '$ne': true }, 'p3': 10, 'p4': false, 'nested.p5': 'abcd' }'`

## get-vectors

Fetch vectors from a Vectorize index using the provided ids.

```
npx wrangler vectorize get-vectors <INDEX_NAME> [OPTIONS]
```

- `INDEX_NAME string` required
  - The name of the Vectorize index from which vectors need to be fetched.
- `--ids array` required
  - List of ids for which vectors must be fetched.

## delete-vectors

Delete vectors in a Vectorize index using the provided ids.

```
npx wrangler vectorize delete-vectors <INDEX_NAME> [OPTIONS]
```

- `INDEX_NAME string` required
  - The name of the Vectorize index from which vectors need to be deleted.
- `--ids array` required
  - List of ids corresponding to the vectors that must be deleted.

## create-metadata-index

Enable metadata filtering on the specified property.

```
npx wrangler vectorize create-metadata-index <INDEX_NAME> [OPTIONS]
```

- **INDEX\_NAME** **string** required
  - The name of the Vectorize index for which metadata index needs to be created.
- **--property-name** **string** required
  - Metadata property for which metadata filtering should be enabled.
- **--type** **string** required
  - Data type of the property. Must be one of `string`, `number`, or `boolean`.

## list-metadata-index

List metadata properties on which metadata filtering is enabled.

```
npx wrangler vectorize list-metadata-index <INDEX_NAME> [OPTIONS]
```

- **INDEX\_NAME** **string** required
  - The name of the Vectorize index for which metadata indexes needs to be fetched.

## delete-metadata-index

Disable metadata filtering on the specified property.

```
npx wrangler vectorize delete-metadata-index <INDEX_NAME> [OPTIONS]
```

- **INDEX\_NAME** **string** required
  - The name of the Vectorize index for which metadata index needs to be disabled.
- **--property-name** **string** required
  - Metadata property for which metadata filtering should be disabled.

# dev

Start a local server for developing your Worker.

```
wrangler dev [<SCRIPT>] [OPTIONS]
```

## Note

None of the options for this command are required. Many of these options can be set in your Wrangler file. Refer to the [Wrangler configuration](#) documentation for more information.

- **SCRIPT** **string**
  - The path to an entry point for your Worker. Only required if your [Wrangler configuration file](#) does not include a main key (for example, `main = "index.js"`).
- **--name** **string** optional
  - Name of the Worker.
- **--config, -c** **string[]** optional
  - Path(s) to [Wrangler configuration file](#). If not provided, Wrangler will use the nearest config file based on your current working directory.
  - You can provide multiple configuration files to run multiple Workers in one dev session like this: `wrangler dev -c ./wrangler.toml -c ../other-worker/wrangler.toml`. The first config will be treated as the *primary* Worker, which will be exposed over HTTP. The remaining config files will only be accessible via a service binding from the primary Worker.
- **--no-bundle** **boolean** (default: false) optional
  - Skip Wrangler's build steps. Particularly useful when using custom builds. Refer to [Bundling ↗](#) for more information.
- **--env** **string** optional
  - Perform on a specific environment.
- **--compatibility-date** **string** optional
  - A date in the form yyyy-mm-dd, which will be used to determine which version of the Workers runtime is used.
- **--compatibility-flags, --compatibility-flag** **string[]** optional

- Flags to use for compatibility checks.
- `--latest` **boolean** (default: true) optional
  - Use the latest version of the Workers runtime.
- `--ip` **string** optional
  - IP address to listen on, defaults to `localhost`.
- `--port` **number** optional
  - Port to listen on.
- `--inspector-port` **number** optional
  - Port for devtools to connect to.
- `--routes, --route` **string[]** optional
  - Routes to upload.
  - For example: `--route example.com/*`.
- `--host` **string** optional
  - Host to forward requests to, defaults to the zone of project.
- `--local-protocol` **'http'|'https'** (default: http) optional
  - Protocol to listen to requests on.
- `--https-key-path` **string** optional
  - Path to a custom certificate key.
- `--https-cert-path` **string** optional
  - Path to a custom certificate.
- `--local-upstream` **string** optional
  - Host to act as origin in local mode, defaults to `dev.host` or `route`.
- `--assets` **string** optional beta
  - Folder of static assets to be served. Replaces [Workers Sites](#). Visit [assets](#) for more information.
- `--site` **string** optional deprecated, use `--assets``
  - Folder of static assets for Workers Sites.

### **Warning**

Workers Sites is deprecated. Please use [Workers Assets](#) or [Pages](#).

- `--site-include` **string[]** optional deprecated

- Array of `.gitignore`-style patterns that match file or directory names from the sites directory. Only matched items will be uploaded.
- `--site-exclude string[]` optional deprecated
  - Array of `.gitignore`-style patterns that match file or directory names from the sites directory. Matched items will not be uploaded.
- `--upstream-protocol 'http'|'https'` (default: https) optional
  - Protocol to forward requests to host on.
- `--var key:value[]` optional
  - Array of `key:value` pairs to inject as variables into your code. The value will always be passed as a string to your Worker.
  - For example, `--var "git_hash:'$(git rev-parse HEAD)'" "test:123"` makes the `git_hash` and `test` variables available in your Worker's env.
  - This flag is an alternative to defining [vars](#) in your [Wrangler configuration file](#). If defined in both places, this flag's values will be used.
- `--define key:value[]` optional
  - Array of `key:value` pairs to replace global identifiers in your code.
  - For example, `--define "GIT_HASH:'$(git rev-parse HEAD)'"` will replace all uses of `GIT_HASH` with the actual value at build time.
  - This flag is an alternative to defining [define](#) in your [Wrangler configuration file](#). If defined in both places, this flag's values will be used.
- `--tsconfig string` optional
  - Path to a custom `tsconfig.json` file.
- `--minify boolean` optional
  - Minify the Worker.
- `--persist-to string` optional
  - Specify directory to use for local persistence.
- `--remote boolean` (default: false) optional
  - Develop against remote resources and data stored on Cloudflare's network.
- `--test-scheduled boolean` (default: false) optional
  - Exposes a `/__scheduled` fetch route which will trigger a scheduled event (Cron Trigger) for testing during development. To simulate different cron patterns, a cron query parameter can be passed in: `/__scheduled?cron=*****+*` or `/cdn-cgi/handler/scheduled?cron=*****+*`.

- `--log-level` `'debug'|'info'|'log'|'warn'|'error'|'none'` (default: log) optional
  - Specify Wrangler's logging level.
- `--show-interactive-dev-session` `boolean` (default: true if the terminal supports interactivity) optional
  - Show the interactive dev session.
- `--alias` `Array<string>`
  - Specify modules to alias using [module aliasing](#).

The following global flags work on every command:

- `--help` `boolean`
  - Show help.
- `--config` `string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` `string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

`wrangler dev` is a way to [locally test](#) your Worker while developing. With `wrangler dev` running, send HTTP requests to `localhost:8787` and your Worker should execute as expected. You will also see `console.log` messages and exceptions appearing in your terminal.

## deploy

Deploy your Worker to Cloudflare.

```
wrangler deploy [<SCRIPT>] [OPTIONS]
```

### Note

None of the options for this command are required. Also, many can be set in your Wrangler file. Refer to the [Wrangler configuration](#) documentation for more information.

- `SCRIPT` `string`

- The path to an entry point for your Worker. Only required if your [Wrangler configuration file](#) does not include a main key (for example, `main = "index.js"`).
- `--name string` optional
  - Name of the Worker.
- `--no-bundle boolean` (default: false) optional
  - Skip Wrangler's build steps. Particularly useful when using custom builds. Refer to [Bundling ↗](#) for more information.
- `--env string` optional
  - Perform on a specific environment.

### **Note**

If you're using the [Cloudflare Vite plugin](#), you select the environment at dev or build time via the `CLOUDFLARE_ENV` environment variable rather than the `--env` flag. Otherwise, environments are defined in your Worker config file as usual. For more detail on using environments with the Cloudflare Vite plugin, refer to the [plugin documentation](#).

- `--outdir string` optional
  - Path to directory where Wrangler will write the bundled Worker files.
- `--compatibility-date string` optional
  - A date in the form `yyyy-mm-dd`, which will be used to determine which version of the Workers runtime is used.
- `--compatibility-flags, --compatibility-flag string[]` optional
  - Flags to use for compatibility checks.
- `--latest boolean` (default: true) optional
  - Use the latest version of the Workers runtime.
- `--assets string` optional beta
  - Folder of static assets to be served. Replaces [Workers Sites](#). Visit [assets](#) for more information.
- `--site string` optional deprecated, use `--assets``
  - Folder of static assets for Workers Sites.

### **Warning**

Workers Sites is deprecated. Please use [Workers Assets](#) or [Pages](#).

- `--site-include string[]` optional deprecated
  - Array of `.gitignore`-style patterns that match file or directory names from the sites directory. Only matched items will be uploaded.
- `--site-exclude string[]` optional deprecated
  - Array of `.gitignore`-style patterns that match file or directory names from the sites directory. Matched items will not be uploaded.
- `--var key:value\[]` optional
  - Array of `key:value` pairs to inject as variables into your code. The value will always be passed as a string to your Worker.
  - For example, `--var git_hash:$(git rev-parse HEAD) test:123` makes the `git_hash` and `test` variables available in your Worker's env.
  - This flag is an alternative to defining [vars](#) in your [Wrangler configuration file](#). If defined in both places, this flag's values will be used.
- `--define key:value\[]` optional
  - Array of `key:value` pairs to replace global identifiers in your code.
  - For example, `--define GIT_HASH:$(git rev-parse HEAD)` will replace all uses of `GIT_HASH` with the actual value at build time.
  - This flag is an alternative to defining [define](#) in your [Wrangler configuration file](#). If defined in both places, this flag's values will be used.
- `--triggers, --schedule, --schedules string[]` optional
  - Cron schedules to attach to the deployed Worker. Refer to [Cron Trigger Examples](#).
- `--routes, --route string[]` optional
  - Routes where this Worker will be deployed.
  - For example: `--route example.com/*`.
- `--tsconfig string` optional
  - Path to a custom `tsconfig.json` file.
- `--minify boolean` optional
  - Minify the bundled Worker before deploying.
- `--dry-run boolean` (default: false) optional
  - Compile a project without actually deploying to live servers. Combined with `--outdir`, this is also useful for testing the output of `npx wrangler deploy`. It also gives developers a chance to upload our generated sourcemap to a service like Sentry, so

that errors from the Worker can be mapped against source code, but before the service goes live.

- `--keep-vars` **boolean** (default: false) optional
  - It is recommended best practice to treat your Wrangler developer environment as a source of truth for your Worker configuration, and avoid making changes via the Cloudflare dashboard.
  - If you change your environment variables in the Cloudflare dashboard, Wrangler will override them the next time you deploy. If you want to disable this behaviour set `keep-vars` to `true`.
  - Secrets are never deleted by a deployment whether this flag is true or false.
- `--dispatch-namespace` **string** optional
  - Specify the [Workers for Platforms dispatch namespace](#) to upload this Worker to.
- `--metafile` **string** optional
  - Specify a file to write the build metadata from esbuild to. If flag is used without a path string, this defaults to `bundle-meta.json` inside the directory specified by `--outdir`. This can be useful for understanding the bundle size.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

---

## delete

Delete your Worker and all associated Cloudflare developer platform resources.

```
wrangler delete [<SCRIPT>] [OPTIONS]
```

- **SCRIPT** **string**
  - The path to an entry point for your Worker. Only required if your [Wrangler configuration file](#) does not include a main key (for example, `main = "index.js"`).
- **--name** **string** optional
  - Name of the Worker.
- **--env** **string** optional
  - Perform on a specific environment.
- **--dry-run** **boolean** (default: false) optional
  - Do not actually delete the Worker. This is useful for testing the output of `wrangler delete`.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

---

## kv namespace

Manage Workers KV namespaces.

### Note

The `kv ...` commands allow you to manage your Workers KV resources in the Cloudflare network. Learn more about using Workers KV with Wrangler in the [Workers KV guide](#).

### Warning

Since version 3.60.0, Wrangler supports the `kv ...` syntax. If you are using versions below 3.60.0, the command follows the `kv: ...` syntax. Learn more about the deprecation of the `kv: ...` syntax in the [Wrangler commands](#) for KV page.

# create

Create a new namespace.

```
wrangler kv namespace create <NAMESPACE> [OPTIONS]
```

- **NAMESPACE** **string** required
  - The name of the new namespace.
- **--env** **string** optional
  - Perform on a specific environment.
- **--preview** **boolean** optional
  - Interact with a preview namespace (the `preview_id` value).

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example of using the `create` command to create a KV namespace called `MY_KV`.

```
npx wrangler kv namespace create "MY_KV"
```

```
🌀 Creating namespace with title "worker-MY_KV"
```

```
🌟 Success!
```

```
Add the following to your configuration file in your kv_namespaces array:
```

```
kv_namespaces = [  
  { binding = "MY_KV", id = "e29b263ab50e42ce9b637fa8370175e8" }  
]
```

The following is an example of using the create command to create a preview KV namespace called MY\_KV.

```
npx wrangler kv namespace create "MY_KV" --preview
```

```
🌀 Creating namespace with title "my-site-MY_KV_preview"
🌟 Success!
Add the following to your configuration file in your kv_namespaces array:
kv_namespaces = [
  { binding = "MY_KV", preview_id = "15137f8edf6c09742227e99b08aaf273" }
]
```

## list

List all KV namespaces associated with the current account ID.

```
wrangler kv namespace list
```

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example that passes the Wrangler command through the jq command:

```
npx wrangler kv namespace list | jq "."
```

```
[
  {
    "id": "06779da6940b431db6e566b4846d64db",
    "title": "TEST_NAMESPACE"
  },
  {
    "id": "32ac1b3c2ed34ed3b397268817dea9ea",
    "title": "STATIC_CONTENT"
  }
]
```

## delete

Delete a given namespace.

```
wrangler kv namespace delete {--binding=<BINDING>|--namespace-id=
<NAMESPACE_ID>} [OPTIONS]
```

### Warning

This command requires `--binding` or `--namespace-id`.

- `--binding` **string**
  - The binding name of the namespace, as stored in the Wrangler file, to delete.
- `--namespace-id` **string**
  - The ID of the namespace to delete.
- `--env` **string** optional
  - Perform on a specific environment.
- `--preview` **boolean** optional
  - Interact with a preview namespace instead of production.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)

- Path to your [Wrangler configuration file](#).
- `--cwd` `string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example of deleting a KV namespace called MY\_KV.

```
npx wrangler kv namespace delete --binding=MY_KV
```

```
Are you sure you want to delete namespace f7b02e7fc70443149ac906dd81ec1791?
[y/n]
yes
Deleting namespace f7b02e7fc70443149ac906dd81ec1791
Deleted namespace f7b02e7fc70443149ac906dd81ec1791
```

The following is an example of deleting a preview KV namespace called MY\_KV.

```
npx wrangler kv namespace delete --binding=MY_KV --preview
```

```
Are you sure you want to delete namespace 15137f8edf6c09742227e99b08aaf273?
[y/n]
yes
Deleting namespace 15137f8edf6c09742227e99b08aaf273
Deleted namespace 15137f8edf6c09742227e99b08aaf273
```

## kv key

Manage key-value pairs within a Workers KV namespace.

### Note

The `kv ...` commands allow you to manage your Workers KV resources in the Cloudflare network. Learn more about using Workers KV with Wrangler in the [Workers KV guide](#).

 **Warning**

Since version 3.60.0, Wrangler supports the `kv ...` syntax. If you are using versions below 3.60.0, the command follows the `kv:...` syntax. Learn more about the deprecation of the `kv:...` syntax in the [Wrangler commands](#) for KV page.

## put

Write a single key-value pair to a particular namespace.

```
wrangler kv key put <KEY> {<VALUE>|--path=<PATH>} {--binding=<BINDING>|--  
namespace-id=<NAMESPACE_ID>} [OPTIONS]
```

 **Warning**

This command requires a `VALUE` or `--path`.

This command requires a `--binding` or `--namespace-id` flag.

- `KEY` **string** required
  - The key to write to.
- `VALUE` **string** optional
  - The value to write.
- `--path` optional
  - When defined, the value is loaded from the file at `--path` rather than reading it from the `VALUE` argument. This is ideal for security-sensitive operations because it avoids saving keys and values into your terminal history.
- `--binding` **string**
  - The binding name of the namespace, as stored in the Wrangler file, to write to.
- `--namespace-id` **string**
  - The ID of the namespace to write to.
- `--env` **string** optional
  - Perform on a specific environment.
- `--preview` **boolean** optional
  - Interact with a preview namespace instead of production.

- `--ttl` **number** optional
  - The lifetime (in number of seconds) that the key-value pair should exist before expiring. Must be at least 60 seconds. This option takes precedence over the expiration option.
- `--expiration` **number** optional
  - The timestamp, in UNIX seconds, indicating when the key-value pair should expire.
- `--metadata` **string** optional
  - Any (escaped) JSON serialized arbitrary object to a maximum of 1024 bytes.
- `--local` **boolean** (default: true) optional
  - Interact with locally persisted data.
- `--remote` **boolean** (default: false) optional
  - Interact with remote storage.
- `--persist-to` **string** optional
  - Specify directory for locally persisted data.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example that puts a key-value into the namespace with binding name of MY\_KV.

```
npx wrangler kv key put --binding=MY_KV "my-key" "some-value"
```

Writing the value "some-value" to key "my-key" on namespace  
f7b02e7fc70443149ac906dd81ec1791.

The following is an example that puts a key-value into the preview namespace with binding name of MY\_KV.

```
npx wrangler kv key put --binding=MY_KV --preview "my-key" "some-value"
```

Writing the value "some-value" to key "my-key" on namespace 15137f8edf6c09742227e99b08aaf273.

The following is an example that puts a key-value into a namespace, with a time-to-live value of 10000 seconds.

```
npx wrangler kv key put --binding=MY_KV "my-key" "some-value" --ttl=10000
```

Writing the value "some-value" to key "my-key" on namespace f7b02e7fc70443149ac906dd81ec1791.

The following is an example that puts a key-value into a namespace, where the value is read from the value.txt file.

```
npx wrangler kv key put --binding=MY_KV "my-key" --path=value.txt
```

Writing the contents of value.txt to the key "my-key" on namespace f7b02e7fc70443149ac906dd81ec1791.

## list

Output a list of all keys in a given namespace.

```
wrangler kv key list {--binding=<BINDING>|--namespace-id=<NAMESPACE_ID>}  
[OPTIONS]
```

 **Warning**

This command requires `--binding` or `--namespace-id`.

- `--binding` **string**
  - The binding name of the namespace, as stored in the Wrangler file, to list from.
- `--namespace-id` **string**
  - The ID of the namespace to list from.
- `--env` **string** optional
  - Perform on a specific environment.
- `--preview` **boolean** optional
  - Interact with a preview namespace instead of production.
- `--prefix` **string** optional
  - Only list keys that begin with the given prefix.
- `--local` **boolean** (default: true) optional
  - Interact with locally persisted data.
- `--remote` **boolean** (default: false) optional
  - Interact with remote storage.
- `--persist-to` **string** optional
  - Specify directory for locally persisted data.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

Below is an example that passes the Wrangler command through the `jq` command:

```
npx wrangler kv key list --binding=MY_KV --prefix="public" | jq "."
```

```
[
  {
    "name": "public_key"
  },
  {
    "name": "public_key_with_expiration",
    "expiration": "2019-09-10T23:18:58Z"
  }
]
```

## get

Read a single value by key from the given namespace.

```
wrangler kv key get <KEY> {--binding=<BINDING>|--namespace-id=
<NAMESPACE_ID>} [OPTIONS]
```

### Warning

Exactly one of `--binding` or `--namespace-id` is required.

- **KEY** **string** required
  - The key value to get.
- **--binding** **string**
  - The binding name of the namespace, as stored in the Wrangler file, to get from.
- **--namespace-id** **string**
  - The ID of the namespace to get from.
- **--env** **string** optional
  - Perform on a specific environment.
- **--preview** **boolean** optional
  - Interact with a preview namespace instead of production.
- **--text** **boolean** optional

- Decode the returned value as a UTF-8 string.
- `--local` **boolean** (default: true) optional
  - Interact with locally persisted data.
- `--remote` **boolean** (default: false) optional
  - Interact with remote storage.
- `--persist-to` **string** optional
  - Specify directory for locally persisted data.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example that gets the value of the "my-key" key from the KV namespace with binding name MY\_KV.

```
npx wrangler kv key get --binding=MY_KV "my-key"
```

```
value
```

## delete

Remove a single key value pair from the given namespace.

```
wrangler kv key delete <KEY> {--binding=<BINDING>|--namespace-id=<NAMESPACE_ID>} [OPTIONS]
```

 **Warning**

Exactly one of `--binding` or `--namespace-id` is required.

- `KEY` **string** required
  - The key value to get.
- `--binding` **string**
  - The binding name of the namespace, as stored in the Wrangler file, to delete from.
- `--namespace-id` **string**
  - The ID of the namespace to delete from.
- `--env` **string** optional
  - Perform on a specific environment.
- `--preview` **boolean** optional
  - Interact with a preview namespace instead of production.
- `--local` **boolean** (default: true) optional
  - Interact with locally persisted data.
- `--remote` **boolean** (default: false) optional
  - Interact with remote storage.
- `--persist-to` **string** optional
  - Specify directory for locally persisted data.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example that deletes the key-value pair with key "my-key" from the KV namespace with binding name MY\_KV.

```
npx wrangler kv key delete --binding=MY_KV "my-key"
```

Deleting the key "my-key" on namespace f7b02e7fc70443149ac906dd81ec1791.

## kv bulk

Manage multiple key-value pairs within a Workers KV namespace in batches.

### Note

The `kv ...` commands allow you to manage your Workers KV resources in the Cloudflare network. Learn more about using Workers KV with Wrangler in the [Workers KV guide](#).

### Warning

Since version 3.60.0, Wrangler supports the `kv ...` syntax. If you are using versions below 3.60.0, the command follows the `kv: ...` syntax. Learn more about the deprecation of the `kv: ...` syntax in the [Wrangler commands](#) for KV page.

## put

Write a JSON file containing an array of key-value pairs to the given namespace.

```
wrangler kv bulk put <FILENAME> {--binding=<BINDING>|--namespace-id=<NAMESPACE_ID>} [OPTIONS]
```

### Warning

This command requires `--binding` or `--namespace-id`.

- `FILENAME` **string** *required*
  - The JSON file containing an array of key-value pairs to write to the namespace.
- `--binding` **string**
  - The binding name of the namespace, as stored in the Wrangler file, to write to.

- `--namespace-id` **string**
  - The ID of the namespace to write to.
- `--env` **string** optional
  - Perform on a specific environment.
- `--preview` **boolean** optional
  - Interact with a preview namespace instead of production.
- `--local` **boolean** (default: true) optional
  - Interact with locally persisted data.
- `--remote` **boolean** (default: false) optional
  - Interact with remote storage.
- `--persist-to` **string** optional
  - Specify directory for locally persisted data.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

This command takes a JSON file as an argument with a list of key-value pairs to upload. An example of JSON input:

```
[
  {
    "key": "test_key",
    "value": "test_value",
    "expiration_ttl": 3600
  }
]
```

KV namespace values can only store strings. In order to save complex a value, stringify it to JSON:

```
[
  {
    "key": "test_key",
    "value": "{\"name\": \"test_value\"}",
    "expiration_ttl": 3600
  }
]
```

Refer to the full schema for key-value entries uploaded via the bulk API:

- **key** **string** required
  - The key's name. The name may be 512 bytes maximum. All printable, non-whitespace characters are valid.
- **value** **string** required
  - The UTF-8 encoded string to be stored, up to 25 MB in length.
- **metadata** **object** optional
  - Any arbitrary object (must serialize to JSON) to a maximum of 1,024 bytes.
- **expiration** **number** optional
  - The time, measured in number of seconds since the UNIX epoch, at which the key should expire.
- **expiration\_ttl** **number** optional
  - The number of seconds the document should exist before expiring. Must be at least 60 seconds.
- **base64** **boolean** optional
  - When true, the server will decode the value as base64 before storing it. This is useful for writing values that would otherwise be invalid JSON strings, such as images. Defaults to false.

### Note

If both `expiration` and `expiration_ttl` are specified for a given key, the API will prefer `expiration_ttl`.

The following is an example of writing all the key-value pairs found in the `allthethingsupload.json` file.

```
npx wrangler kv bulk put --binding=MY_KV allthethingsupload.json
```

Success!

## delete

Delete all keys read from a JSON file within a given namespace.

```
wrangler kv bulk delete <FILENAME> {--binding=<BINDING>|--namespace-id=<NAMESPACE_ID>} [OPTIONS]
```



### Warning

This command requires `--binding` or `--namespace-id`.

- **FILENAME** **string** required
  - The JSON file containing an array of keys to delete from the namespace.
- **--binding** **string**
  - The binding name of the namespace, as stored in the Wrangler file, to delete from.
- **--namespace-id** **string**
  - The ID of the namespace to delete from.
- **--env** **string** optional
  - Perform on a specific environment.
- **--preview** **boolean** optional
  - Interact with a preview namespace instead of production.
- **--local** **boolean** (default: true) optional
  - Interact with locally persisted data.
- **--remote** **boolean** (default: false) optional
  - Interact with remote storage.
- **--persist-to** **string** optional
  - Specify directory for locally persisted data.

The following global flags work on every command:

- `--help` `boolean`
  - Show help.
- `--config` `string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` `string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

This command takes a JSON file as an argument containing the keys to delete.

The following is an example of the JSON input:

```
["test_key_1", "test_key_2"]
```

The command also accepts keys in the format output from `wrangler kv key list`:

```
[{ "name": "test_key_1" }, { "name": "test_key_2" }]
```

The following is an example of deleting all the keys found in the `allthethingsdelete.json` file.

```
npx wrangler kv bulk delete --binding=MY_KV allthethingsdelete.json
```

```
? Are you sure you want to delete all keys in allthethingsdelete.json from  
kv-namespace with id "f7b02e7fc70443149ac906dd81ec1791"? > (Y/n)  
Success!
```

## r2 bucket

Interact with buckets in an R2 store.

### Note

The `r2 bucket` commands allow you to manage application data in the Cloudflare network to be accessed from Workers using [the R2 API](#).

## create

Create a new R2 bucket.

```
wrangler r2 bucket create <NAME>
```

- `NAME` **string** required
  - The name of the new R2 bucket.
- `--location` **string** optional
  - The optional [location hint](#) that determines geographic placement of the R2 bucket.
- `--storage-class` **'Standard|InfrequentAccess'** optional
  - The default storage class for objects uploaded to the bucket.
- `--jurisdiction` **string** optional
  - The jurisdiction where the R2 bucket is created. Refer to [jurisdictional restrictions](#).

## info

Get information about an R2 bucket, including the bucket size and number of objects.

```
wrangler r2 bucket info <NAME>
```

- `NAME` **string** required
  - The name of the R2 bucket to get information about.
- `--jurisdiction` **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).

## delete

Delete an R2 bucket.

```
wrangler r2 bucket delete <NAME>
```

- **NAME** `string` required
  - The name of the R2 bucket to delete.

## list

List R2 bucket in the current account.

```
wrangler r2 bucket list
```

## catalog enable

Enable [R2 Data Catalog](#) on an R2 bucket.

```
wrangler r2 bucket catalog enable <NAME> [OPTIONS]
```

- **NAME** `string` required
  - The name of the bucket to enable R2 Data Catalog for.

## catalog disable

Disable [R2 Data Catalog](#) on an R2 bucket.

```
wrangler r2 bucket catalog disable <NAME> [OPTIONS]
```

- **NAME** `string` required
  - The name of the bucket to disable R2 Data Catalog for.

## catalog get

Get the status of [R2 Data Catalog](#) for an R2 bucket, including catalog URI and warehouse name.

```
wrangler r2 bucket catalog get <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket whose data catalog status to retrieve.

## **cors set**

Set the [CORS configuration](#) for an R2 bucket from a JSON file.

```
wrangler r2 bucket cors set <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to set the CORS configuration for.
- **--file** **string** required
  - Path to the JSON file containing CORS configuration (file must be in format of request body of [put bucket CORS policy API](#)).
- **--jurisdiction** **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).
- **--force** **boolean** optional
  - Skip confirmation when setting CORS configuration.

## **cors delete**

Clear the [CORS configuration](#) for an R2 bucket.

```
wrangler r2 bucket cors delete <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to delete the CORS configuration for.
- **--jurisdiction** **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).
- **--force** **boolean** optional

- Skip confirmation when clearing the CORS configuration.

## cors list

List the [CORS configuration](#) rules for an R2 bucket.

```
wrangler r2 bucket cors list <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to list the CORS rules for.
- **--jurisdiction** **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).

## dev-url enable

Enable public access via the [r2.dev URL](#) for an R2 bucket.

```
wrangler r2 bucket dev-url enable <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to enable public access via its r2.dev URL.
- **--jurisdiction** **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).
- **--force** **boolean** optional
  - Skip confirmation when enabling public access via r2.dev URL.

## dev-url disable

Disable public access via the [r2.dev URL](#) for an R2 bucket.

```
wrangler r2 bucket dev-url disable <NAME> [OPTIONS]
```

- **NAME** **string** required

- The name of the R2 bucket to disable public access via its r2.dev URL.
- `--jurisdiction` **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).
- `--force` **boolean** optional
  - Skip confirmation when disabling public access via r2.dev URL.

## dev-url get

Get the [r2.dev URL](#) and status for an R2 bucket.

```
wrangler r2 bucket dev-url get <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket whose r2.dev URL status to retrieve.
- `--jurisdiction` **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).

## domain add

Connect a [custom domain](#) to an R2 bucket.

```
wrangler r2 bucket domain add <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to connect a custom domain to.
- `--domain` **string** required
  - The custom domain to connect to the R2 bucket.
- `--zone-id` **string** required
  - The [zone ID](#) associated with the custom domain.
- `--min-tls` **'1.0'|'1.1'|'1.2'|'1.3'** optional
  - Set the minimum TLS version for the custom domain (defaults to 1.0 if not set).
- `--jurisdiction` **string** optional

- The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).
- `--force` **boolean** optional
  - Skip confirmation when adding the custom domain.

## domain remove

Remove a [custom domain](#) from an R2 bucket.

```
wrangler r2 bucket domain remove <NAME> [OPTIONS]
```

- `NAME` **string** required
  - The name of the R2 bucket to remove the custom domain from.
- `--domain` **string** required
  - The custom domain to remove from the R2 bucket.
- `--jurisdiction` **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).
- `--force` **boolean** optional
  - Skip confirmation when removing the custom domain.

## domain update

Update settings for a [custom domain](#) connected to an R2 bucket.

```
wrangler r2 bucket domain update <NAME> [OPTIONS]
```

- `NAME` **string** required
  - The name of the R2 bucket associated with the custom domain to update.
- `--domain` **string** required
  - The custom domain whose settings will be updated.
- `--min-tls` **'1.0'|'1.1'|'1.2'|'1.3'** optional
  - Update the minimum TLS version for the custom domain.
- `--jurisdiction` **string** optional

- The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).

## domain get

Get [custom domain](#) connected to an R2 bucket.

```
wrangler r2 bucket domain get <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket whose custom domain to retrieve.
- **--domain** **string** required
  - The custom domain to get information for.
- **--jurisdiction** **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).

## domain list

List [custom domains](#) for an R2 bucket.

```
wrangler r2 bucket domain list <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket whose connected custom domains will be listed.
- **--jurisdiction** **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).

## lifecycle add

Add an [object lifecycle](#) rule to an R2 bucket.

```
wrangler r2 bucket lifecycle add <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to add a lifecycle rule to.
- **--name** **string** optional
  - A unique name for the lifecycle rule, used to identify and manage it. For example: `delete-logs-180-days`.
- **--prefix** **string** optional
  - Prefix condition for the lifecycle rule (leave empty for all prefixes).
- **--expire-days** **number** optional
  - Sets the lifecycle rule action to expire objects after this number of days. Note you can provide only one of `--expire-days` or `--expire-date`.
- **--expire-date** **string** optional
  - Sets the lifecycle rule action to expire objects after this date (YYYY-MM-DD). Note you can provide only one of `--expire-days` or `--expire-date`.
- **--ia-transition-days** **number** optional
  - Sets the lifecycle rule action to transition objects to Infrequent Access storage after this number of days. Note you can provide only one of `--ia-transition-days` or `--ia-transition-date`.
- **--ia-transition-date** **string** optional
  - Sets the lifecycle rule action to transition objects to Infrequent Access storage after this date (YYYY-MM-DD). Note you can provide only one of `--ia-transition-days` or `--ia-transition-date`.
- **--abort-multipart-days** **number** optional
  - Sets the lifecycle rule action to abort incomplete multipart uploads after this number of days.
- **--jurisdiction** **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).
- **--force** **boolean** optional
  - Skip confirmation when adding the lifecycle rule.

## lifecycle remove

Remove an [object lifecycle](#) rule from an R2 bucket.

```
wrangler r2 bucket lifecycle remove <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to remove a lifecycle rule from.
- **--name** **string** required
  - The unique name of the lifecycle rule to remove.
- **--jurisdiction** **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).

## lifecycle list

List [object lifecycle](#) rules for an R2 bucket.

```
wrangler r2 bucket lifecycle list <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to list lifecycle rules for.
- **--jurisdiction** **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).

## lifecycle set

Set the [object lifecycle](#) configuration for an R2 bucket from a JSON file.

```
wrangler r2 bucket lifecycle set <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to set lifecycle configuration for.
- **--file** **string** required
  - Path to the JSON file containing lifecycle configuration (file must be in format of request body of [put object lifecycle configuration API](#)).
- **--jurisdiction** **string** optional

- The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).
- `--force` **boolean** optional
  - Skip confirmation when setting object lifecycle configuration.

## lock add

Add a [bucket lock](#) rule to an R2 bucket.

```
wrangler r2 bucket lock add <NAME> [OPTIONS]
```

- `NAME` **string** required
  - The name of the R2 bucket to add a bucket lock rule to.
- `--name` **string** optional
  - A unique name for the bucket lock rule, used to identify and manage it. For example: `retain-logs-180-days`.
- `--prefix` **string** optional
  - Prefix condition for the bucket lock rule (leave empty for all prefixes).
- `--retention-days` **number** optional
  - Sets the number of days to retain objects for. Note you can provide only one of `--retention-days`, `--retention-date`, or `--retention-indefinite`.
- `--retention-date` **string** optional
  - Sets the number of days to retain objects for. Note you can provide only one of `--retention-days`, `--retention-date`, or `--retention-indefinite`.
- `--retention-indefinite` **string** optional
  - Sets the retention period to indefinite — meaning the lock will remain in place until explicitly removed. Note you can provide only one of `--retention-days`, `--retention-date`, or `--retention-indefinite`.
- `--jurisdiction` **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).
- `--force` **boolean** optional
  - Skip confirmation when adding the bucket lock rule.

## lock remove

Remove a [bucket lock](#) rule from an R2 bucket.

```
wrangler r2 bucket lock remove <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to remove a bucket lock rule from.
- **--name** **string** required
  - The unique name of the bucket lock rule to remove.
- **--jurisdiction** **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).

## lock list

List [bucket lock](#) rules for an R2 bucket.

```
wrangler r2 bucket lock list <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to list bucket locks rules for.
- **--jurisdiction** **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).

## lock set

Set the [bucket lock](#) configuration for an R2 bucket from a JSON file.

```
wrangler r2 bucket lock set <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to set bucket lock configuration for.
- **--file** **string** required

- Path to the JSON file containing bucket lock configuration (file must be in format of request body of [put bucket lock configuration API](#)).
- `--jurisdiction` **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).
- `--force` **boolean** optional
  - Skip confirmation when setting bucket lock configuration.

## notification create

Create an [event notification](#) rule for an R2 bucket.

```
wrangler r2 bucket notification create <NAME> [OPTIONS]
```

- `NAME` **string** required
  - The name of the R2 bucket to create an event notification rule for.
- `--event-type` **'object-create'|'object-delete'[]** required
  - The [type of event\(s\)](#) that will trigger event notifications.
- `--queue` **string** required
  - The name of the queue that will receive event notification messages.
- `--prefix` **string** optional
  - The prefix that an object must match to emit event notifications (note: regular expressions are not supported).
- `--suffix` **string** optional
  - The suffix that an object must match to emit event notifications (note: regular expressions are not supported).
- `--description` **string** optional
  - A description that can be used to identify the event notification rule after creation.

## notification delete

Remove an event notification rule from a bucket's [event notification](#) configuration.

```
wrangler r2 bucket notification delete <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to delete an event notification rule for.
- **--queue** **string** required
  - The name of the queue that corresponds to the event notification rule. If no rule is provided, all event notification rules associated with the queue will be deleted.
- **--rule** **string** optional
  - The ID of the event notification rule to delete.

## notification list

List the [event notification](#) rules for a bucket.

```
wrangler r2 bucket notification list <NAME>
```

- **NAME** **string** required
  - The name of the R2 bucket to get event notification rules for.

## sippy enable

Enable [Sippy](#) incremental migration for a bucket.

```
wrangler r2 bucket sippy enable <NAME> [OPTIONS]
```

- **NAME** **string** required
  - The name of the R2 bucket to enable Sippy.
- **--provider** **'AWS'|'GCS'** required
  - The provider of your source object storage bucket.
- **--bucket** **string** required
  - The name of your source object storage bucket.
- **--r2-key-id** **string** required
  - Your R2 Access Key ID. Requires read and write access.
- **--r2-secret-access-key** **string** required

- Your R2 Secret Access Key. Requires read and write access.
- `--jurisdiction` **string** optional
  - The jurisdiction where the bucket exists, if a jurisdiction has been specified. Refer to [jurisdictional restrictions](#).
- **AWS S3 provider-specific options:**
- `--key-id` **string** optional
  - Your AWS Access Key ID. Requires [read and list access](#).
- `--secret-access-key` **string** optional
  - Your AWS Secret Access Key. Requires [read and list access](#).
- `--region` **string** optional
  - The AWS region where your S3 bucket is located. For example: `us-west-2`.
- **Google Cloud Storage provider-specific options:**
- `--service-account-key-file` **string** optional
  - The path to your Google Cloud service account key JSON file. This will read the service account key file and populate `client_email` and `private_key` options. Requires [read and list access](#).
- `--client-email` **string** optional
  - The client email for your Google Cloud service account key. Requires [read and list access](#).
- `--private-key` **string** optional
  - The private key for your Google Cloud service account key. Requires [read and list access](#).
- Note that you must provide either `service-account-key-file` or `client_email` and `private_key` for this command to run successfully.

## sippy disable

Disable [Sippy](#) incremental migration for a bucket.

```
wrangler r2 bucket sippy disable <NAME>
```

- **NAME** **string** required
  - The name of the R2 bucket to disable Sippy.

## sippy get

Get the status of [Sippy](#) incremental migration for a bucket.

```
wrangler r2 bucket sippy get <NAME>
```

- **NAME** **string** required
  - The name of the R2 bucket to get the status of Sippy.

## r2 object

Interact with R2 objects.

### Note

The `r2 object` commands allow you to manage application data in the Cloudflare network to be accessed from Workers using [the R2 API](#).

## get

Fetch an object from an R2 bucket.

```
wrangler r2 object get <OBJECT_PATH> [OPTIONS]
```

- **OBJECT\_PATH** **string** required
  - The source object path in the form of `{bucket}/{key}`.
- **--local** **boolean** (default: true) optional
  - Interact with locally persisted data.
- **--remote** **boolean** (default: false) optional
  - Interact with remote storage.
- **--persist-to** **string** optional
  - Specify directory for locally persisted data.

## put

Create an object in an R2 bucket.

```
wrangler r2 object put <OBJECT_PATH> [OPTIONS]
```

- **OBJECT\_PATH** **string** required
  - The destination object path in the form of {bucket}/{key}.
- **--file** **string** optional
  - The path of the file to upload. Note you must provide either **--file** or **--pipe**.
- **--pipe** **boolean** optional
  - Enables the file to be piped in, rather than specified with the **--file** option. Note you must provide either **--file** or **--pipe**.
- **--content-type** **string** optional
  - A standard MIME type describing the format of the object data.
- **--content-disposition** **string** optional
  - Specifies presentational information for the object.
- **--content-encoding** **string** optional
  - Specifies what content encodings have been applied to the object and thus what decoding mechanisms must be applied to obtain the media-type referenced by the Content-Type header field.
- **--content-language** **string** optional
  - The language the content is in.
- **--cache-control** **string** optional
  - Specifies caching behavior along the request/reply chain.
- **--expires** **string** optional
  - The date and time at which the object is no longer cacheable.
- **--local** **boolean** (default: true) optional
  - Interact with locally persisted data.
- **--remote** **boolean** (default: false) optional
  - Interact with remote storage.
- **--persist-to** **string** optional
  - Specify directory for locally persisted data.

## delete

Delete an object in an R2 bucket.

```
wrangler r2 object delete <OBJECT_PATH> [OPTIONS]
```

- **OBJECT\_PATH** **string** required
  - The destination object path in the form of {bucket}/{key}.
- **--local** **boolean** (default: true) optional
  - Interact with locally persisted data.
- **--remote** **boolean** (default: false) optional
  - Interact with remote storage.
- **--persist-to** **string** optional
  - Specify directory for locally persisted data.

### Note

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

---

## secret

Manage the secret variables for a Worker.

This action creates a new [version](#) of the Worker and [deploys](#) it immediately. To only create a new version of the Worker, use the [wrangler versions secret](#) commands.

## put

Create or replace a secret for a Worker.

```
wrangler secret put <KEY> [OPTIONS]
```

- **KEY** **string** required
  - The variable name for this secret to be accessed in the Worker.
- **--name** **string** optional
  - Perform on a specific Worker rather than inheriting from a [Wrangler configuration file](#).
- **--env** **string** optional
  - Perform on a specific environment.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

When running this command, you will be prompted to input the secret's value:

```
npx wrangler secret put F00
```

```
? Enter a secret value: > ***  
🌀 Creating the secret for script worker-app  
✨ Success! Uploaded secret F00
```

The put command can also receive piped input. For example:

```
echo "-----BEGIN PRIVATE KEY-----\nM...==\n-----END PRIVATE KEY-----\n" |  
wrangler secret put PRIVATE_KEY
```

# delete

Delete a secret for a Worker.

```
wrangler secret delete <KEY> [OPTIONS]
```

- **KEY** **string** required
  - The variable name for this secret to be accessed in the Worker.
- **--name** **string** optional
  - Perform on a specific Worker rather than inheriting from the [Wrangler configuration file](#).
- **--env** **string** optional
  - Perform on a specific environment.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

# list

List the names of all the secrets for a Worker.

```
wrangler secret list [OPTIONS]
```

- **--name** **string** optional
  - Perform on a specific Worker rather than inheriting from the [Wrangler configuration file](#).
- **--env** **string** optional
  - Perform on a specific environment

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example of listing the secrets for the current Worker.

```
npx wrangler secret list
```

```
[
  {
    "name": "F00",
    "type": "secret_text"
  }
]
```

## secret bulk

Upload multiple secrets for a Worker at once.

```
wrangler secret bulk [<FILENAME>] [OPTIONS]
```

- **FILENAME** **string** optional
  - A file containing either [JSON ↗](#) or the [.env ↗](#) format
  - The JSON file containing key-value pairs to upload as secrets, in the form `{"SECRET_NAME": "secret value", ...}`.
  - The `.env` file containing [key-value pairs to upload as secrets](#), in the form `SECRET_NAME=secret value`.

- If omitted, Wrangler expects to receive input from `stdin` rather than a file.
- `--name string` optional
  - Perform on a specific Worker rather than inheriting from the [Wrangler configuration file](#).
- `--env string` optional
  - Perform on a specific environment.

The following global flags work on every command:

- `--help boolean`
  - Show help.
- `--config string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example of uploading secrets from a JSON file redirected to `stdin`. When complete, the output summary will show the number of secrets uploaded and the number of secrets that failed to upload.

```
{
  "secret-name-1": "secret-value-1",
  "secret-name-2": "secret-value-2"
}
```

```
npx wrangler secret bulk < secrets.json
```

```
🌀 Creating the secrets for the Worker "script-name"
✨ Successfully created secret for key: secret-name-1
...
🚫 Error uploading secret for key: secret-name-1
✨ Successfully created secret for key: secret-name-2

Finished processing secrets JSON file:
✨ 1 secrets successfully uploaded
🚫 1 secrets failed to upload
```

## secrets-store secret

With the release of [Secrets Store](#) in open beta, you can use the following commands to manage your account secrets.

### 📘 `--remote` option

In order to interact with Secrets Store in production, you should append `--remote` to your command. Without it, your command will default to [local development mode](#).

## create

Create a secret within a store.

```
wrangler secrets-store secret create <STORE_ID> [OPTIONS]
```

- `STORE_ID` **string** required
  - The secret store public ID. You can find it and copy from the [Secrets Store tab](#) [↗](#) on the dashboard.
- `--name` **string** required
  - A descriptive name for the account-level secret. Cannot contain spaces.
- `--value` **string** test only
  - Value of the secret.

### ⚠️ Only use for testing

This will leave the secret value in plain-text in terminal history. For real secret values, use the automatic prompt instead. Find an example below.

- `--scopes` **string** required
  - Which services will have access to the account-level secret. Currently, only workers is available.
- `--comment` **string** optional
  - Additional information about the account-level secret.
- `--remote` **boolean** (default: false) optional
  - Execute the command against the remote Secrets Store. To interact with account-level secrets in production, make sure to append `--remote` to your commands.

The following is an example of using the `create` command to create an account-level secret.

```
npx wrangler secrets-store secret create 8f7a1cdced6342c18d223ece462fd88d --
name ServiceA_key-1 --scopes workers --remote
```

✓ Enter a secret value: > \*\*\*

🔑 Creating secret... (Name: ServiceA\_key-1, Value: REDACTED, Scopes: workers, Comment: undefined)

✓ Select an account: > My account

✅ Created secret! (ID: 13bc7498c6374a4e9d13be091c3c65f1)

## update

Update a secret within a store.

```
wrangler secrets-store secret update <STORE_ID> [OPTIONS]
```

- `STORE_ID` **string** required
  - The ID of the secrets store that contains the secret you are updating.
- `--secret-id` **string** required

- The ID of the secret to update.
- `--value` **string** test only
  - Updated value of the secret.

 **Only use for testing**

This will leave the secret value in plain-text in terminal history. For real secret values, use the automatic prompt instead.

- `--scopes` **string** required
  - Which services will have access to the account-level secret. Currently, only workers is available.
- `--comment` **string** optional
  - Updated comment for the account-level secret.
- `--remote` **boolean** (default: false) optional
  - Execute the command against the remote Secrets Store. To interact with account-level secrets in production, make sure to append `--remote` to your commands.

## duplicate

Duplicate a secret within a store. Use this command to create a new secret that holds the same secret value as an existing secret.

```
wrangler secrets-store secret duplicate <STORE_ID> [OPTIONS]
```

- `STORE_ID` **string** required
  - The ID of the secrets store that contains the secret you are duplicating.
- `--secret-id` **string** required
  - The ID of the secret you are duplicating.
- `--name` **string** required
  - A name for the new secret. Cannot contain spaces.
- `--scopes` **string** required
  - Which services will have access to the new account-level secret. Currently, only workers is available.
- `--comment` **string** optional

- Additional information about the new account-level secret.
- `--remote` **boolean** (default: false) optional
  - Execute the command against the remote Secrets Store. To interact with account-level secrets in production, make sure to append `--remote` to your commands.

## get

Get information on a secret within a store.

```
wrangler secrets-store secret get <STORE_ID> [OPTIONS]
```

- `STORE_ID` **string** required
  - The ID of the secrets store that contains the secret you want to get.
- `--secret-id` **string** required
  - The ID of the secret you want to get.
- `--remote` **boolean** (default: false) optional
  - Execute the command against the remote Secrets Store. To interact with account-level secrets in production, make sure to append `--remote` to your commands.

The following is an example with the expected output:

```
npx wrangler secrets-store secret get 8f7a1cdced6342c18d223ece462fd88d --
secret-id 13bc7498c6374a4e9d13be091c3c65f1 --remote
```

```
🔑 Getting secret... (ID: 13bc7498c6374a4e9d13be091c3c65f1)
✓ Select an account: > My account
| Name | ID | StoreID |
| Comment | Scopes | Status | Created | Modified |
|-----|-----|-----|-----|-----|
| ServiceA_key-1 | 13bc7498c6374a4e9d13be091c3c65f1 | 8f7a1cdced6342c18d223ece462fd88d | workers | active | 4/9/2025, 10:06:01 PM | 4/15/2025, 09:13:05 AM |
```

# delete

Delete a secret within a store.

## Warning

Before deleting a secret, make sure it is not deployed in any Workers application.

```
wrangler secrets-store secret delete <STORE_ID> [OPTIONS]
```

- **STORE\_ID** **string** required
  - The ID of the secrets store that contains the secret you are deleting.
- **--secret-id** **string** required
  - The ID of the secret you are deleting.
- **--remote** **boolean** (default: false) optional
  - Execute the command against the remote Secrets Store. To interact with account-level secrets in production, make sure to append **--remote** to your commands.

# list

List secrets within a store.

```
wrangler secrets-store secret list <STORE_ID>
```

- **STORE\_ID** **string** required
  - The secret store public ID. You can find it and copy from the [Secrets Store tab](#) on the dashboard.

# secrets-store store

Use the following commands to manage your store.

## Store limitation

[Secrets Store](#) is in open beta. Currently, you can only have one store per Cloudflare account.

## create

Create a store within Secrets Store.

```
wrangler secrets-store store create <name>
```

- **name** **string** required
  - A descriptive name for the account-level secret. Cannot contain spaces.
- **--remote** **boolean** (default: false) required
  - Execute the command against the remote Secrets Store.

The following is an example of using the create command to create a store.

```
npx wrangler secrets-store store create default --remote
```

```
🔑 Creating store... (Name: default)
✅ Created store! (Name: default, ID: 2e2a82d317134506b58defbe16982d54)
```

## delete

Delete a store within Secrets Store.

```
wrangler secrets-store store delete <STORE_ID>
```

- **STORE\_ID** **string** required
  - The secret store public ID. You can find it and copy from the [Secrets Store tab](#) on the dashboard.
- **--remote** **boolean** (default: false) required
  - Execute the command against the remote Secrets Store.

The following is an example of using the delete command to delete a store.

```
npx wrangler secrets-store store delete d2dafaeac9434de2b6d08b292ce08211 --remote
```

 Deleting store... (Name: d2dafaeac9434de2b6d08b292ce08211)  
 Deleted store! (ID: d2dafaeac9434de2b6d08b292ce08211)

# list

List the stores within an account.

```
wrangler secrets-store store list
```

- `--remote` **boolean** (default: false) required
  - Execute the command against the remote Secrets Store.

The following is an example of using the `list` command to list stores.

```
npx wrangler secrets-store store list --remote
```

 Listing stores...

| Name    | ID                               | AccountID |                      |
|---------|----------------------------------|-----------|----------------------|
| default | 8876bad33f164462bf0743fe8adf98f4 | REDACTED  | 4/9/2025, 1:11:48 PM |

# workflows

### Note

The `wrangler workflows` command requires Wrangler version **3.83.0** or greater. Use `npx wrangler@latest` to always use the latest Wrangler version when invoking commands.

Manage and configure [Workflows](#).

## list

Lists the registered Workflows for this account.

```
wrangler workflows list
```

- `--page` **number** optional
  - Show a specific page from the listing. You can configure page size using "per-page".
- `--per-page` **number** optional
  - Configure the maximum number of Workflows to show per page.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## instances

Manage and interact with specific instances of a Workflow.

## instances list

List Workflow instances.

```
wrangler workflows instances list <WORKFLOW_NAME> [OPTIONS]
```

- **WORKFLOW\_NAME** **string** required
  - The name of a registered Workflow.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## instances describe

Describe a specific instance of a Workflow, including its current status, any persisted state, and per-step outputs.

```
wrangler workflows instances describe <WORKFLOW_NAME> <ID> [OPTIONS]
```

- **WORKFLOW\_NAME** **string** required
  - The name of a registered Workflow.
- **ID** **string** required
  - The ID of a Workflow instance. You can optionally provide `latest` to refer to the most recently created instance of a Workflow.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.

- `--config` `string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` `string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

*# Passing `latest` instead of an explicit ID will describe the most recently queued instance*

```
wrangler workflows instances describe my-workflow latest
```

```
Workflow Name:      my-workflow
Instance Id:        51c73fc8-7fd5-47d9-bd82-9e301506ee72
Version Id:         cedc33a0-11fa-4c26-8a8e-7d28d381a291
Status:              Completed
Trigger:             API
Queued:             10/16/2024, 2:00:39 PM
Success:             Yes
Start:              10/16/2024, 2:00:39 PM
End:                10/16/2024, 2:01:40 PM
Duration:           1 minute
```

*# Remaining output truncated*

## instances terminate

Terminate (permanently stop) a Workflow instance.

```
wrangler workflows instances terminate <WORKFLOW_NAME> <ID> [OPTIONS]
```

- `WORKFLOW_NAME` `string` required
  - The name of a registered Workflow.
- `ID` `string` required
  - The ID of a Workflow instance.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## instances pause

Pause (until resumed) a Workflow instance.

```
wrangler workflows instances pause <WORKFLOW_NAME> <ID> [OPTIONS]
```

- `WORKFLOW_NAME` **string** required
  - The name of a registered Workflow.
- `ID` **string** required
  - The ID of a Workflow instance.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## instances resume

Resume a paused Workflow instance.

```
wrangler workflows instances resume <WORKFLOW_NAME> <ID> [OPTIONS]
```

- **WORKFLOW\_NAME** **string** required
  - The name of a registered Workflow.
- **ID** **string** required
  - The ID of a Workflow instance.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## describe

```
wrangler workflows describe <WORKFLOW_NAME> [OPTIONS]
```

- **WORKFLOW\_NAME** **string** required
  - The name of a registered Workflow.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

# delete

Delete a Workflow and all its instances.

```
wrangler workflows delete <WORKFLOW_NAME> [OPTIONS]
```

- **WORKFLOW\_NAME** **string** required
  - The name of a registered Workflow.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

```
wrangler workflows instances delete my-workflow
```

# trigger

Trigger (create) a Workflow instance.

```
wrangler workflows trigger <WORKFLOW_NAME> <PARAMS> [OPTIONS]
```

- **WORKFLOW\_NAME** **string** required
  - The name of a registered Workflow.
- **PARAMS** **string** optional
  - The parameters to pass to the Workflow as an event. Must be a JSON-encoded string.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

```
# Pass optional params to the Workflow.  
wrangler workflows trigger my-workflow '{"hello":"world"}'
```

## tail

Start a session to livestream logs from a deployed Worker.

```
wrangler tail <WORKER> [OPTIONS]
```

- `WORKER` **string** required
  - The name of your Worker or the route the Worker is running on.
- `--format` **'json'|'pretty'** optional
  - The format of the log entries.
- `--status` **'ok'|'error'|'canceled'** optional
  - Filter by invocation status.
- `--header` **string** optional
  - Filter by HTTP header.
- `--method` **string** optional
  - Filter by HTTP method.
- `--sampling-rate` **number** optional
  - Add a fraction of requests to log sampling rate (between 0 and 1).
- `--search` **string** optional

- Filter by a text match in `console.log` messages.
- `--ip (string|'self')\[\] "` optional
  - Filter by the IP address the request originates from. Use `"self"` to show only messages from your own IP.
- `--version-id string` optional
  - Filter by Worker version.

The following global flags work on every command:

- `--help boolean`
  - Show help.
- `--config string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

After starting `wrangler tail`, you will receive a live feed of console and exception logs for each request your Worker receives.

If your Worker has a high volume of traffic, the tail might enter sampling mode. This will cause some of your messages to be dropped and a warning to appear in your tail logs. To prevent messages from being dropped, add the options listed above to filter the volume of tail messages.

### Note

It may take up to 1 minute (60 seconds) for a tail to exit sampling mode after adding an option to filter tail messages.

If sampling persists after using options to filter messages, consider using [instant logs ↗](#).

## pages

Configure Cloudflare Pages.

# dev

Develop your full-stack Pages application locally.

```
wrangler pages dev [<DIRECTORY>] [OPTIONS]
```

- **DIRECTORY** **string** optional
  - The directory of static assets to serve.
- **--local** **boolean** optional (default: true)
  - Run on your local machine.
- **--ip** **string** optional
  - IP address to listen on, defaults to localhost.
- **--port** **number** optional (default: 8788)
  - The port to listen on (serve from).
- **--config, -c** **string[]** optional
  - Path(s) to [Wrangler configuration file](#). If not provided, Wrangler will use the nearest config file based on your current working directory.
  - You can provide additional configuration files in order to run Workers alongside your Pages project, like this: `wrangler pages dev -c ./wrangler.toml -c ../other-worker/wrangler.toml`. The first argument must point to your Pages configuration file, and the subsequent configurations will be accessible via a Service binding from your Pages project.
- **--binding** **string[]** optional
  - Bind an environment variable or secret (for example, `--binding <VARIABLE_NAME>=<VALUE>`).
- **--kv** **string[]** optional
  - Binding name of [KV namespace](#) to bind (for example, `--kv <BINDING_NAME>`).
- **--r2** **string[]** optional
  - Binding name of [R2 bucket](#) to bind (for example, `--r2 <BINDING_NAME>`).
- **--d1** **string[]** optional
  - Binding name of [D1 database](#) to bind (for example, `--d1 <BINDING_NAME>`).
- **--do** **string[]** optional

- Binding name of Durable Object to bind (for example, `--do <BINDING_NAME>=<CLASS>`).
- `--live-reload` **boolean** optional (default: false)
  - Auto reload HTML pages when change is detected.
- `--compatibility-flag` **string[]** optional
  - Runtime compatibility flags to apply.
- `--compatibility-date` **string** optional
  - Runtime compatibility date to apply.
- `--show-interactive-dev-session` **boolean** optional (default: true if the terminal supports interactivity)
  - Show the interactive dev session.
- `--https-key-path` **string** optional
  - Path to a custom certificate key.
- `--https-cert-path` **string** optional
  - Path to a custom certificate.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## download config

Download your Pages project config as a [Wrangler configuration file](#).

```
wrangler pages download config <PROJECT_NAME>
```

The following global flags work on every command:

- `--help` **boolean**

- Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## project list

List your Pages projects.

```
wrangler pages project list
```

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## project create

Create a new Cloudflare Pages project.

```
wrangler pages project create <PROJECT_NAME> [OPTIONS]
```

- `PROJECT_NAME` **string** *required*
  - The name of your Pages project.
- `--production-branch` **string** *optional*
  - The name of the production branch of your project.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## project delete

Delete a Cloudflare Pages project.

```
wrangler pages project delete <PROJECT_NAME> [OPTIONS]
```

- `PROJECT_NAME` **string** required
  - The name of the Pages project to delete.
- `--yes` **boolean** optional
  - Answer "yes" to confirmation prompt.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## deployment list

List deployments in your Cloudflare Pages project.

```
wrangler pages deployment list [--project-name <PROJECT_NAME>]
```

- `--project-name` **string** optional
  - The name of the project you would like to list deployments for.
- `--environment` **'production' | 'preview'** optional
  - Environment type to list deployments for.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## deployment tail

Start a session to livestream logs from your deployed Pages Functions.

```
wrangler pages deployment tail [<DEPLOYMENT>] [OPTIONS]
```

- `DEPLOYMENT` **string** optional
  - ID or URL of the deployment to tail. Specify by environment if deployment ID is unknown.
- `--project-name` **string** optional
  - The name of the project you would like to tail.
- `--environment` **'production' | 'preview'** optional
  - When not providing a specific deployment ID, specifying environment will grab the latest production or preview deployment.
- `--format` **'json' | 'pretty'** optional
  - The format of the log entries.
- `--status` **'ok' | 'error' | 'canceled'** optional
  - Filter by invocation status.
- `--header` **string** optional

- Filter by HTTP header.
- `--method` **string** optional
  - Filter by HTTP method.
- `--sampling-rate` **number** optional
  - Add a percentage of requests to log sampling rate.
- `--search` **string** optional
  - Filter by a text match in `console.log` messages.
- `--ip` **(string|'self')[]** optional
  - Filter by the IP address the request originates from. Use `"self"` to show only messages from your own IP.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

### Note

Filtering with `--ip self` will allow tailing your deployed Functions beyond the normal request per second limits.

After starting `wrangler pages deployment tail`, you will receive a live stream of console and exception logs for each request your Functions receive.

## deploy

Deploy a directory of static assets as a Pages deployment.

```
wrangler pages deploy <BUILD_OUTPUT_DIRECTORY> [OPTIONS]
```

- `BUILD_OUTPUT_DIRECTORY` **string** optional

- The [directory](#) of static files to upload. As of Wrangler 3.45.0, this is only required when your Pages project does not have a Wrangler file. Refer to the [Pages Functions configuration guide](#) for more information.
- `--project-name` **string** optional
  - The name of the project you want to deploy to.
- `--branch` **string** optional
  - The name of the branch you want to deploy to.
- `--commit-hash` **string** optional
  - The SHA to attach to this deployment.
- `--commit-message` **string** optional
  - The commit message to attach to this deployment.
- `--commit-dirty` **boolean** optional
  - Whether or not the workspace should be considered dirty for this deployment.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

### Note

Your site is deployed to `<PROJECT_NAME>.pages.dev`. If you do not provide the `--project-name` argument, you will be prompted to enter a project name in your terminal after you run the command.

## secret put

Create or update a secret for a Pages project.

```
wrangler pages secret put <KEY> [OPTIONS]
```

- **KEY** `string` required
  - The variable name for this secret to be accessed in the Pages project.
- **--project-name** `string` optional
  - The name of your Pages project.

The following global flags work on every command:

- **--help** `boolean`
  - Show help.
- **--config** `string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** `string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## secret delete

Delete a secret from a Pages project.

```
wrangler pages secret delete <KEY> [OPTIONS]
```

- **KEY** `string` required
  - The variable name for this secret to be accessed in the Pages project.
- **--project-name** `string` optional
  - The name of your Pages project.

The following global flags work on every command:

- **--help** `boolean`
  - Show help.
- **--config** `string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** `string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## secret list

List the names of all the secrets for a Pages project.

```
wrangler pages secret list [OPTIONS]
```

- **--project-name** *string* optional
  - The name of your Pages project.

The following global flags work on every command:

- **--help** *boolean*
  - Show help.
- **--config** *string* (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** *string*
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## secret bulk

Upload multiple secrets for a Pages project at once.

```
wrangler pages secret bulk [<FILENAME>] [OPTIONS]
```

- **FILENAME** *string* optional
  - A file containing either [JSON](#) or the [.env](#) format
  - The JSON file containing key-value pairs to upload as secrets, in the form `{"SECRET_NAME": "secret value", ...}`.
  - The `.env` file containing [key-value pairs to upload as secrets](#), in the form `SECRET_NAME=secret value`.
  - If omitted, Wrangler expects to receive input from `stdin` rather than a file.
- **--project-name** *string* optional
  - The name of your Pages project.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## functions build

Compile a folder of Pages Functions into a single Worker.

```
wrangler pages functions build [<DIRECTORY>] [OPTIONS]
```

- `DIRECTORY` **string** optional (default: ``functions``)
  - The directory of Pages Functions.
- `--outdir` **string** optional
  - Output directory for the bundled Worker.
- `--fallback-service` **string** optional (default: ``ASSETS``)
  - The service to fallback to at the end of the next chain. Setting to `` `` will fallback to the global fetch.
- `--compatibility-date` **string** optional
  - Date to use for compatibility checks.
- `--compatibility-flags` **string[]** optional
  - Flags to use for compatibility checks.
- `--metafile` **string** optional
  - Specify a file to write the build metadata from esbuild to. If flag is used without a path string, this defaults to `bundle-meta.json` inside the directory specified by `--outdir`. This can be useful for understanding the bundle size.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.

- `--config string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## pipelines

Manage your [Pipelines](#).

### Note

Pipelines is currently in open beta. Report Pipelines bugs in [GitHub ↗](#).

## create

Create a new pipeline

```
wrangler pipelines create <name> --r2 <r2-bucket-name> [OPTIONS]
```

- `name string` required
  - The name of the pipeline to create
- `--source array` optional
  - List of allowed sources. Options: `http` or `worker`
- `--require-http-auth boolean` optional
  - Require Cloudflare API token to authenticate with the HTTPS endpoint. Defaults to `false`.
- `--cors-origins array` optional
  - CORS Origin allowlist for HTTP endpoint. Allows `*`. Defaults to an empty array.
- `--batch-max-mb number` optional
  - The maximum size of a batch in megabytes before data is written. Defaults to `100`. Must be between `1` and `100`.
- `--batch-max-rows number` optional

- The maximum number of rows in a batch before data is written. Defaults to **10000000**. Must be between 1 and **10000000**.
- **--batch-max-seconds** **number** optional
  - The maximum duration of a batch before data is written in seconds. Defaults to **300**. Must be between 1 and **300**.
- **--r2-bucket** **string** required
  - The name of the R2 bucket used as the destination to store the data.
- **--r2-bucket-access-key-id** **string** optional
  - Access key ID used to authenticate with R2. Leave empty for oauth confirmation.
- **--r2-bucket-secret-access-key** **string** optional
  - Secret access key ID used to authenticate with R2. Leave empty for oauth confirmation.
- **--r2-prefix** **string** optional
  - Prefix for storing files in the destination bucket.
- **--compression** **string** optional
  - Type of compression to apply to output files. Choices: none, gzip, deflate
- **--shard-count** **number** optional
  - Number of pipeline shards. More shards handle higher request volume; fewer shards produce larger output files. Defaults to 2. Must be between 1 and 15.

## update

Update an existing pipeline

```
wrangler pipelines update <name> [OPTIONS]
```

- **name** **string** required
  - The name of the pipeline to create
- **--source** **array** optional
  - List of allowed sources. Options: http or worker
- **--require-http-auth** **boolean** optional
  - Require Cloudflare API token to authenticate with the HTTPS endpoint. Defaults to false.

- `--cors-origins` **array** optional
  - CORS Origin allowlist for HTTP endpoint. Allows \*. Defaults to an empty array.
- `--batch-max-mb` **number** optional
  - The maximum size of a batch in megabytes before data is written. Defaults to 100. Must be between 1 and 100.
- `--batch-max-rows` **number** optional
  - The maximum number of rows in a batch before data is written. Defaults to 10000000. Must be between 1 and 10000000.
- `--batch-max-seconds` **number** optional
  - The maximum duration of a batch before data is written in seconds. Defaults to 300. Must be between 1 and 300.
- `--r2-bucket` **string** required
  - The name of the R2 bucket used as the destination to store the data.
- `--r2-bucket-access-key-id` **string** optional
  - Access key ID used to authenticate with R2. Leave empty for oauth confirmation.
- `--r2-bucket-secret-access-key` **string** optional
  - Secret access key ID used to authenticate with R2. Leave empty for oauth confirmation.
- `--r2-prefix` **string** optional
  - Prefix for storing files in the destination bucket.
- `--compression` **string** optional
  - Type of compression to apply to output files. Choices: none, gzip, deflate
- `--shard-count` **number** optional
  - Number of pipeline shards. More shards handle higher request volume; fewer shards produce larger output files. Defaults to 2. Must be between 1 and 15.

## get

Get the configuration for an existing pipeline.

```
wrangler pipelines get <name> [OPTIONS]
```

- `name` **string** required

- The name of the pipeline to inspect

## delete

Deletes an existing pipeline

```
wrangler pipelines delete <name> [OPTIONS]
```

- **name** **string** required
  - The name of the pipeline to delete

## list

Lists all pipelines in your account.

```
wrangler pipelines list [OPTIONS]
```

## queues

Manage your Workers [Queues](#) configurations.

## create

Create a new queue.

```
wrangler queues create <name> [OPTIONS]
```

- **name** **string** required
  - The name of the queue to create.
- **--delivery-delay-secs** **number** optional
  - How long a published message should be delayed for, in seconds. Must be a positive integer.
- **--message-retention-period-secs** **number** optional

- How long a published message is retained in the Queue. Must be a positive integer between 60 and 1209600 (14 days). Defaults to 345600 (4 days).

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## update

Update an existing queue.

```
wrangler queues update <name> [OPTIONS]
```

- `name` **string** required
  - The name of the queue to update.
- `--delivery-delay-secs` **number** optional
  - How long a published message should be delayed for, in seconds. Must be a positive integer.
- `--message-retention-period-secs` **number** optional
  - How long a published message is retained on the Queue. Must be a positive integer between 60 and 1209600 (14 days). Defaults to 345600 (4 days).

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**

- Run as if Wrangler was started in the specified directory instead of the current working directory.

## delete

Delete an existing queue.

```
wrangler queues delete <name> [OPTIONS]
```

- **name** **string** required
  - The name of the queue to delete.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## list

List all queues in the current account.

```
wrangler queues list [OPTIONS]
```

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**

- Run as if Wrangler was started in the specified directory instead of the current working directory.

## info

Get information on individual queues.

```
wrangler queues info <name>
```

- **name** **string** required
  - The name of the queue to inspect.

## consumer

Manage queue consumer configurations.

### consumer add <script-name>

Add a Worker script as a [queue consumer](#).

```
wrangler queues consumer add <queue-name> <script-name> [OPTIONS]
```

- **queue-name** **string** required
  - The name of the queue to add the consumer to.
- **script-name** **string** required
  - The name of the Workers script to add as a consumer of the named queue.
- **--batch-size** **number** optional
  - Maximum number of messages per batch. Must be a positive integer.
- **--batch-timeout** **number** optional
  - Maximum number of seconds to wait to fill a batch with messages. Must be a positive integer.
- **--message-retries** **number** optional
  - Maximum number of retries for each message. Must be a positive integer.
- **--max-concurrency** **number** optional

- The maximum number of concurrent consumer invocations that will be scaled up to handle incoming message volume. Must be a positive integer.
- `--retry-delay-secs` **number** optional
  - How long a retried message should be delayed for, in seconds. Must be a positive integer.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## consumer remove

Remove a consumer from a queue.

```
wrangler queues consumer remove <queue-name> <script-name>
```

- `queue-name` **string** required
  - The name of the queue to remove the consumer from.
- `script-name` **string** required
  - The name of the Workers script to remove as the consumer.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## purge

Permanently delete all messages in a queue.

```
wrangler queues purge <queue-name>
```

- **queue-name** **string** required
  - The name of the queue from which messages should be deleted.

## pause-delivery

Pause message delivery from a Queue to consumers (including push consumers, and HTTP pull consumers)

```
wrangler queues pause-delivery <queue-name>
```

- **queue-name** **string** required
  - The name of the queue which delivery should be paused.

## resume-delivery

Resume delivery from a Queue to consumers (including push consumers, and HTTP pull consumers)

```
wrangler queues resume-delivery <queue-name>
```

- **queue-name** **string** required
  - The name of the queue from which delivery should be resumed.

## login

Authorize Wrangler with your Cloudflare account using OAuth. Wrangler will attempt to automatically open your web browser to login with your Cloudflare account.

If you prefer to use API tokens for authentication, such as in headless or continuous integration environments, refer to [Running Wrangler in CI/CD](#).

```
wrangler login [OPTIONS]
```

- `--scopes-list` **string** optional
  - List all the available OAuth scopes with descriptions.
- `--scopes` **string** optional
  - Allows to choose your set of OAuth scopes. The set of scopes must be entered in a whitespace-separated list, for example, `npx wrangler login --scopes account:read user:read`.
- `--callback-host` **string** optional
  - Defaults to `localhost`. Sets the IP or hostname where Wrangler should listen for the OAuth callback.
- `--callback-port` **string** optional
  - Defaults to 8976. Sets the port where Wrangler should listen for the OAuth callback.

### Note

`wrangler login` uses all the available scopes by default if no flags are provided.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

If Wrangler fails to open a browser, you can copy and paste the URL generated by `wrangler login` in your terminal into a browser and log in.

## Use `wrangler login` on a remote machine

If you are using Wrangler from a remote machine, but run the login flow from your local browser, you will receive the following error message after logging in: This site can't be reached.

To finish the login flow, run `wrangler login` and go through the login flow in the browser:

```
npx wrangler login
```

```
☁ wrangler 2.1.6
-----
Attempting to login via OAuth...
Opening a link in your default browser: https://dash.cloudflare.com/oauth2/auth?
xyz...
```

The browser login flow will redirect you to a `localhost` URL on your machine.

Leave the login flow active. Open a second terminal session. In that second terminal session, use `curl` or an equivalent request library on the remote machine to fetch this `localhost` URL. Copy and paste the `localhost` URL that was generated during the `wrangler login` flow and run:

```
curl <LOCALHOST_URL>
```

## Logout

Remove Wrangler's authorization for accessing your account. This command will invalidate your current OAuth token.

```
wrangler logout
```

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)

- Path to your [Wrangler configuration file](#).
- `--cwd` `string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

If you are using `CLOUDFLARE_API_TOKEN` instead of OAuth, and you can logout by deleting your API token in the Cloudflare dashboard:

1. Log in to the [Cloudflare dashboard](#) ↗.
2. Go to **My Profile** > **API Tokens**.
3. Select the three-dot menu on your Wrangler token.
4. Select **Delete**.

---

## whoami

Retrieve your user information and test your authentication configuration.

```
wrangler whoami
```

The following global flags work on every command:

- `--help` `boolean`
  - Show help.
- `--config` `string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` `string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

---

## versions

**Note**

The minimum required wrangler version to use these commands is 3.40.0. For versions before 3.73.0, you will need to add the `--x-versions` flag.

## upload

Upload a new [version](#) of your Worker that is not deployed immediately.

```
wrangler versions upload [OPTIONS]
```

- `--tag` **string** optional
  - Add a version tag. Accepts empty string.
- `--message` **string** optional
  - Add a version message. Accepts empty string.
- `--name` **string** optional
  - Perform on a specific Worker rather than inheriting from the [Wrangler configuration file](#).
- `--env` **string** optional
  - Perform on a specific environment.

**Note**

If you're using the [Cloudflare Vite plugin](#), you select the environment at dev or build time via the `CLOUDFLARE_ENV` environment variable rather than the `--env` flag. Otherwise, environments are defined in your Worker config file as usual. For more detail on using environments with the Cloudflare Vite plugin, refer to the [plugin documentation](#).

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**

- Run as if Wrangler was started in the specified directory instead of the current working directory.

## deploy

Deploy a previously created [version](#) of your Worker all at once or create a [gradual deployment](#) to incrementally shift traffic to a new version by following an interactive prompt.

```
wrangler versions deploy [OPTIONS]
```

- `--name string` optional
  - Perform on a specific Worker rather than inheriting from the [Wrangler configuration file](#).

The following global flags work on every command:

- `--help boolean`
  - Show help.
- `--config string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

### Note

The non-interactive version of this prompt is: `wrangler versions deploy version-id-1@percentage-1% version-id-2@percentage-2 -y`

For example: `wrangler versions deploy 095f00a7-23a7-43b7-a227-e4c97cab5f22@10% 1a88955c-2fbd-4a72-9d9b-3ba1e59842f2@90% -y`

## list

Retrieve details for the 10 most recent versions. Details include Version ID, Created on, Author, Source, and optionally, Tag or Message.

```
wrangler versions list [OPTIONS]
```

- **--name** **string** optional
  - Perform on a specific Worker rather than inheriting from the [Wrangler configuration file](#).

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## secret put

Create or replace a secret for a Worker. Creates a new [version](#) with modified secrets without [deploying](#) the Worker.

```
wrangler versions secret put <KEY> [OPTIONS]
```

- **KEY** **string** required
  - The variable name for this secret to be accessed in the Worker.
- **--name** **string** optional
  - Perform on a specific Worker rather than inheriting from the [Wrangler configuration file](#).
- **--env** **string** optional
  - Perform on a specific environment.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.

- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## secret delete

Delete a secret for a Worker. Creates a new [version](#) with modified secrets without [deploying](#) the Worker.

```
wrangler versions delete <KEY> [OPTIONS]
```

- `KEY` **string** required
  - The variable name for this secret to be accessed in the Worker.
- `--name` **string** optional
  - Perform on a specific Worker rather than inheriting from the [Wrangler configuration file](#).
- `--env` **string** optional
  - Perform on a specific environment.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## secret bulk

Upload multiple secrets for a Worker at once. Creates a new [version](#) with modified secrets without [deploying](#) the Worker.

```
wrangler versions secret bulk <FILENAME> [OPTIONS]
```

- **FILENAME** **string** optional
  - A file containing either [JSON](#) or the [.env](#) format
  - The JSON file containing key-value pairs to upload as secrets, in the form `{"SECRET_NAME": "secret value", ...}`.
  - The `.env` file containing key-value pairs to upload as secrets, in the form `SECRET_NAME=secret value`.
  - If omitted, Wrangler expects to receive input from `stdin` rather than a file.
- **--name** **string** optional
  - Perform on a specific Worker rather than inheriting from the [Wrangler configuration file](#).
- **--env** **string** optional
  - Perform on a specific environment.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## triggers

### Note

The minimum required wrangler version to use these commands is 3.40.0. For versions before 3.73.0, you will need to add the `--x-versions` flag.

## deploy

Apply changes to triggers ([Routes or domains](#) and [Cron Triggers](#)) when using [wrangler versions upload](#).

```
wrangler triggers deploy [OPTIONS]
```

- `--name` **string** optional
  - Perform on a specific Worker rather than inheriting from the [Wrangler configuration file](#).

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## deployments

[Deployments](#) track the version(s) of your Worker that are actively serving traffic.

## list

### Note

The minimum required wrangler version to use these commands is 3.40.0. For versions before 3.73.0, you will need to add the `--x-versions` flag.

Retrieve details for the 10 most recent [deployments](#). Details include Created on, Author, Source, an optional Message, and metadata about the Version(s) in the deployment.

```
wrangler deployments list [OPTIONS]
```

- `--name string` optional
  - Perform on a specific Worker rather than inheriting from the [Wrangler configuration file](#).

The following global flags work on every command:

- `--help boolean`
  - Show help.
- `--config string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## status

Retrieve details for the most recent deployment. Details include Created on, Author, Source, an optional Message, and metadata about the Version(s) in the deployment.

```
wrangler deployments status
```

- `--name string` optional
  - Perform on a specific Worker rather than inheriting from the [Wrangler configuration file](#).

The following global flags work on every command:

- `--help boolean`
  - Show help.
- `--config string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

# rollback



## Warning

A rollback will immediately create a new deployment with the specified version of your Worker and become the active deployment across all your deployed routes and domains. This change will not affect work in your local development environment.

```
wrangler rollback [<VERSION_ID>] [OPTIONS]
```

- **VERSION\_ID** **string** optional
  - The ID of the version you wish to roll back to. If not supplied, the `rollback` command defaults to the version uploaded before the latest version.
- **--name** **string** optional
  - Perform on a specific Worker rather than inheriting from the [Wrangler configuration file](#).
- **--message** **string** optional
  - Add message for rollback. Accepts empty string. When specified, interactive prompts for rollback confirmation and message are skipped.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## dispatch namespace

### list

List all dispatch namespaces.

```
wrangler dispatch-namespace list
```

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## get

Get information about a dispatch namespace.

```
wrangler dispatch-namespace get <NAME>
```

- **NAME** **string** required
  - The name of the dispatch namespace to get details about.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## create

Create a dispatch namespace.

```
wrangler dispatch-namespace create <NAME>
```

- **NAME** **string** required
  - The name of the dispatch namespace to create.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

## delete

Delete a dispatch namespace.

```
wrangler dispatch-namespace get <NAME>
```

### Note

You must delete all user Workers in the dispatch namespace before it can be deleted.

- **NAME** **string** required
  - The name of the dispatch namespace to delete.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**

- Run as if Wrangler was started in the specified directory instead of the current working directory.

## rename

Rename a dispatch namespace.

```
wrangler dispatch-namespace get <OLD_NAME> <NEW_NAME>
```

- **OLD\_NAME** **string** required
  - The previous name of the dispatch namespace.
- **NEW\_NAME** **string** required
  - The new name of the dispatch namespace.

The following global flags work on every command:

- **--help** **boolean**
  - Show help.
- **--config** **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- **--cwd** **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

---

## mtls-certificate

Manage client certificates used for mTLS connections in subrequests.

These certificates can be used in [mtls\\_certificate bindings](#), which allow a Worker to present the certificate when establishing a connection with an origin that requires client authentication (mTLS).

## upload

Upload a client certificate.

```
wrangler mtls-certificate upload --cert <PATH> --key <PATH> [OPTIONS]
```

- `--cert` **string** required
  - A path to the TLS certificate to upload. Certificate chains are supported.
- `--key` **string** required
  - A path to the private key to upload.
- `--name` **string** optional
  - The name assigned to the mTLS certificate at upload.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example of using the `upload` command to upload an mTLS certificate.

```
npx wrangler mtls-certificate upload --cert cert.pem --key key.pem --name my-origin-cert
```

```
Uploading mTLS Certificate my-origin-cert...
Success! Uploaded mTLS Certificate my-origin-cert
ID: 99f5fef1-6cc1-46b8-bd79-44a0d5082b8d
Issuer: CN=my-secured-origin.com,OU=my-team,O=my-org,L=San Francisco,ST=California,C=US
Expires: 1/01/2025
```

You can then add this certificate as a [binding](#) in your [Wrangler configuration file](#):

**{ }** wrangler.jsonc wrangler.toml

```
{
  "mtls_certificates": [
    {
      "binding": "MY_CERT",
      "certificate_id": "99f5fef1-6cc1-46b8-bd79-44a0d5082b8d"
    }
  ]
}
```

Note that the certificate and private keys must be in separate (typically `.pem`) files when uploading.

## list

List mTLS certificates associated with the current account ID.

```
wrangler mtls-certificate list
```

The following global flags work on every command:

- `--help` `boolean`
  - Show help.
- `--config` `string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` `string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example of using the `list` command to upload an mTLS certificate.

```
npx wrangler mtls-certificate list
```

```
ID: 99f5fef1-6cc1-46b8-bd79-44a0d5082b8d
Name: my-origin-cert
Issuer: CN=my-secured-origin.com,OU=my-team,O=my-org,L=San
Francisco,ST=California,C=US
Created on: 1/01/2023
Expires: 1/01/2025
```

```
ID: c5d004d1-8312-402c-b8ed-6194328d5cbe
Issuer: CN=another-origin.com,OU=my-team,O=my-org,L=San
Francisco,ST=California,C=US
Created on: 1/01/2023
Expires: 1/01/2025
```

## delete

Delete a client certificate.

```
wrangler mtls-certificate delete {--id <ID|--name <NAME>}
```

- `--id` `string`
  - The ID of the mTLS certificate.
- `--name` `string`
  - The name assigned to the mTLS certificate at upload.

The following global flags work on every command:

- `--help` `boolean`
  - Show help.
- `--config` `string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` `string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example of using the `delete` command to delete an mTLS certificate.

```
npx wrangler mtls-certificate delete --id 99f5fef1-6cc1-46b8-bd79-44a0d5082b8d
```

```
Are you sure you want to delete certificate 99f5fef1-6cc1-46b8-bd79-44a0d5082b8d (my-origin-cert)? [y/n]
yes
Deleting certificate 99f5fef1-6cc1-46b8-bd79-44a0d5082b8d...
Deleted certificate 99f5fef1-6cc1-46b8-bd79-44a0d5082b8d successfully
```

## cert

Manage mTLS client certificates and Certificate Authority (CA) chain certificates used for secured connections.

These certificates can be used in Hyperdrive configurations, enabling them to present the certificate when connecting to an origin database that requires client authentication (mTLS) or a custom Certificate Authority (CA).

## upload mtls-certificate

Upload a client certificate.

```
wrangler cert upload mtls-certificate --cert <PATH> --key <PATH> [OPTIONS]
```

- **--cert** **string** required
  - A path to the TLS certificate to upload. Certificate chains are supported.
- **--key** **string** required
  - A path to the private key to upload.
- **--name** **string** optional
  - The name assigned to the mTLS certificate at upload.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example of using the `upload` command to upload an mTLS certificate.

```
npx wrangler cert upload --cert cert.pem --key key.pem --name my-origin-cert
```

```
Uploading mTLS Certificate my-origin-cert...
Success! Uploaded mTLS Certificate my-origin-cert
ID: 99f5fef1-6cc1-46b8-bd79-44a0d5082b8d
Issuer: CN=my-secured-origin.com,OU=my-team,O=my-org,L=San
Francisco,ST=California,C=US
Expires: 1/01/2025
```

Note that the certificate and private keys must be in separate (typically `.pem`) files when uploading.

## upload certificate-authority

Upload a client certificate.

```
wrangler cert upload certificate-authority --ca-cert <PATH> [OPTIONS]
```

- `--ca-cert` **string** *required*
  - A path to the Certificate Authority (CA) chain certificate to upload.
- `--name` **string** *optional*
  - The name assigned to the mTLS certificate at upload.

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example of using the `upload` command to upload an CA certificate.

```
npx wrangler cert upload certificate-authority --ca-cert server-ca-chain.pem
--name SERVER_CA_CHAIN
```

```
Uploading CA Certificate SERVER_CA_CHAIN...
Success! Uploaded CA Certificate SERVER_CA_CHAIN
ID: 99f5fef1-6cc1-46b8-bd79-44a0d5082b8d
Issuer: CN=my-secured-origin.com,OU=my-team,O=my-org,L=San
Francisco,ST=California,C=US
Expires: 1/01/2025
```

## list

List mTLS certificates associated with the current account ID. This will display both mTLS certificates and CA certificates.

```
wrangler cert list
```

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**

- Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example of using the `list` command to upload an mTLS or CA certificate.

```
npx wrangler cert list
```

```
ID: 99f5fef1-6cc1-46b8-bd79-44a0d5082b8d
Name: my-origin-cert
Issuer: CN=my-secured-origin.com,OU=my-team,O=my-org,L=San
Francisco,ST=California,C=US
Created on: 1/01/2023
Expires: 1/01/2025

ID: c5d004d1-8312-402c-b8ed-6194328d5cbe
Issuer: CN=another-origin.com,OU=my-team,O=my-org,L=San
Francisco,ST=California,C=US
Created on: 1/01/2023
Expires: 1/01/2025
```

## delete

Delete a client certificate.

```
wrangler cert delete {--id <ID>|--name <NAME>}
```

- `--id` `string`
  - The ID of the mTLS or CA certificate.
- `--name` `string`
  - The name assigned to the mTLS or CA certificate at upload.

The following global flags work on every command:

- `--help` `boolean`
  - Show help.
- `--config` `string` (not supported by Pages)

- Path to your [Wrangler configuration file](#).
- `--cwd` `string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

The following is an example of using the `delete` command to delete an mTLS or CA certificate.

```
npx wrangler cert delete --id 99f5fef1-6cc1-46b8-bd79-44a0d5082b8d
```

```
Are you sure you want to delete certificate 99f5fef1-6cc1-46b8-bd79-44a0d5082b8d (my-origin-cert)? [y/n]
yes
Deleting certificate 99f5fef1-6cc1-46b8-bd79-44a0d5082b8d...
Deleted certificate 99f5fef1-6cc1-46b8-bd79-44a0d5082b8d successfully
```

## types

Generate types based on your Worker configuration, including Env types based on your bindings, module rules, and [runtime types](#) based on the `compatibility_date` and `compatibility_flags` in your [config file](#).

```
wrangler types [<PATH>] [OPTIONS]
```

### Note

If you are running a version of Wrangler that is greater than 3.66.0 but below 4.0.0, you will need to include the `--experimental-include-runtime` flag. During its experimental release, runtime types were output to a separate file (`./wrangler/types/runtime.d.ts` by default). If you have an older version of Wrangler, you can access runtime types through the `@cloudflare/workers-types` package.

- `PATH` `string` (default: `./worker-configuration.d.ts`)
  - The path to where types for your Worker will be written.

- The path must have a `.ts` extension.
- `--env-interface` **string** (default: ``Env``)
  - The name of the interface to generate for the environment object.
  - Not valid if the Worker uses the Service Worker syntax.
- `--include-runtime` **boolean** (default: `true`)
  - Whether to generate runtime types based on the `compatibility_date` and `compatibility_flags` in your [config file](#).
- `--include-env` **boolean** (default: `true`)
  - Whether to generate Env types based on your Worker bindings.
- `--strict-vars` **boolean** optional (default: `true`)
  - Control the types that Wrangler generates for vars bindings.
  - If `true`, (the default) Wrangler generates literal and union types for bindings (e.g. `myVar: 'my dev variable' | 'my prod variable'`).
  - If `false`, Wrangler generates generic types (e.g. `myVar: string`). This is useful when variables change frequently, especially when working across multiple environments.
- `--config, -c` **string[]** optional
  - Path(s) to [Wrangler configuration file](#). If the Worker you are generating types for has service bindings or bindings to Durable Objects, you can also provide the paths to those configuration files so that the generated Env type will include RPC types. For example, given a Worker with a service binding, `wrangler types -c wrangler.toml -c ../bound-worker/wrangler.toml` will generate an Env type like this:

```
interface Env {
  SERVICE_BINDING: Service<import("../bound-worker/src/index").Entrypoint>;
}
```

- If your service binding targets a [WorkerEntrypoint](#) that is a default export, make sure you set `entrypoint: "default"` in your Wrangler config when you configure your service binding.

## telemetry

Cloudflare collects anonymous usage data to improve Wrangler. You can learn more about this in our [data policy](#).

You can manage sharing of usage data at any time using these commands.

## disable

Disable telemetry collection for Wrangler.

```
wrangler telemetry disable
```

## enable

Enable telemetry collection for Wrangler.

```
wrangler telemetry enable
```

## status

Check whether telemetry collection is currently enabled. The return result is specific to the directory where you have run the command.

This will resolve the global status set by `wrangler telemetry disable / enable`, the environment variable `WRANGLER_SEND_METRICS`, and the `send_metrics` key in the [Wrangler configuration file](#).

```
wrangler telemetry status
```

The following global flags work on every command:

- `--help` **boolean**
  - Show help.
- `--config` **string** (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd` **string**

- Run as if Wrangler was started in the specified directory instead of the current working directory.

## check

### startup

Generate a CPU profile of your Worker's startup phase.

After you run `wrangler check startup`, you can import the profile into Chrome DevTools or open it directly in VSCode to view a flamegraph of your Worker's startup phase. Additionally, when a Worker deployment fails with a startup time error Wrangler will automatically generate a CPU profile for easy investigation.

```
wrangler check startup
```

- `--args` **string** optional
  - To customise the way `wrangler check startup` builds your Worker for analysis, provide the exact arguments you use when deploying your Worker with `wrangler deploy`, or your Pages project with `wrangler pages functions build`. For instance, if you deploy your Worker with `wrangler deploy --no-bundle`, you should use `wrangler check startup --args="--no-bundle"` to profile the startup phase.
- `--worker` **string** optional
  - If you don't use Wrangler to deploy your Worker, you can use this argument to provide a Worker bundle to analyse. This should be a file path to a serialized multipart upload, with the exact same format as [the API expects](#).
- `--pages` **boolean** optional
  - If you don't use a Wrangler config file with your Pages project (i.e. a Wrangler config file containing `pages_build_output_dir`), use this flag to force `wrangler check startup` to treat your project as a Pages project.

The following global flags work on every command:

- `--help` **boolean**

- Show help.
- `--config string` (not supported by Pages)
  - Path to your [Wrangler configuration file](#).
- `--cwd string`
  - Run as if Wrangler was started in the specified directory instead of the current working directory.

Was this helpful?



Previous

← Bundling

Next

Configuration →

Last updated: Jun 3, 2025

Resources

- API
- New to Cloudflare?
- Products
- Sponsorships
- Open Source

Company

- cloudflare.com
- Our team
- Careers

Community

- X
- Discord

Support

- Help Center
- System Status
- Compliance
- GDPR

Tools

- Cloudflare Radar
- Speed Test
- Is BGP Safe Yet?
- RPKI Toolkit
- Certificate Transparency

 YouTube

 GitHub

2025 Cloudflare, Inc. • [Privacy Policy](#) • [Terms of Use](#) • [Report Security Issues](#) • [Trademark](#) • 